

**papiNet**

**papiNet V2R31**

**Data Dictionary**

**Global Standard for the Paper and Forest  
Products Supply Chain**

**Build V2R31\_20110411**

**Date 2011-05-10**

**Production Release**

# papiNet V2R31

---

---

## Copyright

Copyright 2000 – 2011 papiNet G.I.E (“papiNet”) and International Digital Enterprise Alliance, Inc. (“IDEAlliance”) collectively “Copyright Owner”. All rights reserved by the Copyright Owner under the laws of the United States, Belgium, the European Economic Community, and all states, domestic and foreign. This document may be downloaded and copied provided that all copies retain and display the copyright and any other proprietary notices contained in this document. This document may not be sold, modified, edited, or taken out of context such that it creates a false or misleading statement or impression as to the purpose or use of the papiNet specification, which is an open standard. Use of this Standard, in accord with the foregoing limited permission, shall not create for the user any rights in or to the copyright, which rights are exclusively reserved to the Copyright Owner.

papiNet, IDEAlliance, and the members of all papiNet Groups (collectively and individually, “Presenters”) make no representations or warranties, express or implied, including, but not limited to, warranties of merchantability, fitness for a particular purpose, title, or non-infringement. The presenters do not make any representation or warranty that the contents of this document are free from error, suitable for any purpose of any user, or that implementation of such contents will not infringe any third party patents, copyrights, trademarks or other rights. By making use of this document, the user assumes all risks and waives all claims against Presenters.

In no event shall Presenters be liable to user (or other person) for direct, indirect, special or consequential damages arising from or related to any use of this document, including, without limitation, lost profits, business interruption, loss of programs, or other data on your information handling system even if Presenters are expressly advised of the possibility of such damages.

---

### **Use of Documents in papiNet Implementations**

Documents may be used as templates for a papiNet implementation. The Presenters grant the right to modify and edit them to fit an actual implementation project provided all copies display the copyright and any other proprietary notices contained in this document. Such modified documents must not be distributed beyond the trading partners implementing or maintaining a papiNet connection.

# papiNet V2R31

---

---

## Table of Contents

Copyright .....	2
Use of Documents in papiNet Implementations .....	2
Table of Contents .....	3
Data Dictionary: papiNet Version 2.31 .....	37
a .....	37
Abrasion .....	38
AbsorptionInk .....	39
AbsorptionLight .....	41
AbsorptionWater .....	42
ActionType [attribute] .....	43
ActualNominal [attribute] .....	44
AdditionalTest .....	45
AdditionalTestName .....	46
AdditionalText .....	46
Address1 .....	46
Address2 .....	46
Address3 .....	47
Address4 .....	47
AdjustmentFixedAmount .....	47
AdjustmentPercentage .....	47
AdjustmentType (Financial) [attribute] .....	48
AdjustmentType (Tare) [attribute] .....	52
AdjustmentTypeReason .....	54
AdjustmentValue .....	54
Age .....	55
Agency [attribute] .....	55
AggregatedUsageLineItem .....	59
Alignment .....	60
Altitude .....	61
AmbientTemperature .....	61
Amount .....	62
AmountSubjectToTermsDiscount .....	62
AmountType [attribute] .....	62
Appearance .....	63
AppliesTo [attribute] .....	64
ArrivalDate .....	64
Ash .....	65
AssemblyInstructions .....	66
AssemblyType [attribute] .....	66
AssignedBy [attribute] .....	67
AttachmentFileName .....	72
AudioCassette .....	73
AudioCassetteCaseType [attribute] .....	75
AudioCassetteTapeLengthType [attribute] .....	75
Availability .....	76
AvailabilityDetail .....	77
AvailabilityHeader .....	79
AvailabilityIssueDate .....	80
AvailabilityNumber .....	81
AvailabilityStatusRequestDetail .....	82
b .....	83
Bale .....	84
BaleCharacteristics .....	84
BaleConversionCharacteristics .....	85
BaleDepth .....	86
BaleHeight .....	86
BaleItem .....	87

# papiNet V2R31

---

BalePackagingCharacteristics .....	89
BaleReference .....	89
BaleReferenceType [attribute] .....	90
BalesPerUnit .....	90
BaleStandardWeight .....	90
BaleType [attribute] .....	91
BaleWidth .....	91
BandCharacteristics .....	92
BandColour .....	92
BandDirection [attribute] .....	93
BandLocationType [attribute] .....	93
BandMaterial .....	93
BandsRequired [attribute] .....	93
BandType [attribute] .....	94
BarcodeSuppliedByPublisher [attribute] .....	94
Bark .....	95
BaseAmountInfo .....	96
BaseNetAmount .....	96
BasisWeight .....	97
BasisWeightVariation .....	98
BendingResistance .....	99
BendingStiffness .....	101
BestBeforeDate .....	102
Billable [attribute] .....	102
BillOfMaterials .....	102
BillToParty .....	103
BinaryValue .....	104
BindingBackingType [attribute] .....	104
BindingBackStyleType [attribute] .....	104
BindingCoverScoring [attribute] .....	104
BindingExtras .....	105
BindingExtrasDescription .....	105
BindingMaterialCharacteristics .....	106
BindingMaterialDescription .....	107
BindingReinforcement [attribute] .....	107
BindingRibbon [attribute] .....	107
BindingStyleType [attribute] .....	107
BindingType [attribute] .....	109
Black .....	109
Blanket .....	110
BlanketPacking .....	110
BlanketType .....	110
BleachingProcess [attribute] .....	111
Bleed [attribute] .....	111
Blue .....	111
BookBlock .....	112
BookBlockBulk .....	112
BookBlockEdgeTrim .....	113
BookBlockFinishExtras .....	113
BookClassification .....	114
BookClassificationType [attribute] .....	114
BookManufacturing .....	115
BookPackageInformation .....	117
BookSpecification .....	119
BookSubClassification .....	121
BookSubClassificationType [attribute] .....	121
BookUnitPacking .....	129
BookUnitType [attribute] .....	130
BooleanValue .....	130

---

# papiNet V2R31

---

BoxCharacteristics .....	131
BoxItem .....	133
BoxMeasurementsAppliesTo [attribute] .....	135
BoxReference .....	135
BoxReferenceType [attribute] .....	136
BoxType [attribute] .....	136
Brand .....	136
Brightness .....	137
Brilliance .....	138
BucketType [attribute] .....	139
Bulk .....	140
BulkNumberOfUnits .....	141
Burst .....	142
BurstIndex .....	143
BusinessAcceptance .....	145
BusinessAcceptanceDate .....	146
BusinessAcceptanceNumber .....	147
BusinessAcceptanceParty .....	147
BusinessAcceptanceStatus [attribute] .....	148
BusinessAcknowledgement .....	148
BusinessAcknowledgementDate .....	150
BusinessAcknowledgementNumber .....	150
BuyerParty .....	151
ByInvoice .....	151
ByJob .....	152
ByLoad .....	153
ByLoadType [attribute] .....	153
ByPeriod .....	154
ByProduct .....	154
ByPurchaseOrder .....	155
ByQualifiedDeliveryMessage .....	156
ByQualifiedPurchaseOrderInformation .....	156
ByShipTo .....	157
BySupplierOrder .....	158
BySupplierOrderNumber .....	159
Calendar .....	159
CalendarEntry .....	160
CalendarEntryPeriod [attribute] .....	161
CalendarHeader .....	161
CalendarIssueDate .....	162
CalendarNumber .....	163
CalendarRequestDetail .....	163
CalendarSequence .....	164
CalendarSequenceNumber .....	165
CalendarStatus [attribute] .....	165
CalendarType [attribute] .....	165
Calibration .....	166
CalibrationDate .....	166
CalibrationDescription .....	167
CalibrationNumber .....	167
Caliper .....	167
CallOff .....	168
CallOffConfirmationIssuedDate .....	169
CallOffConfirmationLineItemNumber .....	170
CallOffConfirmationNumber .....	170
CallOffHeader .....	171
CallOffHeaderStatusType [attribute] .....	173
CallOffInformation .....	174
CallOffIssuedDate .....	175

---

# papiNet V2R31

---

CallOffLineItem .....	176
CallOffLineItemDocumentStatus [attribute] .....	178
CallOffLineItemDocumentStatus [attribute] .....	178
CallOffLineItemNumber .....	179
CallOffLineItemStatusType [attribute] .....	179
CallOffLineItemText .....	179
CallOffNumber .....	179
CallOffPaper .....	180
CallOffProduct .....	180
CallOffProductConversionType .....	182
CallOffPurchaseOrderLineItem .....	182
CallOffReel .....	183
CallOffReference .....	183
CallOffReferenceType [attribute] .....	183
CallOffSheet .....	184
CallOffStatusType [attribute] .....	184
CallOffSummary .....	185
CallOffType [attribute] .....	185
CallOffWood .....	186
CallOffWoodHeader .....	187
CallOffWoodLineItem .....	189
CallOffWoodProductGroup .....	191
CallOffWoodSummary .....	192
CarrierParty .....	193
Case .....	194
CaseBoardMaterials .....	195
CaseBoardType [attribute] .....	195
CaseFlushFoot [attribute] .....	196
CaseLining .....	196
CaseLiningDescription .....	196
CaseLocationType [attribute] .....	196
CaseMaking .....	197
CaseMaterial .....	197
CaseOversize .....	198
CaseShow .....	198
CaseShowType [attribute] .....	199
CaseSupers .....	199
CaseType [attribute] .....	199
CassetteCardReference .....	199
CassetteLabelCharacteristics .....	200
CassetteLabelSide [attribute] .....	200
CassetteLabelType [attribute] .....	200
CD .....	201
CDFormatType [attribute] .....	202
CDManufacturingProcess [attribute] .....	202
CDPackaging .....	203
CDRTYPE [attribute] .....	203
CertificationBody [attribute] .....	203
ChainOfCustody .....	203
ChangeDetailType [attribute] .....	204
Charge .....	204
ChargeAmount .....	205
ChargeContext [attribute] .....	205
ChargeInformation .....	206
ChargeNetAmount .....	207
ChargeOrAllowance .....	207
ChargeOrAllowanceType [attribute] .....	208
ChargePerUnit .....	212
ChargeType [attribute] .....	213

---

# papiNet V2R31

---

ChildrensTitle [attribute] .....	215
Chip .....	215
ChipCharacteristics .....	216
ChipFraction .....	217
ChipFractionAnalysisDate.....	217
ChipFractionClass .....	218
ChipFractionDescription .....	218
ChipFractionInfo.....	218
ChipFractionNumber .....	219
ChipFractionPropertyType [attribute].....	219
ChipFractionValue.....	220
ChipPackagingCharacteristics .....	221
City .....	221
ClassIdentifier .....	222
Classification.....	222
ClassificationCode.....	223
ClassificationDescription .....	223
ClothCrossCut [attribute].....	223
CMYK.....	224
Coating .....	225
CoatingBottom [attribute].....	227
CoatingCoverageType [attribute] .....	227
CoatingLocation [attribute] .....	228
CoatingLocationType [attribute].....	228
CoatingTop [attribute].....	229
CoatWeight.....	230
Collated [attribute] .....	231
CoLoading .....	231
CoLoadingNumber .....	232
CoLoadingReference .....	232
CoLoadingReferenceType [attribute].....	233
CoLoadingType [attribute] .....	233
ColourCode.....	233
ColourDescription .....	234
ColourDetail.....	234
ColourLocation [attribute] .....	235
ColourMatchDescription .....	235
ColourShade .....	236
ColourSpecs .....	236
CommodityGoodsCode .....	237
CommonContact.....	238
CommunicationRole [attribute] .....	239
Complaint.....	239
ComplaintHeader.....	241
ComplaintInformation .....	243
ComplaintIssueDate.....	243
ComplaintLineItem .....	244
ComplaintLineItemDetail .....	246
ComplaintLineItemDetailNumber.....	248
ComplaintLineItemNumber .....	248
ComplaintLineNetChargeAmount.....	248
ComplaintNumber.....	248
ComplaintReason.....	248
ComplaintReasonCode.....	249
ComplaintReasonDescription .....	249
ComplaintReasonType [attribute].....	249
ComplaintReference .....	250
ComplaintReferenceType [attribute] .....	250
ComplaintResponse .....	251

---

# papiNet V2R31

---

ComplaintResponseHeader.....	253
ComplaintResponseHeaderStatusType [attribute].....	255
ComplaintResponseIssueDate.....	256
ComplaintResponseLineItem.....	257
ComplaintResponseLineItemDetail.....	260
ComplaintResponseLineItemDetailNumber.....	261
ComplaintResponseLineItemNumber.....	261
ComplaintResponseLineNetChargeAmount.....	262
ComplaintResponseLineStyleType [attribute].....	262
ComplaintResponseNumber.....	262
ComplaintResponseReason.....	262
ComplaintResponseReasonCode.....	263
ComplaintResponseReasonDescription.....	263
ComplaintResponseReasonType [attribute].....	263
ComplaintResponseReference.....	264
ComplaintResponseReferenceType [attribute].....	264
ComplaintResponseSpecification.....	265
ComplaintResponseSummary.....	266
ComplaintResponseType [attribute].....	267
ComplaintSpecification.....	267
ComplaintSummary.....	268
ComplaintType [attribute].....	269
ComponentDueDate.....	269
ComponentNeededDate.....	270
ComponentShipDate.....	271
CompositeAndVeneerWoodPanels.....	271
CompoundAgency [attribute].....	272
CompoundType [attribute].....	272
ConcernIndicatorType [attribute].....	272
ConstructionPackagesAndPreFabPanels.....	272
ConsumptionProcess.....	273
ContactIdentifier.....	274
ContactIdentifierType [attribute].....	274
ContactName.....	275
ContactType [attribute].....	275
ConversionCode.....	276
CoordinateFormatType [attribute].....	277
Coordinates.....	277
CoreCharacteristics.....	278
CoreCode.....	278
CoreDiameterInside.....	279
CoreDiameterOutside.....	279
CoreEndType [attribute].....	280
CoreMaterialType [attribute].....	280
CorePlugs.....	281
CoreStrengthCode.....	281
CorrectiveAction.....	282
CostComponent.....	282
CostComponentCode.....	282
CostComponentDescription.....	283
Country.....	283
CountryOfConsumption.....	283
CountryOfDestination.....	284
CountryOfOrigin.....	284
County.....	284
CreditDebitNote.....	285
CreditDebitNoteAmountSubtotal.....	286
CreditDebitNoteBaseAmountInformation.....	286
CreditDebitNoteDate.....	286

---

# papiNet V2R31

---

CreditDebitNoteHeader.....	288
CreditDebitNoteLineAmount.....	290
CreditDebitNoteLineItem.....	291
CreditDebitNoteLineItemNumber.....	294
CreditDebitNoteNumber.....	294
CreditDebitNoteReason.....	294
CreditDebitNoteReasonCode.....	294
CreditDebitNoteReasonType [attribute].....	295
CreditDebitNoteReference.....	295
CreditDebitNoteReferenceType [attribute].....	296
CreditDebitNoteSummary.....	297
CreditDebitNoteType [attribute].....	299
CurrencyFromType [attribute].....	299
CurrencyType [attribute].....	299
CurrencyValue.....	299
CustomerMarks.....	300
CustomerMarksType [attribute].....	300
CustomsParty.....	302
CustomsReferenceNumber.....	303
CustomsReferenceNumberType [attribute].....	303
CustomsStampDate.....	303
CustomsStampHeaderText.....	304
CustomsStampInformation.....	304
CustomsStampTrailerText.....	305
CustomsTariffCode.....	305
CustomsTotals.....	305
CuttingDetails.....	305
CuttingTemplateCode.....	306
Cyan.....	307
Date.....	308
DateFinished.....	308
DateMade.....	309
DateSheeted.....	309
DateTimeFrom.....	310
DateTimeRange.....	310
DateTimeTo.....	311
DateTimeValue.....	311
DateType [attribute].....	311
DateWound.....	315
Day.....	316
Days.....	316
Debarked [attribute].....	316
DeckAndPorchFlooringMaterials-NaturalWood.....	316
DeckAndPorchFlooringMaterials-NaturalWoodCharacteristics.....	317
DecorationCoverage.....	319
DecorationLocationType [attribute].....	319
DecorationSpecs.....	320
DecorationType [attribute].....	321
DeliveryDate.....	321
DeliveryDateType [attribute].....	322
DeliveryDateWindow.....	323
DeliveryDestination.....	325
DeliveryIndicator.....	326
DeliveryInfo.....	327
DeliveryInstruction.....	328
DeliveryInstructionDate.....	329
DeliveryInstructionHeader.....	330
DeliveryInstructionHeaderStatusType [attribute].....	331
DeliveryInstructionNumber.....	332

---

# papiNet V2R31

---

DeliveryInstructionReference.....	332
DeliveryInstructionReferenceType [attribute].....	332
DeliveryInstructionSequence.....	333
DeliveryInstructionSequenceLineItem.....	336
DeliveryInstructionSequenceLineItemNumber.....	339
DeliveryInstructionSequenceNumber.....	339
DeliveryInstructionSequenceStatusType [attribute].....	339
DeliveryInstructionStatusType [attribute].....	340
DeliveryInstructionSummary.....	340
DeliveryInstructionType [attribute].....	341
DeliveryLastDateOfChange.....	341
DeliveryLeg.....	343
DeliveryLegReference.....	345
DeliveryLegReferenceType [attribute].....	346
DeliveryLegSequenceNumber.....	346
DeliveryLegType [attribute].....	346
DeliveryLineNumber.....	347
DeliveryMessage.....	347
DeliveryMessageBook.....	348
DeliveryMessageBookHeader.....	350
DeliveryMessageBookShipment.....	352
DeliveryMessageBookSummary.....	353
DeliveryMessageContextType [attribute].....	353
DeliveryMessageDate.....	354
DeliveryMessageHeader.....	355
DeliveryMessageLineItem.....	358
DeliveryMessageLineItemNumber.....	361
DeliveryMessageNumber.....	361
DeliveryMessageProductGroup.....	361
DeliveryMessageReelCharacteristics.....	362
DeliveryMessageReference.....	363
DeliveryMessageReferenceType [attribute].....	364
DeliveryMessageShipment.....	364
DeliveryMessageStatusType [attribute].....	365
DeliveryMessageSummary.....	365
DeliveryMessageType (Book) [attribute].....	366
DeliveryMessageType [attribute].....	367
DeliveryMessageType (Wood) [attribute].....	367
DeliveryMessageWood.....	368
DeliveryMessageWoodHeader.....	370
DeliveryMessageWoodSummary.....	372
DeliveryModeType [attribute].....	373
DeliveryOrigin.....	374
DeliveryRouteCode.....	375
DeliverySchedule.....	376
DeliveryScheduleReference.....	377
DeliveryScheduleReferenceType [attribute].....	378
DeliveryShipmentBookLineItem.....	379
DeliveryShipmentId.....	381
DeliveryShipmentLineItem.....	382
DeliveryShipmentLineItemNumber.....	385
DeliveryStatus.....	385
DeliveryStatusType [attribute].....	385
DeliveryTransitTime.....	386
Density.....	387
DepartureDate.....	388
DetailRangeMax.....	389
DetailRangeMin.....	389
DetailValue.....	389

---

# papiNet V2R31

---

DiameterBreastHeight .....	389
DieCut [attribute] .....	390
DieCutDescription .....	390
DirectLoading [attribute] .....	390
DirectUnloading [attribute] .....	390
Dirt .....	391
DiscPrinting [attribute] .....	392
DistanceFromCore .....	392
DistanceFromEdge .....	393
DistanceMeasuredTo [attribute] .....	393
DistanceToNextStop .....	394
Document .....	394
DocumentContent .....	395
DocumentContentText .....	396
DocumentContentType [attribute] .....	396
DocumentDate .....	398
DocumentInformation .....	399
DocumentInstruction .....	399
DocumentName [attribute] .....	400
DocumentNumber .....	405
DocumentReference .....	405
DocumentReferenceID .....	406
DocumentReferenceIDLineNumber .....	406
DocumentReferenceIDType [attribute] .....	407
DocumentReferenceInformation .....	407
DocumentReferenceType [attribute] .....	408
DocumentRequired .....	408
DocumentRequiredType [attribute] .....	409
DocumentType [attribute] .....	409
DocumentType [attribute] .....	410
DocumentVersionNumber .....	415
DominantWavelength .....	416
DoubleBunked [attribute] .....	417
DownGradingInfo .....	417
DownGradingReason .....	418
DownGradingReasonCode .....	418
DownGradingReasonDescription .....	418
Downtime .....	418
DowntimeDescription .....	419
DowntimeReasonCode .....	419
DrainageResistance .....	420
Drilled [attribute] .....	421
DuplicationRatio [attribute] .....	421
DVD .....	422
DVDFormatType [attribute] .....	423
eAttachment .....	423
e-Attachment .....	424
Edge .....	424
Edge .....	425
EdgeFinish .....	425
EdgeLocation [attribute] .....	426
EdgeLocationType [attribute] .....	426
EdgeMachiningProfile .....	426
EdgePaddable [attribute] .....	427
EdgeType [attribute] .....	427
EdgeType [attribute] .....	427
Email .....	427
Embossing .....	428
EmbossingCode .....	428

---

# papiNet V2R31

---

EmbossingDescription .....	428
EndCaps.....	429
EndIdentifierRange .....	429
EndsDiscountInformation.....	429
EndsDiscountPercent.....	430
EndsDiscountRule [attribute].....	430
EndsheetCopyDescription .....	430
EndsheetInformation.....	431
EndsheetLocationType [attribute] .....	431
EndsheetMaterials .....	432
EndsheetReinforcementMaterials .....	432
EndsheetReinforcementType [attribute] .....	433
EndsheetType [attribute].....	433
EndsLengthMax.....	433
EndsPermittedPercent .....	434
EndUserParty.....	434
EndUses.....	435
Error.....	435
ErrorCode.....	436
ErrorDescription .....	436
ErrorReference.....	436
ErrorReferenceType [attribute] .....	437
ErrorSeverity .....	437
EstimatedArrivalDate .....	437
EvenSpacing.....	438
EventDate .....	438
EventType [attribute].....	438
ExchangeRate.....	439
ExchangeRateType [attribute] .....	440
ExcitationPurity.....	440
ExLog .....	441
ExtraFeature.....	442
ExtraFeatureDescription .....	442
Face [attribute].....	442
Fax.....	442
FibreClassification.....	443
FibreLength .....	444
FibreSource [attribute].....	445
FinishedSize .....	447
FinishPrep .....	447
FinishPrepInput.....	448
FinishPrepInputType .....	448
FinishPrepOutputType [attribute] .....	449
FinishSpecs .....	449
FinishType [attribute].....	450
FireTreatment .....	452
FireTreatmentType [attribute] .....	452
FlapLocation [attribute] .....	452
FlapWidth.....	453
FlatAmountAdjustment.....	453
FlatSize.....	454
Floor.....	454
FloorLocationType [attribute] .....	454
FloorPackage .....	455
FloorPanel .....	455
FloorTruss .....	455
Folded [attribute] .....	455
Folding.....	456
Foot .....	457

---

# papiNet V2R31

---

ForestWood .....	458
ForestWoodCharacteristics .....	459
ForestWoodClass .....	459
ForestWoodClassCode .....	460
ForestWoodClassDescription .....	460
ForestWoodClassType [attribute] .....	460
ForestWoodItemType [attribute] .....	460
ForestWoodPackagingCharacteristics .....	461
ForestWoodProcessingCharacteristics .....	461
ForestWoodType [attribute] .....	461
Formation .....	463
ForwarderParty .....	464
FountainSolutionConductivity .....	465
FountainSolutionpH .....	465
Freeness .....	466
FreightPayableAt .....	467
Friction .....	468
From .....	469
FromProduct .....	470
GeneralLedgerAccount .....	471
Gimmick .....	471
Gloss .....	472
GlueExposure .....	473
GlueExposure .....	473
GlueExposureID .....	474
GoodsLoadingPrinciple [attribute] .....	474
GoodsReceipt .....	475
GoodsReceiptAcceptance [attribute] .....	476
GoodsReceiptAcceptance [attribute] .....	477
GoodsReceiptArrivalDate .....	478
GoodsReceiptHeader .....	479
GoodsReceiptHeaderAcceptance [attribute] .....	481
GoodsReceiptIssueDate .....	482
GoodsReceiptLineItem .....	484
GoodsReceiptLineItemNumber .....	486
GoodsReceiptNumber .....	486
GoodsReceiptPackage .....	486
GoodsReceiptReference .....	487
GoodsReceiptReferenceType [attribute] .....	488
GoodsReceiptStatusType [attribute] .....	488
GoodsReceiptSummary .....	489
GoodsReceiptUnloadDate .....	489
GoodsReceivedRejectedType [attribute] .....	490
GPSCoordinates .....	491
GPSSystem [attribute] .....	492
Grade .....	492
GradeAgency [attribute] .....	492
GradeAgency .....	493
GradeCode .....	493
GradeName .....	494
GradeStamp .....	494
GradeStamped [attribute] .....	494
GradeStampLocation .....	494
GradeStampMillNumber .....	495
GradeType [attribute] .....	495
GradingRule [attribute] .....	503
GrainDirection .....	503
Green .....	504
Gutter .....	505

---

# papiNet V2R31

---

Gypsum .....	505
Halftones .....	506
HardwoodLumber .....	506
HardwoodLumberCharacteristics .....	506
Head .....	507
Headband.....	508
HeatTreatment.....	508
HeatTreatmentType [attribute].....	509
Height .....	509
Height .....	510
HighlightedPlanningBucket.....	510
HolePunchInformation.....	511
HolePunchTemplateReference.....	511
HolePunchThroughCover [attribute] .....	511
HolePunchType .....	511
HoleReinforcement .....	512
HoleSpacing .....	512
Hours .....	512
HSB.....	513
Hue .....	514
Humidity .....	515
Identifier .....	515
IdentifierCodeType [attribute] .....	516
IdentifierFormatType [attribute] .....	518
IdentifierType [attribute] .....	519
Impressions.....	520
Incoterms [attribute] .....	520
IncotermsLocation .....	522
IncotermsVersion [attribute].....	522
IncrementalOrderQuantity .....	523
IncrementalValue .....	523
InfoRequest.....	524
InfoRequestType [attribute].....	526
InformationalAmount .....	527
InformationalPricePerUnit .....	528
InformationalPricePerUnitType [attribute] .....	528
InformationalQuantity .....	529
Ink.....	530
InkCharacteristics.....	531
InkCoverage.....	532
InkCoverageType [attribute] .....	532
InkDelivery.....	532
InkManufacturer.....	533
InkTack.....	533
InkTypeDescription.....	533
InkViscosity.....	533
InlayCardQuantity [attribute] .....	534
InsertReference.....	534
InstructionByType [attribute] .....	534
Insurance.....	535
InsuranceContractNo .....	535
InsuranceInfo .....	535
InsuredValue .....	535
Insurer .....	536
InventoryChange.....	536
InventoryChangeHeader.....	537
InventoryChangeIssuedDate .....	538
InventoryChangeLineItem.....	540
InventoryChangeLineItemDetail.....	542

---

# papiNet V2R31

---

InventoryChangeLineItemDetailNumber .....	543
InventoryChangeLineItemNumber .....	544
InventoryChangeNumber .....	544
InventoryChangeReason .....	544
InventoryChangeReasonCode .....	544
InventoryChangeReference .....	545
InventoryChangeReferenceType [attribute] .....	545
InventoryChangeStatusType [attribute] .....	545
InventoryChangeSummary .....	546
InventoryChangeType [attribute] .....	547
InventoryClass .....	548
InventoryClassCode .....	549
InventoryClassDescription .....	549
InventoryClassLevel [attribute] .....	549
InventoryDispositionInstructions .....	550
InventoryDispositionInstructionsDetail .....	551
InventoryDispositionInstructionsHeader .....	553
InventoryDispositionInstructionsIssuedDate .....	554
InventoryDispositionInstructionsLineNumber .....	555
InventoryDispositionInstructionsNumber .....	555
InventoryDispositionInstructionsReference .....	555
InventoryDispositionInstructionsReferenceType [attribute] .....	556
InventoryDispositionInstructionsType [attribute] .....	556
InventoryInspectionDate .....	556
InventoryOwnedBy [attribute] .....	557
InventoryStatus .....	557
InventoryStatusHeader .....	559
InventoryStatusIssuedDate .....	560
InventoryStatusLineItem .....	561
InventoryStatusLineItemDetail .....	563
InventoryStatusLineItemDetailNumber .....	564
InventoryStatusLineItemNumber .....	564
InventoryStatusNumber .....	564
InventoryStatusReference .....	564
InventoryStatusReferenceType [attribute] .....	565
InventoryStatusReportingDetailType [attribute] .....	565
InventoryStatusRequestDetail .....	566
InventoryStatusRequestDetailType [attribute] .....	568
InventoryStatusSummary .....	569
InventoryStatusType [attribute] .....	569
Invoice .....	570
InvoiceContextType [attribute] .....	571
InvoiceDate .....	571
InvoiceDeliveryInformation .....	573
InvoiceHeader .....	575
InvoiceLineAmount .....	577
InvoiceLineBaseAmount .....	577
InvoiceLineBaseAmountInformation .....	577
InvoiceLineItem .....	579
InvoiceLineNumber .....	582
InvoiceNumber .....	582
InvoiceNumberMax .....	582
InvoiceNumberMin .....	583
InvoiceNumberRange .....	583
InvoicePrimaryStatus .....	583
InvoiceProductGroup .....	583
InvoiceReference .....	584
InvoiceReferenceType [attribute] .....	584
InvoiceSecondaryStatus .....	585

---

# papiNet V2R31

---

InvoiceShipment .....	585
InvoiceStatusCode [attribute] .....	585
InvoiceSummary .....	586
InvoiceType [attribute].....	588
InvoiceWood.....	590
InvoiceWoodHeader .....	592
InvoiceWoodLineItem.....	595
InvoiceWoodSummary .....	599
IsAverageValue [attribute].....	601
IsBindingHandSeparation [attribute] .....	601
IsBoxed [attribute] .....	601
IsEaselBound [attribute].....	602
IsFinalInvoice [attribute] .....	602
IsHalftones [attribute].....	602
ISOCountryCode [attribute] .....	602
IsOptionalDestination [attribute].....	603
IsPalletized [attribute].....	603
IsPartialIndicator [attribute].....	603
IsPartialPalletsAllowed [attribute] .....	603
IssueOrEventID.....	603
IsThirdPartyAdvice [attribute] .....	604
IsThirdPartyShipment [attribute] .....	604
IsTradeRegionAvailable [attribute] .....	604
ItemCount .....	604
ItemDetails.....	605
ItemInfo .....	606
ItemInformation.....	607
ItemisedUsageLineItem .....	608
ItemMeasuringInfo .....	609
ItemReference .....	610
ItemReferenceType [attribute] .....	610
ItemsPerPallet.....	611
ItemsPerTier.....	611
ItemType [attribute] .....	611
JewelBox.....	612
JewelBoxType [attribute].....	613
JobCode.....	613
JobDateTimeRange .....	613
JobDescription .....	614
JobID.....	614
JobInformation.....	614
Joining.....	615
JoiningType [attribute] .....	615
L.....	616
Lab.....	617
LabelBrandName .....	618
LabelCharacteristics .....	618
LabelOrientation [attribute].....	619
LabelPosition .....	619
LabelStock.....	619
LabelStockCharacteristics .....	620
LabelStockLayer .....	620
LabelStockLayerNumber .....	621
LabelStockLayerType .....	621
LabelStyle .....	621
Language [attribute].....	621
LargeEndDiameter .....	622
LastDateOfChange.....	622
Latitude .....	622

---

# papiNet V2R31

---

LayerMaterial .....	623
LayerMaterialName .....	623
LayersPerUnit .....	623
LegStageType [attribute] .....	623
Length .....	624
Length .....	625
Length .....	625
LengthCategory .....	626
LengthCutDescription .....	626
LengthCutType [attribute] .....	626
LengthFromCore .....	627
LengthSpecification .....	627
LicenceNumber .....	628
LightScattering .....	628
LineBaseAmount .....	629
LineItemSubTotal .....	629
LoadAvailable .....	630
LoadAvailableConfirmationIssuedDate .....	631
LoadAvailableHeader .....	632
LoadAvailableHeaderStatusType [attribute] .....	634
LoadAvailableInformation .....	635
LoadAvailableIssuedDate .....	636
LoadAvailableLineItem .....	637
LoadAvailableLineItemNumber .....	639
LoadAvailableLineItemStatusType [attribute] .....	639
LoadAvailableNumber .....	640
LoadAvailableReference .....	640
LoadAvailableReferenceType [attribute] .....	640
LoadAvailableStatusType [attribute] .....	641
LoadAvailableSummary .....	641
LoadAvailableType [attribute] .....	642
LoadingTolerance [attribute] .....	642
LoadNumber .....	642
LoadOpeningSide [attribute] .....	642
LoadReleaseNumber .....	643
LoadTender .....	643
LoadTenderAmount .....	644
LoadTenderHeader .....	645
LoadTenderHeaderStatusType [attribute] .....	647
LoadTenderIssueDate .....	647
LoadTenderLineItem .....	648
LoadTenderLineItemAmount .....	650
LoadTenderLineItemBaseAmountInformation .....	650
LoadTenderLineItemNumber .....	650
LoadTenderNumber .....	650
LoadTenderReference .....	651
LoadTenderReferenceType [attribute] .....	651
LoadTenderResponse .....	652
LoadTenderResponseHeader .....	654
LoadTenderResponseHeaderStatusType [attribute] .....	656
LoadTenderResponseIssueDate .....	657
LoadTenderResponseLineItem .....	658
LoadTenderResponseLineItemNumber .....	660
LoadTenderResponseNumber .....	660
LoadTenderResponseReference .....	660
LoadTenderResponseReferenceType [attribute] .....	661
LoadTenderResponseSegment .....	662
LoadTenderResponseSegmentDocumentStatus [attribute] .....	664
LoadTenderResponseSegmentNumber .....	665

---

# papiNet V2R31

---

LoadTenderResponseSegmentStatusType [attribute] .....	665
LoadTenderResponseStatusType [attribute].....	665
LoadTenderResponseSummary .....	666
LoadTenderResponseType [attribute] .....	667
LoadTenderSegment .....	668
LoadTenderSegmentDocumentStatus [attribute] .....	670
LoadTenderSegmentNumber .....	670
LoadTenderSegmentStatusType [attribute] .....	670
LoadTenderStatusType [attribute].....	671
LoadTenderSummary .....	671
LoadTenderType [attribute] .....	672
LocationCode .....	672
LocationIdentifier .....	672
LocationInformation .....	673
LocationParty .....	674
LocationQualifier [attribute] .....	675
LocationType [attribute] .....	676
LocationType [attribute] .....	676
Log.....	677
LogCharacteristics .....	677
LogConversionRule [attribute] .....	678
LogisticsRole [attribute] .....	679
LogLengthType [attribute] .....	679
LogPackagingCharacteristics .....	679
Longitude .....	680
LumberGrade .....	681
LumberSpecies.....	682
Luminance.....	683
Machine .....	684
MachineConditions .....	685
MachineDownTime.....	685
MachineID .....	686
MachineLocation.....	686
MachineSpeed.....	686
MachineStoppage [attribute] .....	687
Magenta.....	687
MailAttachment .....	688
MailAttachmentType [attribute] .....	688
MakeTo .....	688
ManufacturingProcess .....	689
ManufacturingProcessAgency [attribute] .....	689
ManufacturingProcessType [attribute].....	690
ManufacturingSpecifications .....	692
MapCoordinates .....	693
MapCoordinateType [attribute] .....	693
MapPoint .....	695
MapPointComment.....	696
MapPointDisplayType [attribute] .....	696
MapPointName .....	696
MapPointType [attribute] .....	696
MapReferenceSystem [attribute].....	698
Margins.....	700
MasterReelWidth .....	700
MasterSource [attribute] .....	701
MasterStorageOption .....	701
MaterialCharacteristics .....	702
MaxCurrencyValue .....	704
MaximumClampingForce.....	704
MaximumGrossWeight.....	704

---

# papiNet V2R31

---

MaximumHeight .....	705
MaximumNumberOfJoins .....	705
MaximumOffcut .....	706
MaximumOrderQuantity .....	706
MeasurementModule .....	707
MeasurementsAre [attribute] .....	707
MeasurementSystem.....	707
MeasuringAgency [attribute] .....	707
MeasuringCode .....	708
MeasuringDate .....	708
MeasuringDescription .....	709
MeasuringEquipment.....	709
MeasuringEquipmentCode.....	709
MeasuringLineID .....	710
MeasuringLocation .....	710
MeasuringMethod [attribute] .....	710
MeasuringMethodType [attribute] .....	710
MeasuringNumber .....	711
MeasuringParty .....	711
MeasuringSpecification .....	712
MeasuringTicket .....	713
MeasuringTicketHeader .....	714
MeasuringTicketIssueDate .....	715
MeasuringTicketNumber .....	716
MeasuringTicketReference .....	716
MeasuringTicketReferenceType [attribute].....	717
MeasuringTicketSequence .....	718
MeasuringTicketSequenceLineItem.....	721
MeasuringTicketSequenceLineItemNumber .....	723
MeasuringTicketSequenceNumber .....	723
MeasuringTicketStatusType [attribute] .....	723
MeasuringTicketSummary .....	724
MeasuringTicketType [attribute] .....	724
MeasuringType [attribute] .....	725
MechanicalMaterial .....	725
MechanicalMaterialCharacteristics .....	726
MechanicalMaterialDescription .....	726
Media .....	727
MediaLength .....	728
MediaType [attribute] .....	728
MerchantParty.....	729
Method [attribute] .....	729
MethodOfPayment .....	730
MillCharacteristics.....	730
MillJoinLocation .....	731
MillJoinNumber.....	731
MillOrderInformation .....	731
MillOrderLineItemNumber .....	732
MillOrderNumber .....	732
MillParty.....	732
MillProductionInformation .....	733
Millwork .....	733
MinCurrencyValue.....	734
MinimumOrderQuantity .....	734
Minutes.....	734
MixedProductPalletIndicator [attribute] .....	735
MixProductIndicator [attribute].....	735
MobilePhone .....	735
ModulusElasticity [attribute].....	735

---

# papiNet V2R31

---

Moisture.....	736
MoistureContent.....	737
MoistureContentPercentage [attribute].....	737
MonetaryAdjustment.....	739
MonetaryAdjustmentAmount.....	741
MonetaryAdjustmentLine.....	741
MonetaryAdjustmentReferenceLine.....	741
MonetaryAdjustmentStartAmount.....	741
MonetaryAdjustmentStartQuantity.....	741
Month.....	742
Mullen.....	743
MWeight.....	744
Name1.....	744
Name2.....	745
Name3.....	745
NameAddress.....	746
NASTA [attribute].....	747
NaturalWoodSiding.....	748
NaturalWoodSidingCharacteristics.....	749
NaturalWoodSiding-Other.....	751
NaturalWoodSiding-OtherCharacteristics.....	752
NetAmount.....	754
NetChargeAmount.....	754
NoiseReduction [attribute].....	754
NonPressComponent.....	755
NonStandardPulp.....	755
NumberOfAttachments.....	756
NumberOfBands.....	756
NumberOfBindComponents.....	756
NumberOfColours.....	756
NumberOfComplaintLineItemDetail.....	756
NumberOfComplaintResponseLineItemDetail.....	756
NumberOfDocuments.....	756
NumberOfDocumentsRequired.....	757
NumberOfGoodsReceiptPackages.....	757
NumberOfHits.....	757
NumberOfHoles.....	757
NumberOfInventoryChangeLineItemDetails.....	757
NumberOfInventoryStatusLineItemDetails.....	757
NumberOfItemMeasuringInfo.....	757
NumberOfLabels.....	758
NumberOfMillJoins.....	758
NumberOfPackages.....	758
NumberOfPackingListItems.....	758
NumberOfPages.....	758
NumberOfPlies.....	758
NumberOfRibbons.....	758
NumberOfSides.....	758
NumberOfSignatures.....	759
NumberOfUncompletedMeasuredItems.....	759
NumberOfWraps.....	759
NumberOrderDocumentRequired.....	759
NumberPerProduct.....	759
NumericValue.....	760
OldInformationalQuantity.....	761
OldInventoryClass.....	762
OldQuantity.....	763
Opacity.....	765
OrderConfirmation.....	766

---

# papiNet V2R31

---

OrderConfirmationHeader .....	768
OrderConfirmationHeaderStatusType [attribute] .....	771
OrderConfirmationHeaderStatusTypeText .....	771
OrderConfirmationIssuedDate .....	771
OrderConfirmationLineItem .....	773
OrderConfirmationLineItemDocumentStatus [attribute] .....	777
OrderConfirmationLineItemDocumentStatus [attribute] .....	777
OrderConfirmationLineItemNumber .....	778
OrderConfirmationLineItemStatusType [attribute] .....	778
OrderConfirmationLineItemStatusTypeText .....	778
OrderConfirmationNumber .....	778
OrderConfirmationReference .....	779
OrderConfirmationReferenceType [attribute] .....	779
OrderConfirmationStatusType [attribute] .....	780
OrderConfirmationSummary .....	781
OrderConfirmationWood .....	783
OrderConfirmationWoodHeader .....	785
OrderConfirmationWoodLineItem .....	788
OrderConfirmationWoodProductGroup .....	792
OrderConfirmationWoodSummary .....	793
OrderContextType [attribute] .....	795
OrderDocumentRequired .....	795
OrderHeaderStatusType [attribute] .....	796
OrderLineItemDocumentStatus [attribute] .....	796
OrderLineItemStatusType [attribute] .....	797
OrderPrimaryStatus .....	797
OrderQuantities .....	797
OrderSecondaryStatus .....	798
OrderStatus .....	798
OrderStatusCode [attribute] .....	799
OrderStatusDetail .....	801
OrderStatusHeader .....	804
OrderStatusInformation .....	805
OrderStatusInformationDate .....	806
OrderStatusNumber .....	806
OrderStatusReference .....	806
OrderStatusReferenceType [attribute] .....	807
OrderStatusRequestDetail .....	808
OrderStatusRequestDetailType [attribute] .....	810
OrderStatusResponseDate .....	810
OrderStatusType [attribute] .....	811
OrderStatusType [attribute] .....	811
OrderType [attribute] .....	811
OrderType [attribute] .....	812
OrderType [attribute] .....	813
OrganisationUnit .....	814
OrganisationUnitCode .....	814
OrganisationUnitName .....	814
OrganisationUnitType [attribute] .....	814
OrientationWithFaceWoodPanelGrain [attribute] .....	815
Original [attribute] .....	815
OtherDate .....	815
OtherParty .....	817
OtherTreatment .....	817
Overlay .....	818
OverlaySide [attribute] .....	818
PackageAgency [attribute] .....	818
PackageCharacteristics .....	819
PackageCode .....	820

---

# papiNet V2R31

---

PackageIdentifier.....	820
PackageIDInformation.....	820
PackageInformation.....	821
PackageLevel [attribute].....	824
PackageMeasuringInfo.....	824
PackageName.....	825
PackageReference.....	825
PackageReferenceType [attribute].....	825
PackagesPerWrap.....	826
PackageType [attribute].....	826
PackageType.....	827
Packaging.....	828
PackagingCharacteristics.....	828
PackagingCode.....	829
PackagingCodeSpecification.....	830
PackagingDescription.....	830
PackagingInformation.....	831
PackingList.....	832
PackingListDate.....	833
PackingListHeader.....	834
PackingListItem.....	836
PackingListItemNumber.....	837
PackingListItemType [attribute].....	838
PackingListNumber.....	838
PackingListReference.....	838
PackingListReferenceType [attribute].....	839
PackingListStatusType [attribute].....	839
PackingListSummary.....	839
PackingUnit.....	841
PackingUnitMeasurements.....	842
PackingUnitSerialNumber.....	842
PackingUnitType [attribute].....	843
PagesPerSet.....	843
PagesPerSignature.....	843
Pagination.....	843
PalletAdditionsType [attribute].....	843
PalletCharacteristics.....	844
PalletCoverType [attribute].....	846
PalletLedgeType [attribute].....	846
PalletLength.....	847
PalletPackagingCharacteristics.....	847
PalletTopType [attribute].....	848
PalletType [attribute].....	849
PalletWidth.....	850
Paper.....	850
PaperCharacteristics.....	851
PaperSizeType.....	857
PartyIdentifier.....	857
PartyIdentifierType [attribute].....	857
PartyType [attribute].....	861
PasteDiameter.....	866
PatternProfile.....	867
PatternProfileAgency [attribute].....	868
PatternProfileCode.....	868
PatternProfileType [attribute].....	869
PerCarton.....	874
Perforated [attribute].....	874
Perforation.....	875
PerforationType [attribute].....	875

---

# papiNet V2R31

---

PeriodType [attribute] .....	875
Permeability .....	876
PerPallet .....	877
PerReam .....	877
PerTab .....	877
pH.....	878
PiecesPerRow.....	879
PlacementInOrderOfMatter.....	879
PlacementLocation [attribute] .....	880
PlacementReference [attribute] .....	880
PlacementSequence [attribute].....	880
Planning.....	881
PlanningBucket .....	882
PlanningBucketStatusType [attribute].....	883
PlanningHeader .....	884
PlanningIdentifier .....	885
PlanningIssueDate .....	885
PlanningLineItem.....	887
PlanningLineItemNumber.....	889
PlanningMessageNumber .....	889
PlanningProcessType [attribute] .....	889
PlanningReference .....	889
PlanningReferenceType [attribute] .....	890
PlanningRequestDetail.....	890
PlasticMaterial.....	891
PlasticMaterialType [attribute].....	892
PlasticPrinting [attribute] .....	892
PlasticPrintingDescription.....	892
Plate.....	892
PlateType.....	892
PlyAttributes.....	893
PlyBond .....	898
PlyNumber .....	899
PlySet.....	899
PlywoodLayupStructure .....	900
PlywoodMachining .....	900
PlywoodOSBGrade.....	901
PlywoodOSBSpecies.....	901
PlywoodPlyCharacteristics .....	902
PlywoodPlyGrade.....	902
PlywoodPlySet.....	902
Porosity .....	903
PositionInSheet .....	904
PositionMeasuredFrom [attribute] .....	904
PositionOnItem .....	905
PostalCode .....	905
PostConsumerWaste .....	906
PPI .....	907
PreConsumerWaste.....	908
PrepDueDate .....	909
PrepInformation .....	910
PrepNeededDate .....	910
PrepShipDate.....	911
PrepType [attribute] .....	912
PressBreakLocation.....	913
PressComponent .....	913
PressConditions.....	914
PressFormType .....	915
PressImpositionType [attribute].....	915

---

# papiNet V2R31

---

PressPrep .....	915
PressPrepInput.....	916
PressPrepInputType .....	916
PressPrepOutputType [attribute].....	917
PressType [attribute] .....	917
PressureTreatment .....	918
PressureTreatmentCompound.....	919
PressureTreatmentComStdorUseCategory .....	919
PressureTreatmentConcentration .....	920
PriceAdjustment .....	921
PriceAndAmountInfo .....	921
PriceDetails .....	922
PricePerUnit.....	923
PriceQuantityBasis [attribute].....	924
PriceTaxBasis [attribute] .....	925
PrintedMediaSpecs.....	926
PrintingMaterials .....	927
PrintParameters .....	928
PrintType [attribute] .....	928
PrintUnit .....	930
PrintUnitNumber.....	930
PrintUnitType [attribute].....	930
PriorityOrder [attribute] .....	931
ProcessingCode .....	931
ProcessingCodeSpecification.....	931
ProcessingDescription .....	931
Product .....	932
ProductAttributes .....	933
ProductAttributesHeader.....	935
ProductAttributesIssueDate.....	937
ProductAttributesLineItem .....	938
ProductAttributesLineItemStatusType [attribute].....	940
ProductAttributesProductURL.....	940
ProductAttributesReference.....	941
ProductAttributesReferenceType [attribute] .....	941
ProductAttributesStatusType [attribute].....	942
ProductAttributesType [attribute].....	942
ProductBasisSizeType [attribute] .....	942
ProductDescription.....	943
ProductGroupID .....	944
ProductGroupIDType [attribute] .....	944
ProductGroupSummary .....	944
ProductIdentification .....	945
ProductIdentifier .....	945
ProductIdentifierType [attribute].....	946
ProductionLastDateOfChange .....	948
ProductionRunNumber.....	948
ProductionStatus .....	948
ProductionStatusType [attribute] .....	949
ProductPackaging .....	950
ProductPercentage.....	951
ProductPerformance.....	951
ProductPerformanceConcerns .....	952
ProductPerformanceConditions .....	953
ProductPerformanceDate .....	953
ProductPerformanceHeader .....	954
ProductPerformanceIssueDate.....	955
ProductPerformanceLineItem.....	956
ProductPerformanceLineItemNumber.....	957

---

# papiNet V2R31

---

ProductPerformanceNumber .....	958
ProductPerformanceReference .....	958
ProductPerformanceReferenceType [attribute] .....	958
ProductPerformanceStatusType [attribute] .....	959
ProductPerformanceSummary .....	959
ProductQuality .....	960
ProductQualityHeader .....	961
ProductQualityIssueDate .....	963
ProductQualityMessageNumber .....	963
ProductQualityPeriod .....	964
ProductQualityPurchaseOrder .....	967
ProductQualityReference .....	969
ProductQualityReferenceType [attribute] .....	970
ProductQualityRequestDetail .....	970
ProductQualityRequestDetailType [attribute] .....	971
ProductQualityShipment .....	972
ProductQualityStatusType [attribute] .....	974
ProductSummary .....	975
ProofApprovalDate .....	975
ProofDueDate .....	976
ProofInformationalQuantity .....	977
ProofType [attribute] .....	978
PropertyAverageValue .....	979
PropertyType [attribute] .....	980
PropertyValue .....	983
Pulp .....	984
PulpCharacteristics .....	986
PulpConcernCode .....	989
PulpConcernDescription .....	989
PulpConcerns .....	989
PulpingProcess [attribute] .....	990
PulpUnitCharacteristics .....	991
PunchedHoleDetails .....	992
PurchaseOrder .....	993
PurchaseOrderDetail .....	994
PurchaseOrderHeader .....	996
PurchaseOrderHeaderStatusType [attribute] .....	998
PurchaseOrderInformation .....	999
PurchaseOrderIssuedDate .....	1000
PurchaseOrderLineItem .....	1001
PurchaseOrderLineItemDocumentStatus [attribute] .....	1004
PurchaseOrderLineItemNumber .....	1004
PurchaseOrderLineItemStatusType [attribute] .....	1005
PurchaseOrderNumber .....	1005
PurchaseOrderReference .....	1005
PurchaseOrderReferenceType [attribute] .....	1006
PurchaseOrderReleaseNumber .....	1006
PurchaseOrderStatusType [attribute] .....	1006
PurchaseOrderSummary .....	1007
PurchaseOrderType [attribute] .....	1008
PurchaseOrderWood .....	1009
PurchaseOrderWoodHeader .....	1011
PurchaseOrderWoodLineItem .....	1014
PurchaseOrderWoodProductGroup .....	1018
PurchaseOrderWoodSummary .....	1019
Quantity .....	1021
QuantityByProperty .....	1022
QuantityDeviation .....	1023
QuantityInformation .....	1023

---

# papiNet V2R31

---

QuantityInUnit .....	1024
QuantityOrderedInformation .....	1024
QuantityType [attribute] .....	1025
QuantityTypeContext [attribute] .....	1027
QuoteInCurrency .....	1029
RangeMax .....	1030
RangeMin .....	1030
RawMaterialSet .....	1030
ReamItem .....	1031
ReamType .....	1032
ReamWeight .....	1032
ReasonCode [attribute] .....	1033
ReasonDescription .....	1033
ReceiverParty .....	1033
RecoveredPaper .....	1034
RecoveredPaperAttributes .....	1034
Recycled .....	1035
RecycledCharacteristics .....	1036
RecycledRequired [attribute] .....	1036
Red .....	1037
Reel .....	1037
ReelArm .....	1038
ReelBreakDiameter .....	1038
ReelConversionCharacteristics .....	1039
ReelDiameter .....	1040
ReelItem .....	1041
ReelLength .....	1042
ReelPackagingCharacteristics .....	1043
ReelsPerPack .....	1044
ReelStandUnit .....	1045
ReelWidth .....	1045
referenceType [simple type] .....	1045
Reissued [attribute] .....	1061
RelativeLocation [attribute] .....	1061
RemitToParty .....	1061
RequestedAction .....	1062
RequestingParty .....	1062
RequestNumber .....	1063
Resistance .....	1063
RespondByDate .....	1064
RespondToParty .....	1065
ResultSource [attribute] .....	1066
ReturnReason .....	1066
ReturnReasonCode .....	1067
ReturnReasonDescription .....	1067
ReturnType [attribute] .....	1067
RewoundIndicator [attribute] .....	1068
RFQ .....	1068
RFQHeader .....	1069
RFQHeaderStatusType [attribute] .....	1071
RFQInformation .....	1072
RFQIssuedDate .....	1072
RFQLineItem .....	1073
RFQLineItemDocumentStatus [attribute] .....	1076
RFQLineItemNumber .....	1076
RFQLineItemStatusType [attribute] .....	1076
RFQNumber .....	1076
RFQReference .....	1077
RFQReferenceType [attribute] .....	1077

---

# papiNet V2R31

---

RFQRespondByDate .....	1077
RFQResponse.....	1078
RFQResponseHeader .....	1080
RFQResponseHeaderStatusType [attribute] .....	1082
RFQResponseHeaderStatusTypeText .....	1083
RFQResponseIssuedDate .....	1083
RFQResponseLineItem.....	1084
RFQResponseLineItemDocumentStatus [attribute] .....	1087
RFQResponseLineItemPriceDetail .....	1087
RFQResponseLineItemStatusType [attribute] .....	1088
RFQResponseLineItemStatusTypeText .....	1088
RFQResponseNumber .....	1088
RFQResponseReference .....	1089
RFQResponseReferenceType [attribute] .....	1089
RFQResponseStatusType [attribute] .....	1090
RFQResponseSummary .....	1091
RFQResponseValidityDate .....	1093
RFQStatusType [attribute] .....	1093
RFQSummary .....	1094
RFQType [attribute] .....	1095
RGB.....	1095
Ribbon .....	1096
RibbonExposure .....	1096
RibbonFacingType [attribute] .....	1096
RibbonMaterialCharacteristics .....	1097
RingCrush .....	1098
RoadAccessibilityType [attribute] .....	1099
RoadAvailability.....	1099
RoadBearingCapacity .....	1100
RoadBearingCapacityType [attribute] .....	1100
RoadCharacteristics .....	1101
RoadClassification.....	1102
RoadClassificationCode.....	1103
RoadClassificationDescription .....	1103
RoadKeeperType [attribute] .....	1103
RoadName.....	1103
RoadNumber.....	1104
RoadObstruction.....	1104
RoadObstructionType [attribute].....	1105
RoadOwnerType [attribute].....	1106
RoadPassingPossibility [attribute] .....	1106
RoadSlopePercent.....	1106
RoadTurningPointType [attribute] .....	1106
RoadTurningPossibilityType [attribute].....	1106
Roof .....	1107
RoofingSidingDeckingFencing .....	1107
RoofPackage .....	1108
RoofPanel.....	1108
RoofTruss.....	1108
Roughness .....	1109
RoundCornered [attribute].....	1110
Route .....	1110
RouteComment .....	1111
RouteDefinition .....	1112
RouteDefinitionFormat [attribute] .....	1112
RouteLeg.....	1112
RouteLegLength .....	1113
RouteLegName.....	1113
RouteLegNumber.....	1114

---

# papiNet V2R31

---

RouteLength .....	1114
RouteName .....	1114
RouteType [attribute] .....	1114
RowsPerUnit .....	1115
RunnabilityIndex .....	1115
SafetyAndEnvironmentalCertification .....	1116
SafetyAndEnvironmentalInformation .....	1117
SafetyAndEnvironmentalType [attribute] .....	1118
SalesOfficeParty .....	1119
SampleSize .....	1120
SampleType [attribute] .....	1120
Saturation .....	1121
Sawdust .....	1122
ScaleHouseID .....	1123
ScaleHouseIn .....	1123
ScaleHouseInfo .....	1124
ScaleHouseName .....	1125
ScaleHouseOut .....	1125
ScaleHouseTicketNumber .....	1126
ScalerID .....	1126
ScalerName .....	1126
ScaleTicket .....	1127
ScaleTicketAcceptance [attribute] .....	1128
ScaleTicketHeader .....	1129
ScaleTicketIssueDate .....	1131
ScaleTicketLineItem .....	1132
ScaleTicketLineNumber .....	1133
ScaleTicketNumber .....	1133
ScaleTicketReference .....	1133
ScaleTicketReferenceType [attribute] .....	1134
ScaleTicketRejectedType [attribute] .....	1134
ScaleTicketStatusType [attribute] .....	1135
ScaleTicketSummary .....	1136
Scored [attribute] .....	1136
Screened [attribute] .....	1137
Seasoning .....	1137
SeasoningType [attribute] .....	1137
Secure [attribute] .....	1138
SenderParty .....	1138
SenderProductAttributesDescription .....	1139
SenderProductAttributesIdentifier .....	1139
SenderProductAttributesName .....	1139
SequenceNumber .....	1140
ServiceLevel .....	1140
ServiceLevelContextType [attribute] .....	1140
ServiceLevelReference .....	1141
ServiceLevelReferenceType [attribute] .....	1141
ServiceLevelText .....	1141
ShapeOfHole [attribute] .....	1141
SetNumber .....	1142
SetPosition .....	1142
ShapeOfHole [attribute] .....	1142
Sheet .....	1142
SheetConcern .....	1143
SheetConcernCode .....	1143
SheetConcernDescription .....	1144
SheetConcernType [attribute] .....	1144
SheetConversionCharacteristics .....	1145
SheetCount .....	1146

---

# papiNet V2R31

---

SheetCountMethodType [attribute] .....	1147
SheeterConcerns .....	1147
SheeterConditions .....	1148
SheetItem .....	1148
SheetPackagingCharacteristics .....	1150
SheetSize .....	1151
ShellColour .....	1152
ShellType [attribute] .....	1152
ShipFromCharacteristics .....	1152
ShipFromParty .....	1153
ShipmentComplete [attribute] .....	1154
ShipmentDetails .....	1154
ShipmentDetailsType [attribute] .....	1155
ShipmentEventDate .....	1155
ShipmentEventDuration .....	1156
ShipmentEventIdentifier .....	1156
ShipmentEventInformation .....	1157
ShipmentEventQualifierType [attribute] .....	1158
ShipmentEventReference .....	1159
ShipmentEventReferenceType [attribute] .....	1159
ShipmentEventType [attribute] .....	1159
ShipmentID .....	1160
ShipmentIDType [attribute] .....	1160
ShipmentIncident .....	1161
ShipmentIncidentAccountability .....	1162
ShipmentIncidentCategory .....	1163
ShipmentIncidentCause .....	1163
ShipmentIncidentCode .....	1164
ShipmentIncidentDate .....	1165
ShipmentIncidentPartOfSupplyChain .....	1165
ShipmentLoadDetails .....	1167
ShipmentMethodOfPayment .....	1169
ShipmentStatus .....	1169
ShipmentStatusDate .....	1170
ShipmentStatusDescription .....	1170
ShipmentStatusHeader .....	1171
ShipmentStatusIdentifier .....	1172
ShipmentStatusIssueDate .....	1172
ShipmentStatusNumber .....	1173
ShipmentStatusReference .....	1173
ShipmentStatusReferenceType [attribute] .....	1173
ShipmentStatusRequestDetail .....	1174
ShipmentStatusSearchReference .....	1175
ShipmentStatusSearchReferenceType [attribute] .....	1175
ShipmentStatusShipment .....	1176
ShipmentStatusType [attribute] .....	1177
ShipmentSummary .....	1178
ShippingInstructions .....	1179
ShippingInstructionsConfirmationIssuedDate .....	1180
ShippingInstructionsHeader .....	1181
ShippingInstructionsHeaderStatusType [attribute] .....	1182
ShippingInstructionsInformation .....	1183
ShippingInstructionsIssuedDate .....	1184
ShippingInstructionsLineItemByProduct .....	1185
ShippingInstructionsLineItemByShipTo .....	1186
ShippingInstructionsLineItemNumber .....	1188
ShippingInstructionsLineItemStatusType [attribute] .....	1188
ShippingInstructionsNumber .....	1188
ShippingInstructionsPurchaseOrderLineItem .....	1189

---

# papiNet V2R31

---

ShippingInstructionsReference .....	1189
ShippingInstructionsReferenceType [attribute] .....	1190
ShippingInstructionsRequestDetail .....	1191
ShippingInstructionsStatusType [attribute] .....	1192
ShippingInstructionsSummary .....	1192
ShippingInstructionsType [attribute] .....	1193
ShippingMark .....	1193
ShipToCharacteristics .....	1193
ShipToInformation .....	1194
ShipToParty .....	1195
ShowThrough .....	1196
Side .....	1197
SideOneTime .....	1198
SideTwoTime .....	1198
SignatureID .....	1198
Signatures .....	1198
SingleWidthReel .....	1198
SingleWidthReelConversionCharacteristics .....	1199
SizeOfHolePunch .....	1200
Sizing .....	1201
Sleeve .....	1202
SleeveInsertType .....	1202
Slide .....	1203
SlideContainerDescription .....	1204
SlideContainerMail .....	1204
SlideMailerSizeDescription .....	1204
SlideMountCaptions [attribute] .....	1205
SlideMountDescription .....	1205
SlideMountMaterial .....	1205
SlideMountNumbering [attribute] .....	1205
SlidesPerPage .....	1205
SlitReel .....	1206
SlitReelLineNumber .....	1206
SlitReelOrderQuantity .....	1207
SlitReelReference .....	1208
SlitReelReferenceType [attribute] .....	1208
SlitReelsInSet .....	1208
SlitReelWidth .....	1209
Slurry .....	1209
SmallEndDiameter .....	1210
Smoothness .....	1211
SoftwoodLumber .....	1212
SoftwoodLumberCharacteristics .....	1213
SoftwoodPlywood .....	1216
SpanRating .....	1218
SpecAssembly .....	1218
SpecBinding .....	1220
SpecComponent .....	1222
SpecGeneral .....	1224
SpecGroupingID .....	1225
SpeciesAgency [attribute] .....	1225
SpeciesCode .....	1226
SpeciesOrigin [attribute] .....	1226
SpeciesType [attribute] .....	1227
SpecificationNumber .....	1232
SpecInformation .....	1232
SpecIssueDate .....	1232
SpecPacking .....	1233
SpecReference .....	1234

---

# papiNet V2R31

---

SpecReferenceType [attribute] .....	1235
SpecStatusType [attribute] .....	1235
SpecType [attribute] .....	1235
SpecVersion.....	1236
SpeedType [attribute] .....	1236
SpineLabel [attribute] .....	1236
SpineLabel [attribute] .....	1236
SpineSize .....	1236
StackingMethod .....	1237
StacksPerPallet .....	1237
StandardDeviation .....	1237
StandardSpacing .....	1237
StartIdentifierRange .....	1237
Statement .....	1238
StatementDetail .....	1239
StatementHeader .....	1241
StatementInformation .....	1242
StatementNumber .....	1243
StatementRequestDetail .....	1243
StatementRequestType [attribute] .....	1244
StatementResponseDate .....	1244
StatementType [attribute] .....	1245
StateOrProvince .....	1245
StateOrProvince [attribute] .....	1245
StatisticalGoodsInformation .....	1245
Status [attribute] .....	1246
StatusAsOfDate.....	1246
StencilCharacteristics .....	1247
StencilContent [attribute] .....	1248
StencilFormat [attribute] .....	1250
StencilInkType [attribute] .....	1250
StencilLocation [attribute] .....	1251
StencilText .....	1251
StencilType [attribute] .....	1251
Stiffness.....	1252
StopOffInformation.....	1253
StrengthGroup .....	1253
Stretch .....	1254
SubClassification .....	1255
SubClassificationCode .....	1255
SupersType [attribute] .....	1256
Supplemental.....	1256
SupplementalSpecification [attribute] .....	1256
SuppliedComponentFinishSpecs.....	1257
SuppliedComponentInformation.....	1258
SuppliedComponentReference .....	1260
SuppliedComponentReferenceType [attribute] .....	1260
SuppliedComponentType [attribute] .....	1260
SupplierCustomsReference.....	1261
SupplierCustomsReferenceType [attribute] .....	1261
SupplierMarks .....	1261
SupplierOrderLineItemNumber .....	1262
SupplierOrderNumber .....	1262
SupplierParty .....	1262
SupplyPoint .....	1263
SupplyPointCode .....	1263
SupplyPointDescription.....	1264
Surface .....	1264
SurfaceStrength .....	1265

---

# papiNet V2R31

---

SurfaceType [attribute]	1266
Tabs [attribute]	1266
TambourID	1267
TapeDescription	1267
TargetMoisture	1267
TargetProductWeight	1267
TargetSolidsContent	1268
TaxAdjustment	1269
TaxAmount	1270
TaxCategoryType [attribute]	1270
TaxLocation	1270
TaxPercent	1270
TaxStatement	1271
TaxStatementCode	1271
TaxStatementDescription	1271
TaxType [attribute]	1272
TEA	1273
Tear	1274
TearIndex	1276
TearStripType [attribute]	1277
Telephone	1277
Tensile	1278
TensileIndex	1279
Tension	1280
TermsAndDisclaimers	1281
TermsBasisDate	1281
TermsBasisDateType [attribute]	1282
TermsDescription	1283
TermsDiscountDaysDue	1283
TermsDiscountDueDate	1283
TermsDiscountPercent	1284
TermsInformation	1284
TermsInterestPenaltyPercent	1285
TermsNetDaysDue	1285
TermsNetDueDate	1285
TermsOfChartering	1286
TermsOfCharteringType [attribute]	1286
TermsOfDelivery	1286
TermsOfPayment	1288
TermsOfPaymentCode	1289
TestAgency [attribute]	1289
TestMethod [attribute]	1290
TextValue	1290
Thickness	1291
Thickness	1292
Thumb	1292
TiersPerPallet	1293
TimberCharacteristics	1293
Time	1293
TimePeriod	1294
TimeSlot	1295
TimeSlotAvailability [attribute]	1295
TimeSlotInformation	1295
To	1296
ToProduct	1296
TopSide [attribute]	1298
TotalAdjustments	1298
TotalAmount	1298
TotalBlanketOrderValue	1298

---

# papiNet V2R31

---

TotalFASAmount .....	1299
TotalInformationalAmount .....	1299
TotalInformationalQuantity .....	1300
TotalNetAmount .....	1301
TotalNetOfTermsDiscount .....	1302
TotalNumberOfLineItems .....	1303
TotalNumberOfPackingListItems .....	1303
TotalNumberOfPackingListPackingUnits .....	1303
TotalNumberOfSequences .....	1303
TotalNumberOfShipments .....	1303
TotalNumberOfUnits .....	1303
TotalOldInformationalQuantity .....	1304
TotalOldQuantity .....	1306
TotalOpenAmount .....	1307
TotalPageCount .....	1307
TotalPaymentAmount .....	1307
TotalQuantity .....	1308
TotalQuantityInformation .....	1309
TotalRunningLength .....	1310
TotalSetNumbers .....	1311
TotalSetPositions .....	1311
TotalTaxAmount .....	1311
TotalTermsDiscountAmount .....	1311
TotalTermsDiscountAmountDue .....	1311
TotalTermsDiscountNetAmount .....	1312
TotalTermsDiscountNetAmountDue .....	1312
TotalTermsDiscountNetAmountTax .....	1312
TotalTermsDiscountTaxAmount .....	1313
TotalTime .....	1313
TrackingReferenceID .....	1313
TrackingReferenceIDType [attribute] .....	1314
TrackType [attribute] .....	1314
TradeRegion .....	1314
TransactionHistoryConfirmationNumber .....	1314
TransactionHistoryNumber .....	1315
TransportationComment .....	1315
TransportContextType [attribute] .....	1315
TransportDeckOption [attribute] .....	1315
TransportInformation .....	1316
TransportInstructionCode .....	1317
TransportInstructionText .....	1317
TransportInstructionType [attribute] .....	1318
TransportLoadingCharacteristics .....	1318
TransportLoadingCode .....	1319
TransportLoadingCodeDescription .....	1320
TransportLoadingText .....	1320
TransportLoadingType [attribute] .....	1320
TransportModeCharacteristics .....	1321
TransportModeCode .....	1321
TransportModeText .....	1322
TransportModeType [attribute] .....	1322
TransportOtherInstructions .....	1323
TransportPackageInformation .....	1324
TransportPropertyType [attribute] .....	1326
TransportPropertyValue .....	1327
TransportStatus .....	1328
TransportStatusIssueDate .....	1328
TransportUnitCharacteristics .....	1329
TransportUnitCode .....	1330

---

# papiNet V2R31

---

TransportUnitCount .....	1330
TransportUnitDetail.....	1331
TransportUnitDetailCode.....	1331
TransportUnitDetailType [attribute].....	1332
TransportUnitEquipment.....	1334
TransportUnitEquipmentCode.....	1334
TransportUnitEquipmentDescription.....	1335
TransportUnitHeight.....	1335
TransportUnitIdentifier.....	1336
TransportUnitIdentifierType [attribute].....	1336
TransportUnitLength.....	1337
TransportUnitLevel [attribute].....	1338
TransportUnitMeasurements.....	1338
TransportUnitText.....	1339
TransportUnitType [attribute].....	1339
TransportUnitVariable [attribute].....	1340
TransportUnitWeight.....	1340
TransportUnitWidth.....	1341
TransportUnloadingCharacteristics.....	1341
TransportUnloadingCode.....	1342
TransportUnloadingCodeDescription.....	1342
TransportUnloadingText.....	1343
TransportUnloadingType [attribute].....	1343
TransportVehicleCharacteristics.....	1344
TransportVehicleCode.....	1345
TransportVehicleCount.....	1345
TransportVehicleEquipment.....	1345
TransportVehicleEquipmentCode.....	1346
TransportVehicleEquipmentDescription.....	1346
TransportVehicleHeight.....	1346
TransportVehicleIdentifier.....	1347
TransportVehicleIdentifierType [attribute].....	1347
TransportVehicleLength.....	1348
TransportVehicleMeasurements.....	1349
TransportVehicleText.....	1349
TransportVehicleType [attribute].....	1349
TransportVehicleWeight.....	1350
TransportVehicleWidth.....	1351
TrayColourType [attribute].....	1351
TreeSpeciesGroup.....	1352
TreeSpeciesGroupCode.....	1352
TreeSpeciesGroupDescription.....	1352
Trim.....	1352
TrimmedOrderType.....	1353
TrimmedReel.....	1353
TrimmedReelConversionCharacteristics.....	1354
TrimSize.....	1355
TrimType [attribute].....	1355
TwoSigmaLower.....	1356
TwoSigmaUpper.....	1356
UnCompletedMeasurement [attribute].....	1356
UnevenSpacing.....	1356
UnitCharacteristics.....	1357
UnitDimension.....	1357
UnitItem.....	1358
UnitReference.....	1359
UnitReferenceType [attribute].....	1359
UnitsPerCarton.....	1360
UOM [attribute].....	1360

---

# papiNet V2R31

---

URL .....	1368
URLContext [attribute] .....	1368
Usage .....	1368
UsageHeader .....	1370
UsageHeaderReference .....	1371
UsageIssuedDate .....	1372
UsageLineItem .....	1373
UsageLineItemDetail .....	1374
UsageLineItemNumber .....	1375
UsageNumber .....	1375
UsageReference .....	1376
UsageReferenceType [attribute] .....	1376
UsageStatus [attribute] .....	1376
UsageStatusType [attribute] .....	1377
UsageSummary .....	1378
ValidityPeriod .....	1378
Value .....	1379
VarianceType [attribute] .....	1379
VideoCassette .....	1380
VideoCassetteCaseType [attribute] .....	1381
VideoFormatType [attribute] .....	1381
VirginFibre .....	1382
Viscosity .....	1383
Wall .....	1384
WallPackage .....	1384
WallPanel .....	1384
WasteImpressions .....	1385
WasteQuantity .....	1385
WasteType [attribute] .....	1385
Watermark .....	1386
WatermarkCode .....	1386
WatermarkDescription .....	1386
Webbing .....	1387
WebBreak .....	1387
WebBreakCause .....	1388
WebBreakCauseAgency [attribute] .....	1388
WebBreakCauseCode .....	1392
WebBreakCauseType [attribute] .....	1392
WebBreakDate .....	1393
WebBreakDescription .....	1393
WebBreaks .....	1394
WebBreakType [attribute] .....	1394
WebConcerns .....	1394
WebConfiguration .....	1395
Week .....	1395
Weight .....	1395
Whiteness .....	1396
Width .....	1397
Width .....	1398
Width .....	1399
WindingDirection .....	1399
WireCoating [attribute] .....	1400
WireGauge .....	1400
WireMaterial .....	1400
WithGrain [attribute] .....	1401
WoodBasedPanelGrade .....	1401
WoodItem .....	1402
WoodPanelCharacteristics .....	1403
WoodPanelManufacturingMethod .....	1404

---

# papiNet V2R31

---

---

WoodPanelProducts .....	1405
WoodPanelSpecies .....	1406
WoodProducts .....	1407
WoodTimbersDimensionalLumberBoards .....	1408
Wrap .....	1409
WrapCharacteristics .....	1410
WrapLocation [attribute] .....	1410
WrapProperties [attribute] .....	1410
WrapType [attribute] .....	1411
Year .....	1411
Yellow.....	1412

Data Dictionary: papiNet Version 2.31

**a**

The "a" portion of the method of colour represented by L\*a\*b.


**(sequence)**

The sequence of items below is mandatory. A single instance is required.

**DetailValue**

DetailValue is mandatory. A single instance is required.

A numeric value expressed in the unit of measure (UOM).



**DetailRangeMin**

DetailRangeMin is optional. A single instance might exist.

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

**DetailRangeMax**

DetailRangeMax is optional. A single instance might exist.

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

**StandardDeviation**

StandardDeviation is optional. A single instance might exist.

A statistic used as a measure of dispersion in a distribution.

**SampleSize**

SampleSize is optional. A single instance might exist.

The number of samples used to determine the product characteristic in question.

**TwoSigmaLower**


TwoSigmaLower is optional. A single instance might exist.

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

**TwoSigmaUpper**

TwoSigmaUpper is optional. A single instance might exist.

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.



## Abrasion

A group item used to communicate abrasion loss target or test value.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.


#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*



# papiNet V2R31

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

## AbsorptionInk

A group item used to communicate ink absorption target or test value.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.


### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)



# papiNet V2R31

---

*The sequence of items below is mandatory. A single instance is required.*

## **DetailValue**

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

## **DetailRangeMin**

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

## **DetailRangeMax**

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

## **StandardDeviation**

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## **TwoSigmaUpper**

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

## AbsorptionLight

A group item used to communicate light absorption target or test value.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.


#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*



# papiNet V2R31

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

## AbsorptionWater

A group item used to communicate water absorption target or test value.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.


### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)



# papiNet V2R31

---

*The sequence of items below is mandatory. A single instance is required.*

## **DetailValue**

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

## **DetailRangeMin**

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

## **DetailRangeMax**

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

## **StandardDeviation**

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## **TwoSigmaUpper**

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## **ActionType [attribute]**

Used to trigger an action concerning the element to which it refers.

*This item is restricted to the following list.*

### **Special**

Specifies that an action is required.

### **Standard**

Specifies that no action is required.

attribute	
<b>ActionType</b>	
type	actionType
default	Standard

## ActualNominal [attribute]

Indicates the measurement approach used to communicate the dimensions of the individual pieces.



*This item is restricted to the following list.*

### **Actual**

The measurement approach is based on the actual dimensions of the piece.

### **Covering**

The measurement approach is based on an overlay of the piece.

### **Modal**

The measurement approach is based on statistical data.

### **Nominal**

A stated value rather than the actual value.

## AdditionalTest

AdditionalTest exists to enable the inclusion of a test that has not been identified by papiNet.org. It is always a single-instance element so it is very important that users, who come upon a test that papiNet.org has not identified, communicate the need for this test to us at [www.papiNet.org](http://www.papiNet.org).

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### AdditionalTestName

*AdditionalTestName is mandatory. A single instance is required.*

The name of the additional test being communicated in the product definition.


#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*



# papiNet V2R31

---

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

## **DetailRangeMax**

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

## **StandardDeviation**

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## **TwoSigmaUpper**

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## **AdditionalTestName**

The name of the additional test being communicated in the product definition.

<b>AdditionalTestName</b>	
type	s20

---

## **AdditionalText**

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

<b>AdditionalText</b>	
type	s255

---

## **Address1**

The primary-level address of an organisation or business entity (for example, street name, and number).

<b>Address1</b>	
type	s60

---

## **Address2**


The second-level address of an organisation or business entity.

<b>Address2</b>	
type	s60

---

## Address3


The third-level address of an organisation or business entity.



---

## Address4

The fourth-level address of an organisation or business entity.



---

## AdjustmentFixedAmount

A fixed monetary amount, either negative or positive, that is the value of the adjustment being applied in an instance of the MonetaryAdjustment structure.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.


---

## AdjustmentPercentage

A percentage, either negative or positive, that is applied to either the price, or a starting amount to determine the value of the particular MonetaryAdjustment.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax


*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## AdjustmentType (Financial) [attribute]

Describes the type of adjustment applied to a monetary oriented element. Adjustment values should always be given as negative or positive adjustments even if AdjustmentType indicates the sign. For example, a rebate of 1% on an Invoice should be given as an adjustment percentage of -1%.



*This item is restricted to the following list.*

### **BillOfLadingCharge**

An extra charge for creating a Bill of Lading.

### **CancellationCharge**

A charge applied because a cancellation was late (after the last date of change) and all or part of the ordered product has already been made.

### **CashDiscount**

A reduction due to a discount applied.

### **CertificateCharge**

An extra charge for creating a certificate. Some countries requires Certificates in which different characteristics of the delivery, transport unit, route, product, and others must be proved.

There are certificates for gasen pallets, for the place of production, for the age of the ship/vessel, for not departing from one country's harbour when delivering to another.

### **ChargesForward**

A pending Invoice amount brought forward from a previous Invoice.

### **ClaimAdjustment**

An adjustment related to a filed complaint.

### **Commission**

Commission costs paid to the trading agency or trader.

### **CompetitiveAllowance**

An allowance provided for competitive reasons.

### **CongestionCharge**

An extra fee from ports for waiting time of ships in ports, railcars on a siding, trucks at a dock. (Synonym: Demurrage.)

### **ConsigneeUnloadCharge**

An unloading charge that is the responsibility of the consignee.

### **ContractAllowance**

An allowance for a volume discount, usually because the agreed amount has been exceeded.

## **CurrencyAdjustmentCharge**

An extra fee to adjust for currency variations.

## **DecimalRounding**

Adjustments for rounding of total amounts to fit the business agreement or national monetary legislation.

For example, Finland does not use smaller than 5 cent coins. All cash payments are rounded to a 5 cent divisible amount according to national legislation. Alternatively, certain market segments prefer to remove all decimals.

## **DefectiveAllowance**

An allowance provided for defective material.

## **DeliveryCharge**

The charge for delivering the product.

## **DeliveryNonConformanceAllowance**

An allowance due to non-conformance with the purchase agreement regarding a delivery.

## **DeliveryTimeBonus**

A bonus given for deliveries of products within a certain time period.

## **EarlyShipAllowance**

An allowance due to a delivery that took place earlier than planned. The seller may be charged a penalty. If this is found before issuing the Invoice, it can be handled through this allowance. If found later, it will be handled through a credit note.

## **EnergySurcharge**

A charge related to increases in the cost of energy.

## **Environmental**

An allowance applied due to environmental regulations.

## **ExpeditedShipmentCharge**

An extra cost charged due to unexpected or emergency requirements (for example, breaking off a run in the mill to reach the production date for a rush order).

## **ExportClearanceCharge**

An extra fee for customs administration.

## **FlatRateCharge**

A general flat charge.

## **FreightAllowance**

The freight cost allowed by the mill. This amount is negative, and will be deducted from the Invoice (U.S. business practice, in the European Union (EU), use only Freight Charge).

**FreightCharge**

The actual cost incurred to deliver the product. This amount is positive, and will be added to the Invoice.

**FuelAdjustmentCharge**

An extra fee, usually from shipping companies, to adjust fuel prices.

**HandlingCharge**

A charge related to the handling of the product.

**Inspection**

The cost associated with performing an inspection of the product.

**InterestCharge**

A charge applied for interest on overdue payments.

**LabourAllowance**

An allowance due to additional labour required in the use or acceptance of the product.

**LabourCharge**

A charge due to additional labour required in the use or acceptance of the product.

**LoggingDamage**

An adjustment caused by logging damages on Forest Wood products. Logging damages normally cause a reduction of the product price.

**LotCharge**

A charge applied to the lot of material.

**MetalDetection**

A charge for additional metal detection applied to the goods.

**ModelHomeDiscount**

A discount associated with the building of the model home.

**NewStoreCouponDiscount**

A discount associated with entry into a new store.

**OrderQuantity**

A charge or allowance for small/big ordered quantities.

**PalletCharge**

A charge that represents the cost or rental of the pallet.

**PickUpAllowance**

An allowance provided to compensate for the cost of picking up the product.

**PromotionalAllowance**

An allowance provided for the promotion of the product.

**PromotionalCharge**

A charge associated with the promotion of the product.

**PriceCorrection**

An adjustment associated with a correction of the product's price.

**ProductionSetUpCharge**

A special charge applied due to specific buyer requests.

**Provision**

The act of making ready or equipping for use.

**Rebate**

A rebate accepted by the buyer and seller based on the agreed price and volume.

**ReelDiscount**

An allowance for purchasing reels instead of sheets.

**ReturnedLoadAllowance**

An allowance applied due to the return of the load.

**ReturnLoadCharge**

A charge applied due to the return of the load.

**RoadFeeCharge**

A freight charge for a special tax applied to road transports in some countries, e.g. Germany

**ScrapAndDunnageCharge**

A charge that represents the scrapping of the material and its removal.

**ServiceCharge**

A charge associated with a miscellaneous service.

**SpecialConversionCharge**

Additional charge for a special conversion of the product.

**SpecialDeliveryCharge**

A special charge for delivering the product differently from the usual or agreed-to method.

**SpecialHandlingCharge**

A special charge for handling the product differently from the usual or agreed-to method.

**SpecialPackagingCharge**

A special charge for packaging the product differently from the usual or agreed-to method, or if packaging as requested is out of spec.

**StopOffAllowance**

An allowance for a delivery stop-off.

**StopOffCharge**

A charge for a delivery stop-off.

**StorageAllowance**

An allowance for storing the product.

## **StorageCharge**

An extra cost charged for storing the product on location (in the plant).

## **Tax**

An adjustment that reflects a tax item.

## **TestingCharge**

A charge related to testing a paper grade.

## **TradeDiscount**

A discount based on the terms of the trade given on the agreed price. Usually a percentage.

## **TrialDiscount**

A discount applied for a trial run of a new or improved product.

## **TransferCharge**

A freight charge incurred by the goods transfer from one location to another location not previously agreed upon.

## **UnloadingAllowance**

An allowance to compensate for the unloading the product.

## **UnloadingCharge**

A charge for the unloading the product.

## **VolumeDiscount**

A rebate accepted by the buyer and the seller based on the agreed volume

## **WarRiskCharge**

An extra fee from transport companies for transport units that cross war zones.

## **Other**

Any other adjustment not covered by the attribute list.

---

## **AdjustmentType (Tare) [attribute]**

Describes the type of adjustment associated with a quantity.

*This item is restricted to the following list.*

attribute
<b>AdjustmentType</b>
type   adjustmentTypeTare

### **Advances**

Product samples that are typically used by the Publisher sales people as product samples in the selling cycle.

### **Core**

The adjustment is describing the core.

### **Ends**

The volume of short pieces for calculation of the "ends discount". In the timber

business traditionally 'ends' refers to a time when ships were stowed tightly. Short timber pieces were used in this job and customers were given a discount because of the possible damage to these pieces. Today short lengths are in some cases sold for lower price because folks can't use these efficiently (short lengths are between 1.8 - 2.4 m).

## **Excess**

The adjustment is describing a quantity that is the difference between the actual quantity and the contractual quantity. An Excess quantity can e.g. occur when actual dimensions are greater than contractual dimensions.

## **IncludesOverage**

Quantity contains an amount over the order quantity for purposes of spoilage and contractual overproduction.

Example: PO to Printer/Binder has an order quantity of 10,000 and there is a supplied component for the cover under one of the line-items with a quantity of 10,800. Including the AdjustmentType attribute with a setting of IncludesOverage explains the difference in the order quantity for the book vs. the supplied component quantity.

## **IncludesPlannedOverProduction**

The adjustment is describing a quantity that is a planned overrun production of the component or product.

## **MeasuringCorrection**

The adjustment is describing a correction that is based on measuring statistics for populations of products.

## **None**

Used to indicate that there is no adjustment. (Typically used in the scenario where trading partners always want to communicate an adjustment type attribute.)

## **Pallet**

The adjustment is describing the pallet.

## **Reduction**

The adjustment is describing a quantity that is reduced from the actual quantity because of inappropriate content, e.g. a log pile containing snow, ice or logging residues.

## **Samples**

Product samples that are sent to the buyer as an example of the production.

## **SchoolAdoption**

The adjustment is describing text books that will be used by the school districts in that state.

## **Straps**

The adjustment is describing the straps.

## **Total**

The adjustment is describing the total adjustments.

## Wrap

The weight adjustment value is the weight of the wrapper for a reel, the weight of a box for a box of reams, or the weight of any wrapping applied to a pallet.

## WrapCore

The adjustment is describing the wrapping plus the core

---

## AdjustmentTypeReason

Provides additional information about the type of adjustment. Can be viewed as a sub-classification of the adjustment type attribute or as a textual explanation.

<b>AdjustmentTypeReason</b>
type s255

---

## AdjustmentValue


A group element that contains a currency value, either positive or negative, and a measurement value (in other words a price per unit structure) that will be used in the price adjustment AdjustmentValue.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

<b>AdjustmentValue</b>
type pricePerUnit

(sequence)



### CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## Age

Used to report the age of the wood.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)




## Agency [attribute]

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.



*This item is restricted to the following list.*

### AFPA

American Forest and Paper Association.

### ANSI

American National Standards Institute.

### APPITA

Technical Association of the Australian and NZ Pulp and Paper Industry

### ATA

ATA (American Truckers Association)

### BISAC

Book Industry Study Group

### Bowker

The agency that issues the StandardAddressNumber (www.bowker.com).

**BSI**

British Standards Institute (refer to [bsi-global.com](http://bsi-global.com) for more information).

**Buyer**

The buyer has defined the codes used in the particular element of the transaction. Care must be used when using this agency to assure that the recipient of the e-Document understands what is being communicated. (Not to be used for logistics buyer, see LogisticsBuyer.)

**Carrier**

The carrier has defined the codes used in the particular element of the transaction. Care must be used when using this agency to assure that the recipient of the e-Document understands what is being communicated.

**CCTI**

Composite Can and Tube Institute

**CEN**

European Committee for Standardisation (<http://www.cenorm.be>)

**CEPI**

Confederation of European Paper Industries.

**CoSe**

Agency for the the wood processing industry. ([www.commonsense.at](http://www.commonsense.at))

**Customs**

Any customs agency.

**DUNS**

Dun & Bradstreet.

**EAN**

European Article Numbering Agency.

**ECTA-EPCA-CEFIC**

European Chemical Transport Association, European Petrochemical Association, European Chemical Council. Information about the joint guidelines developed by these agencies can be found at [www.ecta.be](http://www.ecta.be).

**EndUser**

The end-user has defined the codes used in the particular element of the transaction. Care must be used when using this agency to assure that the recipient of the e-Document understands what is being communicated

**FINFO**

Article numbering agency and system in some Nordic countries for all building products. ([www.finno.se](http://www.finno.se))

**Forwarder**

The OtherParty indicated by party type "Forwarder" or when communicating OrderStatus the party indicated by ForwarderParty.

**FSC**

Forest Stewardship Council

## **GCA**

Graphic Communications Association. (This agency now calls itself IDEAlliance.)

## **GCA-CCTI**

The GCA and CCTI combined coding

## **GOST**

Russian federal agency on technical regulating and metrology  
(<http://www.gost.ru>)

## **IFRA**

INCA FIEJ Research Association (Technical Research and Consulting Association for the Newspaper Industry).

## **Intrastat**

The agency responsible for collecting statistics on the physical trade of goods between the members of the EU.

## **ISO**

International Organisation for Standardisation.

## **ISRI**

Institute of Scrap Recycling Industries

## **LogisticsBuyer**

The buyer of the logistics service has defined the codes used in the particular element of the transaction. Care must be used when using this agency to assure that the recipient of the e-Document understands what is being communicated.

## **LogisticsSeller**

The seller of the logistics service has defined the codes used in the particular element of the transaction. Care must be used when using this agency to assure that the recipient of the e-Document understands what is being communicated.

## **LogisticsSupplier**

The supplier of the logistics service has defined the codes used in the particular element of the transaction. Care must be used when using this agency to assure that the recipient of the e-Document understands what is being communicated.

## **Mill**

The OtherParty indicated by party type "Mill" or when available the party indicated by MillParty.

## **NOBB**

Norwegian Building Products database, (Norsk ByggvareBase)

## **NMFTA**

National Motor Freight Traffic Association (NMFTA)

**NPTA**

National Paper Trade Association.

**Ondule**

European Association of Corrugated Base Papers Manufacturers (actually Ondule).

**PEFC**

[www.pefc.org](http://www.pefc.org)

**PMS**

Pantone Matching System is a colour matching system that is widely used in the book industry. See [www.pantone.com](http://www.pantone.com) for more information.

**PPPC**

Pulp and Paper Products Council

**Publisher**

The person, company or organization responsible for placing a book, journal, or other publication on the market (as opposed to the printer or bookseller); also referred to as the "buyer".

**RASI**

Article numbering agency and system in Finland for building products. ([www.rasi.fi](http://www.rasi.fi))

**RevenueCanada**

Canadian Revenue Agency. See [www.cra.gc.ca](http://www.cra.gc.ca)

**RVR**

Agency maintaining codes for the German wood supply segment. RVR is the abbreviation for "RahmenVereinbarung für den Rohholzhandel in Deutschland". ([www.rvr-deutschland.de](http://www.rvr-deutschland.de)).

**SD**

Agency maintaining codes for the Norwegian wood supply segment ([www.skogdata.no](http://www.skogdata.no)).

**SDC**

Agency maintaining codes for the Swedish wood supply segment ([www.sdc.se](http://www.sdc.se)).

**Seller**

The seller of the product has defined the codes used in the particular element of the transaction. Care must be used when using this agency to assure that the recipient of the e-Document understands what is being communicated. (Not to be used for logistics seller, see LogisticsSeller.)

**Supplier**

The supplier has defined the codes used in the particular element of the transaction. Care must be used when using this agency to assure that the recipient of the e-Document understands what is being communicated. (Not to be used for logistics supplier, see LogisticsSupplier.)

## TAPPI

Technical Association for the Paper and Pulp Industry

## UCC

The Uniform Code Council.

## UIC

International Union of Railways. (<http://www.uic.org>)  
(Union Internationale des Chemins de fer)

## UN/ECE

The United Nations – Economic Commission for Europe

## WarehouseOperator

## WCO

World Customs Organization (refer to [wcoomd.org](http://wcoomd.org) for more information).

## XBITS

XML Book Industry Transaction Standards

## Other

Used when the agency responsible for a coding system is not defined in the attribute list, or there is no agency responsible for the codes used.

## AggregatedUsageLineItem


A group item that summarises item usage at the Product level or at the Product plus PurchaseOrder level. Details concerning the individual items used are not included.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Product

*Product is*



*mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

#### OtherParty

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-

Document.

## PurchaseOrderInformation

*PurchaseOrderInformation is optional. A single instance might exist.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

## PurchaseOrderLineItemNumber

*PurchaseOrderLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the PurchaseOrder line item.

## Quantity

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## InformationalQuantity

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## BasisWeightVariation

*BasisWeightVariation is optional. A single instance might exist.*

BasisWeightVariation is the measured difference between the mill target basis weight and the mill actual basis weight.

---

## Alignment

A measurement of how the reel is aligned on printing press

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value


*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.



## RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)


---

## Altitude

The height of a location above a ground reference point as specified by the map reference system.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)


---

## AmbientTemperature

The temperature of the surrounding environment.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax


*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## Amount

An element that contains the amount including tax. The Amount encapsulates CurrencyValue.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### CurrencyValue


*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

---

## AmountSubjectToTermsDiscount

The amount against which prompt payment terms can be applied.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*


The amount in the referenced currency as defined by the CurrencyType attribute.

---

## AmountType [attribute]

Defines the type of amount.

*This item is restricted to the following list.*



### Adjustment

Adjustment amount, i.e. the sum of all instances of PriceAdjustment and FlatAmountAdjustment but excluding tax amounts.

### Net

Net amount, i.e. an amount excluding tax

### Tax

Tax amount

### TermsDiscountNet

The prompt payment discount amount excluding tax.

### Total

Total amount, i.e. an amount including tax.

## Appearance

A group item used to communicate appearance.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin


*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the



parent of this element.

## StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## AppliesTo [attribute]

Specifies the type of item to which measurements apply to.


*This item is restricted to the following list.*

### Payload

Measurements apply to the payload.

### Unit

Measurements apply to the transport unit.




---

## ArrivalDate

The date of arrival.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is mandatory. A single instance is required.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone

# papiNet V2R31

is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## Ash

A group item used to communicate the ash content of the product according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).



# papiNet V2R31

---

## **DetailRangeMin**

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

## **DetailRangeMax**

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

## **StandardDeviation**

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## **TwoSigmaUpper**

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## **AssemblyInstructions**

Instructions for assembly.

<b>AssemblyInstructions</b>
type   s255

---

## **AssemblyType [attribute]**

Assembly type

*This item is restricted to the following list.*

**AVC**

**BulkPack**

**Capsule**

**CDBookStyle**

**CDOSleeve**

**CDWallet**

**CO/CR/CF-1**

**CO/CR/CF-2**

attribute
<b>AssemblyType</b>
type   assemblyType

CO/CR/CF-3

CO/CR/CF-4

CPN1

CPN2

CPN3

CPN4

DCN1

DCN2

ICanRead

OCard

PVCBag

UAB

UAS6

UAS8

---

## AssignedBy [attribute]

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

*This item is restricted to the following list.*



### **Auditor**

A third party that is authorized for making audits and checkings.

### **Bank**

The banking representative.

### **BillTo**

The address where the Invoice is to be sent. (Not to be used for logistics BillTo, see LogisticsBillTo.)

### **BorderCrossing**

A geographic location separating two countries authorised to validate customs documentation.

### **Broker**

The organisation acting as a broker for the buyer or supplier.

### **Buyer**

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the "Payer", the "Buyer" is the "Payer". (Not to be used for logistics buyer, see LogisticsBuyer.)

### **BuyerAgent**

The entity acting for the buyer in the transaction. (Not to be used for logistics BuyerAgent, see LogisticsBuyerAgent.)

**Carrier**

The organisation or business entity that transports goods.

**CarrierAssignmentResponsible**

The organisation to which the carrier has assigned some task.

**ComponentVendor**

Vendor producing supplied components.

**Consignee**

To be deprecated in version 3.0 (no date determined). Use LogisticsRole attribute to communicate this information.

**Consignor**

To be deprecated in version 3.0 (no date determined). Use LogisticsRole attribute to communicate this information.

**Consuming**

The eventual consumer of the material

**Converter**

The organisation responsible for changing one form of paper into another form, providing specialised functions not available to the supplier.

**CreditDepartment**

The party responsible for credit authorization.

**CrossDock**

A third party involved in the transport of goods.

**CustomerFacility**

The type of the origin or destination location of a transport leg in a route is a buyer facility, usually a print site, or a warehouse owned by the buyer.

**CustomerStock**

A "virtual" location that indicates that the material is owned by the customer.

**Customs**

Any customs agency.

**CustomsForwarder**

A forwarder responsible for managing the transfer of goods through customs.

**DomesticForwarder**

A forwarder responsible for managing the transfer of goods.

**EndUser**

EndUser is the party using, consuming, or converting the product. For example, a printer using paper reels to print a job for a publisher (printer is the end user). The final ShipTo destination for a product is normally to the EndUser facilities.

**ExportForwarder**

A forwarder responsible for managing the export process.

**ForestForwarder**

The party responsible for transporting forest wood products from logging areas to roadside landings.

**ForestHarvester**

The party responsible for harvesting of forest wood products at logging areas.

**Forwarder**

The party responsible for shipping arrangements.

**FreightPayer**

The party responsible for paying freight.

**Insurer**

The party providing insurance coverage for the goods.

**Landowner**

The party who owns the land upon which the product was produced.

**LoadingOperator**

A party that is carrying out loading of transport units.

**LoggingArea**

A geographic location in the forest where logging takes place.

**LogisticsBillTo**

The address where the logistics Invoice is to be sent.

**LogisticsBuyer**

The buyer of logistics services. The legal entity to which the service is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the "LogisticsPayer", the "LogisticsBuyer" is the payer.

**LogisticsBuyerAgent**

The entity acting for the logistics buyer in the transaction.

**LogisticsSeller**

The seller of logistics services. LogisticsSupplier is the seller of the service, if logistics seller is not specified as OtherParty = LogisticsSeller

**LogisticsSupplier**

The party responsible for providing the service. LogisticsSupplier is also the seller of the service, if logistics seller is not specified as OtherParty = LogisticsSeller

**LogisticsPayee**

The party handling and receiving logistics payments on behalf of another party.

**LogisticsPayer**

The party handling and sending logistics payments of behalf of another party.

**MainCarrier**

The primary carrier involved in the movement of goods.

**Measurer**

The party that's carrying out the measurement of the products quantity and/or quality. The party is doing this for example on behalf of both the buyer and seller and the result can be used as basis for invoicing.

**Merchant**

A third party buying and reselling products.

**Mill**

A production facility.

**NotifyParty**

A party that needs to be notified of the status of the transaction.

**OnBehalfOf**

The activity in question is being made on behalf of this party.

**OrderParty**

The organisation or business entity placing the order if different from the buyer party.

**OriginalSupplier**

The first supplier in a supply chain. OriginalSupplier is only intended to identify the business party, not the origin of the product.

**Payee**

The party handling and receiving payments on behalf of another party. (Not to be used for logistics payee, see LogisticsPayee.)

**Payer**

The party handling and sending payments of behalf of another party. (Not to be used for logistics payer, see LogisticsPayer.)

**PlaceFinalDestination**

The final destination of the goods.

**PlaceOfAccept**

The location where acceptance of the goods is to take place.

**PlaceOfDespatch**

The location where despatch took place.

**PlaceOfDischarge**

The location where the goods were unloaded.

**PlaceOfLoading**

The location where loading is to or took place.

**PlaceOfMeasuring**

The location where the products are measured.

**PlaceOfReloading**

A location where the goods were transferred from one transport type to another.

**Port**

The type of the origin or destination location of a transport leg in a route. It is a maritime location.

**PreCarrier**

The party responsible for activities prior to carrier accepting the goods (but after shipping has taken place).

**PrinterFacility**

The location of the printer who will be using the product.

**ProFormalInvoice**

The organisation or business entity to which the pro-forma Invoice will be sent.

**Producer**

The manufacturer of the goods.

**RemitTo**

The organisation or business entity to which payment will be made.

**Requestor**

The originator of the original PurchaseOrder requisition (for example, a printing plant ordering through a central purchasing organisation).

**RoadKeeper**

The party who is responsible for the maintenance of the road.

**RoadOwner**

The party who is the legal owner of the road.

**SalesAgent**

The organisation or person responsible for product sales acting on behalf of the seller.

**SalesOffice**

The functional unit in an organisation or business entity that is responsible for product sales.

**Seller**

The seller of the product. SupplierParty is the seller of the product, if Seller is not specified as OtherParty = Seller. (Not to be used for logistics seller, see LogisticsSeller.)

**ShipFromLocation**

The location the goods were shipped from.

**ShipOwner**

The owner of the vessel used to ship the goods.

**ShipTo**

The address the material should be shipped to.

**SubCarrier**

# papiNet V2R31

---

A sub carrier of another the shipping company.

## **Supplier**

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller. (Not to be used for logistics supplier, see LogisticsSupplier.)

## **Terminal**

The type of the origin or destination location of a transport leg in a route. It can be a sea, road or rail terminal.

## **TerminalOperator**

The party providing facilities such as loading, unloading, or warehousing.

## **UnloadingOperator**

A party that is carrying out unloading of transport units.

## **Warehouse**

A storage location. It can be the origin or destination location of a transport leg in a route.

## **WillAdvise**

Indicates that party will be identified at a later time

## **Other**

Any other organisation or business entity that may get involved in the transaction and that is not covered by the list.

---

## **AttachmentFileName**

The name of the attached file.

<b>AttachmentFileName</b>
type   s60

## AudioCassette

Audio cassette

### SpineLabel [attribute]

*SpineLabel is optional. A single instance might exist.*

Is there a spine label?

Refer to SpineLabel definition for any enumerations.

### NoiseReduction [attribute]

*NoiseReduction is optional. A single instance might exist.*

The noise reduction method

Refer to NoiseReduction definition for any enumerations.

### DuplicationRatio [attribute]

*DuplicationRatio is optional. A single instance might exist.*

Duplication ratio

Any valid string

### TrackType [attribute]

*TrackType is optional. A single instance might exist.*

The type of track

Refer to TrackType definition for any enumerations.

### Tabs [attribute]

*Tabs is optional. A single instance might exist.*

The type of tabs

Refer to Tabs definition for any enumerations.

### AudioCassetteCaseType [attribute]

*AudioCassetteCaseType is optional. A single instance might exist.*


Describes the type of audio cassette case.

Refer to AudioCassetteCaseType definition for any enumerations.

### AudioCassetteTapeLengthType [attribute]

*AudioCassetteTapeLengthType is optional. A single instance might exist.*

Describes the length of the tape used in the audio cassette. The number indicates the expected number of minutes the tape will run.



Refer to AudioCassetteTapeLengthType definition for any enumerations.

## **ShellType [attribute]**

*ShellType is optional. A single instance might exist.*

The type of shell

Refer to ShellType definition for any enumerations.

## **AssemblyType [attribute]**

*AssemblyType is optional. A single instance might exist.*

Assembly type

Refer to AssemblyType definition for any enumerations.

## **WrapType [attribute]**

*WrapType is optional. A single instance might exist.*

Communicates the type of material used to wrap the product.

Refer to WrapType definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **SequenceNumber**

*SequenceNumber is optional. A single instance might exist.*

### **ShellColour**

*ShellColour is optional. A single instance might exist.*

Shell colour

### **TapeDescription**

*TapeDescription is optional. A single instance might exist.*

Tape description

### **MediaLength**

*MediaLength is optional. A single instance might exist.*

Media length

### **CassetteLabelCharacteristics**

*CassetteLabelCharacteristics is optional.*

Cassette label characteristics

### **CassetteCardReference**

*CassetteCardReference is optional. A single instance might exist.*

Cassette card reference

### **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## AudioCassetteCaseType [attribute]

Describes the type of audio cassette case.

*This item is restricted to the following list.*

**PolyBox**

**BlackClearNorelco**

**ClearClearNorelco**

**OCard**



---

## AudioCassetteTapeLengthType [attribute]

Describes the length of the tape used in the audio cassette. The number indicates the expected number of minutes the tape will run.

*This item is restricted to the following list.*

**C-10**

A tape length of 10 minutes.

**C-15**

A tape length of 15 minutes.

**C-20**

A tape length of 20 minutes.

**C-25**

A tape length of 25 minutes.

**C-30**

A tape length of 30 minutes.

**C-35**

A tape length of 35 minutes.

**C-40**

A tape length of 40 minutes.

**C-45**

A tape length of 45 minutes.

**C-50**

A tape length of 50 minutes.

**C-55**

A tape length of 55 minutes.

**C-60**

A tape length of 60 minutes.

**C-65**



A tape length of 65 minutes.

**C-70**

A tape length of 70 minutes.

**C-75**

A tape length of 75 minutes.

**C-80**

A tape length of 80 minutes.

**C-85**

A tape length of 85 minutes.

**C-90**

A tape length of 90 minutes.

**C-95**

A tape length of 95 minutes.

**C-100**

A tape length of 100 minutes.

**C-105**

A tape length of 105 minutes.

**C-110**

A tape length of 110 minutes.

**C-115**

A tape length of 115 minutes.

**C-120**


A tape length of 120 minutes.

---

## Availability

The Availability element is the root element for the Availability e-Document.

The purpose of the Availability e-Document is to provide a means to ask about the availability of the specified product. The amount of the product immediately available (on-hand) is anticipated to be returned. Optionally, the anticipated availability of the product at a point in future can be communicated.



### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**AvailabilityHeader**

*AvailabilityHeader is mandatory. A single instance is required.*

The AvailabilityHeader contains items that apply to the entire Availability e-Document.

**AvailabilityDetail**

*AvailabilityDetail is mandatory. One instance is required, multiple instances might exist.*

AvailabilityDetail provides the detailed availability information for the requested product.

## AvailabilityDetail

AvailabilityDetail provides the detailed availability information for the requested product.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**Product**

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification.  
Book



Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.


**TimePeriod**

*TimePeriod is mandatory. A single instance is required.*

The TimePeriod element is used to communicate a duration period of time as indicated in PeriodType.

**Quantity**

*Quantity is optional. A single instance*



*might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

### **(sequence)**

*The sequence of items below is optional. A single instance might exist.*

#### **LocationParty**

*LocationParty is mandatory. A single instance is required.*

The organization or business entity where the business event took place or will take place.

#### **MachineID**

*MachineID is optional. A single instance might exist.*

An identifier assigned to the particular machine being referenced. For example, a machine could be a paper machine, an off-line coater, a sheeter, or a printing press. The particular machine being referenced will be determined by the business event being supported.

## **PackageInformation**

*PackageInformation is optional. Multiple instances might exist.*

The purpose of the PackageInformation structure is to clearly identify physical handling items that constitute the delivery.

PackageInformation is the highest level of product packaging it describes the shipping or warehousing unit.

If you are communicating a package, usually for logistics or transport purposes, you should include the PackageType, Identifier, ItemCount, and Quantity. (Note: you still have the ability to describe the item with one of the "named" items.)

If you are communicating one of the named Items there is no need to include PackageType, Identifier, ItemCount, and Quantity.

Since either of these two approaches can be used the entire contents of this element are optional even though the parent may be required. It is expected that you will fill in the appropriate details.

## **LengthSpecification**

*LengthSpecification is optional. Multiple instances might exist.*

Length specification of the wood product.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## OtherDate

*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## SafetyAndEnvironmentalInformation

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

## AvailabilityHeader

The AvailabilityHeader contains items that apply to the entire Availability e-Document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### AvailabilityNumber

*AvailabilityNumber is mandatory. A single instance is required.*

An element that contains the unique identifying number of the Availability e-Document.

### AvailabilityIssueDate

*AvailabilityIssueDate is mandatory. A single instance is required.*

The date and time that the Availability was issued.

### RequestNumber

*RequestNumber is optional. A single instance might exist.*


A unique tracking number specifically identifying the InfoRequest e-Document to the originator. The tracking number is returned with the "information", the answer, to help match the answer to the request.

### SenderParty

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.



## ReceiverParty

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## RequestingParty

*RequestingParty is optional. A single instance might exist.*

The party requesting the information.

## BuyerParty

*BuyerParty is optional. Multiple instances might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## ShipToParty

*ShipToParty is optional. Multiple instances might exist.*

The name and/or address to which the goods should be delivered with the party type indicated by the PartyType attribute.

## OtherParty

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## EndUserParty

*EndUserParty is optional. Multiple instances might exist.*

The party using, consuming, or converting the product. For example, a printer using paper reels for a print job for a publisher. The final ShipTo destination for a product is normally to the end user's facilities.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.


---

## AvailabilityIssueDate

The date and time that the Availability was issued.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

# papiNet V2R31

---

A group element that contains the specification of Year, Month, and Day.

## Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

---

## AvailabilityNumber

An element that contains the unique identifying number of the Availability e-Document.

<b>AvailabilityNumber</b>	
type	s30

## AvailabilityStatusRequestDetail

AvailabilityStatusRequestDetail is a conditional element. Its existence is mutually exclusive with that of the InventoryStatusRequestDetail and OrderStatusRequestDetail.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Product

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its



characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

#### TimePeriod

*TimePeriod is optional. A single instance might exist.*

The TimePeriod element is used to communicate a duration period of time as indicated in PeriodType.

#### Quantity

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

#### InformationalQuantity

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.


#### LocationParty

*LocationParty is optional. Multiple instances might exist.*

The organization or business entity where the business event took place or will take place.

#### BuyerParty

*BuyerParty is optional. Multiple instances might exist.*



The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## ShipToParty

*ShipToParty is optional. Multiple instances might exist.*

The name and/or address to which the goods should be delivered with the party type indicated by the PartyType attribute.

## EndUserParty

*EndUserParty is optional. Multiple instances might exist.*

The party using, consuming, or converting the product. For example, a printer using paper reels for a print job for a publisher. The final ShipTo destination for a product is normally to the end user's facilities.

## b

The "b" component of the method of communicating colour termed  $L^*a^*b$ .


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).



#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

#### SampleSize


*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

#### TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.



## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

## Bale


A single or rectangular grouping of product

### BaleType [attribute]

*BaleType is mandatory. A single instance is required.*

Defines the type of bale being produced. A different production process is indicated by each type.

Refer to BaleType definition for any enumerations.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### BaleConversionCharacteristics

*BaleConversionCharacteristics is mandatory. A single instance is required.*

A group element that contains data relevant to the physical characteristics of a bale of product.

#### BalePackagingCharacteristics

*BalePackagingCharacteristics is optional. A single instance might exist.*

A group element containing information relating to packaging of a bale.

## BaleCharacteristics

A group item for actual measurement and manufacturing characteristics for a bale.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### BaleHeight


*BaleHeight is optional. A single instance might exist.*

A measurement of one side of the bale, which, in conjunction with the BaleDepth a BaleWidth make up the three measurements of the bale.

#### BaleWidth

*BaleWidth is optional. A single instance might exist.*

A measurement of one side of the bale, which, in conjunction with the BaleDepth



and BaleHeight make up the three measurements of the bale.

## BaleDepth

*BaleDepth is optional. A single instance might exist.*

A measurement of one side of the bale, in conjunction with BaleHeight and BaleWidth makes up the three measurements of the bale.

## DateMade

*DateMade is optional. A single instance might exist.*

The Date and optionally the Time when an item was produced. DateMade is normally a date before the wrapping and labelling date of the item.

## DateFinished

*DateFinished is optional. A single instance might exist.*

The Date and optionally the Time that an item was finished. For example, this could be the wrapping date for a reel or ream or the date the sheet(s) were packaged in preparation for shipment


---

## BaleConversionCharacteristics

A group element that contains data relevant to the physical characteristics of a bale of product.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



## ConversionCode

*ConversionCode is optional. A single instance might exist.*

A code, as assigned by an Agency, used to identify a group of conversion characteristics.

## BaleHeight

*BaleHeight is optional. A single instance might exist.*

A measurement of one side of the bale, which, in conjunction with the BaleDepth and BaleWidth make up the three measurements of the bale.

## BaleWidth

*BaleWidth is optional. A single instance might exist.*

A measurement of one side of the bale, which, in conjunction with the BaleDepth and BaleHeight make up the three measurements of the bale.

## BaleDepth

*BaleDepth is optional. A single instance might exist.*

A measurement of one side of the bale, in conjunction with BaleHeight and BaleWidth makes up the three measurements of the bale.

## BaleStandardWeight

*BaleStandardWeight is optional. A single instance might exist.*

An individual mill usually produces bales of a target uniform weight to facilitate


storage and stowage.

## BaleDepth

A measurement of one side of the bale, in conjunction with BaleHeight and BaleWidth makes up the three measurements of the bale.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*


The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## BaleHeight

A measurement of one side of the bale, which, in conjunction with the BaleDepth a BaleWidth make up the three measurements of the bale.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## BaleItem

An individual bale included as part of a delivery.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Identifier

*Identifier is optional. Multiple instances might exist.*

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code.

Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.

### (choice)

*[choice] is optional because of choice construct.*

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PartyIdentifier

*PartyIdentifier is mandatory. One instance is required, multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

#### MachineID


*MachineID is optional. A single instance might exist.*

An identifier assigned to the particular machine being referenced. For example, a machine could be a paper machine, an off-line coater, a sheeter, or a printing press. The particular machine being referenced will be determined by the business event being supported.

#### Product

*Product is optional because of choice construct.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper,



Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **Quantity**

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **InventoryClass**

*InventoryClass is optional. A single instance might exist.*

A group item containing information about status of inventory and goods items.

## **BaleCharacteristics**

*BaleCharacteristics is optional. A single instance might exist.*

A group item for actual measurement and manufacturing characteristics for a bale.

## **BaleReference**

*BaleReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the Bale. The type of reference is identified by the attributes BaleReferenceType and AssignedBy.

## **OtherDate**

*OtherDate is optional. Multiple instances might exist.*


A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## BalePackagingCharacteristics

A group element containing information relating to packaging of a bale.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### PackagingCode

*PackagingCode is optional. A single instance might exist.*

PackagingCode is a code describing the packaging of the product.

### CustomerMarks

*CustomerMarks is optional. A single instance might exist.*

The text that the buyer wants the seller to print on the package label or elsewhere.

### StencilCharacteristics

*StencilCharacteristics is optional. Multiple instances might exist.*

A group element specifying attributes of a stencil to be applied to an item, and optional text.

### PulpUnitCharacteristics

*PulpUnitCharacteristics is optional. A single instance might exist.*

A group element that contains information primarily of use for ordering.

## BaleReference

An element detailing relevant references pertaining to the Bale. The type of reference is identified by the attributes BaleReferenceType and AssignedBy.

### BaleReferenceType [attribute]

*BaleReferenceType is mandatory. A single instance is required.*


Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to BaleReferenceType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is mandatory. A single instance is required.*

Identifies the type of party that has assigned the associated item, e.g. a



reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

## BaleReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", Warehouse" or Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute AssignedBy will communicate the information previously communicated in the prefix.

<b>BaleReferenceType</b>	
type	referenceType

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## BalesPerUnit

The number of bales included on the shipping, handling, or delivery unit.


<b>BalesPerUnit</b>	
type	nni2

## BaleStandardWeight

An individual mill usually produces bales of a target uniform weight to facilitate storage and stowage.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax


*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## BaleType [attribute]

Defines the type of bale being produced. A different production process is indicated by each type.

*This item is restricted to the following list.*



### FlashDried

Fibres pressed together to form a bale.

### Sheet

A dried and cut product, stacked, pressed, and packaged together.

### WetLap


A pressed sheet stacked and usually placed on pallets.

## BaleWidth

A measurement of one side of the bale, which, in conjunction with the BaleDepth and BaleHeight make up the three measurements of the bale.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## BandCharacteristics

A group item that organises the packaging band detail information.

### BandType [attribute]

*BandType is optional. A single instance might exist.*

Communicates the type of band to be used on the product package (metal, nylon, plastic)

Refer to BandType definition for any enumerations.

### BandsRequired [attribute]

*BandsRequired is optional. A single instance might exist.*

Communicates whether or not bands are required or not on the product. When this optional element is not included bands are assumed not to be required.

Refer to BandsRequired definition for any enumerations.

### BandDirection [attribute]

*BandDirection is optional. A single instance might exist.*

The direction of the binding material.

Refer to BandDirection definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### NumberOfBands


*NumberOfBands is optional. A single instance might exist.*

The number of bands to be applied to the package.

#### BandColour

*BandColour is optional. Multiple instances might exist.*


The colour of the packaging bands to be applied to the package.



---

## BandColour

The colour of the packaging bands to be applied to the package.



## BandDirection [attribute]

The direction of the binding material.

*This item is restricted to the following list.*

### Long

The binding material is on the long side.

### Short

The binding material is on the short side.

### Both

The binding material is on both the long and the short sides.

attribute
<b>BandDirection</b>
type bandDirectionType

---

## BandLocationType [attribute]

Band location type

*This item is restricted to the following list.*

### Head

The band is located on the top.

### Foot

The band is located on the bottom.

### Both

The band is located on the top and on the bottom.

### None

There is no band.

attribute
<b>BandLocationType</b>
type bandLocationType

---

## BandMaterial

Band material

<b>BandMaterial</b>
type s30

---

## BandsRequired [attribute]

Communicates whether or not bands are required or not on the product. When this optional element is not included bands are assumed not to be required.

*This item is restricted to the following list.*


### Yes

### No

attribute
<b>BandsRequired</b>
type yesNo

## BandType [attribute]

Communicates the type of band to be used on the product package (metal, nylon, plastic)



*This item is restricted to the following list.*

### **Metal**

The band(s) applied to the packaging on the article is/are made of metal.

### **Nylon**

The band(s) applied to the packaging on the article is/are made of nylon.

### **Plastic**

The band(s) applied to the packaging on the article is/are made of plastic.

### **Standard**

The bands used are agreed to by the trading partners involved.

---

## BarcodeSuppliedByPublisher [attribute]

Barcode supplied by publisher

*This item is restricted to the following list.*

**Yes**

**No**



## Bark

Used to report bark content in chips as a detail measurement.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.


#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*



A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper


*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## BaseAmountInfo

A grouping element that contains information about price and base amount without any taxes.



**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### PriceDetails

*PriceDetails is optional. A single instance might exist.*

An element that groups together price information.

### BaseNetAmount


*BaseNetAmount is mandatory. A single instance is required.*

An element that contains the result of the calculation Quantity times the PricePerUnit. As such it does not include any taxes. The BaseNetAmount encapsulates CurrencyValue.

---

## BaseNetAmount

An element that contains the result of the calculation Quantity times the PricePerUnit. As such it does not include any taxes. The BaseNetAmount encapsulates CurrencyValue.



**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

## BasisWeight

The weight of the paper expressed as a mass for a given surface area. In countries using the metric system, the basis weight is expressed as the weight in grams of one sheet of paper that is one square meter in area—not dependent on basic sheet size. In countries using the imperial system, the weight is expressed in pounds for a given ProductBasisSizeType.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### ProductBasisSizeType [attribute]

*ProductBasisSizeType is optional. A single instance might exist.*

An attribute list that indicates the size of paper used as the base for the basis weight calculation


Refer to ProductBasisSizeType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*



# papiNet V2R31

---

A numeric value expressed in the unit of measure (UOM).

## DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

## DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

## StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

## IncrementalValue

*IncrementalValue is optional. Multiple instances might exist.*

Many times paper is produce in BasisWeights of discreet values. This element permits the expression of those increments.

---

## BasisWeightVariation

BasisWeightVariation is the measured difference between the mill target basis weight and the mill actual basis weight.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*


#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin

*RangeMin is optional. A single instance might exist.*



# papiNet V2R31

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

## RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## BendingResistance

Bending resistance

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*


#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*



The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

## **DetailRangeMax**

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

## **StandardDeviation**

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## **TwoSigmaUpper**

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

## BendingStiffness

### BendingStiffness

#### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

#### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

#### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

#### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

#### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax


*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.



## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*


Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## BestBeforeDate

The date, prior to which, the product is suggested to be used.

**(sequence)**



*The sequence of items below is mandatory. A single instance is required.*

### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

---

## Billable [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

**Yes**

**No**




---

## BillOfMaterials

A specification of the components and other items that are used to produce the item in question.

**(sequence)**

*The sequence of items below is mandatory. One instance is required, multiple instances might exist.*



### ProductIdentifier

*ProductIdentifier is mandatory. A single instance is required.*

Used to communicate the code of the article, in a variety of formats designated by

the type.

## ProductDescription

*ProductDescription is optional. Multiple instances might exist.*

An element used to communicate a human readable description of the product in the language specified by the Language attribute.

## Quantity

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## BillToParty

The address where the Invoice is to be sent.

### LogisticsRole [attribute]

*LogisticsRole is optional. A single instance might exist.*

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### PartyIdentifier

*PartyIdentifier is optional. Multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

### NameAddress

*NameAddress is mandatory. A single instance is required.*

A group item containing name and address of an organisation or business entity.


### URL

*URL is optional. A single instance might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

### CommonContact

*CommonContact is optional. Multiple instances might exist.*



Identifies a specific individual associated with the party.

---

## BinaryValue

A value in base-64-encoded binary format.

<b>BinaryValue</b>	
type	xs:base64Binary

## BindingBackingType [attribute]

Binding backing type

*This item is restricted to the following list.*

**Round**

**Flat**

attribute	
<b>BindingBackingType</b>	
type	bindingBackingType

## BindingBackStyleType [attribute]

Binding back style type

*This item is restricted to the following list.*

**Tight**

**Loose**

attribute	
<b>BindingBackStyleType</b>	
type	bindingBackStyleType

## BindingCoverScoring [attribute]

Binding cover scoring

*This item is restricted to the following list.*

**Yes**

**No**

attribute	
<b>BindingCoverScoring</b>	
type	yesNo

## BindingExtras

Binding extras

### EdgeLocationType [attribute]

*EdgeLocationType is optional. A single instance might exist.*

Edge location type.

Refer to EdgeLocationType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### BindingExtrasDescription

*BindingExtrasDescription is mandatory. A single instance is required.*

Binding Extras Description

### Quantity

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

### UnitCharacteristics

*UnitCharacteristics is optional. A single instance might exist.*

Unit characteristics.

### BindingMaterialCharacteristics


*BindingMaterialCharacteristics is optional. Multiple instances might exist.*

Binding Material Characteristics

### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## BindingExtrasDescription

Binding Extras Description



## BindingMaterialCharacteristics

### Binding Material Characteristics

#### FinishType [attribute]

*FinishType is optional. A single instance might exist.*

Defines the finish of a sheet of paper, which means the condition of its surface (refer to Embossing for more information).

Finishes may be produced on or off machine. Finishes that are created off-machine are called embossed. (Embossing is a child element of ReelConversionCharacteristics and SheetConversionCharacteristics.)

Note:

Embossed" as a finish type is just a generalized choice for one of the more specific choices listed.

Unsupercalendered" as a finish type would be indicated by not communicating a finish type.

Refer to FinishType definition for any enumerations.

#### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### BindingMaterialDescription

*BindingMaterialDescription is mandatory. A single instance is required.*

Binding material description

#### BasisWeight

*BasisWeight is optional. A single instance might exist.*

The weight of the paper expressed as a mass for a given surface area. In countries using the metric system, the basis weight is expressed as the weight in grams of one sheet of paper that is one square meter in area—not dependent on basic sheet size. In countries using the imperial system, the weight is expressed in pounds for a given ProductBasisSizeType.

#### ColourCode

*ColourCode is optional. A single instance might exist.*


A code indicating the colour.

#### ColourDescription

*ColourDescription is optional. A single instance might exist.*

A free form description of the colour.

#### ProductIdentification



# papiNet V2R31

---

*ProductIdentification is optional. Multiple instances might exist.*

A grouping element designed to communicate product identification related to the parent element that contains this item.

## **Length**

*Length is optional. A single instance might exist*

The length of the object.

## **Width**

*Width is optional. A single instance might exist*

The width of the object.

---

## **BindingMaterialDescription**

Binding material description

<b>BindingMaterialDescription</b>
type   s72

---

## **BindingReinforcement [attribute]**

Binding reinforcement

*This item is restricted to the following list.*

**Yes**

**No**

attribute
<b>BindingReinforcement</b>
type   yesNo

---

## **BindingRibbon [attribute]**

Binding ribbon

*This item is restricted to the following list.*

**Yes**

**No**

attribute
<b>BindingRibbon</b>
type   yesNo

---

## **BindingStyleType [attribute]**

Indicates the style of binding used.

*This item is restricted to the following list.*

**Accordion**

**Adhesive**

**AdhesiveBurst**

**AdhesiveSewn**

**BoardBook**

**BookLock**

**Burst**

attribute
<b>BindingStyleType</b>
type   bindingStyleType

**CombinationBinding**

**Custom**

**Durasew**

**FlexiBind**

**IMS**

**LayFlatSoft**

**LayflatBind**

**LooseLeaf**

**McCainSideSewn**

**Notch**

**Pad**

**Patent**

**PerfectAdhesive**

**PerfectBound**

**PlasticComb**

**Repkover**

**Ring**

**RoundBound**

**SaddleStitch**

**SaddleWire**

**SelfCover**

**SemiConcealedWireO**

**SideSewn**

**Sidewire**

**SmythSewn**

**Spiral**

**SpiralHardFrontHardBack**

**SpiralSoftFrontHardBack**

**SpiralSoftFrontSoftBack**

**SquareBackSaddleWire**

Saddlewire binding method where the spine is flattened rather than folded.

**Thermal**

Binding method that uses a one piece cover with glue down the spine to quickly and easily bind documents.

**Threadseal**

**ThreadSewn**

**Trim4SideDrill**

**TrimFourSides**

**UltraFan**

**WireO**

**WireOConcealed**

Wire binding where the wire is concealed in the spine of the book.

**Other**

## BindingType [attribute]

Binding type

*This item is restricted to the following list.*

**Hardcover**

**Softcover**


**Layflat**

**Loose**

Finished product consists of loose pages or signatures rather than bound; example is a packet of loose leaf pages that are drilled for insertion into a ring binder.

**Mechanical**

**Self**



## Black

The Black component of a colour.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**DetailValue**

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

**DetailRangeMin**

*DetailRangeMin is optional. A single instance might exist.*


The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

**DetailRangeMax**

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

**StandardDeviation**



*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.


---

## Blanket

Blanket is a group element that contains elements that describe this component of the printing process.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### BlanketType

*BlanketType is optional. A single instance might exist.*

Rubber coated pad mounted on the cylinder of an offset press that receives the inked image and transfers it to the print surface.

### BlanketPacking

*BlanketPacking is optional. A single instance might exist.*

The thickness of the paper that is placed between the cylinder and the blanket to obtain the proper pressure for printing. Usually this ranges from .010 to .008 inches.

---

## BlanketPacking

The thickness of the paper that is placed between the cylinder and the blanket to obtain the proper pressure for printing. Usually this ranges from .010 to .008 inches.



---

## BlanketType

Rubber coated pad mounted on the cylinder of an offset press that receives the inked image and transfers it to the print surface.



## BleachingProcess [attribute]

Communicates the type of bleaching process used to make the pulp fibre

*This item is restricted to the following list.*



### ChlorineBleached

The product is bleached using chlorine.

### ElementaryChlorineFree

The product is bleached using a process that does not use chlorine in its basic or elementary form.

### TotallyChlorineFree

The product is bleached using a process that does not use chlorine in either its basic (elementary form) or in its bound (compound form),

### Unbleached

The product has not gone through a bleaching process.


## Bleed [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

**Yes**

**No**



## Blue

The "Blue" portion of the method of representing colour termed RGB.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).



#### DetailRangeMin


*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.



## StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

## BookBlock

Book block information.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### BookBlockBulk

*BookBlockBulk is optional. A single instance might exist.*

Book block bulk.

#### BookBlockEdgeTrim

*BookBlockEdgeTrim is optional. Multiple instances might exist.*

Book block edge trim.

#### BookBlockFinishExtras

*BookBlockFinishExtras is optional. Multiple instances might exist.*


Book block finish extras.

Refer to BookBlockFinishExtras definition for any enumerations.

#### NumberOfBindComponents

*NumberOfBindComponents is optional. A single instance might exist.*


Total number of components contained in the book block.



## BookBlockBulk

Book block bulk

### (sequence)



The sequence of items below is mandatory. A single instance is required.

## Value

Value is mandatory. A single instance is required.

A numeric value expressed in the unit of measure (UOM).

## BookBlockEdgeTrim

Book block edge trim

### EdgeLocationType [attribute]

EdgeLocationType is optional. A single instance might exist.

Edge location type.

Refer to EdgeLocationType definition for any enumerations.

### (sequence)

The sequence of items below is mandatory. One instance is required, multiple instances might exist.

### EdgeFinish

EdgeFinish is mandatory. A single instance is required.

The finish applied to the edge.

Refer to EdgeFinish definition for any enumerations.

### ColourSpecs


ColourSpecs is optional. A single instance might exist.

Colour specs

### AdditionalText

AdditionalText is optional. Multiple instances might exist.

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## BookBlockFinishExtras

Book block finish extras

This item is restricted to the following list.

**DieCut**


**RoundedCorners**

**ThumbCuts**



## BookClassification

Category under which the product or a component within the product is classified.



### BookClassificationType [attribute]

*BookClassificationType is mandatory. A single instance is required.*

Category under which the product or a component within the product is classified.

Refer to BookClassificationType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ClassificationDescription

*ClassificationDescription is optional. Multiple instances might exist.*

A free form description of the classification.

#### BookSubClassification


*BookSubClassification is optional. Multiple instances might exist.*

Sub Category of the BookClassification under which the product or a component within the product is classified.

## BookClassificationType [attribute]

Category under which the product or a component within the product is classified.

*This item is restricted to the following list.*



### Assembly

### Audio

### Binding

### Book

Written work or composition printed on pages bound together that has been published.

### Box

### Cover

### Endsheet

### Envelope

A paper or cardboard wrapper used to enclose and small, flat items such as a letter for mailing.

## FinishedGoods

## Insert

## Jacket

## Kit

Assembled components that comprise a finished product or package.

## Label

## Material

## Media

## MediaHolder

## MultiVolumeSet

Product that is comprised of multiple books/volumes.

## Other

Part of a finished product that is not a book component such as a toy. The ClassificationDescription can be used to describe the part in more detail.

## Packaging

## Prep

## SlipCase

## Text

## Video

## Wrap

## BookManufacturing

BookManufacturing is a group element that contains the elements that describe the book manufacturing process.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### BookClassification

*BookClassification is optional. Multiple instances might exist.*


Category under which the product or a component within the product is classified.

#### ProofInformationalQuantity

*ProofInformationalQuantity is optional. Multiple instances might exist.*

ProofInformationalQuantity

#### PrepInformation



# papiNet V2R31

---

*PrepInformation is optional. Multiple instances might exist.*

Information related to the preparation of the Book.

## **SuppliedComponentInformation**

*SuppliedComponentInformation is optional. Multiple instances might exist.*

Information about components supplied by the publisher to the vendor i.e. paper supplied to the print vendor or jackets supplied to the bind vendor.

## **PackagingCharacteristics**

*PackagingCharacteristics is optional and repeatable.*

An element containing carton or pallet packing information.  
PackagingCharacteristics can either have the BoxCharacteristics or PalletPackagingCharacteristics element not both.

## BookPackageInformation

The purpose of the BookPackageInformation structure is to clearly identify physical handling items that constitute the delivery.

BookPackageInformation is the highest level of product packaging and describes the shipping or warehousing unit.

### PackageType [attribute]

*PackageType is mandatory. A single instance is required.*

Communicates the configuration of the item being reported.

Refer to PackageType definition for any enumerations.



### MixedProductPalletIndicator [attribute]

*MixedProductPalletIndicator is optional. A single instance might exist.*

Specifies whether a product can be mixed with other products on the same pallet

Refer to MixedProductPalletIndicator definition for any enumerations.

### IsPartialIndicator [attribute]

*IsPartialIndicator is optional. A single instance might exist.*

Specifies if the container (e.g. pallet, box) is partially full or not.

Refer to IsPartialIndicator definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*


#### Identifier

*Identifier is mandatory. One instance is required, multiple instances might exist.*

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.

#### RawMaterialSet

*RawMaterialSet is optional. Multiple instances might exist.*



# papiNet V2R31

---

This identifier derived element indicates a grouping of raw materials that were used to manufacture the product.

## **ItemCount**

*ItemCount is mandatory. A single instance is required.*

A count of the number of items (examples: a count of the number of boxes on a pallet or of reams in a box).

## **Quantity**

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **PackageReference**

*PackageReference is optional. Multiple instances might exist.*

An element detailing the relevant references pertaining to a package. The type of reference is identified by the attributes PackageReferenceType and AssignedBy.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **PalletCharacteristics**

*PalletCharacteristics is optional. A single instance might exist.*

A group item that provides pallet detail information.

## **OtherDate**

*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## **(choice)**

*[choice] is optional because of choice construct.*

### **BaleItem**

*BaleItem is optional because of choice construct.*

An individual bale included as part of a delivery.

### **BoxItem**

*BoxItem is optional because of choice construct.*

A four-sided container for reams or sheet items. A pallet can contain zero or more boxes. The term Carton is a synonym for BoxItem. The term "Box" is used as constraint within the ItemType attribute of the UsageLineItemDetail to refer to a box that contains other boxes.

### **UnitItem**

*UnitItem is optional because of choice construct.*

Unit Item.

## BookSpecification

The BookSpecification element is the root element for the BookSpecification e-Document.

The BookSpecification e-Document represents established product specifications that can be referenced by multiple transactions in the manufacturing life cycle of a product from RFQ through Invoice and subsequent reprints and/or reorders. It captures unique book manufacturing industry data elements as established by the buyer that are needed by the supplier for manufacturing.

### SpecType [attribute]

*SpecType is optional. A single instance might exist.*

Used to identify what type of BookSpecification e-Document this transaction is.

Refer to SpecType definition for any enumerations.

### SpecStatusType [attribute]

*SpecStatusType is optional. A single instance might exist.*

Identifies the status of the entire BookSpecification e-Document (in other words, at the root level).

Refer to SpecStatusType definition for any enumerations.

### NASTA [attribute]

*NASTA is optional. A single instance might exist.*

Used to indicate the specification must conform to the NASTA requirements. Refer to NASTA definition for any enumerations.


### ChildrensTitle [attribute]

*ChildrensTitle is optional. A single instance might exist.*

Specifies if the book product is designated for use by children 12 and under or not.

Refer to ChildrensTitle definition for any enumerations.

**BookSpecification**



## **Secure [attribute]**

*Secure is optional. A single instance might exist.*

This attribute indicates that the product requires a secure manufacturing plant. For example when manufacturing ACT booklets and other testing products.

Refer to Secure definition for any enumerations.

## **Reissued [attribute]**

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

## **Language [attribute]**

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **SpecGeneral**

*SpecGeneral is mandatory. A single instance is required.*

Spec General

### **SpecComponent**

*SpecComponent is optional. Multiple instances might exist.*

Group element used to identify all the necessary component information for this BookSpecification.

Each occurrence of this construct identifies a single component.

### **SpecAssembly**

*SpecAssembly is optional. A single instance might exist.*

SpecAssembly contains assemblies that are used in the manufacturing of books.

### **SpecBinding**

*SpecBinding is optional. A single instance might exist.*

SpecBinding describes the binding process.


### **SpecPacking**

*SpecPacking is optional. Multiple instances might exist.*

SpecPacking defines the book packaging parameters.

## BookSubClassification

Sub Category of the BookClassification under which the product or a component within the product is classified.



### BookSubClassificationType [attribute]

*BookSubClassificationType is mandatory. A single instance is required.*

Sub Category of the BookClassification under which the product or a component within the product is classified.

Refer to BookSubClassificationType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### ClassificationDescription

*ClassificationDescription is optional. Multiple instances might exist.*

A free form description of the classification.

## BookSubClassificationType [attribute]

Sub Category of the BookClassification under which the product or a component within the product is classified.



*This item is restricted to the following list.*

### 2PieceCarton

Type of box where there is a lid that is separate from the bottom.

### AccessCode

A printed card or page that contains a unique code for the purpose of accessing a secure service or device

### Acetate

Component produced with Acetate material which is a transparent or translucent plastic sheet material of a variety of colors, used as a basis for artwork and overlays.

### AdvertisingBrochure

Component printed for purpose of advertising.

### Album

Product manufactured with loose-leaf pages bound by drilling (hole punching).

### Assembly

Product that requires assembly to complete the finished good that usually includes the book and other items such as CDs, toys, etc.

## **Audio**

Audio is a form of multimedia that allows the listener to hear information.

## **BackCoverPanelwShrinkwrap**

Component packaged on the back cover of the book by shrinkwrapping.

## **BackMatter**

Printed matter (usually explanatory) following the main body text of a book, e.g. appendices, bibliography, index etc.

## **BarCode**

Printed matter (usually explanatory) following the main body text of a book, e.g. appendices, bibliography, index etc.

## **BellyBand**

Small strip of paper that wraps around the cover of a book like a dust jacket that usually contains brief publishing information, such as price, printing statement, etc.

also known as a "book band" or "jacket band".

## **Binder**

A cover or holder for unbound papers, pages etc.

## **Binding**

Process of physically assembling a book from a number of folded or unfolded sheets of paper or other material; it also usually involves attaching covers to the resulting book-block.

## **Bind-inSleeve**

Plastic or paper insert that contains a pocket for holding a CD or DVD and is bound inside of the book.

## **BlisterPak**

Pre-formed clear plastic packaging.

## **BlownIn**

Printed promotional piece that is inserted by machine using a "fanning" process during the final production stage of a publication.

## **BluRay**

An optical disc storage medium designed to supersede the standard DVD format.

## **Book**

A written work or composition that has been published (printed on pages bound together).

## **Bookblock**

The gathered and glued or sewn signatures, inserts and other components of the book before the cover is added.

## **Bookmark**

A marker (a piece of paper or ribbon) placed between the pages of a book to

mark the reader's place.

## **Bound**

Secured with a cover or binding.

## **Box**

Box describes a variety of containers and receptacles.

## **BoxWrap**

Material for wrapping the box.

## **Brochure**

A booklet of printed informational matter, like a pamphlet, often for promotional purposes.

## **BubbleBag**

Bags made from bubble cushioning material constructed of pockets of air locked between a top and bottom layer of linear low density polyethylene film.

## **Card**

Type of insert that is usually printed on heavy card stock and placed somewhere in the finished product.

## **Carton**

A specific type of box or container usually made of paperboard and often of corrugated paperboard in which the finished product is packaged.

## **CaseCover**

The cover of a Hardback (casebound) book, usually made of cloth or similar material and boards.

## **Cassette**

A container that holds a magnetic tape used for recording or playing sound or video.

## **CassetteHolder**

A holder usually made of plastic designed to hold the cassette.

## **CD**

Compact Disc; High density storage media based on a 4.75" reflective optical disc.

## **CD-ROM**

Version of the CD that allows the information to be stored and retrieved; once a CD-ROM is pressed, new data cannot be stored and the disc cannot be erased for reuse.

## **Cloth**

Material used for making a casecover.

## **CompanyOwnedStock**

Refers to material that is owned by the publisher.

## **Cover**

Material used on the outside of the book block; refers to the front, back and spine of the book.

## **CoverBack**

Indicates the back cover location.

## **CoverFront**

Indicates the front cover location.

## **Disk**

Generic term for Diskettes, CDs, DVDs.

## **Diskette**

A flexible, oxide-coated disk used to store data.

## **DisketteSleeve**

Plastic or paper insert that contains a pocket for holding the diskette.

## **Divider**

Type of insert that is usually printed on heavy paper and used to divide sections or chapters of a book.

## **Documentation**

The systematic collection of research materials via writing, interviewing, audio and video recording, and photography.

## **DoubleWallCarton**

Corrugated card consisting of a layer of paper / corrugated paper / paper / corrugated paper and finally another layer of paper.

## **DVD**

Digital Versatile Disk; high-capacity optical disk that looks like a CD, but can store much more information.

## **EconoWrap**

A 'fit to book size' low cost thin layer paper container used to package a single book.

## **EndSheet**

Four pages each at the beginning and end of a casebound book, one leaf of each being solidly pasted against the inside board of the case; stock is stronger and heavier than text stock and may be white or colored stock, printed or unprinted. Also called Endpapers, End-leaves or Lining Papers.

## **EndsheetBack**

Specifies the Endsheets that is used to attach the back cover to the book block.

## **EndsheetFront**

Specifies the Endsheets that is used to attach the front cover to the book block.

## **Envelope**

Packaging product, usually made of flat, planar material such as paper or cardboard, and designed to contain a flat object, which in a postal-service context is usually a letter, card or bills.

**FinishedGood**

Completed products awaiting sale.

**FlatSheet**

State of a printed sheetfed component before the flatcut/trimming process.

**FoldedAndGatheredSig**

State of the signature before the trimming process.

**FrontMatter**

Printed matter preceding the main body text of a book, e.g. teacher's guide.

**Gatefold**

Flap from the fore-edge, with a fold running parallel to the spine of the book. The finished page is marginally smaller than the normal trimmed page. A double fold, usually of card or heavy board, from the two outside edges of a folder. The two folded pages meet in the centre of the page, edge to edge, rather like a double gate.

**HalfJacket**

Component, similar to a Jacket, placed around a book to protect the cover; the difference is that this component only partially covers the cover and is glued inside.

**Handbook**

A reference book that provides concise, useful data and other information on a specific subject.

**HollowWrap**

A 'fit to book size' low cost paperboard and fluted material container used to package a single book.

**Insert**

Specially printed piece for insertion in a publication.

**Jacket**

Component placed around a case-bound book to protect the cover.

**Jcard**

Paper card that forms a "J" shape when folded, similar to a Ucard, that is inserted in the plastic storage case of most pre-recorded audio cassette releases; the j-card usually contains an image of the album cover, a track listing, credits, and copyright information.

**JewelCase**

The hinged plastic case in which most CDs are often stored.

**Jiffy**

Thick envelope.

**Jwrap**

Cover-like wrapper that is used to wrap gathered and trimmed signatures.

**Label**

Piece of paper, polymer, cloth, metal, or other material affixed to a container or article, on which is printed a legend, information concerning the product, addresses, etc.; a label may also be printed directly on the container or article.

## **LaserDisc**

A record-like storage medium that uses analogue and laser optical technology to store images.

## **Liner-Corrugation**

Generic term for any paper that functions as a covering for other paper or board material through adhesion, making it a part of the finished product.

## **Loose**

Insert that is not bound into the book.

## **MakeReady**

Machine preparation for each operation in the manufacturing process.

## **Map**

Visual representation of an area.

## **Material**

Refers to paper, cloth or other tangible substance used in the manufacturing of the component or finished good.

## **Media**

Storage devices for audio, video.

## **MediaHolder**

Holder designed for storing/protection of the media.

## **OWrap**

Wrap that fully circles the book (head to foot) and is usually used on shrinkwrapped products.

## **Packaging**

Enclosing or protecting products for distribution, storage, sale, and use.

## **Paper**

Material made of cellulose pulp derived mainly from wood used for the printing process.

## **PaperCover**

Printed sheet used for the outside cover of the book.

## **PeelStickCD**

CD package is made from an adhesive paper-backed material that is applied by removing the paper and exposing the adhesive.

## **Pocket**

Paper, cloth, vinyl or other material made into a pocket either with or without gussets and affixed inside the front or back cover of the book.

## **PolyBag**

Bags are made from 100% virgin polyethylene resin.

## **Prep**

Creation of plates from film or electronic files for the printing process.

## **Preprinted**

Component is printed prior to the manufacturing step.

## **PreprintedCaseside**

Indicates a hardcover created from a printed cover vs. case material.

## **Proof**

A facsimile of press pages for review

## **ReplyCard**

Sender-addressed card included in a mailing on which the recipient indicates a response (positive or negative) to an offer.

## **Run**

"Good" copies produced in each operation in the manufacturing process.

## **SheetSignature**

Refers to the printing of a signature on a sheetfed press.

## **SheetWise**

Sheetfed process where the frontside of all of the components are imposed on one side of the sheet and printed; the plates are changed and then the sheets are then turned over and run back through the press thus completing both sides of the components.

## **Shrinkwrapping**

Protective wrapping for the product made from heat-shrink polyfilm.

## **Signature**

Folded, printed sheet or part of a sheet which forms a section of multiple pages of a book or publication in numerical sequence.

## **SingleWallCarton**

Corrugated card consisting of an outer paper (usually kraft), a single layer of corrugated paper followed by a further layer of paper (usually test).

## **Skagg**

A low cost thin layer paper container used to package a single book.

## **Sleeve**

Plastic or paper insert that contains a pocket for holding another component, usually a type of media.

## **Slide**

Still, positive image created on a transparent base using photochemical means.

## **SlimPack**

CD or DVD slim hinged plastic case in which CDs are stored.

## **SlipCase**

Protective box that holds a book or set of books; slip cases can be made from any material, most often cloth or paper covered cardboard.

## **SlipCaseWrap**

Protective wrapping for a slipcase.

## **SoftwareAccessCode**

A printed card or page that contains a unique code for the purpose of accessing protected software.

## **SoftwareStyle**

A folding carton with top & bottom flaps that includes a "door" on the front of the package with a velcro closure; the purpose is to allow 4 complete surfaces to hold marketing copy.

## **Spine**

Part of a book's cover or jacket, visible when the book is on a shelf.

## **Sticker**

Gummed or adhesive label.

## **SubAssembly**

Group of components that is part of the completed project.

## **SuperJWrap**

Same as Jwrap with the addition of a scored tab which covers the bottom portion of the spine of the book.

## **TCarton**

A carton including a wraparound corner locking flap construction comprising a T-shaped first element joined to part of the carton and two other elements joined to another part of the carton.

## **Tab**

Insert form where a small flap projects out from the thumb edge used for quick access.

## **Text**

The written or printed material which forms the main body of a book.

## **Transparency**

Piece of clear or colored plastic or film used with an overhead projector to make presentations.

## **Transvision**

Set of transparencies that are placed together to create a "full" image but individually contain separate images such as the human body systems.

## **Ucard**

Paper card that forms a "U" shape when folded, similar to a Jcard, that is inserted in the plastic storage case of mostpre-recorded audio cassette releases; the j-card usually contains an image of the album cover, a track listing, credits, and copyright information

## Video

Series of framed images put together, one after another, to simulate motion and interactivity.

## VinylPack

Vinyl material for vacuum packing.

## WebSignature

Component printed on a web press.

## WorkAndBack

Sheetfed process where the press contains enough units to print the front and back of each component in one press run.

## WorkAndTurn

Sheetfed process where the frontside of half of the components and the backside of the remaining components are imposed on one side of the sheet and printed; the sheets are then turned over and run back through the press in the exact same position thus completing both sides of the components without changing the plates.

## Wrap

The cover of a paperback book or covers of a magazine, often printed on colored paper.

## ZipLockBag

Disposable, re-sealable zipper storage bags and containers.

## BookUnitPacking

Book unit packing information

### BookUnitType [attribute]

*BookUnitType is optional. A single instance might exist.*

Book unit type

Refer to BookUnitType definition for any enumerations.

### PackageType [attribute]


*PackageType is optional. A single instance might exist.*

Communicates the configuration of the item being reported.

Refer to PackageType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



## UnitCharacteristics

*UnitCharacteristics is optional. A single instance might exist.*

Unit characteristics.

## LabelCharacteristics

*LabelCharacteristics is optional. Multiple instances might exist.*

A group item that organises the labeling information.

## StencilCharacteristics

*StencilCharacteristics is optional. Multiple instances might exist.*

A group element specifying attributes of a stencil to be applied to an item, and optional text.

## WrapCharacteristics

*WrapCharacteristics is optional. A single instance might exist.*

A group element that contains elements that describe the manner in which the item is wrapped.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## BookUnitType [attribute]

Book unit type

*This item is restricted to the following list.*

### Unit


The book unit is free standing.

### Unit pre-Assembly

The book unit requires previous assembly.

### Unit post-Assembly


The book unit requires post assembly.



---

## BooleanValue

A value in boolean format.



## BoxCharacteristics

BoxCharacteristics is a group element that contains information about the box (or carton)

### BoxType [attribute]

*BoxType is optional. A single instance might exist.*

Communicates the type of carton to use  
Refer to BoxType definition for any enumerations.

BoxCharacteristics

### BoxMeasurementsAppliesTo [attribute]

*BoxMeasurementsAppliesTo is optional. A single instance might exist.*

Used to indicate the nature of the endpoints of the measurement type.  
Refer to BoxMeasurementsAppliesTo definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ProductIdentification

*ProductIdentification is optional. A single instance might exist.*

A grouping element designed to communicate product identification related to the parent element that contains this item.

#### Height

*Height is optional. A single instance might exist.*

The height of the object.

#### Length

*Length is optional. A single instance might exist.*

The length of the object.

#### Width


*Width is optional. A single instance might exist.*

The width of the object.

#### Weight

*Weight is optional. A single instance might exist.*

The weight of the item.



## **Burst**

*Burst is optional. A single instance might exist.*

A group item used to communicate bursting strength target or test value according to a particular TestMethod.

## **BurstIndex**

*BurstIndex is optional. A single instance might exist.*

The burst index.

## **UnitsPerCarton**

*UnitsPerCarton is optional. A single instance might exist.*

The number of units per box.

## **LabelCharacteristics**

*LabelCharacteristics is optional. Multiple instances might exist.*

A group item that organises the labeling information.

## **StencilCharacteristics**

*StencilCharacteristics is optional. Multiple instances might exist.*

A group element specifying attributes of a stencil to be applied to an item, and optional text.

## **WrapCharacteristics**

*WrapCharacteristics is optional. A single instance might exist.*

A group element that contains elements that describes the manner in which the item is wrapped.

## **BandCharacteristics**

*BandCharacteristics is optional. A single instance might exist.*

A group item that organises the packaging band detail information.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## BoxItem

A four-sided container for reams or sheet items. A pallet can contain zero or more boxes. The term Carton is a synonym for BoxItem. The term "Box" is used as constraint within the ItemType attribute of the UsageLineItemDetail to refer to a box that contains other boxes.

### MixProductIndicator [attribute]

*MixProductIndicator is optional. A single instance might exist.*

Specifies whether a product can be mixed with other products on the same shipment.

Refer to MixProductIndicator definition for any enumerations.

### IsPartialIndicator [attribute]

*IsPartialIndicator is optional. A single instance might exist.*

Specifies if the container (e.g. pallet, box) is partially full or not.

Refer to IsPartialIndicator definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Identifier

*Identifier is optional. Multiple instances might exist.*

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.

### (sequence)


*The sequence of items below is optional. A single instance might exist.*

#### PartyIdentifier

*PartyIdentifier is mandatory. One instance is required, multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

#### MachineID



# papiNet V2R31

---

*MachineID is optional. A single instance might exist.*

An identifier assigned to the particular machine being referenced. For example, a machine could be a paper machine, an off-line coater, a sheeter, or a printing press. The particular machine being referenced will be determined by the business event being supported.

## **ItemCount**

*ItemCount is mandatory. A single instance is required.*

A count of the number of items (examples: a count of the number of boxes on a pallet or of reams in a box).

## **Quantity**

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **(choice)**

*[choice] is optional because of choice construct.*

### **ReamItem**

*ReamItem is optional because of choice construct.*

A wrapped quantity of SheetItem(s).

### **SheetItem**

*SheetItem is optional because of choice construct.*

A group item consisting potentially of the date the sheets were converted into sheets and/or packaged or finished.

### **UnitItem**

*UnitItem is optional because of choice construct.*

Unit Item.

## **BoxCharacteristics**

*BoxCharacteristics is optional. A single instance might exist.*

BoxCharacteristics is a group element that contains information about the box (or carton)

## **InventoryClass**

*InventoryClass is optional. A single instance might exist.*

A group item containing information about status of inventory and goods items.

## **BoxReference**

# papiNet V2R31

---

*BoxReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the Box. The type of reference is identified by the attributes `BoxReferenceType` and `AssignedBy`.

## OtherDate

*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the `PurchaseOrderLineItem`).

---

## BoxMeasurementsAppliesTo [attribute]

Used to indicate the nature of the endpoints of the measurement type.


*This item is restricted to the following list.*

### Inside

The measurements provided are for the inside of the box.

### Outside

The measurements provided apply to the outside of the box.



---

## BoxReference

An element detailing relevant references pertaining to the Box. The type of reference is identified by the attributes `BoxReferenceType` and `AssignedBy`.

### BoxReferenceType [attribute]

*BoxReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute `@AssignedBy` will communicate the information previously communicated in the prefix.


Refer to `BoxReferenceType` definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is mandatory. A single instance is required.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type `OrderNumber`.

Refer to `AssignedBy` for any enumerations.



## BoxReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse" or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute AssignedBy will communicate the information previously communicated in the prefix.

<b>BoxReferenceType</b>
type   referenceType

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

---

## BoxType [attribute]

Communicates the type of carton to use

*This item is restricted to the following list.*

### **Corrugated**

The carton type is grooved.

### **DoubleWall**

The carton type has a double wall.

### **SingleWall**

The carton type has a single wall.

### **TripleWall**

The carton type has a triple wall.

attribute
<b>BoxType</b>
type   boxType

---

## Brand

Specifies a brand or trade name of wrapping material to be used when wrapping the product.

<b>Brand</b>
type   s30

## Brightness

A measurement of the degree of light reflectivity of the product.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.


#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*



A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## Brilliance

Measure of brilliance in the HSB colour approach.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

#### SampleSize


*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

#### TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.



## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## BucketType [attribute]

The type of planning information being communicated in the bucket.

*This item is restricted to the following list.*

attribute
<b>BucketType</b>
type   planningBucketType

### **Actual**

The planning information communicates incurred values.

### **Demand**

The planning information communicates requested values.

### **Forecast**

The planning information communicates estimated values.

### **Budget**

The planning information communicates budgeted values.

## Bulk

A group item used to communicate bulking thickness target or test value.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.


#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*



# papiNet V2R31

---

A statistic used as a measure of dispersion in a distribution.

## **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## **TwoSigmaUpper**

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## **BulkNumberOfUnits**

Bulk number of units

<b>BulkNumberOfUnits</b>
type   nni2

## Burst

A group item used to communicate bursting strength target or test value according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*


The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation



*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## BurstIndex

The burst index.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.


### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)



*The sequence of items below is mandatory. A single instance is required.*

## **DetailValue**

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

## **DetailRangeMin**

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

## **DetailRangeMax**

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

## **StandardDeviation**

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## **TwoSigmaUpper**

*TwoSigmaUpper is optional. A single instance might exist.*


Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

## BusinessAcceptance

The BusinessAcceptance element is the root element for the BusinessAcceptance e-Document.

The receiver of a document uses the BusinessAcceptance to confirm to the sender that the document is accepted or rejected. The BusinessAcceptance can be used as a confirmation of acceptance when there is not a papiNet-designed confirmation e-Document available. Although the BusinessAcceptance is optional between two trading partners, its use is strongly recommended when it is important to get a BusinessAcceptance.

**BusinessAcceptance**



### BusinessAcceptanceStatus [attribute]

*BusinessAcceptanceStatus is mandatory. A single instance is required.*

Identifies the status of the BusinessAcceptance.

Refer to BusinessAcceptanceStatus definition for any enumerations.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### BusinessAcceptanceNumber

*BusinessAcceptanceNumber is mandatory. A single instance is required.*

The unique identifier for the BusinessAcceptance.

#### BusinessAcceptanceDate

*BusinessAcceptanceDate is mandatory. A single instance is required.*

The Date and Time when the BusinessAcceptance was issued.

#### SenderParty

*SenderParty is mandatory. A single instance is required.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the

electronic message.

## ReceiverParty

*ReceiverParty is mandatory. A single instance is required.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## Document

*Document is mandatory. A single instance is required.*

A group item containing information applicable to the original document.

## BusinessAcceptanceParty

*BusinessAcceptanceParty is mandatory. A single instance is required.*

The organisation or legal entity authorised to accept or reject e-Document.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.


---

## BusinessAcceptanceDate

The Date and Time when the BusinessAcceptance was issued.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should

be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## BusinessAcceptanceNumber

The unique identifier for the BusinessAcceptance.

<b>BusinessAcceptanceNumber</b>
type s30

## BusinessAcceptanceParty

The organisation or legal entity authorised to accept or reject e-Document.

### PartyType [attribute]

*PartyType is mandatory. A single instance is required.*

Identifies the business role associated with the particular party

Refer to PartyType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### PartyIdentifier

*PartyIdentifier is mandatory. One instance is required, multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

### NameAddress

*NameAddress is mandatory. A single instance is required.*

A group item containing name and address of an organisation or business entity.

### URL


*URL is optional. A single instance might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

### CommonContact

*CommonContact is mandatory. One instance is required, multiple instances might exist.*

Identifies a specific individual associated with the party.



## BusinessAcceptanceStatus [attribute]

Identifies the status of the BusinessAcceptance.

*This item is restricted to the following list.*

BusinessAcceptanceStatus	
type	businessAcceptanceStatus

### Accepted

Content of the e-Document is accepted. The receiver has got a Confirmation of Acceptance for an earlier sent e-Document

### Rejected

Content of the e-Document is rejected. The receiver of a BusinessAcceptance should have in place a resolution process. The resolution process is typically based on manual actions when the content is rejected.

## BusinessAcknowledgement

The BusinessAcknowledgement element is the root element for the BusinessAcknowledgement e-Document.

An e-Document receiver uses the BusinessAcknowledgement to notify the sender that a document has been successfully

presented to the receiver's ERP system. The BusinessAcknowledgement can be used to acknowledge any papiNet e-Document. Although the BusinessAcknowledgement is optional between two trading partners, its use is strongly recommended since it provides positive verification of the beginning of the transaction by the receiver.

### Status [attribute]

*Status is mandatory. A single instance is required.*


Defines whether or not the electronic transaction successfully processed in the receiver ERP system.

Refer to Status definition for any enumerations.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.



Refer to Language definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **BusinessAcknowledgementNumber**

*BusinessAcknowledgementNumber is mandatory. A single instance is required.*

The unique identifier for the BusinessAcknowledgement.

### **BusinessAcknowledgementDate**

*BusinessAcknowledgementDate is mandatory. A single instance is required.*

The Date and Time when the BusinessAcknowledgement was issued.

### **Document**

*Document is mandatory. A single instance is required.*

A group item containing information applicable to the original document.

### **TransactionHistoryNumber**

*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

### **Error**

*Error is optional. Multiple instances might exist.*

A group item that details the errors that are delaying processing on an original document.

### **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

### **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.


---

## BusinessAcknowledgementDate

The Date and Time when the BusinessAcknowledgement was issued.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.


hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

---

## BusinessAcknowledgementNumber

The unique identifier for the BusinessAcknowledgement.



## BuyerParty

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

### LogisticsRole [attribute]

*LogisticsRole is optional. A single instance might exist.*

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PartyIdentifier

*PartyIdentifier is optional. Multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

#### NameAddress

*NameAddress is mandatory. A single instance is required.*

A group item containing name and address of an organisation or business entity.

#### URL


*URL is optional. A single instance might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

#### CommonContact

*CommonContact is optional. Multiple instances might exist.*

Identifies a specific individual associated with the party.




## ByInvoice

Selection criteria for invoice information.

### (choice)

*[choice] is optional because of choice construct.*



#### InvoiceNumber

*InvoiceNumber is optional because of choice construct.*

The identification number of the Invoice, generated by the seller.

#### InvoiceNumberRange

*InvoiceNumberRange is optional because of choice construct.*

A range of invoices to be considered or reported on.

## ByJob

Information about the job being communicated.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### JobID

*JobID is optional. A single instance might exist.*

An element used to communicate the unique identifier of the Job

#### JobDescription

*JobDescription is optional. A single instance might exist.*

A textual description of the job.

#### IssueOrEventID

*IssueOrEventID is optional. A single instance might exist.*

Used to communicate the identifier for a job.

#### EndUserParty

*EndUserParty is optional. A single instance might exist.*

The party using, consuming, or converting the product. For example, a printer using paper reels for a print job for a publisher. The final ShipTo destination for a product is normally to the end user's facilities.

#### Quantity

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

#### InformationalQuantity

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.


#### JobDateTimeRange

*JobDateTimeRange is optional. A single instance might exist.*

The specification of the date range for the job.

#### PurchaseOrderDetail

*PurchaseOrderDetail is optional. Multiple instances might exist.*



Multiple PurchaseOrderDetail instances are allowed.

## ByLoad

By Load

### ByLoadType [attribute]

*ByLoadType is mandatory. A single instance is required.*

By Load Type

Refer to ByLoadType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### LoadNumber

*LoadNumber is mandatory. A single instance is required.*

An element used to communicate the unique identifier of the LoadNumber.

#### Quantity

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

#### InformationalQuantity


*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

#### ShipmentLoadDetails

*ShipmentLoadDetails is optional. Multiple instances might exist.*

A group element that containing information that relates to the shipment load details for the line item. Carrier and transport information may be detailed.




## ByLoadType [attribute]

By Load Type

*This item is restricted to the following list.*

**Forecast**



The load is projected.

## Shipment


The load is actually shipped.

## ByPeriod

This element is mutually exclusive of ByQualifiedPurchaseOrderInformation and ByQualifiedDeliveryMessage.

### (sequence)

The sequence of items below is mandatory. A single instance is required.



### TimePeriod

TimePeriod is mandatory. A single instance is required.

The TimePeriod element is used to communicate a duration period of time as indicated in PeriodType.

### Product

Product is optional. Multiple instances might exist.


Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## ByProduct

Identification takes place by product.

### (sequence)

The sequence of items below is mandatory. A single instance is required.



### (choice)

[choice] is optional because of choice construct.

### Product

Product is optional because of choice construct.

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## ShippingInstructionsPurchaseOrderLineItem

*ShippingInstructionsPurchaseOrderLineItem is optional because of choice construct.*

PurchaseOrder line item information for purchase order being referenced in ShippingInstructions.

### OtherDate

*OtherDate is optional. More than one instance can occur.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## ShippingInstructionsLineItemByProduct

*ShippingInstructionsLineItemByProduct is mandatory. One instance is required, multiple instances might exist.*


ShippingInstructionsLineItemByProduct

## ByPurchaseOrder

Selection criteria for communicating purchase order information.

### (sequence)

The



*sequence of items below is mandatory. A single instance is required.*

### PurchaseOrderInformation

*PurchaseOrderInformation is mandatory. A single instance is required.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

### (choice)

*[choice] is optional because of choice construct.*

### PurchaseOrderLineItemNumber

*PurchaseOrderLineItemNumber is optional because of choice construct.*

The sequential number that uniquely identifies the PurchaseOrder line item.


### Product

*Product is optional because of choice construct.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## ByQualifiedDeliveryMessage

ByQualifiedDeliveryMessage is a conditional element. This element is mutually exclusive of



ByQualifiedPurchaseOrderInformation and ByPeriod. The use of the term “qualified” is to indicate that DeliveryMessageNumber is qualified by the use of DeliveryMessageLineItemNumber.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DeliveryMessageNumber

*DeliveryMessageNumber is mandatory. A single instance is required.*

A unique delivery identifier assigned to each DeliveryMessage as agreed between the trading partners.


#### DeliveryMessageLineItemNumber

*DeliveryMessageLineItemNumber is optional. Multiple instances might exist.*

The sequential number that uniquely identifies the delivery line item.

## ByQualifiedPurchaseOrderInformation

ByQualifiedPurchaseOrderInformation is a conditional element. This element is mutually



exclusive of ByPeriod and ByShipment. The use of the term “qualified” is to indicate that PurchaseOrderInformation is qualified by the use of PurchaseOrderLineItemNumber.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PurchaseOrderInformation

*PurchaseOrderInformation is mandatory. A single instance is required.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

#### PurchaseOrderLineItemNumber

*PurchaseOrderLineItemNumber is optional. Multiple instances might exist.*


The sequential number that uniquely identifies the PurchaseOrder line item.

## ByShipTo

ByShipTo

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### ShipToCharacteristics

*ShipToCharacteristics is mandatory. A single instance is required.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

### DeliveryDateWindow

*DeliveryDateWindow is optional. Multiple instances might exist.*

A group item defining the date/time interval for delivery to take place. An element which may contain the estimated date for which delivery is expected. This date is not absolute.

### TransportInformation

*TransportInformation is optional. A single instance might exist.*

A grouping element for transport information.

### ShippingInstructionsLineItemByShipTo

*ShippingInstructionsLineItemByShipTo is mandatory. One instance is required, multiple instances might exist.*

ShippingInstructions Line Item By Ship To

## BySupplierOrder

Selection criteria for communicating Supplier Order information.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### SupplierOrderNumber

SupplierOrderNumber is mandatory. A single instance is required.



required.

The number of the supplier order.

#### SupplierOrderLineItemNumber

SupplierOrderLineItemNumber is mandatory. A single instance is required.

The number of the line item on the supplier order.

### (sequence)

The sequence of items below is optional. A single instance might exist.

#### PurchaseOrderNumber

PurchaseOrderNumber is mandatory. A single instance is required.

The unique order identifier as designated by the customer.

#### PurchaseOrderLineItemNumber

PurchaseOrderLineItemNumber is optional. A single instance might exist.

The sequential number that uniquely identifies the PurchaseOrder line item.

#### Quantity

Quantity is mandatory. A single instance is required.

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.


#### InformationalQuantity

InformationalQuantity is optional. Multiple instances might exist.

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

#### ShipmentLoadDetails

ShipmentLoadDetails is optional. Multiple instances might exist.




A group element that containing information that relates to the shipment load details for the line item. Carrier and transport information may be detailed.

## BySupplierOrderNumber

Selection criteria for communicating Supplier Order information

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### SupplierOrderNumber

*SupplierOrderNumber is mandatory. A single instance is required.*

The number of the supplier order.

### Product

*Product is optional. Multiple instances might exist.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## Calendar

The Calendar element is the root element for the Calendar e-Document.

The Calendar e-Document is intended to communicate opening times or other details for a location or locations.

### CalendarType [attribute]

*CalendarType is mandatory. A single instance is required.*

Identifies the intention of the entire Calendar e-Document.

Refer to CalendarType definition for any enumerations.

### CalendarStatus [attribute]


*CalendarStatus is optional. A single instance might exist.*

Identifies the status of the entire Calendar e-Document.

Refer to CalendarStatus definition for any enumerations.

### Language [attribute]

*Language is optional. A single instance might exist.*



XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### **CalendarHeader**

*CalendarHeader is mandatory. A single instance is required.*

A group item containing generic information applicable to the entire Calendar.

### **CalendarSequence**

*CalendarSequence is mandatory. One instance is required, multiple instances might exist.*

A group item containing information that relates to a line on the Calendar.

---

## CalendarEntry

Detailed description of the times and contingencies for the given LocationParty.

### **CalendarEntryPeriod [attribute]**

*CalendarEntryPeriod is mandatory. A single instance is required.*

Describes the period to which the given times and contingencies apply. This can be either a weekday or a date range. If it is a date range, the DateTimeRange element is used to specify the range.

Refer to CalendarEntryPeriod definition for any enumerations.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### **TimeSlotInformation**

*TimeSlotInformation is mandatory. One instance is required, multiple instances might exist.*

Description of the beginning and end of a time slot and the contingencies it contains.

### **DateTimeRange**


*DateTimeRange is mandatory. One instance is required, multiple instances might exist.*

The delivery date and/or time range.

### **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*


A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific



elements.

## CalendarEntryPeriod [attribute]

Describes the period to which the given times and contingencies apply. This can be either a weekday or a date range. If it is a date range, the DateTimeRange element is used to specify the range.



*This item is restricted to the following list.*

- Monday**
- Tuesday**
- Wednesday**
- Thursday**
- Friday**
- Saturday**
- Sunday**
- DateTimeRange**

## CalendarHeader

A group item containing generic information applicable to the entire Calendar.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### CalendarNumber

*CalendarNumber is mandatory. A single instance is required.*

The sequential number that uniquely identifies the Calendar e-Document.

### CalendarIssueDate

*CalendarIssueDate is mandatory. A single instance is required.*

The date and optionally time when the Calendar e-Document was created.


### RequestNumber

*RequestNumber is optional. A single instance might exist.*

A unique tracking number specifically identifying the InfoRequest e-Document to the originator. The tracking number is returned with the "information", the answer, to help match the answer to the request.

### SenderParty

*SenderParty is mandatory. A single instance is required.*



The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## ReceiverParty

*ReceiverParty is mandatory. One instance is required, multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## OtherParty

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.


---

## CalendarIssueDate

The date and optionally time when the Calendar e-Document was created.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is mandatory. A single instance is required.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## CalendarNumber

The sequential number that uniquely identifies the Calendar e-Document.

<b>CalendarNumber</b>
type s30

## CalendarRequestDetail

The selection criteria for communicating what Calendar information is desired.

### CalendarType [attribute]

*CalendarType is mandatory. A single instance is required.*

Identifies the intention of the entire Calendar e-Document.

Refer to CalendarType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### SupplierParty

*SupplierParty is optional. Multiple instances might exist.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

### CalendarNumber

*CalendarNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the Calendar e-Document.

### CalendarIssueDate


*CalendarIssueDate is optional. A single instance might exist.*

The date and optionally time when the Calendar e-Document was created.

### DateTimeRange

*DateTimeRange is optional. A single instance might exist.*

The delivery date and/or time range.



## CalendarSequence

A group item containing information that relates to a line on the Calendar.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### CalendarSequenceNumber

*CalendarSequenceNumber is mandatory. A single instance is required.*

The sequential number that uniquely identifies the Calendar sequence within the Calendar e-Document.



#### LocationParty

*LocationParty is mandatory. A single instance is required.*

The organization or business entity where the business event took place or will take place.

### (choice)

*[choice] is optional because of choice construct.*

#### SupplyPoint

*SupplyPoint is optional because of choice construct.*

Grouping element that contains items describing a supply point. A SupplyPoint belongs to a LocationParty, e.g. in a DeliveryOrigin or DeliveryDestination, and describes where goods are stored and can be loaded or unloaded. A SupplyPoint can for example be a loading or unloading gate at a warehouse or a road side landing at a logging area in the forest.

#### LocationCode

*LocationCode is optional because of choice construct.*

A code used to identify a specific physical location within a site identified by a party, e.g. a loading station in a warehouse or an unloading station at a printer site.

LocationCode will be deprecated in a future version. Use SupplyPoint instead of LocationCode.

#### TransportInformation

*TransportInformation is optional. A single instance might exist.*

A grouping element for transport information.

#### CalendarEntry


*CalendarEntry is mandatory. One instance is required, multiple instances might exist.*

Detailed description of the times and contingencies for the given LocationParty.

#### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific



elements.

---

## CalendarSequenceNumber

The sequential number that uniquely identifies the Calendar sequence within the Calendar e-Document.

<b>CalendarSequenceNumber</b>	
type	s30

---

## CalendarStatus [attribute]

Identifies the status of the entire Calendar e-Document.

*This item is restricted to the following list.*

<i>attribute</i>	
<b>CalendarStatus</b>	
type	calendarStatusType

### **Amended**

The supplied information is changed.

### **Cancelled**

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### **Original**

The supplied information is the first version of that information.

---

## CalendarType [attribute]

Identifies the intention of the entire Calendar e-Document.

*This item is restricted to the following list.*

<i>attribute</i>	
<b>CalendarType</b>	
type	calendarType

### **LoadingSchedule**

The schedule for transport vehicle loading.

### **OfficeSchedule**

The schedule for office personnel.

### **SupportSchedule**

The support schedule for transport operations.

### **UnloadingSchedule**


The schedule for transport vehicle unloading.

## Calibration

A grouping element that contains information about calibration of the measuring equipment.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



#### CalibrationNumber

*CalibrationNumber is mandatory. A single instance is required.*

A unique identifier for the calibration event.

#### CalibrationDescription

*CalibrationDescription is optional. Multiple instances might exist.*

A text element describing the calibration event.

#### CalibrationDate

*CalibrationDate is optional. A single instance is required.*


The date when calibration of the measuring equipment was done.

## CalibrationDate

The date when calibration of the measuring equipment was done.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



#### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

#### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

- hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.
- hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.
- hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## CalibrationDescription

A text element describing the calibration event.

<b>CalibrationDescription</b>	
type	s255

## CalibrationNumber

A unique identifier for the calibration event.

<b>CalibrationNumber</b>	
type	s30

## Caliper

The thickness of a sheet of paper under standard test conditions.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test


Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### DetailValue

*DetailValue is mandatory. A single instance is required.*



A numeric value expressed in the unit of measure (UOM).

## DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

## DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

## StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper


*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

## CallOff

The CallOff element is the root element for the CallOff e-Document.

A CallOff is a delivery schedule for product(s). Products to be delivered can be specified by product specifications or by purchase orders. Any party as agreed in a Trading Partner Agreement can send a CallOff. Each line item in a CallOff refers either to a product included in a PurchaseOrder or to the product specifications contained in the line item. The CallOff specifies delivery schedule(s) and quantities for product(s) to be delivered. The schedule may define a specific date and/or time for delivery or include a time range. All products covered by a CallOff must be delivered to a single location.



## **CallOffType [attribute]**

*CallOffType is mandatory. A single instance is required.*

CallOffType defines the type of CallOff.

Refer to CallOffType definition for any enumerations.

## **CallOffStatusType [attribute]**

*CallOffStatusType is mandatory. A single instance is required.*

Identifies the status of the entire CallOff (in other words, at the root level).

Refer to CallOffStatusType definition for any enumerations.

## **Reissued [attribute]**

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

## **Language [attribute]**

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **CallOffHeader**

*CallOffHeader is mandatory. A single instance is required.*

A group item containing generic information applicable to the entire CallOff.

### **CallOffLineItem**

*CallOffLineItem is mandatory. One instance is required, multiple instances might exist.*

A group item containing information that relates to a line on the CallOff.

### **CallOffSummary**

*CallOffSummary is optional. A single instance might exist.*

Contains summary information that applies to the CallOff.


---

## **CallOffConfirmationIssuedDate**

The Date and Time on which the CallOff confirmation was issued.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### **Date**

*Date is mandatory. A single instance is required.*

# papiNet V2R31

---

A group element that contains the specification of Year, Month, and Day.

## Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

---

## CallOffConfirmationLineItemNumber

The sequential number that uniquely identifies the CallOff confirmation line item.

CallOffConfirmationLineItemNumber	
type	lineNumberType

---

## CallOffConfirmationNumber

The unique identifier given to the CallOff confirmation.

CallOffConfirmationNumber	
type	s30

## CallOffHeader

A group item containing generic information applicable to the entire CallOff.

### CallOffHeaderStatusType [attribute]

*CallOffHeaderStatusType is optional. A single instance might exist.*

CallOffHeaderStatusType defines the status of the CallOff header.

Refer to CallOffHeaderStatusType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### CallOffInformation

*CallOffInformation is mandatory. A single instance is required.*

A group item containing information unique to the CallOff which is generated and supplied by the buyer, seller, or any party involved.

#### BuyerParty

*BuyerParty is mandatory. A single instance is required.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

#### BillToParty

*BillToParty is optional. A single instance might exist.*

The address where the Invoice is to be sent.

#### SupplierParty


*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

#### CarrierParty

*CarrierParty is optional. A single instance might exist.*

The party performing the transport of the product from the pickup location to the



ship-to location; could be a hauler.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **ShipToCharacteristics**

*ShipToCharacteristics is mandatory. A single instance is required.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **TransportModeCharacteristics**

*TransportModeCharacteristics is optional. A single instance might exist.*

A group item defining the primary mode of transport.

## **TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

## **TransportUnitCharacteristics**

*TransportUnitCharacteristics is optional. A single instance might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

## **TransportLoadingCharacteristics**

*TransportLoadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be loaded.

## **TransportUnloadingCharacteristics**

*TransportUnloadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be unloaded.

## **TransportOtherInstructions**

*TransportOtherInstructions is optional. Multiple instances might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*


A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **CallOffHeaderStatusType [attribute]**

CallOffHeaderStatusType defines the status of the CallOff header.

*This item is restricted to the following list.*



### **Accepted**

The supplied information is accepted.

### **Amended**

The supplied information is changed.

### **Cancelled**

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### **NoAction**

The supplied information has not been amended and thereby requires no action.

### **Original**

The supplied information is the first version of that information.

### **Rejected**


The supplied information is rejected.

## CallOffInformation

A group item containing information unique to the CallOff which is generated and supplied by the buyer, seller, or any party involved.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### CallOffNumber

*CallOffNumber is mandatory. A single instance is required.*

The unique identifier given to a CallOff. The CallOff number of a previously sent CallOff can be referenced. For example, a seller can refer to a CallOff number in a DeliveryMessage.

### CallOffIssuedDate

*CallOffIssuedDate is mandatory. A single instance is required.*

The Date and Time when the CallOff was issued.

### CallOffConfirmationIssuedDate

*CallOffConfirmationIssuedDate is optional. A single instance might exist.*

The Date and Time on which the CallOff confirmation was issued.

### TransactionHistoryNumber

*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

### TransactionHistoryConfirmationNumber

*TransactionHistoryConfirmationNumber is optional. A single instance might exist.*

A sequential number that indicates the version of the confirmation document being sent.

### CallOffReference

*CallOffReference is optional. Multiple instances might exist.*

An element item detailing relevant references pertaining to the CallOff. CallOffReference uses the CallOffReferenceType attribute.

### CallOffConfirmationNumber

*CallOffConfirmationNumber is optional. A single instance might exist.*


The unique identifier given to the CallOff confirmation.

## CallOffIssuedDate

The Date and Time when the CallOoff was issued.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.


hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## CallOffLineItem

A group item containing information that relates to a line on the CallOff.



### CallOffLineItemStatusType [attribute]

*CallOffLineItemStatusType is mandatory. A single instance is required.*

CallOffLineItemStatusType defines the status of a CallOff line item.

Refer to CallOffLineItemStatusType definition for any enumerations.

### CallOffLineItemDocumentStatus [attribute]

*CallOffLineItemDocumentStatus is optional. A single instance might exist.*

Defines the actual document status for the CallOffLineItem.

Refer to CallOffLineItemDocumentStatus definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### CallOffLineItemNumber

*CallOffLineItemNumber is mandatory. A single instance is required.*

The sequential number that uniquely identifies the CallOff line item.

#### CallOffReference

*CallOffReference is optional. Multiple instances might exist.*

An element item detailing relevant references pertaining to the CallOff.  
CallOffReference uses the CallOffReferenceType attribute.

## **CallOffConfirmationLineItemNumber**

*CallOffConfirmationLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the CallOff confirmation line item.

### **(choice)**

*[choice] is optional because of choice construct.*

#### **CallOffProduct**

*CallOffProduct is optional because of choice construct.*

A group item identifying the product to be called off.

#### **CallOffPurchaseOrderLineItem**

*CallOffPurchaseOrderLineItem is optional because of choice construct.*

A group item referring to a PurchaseOrder line item.

## **DeliverySchedule**

*DeliverySchedule is mandatory. One instance is required, multiple instances might exist.*

A group item defining a series of DeliveryDateWindow(s) in which specified quantities must be delivered.

## **TransportModeCharacteristics**

*TransportModeCharacteristics is optional. A single instance might exist.*

A group item defining the primary mode of transport.

## **TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

## **TransportUnitCharacteristics**

*TransportUnitCharacteristics is optional. A single instance might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

## **TransportLoadingCharacteristics**

*TransportLoadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be loaded.

## **TransportUnloadingCharacteristics**

*TransportUnloadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be unloaded.

## **TransportOtherInstructions**

*TransportOtherInstructions is optional. Multiple instances might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

## **CallOffLineItemText**

*CallOffLineItemText is optional. A single instance might exist.*

A free text field to be used for special item instructions.

---

## CallOffLineItemDocumentStatus [attribute]

Defines the actual document status for the CallOffLineItem.

*This item is restricted to the following list.*

attribute
<b>CallOffLineItemDocumentStatus</b>
type documentStatusType.CallOff

### **Cancelled**

The supplied information of the document item is cancelled. Items that have been cancelled are not included in totals on the summary level of e-Documents.

### **Confirmed**

The supplied information of the document item is agreed. If a requested change or cancellation of an existing document item can not be accepted, then the earlier agreed information of the document item will be re-confirmed.

### **Pending**

The supplied information of the document item is being investigated.

### **Rejected**

The supplied information of the document item can not be accepted. The document item is new or not earlier confirmed.

### **Requested**

The supplied information of the document item is ordered.

---

## CallOffLineItemDocumentStatus [attribute]

Defines the actual document status for the CallOffLineItem.

*This item is restricted to the following list.*

attribute
<b>CallOffLineItemDocumentStatus</b>
type documentStatusType.CallOffWood

### **Cancelled**

The supplied information of the document item is cancelled. Items that have been cancelled are not included in totals on the summary level of e-Documents.

### **Confirmed**

The supplied information of the document item is agreed. If a requested change or cancellation of an existing document item can not be accepted, then the earlier agreed information of the document item will be re-confirmed.

### **Pending**

The supplied information of the document item is being investigated.

### **Rejected**

The supplied information of the document item can not be accepted. The document item is new or not earlier confirmed.

## Requested

The supplied information of the document item is ordered.

---

## CallOffLineItemNumber

The sequential number that uniquely identifies the CallOff line item.

CallOffLineItemNumber	
type	lineNumberType

---

## CallOffLineItemStatusType [attribute]

CallOffLineItemStatusType defines the status of a CallOff line item.

attribute	
CallOffLineItemStatusType	
type	callOffLineItemStatusType

*This item is restricted to the following list.*

### Accepted

The supplied information is accepted.

### Amended

The supplied information is changed.

### Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### NoAction

The supplied information has not been amended and thereby requires no action.

### Original

The supplied information is the first version of that information.

### Pending

The supplied information is not complete and will be updated later.

### Rejected

The supplied information is rejected.

---

## CallOffLineItemText

A free text field to be used for special item instructions.

CallOffLineItemText	
type	s72

---

## CallOffNumber


The unique identifier given to a CallOff. The CallOff number of a previously sent CallOff can be referenced. For example, a seller can refer to a CallOff number in a DeliveryMessage.

CallOffNumber	
type	s30

## CallOffPaper

A group item containing elements that describe the paper item.

**(sequence)**



*The sequence of items below is mandatory. A single instance is required.*

### PaperCharacteristics

*PaperCharacteristics is mandatory. A single instance is required.*

The identifying characteristics of paper most important to the ordering of the item. These are the characteristics that, when associated with a given grade, allow the manufacturer to produce but not convert or package, the paper.

### CallOffProductConversionType

*CallOffProductConversionType is mandatory. A single instance is required.*

A call off reel or a call off sheet.

## CallOffProduct


A group item identifying the product to be called off.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**(sequence)**

*The sequence of items below is mandatory. One instance is required, multiple instances might exist.*



### ProductIdentifier

*ProductIdentifier is mandatory. A single instance is required.*

Used to communicate the code of the article, in a variety of formats designated by the type.


### ProductDescription

*ProductDescription is optional. Multiple instances might exist.*

An element used to communicate a human readable description of the product in the language specified by the Language attribute.

### MillCharacteristics

*MillCharacteristics is optional. A single instance*



*might exist.*

A group item defining the mill party and machine identifier where a product is or was produced.

## **Classification**

*Classification is optional. Multiple instances might exist.*

A group item that details the product classification according to a particular organization's scheme. An item across multiple classifications would still be recognized as the same item. Examples of some product classifications are: Containerboard, Pulp-Dissolving, or Newsprint.

## **(choice)**

*[choice] is optional because of choice construct.*

### **BookManufacturing**

*BookManufacturing is optional because of choice construct.*

BookManufacturing is a group element that contains the elements that describe the book manufacturing process.

### **ForestWood**

*ForestWood is optional because of choice construct.*

A grouping element with information about characteristics for Forest Wood products.

## **(choice)**

*[choice] is optional because of choice construct.*

### **CallOffPaper**

*CallOffPaper is optional because of choice construct.*

A group item containing elements that describe the paper item.

### **Paper**

*Paper is optional because of choice construct.*

A group item defining the characteristics of the paper product.

### **LabelStock**

*LabelStock is optional because of choice construct.*

LabelStock contains the attributes and characteristics that define the label stock product.

### **Pulp**

*Pulp is optional because of choice construct.*

A group item defining the characteristics of pulp that are not dependent on a particular conversion process.

### **RecoveredPaper**

*RecoveredPaper is optional because of choice construct.*

A group item defining the characteristics of recycled fibre that are not dependent on a particular conversion process.

### **VirginFibre**

*VirginFibre is optional because of choice construct.*

Virgin Fibre

### **WoodProducts**

*WoodProducts is optional because of choice construct.*


A grouping element for all wood products.

## CallOffProductConversionType

A call off reel or a call off sheet.

**(choice)**

*[choice] is optional because of choice construct.*



### CallOffReel

*CallOffReel is optional because of choice construct.*

A group item containing reel information for the CallOff.

### CallOffSheet

*CallOffSheet is optional because of choice construct.*


A group item containing sheet information for the CallOff.

## CallOffPurchaseOrderLineItem

A group item referring to a PurchaseOrder line item.

**(sequence)**

*The*



*sequence of items below is mandatory. A single instance is required.*

### PurchaseOrderLineItemNumber

*PurchaseOrderLineItemNumber is mandatory. A single instance is required.*

The sequential number that uniquely identifies the PurchaseOrder line item.

### PurchaseOrderInformation

*PurchaseOrderInformation is mandatory. A single instance is required.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

### PackageIdentifier

*PackageIdentifier is optional. A single instance might exist.*


The identifier of the productpackage (such as reel ID or pallet ID) that is used along with the PurchaseOrderLineItemNumber to call off the product.

## CallOffReel

A group item containing reel information for the CallOff.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



#### ReelWidth

*ReelWidth is mandatory. A single instance is required.*

The width of reel from edge to edge excluding packaging.

#### ReelDiameter

*ReelDiameter is mandatory. A single instance is required.*


The diameter measurement of reel excluding packaging.

## CallOffReference

An element item detailing relevant references pertaining to the CallOff. CallOffReference uses the CallOffReferenceType attribute.

### CallOffReferenceType [attribute]

*CallOffReferenceType is mandatory. A single instance is required.*



Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to CallOffReferenceType definition for any enumerations.

### AssignedBy [attribute]


*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

## CallOffReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead



the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.


---

## CallOffSheet

A group item containing sheet information for the CallOff.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### SheetSize

*SheetSize is mandatory. A single instance is required.*

A group item that contains elements relative to the sheet size.

### PackagingDescription

*PackagingDescription is optional. A single instance might exist.*

A text field element describing the packaging of a product.

### GrainDirection

*GrainDirection is optional. A single instance might exist.*

Defines the primary orientation/alignment (Long or Short) of the cellulose fibres in a sheet or web of paper, which results from the flow of fibres in a water suspension during the papermaking process.


Refer to GrainDirection definition for any enumerations.

---

## CallOffStatusType [attribute]

Identifies the status of the entire CallOff (in other words, at the root level).

*This item is restricted to the following list.*



### Accepted

The supplied information is accepted.

### Amended

The supplied information is changed.

### Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### Original

The supplied information is the first version of that information.

### Rejected


The supplied information is rejected.

## CallOffSummary

Contains summary information that applies to the CallOff.

### (sequence)

The sequence of items below is mandatory. A single instance is required.



### TotalNumberOfLineItems

TotalNumberOfLineItems is optional. A single instance might exist.

The total number of individual line items in the document, regardless of the status or type.

### (sequence)

The sequence of items below is mandatory. One instance is required, multiple instances might exist.

### TotalQuantity

TotalQuantity is mandatory. A single instance is required.

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

### TotalInformationalQuantity

TotalInformationalQuantity is optional. Multiple instances might exist.

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

### TermsAndDisclaimers


TermsAndDisclaimers is optional. Multiple instances might exist.

An element that contains legal information with an indication of what the Language is.

## CallOffType [attribute]

CallOffType defines the type of CallOff.

This item is restricted to the following list.



### CallOff

Defines a CallOff sent by the buyer to the seller.


### CallOffConfirmation

Defines a CallOff confirmation sent in response to a CallOff.

## CallOffWood

The CallOffWood element is the root element for the CallOffWood e-Document.

A CallOffWood is a business transaction instructing the consignor (normally the seller) to despatch goods belonging to one or several orders. A CallOffWood contains information about how the goods are to be loaded, quantities, marking instructions etc. It may also contain information about where borders are to be crossed and information concerning transport, such as name of ship and shipping agent. In cases where the CallOffWood is not used, delivery information is included in the order.



### CallOffType [attribute]

*CallOffType is mandatory. A single instance is required.*

CallOffType defines the type of CallOff.

Refer to CallOffType definition for any enumerations.

### CallOffStatusType [attribute]

*CallOffStatusType is mandatory. A single instance is required.*

Identifies the status of the entire CallOff (in other words, at the root level).

Refer to CallOffStatusType definition for any enumerations.

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### CallOffWoodHeader

*CallOffWoodHeader is mandatory. A single instance is required.*

Information that applies to the entire Wood market segment CallOff e-Document.

## CallOffWoodProductGroup

*CallOffWoodProductGroup is mandatory. One instance is required, multiple instances might exist.*

CallOffWoodProductGroup provides for groupings of line items in the CallOff e-Document.

This construct was introduced in version v2r30. It is recognized that the introduction of this construct is not in conformance with the papiNet policy of backward compatibility within releases of the same version.

## CallOffWoodSummary

*CallOffWoodSummary is optional. A single instance might exist.*

Summary information that applies to the Wood market segment CallOff e-Document.

## CallOffWoodHeader

Information that applies to the entire Wood market segment CallOff e-Document.

### CallOffHeaderStatusType [attribute]

*CallOffHeaderStatusType is optional. A single instance might exist.*

CallOffHeaderStatusType defines the status of the CallOff header.

Refer to CallOffHeaderStatusType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### CallOffInformation

*CallOffInformation is mandatory. A single instance is required.*

A group item containing information unique to the CallOff which is generated and supplied by the buyer, seller, or any party involved.


### BuyerParty

*BuyerParty is mandatory. A single instance is required.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

### BillToParty

*BillToParty is optional. A single instance might exist.*



The address where the invoice is to be sent.

## **SupplierParty**

*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **CarrierParty**

*CarrierParty is optional. A single instance might exist.*

The party performing the transport of the product from the pickup location to the ship-to location; could be a hauler.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **ShipToInformation**

*ShipToInformation is mandatory. A single instance is required.*

Group element containing information about the ship to and delivery of a product.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.


## **DocumentInformation**

*DocumentInformation is optional. Multiple instances might exist.*

A group element containing a specification of required documents in the business process. Additional free text to be printed on documents can also be specified.

## CallOffWoodLineItem

CallOffWoodLineItem has a required attribute that indicates the status of the line item.



### CallOffLineItemStatusType [attribute]

*CallOffLineItemStatusType is mandatory. A single instance is required.*

CallOffLineItemStatusType defines the status of a CallOff line item.

Refer to CallOffLineItemStatusType definition for any enumerations.

### CallOffLineItemDocumentStatus [attribute]

*CallOffLineItemDocumentStatus is optional. A single instance might exist.*

Defines the actual document status for the CallOffLineItem.

Refer to CallOffLineItemDocumentStatus definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### CallOffLineItemNumber

*CallOffLineItemNumber is mandatory. A single instance is required.*

The sequential number that uniquely identifies the CallOff line item.

## **CallOffReference**

*CallOffReference is optional. Multiple instances might exist.*

An element item detailing relevant references pertaining to the CallOff. CallOffReference uses the CallOffReferenceType attribute.

## **CallOffConfirmationLineItemNumber**

*CallOffConfirmationLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the CallOff confirmation line item.

## **(choice)**

*[choice] is optional because of choice construct.*

### **CallOffProduct**

*CallOffProduct is optional because of choice construct.*

A group item identifying the product to be called off.

### **CallOffPurchaseOrderLineItem**

*CallOffPurchaseOrderLineItem is optional because of choice construct.*

A group item referring to a PurchaseOrder line item.

## **MillProductionInformation**

*MillProductionInformation is optional. Multiple instances might exist.*

A grouping element that contains information about production at the mill.

## **DeliveryDateWindow**

*DeliveryDateWindow is optional. Multiple instances might exist.*

A group item defining the date/time interval for delivery to take place. An element which may contain the estimated date for which delivery is expected. This date is not absolute.

## **QuantityOrderedInformation**

*QuantityOrderedInformation is optional. A single instance might exist.*

Used to identify quantity. The construct provides via InformationalQuantity the ability to provide the Quantity in another UOM. Length is also provided to further specify the quantity.

## **TransportLoadingCharacteristics**

*TransportLoadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be loaded.

## **TransportUnloadingCharacteristics**

*TransportUnloadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be unloaded.

## **TransportOtherInstructions**

*TransportOtherInstructions is optional. Multiple instances might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

## **PackageInformation**

# papiNet V2R31

*PackageInformation is optional. Multiple instances might exist.*

The purpose of the PackageInformation structure is to clearly identify physical handling items that constitute the delivery.

PackageInformation is the highest level of product packaging it describes the shipping or warehousing unit.

If you are communicating a package, usually for logistics or transport purposes, you should include the PackageType, Identifier, ItemCount, and Quantity. (Note: you still have the ability to describe the item with one of the "named" items.)

If you are communicating one of the named Items there is no need to include PackageType, Identifier, ItemCount, and Quantity.

Since either of these two approaches can be used the entire contents of this element are optional even though the parent may be required. It is expected that you will fill in the appropriate details.

## QuantityDeviation

*QuantityDeviation is optional. A single instance might exist.*

To be deprecated in a future version. Use the Quantity element with a QuantityContext of "Deviation".

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---


## CallOffWoodProductGroup

CallOffWoodProductGroup provides for groupings of line items in the CallOff e-Document.

This construct was introduced in version v2r30.

It is recognized that the introduction

of this construct is not in conformance with the papiNet policy of backward compatibility within releases of the same version.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ProductGroupID

*ProductGroupID is optional. A single instance might exist.*

Possibility to group packages or Shipments. Example: Creating temporary group ID's for logistic reasons or lot number.

#### CallOffWoodLineItem

*CallOffWoodLineItem is mandatory. One instance is required, multiple instances might exist.*

CallOffWoodLineItem has a required attribute that indicates the status of the line item.

## ProductGroupSummary

*ProductGroupSummary is optional. A single instance might exist.*

Group of elements to provide summary information on product level.


---

## CallOffWoodSummary

Summary information that applies to the Wood market segment CallOff e-Document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### TotalNumberOfLineItems

*TotalNumberOfLineItems is optional. A single instance might exist.*

The total number of individual line items in the document, regardless of the status or type.

### (sequence)

*The sequence of items below is optional. Multiple instances might exist.*

### TotalQuantity

*TotalQuantity is mandatory. A single instance is required.*

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

### TotalInformationalQuantity

*TotalInformationalQuantity is optional. Multiple instances might exist.*

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

### QuantityDeviation

*QuantityDeviation is optional. A single instance might exist.*

To be deprecated in a future version. Use the Quantity element with a QuantityContext of "Deviation".

### TermsAndDisclaimers

*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.

## CarrierParty

The party performing the transport of the product from the pickup location to the ship-to location; could be a hauler.

### LogisticsRole [attribute]

*LogisticsRole is optional. A single instance might exist.*

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PartyIdentifier

*PartyIdentifier is optional. Multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

#### NameAddress

*NameAddress is mandatory. A single instance is required.*

A group item containing name and address of an organisation or business entity.

#### URL


*URL is optional. A single instance might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

#### CommonContact

*CommonContact is optional. Multiple instances might exist.*

Identifies a specific individual associated with the party.



## Case

### Case information

#### **BindingBackingType [attribute]**

*BindingBackingType is optional. A single instance might exist.*

Binding backing type

Refer to BindingBackingType definition for any enumerations.

#### **ClothCrossCut [attribute]**

*ClothCrossCut is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to ClothCrossCut definition for any enumerations.

#### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

#### **CaseLining**

*CaseLining is optional. A single instance might exist.*

Case lining

#### **CaseSupers**

*CaseSupers is optional. A single instance might exist.*

Case supers

#### **Headband**

*Headband is optional. Multiple instances might exist.*

Headband.

#### **CaseMaking**

*CaseMaking is optional. A single instance might exist.*

Case making

#### **DecorationSpecs**


*DecorationSpecs is optional. Multiple instances might exist.*

Decoration specifications

#### **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## CaseBoardMaterials

Case board materials

### CaseLocationType [attribute]

*CaseLocationType is optional. A single instance might exist.*

Case location type

Refer to CaseLocationType definition for any enumerations.

### CaseBoardType [attribute]

*CaseBoardType is optional. A single instance might exist.*

The type of case board material.

Refer to CaseBoardType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Caliper


*Caliper is optional. A single instance might exist.*

The thickness of a sheet of paper under standard test conditions.

#### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## CaseBoardType [attribute]

The type of case board material.

*This item is restricted to the following list.*

**Binders**

**Chipboard**


**Eskaboard**

**Fluted**

**Padded**

**PastedOak**

**Other**



---

## CaseFlushFoot [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

**Yes**

**No**

attribute	
<b>CaseFlushFoot</b>	
type	yesNo


---

## CaseLining

Case lining

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



**Quantity**

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

**CaseLiningDescription**

*CaseLiningDescription is optional. A single instance might exist.*

Case lining description

---

## CaseLiningDescription

Case lining description

<b>CaseLiningDescription</b>	
type	s72

---

## CaseLocationType [attribute]

Case location type

*This item is restricted to the following list.*

**Front**

**Back**

**Spine**

**FrontAndBack**

**FrontAndSpine**

**BackAndSpine**

attribute	
<b>CaseLocationType</b>	
type	caseLocationType

FrontAndBackAndSpine

**CaseMaking**

Case making

**CaseType [attribute]**

*CaseType is optional. A single instance might exist.*

Case type

Refer to CaseType definition for any enumerations.

**CaseFlushFoot [attribute]**

*CaseFlushFoot is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to CaseFlushFoot definition for any enumerations.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**CaseShow**

*CaseShow is optional. A single instance might exist.*

Case show

**CaseOversize**

*CaseOversize is optional. A single instance might exist.*

Case oversize

**CaseBoardMaterials**


*CaseBoardMaterials is optional. Multiple instances might exist.*

Case board materials

**CaseMaterial**

*CaseMaterial is optional. Multiple instances might exist.*

Case material



**CaseMaterial**


Case material

**CaseLocationType [attribute]**

*CaseLocationType is optional. A single instance might exist.*

Case location type

Refer to CaseLocationType



definition for any enumerations.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### **BindingMaterialCharacteristics**

*BindingMaterialCharacteristics is mandatory. A single instance is required.*

Binding Material Characteristics

### **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.


---

## CaseOversize

Case oversize

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### **Length**

*Length is optional. A single instance might exist.*

The length of the object.

### **Width**

*Width is optional. A single instance might exist.*

The width of the object.

---

## CaseShow


Case show

### **CaseShowType [attribute]**

*CaseShowType is optional. A single instance might exist.*

Case show type

Refer to CaseShowType definition for any enumerations.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### **Value**

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

---


## CaseShowType [attribute]

Case show type

*This item is restricted to the following list.*

**SpineOverSide**

**SideOverSpine**



---

## CaseSupers

Case supers

### SupersType [attribute]

*SupersType is optional. A single instance might exist.*

Supers Type

Refer to SupersType definition for any enumerations.

### (sequence)


*The sequence of items below is mandatory. A single instance is required.*

### Quantity

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.



---

## CaseType [attribute]


Case type

*This item is restricted to the following list.*

**OnePiece**

**TwoPiece**

**ThreePiece**



---

## CassetteCardReference

Cassette card reference



---

## CassetteLabelCharacteristics

Cassette label characteristics

### **CassetteLabelSide [attribute]**

*CassetteLabelSide is optional. A single instance might exist.*

Cassette label side

Refer to  
CassetteLabelSide definition for any  
enumerations.

### **CassetteLabelType [attribute]**

*CassetteLabelType is optional. A single instance might exist.*

Cassette label type

Refer to CassetteLabelType definition for any enumerations.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

#### **ColourSpecs**


*ColourSpecs is optional. A single instance might exist.*

Colour specs

#### **PressPrep**

*PressPrep is optional. Multiple instances might exist.*

Press preparation information



---

## CassetteLabelSide [attribute]

Cassette label side

*This item is restricted to the following list.*

**LabelOneSide**

**LabelTwoSide**

**SameLabelBothSide**

**Face**

**Spine**

**FaceAndSpine**

**None**




---

## CassetteLabelType [attribute]

Cassette label type

*This item is restricted to the following list.*

**Braille**



DirectImprint

PaperLabel

None

Other

## CD

CD

### CDFormatType [attribute]

*CDFormatType is optional. A single instance might exist.*

CD format type

Refer to CDFormatType definition for any enumerations.

### CDManufacturingProcess [attribute]

*CDManufacturingProcess is optional. A single instance might exist.*

CD manufacturing process.

Any valid string.

### CDRType [attribute]

*CDRType is optional. A single instance might exist.*

Describes the finish to be applied to the CD.

Refer to CDRType definition for any enumerations.

### DiscPrinting [attribute]

*DiscPrinting is optional. A single instance might exist.*

Disc printing

Refer to DiscPrinting definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### SequenceNumber

*SequenceNumber is optional. A single instance might exist.*

#### NumberOfColours


*NumberOfColours is optional. A single instance might exist.*

The number of colours

#### ColourSpecs

*ColourSpecs is optional. A single instance might exist.*

Colour specs



## MediaLength

*MediaLength is optional. A single instance might exist.*

Media length

## PressPrep

*PressPrep is optional. Multiple instances might exist.*

Press preparation information

## CDPackaging

*CDPackaging is optional. Multiple instances might exist.*

CD Packaging

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## CDFormatType [attribute]

CD format type

*This item is restricted to the following list.*

**Audio**

**CDPhoto**

**CDI**


**Enhanced**

**MixedMode**

**ROM**

**Video**

**Other**




---

## CDManufacturingProcess [attribute]

CD manufacturing process.

Any valid string.




## CDPackaging

CD Packaging

**(choice)**

*[choice] is optional because of choice construct.*



**BulkNumberOfUnits**

*BulkNumberOfUnits is optional because of choice construct.*

Bulk number of units

**JewelBox**

*JewelBox is optional because of choice construct.*

Jewel box.

**Sleeve**

*Sleeve is optional because of choice construct.*

Sleeve.

## CDRType [attribute]

Describes the finish to be applied to the CD.

*This item is restricted to the following list.*


**None**

**CD RCRDBL SLVR**

**PROMEDIA SLVR**


**RITEX/TDK SLVR**

**Other**



## CertificationBody [attribute]

Any valid text string that specifies the entity responsible for certification.




## ChainOfCustody

The chain of custody.

**CertificationBody [attribute]**

*CertificationBody is optional. A single instance might exist.*



Any valid text string that specifies the entity responsible for certification.

## ChangeDetailType [attribute]

Specifies how a package is changed.

*This item is restricted to the following list.*

### Add

The package is added.

### Change

The package is changed.

### Remove

The package is removed.

ChangeDetailType	
type	changeType
default	Change

## Charge

Charge is a group element that contains elements that describe a charge.

### ChargeType [attribute]

*ChargeType is mandatory. A single instance is required.*

The type of charge

Refer to ChargeType definition for any enumerations.

### ChargeContext [attribute]

*ChargeContext is optional. A single instance might exist.*

Describes the relationship of the charge to the associated to the Complaint, generally used for statistical purposes.

Refer to ChargeContext definition for any enumerations.

### Agency [attribute]

*Agency is optional. A single instance might exist.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.


Refer to Agency definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Quantity

*Quantity is optional. A single instance might exist.*



The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## InformationalQuantity

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## ChargePerUnit

*ChargePerUnit is optional. A single instance might exist.*

A group item containing a currency value and measurement to communicate a per unit charge.

## NetChargeAmount

*NetChargeAmount is optional. A single instance might exist.*

A field containing the sum of all instances of the Complaint charges.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*


A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## ChargeAmount

A field containing the total amount of every ChargeInformation including tax.

**(sequence)**



*The sequence of items below is mandatory. A single instance is required.*

## CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

---

## ChargeContext [attribute]

Describes the relationship of the charge to the associated to the Complaint, generally used for statistical purposes.

*This item is restricted to the following list.*

### Administrative



- Logistical
- Production
- Rework
- Storage
- Waste
- Other

## ChargeInformation

A group element that contains elements that describe a charge.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DocumentReferenceInformation

*DocumentReferenceInformation is optional. A single instance might exist.*

A group item containing reference information applicable to a document.



#### CostComponent

*CostComponent is mandatory. A single instance is required.*

A group item that contains information relevant to the freight cost codes.

#### PriceDetails

*PriceDetails is mandatory. A single instance is required.*

An element that groups together price information.

#### MonetaryAdjustment

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates they type of adjustment being communicated.

#### QuantityInformation


*QuantityInformation is mandatory. A single instance is required.*

A group item containing information about quantity and informational quantity of similar items.

#### TransportUnitCharacteristics

*TransportUnitCharacteristics is optional. Multiple instances might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.



## TransportVehicleCharacteristics

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

## ChargeAmount

*ChargeAmount is optional. A single instance might exist.*

A field containing the total amount of every ChargeInformation including tax.

## ChargeNetAmount

*ChargeNetAmount is optional. A single instance might exist.*

A field containing the total amount of every ChargeInformation excluding tax.

## InformationalAmount

*InformationalAmount is optional. Multiple instances might exist.*


A monetary amount used for information purposes only (not for calculation). For example, the invoice price adjustment subtotal is expressed in sterling pounds, and the buyer wants this information expressed in U.S. dollars.

CreditDebitNote and Invoice - The TaxAmount is displayed in the currency that is applicable throughout the e-Document. When a TaxAmount needs to be displayed in a different national currency, this field is used.

---

## ChargeNetAmount

A field containing the total amount of every ChargeInformation excluding tax.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

## CurrencyValue


*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

---

## ChargeOrAllowance

The description of the charge or allowance; such as freight, special handling, and stop-off handling.



## ChargeOrAllowanceType [attribute]

*ChargeOrAllowanceType is mandatory. A single instance is required.*

Defines what type of charge or allowance defines the invoice product.

Refer to ChargeOrAllowanceType definition for any enumerations.

---

## ChargeOrAllowanceType [attribute]

Defines what type of charge or allowance defines the invoice product.

attribute
<b>ChargeOrAllowanceType</b>
type adjustmentTypeFinancial

*This item is restricted to the following list.*

### **BillOfLadingCharge**

An extra charge for creating a Bill of Lading.

### **CancellationCharge**

A charge applied because a cancellation was late (after the last date of change) and all or part of the ordered product has already been made.

### **CashDiscount**

A reduction due to a discount applied.

### **CertificateCharge**

An extra charge for creating a certificate. Some countries requires Certificates in which different characteristics of the delivery, transport unit, route, product, and others must be proved.

There are certificates for gasen pallets, for the place of production, for the age of the ship/vessel, for not departing from one country's harbour when delivering to another.

### **ChargesForward**

A pending Invoice amount brought forward from a previous Invoice.

### **ClaimAdjustment**

An adjustment related to a filed complaint.

### **Commission**

Commission costs paid to the trading agency or trader.

### **CompetitiveAllowance**

An allowance provided for competitive reasons.

### **CongestionCharge**

An extra fee from ports for waiting time of ships in ports, railcars on a siding, trucks at a dock. (Synonym: Demurrage.)

### **ConsigneeUnloadCharge**

An unloading charge that is the responsibility of the consignee.

### **ContractAllowance**

An allowance for a volume discount, usually because the agreed amount has been exceeded.

### **CurrencyAdjustmentCharge**

An extra fee to adjust for currency variations.

### **DecimalRounding**

Adjustments for rounding of total amounts to fit the business agreement or national monetary legislation.

For example, Finland does not use smaller than 5 cent coins. All cash payments are rounded to a 5 cent divisible amount according to national legislation. Alternatively, certain market segments prefer to remove all decimals.

**DefectiveAllowance**

An allowance provided for defective material.

**DeliveryCharge**

The charge for delivering the product.

**DeliveryNonConformanceAllowance**

An allowance due to non-conformance with the purchase agreement regarding a delivery.

**DeliveryTimeBonus**

A bonus given for deliveries of products within a certain time period.

**EarlyShipAllowance**

An allowance due to a delivery that took place earlier than planned. The seller may be charged a penalty. If this is found before issuing the Invoice, it can be handled through this allowance. If found later, it will be handled through a credit note.

**EnergySurcharge**

A charge related to increases in the cost of energy.

**Environmental**

An allowance applied due to environmental regulations.

**ExpeditedShipmentCharge**

An extra cost charged due to unexpected or emergency requirements (for example, breaking off a run in the mill to reach the production date for a rush order).

**ExportClearanceCharge**

An extra fee for customs administration.

**FlatRateCharge**

A general flat charge.

**FreightAllowance**

The freight cost allowed by the mill. This amount is negative, and will be deducted from the Invoice (U.S. business practice, in the European Union (EU), use only Freight Charge).

**FreightCharge**

The actual cost incurred to deliver the product. This amount is positive, and will be added to the Invoice.

**FuelAdjustmentCharge**

An extra fee, usually from shipping companies, to adjust fuel prices.

**HandlingCharge**

A charge related to the handling of the product.

## **Inspection**

The cost associated with performing an inspection of the product.

## **InterestCharge**

A charge applied for interest on overdue payments.

## **LabourAllowance**

An allowance due to additional labour required in the use or acceptance of the product.

## **LabourCharge**

A charge due to additional labour required in the use or acceptance of the product.

## **LoggingDamage**

An adjustment caused by logging damages on Forest Wood products. Logging damages normally cause a reduction of the product price.

## **LotCharge**

A charge applied to the lot of material.

## **MetalDetection**

A charge for additional metal detection applied to the goods.

## **ModelHomeDiscount**

A discount associated with the building of the model home.

## **NewStoreCouponDiscount**

A discount associated with entry into a new store.

## **OrderQuantity**

A charge or allowance for small/big ordered quantities.

## **PalletCharge**

A charge that represents the cost or rental of the pallet.

## **PickUpAllowance**

An allowance provided to compensate for the cost of picking up the product.

## **PromotionalAllowance**

An allowance provided for the promotion of the product.

## **PromotionalCharge**

A charge associated with the promotion of the product.

## **PriceCorrection**

An adjustment associated with a correction of the product's price.

## **ProductionSetUpCharge**

A special charge applied due to specific buyer requests.

## **Provision**

The act of making ready or equipping for use.

**Rebate**

A rebate accepted by the buyer and seller based on the agreed price and volume.

**ReelDiscount**

An allowance for purchasing reels instead of sheets.

**ReturnedLoadAllowance**

An allowance applied due to the return of the load.

**ReturnLoadCharge**

A charge applied due to the return of the load.

**RoadFeeCharge**

A freight charge for a special tax applied to road transports in some countries, e.g. Germany

**ScrapAndDunnageCharge**

A charge that represents the scrapping of the material and its removal.

**ServiceCharge**

A charge associated with a miscellaneous service.

**SpecialConversionCharge**

Additional charge for a special conversion of the product.

**SpecialDeliveryCharge**

A special charge for delivering the product differently from the usual or agreed-to method.

**SpecialHandlingCharge**

A special charge for handling the product differently from the usual or agreed-to method.

**SpecialPackagingCharge**

A special charge for packaging the product differently from the usual or agreed-to method, or if packaging as requested is out of spec.

**StopOffAllowance**

An allowance for a delivery stop-off.

**StopOffCharge**

A charge for a delivery stop-off.

**StorageAllowance**

An allowance for storing the product.

**StorageCharge**

An extra cost charged for storing the product on location (in the plant).

**Tax**

An adjustment that reflects a tax item.

**TestingCharge**

A charge related to testing a paper grade.

## TradeDiscount

A discount based on the terms of the trade given on the agreed price. Usually a percentage.

## TrialDiscount

A discount applied for a trial run of a new or improved product.

## TransferCharge

A freight charge incurred by the goods transfer from one location to another location not previously agreed upon.

## UnloadingAllowance

An allowance to compensate for the unloading the product.

## UnloadingCharge

A charge for the unloading the product.

## VolumeDiscount

A rebate accepted by the buyer and the seller based on the agreed volume

## WarRiskCharge

An extra fee from transport companies for transport units that cross war zones.

## Other

Any other adjustment not covered by the attribute list.

---

## ChargePerUnit

A group item containing a currency value and measurement to communicate a per unit charge.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### CurrencyValue

*CurrencyValue is mandatory.  
A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

#### Value

*Value is mandatory. A single instance is required.*


A numeric value expressed in the unit of measure (UOM).

#### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax



*RangeMax is optional. A single instance might exist.*


The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## ChargeType [attribute]

The type of charge

*This item is restricted to the following list.*



### **AdministrativeCosts**

The administrative costs involved as a result of the complaint, for instance, to sell or scrap the waste.

### **AgreedWasteToScrap**

The agreed to quantity or amount of paper the complainer declares to scrap.

### **AgreedWasteToSell**

The agreed to quantity or amount of paper the complainer declares to sell.

### **ConversionCosts**

Costs associated with product conversion (i.e. slitting, rewrapping, etc).

### **KnownProductionDowntime**

Production down time associated with KnownBreaks.

### **LabourCosts**

The labour costs involved as a result of the complaint, for instance reels that need to be cleaned because of edge cuttings.

### **MachineDamage**

The damage suffered by the machine as a result of poor quality paper supplied.

### **PriceDifference**

A difference in the price.

### **ProductionDowntime**

Production downtime associated with the result of poor quality paper or a service problem.

### **RejectedReel**

The reel(s) rejected because not workable by the converter/printer.

### **UnknownProductionDowntime**

Production downtime associated with Breaks.

### **WasteToScrap**

The proposed quantity or amount of paper the complainer declares to scrap.

### **WasteToSell**

The proposed quantity or amount of paper the complainer declares to sell.

## **WrongQuantity**

The wrong quantity was reported.

## **Other**

Used to communicate a ChargeType that is not available in the enumerated list.

---

## ChildrensTitle [attribute]

Specifies if the book product is designated for use by children 12 and under or not.

*This item is restricted to the following list.*

attribute	
ChildrensTitle	
type	childrensTitleType

### **NotChildrensTitle**

Not a children's product; no testing required for lead or phthalates.

### **ChildrensWithPlayValue**

Designated as a children's product and has "play value" outside of reading and writing; requires testing for lead and phthalates. (Examples of "play value" include paper doll books, sticker books, board books and bathtub books).

### **ChildrensWithoutPlayValue**

Designated as a children's product but does not have any "play value" outside of reading and writing; requires testing for lead but not phthalates.


---

## Chip

Chip information.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### **ChipCharacteristics**

*ChipCharacteristics is optional. A single instance might exist.*

Chip characteristics

### **ChipPackagingCharacteristics**

*ChipPackagingCharacteristics is optional. A single instance might exist.*

ChipPackagingCharacteristics provides information about the containerisation of the wood chips.

## ChipCharacteristics

Chip characteristics

### Screened [attribute]

*Screened is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Screened definition for any enumerations.

### Debarked [attribute]

*Debarked is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Debarked definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Thickness

*Thickness is optional. A single instance might exist.*

Physical dimension of a product.

#### Moisture

*Moisture is optional. A single instance might exist.*

Desired percentage, or other indicator, of water in the product at the time of shipment.

#### Dirt

*Dirt is optional. A single instance might exist.*

A group item used to communicate dirt content target or test value according to a particular TestMethod.

#### Bark


*Bark is optional. A single instance might exist.*

Used to report bark content in chips as a detail measurement.

#### Sawdust

*Sawdust is optional. A single instance might exist.*

Used to report sawdust content in chips as a detail measurement.



## ChipFraction

A grouping element that contains information about one fraction from an analysis of chip fractions.

### ChipFractionPropertyType [attribute]

*ChipFractionPropertyType is mandatory. A single instance is required.*

Defines the type of property for analysis of chip fractions.

Refer to ChipFractionPropertyType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### ChipFractionNumber

*ChipFractionNumber is mandatory. A single instance is required.*

The date when the analysis of chip fractions was done.

### ChipFractionDescription

*ChipFractionDescription is optional. Multiple instances might exist.*

The date when the analysis of chip fractions was done.

### ChipFractionClass


*ChipFractionClass is optional. A single instance might exist.*

The date when the analysis of chip fractions was done.

### ChipFractionValue

*ChipFractionValue is mandatory. A single instance is required.*

A grouping element for a chip fraction value and its statistical measures.




## ChipFractionAnalysisDate

The date when the analysis of chip fractions was done.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss,


# papiNet V2R31

hh:mm:ssZ, or hh:mm:ss±hh:mm.

- hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.
- hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.
- hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.


## ChipFractionClass

Specifies the class of the chip fraction.



## ChipFractionDescription

A free form description of the chip fraction.



## ChipFractionInfo

Grouping element that contains information about analysis of chip fractions.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]


*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*



Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

## **ResultSource [attribute]**

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document

### **ChipFractionAnalysisDate**

*ChipFractionAnalysisDate is mandatory. A single instance is required.*

The date when the analysis of chip fractions was done.

### **ChipFraction**

*ChipFraction is mandatory. Multiple instances might exist.*

The date when the analysis of chip fractions was done.

---

## **ChipFractionNumber**

The identifier of a chip fraction.

ChipFractionNumber	
type	s30

---

## **ChipFractionPropertyType [attribute]**

Defines the type of property for analysis of chip fractions.

*This item is restricted to the following list.*

ChipFractionPropertyType	
type	chipFractionPropertyType

### **Length**

Length of the chip fraction.

### **Size**

Size of the chip fraction.

### **Thickness**

Thickness of the chip fraction.

### **Width**

Width of the chip fraction.

## ChipFractionValue

A grouping element for a chip fraction value and its statistical measures.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

#### SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

#### TwoSigmaLower


*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

#### TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.



---

## ChipPackagingCharacteristics


ChipPackagingCharacteristics provides information about the containerisation of the wood chips.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

ChipPackagingCharacteristics

(sequence)



### Identifier

*Identifier is mandatory. A single instance is required.*

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.

### Quantity

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

### InformationalQuantity


*InformationalQuantity is optional. A single instance might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

---

## City

Name of the city associated with the address elements.




## ClassIdentifier

Standard used for product identification.

### IdentifierCodeType [attribute]

*IdentifierCodeType is mandatory. A single instance is required.*

Defines the type of product identifier used (for example, reel number, ream number, bar code). This code type specifies how to decode the identifier value.



Refer to IdentifierCodeType definition for any enumerations.

### IdentifierType [attribute]

*IdentifierType is mandatory. A single instance is required.*

This attribute specifies whether the Identifier is the primary way to identify the product or a secondary way. Only one of the given identifiers can be primary. In addition, this attribute also specifies the physical support used to code the identifier (for example, a Radio Frequency (RF) Tag).

Refer to IdentifierType definition for any enumerations.

### IdentifierFormatType [attribute]

*IdentifierFormatType is optional. A single instance might exist.*

IdentifierFormatType defines the technical format used to make an IdentifierCodeType readable by technical devices or humans. The IdentifierCodeType specifies how to decode the identifier value


Refer to IdentifierFormatType definition for any enumerations.

## Classification

A group item that details the product classification according to a particular organization's scheme.

An item across multiple classifications would still be recognized as the same item. Examples of some product classifications are: Containerboard, Pulp-

Dissolving, or Newsprint.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ClassificationCode

*ClassificationCode is mandatory. A single instance is required.*

A code assigned by the indicated Agency for this particular class of product.

#### ClassificationDescription

*ClassificationDescription is optional. Multiple instances might exist.*

A free form description of the classification.

---

## ClassificationCode

A code assigned by the indicated Agency for this particular class of product.

### Agency [attribute]


*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.


Refer to Agency definition for any enumerations.



---

## ClassificationDescription

A free form description of the classification.



---


## ClothCrossCut [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

**Yes**

**No**



## CMYK

A definition of colour using the CMYK protocol.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Cyan

*Cyan is mandatory. A single instance is required.*

The Cyan component of a colour in the CMYK approach to colour definition.

#### Magenta

*Magenta is mandatory. A single instance is required.*

The Magenta component of a colour.

Magenta is a locally defined element used in the CMYK element.

#### Yellow


*Yellow is mandatory. A single instance is required.*

The Yellow component of a colour.

#### Black

*Black is mandatory. A single instance is required.*

The Black component of a colour.



## Coating

### Coating

*This item is restricted to the following list.*

#### **AnimalGlueableStampableFilm**

#### **Aqueous**

Aqueous coating is a water-based sealant.

#### **Diamond**

Hard carbon coating.

#### **DiamondUV**

#### **Film**

A thin sheet of material, usually plastic and transparent.

#### **GlossUltracure**

#### **GlossUV**

#### **Gritty**

#### **GrittyMatteUV**

#### **Lacquer**

Clear or coloured varnish that dries by solvent evaporation and often a curing process as well that produces a hard, durable finish, in any sheen level from ultra matte to high gloss and that can be further polished as required.

#### **Laminate**

#### **MatteUV**

#### **MylarFilm**

A thin polyester film.

#### **MylarFilmGloss**

#### **MylarFilmMatte**

#### **MylarFilmSilver**

#### **NoFinish**

#### **Non-Standard**

#### **PHOENIXPremier**

#### **PolyesterFilm**

Made of synthetic resins which are light and strong and weather resistant.

#### **PolyesterGloss**


#### **PolyesterMatte**

#### **PolypropyleneFilm**

#### **PolypropyleneFilmGloss**

#### **PolypropyleneFilmMatte**

#### **Press**



Applied by a unit of the press.

**PressVarnish**

**PressVarnishDull**

**PressUV**

**SatinFilm**

**Silkscreen**

A print made by forcing ink through a fine (silk) mesh.

**SilkscreenGloss**

**SilkscreenUV**

**StayFlat**

Contains materials to prohibit the sheet from curling.

**StayFlatFilmGloss**

**StayFlatFilmMatte**

**Tint**

Screening or adding white to a solid color for results of lightening that specific color.

**TintVarnish**

**Ultracure**

**Ultraviolet**

Ultra-violet coating is a highly reactive, cross-linking system in which the vehicle is dried by exposure to UV radiation.

**Varnish**

Petroleum-based sealant applied by a standard inking unit in the press.

## **CoatingCoverageType [attribute]**

*CoatingCoverageType is optional. A single instance might exist.*

Communicates the degree of coating coverage.

Refer to CoatingCoverageType definition for any enumerations.

## **CoatingLocationType [attribute]**

*CoatingLocationType is optional. A single instance might exist.*

Specifies which side of the product the coating should be applied.

Refer to CoatingLocationType definition for any enumerations.

## **FinishType [attribute]**

*FinishType is optional. A single instance might exist.*

Defines the finish of a sheet of paper, which means the condition of its surface (refer to Embossing for more information).

Finishes may be produced on or off machine. Finishes that are created off-machine are called embossed. (Embossing is a child element of

ReelConversionCharacteristics and SheetConversionCharacteristics.)

Note:

Embossed" as a finish type is just a generalized choice for one of the more specific choices listed.

Unsupercalendered" as a finish type would be indicated by not communicating a finish type.

Refer to FinishType definition for any enumerations.


---

## CoatingBottom [attribute]

Used to specify the type of coating applied to the top or bottom of the paper sheet

*This item is restricted to the following list.*

**Acrylic**  
**Flexolyn**  
**FoilCoated**  
**GreaseBarrier**  
**Metallic**  
**MetalizedPolyester**  
**MoistureBarrier**  
**MoldInhibitor**  
**None**  
**OilBarrier**  
**OxygenBarrier**  
**Plastic**  
**PolyCoating**  
**Polyethylene**  
**Pyroxylin**  
**Silicone**



---

## CoatingCoverageType [attribute]

Communicates the degree of coating coverage.

*This item is restricted to the following list.*

**FullCoverage**

The entire item is coated.

**SpotCoverage**

The item is partially coated.



## CoatingLocation [attribute]

Coating location

*This item is restricted to the following list.*

attribute
<b>CoatingLocation</b>
type coatingLocation

### **Back**

Top ply of a multi-part business form. Its upper surface is not coated. Its lower surface has a coating of microscopic capsules containing colourless dye. When pressure or impact fractures the capsules, the dye is released to react with the sheet of carbonless paper below it having a coated front top surface. The image is formed on the coated front surface.

### **Front**

The coated front sheet is used as the bottom ply of a multi-part form. The coated front sheet can receive the image from the coated back surface of the sheet above it, but it does not transmit the image nor is there a sheet below it in the form.

### **FrontAndBack**

The coated front and back sheet is used for all plies of a carbonless form between the top and bottom plies. The under-surface of each coated front and back sheet is coated with dye capsules (coated back coating). The upper surface (coated front) reacts with the colourless dye released from fractured capsules to produce the image.

### **SelfContained**

Carbonless paper containing both the coated back dye capsules and the coated front receptor coating on the upper surface of the same sheet, Self-contained carbonless paper can be used to create a carbonless copy when used as a second ply below almost any kind of paper.

---

## CoatingLocationType [attribute]

Specifies which side of the product the coating should be applied.

*This item is restricted to the following list.*

attribute
<b>CoatingLocationType</b>
type coatingLocationType

### **Top**

Top side of a printed component

### **Bottom**

Bottom side of a printed component

### **TopAndBottom**

### **Front**

Front side of a book

### **Back**

Back of a book

### **FrontAndBack**

## Spine

Spine of a book which is where the pages are glued or sewn together

**FrontAndSpine**

**BackAndSpine**

**FrontAndBackAndSpine**

---

## CoatingTop [attribute]

Used to specify the type of coating applied to the top or bottom of the paper sheet

*This item is restricted to the following list.*

attribute
<b>CoatingTop</b>
type coatingType

**Acrylic**

**Flexolyn**

**FoilCoated**

**GreaseBarrier**

**Metallic**

**MetalizedPolyester**

**MoistureBarrier**

**MoldInhibitor**

**None**

**OilBarrier**

**OxygenBarrier**

**Plastic**

**PolyCoating**

**Polyethylene**

**Pyroxylin**

**Silicone**

## CoatWeight

A group item used to communicate the coating thickness target or test value according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*


The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation



# papiNet V2R31

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.


## Collated [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

Yes

No



## CoLoading

A group item specifying information about items to be loaded or loaded on the same transport unit.

Used to identify:

Delivery together to the drop point

Transport Orders stuffed together in a container

Transport Orders not splittable


### CoLoadingType [attribute]

*CoLoadingType is mandatory. A single instance is required.*

Provides the Co-Loading type which can control and confirm co-loading.

Refer to CoLoadingType definition for any enumerations.

### (sequence)



# papiNet V2R31

---

The sequence of items below is mandatory. A single instance is required.

## CoLoadingNumber

*CoLoadingNumber is optional. A single instance might exist.*

The identifier for the CoLoading communication.

## DeliveryInstructionNumber

*DeliveryInstructionNumber is optional. A single instance might exist.*

The unique identifier for the DeliveryInstruction.

## DeliveryInstructionSequenceNumber

*DeliveryInstructionSequenceNumber is optional. A single instance might exist.*

A sequential number that uniquely identifies the Sequence of a DeliveryInstruction.

## CoLoadingReference

*CoLoadingReference is optional. Multiple instances might exist.*

An element item detailing relevant references pertaining to the coloding process.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.


---

## CoLoadingNumber

The identifier for the CoLoading communication.

### AssignedBy [attribute]

*AssignedBy is mandatory. A single instance is required.*



Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy definition for any enumerations.


---

## CoLoadingReference

An element item detailing relevant references pertaining to the coloding process.

### CoLoadingReferenceType [attribute]

*CoLoadingReferenceType is mandatory. A single instance is required.*



CoLoadingReferenceType provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Customer", "Seller", and/or "Supplier". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date)

version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to CoLoadingReferenceType definition for any enumerations.

## AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*


Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations

---

## CoLoadingReferenceType [attribute]

CoLoadingReferenceType provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Customer", "Seller", and/or "Supplier". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.



Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

---

## CoLoadingType [attribute]

Provides the Co-Loading type which can control and confirm co-loading.

*This item is restricted to the following list.*

### CoLoaded


The delivery is co-loaded with other goods on the same transport unit.

### Requested

CoLoading is requested and should be executed if possible.

### Required

CoLoading is required and should always be executed.




---

## ColourCode

A code indicating the colour.

## Agency [attribute]

*Agency is optional. A single instance might exist.*



Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.


For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

## ColourDescription

A free form description of the colour.



## ColourDetail

A group item used to communicate details of colour according to the selected colour definition scheme.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### (choice)

*[choice] is optional because of choice construct.*

#### CMYK

*CMYK is optional because of choice construct.*

A definition of colour using the CMYK protocol.

#### ColourShade

*ColourShade is optional because of choice construct.*

The colour shade as defined by the indicated Agency.

#### HSB

*HSB is optional because of choice construct.*

A definition of colour using the HSB protocol.


All the components of the definition are required. The structure of Hue, Saturation, and Brilliance follows DetailMeasurement.

#### Lab

*Lab is optional because of choice construct.*

A definition of colour using the L\*a\*b protocol.

L\*a\*b colour consists of a luminance or lightness component (L) and two chromatic components: a component (from green to red) and the b component



# papiNet V2R31

---

(from blue to yellow). All the components of the definition are required. The structure of Luminance, "a", and "b" follows DetailMeasurement.

## **RGB**

*RGB is optional because of choice construct.*

A definition of colour using the RGB protocol.

## **ColourDescription**

*ColourDescription is optional. Multiple instances might exist.*

A free form description of the colour.

## **ColourCode**

*ColourCode is optional. A single instance might exist.*

A code indicating the colour.

---

## **ColourLocation [attribute]**

*This item is restricted to the following list.*

### **Front**

### **Back**

### **Page1**

Page1 is defined to be the front-outside of a 4 page component such as a cover or a endsheet.

### **Page2**

Page2 is defined to be the front--i Inside of a 4 page component such as a cover or a endsheet.

### **Page3**

Page3 is defined to be the back-inside of a 4 page component such as a cover or a endsheet.

### **Page4**

Page4 is defined to be the back-outside of a 4 page component such as a cover or a endsheet.



---

## **ColourMatchDescription**

Colour match description




## ColourShade

The colour shade as defined by the indicated Agency.

### Agency [attribute]

*Agency is mandatory. A single instance is required.*



Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

## ColourSpecs

Colour specs

### ColourLocation [attribute]

*ColourLocation is optional. A single instance might exist.*

Refer to ColourLocation definition for any enumerations.

### (sequence)

*The sequence of items below is optional. Multiple instances might exist.*

#### ColourCode

*ColourCode is optional. A single instance might exist.*

A code indicating the colour.

#### ColourDescription

*ColourDescription is mandatory. A single instance is required.*

A free form description of the colour.

#### NumberOfColours

*NumberOfColours is optional. A single instance might exist.*

The number of colours.


#### InkTypeDescription

*InkTypeDescription is optional. A single instance might exist.*

Ink type description

#### ColourMatchDescription

*ColourMatchDescription is optional. A single instance might exist.*



Colour match description

## **ColourShade**

*ColourShade is optional. A single instance might exist.*

The colour shade as defined by the indicated Agency.

## **InkCoverage**

*InkCoverage is optional. A single instance might exist.*


Ink coverage

---

## **CommodityGoodsCode**

A code defining the type of goods handled or traded.

The Harmonized Commodity Description and Coding System (HS) of the Customs Cooperation Council (CCC) is used worldwide as a reference for classifications of external trade statistics and for customs tariffs.



### **Agency [attribute]**

*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

## CommonContact

Identifies a specific individual associated with the party.

### ContactType [attribute]

*ContactType is mandatory. A single instance is required.*

Identifies the role of the contact within the party.

Refer to ContactType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ContactName

*ContactName is mandatory. A single instance is required.*

The name of the individual associated with the ContactType.

#### ContactIdentifier

*ContactIdentifier is optional. A single instance might exist.*

The identifier for the contact.

#### Telephone

*Telephone is optional. A single instance might exist.*

The business phone number of the individual associated with the ContactName.

#### MobilePhone

*MobilePhone is optional. A single instance might exist.*

The mobile phone number of the individual associated with the ContactName.

#### Email

*Email is optional. A single instance might exist.*

The primary business email address of the individual associated with the ContactName.

#### Fax

*Fax is optional. A single instance might exist.*


The primary business fax number of the individual associated with the ContactName.

### (choice)

*[choice] is optional because of choice construct.*

#### GPSCoordinates

*GPSCoordinates is optional because of choice construct.*



The location of the party as specified using a Global Positioning System.

## MapCoordinates

*MapCoordinates is optional because of choice construct.*

A group item defining and containing position co-ordinates of a location.

## CommunicationRole [attribute]

Provides information about the sender, receiver, and participants to the document communication.

*This item is restricted to the following list.*

### From

The document originates from this party.

### To

The document is destined to this party.

### CC


This party is copied on the document



## Complaint

The Complaint element is the root element for the Complaint e-Document.

Typically, a Complaint e-Document is sent from the customer or end user to the supplier to communicate information regarding products or services. A response from the supplier is desired and corrective actions, if required. This e-Document must specify the necessary details to enable the supplier to trigger an internal process to verify whether the complaint reason corresponds to the supplier-assessed reason.



### ComplaintType [attribute]

*ComplaintType is mandatory. A single instance is required.*

Indicates if the e-Document represents a Complaint by the sender or Feedback from the sender.

Refer to ComplaintType definition for any enumerations.

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

## **Language [attribute]**

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **ComplaintHeader**

*ComplaintHeader is mandatory. A single instance is required.*

The ComplaintHeader is required and contains information common to the Complaint.

### **ComplaintLineItem**

*ComplaintLineItem is mandatory. One instance is required, multiple instances might exist.*

The detail information of one of the items on the Complaint.

### **ComplaintSummary**

*ComplaintSummary is optional. A single instance might exist.*

Summary information that applies to the entire Complaint e-Document.

## ComplaintHeader

The ComplaintHeader is required and contains information common to the Complaint.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ComplaintNumber

*ComplaintNumber is mandatory. A single instance is required.*

A unique identification number of the Complaint, generated by the complainer.

#### ComplaintIssueDate

*ComplaintIssueDate is mandatory. A single instance is required.*

The date on which the Complaint was issued by the complainer

#### ComplaintReference

*ComplaintReference is optional. Multiple instances might exist.*

A group item detailing relevant references pertaining to the Complaint. ComplaintReference contains the attribute ComplaintReferenceType.

#### RequestedAction

*RequestedAction is optional. A single instance might exist.*

The element that enables the party making the complaint (i.e. SenderParty) to specify what they want done regarding the Complaint (send a credit, send disposition instructions, etc.)

#### SenderParty

*SenderParty is mandatory. A single instance is required.*

The business entity issuing the e-Document, the source of the document.


The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

#### ReceiverParty

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.



## **RespondToParty**

*RespondToParty is mandatory. One instance is required, multiple instances might exist.*

The party the document should be responded to.

## **BuyerParty**

*BuyerParty is optional. A single instance might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## **BillToParty**

*BillToParty is optional. A single instance might exist.*

The address where the Invoice is to be sent.

## **RemitToParty**

*RemitToParty is optional. A single instance might exist.*

A group item containing details of the party to whom payment will be made. The RemitToParty contains all information related to remittance.

## **EndUserParty**

*EndUserParty is optional. A single instance might exist.*

The party using, consuming, or converting the product. For example, a printer using paper reels for a print job for a publisher. The final ShipTo destination for a product is normally to the end user's facilities.

## **SupplierParty**

*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **OtherParty**

*OtherParty is optional. A single instance might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **e-Attachment**

*e-Attachment is optional. A single instance might exist.*

e-Attachment enables the sender to provide information about attachments to the document.

Note: BizTalk users may have problems in processing this element. See the papiNet FAQs ([papiNet.org](http://papiNet.org)) for more information.

## **MailAttachment**

*MailAttachment is optional. Multiple instances might exist.*

MailAttachment enables the complainer to indicate that they are providing by mail (express courier, snail mail etc.) proof of the Complaint.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.


---

## **ComplaintInformation**

ComplaintInformation is a grouping element that contains general information about the Complaint.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### **ComplaintNumber**

*ComplaintNumber is mandatory. A single instance is required.*

A unique identification number of the Complaint, generated by the complainer.

### **ComplaintIssueDate**

*ComplaintIssueDate is mandatory. A single instance is required.*

The date on which the Complaint was issued by the complainer

### **ComplaintReference**

*ComplaintReference is optional. Multiple instances might exist.*

A group item detailing relevant references pertaining to the Complaint. ComplaintReference contains the attribute ComplaintReferenceType.


---

## **ComplaintIssueDate**

The date on which the Complaint was issued by the complainer

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### **Date**

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### **Time**

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a

# papiNet V2R31

generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## ComplaintLineItem

The detail information of one of the items on the Complaint.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### ComplaintLineItemNumber

ComplaintLineItemNumber is mandatory. A single instance is required.

The number used to identify the Complaint line item

#### ComplaintReason

ComplaintReason is mandatory. A single instance is required.

A group item containing the reason for the Complaint.



#### RequestedAction

RequestedAction is optional. A single instance might exist.


The element that enables the party making the complaint (i.e. SenderParty) to specify what they want done regarding the Complaint (send a credit, send disposition instructions, etc.)

#### ConsumptionProcess

ConsumptionProcess is optional. A single instance might exist.

Identifies the process relevant to the situation being described.

Refer to ConsumptionProcess definition for



any enumerations.

## **TransportInformation**

*TransportInformation is optional. A single instance might exist.*

A grouping element for transport information.

## **NumberOfComplaintLineItemDetail**

*NumberOfComplaintLineItemDetail is optional. A single instance might exist.*

The number of ComplaintLineItemDetail elements for a given ComplaintLineItem (Example: the number of reels in a ComplaintLineItem)

### **(choice)**

*[choice] is optional because of choice construct.*

#### **ComplaintSpecification**

*ComplaintSpecification is optional because of choice construct.*

A group item containing information necessary to identify the physical item

#### **ComplaintLineItemDetail**

*ComplaintLineItemDetail is optional because of choice construct.*

A group item containing information necessary to identify the type of article being complained (example: pallet, reel etc.)

## **Quantity**

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **ComplaintLineNetChargeAmount**

*ComplaintLineNetChargeAmount is optional. A single instance might exist.*

The total complained amount per line.

## **e-Attachment**

*e-Attachment is optional. A single instance might exist.*

e-Attachment enables the sender to provide information about attachments to the document.

Note: BizTalk users may have problems in processing this element. See the papiNet FAQs ([papiNet.org](http://papiNet.org)) for more information.

## **MailAttachment**

*MailAttachment is optional. Multiple instances might exist.*

MailAttachment enables the complainer to indicate that they are providing by mail (express courier, snail mail etc.) proof of the Complaint.


## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## ComplaintLineItemDetail

A group item containing information necessary to identify the type of article being complained (example: pallet, reel etc.)



### ItemType [attribute]


*ItemType is mandatory. A single instance is required.*

Indicates the form of the item being reported as being used. Many of the ItemType(s) indicated here have a corresponding named element equivalent, which is referenced here for definition purposes.

Refer to ItemType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### ComplaintLineItemDetailNumber

*ComplaintLineItemDetailNumber is mandatory. A single instance is required.*

The sequential number of an item assigned by the party making the Complaint within ComplaintLineItemDetail

### ComplaintReference

*ComplaintReference is optional. A single instance might exist.*

A group item detailing relevant references pertaining to the Complaint.

ComplaintReference contains the attribute ComplaintReferenceType.

## **ComplaintReason**

*ComplaintReason is optional. A single instance might exist.*

A group item containing the reason for the Complaint.

## **Identifier**

*Identifier is mandatory. One instance is required, multiple instances might exist.*

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.

## **Charge**

*Charge is optional. Multiple instances might exist.*

Charge is a group element that contains elements that describe a charge.

## **Product**

*Product is optional. A single instance might exist.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **(sequence)**

*The sequence of items below is optional. A single instance might exist.*

### **PurchaseOrderInformation**

*PurchaseOrderInformation is mandatory. A single instance is required.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

### **PurchaseOrderLineItemNumber**

*PurchaseOrderLineItemNumber is mandatory. A single instance is required.*

The sequential number that uniquely identifies the PurchaseOrder line item.

## **NetChargeAmount**

*NetChargeAmount is optional. A single instance might exist.*

A field containing the sum of all instances of the Complaint charges.


## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.


## ComplaintLineItemDetailNumber

The sequential number of an item assigned by the party making the Complaint within ComplaintLineItemDetail



## ComplaintLineItemNumber

The number used to identify the Complaint line item




## ComplaintLineNetChargeAmount

The total complained amount per line.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*




**CurrencyValue**

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

## ComplaintNumber

A unique identification number of the Complaint, generated by the complainer.



## ComplaintReason

A group item containing the reason for the Complaint.

**ComplaintReasonType**  
**[attribute]**

*ComplaintReasonType is optional. A single instance might exist.*

The type of complaint reason.

Refer to ComplaintReasonType definition for any enumerations.


**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**ComplaintReasonCode**

*ComplaintReasonCode is optional. A single instance might exist.*

A code for quickly communicating the type of ComplaintReason. The Agency



responsible for the code can be associated with the element.

## **ComplaintReasonDescription**


*ComplaintReasonDescription is optional. Multiple instances might exist.*

A text field element describing the reason for the Complaint

---

## **ComplaintReasonCode**

A code for quickly communicating the type of ComplaintReason. The Agency responsible for the code can be associated with the element.



### **Agency [attribute]**

*Agency is optional. A single instance might exist.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.


For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

---

## **ComplaintReasonDescription**

A text field element describing the reason for the Complaint



---

## **ComplaintReasonType [attribute]**

The type of complaint reason.

*This item is restricted to the following list.*

**Commercial**

**Logistical**


**Technical**



---

## ComplaintReference

A group item detailing relevant references pertaining to the Complaint. ComplaintReference contains the attribute ComplaintReferenceType.



### **ComplaintReferenceType** **[attribute]**

*ComplaintReferenceType is optional. A single instance might exist.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to ComplaintReferenceType definition for any enumerations.

### **AssignedBy** [attribute]

*AssignedBy is optional. A single instance might exist.*


Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## **ComplaintReferenceType** [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.




Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## ComplaintResponse

The ComplaintResponse element is the root element for the ComplaintResponse e-Document.

Typically, a ComplaintResponse e-Document is sent from the supplier or sender parties to the party who has originated the Complaint, or possibly to the RespondToParty. The e-Document is sent to communicate the acceptance, partial acceptance, or rejection, of the preceding complaint(s) with supporting information. Whatever the decision, this e-Document must specify how the complaint will be processed.



### ComplaintResponseType [attribute]

*ComplaintResponseType is mandatory. A single instance is required.*

Indicates if the e-Document represents a Complaint by the sender or Feedback from the sender.

Refer to ComplaintResponseType definition for any enumerations.

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ComplaintResponseHeader

*ComplaintResponseHeader is mandatory. A single instance is required.*

The ComplaintResponseHeader is required and contains information common to the ComplaintResponse.

#### ComplaintResponseLineItem

*ComplaintResponseLineItem is mandatory. One instance is required, multiple instances might exist.*

The detail information about the response for a particular complaint.

# papiNet V2R31

---

Note: In version V2R30 the multiplicity of e-Attachment was changed from optional, repeatable to optional, single. It is recognized that this is not backwardly compatible. We apologize for any issues this causes.

## **ComplaintResponseSummary**

*ComplaintResponseSummary is optional. A single instance might exist.*

Summary information that applies to the entire ComplaintResponse e-Document.

## ComplaintResponseHeader

The ComplaintResponseHeader is required and contains information common to the ComplaintResponse.

### ComplaintResponseHeaderStatusType [attribute]

*ComplaintResponseHeaderStatusType is mandatory. A single instance is required.*

The status of the ComplaintResponse header.

Refer to



ComplaintResponseHeaderStatusType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ComplaintResponseNumber

*ComplaintResponseNumber is mandatory. A single instance is required.*

A unique identification number of the ComplaintResponse, generated by the issuer of the ComplaintResponse.

#### ComplaintResponseIssueDate

*ComplaintResponseIssueDate is mandatory. A single instance is required.*

The date on which the ComplaintResponse was issued within the sender's system.

#### ComplaintInformation

*ComplaintInformation is mandatory. One instance is required, multiple instances might exist.*

ComplaintInformation is a grouping element that contains general information about the Complaint.

#### RequestedAction


*RequestedAction is optional. A single instance might exist.*

The element that enables the party making the complaint (i.e. SenderParty) to specify what they want done regarding the Complaint (send a credit, send disposition instructions, etc.)

#### CorrectiveAction

*CorrectiveAction is mandatory. A single instance is required.*

This element enables the party issuing the ComplaintResponse (i.e. SupplierParty) to specify what is the corrective action they will take in order to close the Complaint (send a credit, send disposition instructions, etc.)



## **SenderParty**

*SenderParty is mandatory. A single instance is required.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **RespondToParty**

*RespondToParty is mandatory. One instance is required, multiple instances might exist.*

The party the document should be responded to.

## **BuyerParty**

*BuyerParty is optional. A single instance might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## **BillToParty**

*BillToParty is optional. A single instance might exist.*

The address where the Invoice is to be sent.

## **RemitToParty**

*RemitToParty is optional. A single instance might exist.*

A group item containing details of the party to whom payment will be made. The RemitToParty contains all information related to remittance.

## **EndUserParty**

*EndUserParty is optional. A single instance might exist.*

The party using, consuming, or converting the product. For example, a printer using paper reels for a print job for a publisher. The final ShipTo destination for a product is normally to the end user's facilities.

## **SupplierParty**

*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-

Document.

## **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **e-Attachment**

*e-Attachment is optional. A single instance might exist.*

e-Attachment enables the sender to provide information about attachments to the document.

Note: BizTalk users may have problems in processing this element. See the papiNet FAQs (papiNet.org) for more information.

## **MailAttachment**

*MailAttachment is optional. Multiple instances might exist.*

MailAttachment enables the complainer to indicate that they are providing by mail (express courier, snail mail etc.) proof of the Complaint.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **ComplaintResponseHeaderStatusType [attribute]**

The status of the ComplaintResponse header.

*This item is restricted to the following list.*



### **Accepted**

The supplied information is accepted.

### **PartiallyAccepted**

The supplied information is not completely accepted.

### **Rejected**

The supplied information is rejected.


---

## ComplaintResponseIssueDate

The date on which the ComplaintResponse was issued within the sender's system.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.


## ComplaintResponseLineItem

The detail information about the response for a particular complaint.

Note: In version V2R30 the multiplicity of e-Attachment was changed from optional, repeatable to optional, single. It is recognized that this

**ComplaintResponseLineItem**

is not backwardly compatible. We apologize for any issues this causes.



### ComplaintResponseLineStatusType [attribute]

*ComplaintResponseLineStatusType* is mandatory. A single instance is required.

The status of the ComplaintResponse line.

Refer to ComplaintResponseLineStatusType definition for any enumerations.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

## **ComplaintResponseLineItemNumber**

*ComplaintResponseLineItemNumber is mandatory. A single instance is required.*

The number used to identify the ComplaintResponse line item

## **ComplaintLineItemNumber**

*ComplaintLineItemNumber is mandatory. A single instance is required.*

The number used to identify the Complaint line item

## **ComplaintResponseReference**

*ComplaintResponseReference is optional. A single instance might exist.*

A group item detailing relevant references pertaining to the ComplaintResponse

## **ComplaintResponseReason**

*ComplaintResponseReason is mandatory. A single instance is required.*

A group item containing the reason assessed by the supplier or sender parties for the ComplaintResponse

## **CorrectiveAction**

*CorrectiveAction is optional. A single instance might exist.*

This element enables the party issuing the ComplaintResponse (i.e. SupplierParty) to specify what is the corrective action they will take in order to close the Complaint (send a credit, send disposition instructions, etc.)

## **RequestedAction**

*RequestedAction is optional. A single instance might exist.*

The element that enables the party making the complaint (i.e. SenderParty) to specify what they want done regarding the Complaint (send a credit, send disposition instructions, etc.)

## **ConsumptionProcess**

*ConsumptionProcess is optional. A single instance might exist.*

Identifies the process relevant to the situation being described.

Refer to ConsumptionProcess definition for any enumerations.

## **TransportInformation**

*TransportInformation is optional. A single instance might exist.*

A grouping element for transport information.

## **NumberOfComplaintResponseLineItemDetail**

*NumberOfComplaintResponseLineItemDetail is optional. A single instance might exist.*

The number of ComplaintResponseLineItemDetail elements for a given ComplaintResponseLineItem

## **(choice)**

*[choice] is optional because of choice construct.*

## **ComplaintResponseSpecification**

*ComplaintResponseSpecification is optional because of choice construct.*

A group item containing information necessary to identify the physical item.

## **ComplaintResponseLineItemDetail**

*ComplaintResponseLineItemDetail is optional because of choice construct.*

A group item containing information necessary to identify the type of article being complained.

## **Quantity**

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **ComplaintResponseLineNetChargeAmount**

*ComplaintResponseLineNetChargeAmount is optional. A single instance might exist.*

The net ComplaintResponse amount per line (excludes adjustments and tax).

## **e-Attachment**

*e-Attachment is optional. A single instance might exist.*

e-Attachment enables the sender to provide information about attachments to the document.

Note: BizTalk users may have problems in processing this element. See the papiNet FAQs ([papiNet.org](http://papiNet.org)) for more information.

## **MailAttachment**

*MailAttachment is optional. Multiple instances might exist.*

MailAttachment enables the complainer to indicate that they are providing by mail (express courier, snail mail etc.) proof of the Complaint.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## ComplaintResponseLineItemDetail

A group item containing information necessary to identify the type of article being complained.

### ItemType [attribute]

#### ComplaintResponseLineItemDetail


*ItemType is mandatory. A single instance is required.*

Indicates the form of the item being reported as being used. Many of the ItemType(s) indicated here have a corresponding named element equivalent, which is referenced here for definition purposes.

Refer to ItemType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### ComplaintResponseLineItemDetailNumber

*ComplaintResponseLineItemDetailNumber is optional. Multiple instances might exist.*

The sequential number of an item assigned by the party making the ComplaintResponse within line item detail.

### ComplaintResponseReference

*ComplaintResponseReference is optional. A single instance might exist.*

A group item detailing relevant references pertaining to the ComplaintResponse

### ComplaintResponseReason

*ComplaintResponseReason is optional. Multiple instances might exist.*

A group item containing the reason assessed by the supplier or sender parties for the ComplaintResponse

### Identifier

*Identifier is mandatory. One instance is required, multiple instances might exist.*

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item

# papiNet V2R31

---

identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.

## **Charge**

*Charge is optional. Multiple instances might exist.*

Charge is a group element that contains elements that describe a charge.

## **Product**

*Product is optional. A single instance might exist.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **(sequence)**

*The sequence of items below is optional. A single instance might exist.*

### **PurchaseOrderInformation**

*PurchaseOrderInformation is mandatory. A single instance is required.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

### **PurchaseOrderLineItemNumber**

*PurchaseOrderLineItemNumber is mandatory. A single instance is required.*

The sequential number that uniquely identifies the PurchaseOrder line item.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **ComplaintResponseLineItemDetailNumber**

The sequential number of an item assigned by the party making the ComplaintResponse within line item detail.

<b>ComplaintResponseLineItemDetailNumber</b>
type   lineNumberType

---

## **ComplaintResponseLineItemNumber**

The number used to identify the ComplaintResponse line item

<b>ComplaintResponseLineItemNumber</b>
type   lineNumberType

## ComplaintResponseLineNetChargeAmount

The net ComplaintResponse amount per line (excludes adjustments and tax).



**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

## ComplaintResponseLineStatusType [attribute]

The status of the ComplaintResponse line.

*This item is restricted to the following list.*



### Accepted

The supplied information is accepted.

### PartiallyAccepted

The supplied information is not completely accepted.

### Rejected

The supplied information is rejected.

## ComplaintResponseNumber

A unique identification number of the ComplaintResponse, generated by the issuer of the ComplaintResponse.




## ComplaintResponseReason

A group item containing the reason assessed by the supplier or sender parties for the



ComplaintResponse



### ComplaintResponseReasonType [attribute]

*ComplaintResponseReasonType is optional. A single instance might exist.*

The type of complaint reason.

Refer to ComplaintResponseReasonType definition for any enumerations.

## (sequence)

The sequence of items below is mandatory. A single instance is required.

### **ComplaintResponseReasonCode**

*ComplaintResponseReasonCode* is optional. A single instance might exist.

The reason for the complaint in code form. Agency provides the context.

### **ComplaintResponseReasonDescription**

*ComplaintResponseReasonDescription* is optional. Multiple instances might exist.

A text field element describing the reason for the ComplaintResponse

---

## **ComplaintResponseReasonCode**

The reason for the complaint in code form. Agency provides the context.

### **Agency [attribute]**

*Agency* is optional. A single instance might exist.

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.


Refer to Agency definition for any enumerations.



---

## **ComplaintResponseReasonDescription**

A text field element describing the reason for the ComplaintResponse



---

## **ComplaintResponseReasonType [attribute]**

The type of complaint reason.

*This item is restricted to the following list.*

**Commercial**

**Logistical**



**Technical**



---

## ComplaintResponseReference

A group item detailing relevant references pertaining to the



ComplaintResponse

### **ComplaintResponseReferenceType [attribute]**

*ComplaintResponseReferenceType is optional. A single instance might exist.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to ComplaintResponseReferenceType definition for any enumerations.

### **AssignedBy [attribute]**

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations


---

## ComplaintResponseReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an

existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.




## ComplaintResponseSpecification

A group item containing information necessary to identify the physical item.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



**Product**

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

**(sequence)**

*The sequence of items below is optional. Multiple instances might exist.*

**PurchaseOrderInformation**

*PurchaseOrderInformation is mandatory. A single instance is required.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

**PurchaseOrderLineItemNumber**

*PurchaseOrderLineItemNumber is mandatory. A single instance is required.*

The sequential number that uniquely identifies the PurchaseOrder line item.

**DeliveryMessageDate**

*DeliveryMessageDate is optional. A single instance might exist.*

The Date and Time when the DeliveryMessage was issued.

**DateTimeRange**

*DateTimeRange is optional. A single instance might exist.*

The delivery date and/or time range.

**Charge**

*Charge is optional. Multiple instances might exist.*

Charge is a group element that contains elements that describe a charge.

**AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## ComplaintResponseSummary

Summary information that applies to the entire ComplaintResponse e-Document.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### TotalNumberOfLineItems

*TotalNumberOfLineItems is optional. A single instance might exist.*

The total number of individual line items in the document, regardless of the status or type.

### TotalQuantity

*TotalQuantity is optional. A single instance might exist.*

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

### TotalInformationalQuantity

*TotalInformationalQuantity is optional. Multiple instances might exist.*

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

### TotalNetAmount

*TotalNetAmount is optional. A single instance might exist.*

A field containing total amount excluding tax. For example, in the Invoice TotalNetAmount is equal to the sum of LineItemSubTotal plus TotalAdjustments. TotalNetAmount encapsulates CurrencyValue.

### TotalInformationalAmount

*TotalInformationalAmount is optional. Multiple instances might exist.*


A monetary amount used for information purposes only (not for calculation). For example, the invoice price adjustment subtotal is expressed in sterling pounds, and the buyer wants this information expressed in U.S. dollars.

### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

### TermsAndDisclaimers




*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.

## ComplaintResponseType [attribute]

Indicates if the e-Document represents a Complaint by the sender or Feedback from the sender.



*This item is restricted to the following list.*

**Claim**

**Feedback**

## ComplaintSpecification


A group item containing information necessary to identify the physical item

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### Product

*Product is optional. A single instance might exist.*



Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.


**(sequence)**

*The sequence of items below is optional. Multiple instances might exist.*

### PurchaseOrderInformation

*PurchaseOrderInformation is mandatory. A single instance is required.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.



## PurchaseOrderLineItemNumber

*PurchaseOrderLineItemNumber is mandatory. A single instance is required.*

The sequential number that uniquely identifies the PurchaseOrder line item.

## ComplaintReference

*ComplaintReference is mandatory. One instance is required, multiple instances might exist.*

A group item detailing relevant references pertaining to the Complaint. ComplaintReference contains the attribute ComplaintReferenceType.

## DeliveryMessageDate

*DeliveryMessageDate is optional. A single instance might exist.*

The Date and Time when the DeliveryMessage was issued.

## DateTimeRange

*DateTimeRange is optional. A single instance might exist.*

The delivery date and/or time range.

## Charge

*Charge is optional. Multiple instances might exist.*

Charge is a group element that contains elements that describe a charge.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## ComplaintSummary

Summary information that applies to the entire complaint e-Document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### TotalNumberOfLineItems

*TotalNumberOfLineItems is optional. A single instance might exist.*

The total number of individual line items in the document, regardless of the status or type.


### TotalQuantity

*TotalQuantity is optional. A single instance might exist.*

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

ComplaintSummary

(sequence)



## TotalInformationalQuantity

*TotalInformationalQuantity is optional. Multiple instances might exist.*

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

## TotalNetAmount

*TotalNetAmount is optional. A single instance might exist.*

A field containing total amount excluding tax. For example, in the Invoice TotalNetAmount is equal to the sum of LineItemSubTotal plus TotalAdjustments. TotalNetAmount encapsulates CurrencyValue.

## TotalInformationalAmount

*TotalInformationalAmount is optional. Multiple instances might exist.*

A monetary amount used for information purposes only (not for calculation). For example, the invoice price adjustment subtotal is expressed in sterling pounds, and the buyer wants this information expressed in U.S. dollars.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## TermsAndDisclaimers

*TermsAndDisclaimers is optional. Multiple instances might exist.*


An element that contains legal information with an indication of what the Language is.

---

## ComplaintType [attribute]

Indicates if the e-Document represents a Complaint by the sender or Feedback from the sender.

*This item is restricted to the following list.*



### Claim

A "Claim" type is used when there is a customer reaction that includes a financial compensation.

### Feedback

A "Feedback" type is used when there is a customer reaction that doesn't include any financial compensation.


---

## ComponentDueDate

Date supplied component is expected to arrive

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



# papiNet V2R31

---

## Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

## Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.


---

## ComponentNeededDate

Date the supplied component is needed by the vendor in order to make the due date of the ordered product.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



## Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

## Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.


hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## ComponentShipDate

Date supplied component is expected to ship

### (sequence)

The sequence of items below is mandatory. A single instance is required.



### Date

Date is mandatory. A single instance is required.

A group element that contains the specification of Year, Month, and Day.

### Time

Time is optional. A single instance might exist.

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.


hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## CompositeAndVeneerWoodPanels

A grouping element that contains the timbler/lumber products that comprise composite and veneer wood panels.



The sequence of items below is mandatory. A single instance is required.

### (choice)

[choice] is optional because of choice construct.

### SoftwoodPlywood

SoftwoodPlywood is optional because of choice construct.

Characteristics of wood panelling products.

### WoodPanelProducts

WoodPanelProducts is optional because of choice construct.

Characteristics of wood panelling products.


## Packaging

*Packaging is optional. A single instance might exist.*

Type of a package that includes individual products.


## CompoundAgency [attribute]

The agency responsible for the compound coding.  
Defines the trade name of the treatment.



## CompoundType [attribute]

Defines the type of chemical treatment used.




## ConcernIndicatorType [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

**Yes**

**No**




## ConstructionPackagesAndPreFabPanels

A grouping element that contains the timber/lumber products that comprise construction packages and pre-fabricated panels.

### (sequence)

*The*



*sequence of items below is mandatory.  
A single instance is required.*

### (choice)

*[choice] is optional because of choice construct.*

#### Floor

*Floor is optional because of choice construct.*

Defines parts and complete flooring systems.

#### Wall

*Wall is optional because of choice construct.*

Defines parts and complete wall systems.

#### Roof

*Roof is optional because of choice construct.*

Defines parts and complete roofing systems.

## **Packaging**

*Packaging is optional. A single instance might exist.*

Type of a package that includes individual products.

---

## **ConsumptionProcess**

Identifies the process relevant to the situation being described.

<b>ConsumptionProcess</b>	
type	printType

*This item is restricted to the following list.*

### **ColdsetOffset**

An offset printing method suitable for newspapers, in other words, ink dries by penetration into the paper.

### **ContinuousForms**

An offset printing method, generally without a hot drying section and suitable for reels.

### **Digital**

An electrostatic printing method, typically a large black-and-white or multicolour printer/copier.

### **Flexography**

A special printing method, which is a follow-up of letter print with advanced print cylinder surface. Suitable for sheets.

### **FoilPrint**

A special printing/finishing method suitable for foils through embossed print plate/cylinder; flat/flat, or circle/flat (form to sheet).

### **Forms**

An offset printing method, generally without a hot drying section and suitable for sheets.

### **Gravure**

A standard printing method with embossed print cylinders. Suitable for sheets.

### **HeatsetOffset**

An offset printing method.

### **InkJet**

An inkjet printing method, typically a large black-and-white or multicolour printer.

### **InstantOffset**

A standard flat printing method (for example, wet offset, or waterless offset) suitable for small print orders and small sheet sizes (for example, max. DIN A3).

### **Laser**

A laser-based printing method, typically a large black-and-white or multicolour printer/copier.

## Letterpress

A special printing method suitable for books or newspapers (old style) with advanced letters. Suitable for sheets.

## LightPrint

- A printing method similar to a facsimile print, a photo-like print with a specific prepared cylinder surface on photo basis or an artificial print.

## MiniWeb

A digital printing method suitable for reels less than 20 inch wide.

## RotoFlexography

## RotoGravure

## RotoLetterpress

## RotoSilkScreen

## SheetfedOffset

## SilkScreen

## WebOffset

---

## ContactIdentifier


The identifier for the contact.

### ContactIdentifierType [attribute]

*ContactIdentifierType is mandatory.  
A single instance is required.*

Indicates which particular identifier is being communicated.

Refer to ContactIdentifierType definition for any enumerations.



---

## ContactIdentifierType [attribute]

Indicates which particular identifier is being communicated.

*This item is restricted to the following list.*

### DriverLicenseID


### PassportID

### PersonalID

### Other

### PasportID

To be deprecated. Use PassportID. This enumeration had a spelling error.



## ContactName

The name of the individual associated with the ContactType.

ContactName
type s60

---

## ContactType [attribute]

Identifies the role of the contact within the party.

*This item is restricted to the following list.*

attribute
ContactType
type contactType

### AccountManager

The person who manages the account for the seller or service provider.

### Carrier

This contact person identified in the transaction works for a carrier.

### CrossDock

This contact person identified in the transaction works at a cross-docking terminal/warehouse.

### CustomerService

This contact person identified in the transaction works for the customer service department of the supplying company.

### ForestForwarder

The contact responsible for transporting forest wood products from logging areas to roadside landings.

### ForestHarvester

The contact responsible for harvesting of forest wood products.

### Forwarder

The contact for freight forwarding.

### HelpDesk

The contact within the trading partner arrangement who services information related requests.

### Measurer

The contact that is doing the measurements.

### Merchant

This contact person identified in the transaction works for a merchant.

### Mill

The paper or pulp mill involved in the transaction.

### OriginalSupplier

The contact for the first supplier in a supply chain.

### Plant

This contact person identified in the transaction works at the plant.

---

## Purchaser

This contact person identified in the transaction works for the entity that is requesting the product.

## RemitTo

This contact person identified in the transaction works for the entity to which payment is to be made.

## SalesOffice

This contact person identified in the transaction works for a sales office.

## Supervisor

A contact that direct or oversee performance or operation.

## Supplier

The contact for the organisation or business entity responsible for providing the product.

## TransportPlanner

The person responsible for planning the transports.

## TransportVehicle

Contact information for the transport vehicle involved in the transaction.

## Warehouse

This contact person identified in the transaction works at a warehouse.

## Other

This contact person identified in the transaction works for someone other than the entity types defined in the attribute list.


---

## ConversionCode

A code, as assigned by an Agency, used to identify a group of conversion characteristics.

### Agency [attribute]

*Agency is mandatory. A single instance is required.*



Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.


For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

---

## CoordinateFormatType [attribute]

CoordinateFormatType defines the format of the string containing the co-ordinates.



*This item is restricted to the following list.*

### Degrees

Latitude and Longitude given in decimal degrees according to ISO Standard 6709. Format:  $\pm DD.DDDD\pm DDD.DDDD$

More info at [http://www.iso.org/iso/iso\\_catalogue.htm](http://www.iso.org/iso/iso_catalogue.htm)

### DegreesMinutes

Latitude and Longitude given in degrees and decimal minutes according to ISO Standard 6709. Format:  $\pm DDMM.MMM\pm DDDMM.MMM$

More info at [http://www.iso.org/iso/iso\\_catalogue.htm](http://www.iso.org/iso/iso_catalogue.htm)

### DegreesMinutesSeconds

Latitude and Longitude given in degrees, minutes and decimal seconds according to ISO Standard 6709. Format:  $\pm DDMMSS.SS\pm DDDMMSS.SS$

More info at [http://www.iso.org/iso/iso\\_catalogue.htm](http://www.iso.org/iso/iso_catalogue.htm)

### XY

X- and Y- co-ordinate separated by the space-character.

### ZoneXY


Zone, X- and Y- co-ordinate separated by space-characters.

---

## Coordinates

Contains the position co-ordinates of a location.

### CoordinateFormatType [attribute]



*CoordinateFormatType is mandatory.  
A single instance is required.*

CoordinateFormatType defines the format of the string containing the co-ordinates.

Refer to CoordinateFormatType definition for any enumerations.

## CoreCharacteristics

A group item that details information used to fully define a core.

### CoreEndType [attribute]

*CoreEndType is optional. A single instance might exist.*

Describes how the core ends are made.

Refer to CoreEndType definition for any enumerations.

### CoreMaterialType [attribute]

*CoreMaterialType is optional. A single instance might exist.*

Specifies the material out of which the core is made.

Refer to CoreMaterialType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### CoreCode

*CoreCode is optional. A single instance might exist.*

A code defining details for a core

#### CoreDiameterInside

*CoreDiameterInside is optional. A single instance might exist.*

The diameter of the core's inner circle.

#### CoreDiameterOutside


*CoreDiameterOutside is optional. A single instance might exist.*

The diameter of the core's outer circle.

#### CoreStrengthCode

*CoreStrengthCode is optional. A single instance might exist.*

CoreStrengthCode is a composite of critical speed, flexural and crush strength of a fibre core, as defined by the indicated Agency.




## CoreCode

A code defining details for a core

### Agency [attribute]

*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.



For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

---

## CoreDiameterInside

The diameter of the core's inner circle.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



---

## CoreDiameterOutside

The diameter of the core's outer circle.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the




parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## CoreEndType [attribute]

Describes how the core ends are made.

*This item is restricted to the following list.*



### **Adaptor**

The Adaptor type is where the end type is adaptable to a 6 inch or 3 inch core diameter. (Spelling validated with core manufacturers.)

### **Bevelled**

The core end is beveled. A grinding wheel has been used to grind down the inside of the core right at the end to enable an easier mounting of the core onto the shaft or the chucks. This is also called a beveled end cut. (Improper spelling noted but will be retained as enumeration choice for backward compatibility.)

### **Bridge**

The core end has a notch that is cut on the inside of the core that is tapered and does not go through the core to edge; this is done so the core can be grasped by a particular type of core chuck on a reel arm on a press. Similar to a tapered core.

### **HalfMetal**

The core is half metal.

### **Notched**

The core end has a notch. Notch can be used to drive the core by the press operator or by manufacturing.

### **NotchedFullMetal**

The core end has a notch. Core end is reinforced with metal cap.

### **Plain**

The core end is smooth, not notched.

### **PlainFullMetal**

The core end has no notch; end is reinforced with a metal tip.

### **Tapered**


The core end is tapered.

---

## CoreMaterialType [attribute]

Specifies the material out of which the core is made.

*This item is restricted to the following list.*



### **Aluminium**

The reel core is made of aluminium.

## Composite

The reel core is made up of a composite of materials, not entirely of fibre content.

## Fibre

The reel core is made of fibre.

## Iron

The reel core is made of iron.

## Paper

The reel core is made of paper.

## Plastic

The reel core is made of plastic.


## Steel

The reel core is made of steel.

---

## CorePlugs

An element that indicates if plugs are to be inserted into the ends of the core. Core plugs can be made of various materials and are used to protect the core ends.




Note: A conversion error took place between Version 1.0 of papiNet and Version 2.0 of papiNet and this item was inadvertently converted from true/false (1.0) to nni1 (2.0). This item has been reinstated to a boolean value. However, please note that for reasons of backward compatibility it is highly recommended that you use the 1/0 approach to communicating true or false where 1 = true and 0 = false. Our apologies for any issues.

---

## CoreStrengthCode

CoreStrengthCode is a composite of critical speed, flexural and crush strength of a fibre core, as defined by the indicated Agency.



### Agency [attribute]

*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.


For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

## CorrectiveAction

This element enables the party issuing the ComplaintResponse (i.e. SupplierParty) to specify what is the corrective action they will take in order to close the Complaint (send a credit, send disposition instructions, etc.)




## CostComponent

A group item that contains information relevant to the freight cost codes.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### CostComponentCode

*CostComponentCode is optional. A single instance might exist.*

An element that communicates a code for the cost component.

For specification of logistics services it is recommended to use UN/ECE as the agency for the cost component code. Currently UN/ECE codes are freight cost codes established according to the UN Freight Cost Code Recommendation N°. 23, which can be found at [www.unece.org/cefact/recommendations/rec\\_index.htm](http://www.unece.org/cefact/recommendations/rec_index.htm). The current version (at the time of this publication) can be found at [www.unece.org/cefact/recommendations/rec23fcc\\_rev1\\_030623.pdf](http://www.unece.org/cefact/recommendations/rec23fcc_rev1_030623.pdf).

It is anticipated that additional UN/ECE cost component codes will be added as they become available.

### CostComponentDescription

*CostComponentDescription is mandatory. A single instance is required.*


The description of the cost component.

## CostComponentCode

An element that communicates a code for the cost component.

For specification of logistics services it is recommended to use UN/ECE as the agency for

the cost component code. Currently UN/ECE codes are freight cost codes established according to the UN Freight Cost Code Recommendation N°. 23, which can be found at [www.unece.org/cefact/recommendations/rec\\_index.htm](http://www.unece.org/cefact/recommendations/rec_index.htm). The current version (at the time of this publication) can be found at [www.unece.org/cefact/recommendations/rec23fcc\\_rev1\\_030623.pdf](http://www.unece.org/cefact/recommendations/rec23fcc_rev1_030623.pdf).



It is anticipated that additional UN/ECE cost component codes will be added as they become available.

## Agency [attribute]

*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.


---

## CostComponentDescription

The description of the cost component.

### Language [attribute]

*Language is optional. A single instance might exist.*




XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

---

## Country

The name of the country associated with the address elements. To ensure reliable matching of addresses, it is suggested to use the attribute **ISOCountryCode** as well.



### ISOCountryCode [attribute]

*ISOCountryCode is optional. A single instance might exist.*

The valid list of ISO Country Codes.

Refer to ISOCountryCode definition for any enumerations.


---

## CountryOfConsumption

The country of consumption for the material.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Country

*Country is mandatory. A single instance is required.*

---

# papiNet V2R31

---

The name of the country associated with the address elements. To ensure reliable matching of addresses, it is suggested to use the attribute ISOCountryCode as well.


---

## CountryOfDestination

The country where the goods will be, or were, shipped to.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



**Country**

*Country is mandatory. A single instance is required.*

The name of the country associated with the address elements. To ensure reliable matching of addresses, it is suggested to use the attribute ISOCountryCode as well.


---

## CountryOfOrigin

The country of origin for the material.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



**Country**


*Country is mandatory. A single instance is required.*

The name of the country associated with the address elements. To ensure reliable matching of addresses, it is suggested to use the attribute ISOCountryCode as well.

---

## County


The name of the county that the address is in.



## CreditDebitNote

The CreditDebitNote element is the root element for the CreditDebitNote e-Document.

The CreditDebitNote e-Document is generally used by the SupplierParty to compensate or charge the trading parties (ShipToParty, BuyerParty, OtherParty, etc.) for matters outside the scope of the Invoice.



### CreditDebitNoteType [attribute]

*CreditDebitNoteType is mandatory. A single instance is required.*

Defines the type of the CreditDebitNote e-Document. There are two types of CreditDebitNote Messages:

Refer to CreditDebitNoteType definition for any enumerations.

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### CreditDebitNoteHeader

*CreditDebitNoteHeader is mandatory. A single instance is required.*

The CreditDebitNoteHeader contains information common to the CreditDebitNote

#### CreditDebitNoteLineItem

*CreditDebitNoteLineItem is mandatory. One instance is required, multiple instances might exist.*

CreditDebitLineItem contains the information about the Credit or Debit being issued.

#### MonetaryAdjustment

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount.

# papiNet V2R31

MonetaryAdjustment contains an attribute that indicates the type of adjustment being communicated.

## CreditDebitNoteSummary


*CreditDebitNoteSummary is mandatory. A single instance is required.*

Contains summary information that applies to the entire e-Document.

---

## CreditDebitNoteAmountSubtotal

A field that contains the result of the calculation Quantity at the



CreditDebitNoteLineItem level times the PricePerUnit.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### CurrencyValue


*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

---

## CreditDebitNoteBaseAmountInformation

A group item containing the price per unit and the CreditDebitNote amount subtotal.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PriceDetails

*PriceDetails is optional. A single instance might exist.*

An element that groups together price information.

#### CreditDebitNoteAmountSubtotal


*CreditDebitNoteAmountSubtotal is optional. A single instance might exist.*

A field that contains the result of the calculation Quantity at the CreditDebitNoteLineItem level times the PricePerUnit.

---

## CreditDebitNoteDate

The issue date of the CreditDebitNote. This date often drives payment terms. Note that this date is not necessarily the same as the creation date of the CreditDebitNote.



### (sequence)

# papiNet V2R31

---

*The sequence of items below is mandatory. A single instance is required.*

## **Date**

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

## **Time**

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## CreditDebitNoteHeader

The CreditDebitNoteHeader contains information common to the CreditDebitNote

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### CreditDebitNoteNumber

*CreditDebitNoteNumber is mandatory. A single instance is required.*

The unique CreditDebitNote identifier as agreed to by the trading partners.

#### CreditDebitNoteDate

*CreditDebitNoteDate is mandatory. A single instance is required.*

The issue date of the CreditDebitNote. This date often drives payment terms. Note that this date is not necessarily the same as the creation date of the CreditDebitNote.



#### CreditDebitNoteReference

*CreditDebitNoteReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the CreditDebitNote. CreditDebitNoteReference uses the CreditDebitNoteReferenceType attribute.

#### CreditDebitNoteReason

*CreditDebitNoteReason is mandatory. A single instance is required.*

A group item containing the reason for the entire CreditDebitNote.

#### BillToParty

*BillToParty is mandatory. A single instance is required.*

The address where the Invoice is to be sent.

#### SupplierParty


*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

#### BuyerParty

*BuyerParty is optional. A single instance might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.



## **RemitToParty**

*RemitToParty is optional. A single instance might exist.*

A group item containing details of the party to whom payment will be made. The RemitToParty contains all information related to remittance.

## **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **CountryOfOrigin**

*CountryOfOrigin is optional. A single instance might exist.*

The country of origin for the material.

## **CountryOfDestination**

*CountryOfDestination is optional. A single instance might exist.*

The country where the goods will be, or were, shipped to.

## **CountryOfConsumption**

*CountryOfConsumption is optional. A single instance might exist.*

The country of consumption for the material.

## **AdditionalText**


*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## CreditDebitNoteLineAmount

The total CreditDebitNote amount per line (includes adjustments and tax)

**(sequence)**



*The sequence of items below is mandatory. A single instance is required.*

### CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

## CreditDebitNoteLineItem

CreditDebitLineItem contains the information about the Credit or Debit being issued.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### CreditDebitNoteLineItemNumber

CreditDebitNoteLineItemNumber is mandatory. A single instance is required.

A sequential number that uniquely identifies the CreditDebitNote line item.

### (sequence)

The sequence of items below is optional. Multiple instances might exist.

#### PurchaseOrderInformation

PurchaseOrderInformation is mandatory. A single instance is required.

A group item containing information unique to this PurchaseOrder, which is provided by the buyer.

PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

#### PurchaseOrderLineItemNumber

PurchaseOrderLineItemNumber is optional. Multiple instances might exist.

The sequential number that uniquely identifies the PurchaseOrder line item.

#### ChargeOrAllowance

ChargeOrAllowance is optional. A single instance might exist.

The description of the charge or allowance; such as freight, special handling, and stop-off handling.


#### Product

Product is optional. A single instance might exist.

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

#### Quantity

Quantity is optional. A single instance might exist.



The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **CreditDebitNoteBaseAmountInformation**

*CreditDebitNoteBaseAmountInformation is optional. A single instance might exist.*

A group item containing the price per unit and the CreditDebitNote amount subtotal.

## **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates the type of adjustment being communicated.

## **CreditDebitNoteLineAmount**

*CreditDebitNoteLineAmount is mandatory. A single instance is required.*

The total CreditDebitNote amount per line (includes adjustments and tax)

## **CreditDebitNoteReference**

*CreditDebitNoteReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the CreditDebitNote. CreditDebitNoteReference uses the CreditDebitNoteReferenceType attribute.

## **DeliveryDateWindow**

*DeliveryDateWindow is optional. A single instance might exist.*

A group item defining the date/time interval for delivery to take place. An element which may contain the estimated date for which delivery is expected. This date is not absolute.

## **GeneralLedgerAccount**

*GeneralLedgerAccount is optional. A single instance might exist.*

The general ledger account to be referenced for the item.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

## **MillCharacteristics**

*MillCharacteristics is optional. A single instance might exist.*

A group item defining the mill party and machine identifier where a product is or was produced.

## **ItemInformation**

*ItemInformation is optional. Multiple instances might exist.*

The purpose of the ItemInformation structure is to clearly identify physical items. The attribute ItemType defines the type of physical item. Physical items can be handling units like packages as well as items contained in packages.

## **TransportModeCharacteristics**

*TransportModeCharacteristics is optional. A single instance might exist.*

A group item defining the primary mode of transport.

## **CountryOfOrigin**

*CountryOfOrigin is optional. A single instance might exist.*

The country of origin for the material.

## **CountryOfDestination**

*CountryOfDestination is optional. A single instance might exist.*

The country where the goods will be, or were, shipped to.

## **CountryOfConsumption**

*CountryOfConsumption is optional. A single instance might exist.*

The country of consumption for the material.

## **LocationParty**

*LocationParty is optional. Multiple instances might exist.*

The organization or business entity where the business event took place or will take place.

## **TaxStatement**

*TaxStatement is optional. A single instance might exist.*

A group element for declaration of exception from normal charges of tax and the reason for tax exemption.

## **SafetyAndEnvironmentalInformation**


*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the

indicated agency).

### CreditDebitNoteLineItemNumber

A sequential number that uniquely identifies the CreditDebitNote line item.



### CreditDebitNoteNumber

The unique CreditDebitNote identifier as agreed to by the trading partners.




### CreditDebitNoteReason

A group item containing the reason for the entire CreditDebitNote.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



#### CreditDebitNoteReasonCode

*CreditDebitNoteReasonCode is mandatory. A single instance is required.*

A selection of one of the valid reasons for creating a CreditDebitNote.


#### ReasonDescription

*ReasonDescription is optional. A single instance might exist.*

Text associated with a particular ReasonIdentifier

### CreditDebitNoteReasonCode

A selection of one of the valid reasons for creating a CreditDebitNote.



### CreditDebitNoteReasonType [attribute]

*CreditDebitNoteReasonType is mandatory. A single instance is required.*

Describes the type of reasons associated with the CreditDebitNote.

Refer to CreditDebitNoteReasonType definition for any enumerations.

### Agency [attribute]

*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

---

## CreditDebitNoteReasonType [attribute]

Describes the type of reasons associated with the CreditDebitNote.


*This item is restricted to the following list.*

**Claim**

**Commission**

**InvoiceError**



**Rebate**



---

## CreditDebitNoteReference

An element detailing relevant references pertaining to the CreditDebitNote.



CreditDebitNoteReference uses the CreditDebitNoteReferenceType attribute.

### CreditDebitNoteReferenceType [attribute]

*CreditDebitNoteReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to CreditDebitNoteReferenceType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a

reference of type OrderNumber.

Refer to AssignedBy for any enumerations.


---

## CreditDebitNoteReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an

existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.



## CreditDebitNoteSummary

Contains summary information that applies to the entire e-Document.

**(sequence)**

The sequence of items below is mandatory. A single instance is required.


**TotalNumberOfLineItems**

TotalNumberOfLineItems is optional. A single instance might exist.

The total number of individual line items in the document, regardless of the status or type.

**(sequence)**

The sequence of items below is optional. Multiple instances might exist.



**TotalQuantity**

TotalQuantity is mandatory. A single instance is required.

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

**TotalInformationalQuantity**

TotalInformationalQuantity is optional. Multiple instances might exist.

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

**LineItemSubTotal**

LineItemSubTotal is optional. A single instance might exist.

The total amount of all e-Document LineBaseAmount(s) line items without any monetary adjustments that may occur after the e-Document line items.

**TotalAdjustments**


TotalAdjustments is optional. A single instance might exist.

The CurrencyValue of TotalAdjustments contains the total of all MonetaryAdjustmentAmount for all instances of PriceAdjustment and FlatAmountAdjustment in the document (it excludes TaxAdjustments).

**TotalTaxAmount**

TotalTaxAmount is optional. A single instance might exist.

The CurrencyValue of TotalTaxAmount contains the sum of all instances of



TaxAdjustment in the document. TotalTaxAmount contains the sum of all instances of the MonetaryAdjustmentAmount for tax adjustments.

## **TotalNetAmount**

*TotalNetAmount is optional. A single instance might exist.*

A field containing total amount excluding tax. For example, in the Invoice TotalNetAmount is equal to the sum of LineItemSubTotal plus TotalAdjustments. TotalNetAmount encapsulates CurrencyValue.

## **TotalAmount**

*TotalAmount is mandatory. A single instance is required.*

A field containing the total amount including tax.

PurchaseOrder: The total amount, using a valid unit of measure of all the items in the e-Document. Multiple total amounts are allowed so different units of measure or grade sub-totals can be communicated.

CreditDebitNote and Invoice: TotalAmount is equal to TotalNetAmount plus TotalTaxAmount. In certain countries this is the amount that is due for payment based upon the terms of payment.

## **InformationalAmount**

*InformationalAmount is optional. Multiple instances might exist.*

A monetary amount used for information purposes only (not for calculation). For example, the invoice price adjustment subtotal is expressed in sterling pounds, and the buyer wants this information expressed in U.S. dollars.

CreditDebitNote and Invoice - The TaxAmount is displayed in the currency that is applicable throughout the e-Document. When a TaxAmount needs to be displayed in a different national currency, this field is used.

## **(sequence)**

*The sequence of items below is optional. Multiple instances might exist.*

### **TermsOfPayment**

*TermsOfPayment is mandatory. A single instance is required.*

A group item that contains agreed-to terms defining when, how, and under what conditions the payment is to be made.

When TermsOfPayment is optional; if omitted, TermsOfPayment is controlled through previous negotiation.

### **TotalNetOfTermsDiscount**

*TotalNetOfTermsDiscount is optional. A single instance might exist.*

The components of the amount to be paid if prompt payment discount terms are met, including the amount that is subject to the payment terms discount, the discount amount, and the amount due after prompt payment discount.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **TermsAndDisclaimers**

*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language

is.

## TaxStatement

*TaxStatement is optional. A single instance might exist.*

A group element for declaration of exception from normal charges of tax and the reason for tax exemption.

---

## CreditDebitNoteType [attribute]

Defines the type of the CreditDebitNote e-Document. There are two types of CreditDebitNote Messages:



*This item is restricted to the following list.*

### CreditNote

Credits that are provided for amount reductions and complaints. A CreditNode will normally have a reference to an earlier issued Invoice.

### DebitNote

A DebitNote claims payment for additional charges. A DebitNote normally has a reference to an earlier issued Invoice.

---

## CurrencyFromType [attribute]

The from currency in an exchange.

A three-character ISO 4217 currency code in capital letters. The ISO standard classification for currencies.



---

## CurrencyType [attribute]

A three-character ISO 4217 currency code in capital letters. The ISO standard classification for currencies.

A three-character ISO 4217 currency code in capital letters. The ISO standard classification for currencies. Refer to the ISO standard for information about the choices for the attribute's enumerations.




---

## CurrencyValue

The amount in the referenced currency as defined by the CurrencyType attribute.

### CurrencyType [attribute]

*CurrencyType is mandatory. A single instance is required.*



A three-character ISO 4217 currency code in capital letters. The ISO standard classification for currencies.

Refer to CurrencyType definition for any enumerations.

## CustomerMarks


The text that the buyer wants the seller to print on the package label or elsewhere.

### CustomerMarksType [attribute]

*CustomerMarksType is optional.*

Specifies the content type of customer marks

Refer to CustomerMarksType definition for any enumerations.



### AssignedBy [attribute]

*AssignedBy is optional.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy definition for any enumerations.

## CustomerMarksType [attribute]

Specifies the content type of customer marks.

*This item is restricted to the following list.*

### Author

Name of the author of the product or book

### BasisWeight

The weight of the paper expressed as a mass for a given surface area.

### BoxWeight

Weight of the filled box.

### BrandName

A specific product brand name for which the owner or source is specified in the "@AssignedBy" attribute

### Copyright

The year of publication copyright.

### Edition

Identifies the version of the product for which copies were printed and published at one time; For example in book manufacturing values might be 1st, 2nd, etc

### ExportShipMark

An export shipment mark for identification.

### GradeCode

A specific product code for which the owner or source is specified in the "@AssignedBy" attribute



**GradeName**

A specific product name for which the owner or source is specified in the "@AssignedBy" attribute (for example, ImprovedNewsprint-45-1479)

**Identifier**

Identifier of the individual item.

**ISBN10**

10 digit ISBN code without dashes.

**ISBN10Dash**

10 digit ISBN code with dashes.

**ISBN13**

13 digit ISBN code.

**ISBN13Dash**

A 13 character ISBN with dashes.

**LotIdentifier**

A unique code used to identify a grouping of product with one set of quality statistics common to all members of that group. Synonym: Lot Number.

**PartNumber**

An equivalent to the Stock Keeping Unit (SKU) for which the owner or source is specified in the "@AssignedBy" attribute. In other words, this code fully defines the product.

**PrintingNumber**

A reference to the sequential print run number.

**ProfitCenter**

Profit Center identifier.

**PubName**

The publication name.

**PurchaseOrderNumber**

The unique order identifier as designated by the customer.

**ReferenceNumber**

An informational reference (either textual or numeric) for which the owner or source is specified in the "@AssignedBy" attribute.

**RetailPrice**

Cover price of the finished product.

**TambourID**

The unique identifier of the jumbo reel (also called mother reel or Tambour).

**Title**

Proper title of a book product.

**TitleAlias**

Alternate title description for book products, usually for security purposes.

## UnitsPerCarton

Number of units per box.

## UniversalProductIdentifier

Unique identifier for the book, component of a book product, and many other products.

---

## CustomsParty

The party responsible for customs arrangements.

### LogisticsRole [attribute]

*LogisticsRole is optional. A single instance might exist.*

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PartyIdentifier

*PartyIdentifier is optional. Multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

#### NameAddress

*NameAddress is mandatory. A single instance is required.*

A group item containing name and address of an organisation or business entity.

#### URL


*URL is optional. A single instance might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

#### CommonContact

*CommonContact is optional. Multiple instances might exist.*

Identifies a specific individual associated with the party.






in discord with other users of XML.

## CustomsStampHeaderText

Text to be applied prior to the customs stamp.



## CustomsStampInformation

A grouping element that organises the information for customs.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### CustomsStampHeaderText

*CustomsStampHeaderText is optional. Multiple instances might exist.*

Text to be applied prior to the customs stamp.

### CustomsParty

*CustomsParty is optional. A single instance might exist.*

The party responsible for customs arrangements.

### CustomsStampDate

*CustomsStampDate is optional. A single instance might exist.*

The date of the customs stamp.

### CustomsReferenceNumber

*CustomsReferenceNumber is optional. A single instance might exist.*

A reference that applies to customs arrangements.

### SupplierCustomsReference

*SupplierCustomsReference is optional. A single instance might exist.*

Supplier Customs Reference

### MillParty



*MillParty is optional. A single instance might exist.*

The organisation or business entity that actually produces the product.

### CustomsStampTrailerText


*CustomsStampTrailerText is optional. Multiple instances might exist.*

Text to be applied after the customs stamp.



## CustomsStampTrailerText

Text to be applied after the customs stamp.



## CustomsTariffCode

The tariff code for customs purposes.



## CustomsTotals

A grouping element for customs total information.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### CustomsTariffCode

*CustomsTariffCode is mandatory. A single instance is required.*

The tariff code for customs purposes.

### TotalQuantity


*TotalQuantity is mandatory. A single instance is required.*

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

### InformationalQuantity

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.



## CuttingDetails


Cutting Details provides information on how to cut the sheet.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### CuttingTemplateCode

*CuttingTemplateCode is optional. A single instance might exist.*



Cutting Template Code contains the reference to previously defined instructions on how to cut the sheet.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



---

## **CuttingTemplateCode**

Cutting Template Code contains the reference to previously defined instructions on how to cut the sheet.

### **AssignedBy [attribute]**

*AssignedBy is optional. A single instance might exist.*



Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber. Refer to AssignedBy definition for any enumerations.

Refer to AssignedBy definition for any enumerations.

### **Agency [attribute]**

*Agency is optional. A single instance might exist.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

## Cyan

The Cyan component of a colour in the CMYK approach to colour definition.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).



#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

#### SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

#### TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

#### TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.


---

## Date

A group element that contains the specification of Year, Month, and Day.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Year

*Year is mandatory. A single instance is required.*

Identifies the year number when communicating a Calendar date.

### Month

*Month is mandatory. A single instance is required.*

Identifies the month number when communicating a Calendar date.

### Day


*Day is mandatory. A single instance is required.*

Identifies the day of the month when communicating a Calendar date. Day is an integer between 1 and 31.

---

## DateFinished

The Date and optionally the Time that an item was finished. For example, this could be the wrapping date for a reel or ream or the date the sheet(s) were packaged in preparation for shipment



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.


hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be

in discord with other users of XML.

---

## DateMade

The Date and optionally the Time when an item was produced. DateMade is normally a date before the wrapping and labelling date of the item.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

#### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.


---

## DateSheeted

The Date and optionally the Time that the paper was sheeted.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



#### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

#### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss,

# papiNet V2R31

hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.


---

## DateTimeFrom

The start or beginning Date and Time of a date range.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.


---

## DateTimeRange

The delivery date and/or time range.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### DateTimeFrom

# papiNet V2R31

---

*DateTimeFrom is mandatory. A single instance is required.*

The start or beginning Date and Time of a date range.

## **DateTimeTo**

*DateTimeTo is mandatory. A single instance is required.*

The ending Date and Time of a date/time range.


---

## **DateTimeTo**

The ending Date and Time of a date/time range.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### **Date**

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### **Time**

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

---

## **DateTimeValue**

A Date and Time value in the standard W3C xs:dateTime format.



## **DateType [attribute]**


Provides a context for the other date used in the document.

*This item is restricted to the following list.*

### **ActualArrivalDate**

The date the product arrived at the delivery destination.

---



**ActualDepartureDate**

The date the product departed the delivery origin.

**AvailableToShipDate**

The date the product needs to be available to ship.

**BoundBookDate**

Date the book is to be bound

**CancelAfterDate**

An action defined by the context is to be cancelled after the specified date.

**ComponentDueDate**

The date the component is due at the manufacturing or assembly location.

**ComponentShipDate**

The date the component has shipped or should ship.

**ConsumptionDate**

The date the item was or should be consumed.

**DateOfLastChange**

The last date that changes are permitted.

**DateOfTrading**

A date or date range when the supply of goods or services were made or completed. Normally this is the date of delivery but it can be other dates depending on terms of delivery; for example, despatch date.

**DeliveryDate**

The date the product is to be delivered.

**DeliveryPriorToDate**

The delivery must take place prior to this date.

**DeliveryRequestedDate**

The date on which the buyer requests goods to be delivered. Delivery will happen at this date on a "best endeavours" basis.

**DespatchDate**

The date the product is to be despatched.

**DoNotDeliverAfterDate**

The delivery must not take place after the date specified.

**DoNotShipAfterDate**

The shipment must not take place after the date specified.

**DrawDate**

The date removed from stock.

**EarliestDate****EndCallOffDate**

The date that call offs should end.

**EndOfDeliveryMonth**

The end of the month that delivery has taken place.

**EndOfDespatchMonth**

The end of the month that despatch has taken place.

**EndOfInvoiceMonth**

The end of the month that Invoice has taken place.

**EstimatedTimeOfArrival**

The date and time that the shipment is expected to arrive.

**EstimatedTimeOfDeparture**

The date and time that the shipment is expected to leave.

**ExMillDate**

Goods are ready at the mill.

**ForestForwardingDate**

The date when transporting of forest wood products take place from logging areas to roadside landings.

**InvoiceDate**

A date that is qualifying the invoicing period. This date often drives payment terms. Note that this date is not necessarily the same as the issue date of the Invoice.

**LastChangeDate**

The most recent date the document was changed.

**LoadingDate**

The date when the goods are loaded on a transport unit.

**MeasuringDate**

The date when measuring is performed.

**OnPressDate**

Date printing will commence.

**OnSalesDate**

Publicised sales date

**OrderConfirmationDate**

The date that OrderConfirmation took place.

**OrderFirmedDate**

The date that the order will be consider firm unless additional information is received.

**PickUpDate**

Use to notify the collector when to retrieve the load.

**PlannedShipDate**

The anticipated date of shipment.

**PrepDate**

Specifies the date applied to the preparation process.

**PrintDate**

The date on which a job is planned to go on the press to be printed. The ordered product needs to be available before this date.

**ProductionDate**

The date the product is produced.

**ProofDueBackDate**

Date the return of the proof is due back or the review process is to be completed.

**ProofOutDate**

Date the proof is mailed or made available to the buyer for review.

**PublicationDate**

Date the book will be published.

**PurchaseOrderDate**

The date when the PurchaseOrder was issued.

**ReferencePeriod**

A period of time covered by the object, e.g. an e-Document.

**RequiredByDate**

The date by which the activity must be completed. In the context of a PurchaseOrder this date refers to the date by which the material must be at the buyer's location of use.

**ShipEvenlyThroughout**

Distribute shipment of product in relatively even shipments throughout the date range indicated

**ShipmentPriorToDate**

The shipment (despatch) must take place prior to this date—in other words, the goods have to leave the terminal.

**ShipmentRequestedDate**

The date shipment is requested.

**SpecificationVersionDate**

Date of version of a specification

**StartCallOffDate**

The date on which the first CallOff can be placed.

**TheWeekBeginning**

The delivery is to be made at the beginning of the week that is mentioned in the Date construct.

**TheWeekEnding**

The delivery is to be made at the end of the week that is mentioned in the

Date construct.

## WarehouseDate

Depending on the e-Document context this can communicate the date that items are due in the warehouse or have been placed in the warehouse. For example:

Date books are due in the publisher's warehouse

Date reels were unloaded and put into the warehouse


## Other

Any other type of date that is not contained in the attribute list.

---

## DateWound

The Date and optionally the Time that a reel was wound or produced from its parent. RewoundIndicator indicates if the reel has been rewind.



### RewoundIndicator [attribute]

*RewoundIndicator is mandatory. A single instance is required.*

Is the date being communicated the the rewind date (Yes) or the date of original winding (No)?

Refer to RewoundIndicator definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

#### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

---

## Day

Identifies the day of the month when communicating a Calendar date. Day is an integer between 1 and 31.

<b>Day</b>
type   dayType

---

## Days

The qualifier of DeliveryTransitTime. More generally used to communicate duration in days.

<b>Days</b>
type   nni3

---

## Debarked [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

**Yes**


**No**

attribute
<b>Debarked</b>
type   yesNo

---

## DeckAndPorchFlooringMaterials-NaturalWood

Deck and porch flooring materials that are used in natural wood



products.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### **DeckAndPorchFlooringMaterials-NaturalWoodCharacteristics**

*DeckAndPorchFlooringMaterials-NaturalWoodCharacteristics is mandatory. A single instance is required.*

Natural wood characteristics of deck and porch flooring materials.

#### **Packaging**

*Packaging is optional. A single instance might exist.*

Type of a package that includes individual products.

## DeckAndPorchFlooringMaterials-NaturalWoodCharacteristics

Natural wood characteristics of deck and porch flooring materials.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**LumberSpecies**

*LumberSpecies is mandatory. One instance is required, multiple instances might exist.*

Specifies the raw material species.

**LumberGrade**

*LumberGrade is mandatory. A single instance is required.*

Defines quality characteristics achieved by selecting pieces based on a grading rule.

**Length**

*Length is optional.*

The length of the object.

**Width**

*Width is optional.*

The width of the object.

**Thickness**

*Thickness is optional.*

Physical dimension of a product.

**Seasoning**

*Seasoning is optional. A single instance might exist.*

Describes drying/ moisture control method.

**MoistureContent**

*MoistureContent is optional. A single instance might exist.*

Defines the moisture content percentage of the product.

**HeatTreatment**

*HeatTreatment is optional. A single instance might exist.*

Defines the heat treatment method.

**ManufacturingProcess**

*ManufacturingProcess is optional. Multiple instances might exist.*

Defines the different machining and processes made for the product.

**PatternProfile**

*PatternProfile is optional. A single instance might exist.*

Defines the pattern used in machining the product.

**Trim**



*Trim is optional. A single instance might exist.*

Trim

## **Joining**

*Joining is optional. A single instance might exist.*

Defines the method used to join pieces of wood.

## **PressureTreatment**

*PressureTreatment is optional. A single instance might exist.*

Method and parameter values of pressure treatment.

## **FireTreatment**

*FireTreatment is optional. A single instance might exist.*

Fire treatment

## **OtherTreatment**

*OtherTreatment is optional. A single instance might exist.*

Other treatment

## **GradeStamp**

*GradeStamp is optional. A single instance might exist.*

Grade stamp information

## **ExLog**

*ExLog is optional. A single instance might exist.*

Describes the cutting pattern of the log.

## **ClassIdentifier**

*ClassIdentifier is optional. Multiple instances might exist.*

Standard used for product identification.

## **Weight**

*Weight is optional. A single instance might exist.*

The weight of the item.

## **LabelCharacteristics**

*LabelCharacteristics is optional. A single instance might exist.*

A group item that organises the labeling information.

## **StencilCharacteristics**

*StencilCharacteristics is optional. A single instance might exist.*

A group element specifying attributes of a stencil to be applied to an item, and optional text.

## **Wrap**

*Wrap is optional. A single instance might exist.*

A group item that organises wrapping detail information.

## **SafetyAndEnvironmentalInformation**

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC).  
SafetyAndEnvironmental needs a value or measurement to communicate the

percentage of the product is certified (for example, 75% is certified by the indicated agency).

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **LengthCutDescription**

*LengthCutDescription is optional. A single instance might exist.*

Length Cut Description

## **ShippingMark**

*ShippingMark is optional. A single instance might exist.*

A shipping mark identifies the producer and quality on the end side of the product. Not to be mixed with company code/logo or other product marking.

---

## **DecorationCoverage**

Decoration coverage.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

#### **Value**

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### **RangeMin**


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### **RangeMax**

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



---

## **DecorationLocationType [attribute]**

Decoration location type

*This item is restricted to the following list.*

**Front**

**Back**

**Spine**



**FrontAndBack**  
**FrontAndSpine**  
**BackAndSpine**  
**FrontAndBackAndSpine**

## DecorationSpecs

Decoration specifications

### DecorationType [attribute]

*DecorationType is optional. A single instance might exist.*

Describes the finishing process.

Refer to DecorationType definition for any enumerations.

### DecorationLocationType [attribute]

*DecorationLocationType is optional. A single instance might exist.*

Decoration location type

Refer to DecorationLocationType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ColourCode

*ColourCode is optional. A single instance might exist.*

A code indicating the colour.

#### ColourDescription

*ColourDescription is optional. A single instance might exist.*

A free form description of the colour.

#### NumberOfHits

*NumberOfHits is optional. A single instance might exist.*

The number of hits

#### DecorationCoverage


*DecorationCoverage is optional. A single instance might exist.*

Decoration coverage.

#### ProductIdentification

*ProductIdentification is optional. Multiple instances might exist.*

A grouping element designed to communicate product identification related to the parent element that contains this item.



## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*


A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## DecorationType [attribute]

Describes the finishing process.

*This item is restricted to the following list.*



### Debossing

### DieCuts

### Emboss

### FoilStamping

Pressing a design onto a book cover using metallic or pigment foil.

### Hubbing

### InkStamping

Pressing a design onto a book cover using ink

### RaisedBands

### RaisedUV

Raised bumps obtained via an ultra-violet process.


### Stamping

---

## DeliveryDate

The Date and optionally the Time that the partners agree is the date upon which deliveries will be recognised.

Possible choices for this date are either the date despatched or the date received.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

#### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time

# papiNet V2R31

---

Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

---

## DeliveryDateType [attribute]

Provides a context for the delivery date window.

*This item is restricted to the following list.*

attribute
<b>DeliveryDateType</b>
type deliveryDateType

### **ActualArrivalDate**

The date the product arrived at the delivery destination.

### **ActualDepartureDate**

The date the product departed the delivery origin.

### **AvailableToShipDate**

The date that the material is available for shipment. That is, the material can be picked up on this date.

### **CancelAfterDate**

The delivery is to be cancelled if not delivered by this date.

### **DateOfLastChange**

The latest date at which an amendment versus cancellation is allowed to take place. The seller in the e-Document confirmation communicates this date.

### **DateOfTrading**

A date or date range when the supply of goods or services were made or completed. Normally this is the date of delivery but it can be other dates depending on terms of delivery (for example the despatch date).

### **DeliveryRequestedDate**

The date on which a buyer requests goods to be delivered. Delivery will happen at this date on a "best endeavours" basis.

### **DoNotDeliverAfterDate**

The delivery must not take place after the date specified.

### **DoNotShipAfterDate**

The shipment must not take place after the date specified.

### **EndCallOffDate**

The date on which the last CallOff can be placed.

### **EstimatedTimeOfArrival**

The expected time that the goods will arrive. Receiving facilities should be available.

## EstimatedTimeOfDeparture

The date and time that the shipment is expected to leave.

## LastChangeDate

The most recent date the document was changed.

## LoadingDate

The date on which loading should or is planned to take place.

## PickUpDate

The date the material will be, or is available to be, picked-up from the shipping location.

## PlannedShipDate

The date on which shipment is planned to take place.

## ReferencePeriod

A period of time covered by the object, e.g. an e-Document.

## ShipmentPriorToDate

The shipment (despatch) must take place prior to this date—in other words; the goods have to leave the terminal.

## ShipmentRequestedDate

The date on which shipment is requested to take place.

## StartCallOffDate

The date on which the first CallOff can be placed.

## DeliveryDateWindow

A group item defining the date/time interval for delivery to take place. An element which may contain the estimated date for which delivery is expected. This date is not absolute.

### DeliveryDateType [attribute]

*DeliveryDateType is mandatory. A single instance is required.*

Provides a context for the delivery date window.


Refer to DeliveryDateType definition for any enumerations.

### (choice)

*[choice] is optional because of choice construct.*

### DateTimeRange

*DateTimeRange is optional because of choice construct.*



The delivery date and/or time range.

## **Month**

*Month is optional because of choice construct.*

Identifies the month number when communicating a Calendar date.

## **Week**

*Week is optional because of choice construct.*

A field defining the week number of the calendar year. ISO 8601 is used as the basis for this element, "Week 01 of a year is the first week that has the Thursday in this year, which is equivalent to the week that contains the fourth day of January."

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **Date**

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### **Time**

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## DeliveryDestination

The DeliveryDestination specifies the end of one leg of the delivery. In order to comply with the US Trade Act of 2002 you would use this element with a LocationParty/@PartyType of Port.

### IsOptionalDestination [attribute]

*IsOptionalDestination is optional. A single instance might exist.*

Specifies if the Destination is optional or not. The default value is "No".

Refer to IsOptionalDestination definition for any enumerations.

### PriorityOrder [attribute]

*PriorityOrder is optional. A single instance might exist.*

Specifies the priority order of the item as a two digit positive integer. Value 1 is the highest priority.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Date

*Date is optional. A single instance might exist.*

A group element that contains the specification of Year, Month, and Day.

#### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.


hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

#### LocationParty

*LocationParty is mandatory. A single instance is required.*



The organization or business entity where the business event took place or will take place.

**(choice)**

*[choice] is optional because of choice construct.*

**SupplyPoint**

*SupplyPoint is optional because of the choice construct.*

Grouping element that contains items describing a supply point. A SupplyPoint belongs to a LocationParty, e.g. in a DeliveryOrigin or DeliveryDestination, and describes where goods are stored and can be loaded or unloaded. A SupplyPoint can for example be a loading or unloading gate at a warehouse or a road side landing at a logging area in the forest.

**LocationCode**

*LocationCode is optional because of the choice construct.*

A code used to identify a specific physical location within a site identified by a party, e.g. a loading station in a warehouse or an unloading station at a printer site.

LocationCode will be deprecated in a future version. Use SupplyPoint instead of LocationCode.

**(choice)**

*[choice] is optional because of choice construct.*

**GPSCoordinates**

*GPSCoordinates is optional because of choice construct.*

The location of the party as specified using a Global Positioning System.

**MapCoordinates**

*MapCoordinates is optional because of choice construct.*

A group item defining and containing position co-ordinates of a location.

---

## DeliveryIndicator

Indicates if delivery should take place or not.

*This item is restricted to the following list.*

**Deliver**

**DoNotDeliver**

<b>DeliveryIndicator</b>
type   deliveryIndicator

## DeliveryInfo

Information about the delivery.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### TermsOfDelivery

*TermsOfDelivery is optional. A single instance might exist.*

A group item defining the terms under which the delivery of goods will take place. These terms determine when and under what conditions the transfer of ownership will occur. Generally speaking, the Incoterms are primarily used in Europe, whereas the ShipmentMethodOfPayment is primarily used in North America.

### CarrierParty

*CarrierParty is optional. A single instance might exist.*

The party performing the transport of the product from the pickup location to the ship-to location; could be a hauler.

### TransportVehicleCharacteristics

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

### TransportModeCharacteristics

*TransportModeCharacteristics is optional. A single instance might exist.*

A group item defining the primary mode of transport.

### TransportUnitCharacteristics

*TransportUnitCharacteristics is optional. Multiple instances might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

### DeliveryOrigin

*DeliveryOrigin is mandatory. A single instance is required.*

A group item that represents the start of one leg in a route. Compare to DeliveryDestination.


The DeliveryOrigin specifies the start of one leg of the delivery.

In order to comply with the US Trade Act of 2002 you would use this element with a LocationParty/@PartyType of Port.

### DeliveryDestination

*DeliveryDestination is optional. A single instance might exist.*


The DeliveryDestination specifies the end of one leg of the delivery. In order to comply with the US Trade Act of 2002 you would use this element with a LocationParty/@PartyType of Port.



## DeliveryInstruction

A DeliveryInstruction element is the root element for the DeliveryInstruction e-Document.

A DeliveryInstruction can be used to instruct movement of goods to warehouses and movement of goods to virtual locations within warehouses as well as deliveries to customers. The DeliveryInstruction e-Document is designed to fulfil supply chain requirements regarding instruction for goods deliveries to Mills, Suppliers, Forwarders, Warehouse Operators, Customers, and End-Users. The DeliveryInstruction is load oriented which is very efficient when mills and suppliers move goods in large quantities between warehouses.



### DeliveryInstructionType [attribute]

*DeliveryInstructionType is mandatory. A single instance is required.*

DeliveryInstructionType defines the type of DeliveryInstruction.

Refer to DeliveryInstructionType definition for any enumerations.

### DeliveryInstructionStatusType [attribute]

*DeliveryInstructionStatusType is mandatory. A single instance is required.*

Identifies the status of the entire DeliveryInstruction (in other words, at the root level).

Refer to DeliveryInstructionStatusType definition for any enumerations.

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

## DeliveryInstructionHeader

*DeliveryInstructionHeader is mandatory. A single instance is required.*

The DeliveryInstruction Header provides information that applies to the entire DeliveryInstruction.

## DeliveryInstructionSequence

*DeliveryInstructionSequence is mandatory. One instance is required, multiple instances might exist.*

The DeliveryInstruction Sequence contains information about a loading or delivery event, depending on the type of DeliveryInstruction being communicated.

## DeliveryInstructionSummary

*DeliveryInstructionSummary is optional. A single instance might exist.*

The DeliveryInstruction Summary provides summary information used to verify the contents of the e-Document.


---

## DeliveryInstructionDate

The Date and Time when the DeliveryInstruction was issued.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is mandatory. A single instance is required.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.



## SenderParty

*SenderParty is mandatory. A single instance is required.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## ReceiverParty

*ReceiverParty is mandatory. One instance is required, multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## OtherParty

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

---

## DeliveryInstructionHeaderStatusType [attribute]

DeliveryInstructionHeaderStatusType identifies the status of the DeliveryInstruction header.

*This item is restricted to the following list.*



### Amended

The supplied information is changed.

### Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### New

The supplied information is new and supplied for the first time.

### NoAction

The supplied information has not been amended and thereby requires no action.

---

## DeliveryInstructionNumber


The unique identifier for the DeliveryInstruction.

DeliveryInstructionNumber	
type	s30

---

## DeliveryInstructionReference

An element detailing relevant references pertaining to the DeliveryInstruction, as indicated by the



DeliveryInstructionReferenceType and AssignedBy.

### **DeliveryInstructionReferenceType [attribute]**

*DeliveryInstructionReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to DeliveryInstructionReferenceType definition for any enumerations.

### **AssignedBy [attribute]**

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.


---

## DeliveryInstructionReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an

existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.



## DeliveryInstructionSequence

The DeliveryInstructionSequence contains information about a loading or delivery event, depending on the type of DeliveryInstruction being communicated.



### DeliveryInstructionSequenceStatusType [attribute]

*DeliveryInstructionSequenceStatusType is mandatory. A single instance is required.*

DeliveryInstruction sequence status type identifies the status of the DeliveryInstruction sequence

Refer to DeliveryInstructionSequenceStatusType definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **DeliveryInstructionSequenceNumber**

*DeliveryInstructionSequenceNumber is mandatory. A single instance is required.*

A sequential number that uniquely identifies the Sequence of a DeliveryInstruction.

### **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

### **DeliveryLeg**

*DeliveryLeg is mandatory. One instance is required, multiple instances might exist.*

A DeliveryLeg details the sequence, origin, transportation, and destination of each part of the delivery. More than one leg may be required if there is a change of mode, vehicle, or carrier.

Although transportation information is optional, it is strongly recommended that any transportation information available be sent.

### **BuyerParty**

*BuyerParty is optional. A single instance might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

### **BillToParty**

*BillToParty is optional. A single instance might exist.*

The address where the Invoice is to be sent.

### **SupplierParty**

*SupplierParty is optional. A single instance might exist.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

### **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

### **QuantityInformation**

*QuantityInformation is mandatory. One instance is required, multiple instances might exist.*

A group item containing information about quantity and informational quantity of similar items.

## **DeliveryInstructionReference**

*DeliveryInstructionReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the DeliveryInstruction, as indicated by the DeliveryInstructionReferenceType and AssignedBy.

## **CoLoading**

*CoLoading is optional. Multiple instances might exist.*

A group item specifying information about items to be loaded or loaded on the same transport unit.

Used to identify:

- Delivery together to the drop point
- Transport Orders stuffed together in a container
- Transport Orders not splittable

## **DocumentInformation**

*DocumentInformation is optional. Multiple instances might exist.*

A group element containing a specification of required documents in the business process. Additional free text to be printed on documents can also be specified.

## **DeliveryInstructionSequenceLineItem**

*DeliveryInstructionSequenceLineItem is mandatory. One instance is required, multiple instances might exist.*

The group item DeliveryInstructionSequenceLineItem contains information for a line item of a DeliveryInstruction sequence. The line item specifies detail information about product quantities, loading and unloading characteristics, order numbers and other references.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **ValidityPeriod**

*ValidityPeriod is optional. A single instance might exist.*

The validity period for a specific item, e.g. the validity period for an e-Document.

## DeliveryInstructionSequenceLineItem

The group item DeliveryInstructionSequenceLineItem contains information for a line item of a DeliveryInstruction sequence. The line item specifies detail information about product quantities, loading and unloading characteristics, order numbers and other references.

### InstructionByType [attribute]

*InstructionByType is mandatory. A single instance is required.*

Provides the type for how goods are identified on group level when instructed for loading or delivery.

Refer to InstructionByType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### DeliveryInstructionSequenceLineItemNumber

*DeliveryInstructionSequenceLineItemNumber is mandatory. A single instance is required.*

A sequential number that uniquely identifies the line item of a DeliveryInstruction Sequence.

### PurchaseOrderInformation

*PurchaseOrderInformation is optional. A single instance might exist.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

### PurchaseOrderLineItemNumber

*PurchaseOrderLineItemNumber is optional. A single instance might exist.*


The sequential number that uniquely identifies the PurchaseOrder line item.

### MillOrderNumber

*MillOrderNumber is optional. A single instance might exist.*

The manufacturing order number the mill uses.

### MillOrderLineItemNumber



*MillOrderLineItemNumber is optional. A single instance might exist.*

A number that uniquely identifies the line items of the Mill Order.

## **Product**

*Product is optional. A single instance might exist.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **MillParty**

*MillParty is optional. A single instance might exist.*

The organisation or business entity that actually produces the product.

## **SupplierParty**

*SupplierParty is optional. A single instance might exist.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **BuyerParty**

*BuyerParty is optional. A single instance might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **InventoryClass**

*InventoryClass is optional. A single instance might exist.*

A group item containing information about status of inventory and goods items.

## **DeliveryInstructionReference**

*DeliveryInstructionReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the DeliveryInstruction, as indicated by the DeliveryInstructionReferenceType and AssignedBy.

## **SupplyPoint**

*SupplyPoint is optional. Two instances might exist.*

Grouping element that contains items describing a supply point. A SupplyPoint belongs to a LocationParty, e.g. in a DeliveryOrigin or DeliveryDestination, and describes where goods are stored and can be loaded or unloaded. A SupplyPoint can for example be a loading or unloading gate at a warehouse or a road side landing at a logging area in the forest.

## **Quantity**

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of

quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **TransportOtherInstructions**

*TransportOtherInstructions is optional. Multiple instances might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

## **TransportLoadingCharacteristics**

*TransportLoadingCharacteristics is optional. Multiple instances might exist.*

A group item defining how the transported items are to be loaded.

## **TransportUnloadingCharacteristics**

*TransportUnloadingCharacteristics is optional. Multiple instances might exist.*

A group item defining how the transported items are to be unloaded.

## **StatisticalGoodsInformation**

*StatisticalGoodsInformation is optional. A single instance might exist.*

A group item containing statistical information about handled or traded goods.

## **NumberOfPackages**

*NumberOfPackages is optional. A single instance might exist.*

The number of packages in the delivery.

## **PackageInformation**

*PackageInformation is optional. Multiple instances might exist.*

The purpose of the PackageInformation structure is to clearly identify physical handling items that constitute the delivery.

PackageInformation is the highest level of product packaging it describes the shipping or warehousing unit.

If you are communicating a package, usually for logistics or transport purposes, you should include the PackageType, Identifier, ItemCount, and Quantity. (Note: you still have the ability to describe the item with one of the "named" items.)

If you are communicating one of the named Items there is no need to include PackageType, Identifier, ItemCount, and Quantity.

Since either of these two approaches can be used the entire contents of this element are optional even though the parent may be required. It is expected that you will fill in the appropriate details.

## **CountryOfConsumption**

# papiNet V2R31

---

*CountryOfConsumption is optional. A single instance might exist.*

The country of consumption for the material.

## **CountryOfDestination**

*CountryOfDestination is optional. A single instance might exist.*

The country where the goods will be, or were, shipped to.

## **CountryOfOrigin**

*CountryOfOrigin is optional. A single instance might exist.*

The country of origin for the material.

## **OtherDate**

*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## **SafetyAndEnvironmentalInformation**

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

---

## **DeliveryInstructionSequenceLineItemNumber**

A sequential number that uniquely identifies the line item of a DeliveryInstruction Sequence.

<b>DeliveryInstructionSequenceLineItemNumber</b>
type   lineNumberType

---

## **DeliveryInstructionSequenceNumber**

A sequential number that uniquely identifies the Sequence of a DeliveryInstruction.

<b>DeliveryInstructionSequenceNumber</b>
type   lineNumberType

---

## **DeliveryInstructionSequenceStatusType [attribute]**

DeliveryInstruction sequence status type identifies the status of the DeliveryInstruction sequence

*This item is restricted to the following list.*

### **Cancelled**

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### **New**

The supplied information is new and supplied for the first time.

attribute
<b>DeliveryInstructionSequenceStatusType</b>
type   deliveryInstructionSequenceStatusType

## NoAction

The supplied information has not been amended and thereby requires no action.


## Replaced

The supplied information is replacing earlier supplied information. The receiver should revalidate the information in their system based upon the entire information received.

---

## DeliveryInstructionStatusType [attribute]

Identifies the status of the entire DeliveryInstruction (in other words, at the root level).



*This item is restricted to the following list.*

### Amended

The supplied information is changed

### Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### Original

The supplied information is the first version of that information.

---


## DeliveryInstructionSummary

The DeliveryInstruction Summary provides summary information used to verify the contents of the e-Document.


### (sequence)

*The sequence of items below*

*is mandatory. A single instance is required.*



(sequence)



### TotalNumberOfSequences

*TotalNumberOfSequences is optional. A single instance might exist.*

The total number of sequences in the document.

### TotalQuantityInformation

*TotalQuantityInformation is optional. Multiple instances might exist.*

A group item containing information about the total quantity and total informational quantity of similar items in the document. TotalQuantityInformation is primarily used in the summary section of e-Documents where it is repeatable to permit totalling for different units of measure.

### TermsAndDisclaimers

*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.

## DeliveryInstructionType [attribute]

DeliveryInstructionType defines the type of DeliveryInstruction.

*This item is restricted to the following list.*



### DeliveryInstruction

A DeliveryInstruction can specify many delivery events. Each event can contain quantity for one or many loads. A sequence in a DeliveryInstruction specifies all details for one event. The receiver of a DeliveryInstruction can generate many Loading Instructions from one DeliveryInstruction.

### Loading Instruction


A Loading Instruction specifies loading of transport units. A Forwarder receiving a DeliveryInstruction from a supplier can convert it into many Loading Instructions, which are sent to a Warehouse Operator. A sequence in a Loading Instruction specifies all details how to load one transport unit. A Loading Instruction can include goods from many delivery instructions and also goods belonging to many suppliers.

## DeliveryLastDateOfChange

The final Date and optionally Time that a line item or delivery line may be amended or cancelled by the buyer.

The final Date and optionally Time that a line item or delivery line

may be amended or cancelled by the buyer. For example, the buyer can cancel each a delivery line before the DeliveryLastDateOfChange received from the seller on the OrderConfirmation.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

#### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

## papiNet V2R31

---

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## DeliveryLeg

A DeliveryLeg details the sequence, origin, transportation, and destination of each part of the delivery. More than one leg may be required if there is a change of mode, vehicle, or carrier.

Although transportation information is optional, it is strongly recommended that any transportation information available be sent.

### DeliveryModeType [attribute]

*DeliveryModeType is optional. A single instance might exist.*

Provides delivery mode type that specifies if transport arrangement is needed or not.

Refer to DeliveryModeType definition for any enumerations.

### DeliveryLegType [attribute]

*DeliveryLegType is optional. A single instance might exist.*

Provides the delivery leg type that specifies if delivery schedule is supplied or not.

Refer to DeliveryLegType definition for any enumerations.

### EventType [attribute]

*EventType is optional. A single instance might exist.*

The type of transportation event that the DeliveryLeg represents.

Refer to EventType definition for any enumerations.

### LegStageType [attribute]


*LegStageType is optional. A single instance might exist.*

LegStageType is used to identify whether this is the primary transportation process or a transportation process that comes before or after the main transportation process.

Refer to LegStageType definition for any enumerations.

### TransportContextType [attribute]

*TransportContextType is optional. A single*



*instance might exist.*

Provides information about the reason for the transport.

Refer to TransportContextType definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **DeliveryLegSequenceNumber**

*DeliveryLegSequenceNumber is mandatory. A single instance is required.*

The sequential number of the delivery leg. Applicable to multiple delivery segments.

### **DeliveryOrigin**

*DeliveryOrigin is mandatory. A single instance is required.*

A group item that represents the start of one leg in a route. Compare to DeliveryDestination.

The DeliveryOrigin specifies the start of one leg of the delivery.

In order to comply with the US Trade Act of 2002 you would use this element with a LocationParty/@PartyType of Port.

### **CarrierParty**

*CarrierParty is optional. A single instance might exist.*

The party performing the transport of the product from the pickup location to the ship-to location; could be a hauler.

### **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

### **TransportModeCharacteristics**

*TransportModeCharacteristics is optional. A single instance might exist.*

A group item defining the primary mode of transport.

### **TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

### **TransportUnitCharacteristics**

*TransportUnitCharacteristics is optional. Multiple instances might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

### **TransportLoadingCharacteristics**

*TransportLoadingCharacteristics is optional. Multiple instances might exist.*

A group item defining how the transported items are to be loaded.

### **TransportUnloadingCharacteristics**

*TransportUnloadingCharacteristics is optional. Multiple instances might exist.*

A group item defining how the transported items are to be unloaded.

## TransportOtherInstructions

*TransportOtherInstructions is optional. Multiple instances might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

## Route

*Route is optional. Multiple instances might exist.*

Route defines directions and characteristics for how to transport goods between two locations. A route starts at delivery origin or at the supplypoint belonging to the delivery origin.

## DeliveryTransitTime

*DeliveryTransitTime is optional. A single instance might exist.*

A group item representing the number of Days and optionally Hours and Minutes between origin and destination for a DeliveryLeg.

## DeliveryDestination

*DeliveryDestination is optional. A Multiple instances might exist.*

The DeliveryDestination specifies the end of one leg of the delivery. In order to comply with the US Trade Act of 2002 you would use this element with a LocationParty/@PartyType of Port.

## DeliveryDateWindow

*DeliveryDateWindow is optional. Multiple instances might exist.*

A group item defining the date/time interval for delivery to take place. An element which may contain the estimated date for which delivery is expected. This date is not absolute.

## DeliveryLegReference

*DeliveryLegReference is optional. Multiple instances might exist.*

A reference that applies to the delivery leg.

## TermsOfChartering


*TermsOfChartering is optional. Multiple instances might exist.*

The terms of the vessel chartering. There are multiple types of TermsOfChartering that need to be specified. E.g.: Loading Terms and Unloading Terms

---

## DeliveryLegReference

A reference that applies to the delivery leg.



### DeliveryLegReferenceType [attribute]

*DeliveryLegReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill",

"Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to DeliveryLegReferenceType definition for any enumerations.

## AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## DeliveryLegReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

attribute	
<b>DeliveryLegReferenceType</b>	
type	referenceType

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

---

## DeliveryLegSequenceNumber

The sequential number of the delivery leg. Applicable to multiple delivery segments.

<b>DeliveryLegSequenceNumber</b>	
type	lineNumberType

---

## DeliveryLegType [attribute]

Provides the delivery leg type that specifies if delivery schedule is supplied or not.

*This item is restricted to the following list.*

### Fixed

The delivery schedule is supplied and defined.

### Open

The delivery schedule is open and will be given later by other party. This type is often used when goods are picked-up at the warehouse by customer.

attribute	
<b>DeliveryLegType</b>	
type	deliveryLegType
default	Fixed

## DeliveryLineNumber

A sequential number that uniquely identifies a delivery line of the DeliverySchedule; a delivery line consists of a quantity and a date range for the delivery to take place.

<b>DeliveryLineNumber</b>	
type	lineNumberType

## DeliveryMessage

The DeliveryMessage element is the root element for the DeliveryMessage e-Document.

The DeliveryMessage e-Document enables the sender to describe the contents and configuration of a shipment at various levels of detail.

### DeliveryMessageType [attribute]

*DeliveryMessageType is mandatory. A single instance is required.*

DeliveryMessageType defines the type of DeliveryMessage.

Refer to DeliveryMessageType definition for any enumerations.

### DeliveryMessageStatusType [attribute]

*DeliveryMessageStatusType is mandatory. A single instance is required.*

Identifies the status of the entire DeliveryMessage (in other words, at the root level).

Refer to DeliveryMessageStatusType definition for any enumerations.

### DeliveryMessageContextType [attribute]

*DeliveryMessageContextType is optional. A single instance might exist.*

Communicates the reason for this delivery. If not present then this is a standard, typical delivery.

Refer to DeliveryMessageContextType definition for any enumerations.


### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

### Language [attribute]



Language is optional. A single instance might exist.

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

**(sequence)**

The sequence of items below is mandatory. A single instance is required.

**DeliveryMessageHeader**

*DeliveryMessageHeader is mandatory. A single instance is required.*

The DeliveryMessageHeader contains information common to the entire delivery.

**DeliveryMessageLineItem**

*DeliveryMessageLineItem is mandatory. One instance is required, multiple instances might exist.*

The DeliveryMessageLineItem specifies details for an individual delivery line.

**DeliveryMessageSummary**


*DeliveryMessageSummary is optional. A single instance might exist.*

Summary information that applies to the entire DeliveryMessage.

## DeliveryMessageBook

The DeliveryMessageBook element is the root element for the DeliveryMessageBook e-Document.

The DeliveryMessageBook e-Document enables the sender to describe the contents and configuration of a shipment at various levels of detail.



**DeliveryMessageType [attribute]**

*DeliveryMessageType is mandatory. A single instance is required.*

DeliveryMessageType defines the type of DeliveryMessage.

Refer to DeliveryMessageType definition for any enumerations.

**DeliveryMessageStatusType [attribute]**

*DeliveryMessageStatusType is mandatory. A single instance is required.*

Identifies the status of the entire DeliveryMessage (in other words, at the root level).

Refer to DeliveryMessageStatusType definition for any enumerations.

## **DeliveryMessageContextType [attribute]**

*DeliveryMessageContextType is optional. A single instance might exist.*

Communicates the reason for this delivery. If not present then this is a standard, typical delivery.

Refer to DeliveryMessageContextType definition for any enumerations.

## **Reissued [attribute]**

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

## **Language [attribute]**

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **DeliveryMessageBookHeader**

*DeliveryMessageBookHeader is mandatory. A single instance is required.*

The DeliveryMessageBookHeader is required and contains information common to the entire delivery.

### **DeliveryMessageBookShipment**

*DeliveryMessageBookShipment is mandatory. One instance is required, multiple instances might exist.*

DeliveryMessageBookShipment is required. The DeliveryMessageBookShipment specifies an individual shipment. It may contain many shipment line items.

### **DeliveryMessageBookSummary**

*DeliveryMessageBookSummary is mandatory. A single instance is required.*

DeliveryMessageBookSummary is a required element.

## DeliveryMessageBookHeader

The DeliveryMessageBookHeader is required and contains information common to the entire delivery.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**DeliveryMessageNumber**

*DeliveryMessageNumber is mandatory. A single instance is required.*

A unique delivery identifier assigned to each DeliveryMessage as agreed between the trading partners.

**TransactionHistoryNumber**

*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

**DeliveryMessageDate**

*DeliveryMessageDate is mandatory. A single instance is required.*

The Date and Time when the DeliveryMessage was issued.

**DeliveryMessageReference**

*DeliveryMessageReference is optional. Multiple instances might exist.*

An element that identifies the relevant references pertaining to the DeliveryMessage, identified by DeliveryMessageReferenceType.

**BuyerParty**

*BuyerParty is mandatory. A single instance is required.*


The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

**BillToParty**

*BillToParty is optional. A single instance might exist.*

The address where the Invoice is to be sent.

**SupplierParty**



*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **ShipToCharacteristics**

*ShipToCharacteristics is mandatory. A single instance is required.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **CountryOfOrigin**

*CountryOfOrigin is optional. A single instance might exist.*

The country of origin for the material.

## **CountryOfDestination**

*CountryOfDestination is optional. A single instance might exist.*

The country where the goods will be, or were, shipped to.

## **CountryOfConsumption**

*CountryOfConsumption is optional. A single instance might exist.*

The country of consumption for the material.

## **Insurance**

*Insurance is optional. A single instance might exist.*

Group element containing information about insurance

## **DeliveryLeg**

*DeliveryLeg is mandatory. One instance is required, multiple instances might exist.*

A DeliveryLeg details the sequence, origin, transportation, and destination of each part of the delivery. More than one leg may be required if there is a change of mode, vehicle, or carrier.

Although transportation information is optional, it is strongly recommended that any transportation information available be sent.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **ReturnReason**


*ReturnReason is optional. A single instance might exist.*

A group item containing the reason for the Return

---

## **DeliveryMessageBookShipment**

DeliveryMessageBookShipment is required.  
The DeliveryMessageBookShipment specifies an individual shipment. It may contain many shipment line items.



### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

#### **DeliveryShipmentId**

*DeliveryShipmentId is mandatory. A single instance is required.*

Unique identifier for the shipment

#### **DeliveryShipmentBookLineItem**

*DeliveryShipmentBookLineItem is mandatory. One instance is required, multiple instances might exist.*

DeliveryShipmentBookLineItem is required. The DeliveryShipmentBookLineItem specifies an individual shipment delivery line for one PurchaseOrder and PurchaseOrder line item.

#### **ShipmentSummary**

*ShipmentSummary is optional. A single instance might exist.*


Summary information for an entire shipment

## DeliveryMessageBookSummary

DeliveryMessageBookSummary is a required element.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### TotalNumberOfShipments

*TotalNumberOfShipments is mandatory. A single instance is required.*

Total number of shipments referred to in a DeliveryMessage.

### TotalQuantity

*TotalQuantity is optional. A single instance might exist.*

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

### TotalInformationalQuantity

*TotalInformationalQuantity is optional. Multiple instances might exist.*

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

### TermsAndDisclaimers

*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.

## DeliveryMessageContextType [attribute]

Communicates the reason for this delivery. If not present then this is a standard, typical delivery.

*This item is restricted to the following list.*

### Return

The delivery supports the goods return process.




---

## DeliveryMessageDate

The Date and Time when the DeliveryMessage was issued.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## DeliveryMessageHeader

The DeliveryMessageHeader contains information common to the entire delivery.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DeliveryMessageNumber


*DeliveryMessageNumber is mandatory. A single instance is required.*

A unique delivery identifier assigned to each DeliveryMessage as agreed between the trading partners.

#### TransactionHistoryNumber

*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the



TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

#### DeliveryMessageDate

*DeliveryMessageDate is mandatory. A single instance is required.*

The Date and Time when the DeliveryMessage was issued.

#### DeliveryMessageReference

*DeliveryMessageReference is optional. Multiple instances might exist.*

An element that identifies the relevant references pertaining to the DeliveryMessage, identified by DeliveryMessageReferenceType.

#### BuyerParty

*BuyerParty is optional. A single instance might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.


#### BillToParty

*BillToParty is optional. A single instance might exist.*

The address where the Invoice is to be sent.

#### SupplierParty

*SupplierParty is optional. A single instance might exist.*



The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **ShipToCharacteristics**

*ShipToCharacteristics is mandatory. A single instance is required.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **DocumentInformation**

*DocumentInformation is optional. Multiple instances might exist.*

A group element containing a specification of required documents in the business process. Additional free text to be printed on documents can also be specified.

## **CoLoading**

*CoLoading is optional. Multiple instances might exist.*

A group item specifying information about items to be loaded or loaded on the same transport unit.

Used to identify:

- Delivery together to the drop point
- Transport Orders stuffed together in a container
- Transport Orders not splittable

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for

special instructions. To be used only for circumstances not covered by specific elements.

## **DeliveryLeg**

*DeliveryLeg is mandatory. One instance is required, multiple instances might exist.*

A DeliveryLeg details the sequence, origin, transportation, and destination of each part of the delivery. More than one leg may be required if there is a change of mode, vehicle, or carrier.

Although transportation information is optional, it is strongly recommended that any transportation information available be sent.

## **CountryOfOrigin**

*CountryOfOrigin is optional. A single instance might exist.*

The country of origin for the material.

## **CountryOfDestination**

*CountryOfDestination is optional. A single instance might exist.*

The country where the goods will be, or were, shipped to.

## **CountryOfConsumption**

*CountryOfConsumption is optional. A single instance might exist.*

The country of consumption for the material.

## DeliveryMessageLineItem

The DeliveryMessageLineItem specifies details for an individual delivery line.

### ShipmentComplete [attribute]

*ShipmentComplete is optional. A single instance might exist.*

Indicates that all shipments for the particular delivery item are complete

Refer to ShipmentComplete definition for any enumerations.

### InstructionByType [attribute]

*InstructionByType is optional. A single instance might exist.*

Provides the type for how goods are identified on group level when instructed for loading or delivery.

Refer to InstructionByType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### DeliveryMessageLineItem Number

*DeliveryMessageLineItemNumber is mandatory. A single instance is required.*

The sequential number that uniquely identifies the delivery line item.

### PurchaseOrderInformation

*PurchaseOrderInformation is optional. A single instance might exist.*


A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

### PurchaseOrderLineItemNumber

*PurchaseOrderLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the PurchaseOrder line item.

### DeliveryMessageReference



*DeliveryMessageReference is optional. Multiple instances might exist.*

An element that identifies the relevant references pertaining to the DeliveryMessage, identified by DeliveryMessageReferenceType.

## **Product**

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **InventoryClass**

*InventoryClass is optional. A single instance might exist.*

A group item containing information about status of inventory and goods items.

## **NumberOfPackages**

*NumberOfPackages is optional. A single instance might exist.*

The number of packages in the delivery.

## **SupplyPoint**

*SupplyPoint is optional. Two instances might exist.*

Grouping element that contains items describing a supply point. A SupplyPoint belongs to a LocationParty, e.g. in a DeliveryOrigin or DeliveryDestination, and describes where goods are stored and can be loaded or unloaded. A SupplyPoint can for example be a loading or unloading gate at a warehouse or a road side landing at a logging area in the forest.

## **Quantity**

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **TransportOtherInstructions**

*TransportOtherInstructions is optional. Multiple instances might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

## **TransportLoadingCharacteristics**

*TransportLoadingCharacteristics is optional. Multiple instances might exist.*

A group item defining how the transported items are to be loaded.

## **TransportUnloadingCharacteristics**

*TransportUnloadingCharacteristics is optional. Multiple instances might exist  
A group item defining how the transported items are to be unloaded.*

## **BillToParty**

*BillToParty is optional. A single instance might exist.*

The address where the Invoice is to be sent.

## **MillCharacteristics**

*MillCharacteristics is optional. A single instance might exist.*

A group item defining the mill party and machine identifier where a product is or was produced.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **StatisticalGoodsInformation**

*StatisticalGoodsInformation is optional. A single instance might exist.*

A group item containing statistical information about handled or traded goods.

## **PackageInformation**

*PackageInformation is optional. Multiple instances might exist.*

The purpose of the PackageInformation structure is to clearly identify physical handling items that constitute the delivery.

PackageInformation is the highest level of product packaging it describes the shipping or warehousing unit.

If you are communicating a package, usually for logistics or transport purposes, you should include the PackageType, Identifier, ItemCount, and Quantity. (Note: you still have the ability to describe the item with one of the "named" items.)

If you are communicating one of the named Items there is no need to include PackageType, Identifier, ItemCount, and Quantity.

Since either of these two approaches can be used the entire contents of this element are optional even though the parent may be required. It is expected that you will fill in the appropriate details.

## **CountryOfOrigin**

*CountryOfOrigin is optional. A single instance might exist.*

The country of origin for the material.

## **CountryOfDestination**

*CountryOfDestination is optional. A single instance might exist.*

The country where the goods will be, or were, shipped to.

## **CountryOfConsumption**

*CountryOfConsumption is optional. A single instance might exist.*

The country of consumption for the material.

## OtherDate

*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## SafetyAndEnvironmentalInformation

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

## DeliveryMessageLineItemNumber

The sequential number that uniquely identifies the delivery line item.

<b>DeliveryMessageLineItemNumber</b>
type lineNumberType

## DeliveryMessageNumber

A unique delivery identifier assigned to each DeliveryMessage as agreed between the trading partners.


<b>DeliveryMessageNumber</b>
type s30

## DeliveryMessageProductGroup

The DeliveryMessageProductGroup permits the organization of a shipment by a product grouping.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### ProductGroupID

*ProductGroupID is optional. A single instance might exist.*

Possibility to group packages or Shipments. Example: Creating temporary group ID's for logistic reasons or lot number.

### DeliveryShipmentLineItem

*DeliveryShipmentLineItem is mandatory. One instance is required, multiple instances might exist.*

The DeliveryShipmentLineItem specifies an individual delivery line for one order and order line item.

PackageInformation will be deprecated in the version following V2R30, it has been replaced with TransportPackageInformation.

You are encouraged to use TransportPackageInformation.

## ProductGroupSummary

*ProductGroupSummary is optional. A single instance might exist.*

Group of elements to provide summary information on product level.

## DeliveryMessageReelCharacteristics

A group item for actual measurement and manufacturing characteristics.

DeliveryMessageReelCharacteristics is intended to indicate the actual measurements that apply to a reel.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ReelWidth

*ReelWidth is optional. A single instance might exist.*

The width of reel from edge to edge excluding packaging.

#### ReelDiameter

*ReelDiameter is optional. A single instance might exist.*

The diameter measurement of reel excluding packaging.



#### ReelLength

*ReelLength is optional. A single instance might exist.*

The total length of the paper on the reel.

#### MachineID

*MachineID is optional. A single instance might exist.*

An identifier assigned to the particular machine being referenced. For example, a machine could be a paper machine, an off-line coater, a sheeter, or a printing press. The particular machine being referenced will be determined by the business event being supported.

#### TambourID

*TambourID is optional. A single instance might exist.*

The unique identifier of the jumbo reel (also called mother reel or Tambour).

#### SetNumber


*SetNumber is optional. A single instance might exist.*

The part of the radius of the Tambour that constitutes the reel.

#### SetPosition

*SetPosition is optional. A single instance might exist.*

The position of the reel in relation to the reels cut across the Tambour.



# papiNet V2R31

---

## TotalSetPositions

*TotalSetPositions is optional. A single instance might exist.*

The total number of reels cut across the Tambour (in the width direction). Tambour is also called jumbo reel or mother reel.

## TotalSetNumbers

*TotalSetNumbers is optional. A single instance might exist.*

The total number of sets wound from the Tambour (in the radial direction). Tambour is also called jumbo reel or mother reel.

## NumberOfMillJoins

*NumberOfMillJoins is optional. A single instance might exist.*

The number of joins in the reel.

## MillJoinLocation

*MillJoinLocation is optional. Multiple instances might exist.*

A group element detailing the location of each mill join in a reel. The element DeliveryMessageReelCharacteristics/NumberOfMillJoins gives the total number of joins in a reel. DeliveryMessageReelCharacteristics/MillJoinLocation would be repeated the NumberOfMillJoin times.

## DateFinished

*DateFinished is optional. A single instance might exist.*

The Date and optionally the Time that an item was finished. For example, this could be the wrapping date for a reel or ream or the date the sheet(s) were packaged in preparation for shipment

## DateWound

*DateWound is optional. A single instance might exist.*

The Date and optionally the Time that a reel was wound or produced from its parent. RewoundIndicator indicates if the reel has been rewound.

## Caliper


*Caliper is optional. A single instance might exist.*

The thickness of a sheet of paper under standard test conditions.

---

## DeliveryMessageReference

An element that identifies the relevant references pertaining to the DeliveryMessage, identified by



DeliveryMessageReferenceType.

### DeliveryMessageReferenceType [attribute]

*DeliveryMessageReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill",

"Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to DeliveryMessageReferenceType definition for any enumerations.

## AssignedBy [attribute]


*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

## DeliveryMessageReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.




Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## DeliveryMessageShipment

The DeliveryMessageShipment specifies an individual delivery shipment. It may contain product grouping within the shipment.

(sequence)

*The sequence of items below is mandatory. A single instance is required.*



### ShipmentID

*ShipmentID is optional. A single instance might exist.*

The ShipmentID may be a Bill of Lading Marking, which is customer's reference mark on each package used for logistic purposes. Should not be mixed up with Bill of Lading number. Another example of ShipmentID is grouping by a ContainerID.

### DeliveryMessageProductGroup

*DeliveryMessageProductGroup is mandatory. One instance is required, multiple instances might exist.*

The DeliveryMessageProductGroup permits the organization of a shipment by a

product grouping.

## ShipmentSummary

*ShipmentSummary is optional. A single instance might exist.*

Summary information for an entire shipment

## DeliveryMessageStatusType [attribute]

Identifies the status of the entire DeliveryMessage (in other words, at the root level).



*This item is restricted to the following list.*

### Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### Original

The supplied information is the first version of that information.

### Replaced


The supplied information is replacing earlier supplied information. The receiver should revalidate the information in their system based upon the entire information received.

## DeliveryMessageSummary

Summary information that applies to the entire DeliveryMessage.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### TotalNumberOfLineItems

*TotalNumberOfLineItems is optional. A single instance might exist.*

The total number of individual line items in the document, regardless of the status or type.

### (sequence)

*The sequence of items below is mandatory. One instance is required, multiple instances might exist.*

### TotalQuantity

*TotalQuantity is mandatory. A single instance is required.*

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit

totaling for different units of measure.

## **TotalInformationalQuantity**

*TotalInformationalQuantity is optional. Multiple instances might exist.*

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

## **TermsAndDisclaimers**

*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.

---

## **DeliveryMessageType (Book) [attribute]**

DeliveryMessageType defines the type of DeliveryMessageBook.

*This item is restricted to the following list.*

attribute
<b>DeliveryMessageType</b>
type deliveryMessageType.Book

### **DeliveryMessage**

A DeliveryMessage type that contains optional routing information, quantities at the DeliveryMessageLineItem level, and details at the DeliveryMessageLineItemDetail level. The seller uses a DeliveryMessage to provide delivery details to the ship-to party and tracking information.

### **InitialShipmentAdvice**

A DeliveryMessage type that contains detailed routing information, quantities at the DeliveryMessageLineItem level and optionally details at the DeliveryMessageLineItemDetail level. The seller uses the InitialShipmentAdvice to provide preliminary notification of shipment routing and quantities (can be used as an advanced notice of delivery). The quantities indicated may not necessarily be delivered—for example, if there is damage in transit or the delivery is rerouted to another destination.

### **LoadedSpecification**

A DeliveryMessage type that contains a specification of loaded goods on a transport unit (e.g. container, rail wagon). A loading specification (LoadedSpecification) can contain goods belonging to many suppliers and buyers and is normally referring to a Loading Instruction.

### **ShipmentAdvice**

A DeliveryMessage type that contains a specification of goods, that are dispatched and will be delivered to a warehouse. A ShipmentAdvice can refer to a DeliveryInstruction Sequence or a CallOff, but is normally also used for notifying a receiving warehouse operator of shipments to the warehouse.

### **ThirdPartyShipmentAdvice**

Notification of a shipment from a warehouse to a party other than the party that ordered the product from the supplier

### **Waybill**

The forwarding agreement or carrying agreement that is used as a receipt for

cargo and as a contract of carriage.

---

## DeliveryMessageType [attribute]

DeliveryMessageType defines the type of DeliveryMessage.

*This item is restricted to the following list.*



### DeliveryMessage

A DeliveryMessage type that contains optional routing information, quantities at the DeliveryMessageLineItem level, and details at the DeliveryMessageLineItemDetail level. The seller uses a DeliveryMessage to provide delivery details to the ship-to party and tracking information.

### InitialShipmentAdvice

A DeliveryMessage type that contains detailed routing information, quantities at the DeliveryMessageLineItem level and optionally details at the DeliveryMessageLineItemDetail level. The seller uses the InitialShipmentAdvice to provide preliminary notification of shipment routing and quantities (can be used as an advanced notice of delivery). The quantities indicated may not necessarily be delivered—for example, if there is damage in transit or the delivery is rerouted to another destination.

### LoadedSpecification

A DeliveryMessage type that contains a specification of loaded goods on a transport unit (e.g. container, rail wagon). A loading specification (LoadedSpecification) can contain goods belonging to many suppliers and buyers and is normally referring to a Loading Instruction.

### ShipmentAdvice

A DeliveryMessage type that contains a specification of goods, that are dispatched and will be delivered to a warehouse. A ShipmentAdvice can refer to a DeliveryInstruction Sequence or a CallOff, but is normally also used for notifying a receiving warehouse operator of shipments to the warehouse.

### Waybill


The forwarding agreement or carrying agreement that is used as a receipt for cargo and as a contract of carriage.

---

## DeliveryMessageType (Wood) [attribute]

DeliveryMessageType defines the type of DeliveryMessageWood.

*This item is restricted to the following list.*



### DeliveryMessage

A DeliveryMessage type that contains optional routing information, quantities at the DeliveryMessageLineItem level, and details at the DeliveryMessageLineItemDetail level. The seller uses a DeliveryMessage to provide delivery details to the ship-to party and tracking information.

## InitialShipmentAdvice

A DeliveryMessage type that contains detailed routing information, quantities at the DeliveryMessageLineItem level and optionally details at the DeliveryMessageLineItemDetail level. The seller uses the InitialShipmentAdvice to provide preliminary notification of shipment routing and quantities (can be used as an advanced notice of delivery). The quantities indicated may not necessarily be delivered—for example, if there is damage in transit or the delivery is rerouted to another destination.

## LoadingOrder

Specifies delivery schedule, the transport booking requirements and shipping instructions, as well as the internal work order for the shipment

## PackingSpecification

A Packing Specification is a business transaction specifying the complete consignment being shipped from a consignor to a consignee. The specification describes in detail what is being shipped and how it is packed and marked.

## ShipmentAdvice

A DeliveryMessage type that contains a specification of goods, that are dispatched and will be delivered to a warehouse. A ShipmentAdvice can refer to a DeliveryInstruction Sequence or a CallOff, but is normally also used for notifying a receiving warehouse operator of shipments to the warehouse.

## DeliveryMessageWood

The DeliveryMessageWood element is the root element for the DeliveryMessageWood e-Document.

The DeliveryMessageWood e-Document enables the sender to describe the contents and configuration of a shipment at various levels of detail.

### DeliveryMessageType [attribute]


*DeliveryMessageType is mandatory. A single instance is required.*

DeliveryMessageType defines the type of DeliveryMessage.

Refer to DeliveryMessageType definition for any enumerations.

### DeliveryMessageStatusType [attribute]

*DeliveryMessageStatusType is mandatory. A single instance is required.*



Identifies the status of the entire DeliveryMessage (in other words, at the root level).

Refer to DeliveryMessageStatusType definition for any enumerations.

## **DeliveryMessageContextType [attribute]**

*DeliveryMessageContextType is optional. A single instance might exist.*

Communicates the reason for this delivery. If not present then this is a standard, typical delivery.

Refer to DeliveryMessageContextType definition for any enumerations.

## **Reissued [attribute]**

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

## **Language [attribute]**

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **DeliveryMessageWoodHeader**

*DeliveryMessageWoodHeader is mandatory. A single instance is required.*

This element contains the information that is consistent for the entire DeliveryMessageWood document.

Note: DocumentReferenceInformation will be removed from this element in the next version of papiNet. Use the DocumentInformation element instead.

### **DeliveryMessageShipment**

*DeliveryMessageShipment is mandatory. One instance is required, multiple instances might exist.*

The DeliveryMessageShipment specifies an individual delivery shipment. It may contain product grouping within the shipment.

### **DeliveryMessageWoodSummary**

*DeliveryMessageWoodSummary is optional. A single instance might exist.*

The DeliveryMessageWoodSummary contains summary information based on the line items contained in the DeliveryMessageWood document.

## DeliveryMessageWoodHeader

This element contains the information that is consistent for the entire DeliveryMessageWood document.

Note: DocumentReferenceInformation will be removed from this element in the next version of papiNet. Use the DocumentInformation element instead.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### DeliveryMessageNumber

DeliveryMessageNumber is mandatory. A single instance is required.

A unique delivery identifier assigned to each DeliveryMessage as agreed between the trading partners.

#### TransactionHistoryNumber



TransactionHistoryNumber is optional. A single instance might exist.

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

#### DeliveryMessageDate

DeliveryMessageDate is mandatory. A single instance is required.

The Date and Time when the DeliveryMessage was issued.

#### DeliveryMessageReference

DeliveryMessageReference is optional. Multiple instances might exist.

An element that identifies the relevant references pertaining to the DeliveryMessage, identified by DeliveryMessageReferenceType.


#### DocumentReferenceInformation

DocumentReferenceInformation is optional. Multiple instances might exist.

A group item containing reference information applicable to a document.

#### BuyerParty

BuyerParty is mandatory. A single instance is required.



The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## **BillToParty**

*BillToParty is optional. A single instance might exist.*

The address where the Invoice is to be sent.

## **SupplierParty**

*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **ShipToInformation**

*ShipToInformation is mandatory. One instance is required, multiple instances might exist.*

Group element containing information about the ship to and delivery of a product.

## **CountryOfOrigin**

*CountryOfOrigin is optional. A single instance might exist.*

The country of origin for the material.

## **CountryOfDestination**

*CountryOfDestination is optional. A single instance might exist.*

The country where the goods will be, or were, shipped to.

## **CountryOfConsumption**

*CountryOfConsumption is optional. A single instance might exist.*

The country of consumption for the material.

## Insurance

*Insurance is optional. A single instance might exist.*

Group element containing information about insurance

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## DocumentInformation

*DocumentInformation is optional. Multiple instances might exist.*

A group element containing a specification of required documents in the business process. Additional free text to be printed on documents can also be specified.

## DeliveryMessageWoodSummary


The DeliveryMessageWoodSummary contains summary information based on the line items contained in the DeliveryMessageWood document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### TotalNumberOfShipments

*TotalNumberOfShipments is mandatory. A single instance is*



*required.*

Total number of shipments referred to in a DeliveryMessage.

### (sequence)

*The sequence of items below is optional. Multiple instances might exist.*

#### TotalQuantity


*TotalQuantity is mandatory. A single instance is required.*

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

#### TotalInformationalQuantity

*TotalInformationalQuantity is optional. Multiple instances might exist.*

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line



items.

## **ProductSummary**

*ProductSummary is optional. A single instance might exist.*

Group of elements to provide summary information on product level.

## **LengthSpecification**

*LengthSpecification is optional. Multiple instances might exist.*

Length specification of the wood product.

## **QuantityDeviation**

*QuantityDeviation is optional. A single instance might exist.*

To be deprecated in a future version. Use the Quantity element with a QuantityContext of "Deviation".

## **CustomsTotals**

*CustomsTotals is optional. Multiple instances might exist.*

A grouping element for customs total information.

## **CustomsStampInformation**

*CustomsStampInformation is optional. Multiple instances might exist.*

A grouping element that organises the information for customs.

## **TermsAndDisclaimers**

*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.

---

## **DeliveryModeType [attribute]**

Provides delivery mode type that specifies if transport arrangement is needed or not.

*This item is restricted to the following list.*

### **Deliver**

Transport arrangement to be done and goods to be delivered.

### **PickUp**

Goods to be picked up; no transport arrangements are needed.

attribute	
<b>DeliveryModeType</b>	
type	deliveryModeType
default	Deliver

## DeliveryOrigin

A group item that represents the start of one leg in a route. Compare to DeliveryDestination.

The DeliveryOrigin specifies the start of one leg of the delivery.

In order to comply with the US Trade Act of 2002 you would use this element with a LocationParty/@PartyType of Port.



### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### Date

Date is optional. A single instance might exist.

A group element that contains the specification of Year, Month, and Day.

#### Time

Time is optional. A single instance might exist.

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

#### LocationParty

LocationParty is mandatory. A single instance is required.

The organization or business entity where the business event took place or will take place.

#### (choice)


[choice] is optional because of choice construct.

#### SupplyPoint

SupplyPoint is optional because of choice construct.

Grouping element that contains items describing a supply point. A SupplyPoint belongs to a LocationParty, e.g. in a DeliveryOrigin or DeliveryDestination, and describes where goods are stored and can be loaded or unloaded. A SupplyPoint can for example be a loading or unloading gate at a warehouse or a road side landing at a logging area in the forest.

#### LocationCode



*LocationCode is optional because of choice construct.*

A code used to identify a specific physical location within a site identified by a party, e.g. a loading station in a warehouse or an unloading station at a printer site.

LocationCode will be deprecated in a future version. Use SupplyPoint instead of LocationCode.

**(choice)**

*[choice] is optional because of choice construct.*

**GPSCoordinates**

*GPSCoordinates is optional because of choice construct.*

The location of the party as specified using a Global Positioning System.

**MapCoordinates**

*MapCoordinates is optional because of choice construct.*

A group item defining and containing position co-ordinates of a location.

---

## DeliveryRouteCode

A code representing the delivery route as indicated by the Agency.

**Agency [attribute]**


*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.



## DeliverySchedule

A group item defining a series of DeliveryDateWindow(s) in which specified quantities must be delivered.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DeliveryLineNumber

*DeliveryLineNumber is mandatory. A single instance is required.*

A sequential number that uniquely identifies a delivery line of the DeliverySchedule; a delivery line consists of a quantity and a date range for the delivery to take place.



#### ProductionStatus

*ProductionStatus is optional. A single instance might exist.*

A group item used to communicate the release of a delivery line number.

#### DeliveryStatus

*DeliveryStatus is optional. A single instance might exist.*

Used to communicate whether the delivery date indicated is a final date or subject to change. If subject to change the last date of change may be communicated.

#### DeliveryDateWindow

*DeliveryDateWindow is optional. Multiple instances might exist.*

A group item defining the date/time interval for delivery to take place. An element which may contain the estimated date for which delivery is expected. This date is not absolute.

#### Quantity

*Quantity is mandatory. A single instance is required.*


The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

#### InformationalQuantity

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the



invoice quantity of 20,000 pounds.

## PriceDetails

*PriceDetails is optional. A single instance might exist.*

An element that groups together price information.

## MonetaryAdjustment

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates they type of adjustment being communicated.

## DeliveryLeg

*DeliveryLeg is optional. Multiple instances might exist.*

A DeliveryLeg details the sequence, origin, transportation, and destination of each part of the delivery. More than one leg may be required if there is a change of mode, vehicle, or carrier.

Although transportation information is optional, it is strongly recommended that any transportation information available be sent.

## DeliveryScheduleReference

*DeliveryScheduleReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the delivery schedule as indicated by DeliveryScheduleReferenceType.

## AdditionalText


*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## DeliveryScheduleReference

An element detailing relevant references pertaining to the delivery schedule as indicated by



DeliveryScheduleReferenceType.

### DeliveryScheduleReferenceType [attribute]

*DeliveryScheduleReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information

previously communicated in the prefix.

Refer to DeliveryScheduleReferenceType definition for any enumerations.

## **AssignedBy [attribute]**

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.


---

## **DeliveryScheduleReferenceType [attribute]**

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an

existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.



## DeliveryShipmentBookLineItem

DeliveryShipmentBookLineItem is required. The DeliveryShipmentBookLineItem specifies an individual shipment delivery line for one PurchaseOrder and PurchaseOrder line item.

### ShipmentComplete [attribute]

*ShipmentComplete is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to ShipmentComplete definition for any enumerations.



### InstructionByType [attribute]

*InstructionByType is optional. A single instance might exist.*

Provides the type for how goods are identified on group level when instructed for loading or delivery.

Refer to InstructionByType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DeliveryShipmentLineItemNumber

*DeliveryShipmentLineItemNumber is mandatory. A single instance is required.*

Sequential number to identify individual line items within a shipment

#### PurchaseOrderInformation

*PurchaseOrderInformation is optional. A single instance might exist.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

#### PurchaseOrderLineItemNumber

*PurchaseOrderLineItemNumber is optional. A single instance might exist.*



The sequential number that uniquely identifies the PurchaseOrder line item.

## **DeliveryMessageReference**

*DeliveryMessageReference is optional. Multiple instances might exist.*

An element that identifies the relevant references pertaining to the DeliveryMessage, identified by DeliveryMessageReferenceType.

## **DocumentReferenceInformation**

*DocumentReferenceInformation is optional. Multiple instances might exist.*

A group item containing reference information applicable to a document.

## **CountryOfOrigin**

*CountryOfOrigin is optional. A single instance might exist.*

The country of origin for the material.

## **CountryOfDestination**

*CountryOfDestination is optional. A single instance might exist.*

The country where the goods will be, or were, shipped to.

## **CountryOfConsumption**

*CountryOfConsumption is optional. A single instance might exist.*

The country of consumption for the material.

## **Quantity**

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **TransportLoadingCharacteristics**

*TransportLoadingCharacteristics is optional. Multiple instances might exist.*

A group item defining how the transported items are to be loaded.

## **TransportUnloadingCharacteristics**

*TransportUnloadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be unloaded.

## **TransportOtherInstructions**

*TransportOtherInstructions is optional. Multiple instances might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

## **BillToParty**

*BillToParty is optional. A single instance might exist.*

The address where the Invoice is to be sent.

## **BookPackageInformation**

*BookPackageInformation is optional. Multiple instances might exist.*

The purpose of the BookPackageInformation structure is to clearly identify physical handling items that constitute the delivery.

BookPackageInformation is the highest level of product packaging and describes the shipping or warehousing unit.

## **Product**

*Product is optional. A single instance might exist.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **OtherDate**

*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## **SafetyAndEnvironmentalInformation**

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

---

## **DeliveryShipmentId**

Unique identifier for the shipment

<b>DeliveryShipmentId</b>	
type	s30

## DeliveryShipmentLineItem

The DeliveryShipmentLineItem specifies an individual delivery line for one order and order line item.

PackageInformation will be deprecated in the version following V2R30, it has been replaced with TransportPackageInformation.

You are encouraged to use TransportPackageInformation.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DeliveryShipmentLineItemNumber

*DeliveryShipmentLineItemNumber is mandatory. A single instance is required.*

Sequential number to identify individual line items within a shipment

#### PurchaseOrderInformation

*PurchaseOrderInformation is optional. A single instance might exist.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

#### PurchaseOrderLineItemNumber

*PurchaseOrderLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the PurchaseOrder line item.

#### DeliveryMessageReference

*DeliveryMessageReference is optional. Multiple instances might exist.*

An element that identifies the relevant references pertaining to the DeliveryMessage, identified by DeliveryMessageReferenceType.



#### DocumentReferenceInformation

*DocumentReferenceInformation is optional. Multiple instances might exist.*

A group item containing reference information applicable to a document.

#### CountryOfOrigin

*CountryOfOrigin is optional. A single instance might exist.*



The country of origin for the material.

## **CountryOfDestination**

*CountryOfDestination is optional. A single instance might exist.*

The country where the goods will be, or were, shipped to.

## **CountryOfConsumption**

*CountryOfConsumption is optional. A single instance might exist.*

The country of consumption for the material.

## **TotalNumberOfUnits**

*TotalNumberOfUnits is optional. A single instance might exist.*

The total number of units.

## **DeliveryDateWindow**

*DeliveryDateWindow is optional. Multiple instances might exist.*

A group item defining the date/time interval for delivery to take place. An element which may contain the estimated date for which delivery is expected. This date is not absolute.

## **MillProductionInformation**

*MillProductionInformation is optional. A single instance might exist.*

A grouping element that contains information about production at the mill.

## **QuantityOrderedInformation**

*QuantityOrderedInformation is optional. A single instance might exist.*

Used to identify quantity. The construct provides via InformationalQuantity the ability to provide the Quantity in another UOM. Length is also provided to further specify the quantity.

## **TransportLoadingCharacteristics**

*TransportLoadingCharacteristics is optional. Multiple instances might exist.*

A group item defining how the transported items are to be loaded.

## **TransportUnloadingCharacteristics**

*TransportUnloadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be unloaded.

## **TransportOtherInstructions**

*TransportOtherInstructions is optional. Multiple instances might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

## **SafetyAndEnvironmentalInformation**

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

## **BillToParty**

*BillToParty is optional. A single instance might exist.*

The address where the Invoice is to be sent.

## **Product**

*Product is optional. A single instance might exist.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **(choice)**

*[choice] is optional because of choice construct.*

## **PackageInformation**

*PackageInformation is optional because of choice construct.*

The purpose of the PackageInformation structure is to clearly identify physical handling items that constitute the delivery.

PackageInformation is the highest level of product packaging it describes the shipping or warehousing unit.

If you are communicating a package, usually for logistics or transport purposes, you should include the PackageType, Identifier, ItemCount, and Quantity. (Note: you still have the ability to describe the item with one of the "named" items.)

If you are communicating one of the named Items there is no need to include PackageType, Identifier, ItemCount, and Quantity.

Since either of these two approaches can be used the entire contents of this element are optional even though the parent may be required. It is expected that you will fill in the appropriate details.

## **TransportPackageInformation**

*TransportPackageInformation is optional because of choice construct.*

Information of a package used in transportation, can include several normal packages.

## **ProductSummary**

*ProductSummary is optional. A single instance might exist.*

Group of elements to provide summary information on product level.

## **LengthSpecification**

*LengthSpecification is optional. Multiple instances might exist.*

Length specification of the wood product.

## **QuantityDeviation**

*QuantityDeviation is optional. A single instance might exist.*

To be deprecated in a future version. Use the Quantity element with a QuantityContext of "Deviation".

---

## DeliveryShipmentLineItemNumber


Sequential number to identify individual line items within a shipment

<b>DeliveryShipmentLineItemNumber</b>
type nni4

---

## DeliveryStatus

Used to communicate whether the delivery date indicated is a final date or subject to change. If subject to change the last date of change may be communicated.



### DeliveryStatusType [attribute]

*DeliveryStatusType is optional. A single instance might exist.*

Indicates whether or not you are allowed to take action on the delivery or if more information is required

Refer to DeliveryStatusType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### DeliveryLastDateOfChange

*DeliveryLastDateOfChange is optional. A single instance might exist.*

The final Date and optionally Time that a line item or delivery line may be amended or cancelled by the buyer.

The final Date and optionally Time that a line item or delivery line may be amended or cancelled by the buyer. For example, the buyer can cancel each a delivery line before the DeliveryLastDateOfChange received from the seller on the OrderConfirmation.

---

## DeliveryStatusType [attribute]

Indicates whether or not you are allowed to take action on the delivery or if more information is required

attribute
<b>DeliveryStatusType</b>
type deliveryStatusType

*This item is restricted to the following list.*

### Cancelled

The delivery has been cancelled. You are not allowed to deliver this product.

### Free

You are allowed to deliver this product

### NotFree


You are not allowed to deliver this product. More information is required from the receiver.

## DeliveryTransitTime

A group item representing the number of Days and optionally Hours and Minutes between origin and destination for a DeliveryLeg.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Days

*Days is mandatory. A single instance is required.*

The qualifier of DeliveryTransitTime. More generally used to communicate duration in days.

### Hours

*Hours is optional. A single instance might exist.*

A qualifier of DeliveryTransitTime.

### Minutes

*Minutes is optional. A single instance might exist.*

A qualifier for the DeliveryTransitTime.

## Density

A group item used to communicate density target or test value according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*


The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation



*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## **TwoSigmaUpper**

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.


---

## **DepartureDate**

The required or actual date of departure.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### **Date**

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### **Time**

*Time is mandatory. A single instance is required.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

---

## DetailRangeMax


The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

### UOM [attribute]

*UOM is mandatory. A single instance is required.*

Defines the unit of measure for the value.

Refer to UOM definition for any enumerations.



## DetailRangeMin


The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

### UOM [attribute]

*UOM is mandatory. A single instance is required.*

Defines the unit of measure for the value.

Refer to UOM definition for any enumerations.



## DetailValue


A numeric value expressed in the unit of measure (UOM).

### UOM [attribute]

*UOM is mandatory. A single instance is required.*

Defines the unit of measure for the value.

Refer to UOM definition for any enumerations.



## DiameterBreastHeight

Used to report the log diameter 4.5 feet from the butt end as a measurement. Used with the LogConversionRule attribute to determine log's volume conversion to board-feet or other measure.

### (sequence)


*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin



# papiNet V2R31

---

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

## **RangeMax**

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## **DieCut [attribute]**

Either "Yes" or "No".

*This item is restricted to the following list.*

**Yes**

**No**

attribute	
<b>DieCut</b>	
type	yesNo

---

## **DieCutDescription**

Die cut description

<b>DieCutDescription</b>	
type	s255

---

## **DirectLoading [attribute]**

Specifies if the transport unit should be loaded directly with goods received on another transport unit.

*This item is restricted to the following list.*

**Yes**

**No**

attribute	
<b>DirectLoading</b>	
type	yesNo
default	No

---

## **DirectUnloading [attribute]**

Specifies if the transport unit should be unloaded directly on to a new transport unit. Certain transport units, e.g. cassettes, can be stored in warehouses a short period waiting for direct unloading.

*This item is restricted to the following list.*

**Yes**

**No**

attribute	
<b>DirectUnloading</b>	
type	yesNo
default	No

## Dirt

A group item used to communicate dirt content target or test value according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*


The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation



*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## DiscPrinting [attribute]

Disc printing

*This item is restricted to the following list.*

**Screen**

**Thermal**



## DistanceFromCore

The distance from the radius of the core. This element can be used to communicate where a mill join is located.

Compare to LengthFromCore.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## DistanceFromEdge

The distance from the edge of the paper. This element is used to communicate where the hole is.

### EdgeType [attribute]

*EdgeType is optional. A single instance might exist.*

Edge type (paper)

Refer to EdgeType definition for any enumerations.

### DisanceMeasuredTo [attribute]

*DistanceMeasuredTo is optional.*

Defines how the distance is measured from the edge of the paper to the hole.

*This item is restricted to the following list.*

#### Edge

Distance is measured to the edge of the hole.

#### Middle

Distance is measured to the middle of the hole.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax


*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## DistanceMeasuredTo [attribute]

Defines how the distance is measured from the edge of the paper to the hole.



This item is restricted to the following list:

## Edge

Distance is measured to the edge of the hole.

## Middle

Distance is measured to the middle of the hole.


---

## DistanceToNextStop

The distance to the next transportation node.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

---

## Document

A group item containing information applicable to the original document.

### DocumentName [attribute]

*DocumentName is mandatory. A single instance is required.*

Defines the name of e-Documents defined by papiNet.

Refer to DocumentName definition for any enumerations.

### DocumentType [attribute]

*DocumentType is optional. A single instance might exist.*

The type of e-Document being communicated.

Refer to DocumentType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*


#### DocumentNumber

*DocumentNumber is mandatory. A single instance is required.*

The unique identifier of the original document.

#### DocumentVersionNumber

*DocumentVersionNumber is optional. A single instance might exist.*



# papiNet V2R31

The document version number, currently BookSpecification is the only e-Document that has a Version Number.

## DocumentDate

*DocumentDate is mandatory. A single instance is required.*

The Date and optionally Time when the document that is referred to was issued.

## TransactionHistoryNumber

*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

## DocumentReference

*DocumentReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the papiNet e-Document as indicated by the DocumentReferenceType and AssignedBy.

## DocumentContent

A grouping element specifying information contained in a document.

### DocumentContentType [attribute]

*DocumentContentType is mandatory. A single instance is required.*

Specifies the type of information contained in a document.

Refer to DocumentContentType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is mandatory. A single instance is required.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### DocumentContentText

*DocumentContentTextt is optional. Multiple instances might exist.*

Text that is printed on a document.



## DocumentContentText

Text that is printed on a document.



A diagram showing a rectangular box with a header 'DocumentContentText' and a single row below it with the label 'type' and the value 's255'.

DocumentContentText	
type	s255

---

## DocumentContentType [attribute]

Specifies the type of information contained in a document.

*This item is restricted to the following list.*



A diagram showing a rectangular box with a header 'DocumentContentType' and a single row below it with the label 'type' and the value 'documentContentType'. The box is nested under a larger box labeled 'attributes'.

DocumentContentType	
type	documentContentType

### **Author**

Name of the author of the product or book

### **BasisWeight**

The weight of the paper expressed as a mass for a given surface area.

### **BoxWeight**

Weight of the filled box.

### **BrandName**

A specific product brand name for which the owner or source is specified in the "@AssignedBy" attribute.

### **Copyright**

The year of publication copyright.

### **Edition**

Identifies the version of the product for which copies were printed and published at one time; For example in book manufacturing values might be 1st, 2nd, etc

### **ExportShipMark**

An export shipment mark for identification.

### **GradeCode**

A specific product code for which the owner or source is specified in the "@AssignedBy" attribute.

### **GradeName**

A specific product name for which the owner or source is specified in the "@AssignedBy" attribute (for example, ImprovedNewsprint-45-1479).

### **Identifier**

Identifier of the individual item.

### **ISBN10**

10 digit ISBN code without dashes.

### **ISBN10Dash**

10 digit ISBN code with dashes.

### **ISBN13**

13 digit ISBN code.

**ISBN13Dash**

A 13 character ISBN with dashes.

**LotIdentifier**

A unique code used to identify a grouping of product with one set of quality statistics common to all members of that group. Synonym: Lot Number.

**PartNumber**

An equivalent to the Stock Keeping Unit (SKU) for which the owner or source is specified in the "@AssignedBy" attribute. In other words, this code fully defines the product.

**PlainText**

To be removed in a future version. Use instead "ReferenceNumber".

**PrintingNumber**

A reference to the sequential print run number.

**ProductIdentifier**

To be removed in a future version. Use instead specific product identifier types such as BrandName, GradeCode, GradeName and PartNumber.

**ProfitCenter**

Profit Center identifier.

**PubName**

The publication name.

**PurchaseOrderNumber**

The unique order identifier as designated by the customer.

**PurchaseOrderReference**

To be removed in a future version. Use instead "ReferenceNumber".

**ReferenceNumber**

An informational reference (either textual or numeric) for which the owner or source is specified in the "@AssignedBy" attribute

**RetailPrice**

Cover price of the finished product.

**TambourID**

The unique identifier of the jumbo reel (also called mother reel or Tambour).

**Title**

Proper title of a book product.

**TitleAlias**

Alternate title description for book products, usually for security purposes.

**UnitsPerCarton**

Number of units per box.

**UniversalProductIdentifier**

Unique identifier for the book, component of a book product, and many other products.

## VendorBrandName

To be removed in a future version. Use instead "BrandName" and specify owner or source is in the "@AssignedBy" attribute with enumeration "Seller".

## VendorGradeCode

To be removed in a future version. Use instead "GradeCode" and specify owner or source is in the "@AssignedBy" attribute with enumeration "Seller".

## VendorGradeName

To be removed in a future version. Use instead "GradeName" and specify owner or source is in the "@AssignedBy" attribute with enumeration "Seller".


---

## DocumentDate

The Date and optionally Time when the document that is referred to was issued.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## DocumentInformation

A group element containing a specification of required documents in the business process. Additional free text to be printed on documents can also be specified.

### DocumentType [attribute]

*DocumentType is mandatory. A single instance is required.*

Identifies the type of a document

Refer to DocumentType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### NumberOfDocuments

*NumberOfDocuments is optional. Multiple instances might exist.*

Specifies the number of documents needed.

### AdditionalText


*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

### DocumentInstruction

*DocumentInstruction is optional. A single instance might exist.*

A grouping element that specifies instructions and contents related to the creation and use of a document.



## DocumentInstruction

A grouping element that specifies instructions and contents related to the creation and use of a document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### DocumentInstructionText


*DocumentInstructionText is optional. Multiple instances might exist.*

Text that is describing instructions related to the creation and use of a document.

### DocumentContent

*DocumentContent is optional. Multiple instances might exist.*

A grouping element specifying information contained in a document.



## **DocumentName [attribute]**

Defines the name of e-Documents defined by papiNet.

*This item is restricted to the following list.*

### **Availability**

The purpose of the Availability e-Document is to provide a means to ask about the availability of the specified product. The amount of the product immediately available (on-hand) is anticipated to be returned. Optionally, the anticipated availability of the product at a point in future can be communicated.

### **BookSpecification**

The BookSpecification e-Document represents established product specifications that can be referenced by multiple transactions in the manufacturing life cycle of a product from RFQ through Invoice and subsequent reprints and/or reorders. It captures unique book manufacturing industry data elements as established by the buyer that are needed by the supplier for manufacturing.

### **BusinessAcceptance**

The receiver of a document uses the BusinessAcceptance to confirm to the sender that the document is accepted or rejected. The BusinessAcceptance can be used as a confirmation of acceptance when there is not a papiNet-designed confirmation e-Document available. Although the BusinessAcceptance is optional between two trading partners, its use is strongly recommended when it is important to get a BusinessAcceptance.

### **BusinessAcknowledgement**

An e-Document receiver uses the BusinessAcknowledgement to notify the sender that a document has been successfully presented to the receiver's ERP system. The BusinessAcknowledgement can be used to acknowledge any papiNet e-Document. Although the BusinessAcknowledgement is optional between two trading partners, its use is strongly recommended since it provides positive verification of the beginning of the transaction by the receiver.

### **Calendar**

The Calendar e-Document is intended to communicate opening times or other details for a location or locations

### **CallOff**

A CallOff is a delivery schedule for product(s). Products to be delivered can be specified by product specifications or by purchase orders. Any party as agreed in a Trading Partner Agreement can send a CallOff. Each line item in a CallOff refers either to a product included in a PurchaseOrder or to the product specifications contained in the line item. The CallOff specifies delivery schedule(s) and quantities for product(s) to be delivered. The schedule may define a specific date and/or time for delivery or include a time range. All products covered by a CallOff must be delivered to a single location.

### **CallOffWood**

A CallOffWood is a business transaction instructing the consignor (normally the seller) to despatch goods belonging to one or several orders. A CallOffWood

contains information about how the goods are to be loaded, quantities, marking instructions etc. It may also contain information about where borders are to be crossed and information concerning transport, such as name of ship and shipping agent. In cases where the CallOffWood is not used, delivery information is included in the order.

## **Complaint**

Typically, a Complaint e-Document is sent from the customer or end user to the supplier to communicate information regarding products or services. A response from the supplier is desired and corrective actions, if required. This e-Document must specify the necessary details to enable the supplier to trigger an internal process to verify whether the complaint reason corresponds to the supplier-assessed reason.

## **ComplaintResponse**

Typically, a ComplaintResponse e-Document is sent from the supplier or sender parties to the party who has originated the Complaint, or possibly to the RespondToParty. The e-Document is sent to communicate the acceptance, partial acceptance, or rejection, of the preceding complaint(s) with supporting information. Whatever the decision, this e-Document must specify how the complaint will be processed.

## **CreditDebitNote**

The CreditDebitNote e-Document is generally used by the SupplierParty to compensate or charge the trading parties (ShipToParty, BuyerParty, OtherParty, etc.) for matters outside the scope of the Invoice.

## **DeliveryInstruction**

A DeliveryInstruction can be used to instruct movement of goods to warehouses and movement of goods to virtual locations within warehouses as well as deliveries to customers. The DeliveryInstruction e-Document is designed to fulfil supply chain requirements regarding instruction for goods deliveries to Mills, Suppliers, Forwarders, Warehouse Operators, Customers, and End-Users. The DeliveryInstruction is load oriented which is very efficient when mills and suppliers move goods in large quantities between warehouses.

## **DeliveryMessage**

The DeliveryMessage e-Document enables the sender to describe the contents and configuration of a shipment at various levels of detail.

## **DeliveryMessageBook**

The DeliveryMessageBook e-Document enables the sender to describe the contents and configuration of a shipment at various levels of detail.

## **DeliveryMessageWood**

The DeliveryMessageWood e-Document enables the sender to describe the contents and configuration of a shipment at various levels of detail.

## **GoodsReceipt**

The ShipTo party, or authorised agent, sends a GoodsReceipt e-Document to the Supplier and/or to the Buyer acknowledging that a specific delivery or a number of deliveries in a given time period have been received and their status.

## **InfoRequest**

The purpose of InfoRequest e-Document is to allow the requesting party to request from the receiver party an update. The e-Documents that may be returned in response to an InfoRequest are the Availability, Calendar, InventoryStatus , OrderStatus, Planning, ProductQuality, ShipmenStatus, ShippingInstructions or Statement.

## **InventoryChange**

The purpose of the InventoryChange e-Document is to inform involved parties about changes in the inventory at a specific location. The e-Document provides information allowing the receiving party to update their systems for cost tracking, performance, and financial reporting.

## **InventoryDispositionInstructions**

The InventoryDispositionInstructions e-Document permits the owner of inventory stored at a third party location to request the inventory be destroyed, shipped to another location, held in inventory, or physically changed. The receiving party makes the requested changes to the inventory and sends an InventoryChange and ShippingInstructions, if required, to the requestor so their systems can be updated.

## **InventoryStatus**

The InventoryStatus e-Document informs involved parties about physical inventory levels at specific stock locations (warehouse, terminal, printer etc.) at a certain time (snapshot).

## **Invoice**

An Invoice e-Document can handle both debits and credits. Typically a seller sends an Invoice to a buyer after delivering the products or services specified in a PurchaseOrder or as part of an automatic replenishment agreement. Alternatively, an Invoice can be prepared by the buyer as part of a self-billing process. The Invoice is a list of the goods shipped and their quantities, or services rendered, indicating the price, terms of sale, supplemental charges, allowances, and communicates the payment required for the indicated items.

## **InvoiceWood**

An InvoiceWood e-Document can handle both debits and credits. Typically a seller sends an InvoiceWood to a buyer after delivering the products or services specified in a PurchaseOrder or as part of an automatic replenishment agreement. Alternatively, an InvoiceWood can be prepared by the buyer as part of a self-billing process. The InvoiceWood is a list of the goods shipped and their quantities, or services rendered, indicating the price, terms of sale, supplemental charges, allowances, and communicates the payment required for the indicated items.

## **LoadAvailable**

The Supplier party or authorized agent sends a LoadAvailable e-Document to the BuyerParty (consuming mill) indicating that load(s) for specific product is (are) ready on a specific date for acceptance and pickup. The LoadAvailable e-Document from the supplier may include a Shipper Load Number. This number may be used as the consuming mill's release number The Shipper Load Number is used for authorization for pick-up of load at supplier point.

## **LoadTender**

The LoadTender e-Document supports the transport booking process. Transport booking includes the following steps:

- LoadTender – more than one carrier has been informed about the upcoming transport.
- Booking – identifies a transport booking that is part of a detail transport plan, the load has been booked with a single carrier.

## **LoadTenderResponse**

The LoadTenderResponse e-Document supports the transport booking process and is used as a response e-Document to LoadTender e-Document. Transport booking includes the following steps:

- LoadTenderResponse – more than one carrier has been informed about the upcoming transport.
- BookingConfirmation – identifies a transport booking that is part of a detail transport plan, the load has been booked with a single carrier.

## **MeasuringTicket**

The MeasuringTicket e-Document specifies the details from measuring of items. Packages and loads can be measured as well as individual items in packages and loads. Products, Quantities and various measured properties can be reported. These measurements can be used as a base for calculation of billable products.

## **OrderConfirmation**

A seller sends an OrderConfirmation e-Document to a buyer after receiving a PurchaseOrder from that buyer. The e-Document contains a response to the conditions specified in the PurchaseOrder. A supplier may also send an OrderConfirmation e-Document to convey changes that the supplier has made in the order or to convey new information such as a Supplier Reference Number or Job Number.

## **OrderConfirmationWood**

A seller sends an OrderConfirmationWood e-Document to a buyer after receiving a PurchaseOrder from that buyer. The e-Document contains a response to the conditions specified in the PurchaseOrder. A supplier may also send an OrderConfirmationWood e-Document to convey changes that the supplier has made in the order or to convey new information such as a Supplier Reference Number or Job Number.

## **OrderStatus**

The OrderStatus e-Document permits the sender to report the current status of an order, specific order line items, or to report status of multiple orders based upon some specified criteria. The e-Document enables the sender to indicate a primary status as well as an additional secondary status at the order level as well as for each line and component.

## **PackingList**

The PackingList e-Document specifies the details of a shipment that is being despatched. The seller should send the PackingList e-Document in sufficient time so that the recipient can process the information before the goods arrive.

The recipient can then prepare efficiently for the receipt of the goods.

## **Planning**

The Planning e-Document provides a tool for trading partners to exchange forecasted or planned information for a specific product or event within a specified timeframe. The e-Document is designed to support a variety of business processes, which may include securing needed supplies or simply the exchange of information.

## **ProductAttributes**

The ProductAttributes e-Document provides the means to communicate information about products between business partners.

## **ProductPerformance**

The ProductPerformance e-Document is created by the product consumer in order to communicate back to the manufacturer the performance of the product. This e-Document will enable the manufacturer to focus on improvements related to product defects that create inefficiency during performance. The aggregation of performance factors by product will provide the mechanism for achieving the value aspect of the e-Document. The goal is to keep the products of the Pulp & Paper Industry attractive versus competing alternatives.

## **ProductQuality**

The ProductQuality e-Document supports the exchange of quality data for individual items. The agreed properties of the product that are exchanged can include statistical values such as minimum and maximum, standard deviation, sample size, two sigma (lower-limit, upper-limit).

## **PurchaseOrder**

A buyer sends a PurchaseOrder e-Document to a supplier to initiate a trade transaction. This e-Document, which is a request for product, usually represents a firm commitment to buy. (For one type of PurchaseOrder, called a reservation order, the PurchaseOrder is not a firm commitment to buy).

## **PurchaseOrderWood**

A PurchaseOrderWood e-Document is set up between a buyer and a seller. In some cases an agent acts on behalf of the seller or the buyer when setting up the contract. However, the contract is not valid until signed by the buyer and the seller. A PurchaseOrderWood may cover one delivery of merchandise on one occasion or cover a time period with several deliveries. This PurchaseOrderWood refers to a standardised contract form containing all legal details.

## **RFQ**

A buyer sends an RFQ e-Document to a supplier to initiate a request for quotation. This e-Document, which is a request for product information, represents a request for the supplier to provide a quotation for product availability, shipping, and price.

## **RFQResponse**

A supplier sends an RFQResponse e-Document to a buyer as a response to an RFQ e-Document from the buyer. The e-Document specifies a quotation for

product availability, shipping, and price.

## ScaleTicket

The ScaleTicket e-Document provides wood or fibre suppliers with a means to electronically incorporate scale system receiving data into their accounting systems from buying entities' back office systems.

## ShipmentStatus

The ShipmentStatus e-Document is sent to communicate the status of a shipment or consignment with references to other documents. Typically, a ShipmentStatus e-Document is sent from the forwarder or carrier to the consignor / forwarder.

## ShippingInstructions

The ShippingInstructions e-Document communicates delivery information for product(s) supported by a PurchaseOrder.

## Statement

The Statement e-Document permits the manufacturer or supplier to report the current status of an invoice, or a list of invoices based upon specified criteria. The e-Document enables the sender to indicate payment status for the invoice.

## Usage

The Usage e-Document is used to notify a supplier or buyer that material has been consumed within the end user's manufacturing process.

## Other

Other e-documents not specified by papiNet.

---

## DocumentNumber


The unique identifier of the original document.

<b>DocumentNumber</b>
type s255

---

## DocumentReference

An element detailing relevant references pertaining to the papiNet e-Document as indicated by the DocumentReferenceType and AssignedBy.



### DocumentReferenceType [attribute]

*DocumentReferenceType is mandatory. A single instance is required.*

DocumentReferenceType provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Customer", "Seller", and/or "Supplier". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date)

# papiNet V2R31

---

version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to DocumentReferenceType definition for any enumerations.

## AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*


Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy definition for any enumerations.

---

## DocumentReferenceID

Identification for the document being referenced



## DocumentReferenceIDType [attribute]

*DocumentReferenceIDType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to DocumentReferenceIDType definition for any enumerations.

## AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy definition for any enumerations.

---


## DocumentReferenceIDLineItemNumber

Line item number for a specific line of the document being referenced



## DocumentReferenceIDType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.




Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## DocumentReferenceInformation

A group item containing reference information applicable to a document.

(sequence)

*The sequence of items below is mandatory. A single instance is required.*



### DocumentReferenceID

*DocumentReferenceID is mandatory. A single instance is required.*

Identification for the document being referenced

### DocumentReferenceIDLineItemNumber

*DocumentReferenceIDLineItemNumber is optional. A single instance might exist.*

Line item number for a specific line of the document being referenced

### Date

*Date is optional. A single instance might exist.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within

# papiNet V2R31

UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## NumberOfDocumentsRequired


*NumberOfDocumentsRequired is optional. A single instance might exist.*

The number of copies of the document required.

---

## DocumentReferenceType [attribute]

DocumentReferenceType provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Customer", "Seller", and/or "Supplier". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.



Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

---

## DocumentRequired

An element that permits the listing of the documents required.

### DocumentRequiredType [attribute]

*DocumentRequiredType is mandatory. A single instance is required.*

Indicates which documents are required.


Refer to DocumentRequiredType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy definition for any enumerations.




---

## DocumentRequiredType [attribute]

Indicates which documents are required.

Many items are currently prefixed by "Buyer", "Customer", "Seller", and/or "Supplier". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.



Refer to the [referenceType](#) entry for the list of enumerations and their definitions.


---

## DocumentType [attribute]

Identifies the type of a document.

Used by DocumentInformation element

*This item is restricted to the following list.*



**ATR**

**BillOfLading**

**CertificateForPackaging**

**CIM**

**CMR**

**DeliveryNote**

**EUR1**

**Invoice**

**PackingList**

The PackingList e-Document specifies the details of a shipment that is being despatched. The seller should send the PackingList e-Document in sufficient time so that the recipient can process the information before the goods arrive. The recipient can then prepare efficiently for the receipt of the goods.

**PowerOfAttorney**

**TORG12**

**T2**

**T2L**

**UnitPaper**

**WayBill**

## DocumentType [attribute]

The type of e-Document being communicated.  
Used by Document element



*This item is restricted to the following list.*

### **Agreement**

A legally binding exchange of promises between parties that the law will enforce.

### **Approximate**

An Invoice that is created to record ownership transfer without the material physically being moved. Typically what occurs is that the buyer has agreed to take ownership of the item at a certain point in time but has not arranged for transportation. Approximate invoices are invoices that are claiming payment.

### **AvailabilityStatus**

### **BlanketOrder**

An order that communicates the same information as a StandardOrder but also indicates that the order may be completed over a period of time or, until a certain volume is achieved or, until a certain currency amount is spent.

### **Booking**

An indication that time for a service is required. For example a booking that is part of a detail transport plan.

### **BookingConfirmation**

A communication affirming the placement of the booking with a particular party.

### **CalibrationCheckLog**

A MeasuringTicketType that contains a check log with information about calibration of measuring equipment.

### **CallOff**

Defines a CallOff sent by the buyer to the seller.

### **CallOffConfirmation**

Defines a CallOff confirmation sent in response to a CallOff.

### **Claim**

A "Claim" type is used when there is a customer reaction that includes a financial compensation.

### **Complaint**

### **ConfirmingOrder**

A confirming order is used to electronically confirm an order that has not been placed electronically by the customer that is, it was placed using another mean such as fax, phone or email.

### **ConsumptionOrder**

A PurchaseOrder that is based upon consumption for a particular period of time or instance.

## **CreditNote**

Credits that are provided for amount reductions and complaints. A CreditNode will normally have a reference to an earlier issued Invoice.

## **DebitNote**

A DebitNote claims payment for additional charges. A DebitNote normally has a reference to an earlier issued Invoice.

## **DeliveryInstruction**

A DeliveryInstruction can specify many delivery events. Each event can contain quantity for one or many loads. A sequence in a DeliveryInstruction specifies all details for one event. The receiver of a DeliveryInstruction can generate many Loading Instructions from one DeliveryInstruction.

## **DeliveryMessage**

A DeliveryMessage type that contains optional routing information, quantities at the DeliveryMessageLineItem level, and details at the DeliveryMessageLineItemDetail level. The seller uses a DeliveryMessage to provide delivery details to the ship-to party and tracking information.

## **Duplicate**

To be removed in a future version. When an Invoice is reissued as a duplicate the Invoice type should be the same as on the original Invoice. Use attribute Reissued = Yes to indicate a duplicate.

## **Feedback**

A "Feedback" type is used when there is a customer reaction that doesn't include any financial compensation.

## **InitialShipmentAdvice**

A DeliveryMessage type that contains detailed routing information, quantities at the DeliveryMessageLineItem level and optionally details at the DeliveryMessageLineItemDetail level. The seller uses the InitialShipmentAdvice to provide preliminary notification of shipment routing and quantities (can be used as an advanced notice of delivery). The quantities indicated may not necessarily be delivered—for example, if there is damage in transit or the delivery is rerouted to another destination.

## **InventoryChange**

## **InventoryStatus**

## **Invoice**

A regular Invoice (referred to as an Invoice) is claims payment for products, services, and charges supplied under conditions agreed to between seller and buyer. The Invoice communicates, among other things, payment terms, payment method, and the payment amount required for one or more deliveries.

## **InvoiceSpecification**

A MeasuringTicketType that contains information about measured products including prices and amounts. This MeasuringTicketType is normally used as a detailed specification of billable or invoiced products.

## **LoadAvailable**

## **LoadAvailableConfirmation**

### **LoadedSpecification**

A DeliveryMessage type that contains a specification of loaded goods on a transport unit (e.g. container, rail wagon). A loading specification (LoadedSpecification) can contain goods belonging to many suppliers and buyers and is normally referring to a Loading Instruction.

### **LoadingInstruction**

A Loading Instruction specifies loading of transport units. A Forwarder receiving a DeliveryInstruction from a supplier can convert it into many Loading Instructions, which are sent to a Warehouse Operator. A sequence in a Loading Instruction specifies all details how to load one transport unit. A Loading Instruction can include goods from many delivery instructions and also goods belonging to many suppliers.

### **LoadingOrder**

Specifies delivery schedule, the transport booking requirements and shipping instructions, as well as the internal work order for the shipment

### **LoadingSchedule**

The schedule for transport vehicle loading.

### **LoadTender**

More than one carrier has been informed about the upcoming transport requirement (the load).

### **LoadTenderResponse**

Indicates the ability of the respondent to fulfill the load tender request.

### **MeasuringTicket**

A MeasuringTicketType that contains detailed information about measured products and items. This information can be used as a base for calculation of billable products.

### **OfficeSchedule**

The schedule for office personnel.

### **OrderStatus**

### **PackingSpecification**

A Packing Specification is a business transaction specifying the complete consignment being shipped from a consignor to a consignee. The specification describes in detail what is being shipped and how it is packed and marked.

### **PreBooking**

A requirement for a transport vehicle or unit reservation that has risen from a rough transport plan.

### **PreBookingConfirmation**

A communication of the requirement for a transport vehicle or unit reservation that has risen from a rough transport plan.

### **PrePayment**

A prepayment Invoice is used as a notification of amounts to be paid in

advance. It is not a legal Invoice claiming payment for provided products or services.

## **PriceList**

Used when sending a pricelist

## **ProductCrossReference**

Used in the exchange of ProductIdentifier cross-references for the product codes used by two trading partners

## **ProductionTicket**

A MeasuringTicketType that contains information about produced products and items. A ProductionTicket can also contain measuring information for produced items.

## **ProductProperties**

Used when sending a list of ProductAttributes

## **ProForma**

A pro-forma Invoice is not a legal Invoice claiming payment. A pro-forma Invoice is an e-Document serving as a preliminary Invoice, containing on the whole the same information as the final Invoice, but not actually claiming payment. Pro-forma invoices are typically used in a cross-border shipment for customs purposes. Can travel with the product or be sent to a broker.

## **ReleaseOrder**

A release order is used to release a product to be made. This type of order refers to a previous order or agreement, such as a reservation order, a contract, or a blanket order. A release number version which is an incremented number, is used in this type.

## **ReservationOrder**

A reservation order is used to book a paper supplier's capacity for specific quantities of specific products, but it is not yet a firm commitment to buy. Consequently, all line items of a reservation order have a ProductionStatusType of NotFree. To release one or more PurchaseOrder line items of a reservation order, a buyer can use a standard order or a release order.

## **SampleMeasuringTicket**

A MeasuringTicketType that contains detailed information about measured samples taken from e.g. a delivery.

## **SelfBillingStatement**

A SelfBillingStatement is an Invoice that is prepared by the buyer of the product (or the consumer of the service) for the provider of the product or service. The preparer will pay the Invoice.

Typically, logistics cost-charges are the services that are communicated. They are incurred during a certain period of time between the party who provides the logistics services (typically the party with a LogisticsRole of "LogisticsProvider") and the requestor of such services (typically the party with a LogisticsRole of "Consignor").

Raw materials, maintenance, repair, and operating supplies are examples of

products that can be entered on a self billing statement for products. This type of Invoice is also referred to as an invoice for "evaluated receipts" because it developed from the receiving department's evaluation of their receipts and from that creating the Invoice.

The SelfBillingStatement process exists when there is a great deal of trust between the trading partners that permits this cost savings business process.

## **ShipmentAdvice**

A DeliveryMessage type that contains a specification of goods, that are dispatched and will be delivered to a warehouse. A ShipmentAdvice can refer to a DeliveryInstruction Sequence or a CallOff, but is normally also used for notifying a receiving warehouse operator of shipments to the warehouse.

## **ShippingInstructionsConfirmation**

Confirmation of the Shipping Instruction.

## **ShippingInstructionsDistribution**

Shipping Instruction serves as a billable order for shipping product that was produced under a previous manufacturing order.

## **ShippingInstructionsPackaging**

To be deprecated in a future version. Guidance will be given to trading partners not to use this enumeration.

## **ShippingInstructionsRouting**

Shipping instructions issued in conjunction with a PurchaseOrder for shipping the product.

## **SpecOrder**

Used when the BookSpecification e-Document is intended for use with the PurchaseOrder transaction.

## **StandardOrder**

A standard order is a regular one-time order. It defines quantities for one or more products to be purchased and may also define a delivery location and date. A standard order may reference a previous agreement (for example, a quotation, a contract, or a reservation order) for information.

## **SpecRFQ**

Used when the BookSpecification e-Document is intended for use with the Request for Quote (Estimate) transaction.

## **StandardRFQ**

## **SupplierSpec**

Will be removed in a future version. Recommended not to be used.  
(Old definition: Used when the BookSpecification e-Document is intended for use by the Supplier only and is not generated by, or transmitted to the Buyer).

## **SupportSchedule**

The support schedule for transport operations.

## **ThirdPartyShipmentAdvice**

Notification of a shipment from a warehouse to a party other than the party

that ordered the product from the supplier.

## **TrialOrder**

A trial order is used whenever a seller has agreed to have a buyer sample a product. The seller needs to process this order differently from other orders, because a trial order may include a product sold at a discounted rate or even provided for free. A trial order typically is for small quantities.

## **UnloadingSchedule**

The schedule for transport vehicle unloading.

## **Waybill**

The forwarding agreement or carrying agreement that is used as a receipt for cargo and as a contract of carriage.

---

## **DocumentVersionNumber**

The document version number, currently BookSpecification is the only e-Document that has a Version Number.

<b>DocumentVersionNumber</b>	
type	s02

## DominantWavelength

Dominant wavelength

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax


*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.



## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.


## DoubleBunked [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

Yes

No




## DownGradingInfo

A grouping element that contains information about downgrading of products.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### FromProduct

*FromProduct is optional. A single instance might exist.*

Defines from which product the item is downgraded.

### ToProduct

*ToProduct is optional. A single instance might exist.*

Defines to which product the item is downgraded.

### DownGradingReason

*DownGradingReason is mandatory. Multiple instances might exist.*

A free form description of the reason for downgrading.

### QuantityInformation

*QuantityInformation is optional. A single instance might exist.*


A group item containing information about quantity and informational quantity of similar items.

## DownGradingReason

A grouping element that contains the reason for downgrading.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### DownGradingReasonCode

*DownGradingReasonCode is mandatory. A single instance is required.*

A code that specifies the reason for downgrading. The Agency responsible for the code is associated with the element.

### DownGradingReasonDescription

*DownGradingReasonDescription is optional. Multiple instances might exist.*

A free form description of the reason for downgrading.

## DownGradingReasonCode

A code that specifies the reason for downgrading. The Agency responsible for the code is associated with the element.

**Agency [attribute]**


*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.


- For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.



## DownGradingReasonDescription

A free form description of the reason for downgrading.




## Downtime

An element used to communicate when equipment is not available for manufacturing purposes.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



## DowntimeReasonCode

*DowntimeReasonCode is optional. A single instance might exist.*

A reason code created by the indicated agency for downtime.

## DowntimeDescription


*DowntimeDescription is optional. A single instance might exist.*

The description of the downtime.

---

## DowntimeDescription

The description of the downtime.



---

## DowntimeReasonCode

A reason code created by the indicated agency for downtime.

### Agency [attribute]


*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.



## DrainageResistance

A group item used to communicate drainage resistance target or test value.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.


#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*



# papiNet V2R31

---

A statistic used as a measure of dispersion in a distribution.

## **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## **TwoSigmaUpper**

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## **Drilled [attribute]**

Either "Yes" or "No".

*This item is restricted to the following list.*

**Yes**

**No**

The diagram shows a box labeled 'attribute' containing a sub-box labeled 'Drilled'. Inside the 'Drilled' box, there is a field labeled 'type' with the value 'yesNo' next to it.

---

## **DuplicationRatio [attribute]**

Duplication ratio

Any valid string

The diagram shows a box labeled 'attribute' containing a sub-box labeled 'DuplicationRatio'. Inside the 'DuplicationRatio' box, there is a field labeled 'type' with the value 'duplicationRatio' next to it.

## DVD

### DVD

#### DVDFormatType [attribute]

*DVDFormatType is optional. A single instance might exist.*

DVD format type

Refer to DVDFormatType definition for any enumerations.

#### DiscPrinting [attribute]

*DiscPrinting is optional. A single instance might exist.*

Disc printing

Refer to DiscPrinting definition for any enumerations.

#### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

##### SequenceNumber

*SequenceNumber is optional. A single instance might exist.*

##### NumberOfColours

*NumberOfColours is optional. A single instance might exist.*

The number of colours

##### ColourSpecs

*ColourSpecs is optional. A single instance might exist.*

Colour specs

##### MediaLength

*MediaLength is optional. A single instance might exist.*

Media length

##### PressPrep

*PressPrep is optional. Multiple instances might exist.*

Press preparation information

##### CDPackaging


*CDPackaging is mandatory. One instance is required, multiple instances might exist.*

CD Packaging

##### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.




## DVDFormatType [attribute]

DVD format type

*This item is restricted to the following list.*

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8



## eAttachment

eAttachment enables the sender to provide information about attachments to the document.

Note: An element "e-Attachment" also exists. papiNet will no longer use hyphens in our element and attribute names as this causes issues with BizTalk.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### AttachmentFileName

*AttachmentFileName is optional. Multiple instances might exist.*

The name of the attached file.

#### NumberOfAttachments


*NumberOfAttachments is optional. A single instance might exist.*

NumberOfAttachments indicates the number of attachments enclosed in the e-Document

#### URL

*URL is optional. Multiple instances might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.



## e-Attachment

e-Attachment enables the sender to provide information about attachments to the document.

Note: BizTalk users may have problems in processing this element. See the papiNet FAQs (papiNet.org) for more information.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### AttachmentFileName

AttachmentFileName is optional. Multiple instances might exist.

The name of the attached file.

#### NumberOfAttachments


NumberOfAttachments is optional. A single instance might exist.

NumberOfAttachments indicates the number of attachments enclosed in the e-Document

#### URL

URL is optional. Multiple instances might exist.

Universal Resource Locator. While typically a web address you could use this field to hold an email address.



## Edge

Describes the finishing of the edge of the board.

### EdgeType [attribute]

EdgeType is optional. A single instance might exist.

Edge type (plywood)

Refer to EdgeType definition for any enumerations.

### EdgeLocation [attribute]

EdgeLocation is optional. A single instance might exist.

Location of edge of a sheet or board, (e.g. top/bottom/left/right).


Refer to EdgeLocation definition for any enumerations.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### EdgeMachiningProfile

EdgeMachiningProfile is optional. A single instance might exist.



The edge machining profile.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## Edge

Describes the finishing of the edge of the board.

### EdgeType [attribute]

*EdgeType is optional. A single instance might exist.*

Edge type (plywood)

Refer to EdgeType definition for any enumerations.

### EdgeLocation [attribute]

*EdgeLocation is optional. A single instance might exist.*

Location of edge of a sheet or board, (e.g. top/bottom/left/right).

Refer to EdgeLocation definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### EdgeMachiningProfile


*EdgeMachiningProfile is optional. A single instance might exist.*

The edge machining profile.

### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## EdgeFinish

The finish applied to the edge.

*This item is restricted to the following list.*

**Trimmed**

**Rough**

**Deco**

**Stained**



## Guided

---

### EdgeLocation [attribute]

Location of edge of a sheet or board, (e.g. top/bottom/left/right).

*This item is restricted to the following list.*

#### North

Top

#### South

Bottom

#### East

Right

#### West

Left

attribute
<b>EdgeLocation</b>
type   plywoodOSBEdgeLocationType

---

### EdgeLocationType [attribute]

Edge location type.

*This item is restricted to the following list.*

#### Foot

Lowest part of the book.

#### Head

Top part of the book.

#### Margin

The blank space bordering the written part of a book.

#### Spine

Hinged back of the book.

#### Thumb

Front edge of the book.

attribute
<b>EdgeLocationType</b>
type   edgeLocationType

---

### EdgeMachiningProfile

The edge machining profile.

<b>EdgeMachiningProfile</b>
type   s30

## EdgePaddable [attribute]

Refers to the process of applying edge padding glue or adhesive (Yes) or not (No). A liquid adhesive mixture which when brushed or sprayed onto the side of a pile of paper binds the sheets together along one edge, thus forming a pad.

attribute	
<b>EdgePaddable</b>	
type	yesNo

*This item is restricted to the following list.*

**Yes**

**No**

---

## EdgeType [attribute]

Edge type (paper)

*This item is restricted to the following list.*

**Bottom**

**Foot**

**Head**

**Left**

**Margin**

**Right**

**Spine**

**Thumb**

**Top**

attribute	
<b>EdgeType</b>	
type	edgeType

---

## EdgeType [attribute]

Edge type (plywood)

*This item is restricted to the following list.*

**ShipLap**

**SquareEdge**

**TongueAndGroove-FullFace**

**TongueAndGroove-ScantFace**

attribute	
<b>EdgeType</b>	
type	plywoodOSBEdgeType

---


## Email

The primary business email address of the individual associated with the ContactName.

<b>Email</b>	
type	email

## Embossing

Embossing requirements for sheets and reels.  
Embossing involves a physical deformation of the paper surface as part of the conversion process.  
Embossing is applied either in-line (directly after the paper machine) or off-line. Refer to the attribute FinishType for additional information.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### EmbossingCode

*EmbossingCode is mandatory. A single instance is required.*

A code to identify the type of Embossing.

#### EmbossingDescription

*EmbossingDescription is optional. Multiple instances might exist.*


A description of the embossing.

## EmbossingCode

A code to identify the type of Embossing.

### Agency [attribute]

*Agency is mandatory. A single instance is required.*



Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.


## EmbossingDescription

A description of the embossing.




## EndCaps

A cover to protect the ends of the reel, usually circle shaped and made from Kraft paper or plywood.



## EndIdentifierRange

A group element that identifies the ending item identifier in the range of items that contributed to the aggregated measurements for the range.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Identifier

*Identifier is mandatory. A single instance is required.*

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.

## EndsDiscountInformation


Rule for calculating the ends discount, expressed by a code.

### EndsDiscountRule [attribute]

*EndsDiscountRule is optional. A single instance might exist.*

The rule applied for price reduction for product ends

Refer to EndsDiscountRule definition for any enumerations.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### EndsLengthMax

*EndsLengthMax is optional. A single instance might exist.*

Maximum length to be considered as ends.

### EndsPermittedPercent

*EndsPermittedPercent is optional. A single instance might exist.*

The amount of the goods in percentage to be considered as ends.

## EndsDiscountPercent

*EndsDiscountPercent is optional. A single instance might exist.*

The discount percentage agreed between the seller and the buyer.


---

## EndsDiscountPercent

The discount percentage agreed between the seller and the buyer.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## EndsDiscountRule [attribute]

The rule applied for price reduction for product ends

*This item is restricted to the following list.*

### NoDiscount

No Discount

### TotalVolume

Discount based on total volume of product

### TotalVolumeOverPermittedPercent


Discount based on total volume of product in excess of a permitted percent



---

## EndsheetCopyDescription

End sheet copy description



## EndsheetInformation

End sheet information.

### EndsheetType [attribute]

*EndsheetType is optional. A single instance might exist.*

End sheet type

Refer to  
EndsheetType  
definition for any enumerations.

### EndsheetLocationType [attribute]

*EndsheetLocationType is optional. A single instance might exist.*

End sheet location type

Refer to EndsheetLocationType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### EndsheetCopyDescription

*EndsheetCopyDescription is optional. A single instance might exist.*

End sheet copy description

#### EndsheetMaterials

*EndsheetMaterials is optional. A single instance might exist.*

End sheet materials.

#### EndsheetReinforcementMaterials


*EndsheetReinforcementMaterials is optional. A single instance might exist.*

End sheet reinforcement materials

#### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## EndsheetLocationType [attribute]

End sheet location type

*This item is restricted to the following list.*

### Front

End sheet is located only in the front of the ream

### Back

End sheet is located only in the back of the ream



## FrontAndBack


End sheet is located at both the front and the back of the ream

## EndsheetMaterials

End sheet materials.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### BindingMaterialCharacteristics

*BindingMaterialCharacteristics is mandatory. A single instance is required.*

Binding Material Characteristics

### AdditionalText


*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## EndsheetReinforcementMaterials

End sheet reinforcement materials

### EndsheetReinforcementType



### [attribute]

*EndsheetReinforcementType is optional. A single instance might exist.*

End sheet reinforcement type

Refer to EndsheetReinforcementType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### BindingMaterialCharacteristics

*BindingMaterialCharacteristics is mandatory. A single instance is required.*

Binding Material Characteristics

### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## EndsheetReinforcementType [attribute]

End sheet reinforcement type

*This item is restricted to the following list.*

**Concealed**

End sheet reinforcement is hidden

**Exposed**

End sheet reinforcement is visible



---

## EndsheetType [attribute]

End sheet type


*This item is restricted to the following list.*

**Blank**

**Printed**

**SelfEnding**

**UniformStateLabel**



---

## EndsLengthMax

Maximum length to be considered as ends.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**Value**

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

**RangeMin**


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

**RangeMax**

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)




## EndsPermittedPercent

The amount of the goods in percentage to be considered as ends.

### (sequence)

The sequence of items below is mandatory. A single instance is required.



### Value

Value is mandatory. A single instance is required.

A numeric value expressed in the unit of measure (UOM).

### RangeMin

RangeMin is optional. A single instance might exist.

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

RangeMax is optional. A single instance might exist.

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## EndUserParty

The party using, consuming, or converting the product. For example, a printer using paper reels for a print job for a publisher. The final ShipTo destination for a product is normally to the end user's facilities.

### LogisticsRole [attribute]


LogisticsRole is optional. A single instance might exist.

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.

### (sequence)

The sequence of items below is mandatory. A single instance is required.



### PartyIdentifier

PartyIdentifier is optional. Multiple instances might exist.

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

### NameAddress

*NameAddress is mandatory. A single instance is required.*

A group item containing name and address of an organisation or business entity.

## URL

*URL is optional. A single instance might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

## CommonContact

*CommonContact is optional. Multiple instances might exist.*

Identifies a specific individual associated with the party.

---

## EndUses

A text element used to express in human readable form a list of applicable end uses for a product.


Examples of end uses are:

Magazine

Book

Commercial print

etc



## Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

---

## Error

A group item that details the errors that are delaying processing on an original document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ErrorCode


*ErrorCode is optional. A single instance might exist.*

An optional code used to describe why an original document could not be processed

#### ErrorSeverity

*ErrorSeverity is optional. A single instance might exist.*

An optional indicator as to whether an error is business content related or whether it is technical in nature. Use of this item is governed by a Trading Partner agreement.



## ErrorDescription

*ErrorDescription is mandatory. A single instance is required.*

A textural description of why an original document could not be processed

## ErrorReference

*ErrorReference is optional. Multiple instances might exist.*

An item detailing relevant references (such as a PurchaseOrder Line Item) pertaining to the error. The type of reference is identified by the ErrorReferenceType attribute.

---

## ErrorCode

An optional code used to describe why an original document could not be processed

### Agency [attribute]


*Agency is optional. A single instance might exist.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.


Refer to Agency definition for any enumerations.



---

## ErrorDescription

A textural description of why an original document could not be processed



---

## ErrorReference

An item detailing relevant references (such as a PurchaseOrder Line Item) pertaining to the error. The type of reference is identified by the ErrorReferenceType attribute.

### ErrorReferenceType [attribute]

*ErrorReferenceType is mandatory. A single instance is required.*


Provides a contextual explanation of the specific reference identifier.

Refer to ErrorReferenceType for any enumerations.

### AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a




reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## ErrorReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.




Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

---

## ErrorSeverity

An optional indicator as to whether an error is business content related or whether it is technical in nature. Use of this item is governed by a Trading Partner agreement.




---

## EstimatedArrivalDate

An estimation of the arrival date.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.


hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however,

within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

---

## EvenSpacing

The EvenSpacing element is used to communicate the hole-spacing that is equivalent between the holes. The initial spacing between the paper edge and the first hole is handled using the DistanceFromEdge element.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).


---

## EventDate

The date the incident or delay on press was recorded.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*


A group element that contains the specification of Year, Month, and Day.

---

## EventType [attribute]

The type of transportation event that the DeliveryLeg represents.

*This item is restricted to the following list.*



### Historical

A historical transport.

### Current

A current transport.

### Future


A future transport.

### Return

To be removed in a future version. Use instead attribute TransportContextType for Return transports.

## ExchangeRate

The exchange rate as of the date included in the element.



### ExchangeRateType [attribute]

*ExchangeRateType is mandatory. A single instance is required.*

Defines the nature of the exchange rate

Refer to ExchangeRateType definition for any enumerations.

### CurrencyFromType [attribute]

*CurrencyFromType is optional. A single instance might exist.*

The from currency in an exchange.

Refer to CurrencyFromType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### (choice)

*[choice] is optional because of choice construct.*

#### CurrencyValue

*CurrencyValue is optional because of choice construct.*

The amount in the referenced currency as defined by the CurrencyType attribute.

#### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### MinCurrencyValue

*MinCurrencyValue is mandatory. A single instance is required.*

The lower range of the allowed currency amount.

#### MaxCurrencyValue

*MaxCurrencyValue is mandatory. A single instance is required.*

The upper range of the allowed currency amount..

### Date

# papiNet V2R31

*Date is optional. A single instance might exist.*

A group element that contains the specification of Year, Month, and Day.

## ExchangeRateType [attribute]

Defines the nature of the exchange rate


*This item is restricted to the following list.*

### Fixed

A fixed exchange rate

### Float

an exchange rate that floats and is locked in at a particular point in time.



## ExcitationPurity

Excitation purity

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*


Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### DetailValue



# papiNet V2R31

---

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

## **DetailRangeMin**

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

## **DetailRangeMax**

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

## **StandardDeviation**

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## **TwoSigmaUpper**

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.


---

## **ExLog**

Describes the cutting pattern of the log.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### **Value**

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).


---

## ExtraFeature

A special or extra feature that the label has or needs.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### ProductIdentifier

*ProductIdentifier is optional. A single instance might exist.*

Used to communicate the code of the article, in a variety of formats designated by the type.

### ExtraFeatureDescription


*ExtraFeatureDescription is optional. A single instance might exist.*

The definition of the extra feature.

---

## ExtraFeatureDescription

The definition of the extra feature.




---

## Face [attribute]

Used to describe which side (or face) of the product that the grade is applicable to.

*This item is restricted to the following list.*



### Face1

The grade is applicable to the top side of the product.

### Face2

The grade is applicable to the bottom side of the product.


### Both

The grade is applicable to both the top and the bottom side of the product.

---

## Fax

The primary business fax number of the individual associated with the ContactName.



## FibreClassification

A group item used to communicate fibre classification according to the specified classification scheme.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*


The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation



*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

## FibreLength

A group item used to communicate fibre length target or test value according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.


Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.



## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### **DetailValue**

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### **DetailRangeMin**

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

### **DetailRangeMax**

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

### **StandardDeviation**

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

### **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

### **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

### **TwoSigmaUpper**

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## **FibreSource [attribute]**

Communicates the source of the pulp fibre

*This item is restricted to the following list.*

**Acacia**

**Ash**

**Aspen**


**Bagasse**

**Bamboo**

**Basswood**

**Beech**

**Birch**



Blackgum  
Buckeye  
Butternut  
Cedar  
Cherry  
Cottonwood  
Cypress  
DouglasFir  
Elm  
Esparto  
Eucalyptus  
Fir  
Flax  
Hemlock  
Hemp  
Hickory  
Jute  
Larch  
Locust  
Magnolia  
Manilkara  
Maple  
MixedTropicalHardwood  
NorthernMixedHardwood  
Paulonia  
Persea  
Pine  
Poplar  
Radiata  
Rag  
RedOak  
Redwood  
Rope  
SouthernMixedHardwood  
SouthernSoftwood  
Spruce  
Sycamore

- Straw
- Tanoak
- Walnut
- WhiteOak
- Other

## FinishedSize

Finished size

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### Length

Length is optional. A single instance might exist.

The length of the object.

#### Width

Width is optional. A single instance might exist.

The width of the object.

#### Height

Height is optional. A single instance might exist.

The height of the object.

#### FlapWidth


FlapWidth is optional.

The width of a flap.

#### AdditionalText

AdditionalText is optional. Multiple instances might exist.

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## FinishPrep

Finish prep


### FinishPrepOutputType [attribute]

FinishPrepOutputType is optional. A single instance might exist.

Finish Prep Output Type

Refer to FinishPrepOutputType definition for any enumerations.

### (sequence)



The sequence of items below is mandatory. A single instance is required.

## FinishPrepInput

*FinishPrepInput is mandatory. One instance is required, multiple instances might exist.*

Finish prep input

---

## FinishPrepInput


Finish prep input

### MediaType [attribute]

*MediaType is optional. A single instance might exist.*

The type of media

Refer to MediaType definition for any enumerations.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### FinishPrepInputType

*FinishPrepInputType is mandatory. A single instance is required.*

Finish Prep Input Type

Refer to FinishPrepInputType definition for any enumerations.

---

## FinishPrepInputType

Finish Prep Input Type

*This item is restricted to the following list.*

**4PageImposedFilm**

**8PageImposedFilm**

**ApplicationFiles**

**Bookmap**

**CameraCopy**

**CopyBook**

**DuplicateStrip**

**ElectronicFiles**


**ElectronicGraphic**

**Film**

**FilmPageNegatives**

**FilmPagePositives**

**IllustrationFilm**



NegativeImposedPlateMakingFilm

Originals

OriginalArt

Other

Overtakes

PageProof

PDF

PositiveImposedPlateMakingFilm

RachwalFilm

ReflectiveArtBoard

ReproProof

RestripSuppliedFlats

TearSheet

Transparencies

---

## FinishPrepOutputType [attribute]

Finish Prep Output Type


*This item is restricted to the following list.*

**DirectToFilm**

**DirectToPlate**

**DirectToPress**

**Film**



---

## FinishSpecs

Finish specifications

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**Coating**

*Coating is optional. Multiple instances might exist.*


Coating

Refer to Coating definition for any enumerations.

**DecorationSpecs**


*DecorationSpecs is optional. Multiple instances might exist.*

Decoration specifications



## FinishType [attribute]

Defines the finish of a sheet of paper, which means the condition of its surface (refer to Embossing for more information).



Finishes may be produced on or off machine. Finishes that are created off-machine are called embossed. (Embossing is a child element of ReelConversionCharacteristics and SheetConversionCharacteristics.)

Note:

Embossed" as a finish type is just a generalized choice for one of the more specific choices listed.

Unsupercalendered" as a finish type would be indicated by not communicating a finish type.

*This item is restricted to the following list.*

### **Bond**

Grade of writing or printing paper where strength, durability, and permanence are essential requirements.

### **Clear**

Finish process results in a clear coating.

### **CustomTint**

Requires the manufacturer to add a color to the coating process in order to create a custom colored coating.

### **Dull**

A paper surface finish lacking gloss and/or lustre; generally refers to an intermediate gloss of coated papers or to printed ink films.

### **English**

A surface finish for book papers with a smoother, more uniform surface than machine finish.

### **Gloss**

A paper surface finish that is highly reflective.

### **Hazy**

Finish process results in a hazy coating.

### **HighGloss**

Sheen on dry finish that is full gloss.

### **Laid**

A paper surface finish that has a watermark pattern resulting in parallel lines in both the machine and cross machine directions of the web of paper.

### **Linen**

An embossed finish to simulate the pattern originally obtained by pressing paper between sheets of linen cloths.

**Machine**

A paper surface that has no special finish—in other words, the paper is as it comes off the machine.

**Matte**

A non-glossy paper surface finish found on an uncoated sheet of paper or attained by coating without super calendering; this is the least glossy paper surface available.

**Metalized**

Finish process uses a custom metallic coating.

**Satin**

Paper surfaces finish lacking gloss, generally intermediate to a matte finish and a dull finish.

**SCA**

A super-calendered (SC) Grade A finish is the highest level of print gloss and smoothness of the super-calendered types.

**SCB**

A super-calendered (SC) Grade B finish with a mid level of print gloss and smoothness of the super-calendered types.

**SCC**

A super-calendered (SC) Grade C finish is the lowest level of print gloss and smoothness of the super-calendered types.

**ScuffResistant**

Wear-resistant finish to prevent scratching and marring.

**Silk**

A smooth, delicately embossed finished paper with sheen. Also called Satin.

**Silver**

Finish process uses a silver-color metallic coating.

**Smooth**

A paper surface finish mostly free of roughness.

**SoftGloss**

A paper surface finish similar to a matte but with a higher printed gloss; smoother than a matte finish.

**TransparentBlue**

Finish process adds the color blue to the clear coating material.

**Vellum**

A full toothy, relatively rough finish surface for uncoated text or book papers; generally intermediate in smoothness to an antique (very rough) finish and a regular or smooth finish.

**Velvet**

A smooth, delicately embossed finished paper with sheen. Similar to silk.

---

## FireTreatment

Fire treatment

### FireTreatmentType [attribute]

*FireTreatmentType is optional. A single instance might exist.*

Fire treatment type. Define the class (surface spread of flame) of fire treatment.

Refer to FireTreatmentType definition for any enumerations.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



---

## FireTreatmentType [attribute]

Fire treatment type. Define the class (surface spread of flame) of fire treatment.

*This item is restricted to the following list.*

**FireTreated**

**Other**



---

## FlapLocation [attribute]

Flap location

*This item is restricted to the following list.*

**Back**

Flap is located at the back

**Front**

Flap is located at the front

**FrontAndBack**

Flap is located at the back and at the front



## FlapWidth

The width of a flap.

### FlapLocation [attribute]

*FlapLocation is mandatory. A single instance is required.*

Flap location

Refer to FlapLocation definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)




## FlatAmountAdjustment

A group item that contains flat adjustment amount information.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### AdjustmentPercentage

*AdjustmentPercentage is optional. A single instance might exist.*

A percentage, either negative or positive, that is applied to either the price, or a starting amount to determine the value of the particular MonetaryAdjustment.

### AdjustmentFixedAmount

*AdjustmentFixedAmount is optional. A single instance might exist.*

A fixed monetary amount, either negative or positive, that is the value of the adjustment being applied in an instance of the MonetaryAdjustment structure.

## FlatSize

Flat size

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### Length

*Length is optional. A single instance might exist.*

The length of the object.

### Width


*Width is optional. A single instance might exist.*

The width of the object.

### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## Floor

Defines parts and complete flooring systems.

**(choice)**

*[choice] is optional because of choice construct.*

### FloorPanel

*FloorPanel is optional because of choice construct.*

Describes the flooring surface.

### FloorPackage


*FloorPackage is optional because of choice construct.*

Describes the combination of flooring surface and supporting structures.

### FloorTruss

*FloorTruss is optional because of choice construct.*

Describes the supporting material under flooring surface.



## FloorLocationType [attribute]

Floor Location Type


*This item is restricted to the following list.*

### Above

The floor is located above the product

### Below

The floor is located below the product



## FloorPackage

Describes the combination of flooring surface and supporting structures.

FloorPackage	
type	s60

---

## FloorPanel

Describes the flooring surface.

FloorPanel	
type	s60

---

## FloorTruss

Describes the supporting material under flooring surface.

FloorTruss	
type	s60

---

## Folded [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

- Yes**
- No**

attribute	
Folded	
type	yesNo

## Folding

A group item used to communicate folding endurance target or test value according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*


The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation



*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## Foot

Foot

### Bleed [attribute]

*Bleed is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Bleed definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax


*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

#### AdditionalText

*AdditionalText is optional. A single instance might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific



elements.

## ForestWood

A grouping element with information about characteristics for Forest Wood products.

### ForestWoodType [attribute]

*ForestWoodType is mandatory. A single instance is required.*

Defines the type of product for Forest Wood.

Refer to ForestWoodType definition for any enumerations.

### ForestWoodItemType [attribute]

*ForestWoodItemType is mandatory. A single instance is required.*

Defines detail type of items for Forest Wood product types.

Refer to ForestWoodItemType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### TreeSpeciesGroup

*TreeSpeciesGroup is optional. A single instance might exist.*

A grouping element that details information used for describing tree species.

#### ForestWoodClass

*ForestWoodClass is optional. Three instances might exist.*

A grouping element that details information used for describing classes of Forest Wood based on some product properties.

#### ForestWoodCharacteristics

*ForestWoodCharacteristics is optional. A single instance might exist.*

A grouping element that contains characteristics of the Forest Wood product.


#### ForestWoodPackagingCharacteristics

*ForestWoodPackagingCharacteristics is optional. A single instance might exist.*

A grouping element that contains information about packaging of the Forest Wood product.

#### ForestWoodProcessingCharacteristics

*ForestWoodProcessingCharacteristics is optional. A single instance might exist.*



A grouping element that contains information about processing of the Forest Wood product.

## SafetyAndEnvironmentalInformation


*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

---

## ForestWoodCharacteristics

A grouping element that contains characteristics of the Forest Wood product.



**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### PropertyValue


*PropertyValue is optional. Multiple instances might exist.*

Specifies a value for a property of an item. The property is defined by the attribute PropertyType. The attribute MeasuringMethod and AssignedBy can be used to clarified details for a how a property is measured or calculated, e.g. Diameter for a saw log can be measured "Under Bark" or "Over Bark". The attribute MeasuringMethodType defines how the value is created, e.g. measured automatically, calculated etc. The attribute IsAverageValue Indicates if the value is an average value or not.

---

## ForestWoodClass

A grouping element that details information used for describing classes of Forest Wood based on some product properties.



### ForestWoodClassType [attribute]

*ForestWoodClassType is mandatory. A single instance is required.*

Defines the type of class for Forest Wood.

Refer to ForestWoodClassType definition for any enumerations.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### ForestWoodClassCode

*ForestWoodClassCode is mandatory. A single instance is required.*

A code defining the class of Forest Wood.

### ForestWoodClassDescription

*ForestWoodClassDescription is optional. Multiple instances might exist.*

A text description of the class for Forest Wood.

---

## ForestWoodClassCode

A code defining the class of Forest Wood.

### Agency [attribute]


*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.


Refer to Agency definition for any enumerations.



---

## ForestWoodClassDescription

A text description of the class for Forest Wood.



---

## ForestWoodClassType [attribute]

Defines the type of class for Forest Wood.

*This item is restricted to the following list.*

### DiameterClass

The class is based on the diameter of items.

### LengthClass

The class is based on the length of items.

### QualityClass

The class is based on the quality of items.



---

## ForestWoodItemType [attribute]

Defines detail type of items for Forest Wood product types.

*This item is restricted to the following list.*

### LongLog

A cut portion of a stem that is classified as being long.

### ShortLog



A cut portion of a stem that is classified as being short.


## Stem

A felled tree crosscut at the top with all branches removed.

---

## ForestWoodPackagingCharacteristics

A grouping element that



contains information about packaging of the Forest Wood product.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PackagingCodeSpecification


*PackagingCodeSpecification is optional. Multiple instances might exist.*

A grouping element specifying code and description for packaging details.

---

## ForestWoodProcessingCharacteristics

A grouping element that



contains information about processing of the Forest Wood product.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ProcessingCodeSpecification

*ProcessingCodeSpecification is optional. Multiple instances might exist.*

A grouping element specifying code and description for processing details.

---

## ForestWoodType [attribute]

Defines the type of product for Forest Wood..

*This item is restricted to the following list.*



### Bark

Outer covering of the stem and branches of trees (tree bark). Bark from industrially processed logs or trees.

### BioEnergyChips

Wood-based chips for bioenergy.

### BioEnergySmallTree

Small-sized trees which have not been processed, usually used for energy purposes.

### BoardWood

Boards and side cuts used for industrial processes or bioenergy.

## **Firewood**

Firewood produced for heating.

## **IndustrialChips**

Chips coming as by-product from industrial manufacturing processes, usually used for pulp or paper making.

## **IndustrialReject**

Wood rejects from manufacturing processes. It is used as raw material in other industrial processes or for bioenergy.

## **LoggingResidue**

Woody biomass residues which are created during timber harvesting. They include tree tops and branches. More information can be found in standard CEN/TS 14588:2003.

## **OtherWoodEnergy**

Other wood based energy products.

## **Pellets**

Pellets produced for heating.

## **RecycledWood**

Recycled or waste wood, usually used for energy purposes.

## **Roundwood**

Felled trees crosscut at the top, with all branches removed, that may or may not have been further crosscut.

Examples of Roundwood products are saw logs, pulpwood logs, tree length logs, stems, poles and other similar products that have been harvested in the forest but not processed industrially.

## **Sawdust**

Sawdust from industrial manufacturing processes.

## **Stump**

Portion of the tree that remains above and below ground after felling of the tree.

## **Tree**

Tree that has not been delimbed and not cut into logs.

## Formation

A group item used to communicate sheet formation target or test value according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*


The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation



*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## ForwarderParty

The trading partner involved in the forwarding of the shipment.

### LogisticsRole [attribute]

*LogisticsRole is optional. A single instance might exist.*

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### PartyIdentifier

*PartyIdentifier is optional. Multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

### NameAddress

*NameAddress is mandatory. A single instance is required.*


A group item containing name and address of an organisation or business entity.

### URL

*URL is optional. A single instance might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

### CommonContact



*CommonContact is optional. Multiple instances might exist.*



Identifies a specific individual associated with the party.

## FountainSolutionConductivity

Electrical measure of fountain solution measured in micro – siemens.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*



The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## FountainSolutionpH

Measurement of the acidic properties of the fountain solution.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## Freeness

Freeness

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).


#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*



# papiNet V2R31

---

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

## **StandardDeviation**

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## **TwoSigmaUpper**

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## **FreightPayableAt**

The location at which freight charges are calculated.

<b>FreightPayableAt</b>	
type	s40

## Friction

A group item used to communicate static and kinetic friction target or test value according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*


The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation



# papiNet V2R31

---

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## **TwoSigmaUpper**

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## **From**

The beginning point of a timeperiod.

<b>From</b>
type time

## FromProduct


Defines from which product the item is downgraded.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

### (sequence)

The sequence of items below is mandatory. One instance is required, multiple instances might exist.



### ProductIdentifier


*ProductIdentifier is mandatory. A single instance is required.*

Used to communicate the code of the article, in a variety of formats designated by the type.

### ProductDescription

*ProductDescription is optional. Multiple instances might exist.*

An element used to communicate a human readable description of the product in the language specified by the Language attribute.



### Classification

*Classification is optional. Multiple instances might exist.*

A group item that details the product classification according to a particular organization's scheme. An item across multiple classifications would still be recognized as the same item. Examples of some product classifications are: Containerboard, Pulp-Dissolving, or Newsprint.

### (choice)

*[choice] is optional because of choice construct.*

### BookManufacturing

*BookManufacturing is optional because of choice construct.*

BookManufacturing is a group element that contains the elements that describe the book manufacturing process.

### ForestWood

*ForestWood is optional because of choice construct.*

A grouping element with information about characteristics for Forest Wood products.

### LabelStock

*LabelStock is optional because of choice construct.*

# papiNet V2R31

---

LabelStock contains the attributes and characteristics that define the label stock product.

## Paper

*Paper is optional because of choice construct.*

A group item defining the characteristics of the paper product.

## Pulp

*Pulp is optional because of choice construct.*

A group item defining the characteristics of pulp that are not dependent on a particular conversion process.

## RecoveredPaper

*RecoveredPaper is optional because of choice construct.*

A group item defining the characteristics of recycled fibre that are not dependent on a particular conversion process.

## VirginFibre

*VirginFibre is optional because of choice construct.*

Virgin Fibre

## WoodProducts

*WoodProducts is optional because of choice construct.*

A grouping element for all wood products.


---

## GeneralLedgerAccount

The general ledger account to be referenced for the item.

### Agency [attribute]

*Agency is optional. A single instance might exist.*



Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.


---

## Gimmick

Gimmick

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## Gloss

A group item used to communicate specular gloss target or test value according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue


*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent



of this element.

## DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

## StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## GlueExposure

Exposure class as defined by NIST standards and indicated in the grade stamp.

*This item is restricted to the following list.*

**Exterior**

**Interior**

**Exposure1**

**Exposure2**

GlueExposure	
type	plywoodOSBExposureClassType

---

## GlueExposure


A grouping element that is used to specify the standard concerning glueing and other details about gluing.

### Agency [attribute]

*Agency is mandatory.*

*A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a



recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### **GlueExposureID**

*GlueExposureID is optional. Multiple instances might exist.*

Exposure class as defined by NIST standards and indicated in grade stamp.

Refer to GlueExposureID definition for any enumerations.

### **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **GlueExposureID**

Exposure class as defined by NIST standards and indicated in grade stamp.

*This item is restricted to the following list.*

**Exterior**

**Interior**

**Exposure1**

**Exposure2**

**Other**

GlueExposureID	
type	glueExposureIDType

---

## **GoodsLoadingPrinciple [attribute]**

Defines principles for how goods are picked from warehouse and loaded

*This item is restricted to the following list.*

**FirstInFirstOut**

Goods to be picked and loaded on a first in and first out basis. The oldest goods stored into warehouse to be picked first.

**LastInFirstOut**

Goods to be picked and loaded on a last in and first out basis. The latest goods stored into warehouse to be picked first

**Random**

Goods to be picked and loaded in any order


GoodsLoadingPrinciple	
attribute	
type	inventoryRotationType
default	FirstInFirstOut

## GoodsReceipt

The GoodsReceipt element is the root element for the GoodsReceipt e-Document.

The ShipTo party, or authorised agent, sends a GoodsReceipt e-Document to the Supplier and/or to the Buyer acknowledging that a specific delivery or a number of deliveries in a given time period have been received and their status.

GoodsReceipt



### GoodsReceiptStatusType [attribute]

*GoodsReceiptStatusType is mandatory. A single instance is required.*

Defines the status of the entire GoodsReceipt e-Document at root level

Refer to GoodsReceiptStatusType definition for any enumerations.

### GoodsReceiptAcceptance [attribute]

*GoodsReceiptAcceptance is mandatory. A single instance is required.*

Defines the state of the goods received as compared to the DeliveryMessage specifications. The enumeration list is the list of choices that apply to the GoodsReceipt e-Document root.

Refer to GoodsReceiptAcceptance definition for any enumerations.

### GoodsReceivedRejectedType [attribute]

*GoodsReceivedRejectedType is optional. A single instance might exist.*

Defines the reason the goods were rejected

Refer to GoodsReceivedRejectedType definition for any enumerations.

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### **GoodsReceiptHeader**

*GoodsReceiptHeader is mandatory. A single instance is required.*

The GoodsReceiptHeader is required and contains information common to the GoodsReceipt e-Document.

### **GoodsReceiptLineItem**

*GoodsReceiptLineItem is optional. Multiple instances might exist.*

The Optional GoodsReceiptLineItem specifies how a shipment was received for an individual delivery line for one PurchaseOrder and PurchaseOrder line item.

### **GoodsReceiptSummary**

*GoodsReceiptSummary is optional. A single instance might exist.*

Summary information that applies to the entire GoodsReceipt e-Document.

---

## **GoodsReceiptAcceptance [attribute]**

Defines the state of the goods received as compared to the DeliveryMessage specifications. The enumeration list is the list of choices that apply to the GoodsReceipt header and line item.



*This item is restricted to the following list.*

### **GoodsReceivedAsIs**

The delivered goods were received without inspection, or checking of the goods for damage, or accuracy against the DeliveryMessage.

### **GoodsReceivedAsSpecified**

Received goods agree completely with all DeliveryMessage specifications for all lines including item identifiers and item weights. There is no transit damage.

### **GoodsReceivedCancelled**

Received goods notification is being cancelled. This value is only used when the GoodsReceiptStatusType is "Cancelled".

### **GoodsReceivedRejected**

Received goods agree completely with all DeliveryMessage specifications for all lines including item identifiers and item weights; but there has been transit damage resulting in rejection of all goods.

### **GoodsReceivedWithDamage**

Received goods agree completely with all DeliveryMessage specifications for all lines including item identifiers and item weights; but there has been transit damage of some items. All transit damages must be specified.

### **GoodsReceivedWithVariance**

Received goods do not agree completely with the DeliveryMessage specifications. For those items at variance, actual received item identifiers and item weights must be specified.

Additionally, used with the VarianceType of "NotReceived" to indicate items that was on the DeliveryMessage but not in the Delivery as received.

## **GoodsReceivedWithVarianceAndDamage**

Received goods do not agree completely with all DeliveryMessage specifications for all lines including item identifiers and item weights and there has been transit damage of some items. For those items at variance or with transit damage, actual received item identifiers, item weights, and transit damages must be specified.

---

## **GoodsReceiptAcceptance [attribute]**

Defines the state of the goods received as compared to the DeliveryMessage specifications. The enumeration list is the list of choices that apply to the GoodsReceipt e-Document root.



*This item is restricted to the following list.*

### **GoodsReceivedAsIs**

The delivered goods were received without inspection, or checking of the goods for damage, or accuracy against the DeliveryMessage.

### **GoodsReceivedAsSpecified**

Received goods agree completely with all DeliveryMessage specifications for all lines including item identifiers and item weights. There is no transit damage.

### **GoodsReceivedCancelled**

Received goods notification is being cancelled. This value is only used when the GoodsReceiptStatusType is "Cancelled."

### **GoodsReceivedRejected**

Received goods agree completely with all DeliveryMessage specifications for all lines including item identifiers and item weights; but there has been transit damage resulting in rejection of all goods.

### **GoodsReceivedWithDamage**

Received goods agree completely with all DeliveryMessage specifications for all lines including item identifiers and item weights; but there has been transit damage of some items. All transit damages must be specified.

### **GoodsReceivedWithoutDeliveryMessage**

Goods were received but there was no prior DeliveryMessage. This acceptance status applies to the entire GoodsReceipt e-Document and is available only at the e-Document level.

### **GoodsReceivedWithVariance**

Received goods do not agree completely with the DeliveryMessage specifications. For those items at variance, actual received item identifiers and item weights must be specified.

Additionally, used with the VarianceType of "NotReceived" to indicate items that was on the DeliveryMessage but not in the Delivery as received.

## GoodsReceivedWithVarianceAndDamage

Received goods do not agree completely with all DeliveryMessage specifications for all lines including item identifiers and item weights and there has been transit damage of some items. For those items at variance or with transit damage, actual received item identifiers, item weights, and transit damages must be specified.


---

## GoodsReceiptArrivalDate

The Date and optionally Time on which the received goods arrived.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## GoodsReceiptHeader

The GoodsReceiptHeader is required and contains information common to the GoodsReceipt e-Document.

### GoodsReceiptHeaderAcceptance [attribute]

*GoodsReceiptHeaderAcceptance is optional. A single instance might exist.*

Defines the state of the goods received as compared to the DeliveryMessage specifications. The enumeration list is the list of choices that apply to the GoodsReceipt header and line item.

Refer to GoodsReceiptHeaderAcceptance definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### GoodsReceiptNumber

*GoodsReceiptNumber is mandatory. A single instance is required.*

The unique receipt identifier as agreed by the trading partners.

#### GoodsReceiptIssueDate

*GoodsReceiptIssueDate is optional. A single instance might exist.*

The date that the GoodsReceipt e-Document was created.

#### TransactionHistoryNumber

*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

#### GoodsReceiptArrivalDate



*GoodsReceiptArrivalDate is optional. A single instance might exist.*

The Date and optionally Time on which the received goods arrived.

#### TimePeriod

*TimePeriod is optional. A single instance might exist.*

The TimePeriod element is used to communicate a duration period of time as



indicated in PeriodType.

## **GoodsReceiptUnloadDate**

*GoodsReceiptUnloadDate is optional. A single instance might exist.*

The Date and optionally Time on which the received goods were unloaded.

## **GoodsReceiptReference**

*GoodsReceiptReference is optional. Multiple instances might exist.*

A group item detailing relevant references (such as contract number) pertaining to the GoodsReceipt, as indicated by the GoodsReceiptReferenceType.

## **DeliveryMessageNumber**

*DeliveryMessageNumber is optional. A single instance might exist.*

A unique delivery identifier assigned to each DeliveryMessage as agreed between the trading partners.

## **DeliveryMessageDate**

*DeliveryMessageDate is optional. A single instance might exist.*

The Date and Time when the DeliveryMessage was issued.

## **OtherDate**

*OtherDate is optional. A single instance might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## **BuyerParty**

*BuyerParty is optional. A single instance might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## **BillToParty**

*BillToParty is optional. A single instance might exist.*

The address where the Invoice is to be sent.

## **SupplierParty**

*SupplierParty is optional. A single instance might exist.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **CarrierParty**

*CarrierParty is optional. A single instance might exist.*

The party performing the transport of the product from the pickup location to the ship-to location; could be a hauler.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

## **TransportUnitCharacteristics**

*TransportUnitCharacteristics is optional. Multiple instances might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

## **TransportationComment**


*TransportationComment is optional. Multiple instances might exist.*

Textual Commentary on Transportation for an entire GoodsReceipt.

---

## **GoodsReceiptHeaderAcceptance [attribute]**

Defines the state of the goods received as compared to the DeliveryMessage specifications. The enumeration list is the list of choices that apply to the GoodsReceipt header and line item.



*This item is restricted to the following list.*

### **GoodsReceivedAsIs**

The delivered goods were received without inspection, or checking of the goods for damage, or accuracy against the DeliveryMessage.

### **GoodsReceivedAsSpecified**

Received goods agree completely with all DeliveryMessage specifications for all lines including item identifiers and item weights. There is no transit damage.

## **GoodsReceivedCancelled**

Received goods notification is being cancelled. This value is only used when the GoodsReceiptStatusType is "Cancelled".

## **GoodsReceivedRejected**

Received goods agree completely with all DeliveryMessage specifications for all lines including item identifiers and item weights; but there has been transit damage resulting in rejection of all goods.

## **GoodsReceivedWithDamage**

Received goods agree completely with all DeliveryMessage specifications for all lines including item identifiers and item weights; but there has been transit damage of some items. All transit damages must be specified.

## **GoodsReceivedWithVariance**

Received goods do not agree completely with the DeliveryMessage specifications. For those items at variance, actual received item identifiers and item weights must be specified.

Additionally, used with the VarianceType of "NotReceived" to indicate items that was on the DeliveryMessage but not in the Delivery as received.

## **GoodsReceivedWithVarianceAndDamage**

Received goods do not agree completely with all DeliveryMessage specifications for all lines including item identifiers and item weights and there has been transit damage of some items. For those items at variance or with transit damage, actual received item identifiers, item weights, and transit damages must be specified.


---

## **GoodsReceiptIssueDate**

The date that the GoodsReceipt e-Document was created.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### **Date**

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### **Time**

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

## papiNet V2R31

---

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## GoodsReceiptLineItem

The Optional GoodsReceiptLineItem specifies how a shipment was received for an individual delivery line for one PurchaseOrder and PurchaseOrder line item.

### GoodsReceiptAcceptance [attribute]


*GoodsReceiptAcceptance is mandatory. A single instance is required.*

Defines the state of the



goods received as compared to the DeliveryMessage specifications. The enumeration list is the list of choices that apply to the GoodsReceipt header and line item.

Refer to GoodsReceiptAcceptance definition for any enumerations.



### GoodsReceivedRejectedType [attribute]

*GoodsReceivedRejectedType is optional. A single instance might exist.*

Defines the reason the goods were rejected

Refer to GoodsReceivedRejectedType definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **GoodsReceiptLineItemNumber**

*GoodsReceiptLineItemNumber is mandatory. A single instance is required.*

A sequential number that uniquely identifies the GoodsReceipt line item.

### **DeliveryMessageLineItemNumber**

*DeliveryMessageLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the delivery line item.

### **PurchaseOrderInformation**

*PurchaseOrderInformation is optional. A single instance might exist.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

### **PurchaseOrderLineItemNumber**

*PurchaseOrderLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the PurchaseOrder line item.

### **MillParty**

*MillParty is optional. A single instance might exist.*

The organisation or business entity that actually produces the product.

### **GoodsReceiptReference**

*GoodsReceiptReference is optional. Multiple instances might exist.*

A group item detailing relevant references (such as contract number) pertaining to the GoodsReceipt, as indicated by the GoodsReceiptReferenceType.

### **Product**

*Product is optional. A single instance might exist.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

### **Quantity**

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

### **InformationalQuantity**

# papiNet V2R31

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## NumberOfGoodsReceiptPackages

*NumberOfGoodsReceiptPackages is optional. A single instance might exist.*

A count of the number of packages detailed in the GoodsReceiptLineItem.

## GoodsReceiptPackage

*GoodsReceiptPackage is optional. Multiple instances might exist.*

This element represents the manner in which the GoodsReceipt is packaged.

## SafetyAndEnvironmentalInformation

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

---

## GoodsReceiptLineItemNumber

A sequential number that uniquely identifies the GoodsReceipt line item.

<b>GoodsReceiptLineItemNumber</b>
type   lineNumberType

---

## GoodsReceiptNumber

The unique receipt identifier as agreed by the trading partners.

<b>GoodsReceiptNumber</b>
type   s30


---

## GoodsReceiptPackage

This element represents the manner in which the GoodsReceipt is packaged.

### GoodsReceiptAcceptance [attribute]

GoodsReceiptPackage



*GoodsReceiptAcceptance is mandatory. A single instance is required.*

Defines the state of the goods received as compared to the DeliveryMessage specifications. The enumeration list is the list of choices that apply to the GoodsReceipt e-Document root.

Refer to GoodsReceiptAcceptance definition for any enumerations.

## VarianceType [attribute]

*VarianceType is optional. A single instance might exist.*

Defines the type of difference that the GoodsReceiptPackage has from the information on the DeliveryMessage

Refer to VarianceType definition for any enumerations.

## GoodsReceivedRejectedType [attribute]

*GoodsReceivedRejectedType is optional. A single instance might exist.*

Defines the reason the goods were rejected

Refer to GoodsReceivedRejectedType definition for any enumerations.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### PackageInformation

*PackageInformation is mandatory. A single instance is required.*

The purpose of the PackageInformation structure is to clearly identify physical handling items that constitute the delivery.

PackageInformation is the highest level of product packaging it describes the shipping or warehousing unit.

If you are communicating a package, usually for logistics or transport purposes, you should include the PackageType, Identifier, ItemCount, and Quantity. (Note: you still have the ability to describe the item with one of the "named" items.)



If you are communicating one of the named Items there is no need to include PackageType, Identifier, ItemCount, and Quantity.

Since either of these two approaches can be used the entire contents of this element are optional even though the parent may be required. It is expected that you will fill in the appropriate details.

---

## GoodsReceiptReference

A group item detailing relevant references (such as contract number) pertaining to the GoodsReceipt, as indicated by the



GoodsReceiptReferenceType.

## GoodsReceiptReferenceType [attribute]

*GoodsReceiptReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information

previously communicated in the prefix.

Refer to GoodsReceiptReferenceType definition for any enumerations.

## **AssignedBy [attribute]**

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## **GoodsReceiptReferenceType [attribute]**

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.




Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

---

## **GoodsReceiptStatusType [attribute]**

Defines the status of the entire GoodsReceipt e-Document at root level

*This item is restricted to the following list.*



### **Cancelled**

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### **Original**

The supplied information is the first version of that information.

### **Replaced**

The supplied information is replacing earlier supplied information. The receiver should revalidate the information in their system based upon the entire information received.

## GoodsReceiptSummary

Summary information that applies to the entire GoodsReceipt e-Document.

**(sequence)**

The sequence of items below is mandatory. A single instance is



required.

### TotalNumberOfLineItems

TotalNumberOfLineItems is optional. A single instance might exist.

The total number of individual line items in the document, regardless of the status or type.

**(sequence)**

The sequence of items below is mandatory. One instance is required, multiple instances might exist.

### TotalQuantity

TotalQuantity is mandatory. A single instance is required.

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

### TotalInformationalQuantity


TotalInformationalQuantity is optional. Multiple instances might exist.

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

### TermsAndDisclaimers

TermsAndDisclaimers is optional. Multiple instances might exist.

An element that contains legal information with an indication of what the Language is.



## GoodsReceiptUnloadDate


The Date and optionally Time on which the received goods were unloaded.

**(choice)**

[choice] is optional because of choice construct.

**(sequence)**

The sequence of items below is mandatory. A single instance is required.



### Date

# papiNet V2R31

---

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

## **Time**

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## **DateTimeRange**

*DateTimeRange is optional because of choice construct.*

The delivery date and/or time range.

---

## **GoodsReceivedRejectedType [attribute]**

Defines the reason the goods were rejected

*This item is restricted to the following list.*

### **ExcessiveTransitDamage**

The item(s) is/are damaged beyond acceptable use during transit.

### **ProductQuality**

The delivery did not match the quality of the product ordered or requested.

### **TooEarly**

The delivery has occurred prior to the agreed delivery date/time. For example, there is insufficient storage at the delivered time.

### **TooLate**


The delivery has occurred after the agreed delivery date/time. For example, delivered after press date.

### **UnableToUnload**

The delivered items cannot be unloaded. For example, damaged vehicle doors, load has shifted during transportation, or ShipTo requires reels to be palletised but they are delivered on the vehicle floor.

### **WrongBarcode**

The barcode used to identify the product is incorrect.



## WrongBasisWeight

The basis weight of the product is not what was ordered.

## WrongDeliveryLocation

The product was delivered to the wrong location.

## WrongDiameter

The diameter delivered is unusable. For example, a physical limitation on a reel stand is exceeded.

## WrongLabel

The delivered item has incorrect or missing information, or incorrect label stock that would prevent its use. For example, insufficient peel-off barcode labels.

## WrongProduct

The delivered item was not the product ordered or requested.

## WrongReelWidth

The width of the reel is incorrect.

## WrongVehicleType

The items have been delivered in a vehicle that cannot be unloaded at the ShipTo facility. For example, the ShipTo requires side unloading vehicles, but the delivery vehicle can only be unloaded from the rear.

## WrongWrap

The delivered item is wrapped in material that will prevent its use. For example, a hole is not present in the end cap for vacuum lifting.

---

## GPSCoordinates

The location of the party as specified using a Global Positioning System.

### GPSSystem [attribute]

*GPSSystem is optional. A single instance might exist.*

The type of GPS system.

Refer to GPSSystem definition for any enumerations.

### (sequence)


*The sequence of items below is mandatory. A single instance is required.*

#### Latitude

*Latitude is mandatory. A single instance is required.*

A measurement of the position of the party or contact in degrees north or south of the equator

#### Longitude



# papiNet V2R31

---

*Longitude is mandatory. A single instance is required.*

A measurement of the position of the party or contact in degrees east or west of the prime meridian

## Height

*Height is optional. A single instance might exist.*

The height of the object.

---

## GPSSystem [attribute]

The type of GPS system.

*This item is restricted to the following list.*

### ECEF

Earth Centered Earth Fixed

### HAE

Height about Ellipse

### MSL

Mean Sea Level (default)

attribute	
<b>GPSSystem</b>	
type	gPSSystem
default	MSL

---

## Grade

Grade

<b>Grade</b>	
type	s60

---

## GradeAgency [attribute]

LumberAgency identifies which agency is responsible for assigning the lumber attributes.

*This item is restricted to the following list.*

### BS

### BS-EN

British standard based on a European standard.

### CEN

European Committee for Standardisation (<http://www.cenorm.be>)

### DIN

### EN338

### EN1912

### EN1611-1

### EDISAW

### Generic

attribute	
<b>GradeAgency</b>	
type	LumberAgencyType

## **GOST**

Russian federal agency on technical regulating and metrology  
(<http://www.gost.ru>)

## **ISO**

## **JAS**

Japanese Agricultural Standard

## **NELMA**

## **NLGA**

## **NS**

## **NSLB**

## **RIS**

## **RT**

## **SIS**

## **SPIB**

## **WCLIB**

## **WRCLA**

## **WWPA**

## **Supplier**

---

## **GradeAgency**

North American structural panel grading agencies. Defines the governing organisation of the grading scheme employed.

<b>GradeAgency</b>
type   plywoodOSBGradeAgencyType

Note: There is a GradeAgency attribute, as well.

*This item is restricted to the following list.*

### **APA**

### **PITTSBURG**

### **TECO**

### **MillCertified**

### **None**

---

## **GradeCode**

A specific product code for which the owner or source is specified.

<b>GradeCode</b>
type   s30

## GradeName

A specific product name for which the owner or source is specified (for example, ImprovedNewsprint-45-1479)

<b>GradeName</b>	
type	s30

## GradeStamp

Grade stamp information


### GradeStamped [attribute]

<b>GradeStamp</b>	
type	constructionGradeStampClass

*GradeStamped is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to GradeStamped definition for any enumerations.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### GradeStampMillNumber

*GradeStampMillNumber is optional. Multiple instances might exist.*

Identifies the mill where the special grading was carried out.

#### GradeStampLocation

*GradeStampLocation is mandatory. A single instance is required.*

Defines the location on the piece (of the stamp).

Refer to GradeStampLocation definition for any enumerations.

## GradeStamped [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

**Yes**

**No**

<b>GradeStamped</b>	
type	yesNo

## GradeStampLocation

Defines the location on the piece (of the stamp).

*This item is restricted to the following list.*

**Face**

**Back**

**Good Side**

<b>GradeStampLocation</b>	
type	stampLocationType

Bad Side

Edge

End

---

## GradeStampMillNumber

Identifies the mill where the special grading was carried out.

<b>GradeStampMillNumber</b>
type s255

---

## GradeType [attribute]

Grade Type

*This item is restricted to the following list.*

- #1
- #1 and #2
- #1 and #2 Clear
- #1 (SRB)
- #1 Box
- #1 Commons
- #1 Cuts
- #1 Cuttings
- #1 Dense
- #1 Dense Stadium Grade
- #1 Dense Structural
- #1 Door Cuttings
- #1 Fencing (Select)
- #1 Furniture
- #1 Lath
- #1 Mining
- #1 Non Dense
- #1 Pencil Stock
- #1 Prime
- #1 Sash Cuttings
- #1 Shop
- #1 Stadium Grade
- #1 Structural
- #1 and Btr

attribute
<b>GradeType</b>
type lumberGradeType

#2  
#2 (SRB)  
#2 Box  
#2 Common  
#2 Cuts  
#2 Cuttings  
#2 Dense  
#2 Door Cuttings  
#2 Fencing (Quality)  
#2 Foundation  
#2 Furniture  
#2 Lath  
#2 Mining  
#2 Non Dense  
#2 Pencil Stock  
#2 Prime  
#2 Sash Cuttings  
#2 Shop  
#2 Structural  
#2 and Btr  
#2 and Btr Common  
#2 and Btr Fencing(Rustic)  
#3  
#3 (SRB)  
#3 Clear  
#3 Common  
#3 Cuttings  
#3 Fencing  
#3 Fencing (Rustic)  
#3 Lath  
#3 Pencil Stock  
#3 Shop  
#3 Shop or Sash  
#3 and Btr  
#3 and Btr Common  
#4  
#4 Common

#5 Common

1.5E LAM

1.6E LAM

1.7E LAM

1.8E LAM

1.9E LAM

1200f

1350f

1400f

1450f

1500f

1600f

1650f

1800f

1950f

2.0E LAM

2.1E LAM

2.2E LAM

2.3E LAM

2.4E LAM

2.5E LAM

2.6E LAM

2000f

2100f

2200f Scaffold Plank

2250f

2400f

2400f Scaffold Plank

2550f

26002-83

GOST (agency) export Quality

2700f

2850f

3000f

302-20

302-22

302-24

**3150f**

**3300f**

**8486**

GOST (agency) domestic quality

**900f**

**A**

**A and Btr**

**Appearance Knotty**

**Architect Clear**

**Architect Knotty**

**B**

**B and B**

**B Grade**

**B Laminating**

**B and Btr**

**B and Btr - 1 and 2 Clear**

**B.F.Laminating**

**Barge Framing**

**Barge Planking and Decking**

**Battens**

**C**

**C Laminating**

**C Select**

**C Ship Decking**

**C and Btr**

**C and Btr Dimension**

**C and Btr Select**

**C and Btr-VG Stepping**

**California Fencing**

**Choice**

**Choice and Btr**

**Clear**

**Clear All Heart**

**Clear Door**

**Clear Door Rip**

**Clear Finger Joint**

**Clear Gutter**

Clear Heart  
Clear VG Heart  
Colonial  
Commercial Decking  
Commercial Dex  
Commercial Patio  
Construction  
Construction (SRB)  
Construction Common  
Construction Heart  
Crossarms  
Custom Clear  
Custom knotty  
Cut Door Stock  
D  
D Dimension  
D Laminating  
D Select  
D and Btr  
D and Btr Select  
Deck Common  
Deck Heart  
Dense Commercial Decking  
Dense Industrial Scaffold plank 65  
Dense Industrial Scaffold Plank 72  
Dense Premium  
Dense Select Decking  
Dense Select Structural  
Dense Standard Decking  
Dunnage  
DOVD Stepping  
E  
Economy  
Economy Fencing  
Economy Stud  
Factory Flitches  
Factory Select

FG or MG Ladder Rails  
Fingerjoint Shop Common  
Finish  
Foundation  
Gutter  
Heart B  
Heart Clear  
Industrial  
Industrial 26  
Industrial 45  
Industrial 55  
Knotty  
Knotty Finger Joint  
L1 Dense Laminating  
L1 Laminating  
L1-c Laminating  
L2 Laminating  
L2-d Dense Laminating  
L3 Laminating  
Ladder and Pole Stock  
Ladder Rail Stock  
M-10  
M-11  
M-12  
M-13  
M-14  
M-15  
M-16  
M-17  
M-18  
M-19  
M-20  
M-21  
M-22  
M-23  
M-24  
M-25

M-26

M-27

M-28

M-29

M-30

M-31

M-5

M-6

M-7

M-8

M-9

Margin Plank

Mast Spar and Boat Two and One-Fourth Inch and Thicker

Mast Spar and Boat One to Two Inch

Merchantable

Merchantable Heart

MillGrade

Moulding Stock (A)

Moulding Stock (B)

Moulding and Btr

Mouldings

NeLMA # 1A Furniture

NeLMA # 2A Furniture

None

NSLB #1

NSLB #2

Par99

Patio 1

Patio 2

Pipe Stave Stock

Plank Wall

Premium

Premium and Btr

Prime

Quality

Quality Fencing

Quality Knotty

RadiusEdgeDecking 1  
RadiusEdgeDecking 2  
Rustic  
Rustic Fencing  
Rustic Knotty  
Sash  
Sash Cuttings  
Sawn Railroad Ties  
Scaffold #1  
Scaffold #2  
Select  
Select and Quality Knotty  
Select Decking  
Select Dex  
Select Fencing  
Select Heart  
Select Knotty  
Select Merchantable  
Select Patio  
Select Shop  
Select Structural  
Select Structural (SRB)  
Select Structural Non Dense  
Selected  
Selected #2 Common  
Selected #3 Common  
Selected Decking  
Selected Gutter  
Ship Decking  
Ship Plank  
Shop Flitches  
Short  
Short Select  
SPS 1 Certified Fingerjointed  
SPS 3 Certified Fingerjointed  
Stadium Plank Seats  
Stadium Plank Walk boards

Stadium Planks  
Stained Selects  
Standard  
Standard (SRB)  
Standard Mouldings  
Standard and Btr  
Sterling  
Stud  
Stud (SRB)  
Superior  
Supreme  
Tank Stock Inch and Thicker  
Tank Stock Under Four Inch  
Utility  
Utility (#2 Mining)  
Utility (SRB)  
Utility and Btr  
VG Ladder Rails

---

## GradingRule [attribute]

Grading rule, the rules under which the product has been graded.

*This item is restricted to the following list.*

**European 1611-1**  
**GSSS**  
**Nordic**  
**SS EN 230120**  
**Supplier**  
**Other**

attribute
<b>GradingRule</b>
type   gradingRule

---

## GrainDirection

Defines the primary orientation/alignment (Long or Short) of the cellulose fibres in a sheet or web of paper, which results from the flow of fibres in a water suspension during the papermaking process.

*This item is restricted to the following list.*

**Any**

<b>GrainDirection</b>
type   grainDirection

Grain Direction does not matter.

## Long

Orientation is aligned with the long fibres or with the grain.

## Short

Orientation is aligned with the short fibres or against the grain.

---

## Green

The "Green" portion of the method of representing colour termed RGB


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).



#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

#### SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

#### TwoSigmaLower


*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

#### TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.



## Gutter

### Gutter

#### Bleed [attribute]

*Bleed is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Bleed definition for any enumerations.

#### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax


*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

#### AdditionalText

*AdditionalText is optional. A single instance might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## Gypsum

A placeholder for further definition of gypsum items.

#### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### [Any Type]

Any type of content is permitted at this point.



## Halftones

Halftones are images made up of a series of dots in a specific pattern that simulates the look of a continuous tone image.

### IsHalftones [attribute]

*IsHalftones is mandatory. A single instance is required.*

Indicates if the images are halftones or not.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value


*Value is optional. Multiple instances might exist*

A numeric value expressed in the unit of measure (UOM).

#### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## HardwoodLumber

Product structure for solid wood products made of hardwood.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### HardwoodLumberCharacteristics


*HardwoodLumberCharacteristics is mandatory. A single instance is required.*

A group item that organises the hardwood lumber –product information.

#### Packaging

*Packaging is optional. A single instance might exist.*

Type of a package that includes individual products.




## HardwoodLumberCharacteristics

A group item that organises the hardwood lumber –product information.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### [Any Type]



Any type of content is permitted at this point.

## Head

Head.

### Bleed [attribute]

*Bleed is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Bleed definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax


*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

### AdditionalText

*AdditionalText is optional. A single instance might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## Headband

Headband.

### BandLocationType [attribute]

*BandLocationType is optional. A single instance might exist.*

Band location type

Refer to BandLocationType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ColourCode

*ColourCode is optional. A single instance might exist.*

A code indicating the colour.

#### ColourDescription


*ColourDescription is optional. A single instance might exist.*

A free form description of the colour.

#### BandMaterial

*BandMaterial is optional. A single instance might exist.*

Band material



## HeatTreatment

Defines the heat treatment method.

### HeatTreatmentType [attribute]

*HeatTreatmentType is optional. A single instance might exist.*

Defines the standard to which to product has been heat treated.

Refer to HeatTreatmentType definition for any enumerations.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.




## HeatTreatmentType [attribute]

Defines the standard to which to product has been heat treated.

*This item is restricted to the following list.*


- HT
- HTC/NHTNC
- KD56/30



## Height

The height of the object. (Used in wood/timber items.)

### ActualNominal [attribute]



*ActualNominal is optional. A single instance might exist.*

Indicates the measurement approach used to communicate the dimensions of the individual pieces.

Refer to ActualNominal definition for any enumerations.

### (choice)

*[choice] is optional because of choice construct.*

#### Value

*Value is optional because of choice construct.*

A numeric value expressed in the unit of measure (UOM).

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## Height

The height of the object.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### Value

Value is mandatory. A single instance is required.

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


RangeMin is optional. A single instance might exist.

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax


RangeMax is optional. A single instance might exist.

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## HighlightedPlanningBucket

Provides an indication and information that the planning bucket should be reviewed.



### PlanningBucketStatusType [attribute]

PlanningBucketStatusType is optional. A single instance might exist.

Used to identify the Planning bucket's status. Typically used to highlight a change in status to the receiver of the e-Document.

Refer to PlanningBucketStatusType definition for any enumerations.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### AdditionalText

AdditionalText is optional. A single instance might exist.

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## HolePunchInformation


Hole Punch Information.

### HolePunchThroughCover [attribute]

*HolePunchThroughCover is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to HolePunchThroughCover definition for any enumerations.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PunchedHoleDetails

*PunchedHoleDetails is optional. A single instance might exist.*

A grouping element that will contain the configuration information for punched holes.


#### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## HolePunchTemplateReference

Hole punch template reference



## HolePunchThroughCover [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

**Yes**

**No**




## HolePunchType

Hole punch type.

*This item is restricted to the following list.*

**DIN2**

**DIN4**



**Finnish**  
**Swedish**  
**Any**

---

## HoleReinforcement

Hole reinforcement

*This item is restricted to the following list.*

**Yes**  
**No**

<b>HoleReinforcement</b>	
type	yesNo


---

## HoleSpacing

The HoleSpacing element is used to communicate the distance between holes.

**(choice)**

*[choice] is optional because of choice construct.*



**EvenSpacing**

*EvenSpacing is optional because of choice construct.*

The EvenSpacing element is used to communicate the hole-spacing that is equivalent between the holes. The initial spacing between the paper edge and the first hole is handled using the DistanceFromEdge element.

**UnevenSpacing**

*UnevenSpacing is optional because of choice construct.*

Uneven Spacing

---

## Hours

A qualifier of DeliveryTransitTime.

<b>Hours</b>	
type	nni6

## HSB

A definition of colour using the HSB protocol.

All the components of the definition are required. The structure of Hue, Saturation, and Brilliance follows DetailMeasurement.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Hue

*Hue is mandatory. A single instance is required.*

Measure of colour Hue in the HSB method of communicating colour.

#### Saturation


*Saturation is mandatory. A single instance is required.*

Measure of colour Saturation in the HSB method of communicating colour.

#### Brilliance

*Brilliance is mandatory. A single instance is required.*

Measure of brilliance in the HSB colour approach.



## Hue

Measure of colour Hue in the HSB method of communicating colour.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).



#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

#### SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

#### TwoSigmaLower


*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

#### TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.



## Humidity

Humidity

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax


*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## Identifier

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.



### IdentifierCodeType [attribute]

*IdentifierCodeType is mandatory. A single instance is required.*

Defines the type of product identifier used (for example, reel number, ream number, bar code). This code type specifies how to decode the identifier value.

Refer to IdentifierCodeType definition for any enumerations.

### IdentifierType [attribute]

*IdentifierType is mandatory. A single instance is required.*

This attribute specifies whether the Identifier is the primary way to identify the product or a secondary way. Only one of the given identifiers can be primary. In addition, this attribute also specifies the physical support used to code the identifier (for example, a Radio Frequency (RF)

Tag).

Refer to IdentifierType definition for any enumerations.

## **IdentifierFormatType [attribute]**

*IdentifierFormatType is optional. A single instance might exist.*

IdentifierFormatType defines the technical format used to make an IdentifierCodeType readable by technical devices or humans. The IdentifierCodeType specifies how to decode the identifier value

Refer to IdentifierFormatType definition for any enumerations.

---

## **IdentifierCodeType [attribute]**

Defines the type of product identifier used (for example, reel number, ream number, bar code). This code type specifies how to decode the identifier value.



*This item is restricted to the following list.*

### **Carrier**

Carrier's own identifier coding scheme.

### **EAN8**

European Article Number coded on 8 digits.

### **EAN8Plus2**

### **EAN8Plus5**

### **EAN13**

European Article Number coded on 13 digits.

### **EAN13Plus2**

### **EAN13Plus8**

### **EAN128**

### **EPSMA**

European Association for Pressure Sensitive LabelStock Manufacturers

### **EUGROPA**

European Paper Merchants Association code.

### **GlobalReturnableAssetNumber**

The EAN.UCC Global Returnable Asset Number

### **GlobalTradeItemNumber**

The EAN.UCC Global Trade Item Number

### **IFRA**

IFRA Bar Code using 16 digits and the Interleaved 2/5 symbols.

### **ISBN10**

10 digit ISBN code without dashes

## **ISBN10Dash**

10 digit ISBN code with dashes

## **ISBN13**

13 digit ISBN code.

## **ISBN13Dash**

## **Measurer**

Measurer's own identifier coding scheme.

## **NARI**

North American Roll Identifier coded on 13 digits, and using the Code 39 symbols.

## **NPTA**

National Paper Trade Association code.

## **RFTagSerialNumber**

## **SerializedShippingContainerCode**

The EAN.UCC Serialized Shipping Container Code

## **Supplier**

Supplier's own identifier coding scheme.

## **TAPPI 13**

TAPPI 13-character identifier coding scheme.

## **TAPPI 9**

TAPPI 9-character identifier coding scheme.

## **UCCEAN128SSCC**

## **UCCEANMulti**

## **UIC14**

The CEPI Unit identifier coded on 14 digits. When the CEPI Unit Identifier is used in bar code format, then the symbology must be Code 128C to European Standard EN 799. This is the official European identifier by CEPI. More info at [www.cepi.org](http://www.cepi.org).

## **UIC16**

To be deprecated in future version. Use instead UIC14. UIC16 was the CEPI Unit identifier coded on 16 digits. UIC16 is no longer supported by CEPI.

## **UPC**

Universal Product Code administered by the Universal Code Council. Note: There are several formats used for this coding scheme.

## **UPC\_A**

## **UPC\_A\_Plus2**

## **UPC\_A\_Plus5**


## **UPC\_E**

UPC\_E\_Plus2  
UPC\_E\_Plus5  
UPC\_ShippingContainer

---

## IdentifierFormatType [attribute]

IdentifierFormatType defines the technical format used to make an IdentifierCodeType readable by technical devices or humans. The IdentifierCodeType specifies how to decode the identifier value



*This item is restricted to the following list.*


**Codabar**  
**CodablockA**  
**CodablockF**  
**Code11**  
**Code16K**  
**Code2/5Beared**  
**Code2/5Industrial**  
**Code2/5Interleaved**  
**Code2/5InterleavedMod10**  
**Code2/5MatrixEurope**  
**Code2/5MatrixJapan**  
**Code2/5Standard**  
**Code39**  
**Code39F.ASCII**  
**Code39Mod43**  
**Code93**  
**Code128Auto-Switching**  
**Code128A**  
**Code128B**  
**Code128C**  
**Code128C(F1Mod10)**  
**Composite**  
**Datamatrix**  
**EAN8**  
**EAN8Plus2**  
**EAN8Plus5**

EAN13  
EAN13Plus2  
EAN13Plus8  
EAN128  
HumanReadable  
IBM\_BC412  
ITF14  
Logmars  
MicroPDF14  
PDF417  
Plessey  
Postnet  
QR\_Code  
RSS  
TLC39  
UPC\_A  
UPC\_A\_Plus2  
UPC\_A\_Plus5  
UPC\_E  
UPC\_E\_Plus2  
UPC\_E\_Plus5  
UCCEAN128SSCC  
UCCEAN128Multi  
UPC\_ShippingContainer  
Other

---

## IdentifierType [attribute]

This attribute specifies whether the Identifier is the primary way to identify the product or a secondary way. Only one of the given identifiers can be primary. In addition, this attribute also specifies the physical support used to code the identifier (for example, a Radio Frequency (RF) Tag).



*This item is restricted to the following list.*

### **Barcode**

The physical support used to code the identifier is a bar code.

### **CorrelationID**

Correlation ID

## Primary

This article Identifier is the primary identifier used.

## RFTag

The physical support used to code the identifier is a Radio Frequency Tag.

## Secondary

This article Identifier is the secondary identifier used.


---

## Impressions

The work produced by one revolution of the printing cylinder or unit.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## Incoterms [attribute]

The Incoterms consist of a number official international trade terms defined by International Chamber of Commerce (ICC) plus an additional term called Other. Actual trade terms used are depending on the version of the Incoterms. The Incoterms define the responsibilities of buyers and sellers for delivery under a sales contract. They provide definitions for delivery points, loading and unloading obligations, and customs clearance. (<http://www.iccwbo.org/incoterms>)

*This item is restricted to the following list.*

### CFR

COST AND FREIGHT (... named port of destination)

### CIF

# papiNet V2R31

---

COST, INSURANCE AND FREIGHT (... named port of destination).

## **CIP**

CARRIAGE AND INSURANCE PAID TO (... named place of destination).

## **CPT**

CARRIAGE PAID TO (... named place of destination).

## **DAF**

DELIVERED AT FRONTIER (... named place).

## **DAP**

DELIVERED AT PLACE (... named place of destination).

## **DAT**

DELIVERED AT TERMINAL (... named place of destination).

## **DDP**

DELIVERED DUTY PAID (... named place of destination).

## **DDU**

DELIVERED DUTY UNPAID (... named place of destination).

## **DEQ**

DELIVERED EX QUAY (... named port of destination).

## **DES**

DELIVERED EX SHIP (... named port of destination).

## **EXW**

EX WORKS (... named place).

## **FAS**

FREE ALONGSIDE SHIP (... named port of shipment).

## **FCA**

FREE CARRIER (... named place).

## **FOB**

FREE ON BOARD (... named port of shipment).

## **Other**



Used when the situation is not covered by the 13 official Incoterms (for example, CIN used in Switzerland for CIP)

## IncotermsLocation

Place linked to terms of delivery showing the place where goods are to be delivered.

### Incoterms [attribute]

*Incoterms is mandatory. A single instance is required.*



The Incoterms consist of 13 official international trade terms plus an additional term called Other. The Incoterms define the responsibilities of buyers and sellers for delivery under a sales contract. They provide definitions for delivery points, loading and unloading obligations, and customs clearance.

Refer to Incoterms definition for any enumerations.

### IncotermsVersion [attribute]

*IncotermsVersion is optional. A single instance might exist.*

The version of the IncoTerms codes used.

Refer to IncotermsVersion definition for any enumerations.

## IncotermsVersion [attribute]

The version of the IncoTerms codes used.

*This item is restricted to the following list.*

### 1980

The incoterms definitions provided in 1980.

### 1990

The incoterms definitions provided in 1990.

### 2000


The incoterms definitions provided in 2000.

### 2010

The incoterms definitions provided in 2010

### 20xx

The next group of incoterms definitions anticipated to be provided in 2020. When they are actually released this list will be updated and "20xx" will be used for the next scheduled release..




## IncrementalOrderQuantity

An incremental quantity and units of measure that is added to MinimumOrderQuantity to arrive at an order quantity.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Quantity

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

### InformationalQuantity

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## IncrementalValue


Many times paper is produce in BasisWeights of discreet values. This element permits the expression of those increments.

### UOM [attribute]

*UOM is mandatory. A single instance is required.*

Defines the unit of measure for the value.

Refer to UOM definition for any enumerations.




## InfoRequest

The InfoRequest element is the root element for the InfoRequest e-Document.

The purpose of InfoRequest e-Document is to allow the

requesting party to request from the receiver party an update. The e-Documents that may be returned in response to an InfoRequest are the Availability, Calendar, InventoryStatus, OrderStatus, Planning, ProductQuality, ShipmenStatus, ShippingInstructions or Statement.



### InfoRequestType [attribute]

*InfoRequestType is mandatory. A single instance is required.*

An attribute designed to indicate which response e-Document is expected in response to the InfoRequest e-Document.

Refer to InfoRequestType definition for any enumerations.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### RequestNumber

*RequestNumber is mandatory. A single instance is required.*

A unique tracking number specifically identifying the InfoRequest e-Document to

the originator. The tracking number is returned with the "information", the answer, to help match the answer to the request.

## **RequestingParty**

*RequestingParty is mandatory. A single instance is required.*

The party requesting the information.

## **RespondToParty**

*RespondToParty is mandatory. One instance is required, multiple instances might exist.*

The party the document should be responded to.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **(choice)**

*[choice] is optional because of choice construct.*

### **InventoryStatusRequestDetail**

*InventoryStatusRequestDetail is optional because of choice construct.*

InventoryStatusRequestDetail is a conditional element. Its existence is mutually exclusive with that of the OrderStatusRequestDetail and AvailabilityStatusRequestDetail.

### **OrderStatusRequestDetail**

*OrderStatusRequestDetail is optional because of choice construct.*

The element that contains the details associated with the order status request e-Document.

### **AvailabilityStatusRequestDetail**

*AvailabilityStatusRequestDetail is optional because of choice construct.*

AvailabilityStatusRequestDetail is a conditional element. Its existence is mutually exclusive with that of the InventoryStatusRequestDetail and OrderStatusRequestDetail.

### **PlanningRequestDetail**

*PlanningRequestDetail is optional because of choice construct.*

Its existence is mutually exclusive with that of the InventoryStatusRequestDetail, OrderStatusRequestDetail, Availability, and

ProductQuality.

## **ProductQualityRequestDetail**

*ProductQualityRequestDetail is optional because of choice construct.*

ProductQualityRequestDetail is a conditional element. Its existence is mutually exclusive with that of the InventoryStatusRequestDetail, OrderStatusRequestDetail, AvailabilityStatusRequestDetail, and PlanningRequestDetail.

## **ShippingInstructionsRequestDetail**

*ShippingInstructionsRequestDetail is optional because of choice construct.*

ShippingInstructionsRequestDetail is a conditional element. Its existence is mutually exclusive from the other approaches to requesting information.

## **ShipmentStatusRequestDetail**

*ShipmentStatusRequestDetail is optional because of choice construct.*

A grouping element that provides the parameters to be used when responding with a shipment status information (using the ShipmentStatus e-Document).

## **StatementRequestDetail**

*StatementRequestDetail is optional because of choice construct.*

The request criteria associated with statement information.

## **CalendarRequestDetail**


*CalendarRequestDetail is optional because of choice construct.*

The selection criteria for communicating what Calendar information is desired.

---

## **InfoRequestType [attribute]**

An attribute designed to indicate which response e-Document is expected in response to the InfoRequest e-Document.



*This item is restricted to the following list.*

### **Availability**

The sender is requesting Availability information.

### **Calendar**

The sender is requesting Calendar information.

### **InventoryStatus**

The sender is requesting InventoryStatus information.

### **OrderStatus**

The sender is requesting OrderStatus information.

### **Planning**

The sender is requesting Planning information.

### **ProductQuality**

The sender is requesting ProductQuality information.

### **ShipmentStatus**

The sender is requesting ShipmentStatus information.

## ShippingInstructions

The sender is requesting ShippingInstructions information.

## Statement


The sender is requesting a Statement.

---

## InformationalAmount

A monetary amount used for information purposes only (not for calculation). For example, the invoice price adjustment subtotal is expressed in sterling pounds, and the buyer wants this information expressed in U.S. dollars.

CreditDebitNote and Invoice - The TaxAmount is displayed in the currency that is applicable throughout the e-Document. When a TaxAmount needs to be displayed in a different national currency, this field is used.



### AmountType [attribute]

*AmountType is optional. A single instance might exist.*

Defines the type of amount.

Refer to AmountType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

#### ExchangeRate

*ExchangeRate is optional. A single instance might exist.*

The exchange rate as of the date included in the element.


#### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## InformationalPricePerUnit

A group item containing a currency value and a measurement value used convey a secondary PricePerUnit. For example, where PricePerUnit is dollars per ton. InformationalPricePerUnit could be dollars per kilogram.



### InformationalPricePerUnitType [attribute]

Defines what type of Price is being supplied.

Refer to InformationalPricePerUnit for any enumerations

#### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## InformationalPricePerUnitType [attribute]

Defines what type of Price is being supplied.

*This item is restricted to the following list.*

#### AlternatePrice

Alternate price calculated by the Buyer.

#### CoverPrice



Price that appears on the cover of a book.

**ProductPrice**


Price for the product specified in the Product element in the e-Document.

**ProductionPrice**

Price calculated by the Buyer's Production department.

## InformationalQuantity

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.



**QuantityType [attribute]**

*QuantityType is mandatory. A single instance is required.*

QuantityType communicates information about the type of quantity being communicated and how the receiver might use the information.

Refer to QuantityType definition for any enumerations.

**QuantityTypeContext [attribute]**

*QuantityTypeContext is optional. A single instance might exist.*

Provides the location in the value chain where the quantity is being reported.

Refer to QuantityTypeContext definition for any enumerations.

**AdjustmentType [attribute]**


*AdjustmentType is optional. A single instance might exist.*

Describes the type of adjustment associated with a quantity.

Refer to AdjustmentType definition for any enumerations.

**MeasuringMethodType [attribute]**

*MeasuringMethodType is optional. A single instance might exist.*



Specifies how a measurement value is created.

Refer to MeasuringMethodType definition for any enumerations.

## MeasuringAgency [attribute]

*MeasuringAgency is optional. A single instance might exist.*

The agency defining measuring methods.

Refer to MeasuringAgency definition for any enumerations.

## MeasuringMethod [attribute]

*MeasuringMethod is optional. A single instance might exist.*

The method used to determine how the item under consideration is measured. Measuring methods are defined by the measuring agency.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## Ink

A grouping element that describes the ink used in the process.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*


### InkManufacturer

*InkManufacturer is optional. A single instance might exist.*

Company that produced the ink used in the job.

### ColourCode

*ColourCode is optional. A single instance might exist.*



A code indicating the colour.

## **InkTack**

*InkTack is optional. A single instance might exist.*

The stickiness of the ink.

## **InkViscosity**

*InkViscosity is optional. A single instance might exist.*

The measured thickness of the ink.

## **FountainSolutionpH**

*FountainSolutionpH is optional. A single instance might exist.*

Measurement of the acidic properties of the fountain solution.

## **FountainSolutionConductivity**

*FountainSolutionConductivity is optional. A single instance might exist.*


Electrical measure of fountain solution measured in micro – siemens.

---

## **InkCharacteristics**

The ink characteristics.

Note: The child element, InkCoverage, will be deprecated from InkCharacteristics in an upcoming version. Use the instance of InkCoverage found in ColourSpecs.



### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

## **InkCoverage**

*InkCoverage is optional. Multiple instances might exist.*

Ink coverage

## **NumberOfColours**

*NumberOfColours is mandatory. A single instance is required.*

The number of colours

## **ColourSpecs**

*ColourSpecs is mandatory.*

Colour specs

## InkCoverage

Ink coverage

### **InkCoverageType [attribute]**

*InkCoverageType is optional. A single instance might exist.*

Ink coverage type

Refer to InkCoverageType definition for any enumerations.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

#### **Value**

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### **RangeMin**


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### **RangeMax**

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## **InkCoverageType [attribute]**

Ink coverage type

*This item is restricted to the following list.*

**AcrossFlap**

**FullBackground**

**Illustrations**



## **InkDelivery**

The delivery mechanism used in the printing process.



# papiNet V2R31

---

## InkManufacturer

Company that produced the ink used in the job.

<b>inkManufacturer</b>
type   s60

---

## InkTack

The stickiness of the ink.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



---

## InkTypeDescription

Ink type description

<b>inkTypeDescription</b>
type   s30

---

## InkViscosity

The measured thickness of the ink.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*


#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin

*RangeMin is optional. A single instance might exist.*



The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

## **RangeMax**

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## **InlayCardQuantity [attribute]**

Inlay card quantity

*This item is restricted to the following list.*

**0**


There are zero inlay cards.

**1**

There is one inlay card.

**2**


There are two inlay cards.



---

## **InsertReference**

Insert reference



---

## **InstructionByType [attribute]**

Provides the type for how goods are identified on group level when instructed for loading or delivery.

*This item is restricted to the following list.*

### **ByMillOrder**


Goods are identified on group level by mill order and mill order line item.

### **ByProduct**

Goods are identified on group level by a product specification with all required product details.

### **ByPurchaseOrder**

Goods are identified on group level by PurchaseOrder and PurchaseOrder line item.




## Insurance

Group element containing information about insurance

### (sequence)

The sequence of items below is mandatory. A single instance is required.



#### Insurer

Insurer is optional. A single instance might exist.

Name of the insurer

#### InsuranceContractNo

InsuranceContractNo is optional. A single instance might exist.

Insurance contract number

#### InsuredValue

InsuredValue is optional. A single instance might exist.

The amount the goods are insured for.


#### InsuranceInfo

InsuranceInfo is optional. A single instance might exist.

Any addition information about the insurance


## InsuranceContractNo

Insurance contract number



## InsuranceInfo

Any addition information about the insurance




## InsuredValue

The amount the goods are insured for.

### (sequence)

The sequence of items below is mandatory. A single instance is required.



#### CurrencyValue

CurrencyValue is mandatory. A single instance is required.

The amount in the referenced currency as defined by the CurrencyType attribute.

## Insurer


Name of the insurer

insurer	
type	s40

## InventoryChange

The InventoryChange element is the root element for the InventoryChange e-Document.

The purpose of the InventoryChange e-Document is to inform involved parties about changes in the inventory at a specific location. The e-Document provides information allowing the receiving party to update their systems for cost tracking, performance, and financial reporting.



### InventoryChangeType [attribute]

*InventoryChangeType is mandatory. A single instance is required.*

Identifies the reason for the inventory change

Refer to InventoryChangeType definition for any enumerations.

### InventoryChangeStatusType [attribute]

*InventoryChangeStatusType is optional. A single instance might exist.*

Defines the status of the entire InventoryChange e-Document at root level

Refer to InventoryChangeStatusType definition for any enumerations.

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### InventoryChangeHeader

*InventoryChangeHeader is mandatory. A single instance is required.*

Common information that applies to the entire InventoryChange e-Document.

## InventoryChangeLineItem

*InventoryChangeLineItem is mandatory. One instance is required, multiple instances might exist.*

The detail information for a given InventoryChange item.

## InventoryChangeSummary

*InventoryChangeSummary is optional. A single instance might exist.*

Summary information that applies to the entire InventoryChange e-Document.

## InventoryChangeHeader

Common information that applies to the entire InventoryChange e-Document.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### InventoryChangeIssuedDate

*InventoryChangeIssuedDate is mandatory. A single instance is required.*

The Date and Time when the InventoryChange was issued.

### TransactionHistoryNumber

*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

### InventoryChangeNumber

*InventoryChangeNumber is mandatory. A single instance is required.*


An identifier allowing the InventoryChange to be uniquely identified.

### InventoryChangeReason

*InventoryChangeReason is optional. A single instance might exist.*

The reason for the inventory change.

### LocationParty



*LocationParty is mandatory.*

The organization or business entity where the business event took place or will take place.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **InventoryChangeReference**

*InventoryChangeReference is optional. Multiple instances might exist.*

An element detailing relevant references (such as contract number) pertaining to the InventoryChange, identified by InventoryChangeReferenceType.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.


---

## **InventoryChangeIssuedDate**

The Date and Time when the InventoryChange was issued.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### **Date**

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### **Time**

## papiNet V2R31

---

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## InventoryChangeLineItem

The detail information for a given InventoryChange item.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### InventoryChangeLineItemNumber

InventoryChangeLineItemNumber is mandatory. A single instance is required.

An identifier for the InventoryChangeLineItem.


### (sequence)

The sequence of items below is optional. A single instance might exist.

#### PurchaseOrderInformation

PurchaseOrderInformation is mandatory. A single instance is required.

A group item containing information unique to this



PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

#### PurchaseOrderLineItemNumber

PurchaseOrderLineItemNumber is optional. A single instance might exist.

The sequential number that uniquely identifies the PurchaseOrder line item.


#### Product

Product is optional. A single instance might exist.

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

#### MillParty

MillParty is optional. A single instance might exist.



The organisation or business entity that actually produces the product.

## **InventoryChangeReference**

*InventoryChangeReference is optional. Multiple instances might exist.*

An element detailing relevant references (such as contract number) pertaining to the InventoryChange, identified by InventoryChangeReferenceType.

## **InventoryClass**

*InventoryClass is optional. A single instance might exist.*

A group item containing information about status of inventory and goods items.

## **OldInventoryClass**

*OldInventoryClass is optional. A single instance might exist.*

A group item containing information about what the InventoryClass was prior to the event described taking place.

## **NumberOfInventory ChangeLineItemDetails**

*NumberOfInventory  
ChangeLineItemDetails is optional. A single instance might exist.*

The number of InventoryChangeLineItemDetail elements included in the InventoryChangeLineItem.

## **InventoryChangeLineItemDetail**

*InventoryChangeLineItemDetail is optional. Multiple instances might exist.*

Unit level details associated with the InventoryChange.

## **SupplyPoint**

*SupplyPoint is optional. Two instances might exist.*

Grouping element that contains items describing a supply point. A SupplyPoint belongs to a LocationParty, e.g. in a DeliveryOrigin or DeliveryDestination, and describes where goods are stored and can be loaded or unloaded. A SupplyPoint can for example be a loading or unloading gate at a warehouse or a road side landing at a logging area in the forest.

## **Quantity**

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **OldQuantity**

*OldQuantity is optional. A single instance might exist.*

What the Quantity was prior to the event described taking place

## Old InformationalQuantity

*OldInformationalQuantity is optional. Multiple instances might exist.*

What the InformationalQuantity was prior to the event described taking place.

## Inventory InspectionDate

*InventoryInspectionDate is optional. A single instance might exist.*

The physical inspection Date and Time of inventory.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## SafetyAndEnvironmentalInformation

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

## InventoryChangeLineItemDetail

Unit level details associated with the InventoryChange.

### ChangeDetailType [attribute]

*ChangeDetailType is optional. A single instance might exist.*




Specifies how a package is changed.

Refer to ChangeDetailType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



## InventoryChangeLineItemDetailNumber

*InventoryChangeLineItemDetailNumber is mandatory. A single instance is required.*

# papiNet V2R31

---

An identifier allowing the line item to be uniquely identified.

## **OldQuantity**

*OldQuantity is optional. Multiple instances might exist.*

What the Quantity was prior to the event described taking place

## **OldInformationalQuantity**

*OldInformationalQuantity is optional. Multiple instances might exist.*

What the InformationalQuantity was prior to the event described taking place.

## **OldInventoryClass**

*OldInventoryClass is optional. A single instance might exist.*

A group item containing information about what the InventoryClass was prior to the event described taking place.

## **PriceDetails**

*PriceDetails is optional. A single instance might exist.*

An element that groups together price information.

## **Product**

*Product is optional. A single instance might exist.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **PackageInformation**

*PackageInformation is mandatory. A single instance is required.*

The purpose of the PackageInformation structure is to clearly identify physical handling items that constitute the delivery.

PackageInformation is the highest level of product packaging it describes the shipping or warehousing unit.

If you are communicating a package, usually for logistics or transport purposes, you should include the PackageType, Identifier, ItemCount, and Quantity. (Note: you still have the ability to describe the item with one of the "named" items.)

If you are communicating one of the named Items there is no need to include PackageType, Identifier, ItemCount, and Quantity.

Since either of these two approaches can be used the entire contents of this element are optional even though the parent may be required. It is expected that you will fill in the appropriate details.

---

## **InventoryChangeLineItemDetailNumber**

An identifier allowing the line item to be uniquely identified.

<b>InventoryChangeLineItemDetailNumber</b>
type   lineNumberType

## InventoryChangeLineItemNumber

An identifier for the InventoryChangeLineItem.

InventoryChangeLineItemNumber	
type	lineNumberType

## InventoryChangeNumber

An identifier allowing the InventoryChange to be uniquely identified.

InventoryChangeNumber	
type	s30


## InventoryChangeReason

The reason for the inventory change.

### (sequence)

*The sequence of items below is mandatory.*

*A single instance is required.*



### InventoryChangeReasonCode

*InventoryChangeReasonCode is mandatory. A single instance is required.*

A code representing the reason for the inventory change, identified by Agency.

### ReasonDescription

*ReasonDescription is optional. A single instance might exist.*

Text associated with a particular ReasonIdentifier

## InventoryChangeReasonCode

A code representing the reason for the inventory change, identified by Agency.

### Agency [attribute]

*Agency is mandatory. A single instance is required.*



Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.



For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

---

## InventoryChangeReference

An element detailing relevant references (such as contract number) pertaining to the InventoryChange, identified by



InventoryChangeReferenceType.

### **InventoryChangeReferenceType [attribute]**

*InventoryChangeReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to InventoryChangeReferenceType definition for any enumerations.

### **AssignedBy [attribute]**

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.


---

## InventoryChangeReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an

existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.



---

## InventoryChangeStatusType [attribute]

Defines the status of the entire InventoryChange e-Document at root level

*This item is restricted to the following list.*

**Cancelled**



The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

**Original**

The supplied information is the first version of that information.

**Replaced**

The supplied information is replacing earlier supplied information. The receiver should revalidate the information in their system based upon the entire information received.


**InventoryChangeSummary**

Summary information that applies to the entire InventoryChange e-Document.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**TotalNumberOfLineItems**



*TotalNumberOfLineItems is optional. A single instance might exist.*

The total number of individual line items in the document, regardless of the status or type.

**(sequence)**

*The sequence of items below is mandatory. One instance is required, multiple instances might exist.*

**TotalQuantity**

*TotalQuantity is mandatory. A single instance is required.*

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

**TotalInformationalQuantity**

*TotalInformationalQuantity is optional. Multiple instances might exist.*

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.


**(sequence)**

*The sequence of items below is optional. Multiple instances might exist.*

**TotalOldQuantity**

*TotalOldQuantity is mandatory. A single instance is required.*

A summary of the OldQuantity in the document. TotalOldQuantity uses the



QuantityInformation attribute group and the Measurement group (element grouping).

## **TotalOldInformationalQuantity**

*TotalOldInformationalQuantity is optional. Multiple instances might exist.*

A summary of the OldInformationQuantity in the document.

TotalOldInformationalQuantity uses the QuantityInformation attribute group and the Measurement group (element grouping).

## **TermsAndDisclaimers**

*TermsAndDisclaimers is optional. A single instance might exist.*

An element that contains legal information with an indication of what the Language is.

---

## **InventoryChangeType [attribute]**

Identifies the reason for the inventory change

*This item is restricted to the following list.*



### **Buy**

The material has been purchased

### **Classification**

The inventory change is due to a change in classification

### **Conversion**

### **InventoryTransfer**

The material has been transferred

### **LocationTransfer**

The material has been moved

### **OwnershipTransfer**

The party owning the material is being changed.

### **QualityReject**

The change is due to rejection.

### **Rewrapping**

The material has been rewrapped

### **Sell**

The material has been sold

### **SiteDamage**

Damage has taken place at the storage site.

### **StockCount**

### **TransitDamage**

Damage has taken place in transit.

### **Waste**

The quantity is being changed due to spoilage or waste of material.

## InventoryClass

A group item containing information about status of inventory and goods items.

### InventoryStatusType [attribute]

*InventoryStatusType is optional. A single instance might exist.*

Provides the status type for inventory/goods belonging to a product and/or an order.

Refer to InventoryStatusType definition for any enumerations.

### InventoryOwnedBy [attribute]

*InventoryOwnedBy is optional. A single instance might exist.*

Specifies who is the owner of the inventory/goods.

Refer to InventoryOwnedBy definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### (sequence)

*The sequence of items below is optional. Multiple instances might exist.*

#### InventoryClassCode

*InventoryClassCode is mandatory. A single instance is required.*

A code specifying the inventory and goods status. Classification of statuses can be done on multiple levels indicated by InventoryClassLevel.

#### InventoryClassDescription


*InventoryClassDescription is optional. Multiple instances might exist.*

A description of the inventory class.

#### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



---

## InventoryClassCode

A code specifying the inventory and goods status. Classification of statuses can be done on multiple levels indicated by InventoryClassLevel.

### Agency [attribute]

*Agency is mandatory. A single instance is required.*

InventoryClassCode	
type	s30

attributes	
Agency	
type	agencyCode
InventoryClassLevel	
type	nni1
default	1

Describes the agency maintaining the list of codes.

To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

### InventoryClassLevel [attribute]

*InventoryClassLevel is optional. A single instance might exist.*

The sequential number that uniquely identifies the level of stacked Inventory Class Codes. E.g. On level 1 "Damaged" can be given as an inventory class code while details on damages can be specified with inventory class codes on level 2.

---

## InventoryClassDescription

A description of the inventory class.

InventoryClassDescription	
type	s72

---


### InventoryClassLevel [attribute]

The sequential number that uniquely identifies the level of stacked Inventory Class Codes. E.g. On level 1 "Damaged" can be given as an inventory class code while details on damages can be specified with inventory class codes on level 2.

attribute	
InventoryClassLevel	
type	nni1
default	1

## InventoryDispositionInstructions

The



InventoryDispositionInstructions element is the root element for the InventoryDispositionInstructions e-Document.

The InventoryDispositionInstructions e-Document permits the owner of inventory stored at a third party location to request the inventory be destroyed, shipped to another location, held in inventory, or physically changed. The receiving party makes the requested changes to the inventory and sends an InventoryChange and ShippingInstructions, if required, to the requestor so their systems can be updated.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### InventoryDispositionInstructionsHeader

*InventoryDispositionInstructionsHeader is mandatory. A single instance is required.*


Provides information that is common for the instructions on how to dispose of problematic inventory.

#### InventoryDispositionInstructionsDetail

*InventoryDispositionInstructionsDetail is mandatory. One instance is required, multiple instances might exist.*

InventoryDispositionInstructionsDetail provides information about the product to be disposed of and the method of disposal.

**InventoryDispositionInstructionsDetail**



InventoryDispositionInstructionsDetail provides information about the product to be disposed of and the method of disposal.

**InventoryDispositionInstructionsType [attribute]**

*InventoryDispositionInstructionsType is mandatory. A single instance is required.*

Indicates the type of inventory disposition that is required. As this attribute is at the line level multiple dispositions can be communicated in a single e-Document.

Refer to InventoryDispositionInstructionsType definition for any enumerations.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### **InventoryDispositionInstructionsLineNumber**

*InventoryDispositionInstructionsLineNumber is mandatory. A single instance is required.*

The sequential number that uniquely identifies the InventoryDispositionInstructions line item.

### **BuyerParty**

*BuyerParty is optional. Multiple instances might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

### **SupplierParty**

*SupplierParty is optional. Multiple instances might exist.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

### **EndUserParty**

*EndUserParty is optional. Multiple instances might exist.*

The party using, consuming, or converting the product. For example, a printer using paper reels for a print job for a publisher. The final ShipTo destination for a product is normally to the end user's facilities.

### **LocationParty**

*LocationParty is optional. Multiple instances might exist.*

The organization or business entity where the business event took place or will take place.

### **InventoryDispositionInstructionsReference**

*InventoryDispositionInstructionsReference is optional. Multiple instances might exist.*

Contains references that pertain to the InventoryDispositionInstructions e-Document.

### **Product**

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

### **PackageInformation**

*PackageInformation is optional. Multiple instances might exist.*

The purpose of the PackageInformation structure is to clearly identify physical handling items that constitute the delivery.

PackageInformation is the highest level of product packaging it describes the shipping or warehousing unit.

If you are communicating a package, usually for logistics or transport purposes, you should include the PackageType, Identifier, ItemCount, and Quantity. (Note: you still have the ability to describe the item with one of the "named" items.)

If you are communicating one of the named Items there is no need to include PackageType, Identifier, ItemCount, and Quantity.

Since either of these two approaches can be used the entire contents of this element are optional even though the parent may be required. It is expected that you will fill in the appropriate details.

## DeliveryDateWindow

*DeliveryDateWindow is optional. Multiple instances might exist.*

A group item defining the date/time interval for delivery to take place. An element which may contain the estimated date for which delivery is expected. This date is not absolute.

## StencilCharacteristics

*StencilCharacteristics is optional. A single instance might exist.*

A group element specifying attributes of a stencil to be applied to an item, and optional text.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.


---

## InventoryDispositionInstructionsHeader

Provides information that is common for the instructions on how to dispose of problematic inventory.

**(sequence)**

*The sequence of items below is*



*mandatory. A single instance is required.*



## InventoryDispositionInstructionsNumber

*InventoryDispositionInstructionsNumber is mandatory. A single instance is required.*

The identifying number for the Inventory Disposition e-Document.

## InventoryDispositionInstructionsIssuedDate

*InventoryDispositionInstructionsIssuedDate is mandatory. A single instance is required.*

# papiNet V2R31

---

The date that the disposition instructions were issued.

## SenderParty

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## ReceiverParty

*ReceiverParty is optional. A single instance might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## OtherParty

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.


---

## InventoryDispositionInstructionsIssuedDate

The date that the disposition instructions were issued.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be

in discord with other users of XML.

---

## InventoryDispositionInstructionsLineNumber

The sequential number that uniquely identifies the InventoryDispositionInstructions line item.

InventoryDispositionInstructionsLineNumber	
type	lineNumberType

---

## InventoryDispositionInstructionsNumber


The identifying number for the InventoryDispositionInstructions e-Document.

InventoryDispositionInstructionsNumber	
type	s30

---

## InventoryDispositionInstructionsReference

Contains references that pertain to the



InventoryDispositionInstructions e-Document.

### **InventoryDispositionInstructionsReferenceType [attribute]**

*InventoryDispositionInstructionsReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute `@AssignedBy` will communicate the information previously communicated in the prefix.

Refer to `InventoryDispositionInstructionsReferenceType` definition for any enumerations.

### **AssignedBy [attribute]**


*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type `OrderNumber`.

Refer to `AssignedBy` for any enumerations.

## InventoryDispositionInstructionsReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.



Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## InventoryDispositionInstructionsType [attribute]

Indicates the type of inventory disposition that is required. As this attribute is at the line level multiple dispositions can be communicated in a single e-Document.



*This item is restricted to the following list.*

### Scrap

Raw Material or Work in Process to be scrapped.

### Destroy

Finished Goods or Work in Process containing copyrighted information that must be physically destroyed.

### Hold

Excess raw materials, Work in Process, or Finished Goods that should be held for future production or until other Disposition Instructions are received at the current location.

### Transfer


Raw materials or Work in Process that will be shipped to another location.

## InventoryInspectionDate

The physical inspection Date and Time of inventory.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

# papiNet V2R31

A group element that contains the specification of Year, Month, and Day.

## Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## InventoryOwnedBy [attribute]

Specifies who is the owner of the inventory/goods.

*This item is restricted to the following list.*

### Buyer

The owner of the inventory/goods is the buyer. The inventory/goods have already been invoiced.

### Seller

The owner of the inventory/goods is the seller

InventoryOwnedBy	
type	ownedByType
default	Seller

## InventoryStatus

The InventoryStatus element is the root element for the InventoryStatus e-Document.


The InventoryStatus e-Document informs involved parties about physical inventory levels at specific stock locations (warehouse, terminal, printer etc.) at a certain time (snapshot).

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.



## **Language [attribute]**

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

## **InventoryStatusRequestDetailType [attribute]**

*InventoryStatusRequestDetailType is optional. A single instance might exist.*

Communicates the method in which the InventoryStatus should be summarized.

Refer to InventoryStatusRequestDetailType definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **InventoryStatusHeader**

*InventoryStatusHeader is mandatory. A single instance is required.*

Information that applies to all items on the InventoryStatus e-Document.

### **InventoryStatusLineItem**

*InventoryStatusLineItem is mandatory. One instance is required, multiple instances might exist.*

Individual information about the item(s) on an InventoryStatus e-Document.

### **InventoryStatusSummary**

*InventoryStatusSummary is optional. A single instance might exist.*

Summary information that applies to the entire InventoryStatus e-Document.

## InventoryStatusHeader

Information that applies to all items on the InventoryStatus e-Document.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### InventoryStatusIssuedDate

*InventoryStatusIssuedDate is mandatory. A single instance is required.*

The effective date of the InventoryStatus e-Document.

### RequestNumber

*RequestNumber is optional. A single instance might exist.*

A unique tracking number specifically identifying the InfoRequest e-Document to the originator. The tracking number is returned with the "information", the answer, to help match the answer to the request.

### TransactionHistoryNumber

*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

### InventoryStatusNumber

*InventoryStatusNumber is mandatory. A single instance is required.*

An identifier that allows for unique identification of the InventoryStatus.

### LocationParty

*LocationParty is optional. A single instance might exist.*

The organization or business entity where the business event took place or will take place.

### OtherParty

*OtherParty is optional. Multiple instances might exist.*


An organisation or business entity other than those specifically detailed within a e-Document.

### SenderParty

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the



# papiNet V2R31

---

message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## ReceiverParty

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## InventoryStatusReference

*InventoryStatusReference is optional. Multiple instances might exist.*

A group item detailing relevant references pertaining to the InventoryChange, identified by InventoryStatusReferenceType.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.


---

## InventoryStatusIssuedDate

The effective date of the InventoryStatus e-Document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be

in discord with other users of XML.

## InventoryStatusLineItem

Individual information about the item(s) on an InventoryStatus e-Document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### InventoryStatusLineItemNumber

*InventoryStatusLineItemNumber is mandatory. A single instance is required.*

An identifier that allows for unique identification of the InventoryStatusLineItem.

#### PurchaseOrderInformation

*PurchaseOrderInformation is optional. A single instance might exist.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.



#### PurchaseOrderLineItemNumber

*PurchaseOrderLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the PurchaseOrder line item.

#### Product

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

#### MillParty

*MillParty is optional. A single instance might exist.*

The organisation or business entity that actually produces the product.

#### InventoryStatusReference



*InventoryStatusReference is optional. Multiple instances might exist.*

A group item detailing relevant references pertaining to the InventoryChange, identified by InventoryStatusReferenceType.

## **InventoryClass**

*InventoryClass is optional. A single instance might exist.*

A group item containing information about status of inventory and goods items.

## **InventoryStatusLineItemDetail**

*InventoryStatusLineItemDetail is optional. Multiple instances might exist.*

A group element that contains InventoryStatus details.

## **NumberOfInventoryStatusLineItemDetails**

*NumberOfInventoryStatusLineItemDetails is optional. A single instance might exist.*

The number of InventoryStatusLineItemDetail elements included in the InventoryStatusLineItem.

## **Quantity**

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InventoryInspectionDate**

*InventoryInspectionDate is optional. A single instance might exist.*

The physical inspection Date and Time of inventory.

## **LocationParty**

*LocationParty is optional. A single instance might exist.*

The organization or business entity where the business event took place or will take place.

## **SupplyPoint**

*SupplyPoint is optional. A single instance might exist.*

Grouping element that contains items describing a supply point. A SupplyPoint belongs to a LocationParty, e.g. in a DeliveryOrigin or DeliveryDestination, and describes where goods are stored and can be loaded or unloaded. A SupplyPoint can for example be a loading or unloading gate at a warehouse or a road side landing at a logging area in the forest.

## **BuyerParty**

*BuyerParty is optional. A single instance might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## **SupplierParty**

*SupplierParty is optional. A single instance might exist.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## EndUserParty

*EndUserParty is optional. A single instance might exist.*

The party using, consuming, or converting the product. For example, a printer using paper reels for a print job for a publisher. The final ShipTo destination for a product is normally to the end user's facilities.

## OtherParty

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## InformationalQuantity

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## OtherDate

*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## SafetyAndEnvironmentalInformation


*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

---

## InventoryStatusLineItemDetail

A group element that contains InventoryStatus details.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### InventoryStatusLineItemDetailNumber

*InventoryStatusLineItemDetailNumber is mandatory. A single instance is required.*

# papiNet V2R31

An identifier that allows for unique identification of the InventoryStatusLineItemDetail.

## PackageInformation

*PackageInformation is mandatory. A single instance is required.*

The purpose of the PackageInformation structure is to clearly identify physical handling items that constitute the delivery.

PackageInformation is the highest level of product packaging it describes the shipping or warehousing unit.

If you are communicating a package, usually for logistics or transport purposes, you should include the PackageType, Identifier, ItemCount, and Quantity.

(Note: you still have the ability to describe the item with one of the "named" items.)

If you are communicating one of the named Items there is no need to include PackageType, Identifier, ItemCount, and Quantity.

Since either of these two approaches can be used the entire contents of this element are optional even though the parent may be required. It is expected that you will fill in the appropriate details.

---

## InventoryStatusLineItemDetailNumber

An identifier that allows for unique identification of the InventoryStatusLineItemDetail.

<b>InventoryStatusLineItemDetailNumber</b>
type   lineNumberType

---

## InventoryStatusLineItemNumber

An identifier that allows for unique identification of the InventoryStatusLineItem.

<b>InventoryStatusLineItemNumber</b>
type   lineNumberType

---

## InventoryStatusNumber

An identifier that allows for unique identification of the InventoryStatus.

<b>InventoryStatusNumber</b>
type   s30

---

## InventoryStatusReference

A group item detailing relevant references pertaining to the InventoryChange, identified by

<b>InventoryStatusReference</b>
type   s255

attributes
<b>InventoryStatusReferenceType</b>
type   referenceType
<b>AssignedBy</b>
type   partyType

InventoryStatusReferenceType.

### InventoryStatusReferenceType [attribute]

*InventoryStatusReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to InventoryStatusReferenceType definition for any enumerations.

## **AssignedBy [attribute]**

*AssignedBy is optional. A single instance might exist.*


Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## **InventoryStatusReferenceType [attribute]**

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.



Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

---

## **InventoryStatusReportingDetailType [attribute]**

Communicates the level of detail in which inventory is to be reported.

*This item is restricted to the following list.*

### **AggregatedInventory**


Inventory is to be reported in summary.

### **DetailedInventory**

Inventory is reported in detail (using the InventoryStatusLineItemDetail element).



InventoryStatusRequestDetail



InventoryStatusRequestDetail is a conditional element. Its existence is mutually exclusive with that of the OrderStatusRequestDetail and AvailabilityStatusRequestDetail.

**InventoryStatusRequestDetailType [attribute]**

InventoryStatusRequestDetailType is mandatory. A single instance is required. Communicates the method in which the InventoryStatus should be summarized. Refer to InventoryStatusRequestDetailType definition for any enumerations.

**InventoryStatusReportingDetailType [attribute]**

*InventoryStatusReportingDetailType is mandatory. A single instance is required.*

Communicates the level of detail in which inventory is to be reported.

Refer to InventoryStatusReportingDetailType definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **BuyerParty**

*BuyerParty is optional. Multiple instances might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

### **SupplierParty**

*SupplierParty is optional. Multiple instances might exist.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

### **EndUserParty**

*EndUserParty is optional. Multiple instances might exist.*

The party using, consuming, or converting the product. For example, a printer using paper reels for a print job for a publisher. The final ShipTo destination for a product is normally to the end user's facilities.

### **LocationParty**

*LocationParty is optional. Multiple instances might exist.*

The organization or business entity where the business event took place or will take place.

### **MillParty**

*MillParty is optional. A single instance might exist.*

The organisation or business entity that actually produces the product.

### **InventoryClass**

*InventoryClass is optional. A single instance might exist.*

A group item containing information about status of inventory and goods items.

## **(choice)**

*[choice] is optional because of choice construct.*

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **PurchaseOrderInformation**

*PurchaseOrderInformation is mandatory. A single instance is required.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

### **PurchaseOrderLineItemNumber**

*PurchaseOrderLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the PurchaseOrder line item.

### **Product**

*Product is optional because of choice construct.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **SupplierOrderNumber**

*SupplierOrderNumber is optional because of choice construct.*

The number of the supplier order.

## **MillOrderInformation**

*MillOrderInformation is optional because of choice construct.*

A group item containing information unique to a mill order.

## **StatusAsOfDate**

*StatusAsOfDate is optional. A single instance might exist.*

The specific Date and Time for which status is requested. This implies that all open transactions have closed for the date before the status is reported.

---

## **InventoryStatusRequestDetailType [attribute]**

Communicates the method in which the InventoryStatus should be summarized.

*This item is restricted to the following list.*

attribute
<b>InventoryStatusRequestDetailType</b>
type inventoryStatusRequestDetailType

### **ByMillOrder**

By the mill order number and mill order line item number the material was manufactured. MillParty has also to be specified in ByMillOrderInformation to defined the mill order origin.

### **ByProduct**

By product

### **ByPurchaseOrder**

By the PurchaseOrder the material was ordered

### **BySupplierOrderNumber**


By the order the material was manufactured

## InventoryStatusSummary

Summary information that applies to the entire InventoryStatus e-Document.

**(sequence)**

*The sequence of items below is mandatory. A single instance is*



*required.*

### TotalNumberOfLineItems

*TotalNumberOfLineItems is optional. A single instance might exist.*

The total number of individual line items in the document, regardless of the status or type.

**(sequence)**

*The sequence of items below is mandatory. One instance is required, multiple instances might exist.*

### TotalQuantity

*TotalQuantity is mandatory. A single instance is required.*

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

### TotalInformationalQuantity

*TotalInformationalQuantity is optional. Multiple instances might exist.*

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

### TermsAndDisclaimers

*TermsAndDisclaimers is optional. A single instance might exist.*

An element that contains legal information with an indication of what the Language is.

## InventoryStatusType [attribute]

Provides the status type for inventory/goods belonging to a product and/or an order.

*This item is restricted to the following list.*

### Sound

Sound inventory are prime inventory/goods without any damages or defects

### Unsound


Unsound inventory/goods are inventory/goods with defects or inventory/goods put on hold for inspection.

attribute	
<b>InventoryStatusType</b>	
type	inventoryStatusType
default	Sound

## Invoice

The Invoice element is the root element for the Invoice e-Document.

An Invoice e-Document can handle both debits and credits. Typically a seller sends an Invoice to a buyer after delivering the products or services specified in a PurchaseOrder or as part of an automatic replenishment agreement. Alternatively, an Invoice can be prepared by the buyer as part of a self-billing process. The Invoice is a list of the goods shipped and their quantities, or services rendered, indicating the price, terms of sale, supplemental charges, allowances, and communicates the payment required for the indicated items.



### InvoiceType [attribute]

*InvoiceType is mandatory. A single instance is required.*

Defines the various types of invoices. The Invoice has been checked and found compliant with the EU Council Directive 2001/115/EC in force from 1 January 2004 in existing EU Member States and from 1 May 2004 in the Accession Countries. Directive 2001/115/EC harmonises, simplifies and modernises invoicing obligations on traders when they sell products or services that are subject to Value Added Tax (VAT). It also creates an EU legal framework for electronic transmission and storage of invoices. Refer to [http://www.eic.ie/legislation/vat\\_invoicing.htm](http://www.eic.ie/legislation/vat_invoicing.htm) for additional information.

Types of invoices not covered in this standard include:

Delcredere – An invoice sent to the party paying for a number of buyers

Factored – An invoice assigned to a third party for collection

Refer to InvoiceType definition for any enumerations.

### InvoiceContextType [attribute]

*InvoiceContextType is optional. A single instance might exist.*

Indicates the nature of what is included in the invoice.

Refer to InvoiceContextType definition for any enumerations.

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

### Language [attribute]

Language is optional. A single instance might exist.

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

## (sequence)

The sequence of items below is mandatory. A single instance is required.

### **InvoiceHeader**

InvoiceHeader is mandatory. A single instance is required.

Information that applies to all items on the Invoice.

### **InvoiceLineItem**

InvoiceLineItem is mandatory. One instance is required, multiple instances might exist.

Information for each item on an Invoice.

### **MonetaryAdjustment**

MonetaryAdjustment is optional. Multiple instances might exist.

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates they type of adjustment being communicated.

### **InvoiceSummary**

InvoiceSummary is mandatory. A single instance is required.

Summary information for all items on an invoice.

---

## **InvoiceContextType [attribute]**

Indicates the nature of what is included in the invoice.


This item is restricted to the following list.

### **LogisticsService**

The invoice is exclusively for logistics services.

### **Product**

The invoice includes product with optional logistics charges.




---

## **InvoiceDate**

A date that is qualifying the invoicing period. This date often drives payment terms. Note that this date is not necessarily the same as the issue date of the invoice.

## (sequence)

The sequence of items below is mandatory. A single instance is required.



# papiNet V2R31

---

## **Date**

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

## **Time**

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## InvoiceDeliveryInformation

A group item that contains delivery information for invoice purposes. The delivery information that is contained will be similar to that on the DeliveryMessage.


### (sequence)

The sequence of items below is mandatory. A single instance is required.


#### DeliveryMessageNumber

DeliveryMessageNumber is mandatory. A single instance is required.

A unique delivery identifier



assigned to each DeliveryMessage as agreed between the trading partners.



#### DeliveryMessageLineItemNumber

DeliveryMessageLineItemNumber is optional. A single instance might exist.

The sequential number that uniquely identifies the delivery line item.

#### DeliveryMessageDate

DeliveryMessageDate is optional. A single instance might exist.

The Date and Time when the DeliveryMessage was issued.

#### DeliveryDate

DeliveryDate is optional. A single instance might exist.

The Date and optionally the Time that the partners agree is the date upon which deliveries will be recognised. Possible choices for this date are either the date

despatched or the date received.

## **Quantity**

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **ChargeInformation**

*ChargeInformation is optional. Multiple instances might exist.*

A group element that contains elements that describe a charge.

## **CountryOfOrigin**

*CountryOfOrigin is optional. A single instance might exist.*

The country of origin for the material.

## **CountryOfDestination**

*CountryOfDestination is optional. A single instance might exist.*

The country where the goods will be, or were, shipped to.

## **CountryOfConsumption**

*CountryOfConsumption is optional. A single instance might exist.*

The country of consumption for the material.

## **TransportVehicleIdentifier**

*TransportVehicleIdentifier is optional. Multiple instances might exist.*

The identifier of the transport vehicle (license plate number, voyage number, or vessel name). TransportVehicleIdentifier contains the TransportVehicleIdentifierType attribute.

## **TransportUnitIdentifier**

*TransportUnitIdentifier is optional. Multiple instances might exist.*

The identifier of the transport unit, such as a container ID. It could be a license plate number if the transport unit is the vehicle at the same time. The type of identifier is indicated by the TransportUnitIdentifierType.

## **DeliveryMessageReference**

*DeliveryMessageReference is optional. Multiple instances might exist.*

An element that identifies the relevant references pertaining to the DeliveryMessage, identified by DeliveryMessageReferenceType.



## **RemitToParty**

*RemitToParty is optional. Multiple instances might exist.*

A group item containing details of the party to whom payment will be made. The RemitToParty contains all information related to remittance.

## **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **LocationParty**

*LocationParty is optional.*

The organization or business entity where the business event took place or will take place.

## **CountryOfOrigin**

*CountryOfOrigin is optional. A single instance might exist.*

The country of origin for the material.

## **CountryOfDestination**

*CountryOfDestination is optional. A single instance might exist.*

The country where the goods will be, or were, shipped to.

## **CountryOfConsumption**

*CountryOfConsumption is optional. A single instance might exist.*

The country of consumption for the material.

## CreditDebitNoteReason

*CreditDebitNoteReason is optional. A single instance might exist.*

A group item containing the reason for the entire CreditDebitNote.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.


---

## InvoiceLineAmount

The total invoice amount per line (includes adjustments and tax).

InvoiceLineAmount is equal to the

InvoiceLineBaseAmount plus the sum of the signed values of the MonetaryAdjustmentAmount for all instances of MonetaryAdjustment.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

---

## InvoiceLineBaseAmount

A field that contains the result of the calculation Quantity at the InvoiceLineItem

level times the PricePerUnit. As such it

does not include any taxes. It appears at the invoice line item level. InvoiceLineBaseAmount encapsulates CurrencyValue.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### CurrencyValue


*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

---

## InvoiceLineBaseAmountInformation

A group item containing the price per unit and the invoice price amount subtotal.



**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**PriceDetails**

*PriceDetails is mandatory. A single instance is required.*

An element that groups together price information.

**InvoiceLineBaseAmount**

*InvoiceLineBaseAmount is optional. A single instance might exist.*

A field that contains the result of the calculation Quantity at the InvoiceLineItem level times the PricePerUnit. As such it does not include any taxes. It appears at the invoice line item level. InvoiceLineBaseAmount encapsulates CurrencyValue.

## InvoiceLineItem

Information for each item on an Invoice.

### IsFinalInvoice [attribute]

*IsFinalInvoice is optional. A single instance might exist.*

Communicates to the receiver that this is the last invoice so that the customer can “close out” the associated PO as completely invoiced.

Refer to IsFinalInvoice definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### InvoiceLineNumber

*InvoiceLineNumber is mandatory. A single instance is required.*

The sequential number that uniquely identifies the invoice line item. It may enable the invoice to be printed, viewed, or discussed in a common order.

### PurchaseOrderInformation

*PurchaseOrderInformation is optional. A single instance might exist.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

### PurchaseOrderLineItemNumber

*PurchaseOrderLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the PurchaseOrder line item.

### ChargeOrAllowance


*ChargeOrAllowance is optional. A single instance might exist.*

The description of the charge or allowance; such as freight, special handling, and stop-off handling.

### Product

*Product is optional. A single instance might exist.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.



## **Quantity**

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **InvoiceLineBaseAmountInformation**

*InvoiceLineBaseAmountInformation is optional. A single instance might exist.*

A group item containing the price per unit and the invoice price amount subtotal.

## **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates the type of adjustment being communicated.

## **ChargeInformation**

*ChargeInformation is optional. Multiple instances might exist.*

A group element that contains elements that describe a charge.

## **InvoiceLineAmount**

*InvoiceLineAmount is mandatory. A single instance is required.*

The total invoice amount per line (includes adjustments and tax).

InvoiceLineAmount is equal to the InvoiceLineBaseAmount plus the sum of the signed values of the MonetaryAdjustmentAmount for all instances of MonetaryAdjustment.

## **InvoiceDeliveryInformation**

*InvoiceDeliveryInformation is optional. Multiple instances might exist.*

A group item that contains delivery information for invoice purposes. The delivery information that is contained will be similar to that on the DeliveryMessage.

## **InvoiceReference**

*InvoiceReference is optional. Multiple instances might exist.*

A group item detailing relevant references pertaining to the invoice e-Document. InvoiceReferenceType describes the content.

## **DocumentReferenceInformation**

*DocumentReferenceInformation is optional. Multiple instances might exist.*

A group item containing reference information applicable to a document.

## **GeneralLedgerAccount**

*GeneralLedgerAccount is optional. A single instance might exist.*

The general ledger account to be referenced for the item.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **MillCharacteristics**

*MillCharacteristics is optional. A single instance might exist.*

A group item defining the mill party and machine identifier where a product is or was produced.

## **ItemInformation**

*ItemInformation is optional. Multiple instances might exist.*

The purpose of the ItemInformation structure is to clearly identify physical items. The attribute ItemType defines the type of physical item. Physical items can be handling units like packages as well as items contained in packages.

## **TransportModeCharacteristics**

*TransportModeCharacteristics is optional and repeatable. Multiple instances might exist.*

A group item defining the primary mode of transport.

## **TransportUnitCharacteristics**

*TransportUnitCharacteristics is optional. Multiple instances might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

## **TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

## **CountryOfOrigin**

*CountryOfOrigin is optional. A single instance might exist.*

The country of origin for the material.

## **CountryOfDestination**

*CountryOfDestination is optional. A single instance might exist.*

The country where the goods will be, or were, shipped to.

## **CountryOfConsumption**

# papiNet V2R31

---

*CountryOfConsumption is optional. A single instance might exist.*

The country of consumption for the material.

## **LocationParty**

*LocationParty is optional. Multiple instances might exist.*

The organization or business entity where the business event took place or will take place.

## **DeliveryDateWindow**

*DeliveryDateWindow is optional. A single instance might exist.*

A group item defining the date/time interval for delivery to take place. An element which may contain the estimated date for which delivery is expected. This date is not absolute.

## **TaxStatement**

*TaxStatement is optional. A single instance might exist.*

A group element for declaration of exception from normal charges of tax and the reason for tax exemption.

## **SafetyAndEnvironmentalInformation**

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

---

## **InvoiceLineNumber**

The sequential number that uniquely identifies the invoice line item. It may enable the invoice to be printed, viewed, or discussed in a common order.

<b>InvoiceLineNumber</b>
type   lineNumberType

---

## **InvoiceNumber**

The identification number of the papiNet e-Document Invoice. This number uniquely identifies documents for all InvoiceType such as Invoice, DebitNote, CreditNote, Approximate, SelfBillingStatement etc

<b>InvoiceNumber</b>
type   s30

---

## **InvoiceNumberMax**

The upper range of invoices being communicated or requested.

<b>InvoiceNumberMax</b>
type   s30

## InvoiceNumberMin

The lower limit of a range of invoices being communicated or requested.


InvoiceNumberMin	
type	s30

## InvoiceNumberRange

A range of invoices to be considered or reported on.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### InvoiceNumberMin

*InvoiceNumberMin is mandatory. A single instance is required.*

The lower limit of a range of invoices being communicated or requested.

### InvoiceNumberMax

*InvoiceNumberMax is mandatory. A single instance is required.*


The upper range of invoices being communicated or requested.

## InvoicePrimaryStatus

The primary status of the invoice.

### InvoiceStatusCode [attribute]

*InvoiceStatusCode is mandatory. A single instance is required.*



A code communicating the payment status of an invoice.


Refer to InvoiceStatusCode definition for any enumerations.

## InvoiceProductGroup

Product grouping for invoiced items.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### ProductGroupID

*ProductGroupID is optional. A single instance might exist.*

Possibility to group packages or Shipments. Example: Creating temporary group ID's for logistic reasons or lot number.

### InvoiceWoodLineItem

*InvoiceWoodLineItem is mandatory. One instance is required, multiple instances might exist.*

Specific information for a given item on an Invoice.

Note Business Rule IVW017: At least one instance of either the Product or ChargeOrAllowance elements is required.

## ProductGroupSummary

*ProductGroupSummary is optional. A single instance might exist.*

Group of elements to provide summary information on product level.

---

## InvoiceReference

A group item detailing relevant references pertaining to the invoice e-Document. InvoiceReferenceType describes the content.

### InvoiceReferenceType [attribute]

*InvoiceReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.


Refer to InvoiceReferenceType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.




---

## InvoiceReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.



---

## InvoiceSecondaryStatus

The secondary status of the invoice.

InvoiceSecondaryStatus	
type	s60


---

## InvoiceShipment

Shipment grouping for invoiced items.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### ShipmentID

*ShipmentID is optional. A single instance might exist.*

The ShipmentID may be a Bill of Lading Marking, which is customer's reference mark on each package used for logistic purposes. Should not be mixed up with Bill of Lading number. Another example of ShipmentID is grouping by a ContainerID.

### InvoiceProductGroup

*InvoiceProductGroup is mandatory. One instance is required, multiple instances might exist.*

Product grouping for invoiced items.

### ShipmentSummary

*ShipmentSummary is optional. A single instance might exist.*

Summary information for an entire shipment

---

## InvoiceStatusCode [attribute]

A code communicating the payment status of an invoice.

*This item is restricted to the following list.*

attribute	
InvoiceStatusCode	
type	invoiceStatusCode

### Unpaid

No payments were booked against this invoice.

### PartiallyPaid

Payments have been booked against this invoice, but the invoice is not completely paid and cleared.

### Cleared

The invoice is paid to such an extent that no other money is expected or required.

## InvoiceSummary

Summary information for all items on an invoice.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### TotalNumberOfLineItems

TotalNumberOfLineItems is optional. A single instance might exist.

The total number of individual line items in the document, regardless of the status or type.

### (sequence)

The sequence of items below is mandatory. One instance is required, multiple



instances might exist.

#### TotalQuantity

TotalQuantity is mandatory. A single instance is required.

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

#### TotalInformationalQuantity

TotalInformationalQuantity is optional. Multiple instances might exist.

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

#### LineItemSubTotal

LineItemSubTotal is optional. A single instance might exist.

The total amount of all e-Document LineBaseAmount(s) line items without any monetary adjustments that may occur after the e-Document line items.


#### TotalAdjustments

TotalAdjustments is optional. A single instance might exist.

The CurrencyValue of TotalAdjustments contains the total of all MonetaryAdjustmentAmount for all instances of PriceAdjustment and FlatAmountAdjustment in the document (it excludes TaxAdjustments).

#### TotalTaxAmount

TotalTaxAmount is optional. A single instance might exist.



# papiNet V2R31

---

The CurrencyValue of TotalTaxAmount contains the sum of all instances of TaxAdjustment in the document. TotalTaxAmount contains the sum of all instances of the MonetaryAdjustmentAmount for tax adjustments.

## **TotalNetAmount**

*TotalNetAmount is optional. A single instance might exist.*

A field containing total amount excluding tax. For example, in the Invoice TotalNetAmount is equal to the sum of LineItemSubTotal plus TotalAdjustments. TotalNetAmount encapsulates CurrencyValue.

## **TotalAmount**

*TotalAmount is mandatory. A single instance is required.*

A field containing the total amount including tax.

PurchaseOrder: The total amount, using a valid unit of measure of all the items in the e-Document. Multiple total amounts are allowed so different units of measure or grade sub-totals can be communicated.

CreditDebitNote and Invoice: TotalAmount is equal to TotalNetAmount plus TotalTaxAmount. In certain countries this is the amount that is due for payment based upon the terms of payment.

## **InformationalAmount**

*InformationalAmount is optional. Multiple instances might exist.*

A monetary amount used for information purposes only (not for calculation). For example, the invoice price adjustment subtotal is expressed in sterling pounds, and the buyer wants this information expressed in U.S. dollars.

CreditDebitNote and Invoice - The TaxAmount is displayed in the currency that is applicable throughout the e-Document. When a TaxAmount needs to be displayed in a different national currency, this field is used.

## **(sequence)**

*The sequence of items below is optional. Multiple instances might exist.*

### **TermsOfPayment**

*TermsOfPayment is mandatory. A single instance is required.*

A group item that contains agreed-to terms defining when, how, and under what conditions the payment is to be made.

When TermsOfPayment is optional; if omitted, TermsOfPayment is controlled through previous negotiation.

### **TotalNetOfTermsDiscount**

*TotalNetOfTermsDiscount is optional. A single instance might exist.*

The components of the amount to be paid if prompt payment discount terms are met, including the amount that is subject to the payment terms discount, the discount amount, and the amount due after prompt payment discount.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **TermsAndDisclaimers**

*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.

## **TaxStatement**


*TaxStatement is optional. A single instance might exist.*

A group element for declaration of exception from normal charges of tax and the reason for tax exemption.

---

## **InvoiceType [attribute]**

Defines the various types of invoices. The Invoice has been checked and found compliant with the EU Council Directive 2001/115/EC in force from 1 January 2004 in existing EU Member States and from 1 May 2004 in the Accession Countries. Directive 2001/115/EC harmonises, simplifies and modernises invoicing obligations on traders when they sell products or services that are subject to Value Added Tax (VAT). It also creates an EU legal framework for electronic transmission and storage of invoices. Refer to [http://www.eic.ie/legislation/vat\\_invoicing.htm](http://www.eic.ie/legislation/vat_invoicing.htm) for additional information.



Types of invoices not covered in this standard include:

Delcredere – An invoice sent to the party paying for a number of buyers

Factored – An invoice assigned to a third party for collection

*This item is restricted to the following list.*

### **Approximate**

An invoice that is created to record ownership transfer without the material physically being moved. Typically what occurs is that the buyer has agreed to take ownership of the item at a certain point in time but has not arranged for transportation. Approximate invoices are invoices that are claiming payment.

### **CreditNote**

Credits that are provided for amount reductions and complaints. A CreditNode will normally have a reference to an earlier issued Invoice.

### **DebitNote**

A DebitNote claims payment for additional charges. A DebitNote normally has a reference to an earlier issued Invoice.

### **Duplicate**

To be removed in a future version. When an invoice is reissued as a duplicate the invoice type should be the same as on the original invoice. Use attribute Reissued = Yes to indicate a duplicate.

### **Invoice**

A regular invoice (referred to as an invoice) claims payment for products, services, and charges supplied under conditions agreed to between seller and buyer. The invoice communicates, among other things, payment terms, payment method, and the payment amount required for one or more deliveries.

## **PrePayment**

A prepayment invoice is used as a notification of amounts to be paid in advance. It is not a legal invoice claiming payment for provided products or services.

## **ProForma**

A pro-forma invoice is not a legal invoice claiming payment. A pro-forma invoice is an e-Document serving as a preliminary invoice, containing on the whole the same information as the final invoice, but not actually claiming payment. Pro-forma invoices are typically used in a cross-border shipment for customs purposes. Can travel with the product or be sent to a broker.

## **SelfBillingStatement**

A SelfBillingStatement is an invoice that is prepared by the buyer of the product (or the consumer of the service) for the provider of the product or service. The preparer will pay the invoice.

Typically, logistics cost-charges are the services that are communicated. They are incurred during a certain period of time between the party who provides the logistics services (typically the party with a LogisticsRole of "LogisticsProvider") and the requestor of such services (typically the party with a LogisticsRole of "Consignor").

Raw materials, maintenance, repair, and operating supplies are examples of products that can be entered on a self billing statement for products. This type of invoice is also referred to as an invoice for "evaluated receipts" because it developed from the receiving department's evaluation of their receipts and from that creating the invoice.


The SelfBillingStatement process exists when there is a great deal of trust between the trading partners that permits this cost savings business process.

## InvoiceWood

The InvoiceWood element is the root element for the InvoiceWood e-Document.

An InvoiceWood e-Document can handle both debits and credits. Typically a seller sends an InvoiceWood to a buyer after delivering the products or services specified in a PurchaseOrder or as part of an automatic replenishment agreement.

Alternatively, an InvoiceWood can be prepared by the buyer as part of a self-billing process. The InvoiceWood is a list of the goods shipped and their quantities, or services rendered, indicating the price, terms of sale, supplemental charges, allowances, and communicates the payment required for the indicated items.



### InvoiceType [attribute]

*InvoiceType is mandatory. A single instance is required.*

Defines the various types of invoices. The Invoice has been checked and found compliant with the EU Council Directive 2001/115/EC in force from 1 January 2004 in existing EU Member States and from 1 May 2004 in the Accession Countries. Directive 2001/115/EC harmonises, simplifies and modernises invoicing obligations on traders when they sell products or services that are subject to Value Added Tax (VAT). It also creates an EU legal framework for electronic transmission and storage of invoices. Refer to [http://www.eic.ie/legislation/vat\\_invoicing.htm](http://www.eic.ie/legislation/vat_invoicing.htm) for additional information.

Types of invoices not covered in this standard include:

- Delcredere – An invoice sent to the party paying for a number of buyers
- Factored – An invoice assigned to a third party for collection

Refer to InvoiceType definition for any enumerations.

### InvoiceContextType [attribute]

*InvoiceContextType is optional. A single instance might exist.*

Indicates the nature of what is included in the invoice.

Refer to InvoiceContextType definition for any enumerations.

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

## **Language [attribute]**

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **InvoiceWoodHeader**

*InvoiceWoodHeader is mandatory. A single instance is required.*

This element contains the information that is consistent for the entire InvoiceWood document.

### **InvoiceShipment**

*InvoiceShipment is optional. Multiple instances might exist.*

Shipment grouping for invoiced items.

### **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount.

MonetaryAdjustment contains an attribute that indicates the type of adjustment being communicated.

### **InvoiceWoodSummary**

*InvoiceWoodSummary is mandatory. A single instance is required.*

Summary information that applies to all items on a Wood Market Segment Invoice.

## InvoiceWoodHeader

This element contains the information that is consistent for the entire InvoiceWood document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### InvoiceNumber

*InvoiceNumber is mandatory. A single instance is required.*

The identification number of the papiNet e-Document Invoice. This number uniquely identifies documents for all InvoiceType such as Invoice, DebitNote, CreditNote, Approximate, SelfBillingStatement etc

#### InvoiceDate

*InvoiceDate is mandatory. A single instance is required.*

A date that is qualifying the invoicing period. This date often drives payment terms. Note that this date is not necessarily the same as the issue date of the invoice.

#### InvoiceReference

*InvoiceReference is optional. Multiple instances might exist.*

A group item detailing relevant references pertaining to the invoice e-Document. InvoiceReferenceType describes the content.

#### BillToParty

*BillToParty is mandatory. A single instance is required.*

The address where the invoice is to be sent.

#### SupplierParty

*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

#### BuyerParty

*BuyerParty is mandatory. A single instance is required.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

#### RemitToParty

*RemitToParty is optional. Multiple instances might exist.*


A group item containing details of the party to whom payment will be made. The RemitToParty contains all information related to remittance.

#### ShipToCharacteristics

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To



Party.ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **LocationParty**

*LocationParty is optional.*

The organization or business entity where the business event took place or will take place.

## **CountryOfOrigin**

*CountryOfOrigin is optional. A single instance might exist.*

The country of origin for the material.

## **CountryOfDestination**

*CountryOfDestination is optional. A single instance might exist.*

The country where the goods will be, or were, shipped to.

## **CountryOfConsumption**

*CountryOfConsumption is optional. A single instance might exist.*

The country of consumption for the material.

## **CarrierParty**

*CarrierParty is optional. A single instance might exist.*

The party performing the transport of the product from the pickup location to the ship-to location; could be a hauler.

## **TransportVehicleIdentifier**

*TransportVehicleIdentifier is optional. A single instance might exist.*

The identifier of the transport vehicle (license plate number, voyage number, or vessel name). TransportVehicleIdentifier contains the TransportVehicleIdentifierType attribute.

## **TransportUnitIdentifier**

*TransportUnitIdentifier is optional. A single instance might exist.*

The identifier of the transport unit, such as a container ID It could be a license plate number if the transport unit is the vehicle at the same time. The type of identifier is indicated by the TransportUnitIdentifierType.

## **Insurance**

*Insurance is optional. A single instance might exist.*

Group element containing information about insurance

## **CreditDebitNoteReason**

*CreditDebitNoteReason is optional. A single instance might exist.*

A group item containing the reason for the entire CreditDebitNote.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## InvoiceWoodLineItem

Specific information for a given item on an Invoice.

Note Business Rule IVW017: At least one instance of either the Product or ChargeOrAllowance elements is required.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### InvoiceLineNumber

InvoiceLineNumber is mandatory. A single instance is required.

The sequential number that uniquely identifies the invoice line item. It may enable the invoice to be printed, viewed, or discussed in a common order.

#### PurchaseOrderInformation

PurchaseOrderInformation is optional. A single instance might exist.

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

#### PurchaseOrderLineItemNumber

PurchaseOrderLineItemNumber is optional. A single instance might exist.

The sequential number that uniquely identifies the PurchaseOrder line item.

#### DocumentReferenceInformation

DocumentReferenceInformation is optional. Multiple instances might exist.

A group item containing reference information applicable to a document.

#### EndsDiscountInformation

EndsDiscountInformation is optional. A single instance might exist.

Rule for calculating the ends discount, expressed by a code.


#### ChargeOrAllowance

ChargeOrAllowance is optional. A single instance might exist.

The description of the charge or allowance; such as freight, special handling, and stop-off handling.

#### Product

InvoiceWoodLineItem



*Product is optional. A single instance might exist.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **Quantity**

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **InvoiceLineBaseAmountInformation**

*InvoiceLineBaseAmountInformation is optional. A single instance might exist.*

A group item containing the price per unit and the invoice price amount subtotal.

## **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates they type of adjustment being communicated.

## **ChargeInformation**

*ChargeInformation is optional. Multiple instances might exist.*

A group element that contains elements that describe a charge.

## **InvoiceLineAmount**

*InvoiceLineAmount is mandatory. A single instance is required.*

The total invoice amount per line (includes adjustments and tax).

InvoiceLineAmount is equal to the InvoiceLineBaseAmount plus the sum of the signed values of the MonetaryAdjustmentAmount for all instances of MonetaryAdjustment.

## **InvoiceDeliveryInformation**

*InvoiceDeliveryInformation is optional. Multiple instances might exist.*

A group item that contains delivery information for invoice purposes. The delivery information that is contained will be similar to that on the DeliveryMessage.

## **InvoiceReference**

*InvoiceReference is optional. Multiple instances might exist.*

A group item detailing relevant references pertaining to the invoice e-Document. InvoiceReferenceType describes the content.

## **GeneralLedgerAccount**

*GeneralLedgerAccount is optional. A single instance might exist.*

The general ledger account to be referenced for the item.

## **SafetyAndEnvironmentalInformation**

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **MillCharacteristics**

*MillCharacteristics is optional. A single instance might exist.*

A group item defining the mill party and machine identifier where a product is or was produced.

## **TransportModeCharacteristics**

*TransportModeCharacteristics is optional and repeatable .Multiple instances might exist.*

A group item defining the primary mode of transport.

## **TransportUnitCharacteristics**

*TransportUnitCharacteristics is optional. Multiple instances might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

## **TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

## **DeliveryDateWindow**

*DeliveryDateWindow is optional. A single instance might exist.*

A group item defining the date/time interval for delivery to take place. An element which may contain the estimated date for which delivery is expected. This date is

not absolute.

## **TaxStatement**

*TaxStatement is optional. A single instance might exist.*

A group element for declaration of exception from normal charges of tax and the reason for tax exemption.

## **CountryOfOrigin**

*CountryOfOrigin is optional. A single instance might exist.*

The country of origin for the material.

## **CountryOfDestination**

*CountryOfDestination is optional. A single instance might exist.*

The country where the goods will be, or were, shipped to.

## **CountryOfConsumption**

*CountryOfConsumption is optional. A single instance might exist.*

The country of consumption for the material.

## **LocationParty**

*LocationParty is optional. Multiple instances might exist.*

The organization or business entity where the business event took place or will take place.

## InvoiceWoodSummary

Summary information that applies to all items on a Wood Market Segment Invoice.

**(sequence)**

The sequence of items below is mandatory. A single instance is required.

### TotalNumberOfLineItems


TotalNumberOfLineItems is mandatory. A single instance is required.

The total number of individual line items in the document, regardless of the status or type.

**(sequence)**

The sequence of items below is mandatory. One instance is required, multiple instances might exist.

### TotalQuantity



TotalQuantity is mandatory. A single instance is required.

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

### TotalInformationalQuantity

TotalInformationalQuantity is optional. Multiple instances might exist.

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

### LineItemSubTotal


LineItemSubTotal is optional. A single instance might exist.

The total amount of all e-Document LineBaseAmount(s) line items without any monetary adjustments that may occur after the e-Document line items.

### TotalAdjustments

TotalAdjustments is optional. A single instance might exist.

The CurrencyValue of TotalAdjustments contains the total of all MonetaryAdjustmentAmount for all instances of PriceAdjustment and FlatAmountAdjustment in the document (it excludes TaxAdjustments).



## **TotalTaxAmount**

*TotalTaxAmount is optional. A single instance might exist.*

The CurrencyValue of TotalTaxAmount contains the sum of all instances of TaxAdjustment in the document. TotalTaxAmount contains the sum of all instances of the MonetaryAdjustmentAmount for tax adjustments.

## **TotalFASAmount**

*TotalFASAmount is optional. A single instance might exist.*

TotalFASAmount is the total Free Alongside Ship value.

## **TotalNetAmount**

*TotalNetAmount is optional. A single instance might exist.*

A field containing total amount excluding tax. For example, in the Invoice TotalNetAmount is equal to the sum of LineItemSubTotal plus TotalAdjustments. TotalNetAmount encapsulates CurrencyValue.

## **TotalAmount**

*TotalAmount is mandatory. A single instance is required.*

A field containing the total amount including tax.

PurchaseOrder: The total amount, using a valid unit of measure of all the items in the e-Document. Multiple total amounts are allowed so different units of measure or grade sub-totals can be communicated.

CreditDebitNote and Invoice: TotalAmount is equal to TotalNetAmount plus TotalTaxAmount. In certain countries this is the amount that is due for payment based upon the terms of payment.

## **InformationalAmount**

*InformationalAmount is optional. Multiple instances might exist.*

A monetary amount used for information purposes only (not for calculation). For example, the invoice price adjustment subtotal is expressed in sterling pounds, and the buyer wants this information expressed in U.S. dollars.

CreditDebitNote and Invoice - The TaxAmount is displayed in the currency that is applicable throughout the e-Document. When a TaxAmount needs to be displayed in a different national currency, this field is used.

## **(sequence)**

*The sequence of items below is optional. Multiple instances might exist.*

### **TermsOfPayment**

*TermsOfPayment is mandatory. A single instance is required.*

A group item that contains agreed-to terms defining when, how, and under what conditions the payment is to be made.

When TermsOfPayment is optional; if omitted, TermsOfPayment is controlled through previous negotiation.

### **TotalNetOfTermsDiscount**

*TotalNetOfTermsDiscount is optional. A single instance might exist.*

The components of the amount to be paid if prompt payment discount terms are met, including the amount that is subject to the payment terms discount, the discount amount, and the amount due after prompt payment discount.

## **CustomsTotals**

*CustomsTotals is optional. Multiple instances might exist.*

A grouping element for customs total information.

## **CustomsStampInformation**

*CustomsStampInformation is optional. Multiple instances might exist.*

A grouping element that organises the information for customs.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **TermsAndDisclaimers**

*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.

## **TaxStatement**

*TaxStatement is optional. A single instance might exist.*

A group element for declaration of exception from normal charges of tax and the reason for tax exemption.

---

## **IsAverageValue [attribute]**

Indicates if the value is an average value or not.

*This item is restricted to the following list.*

**Yes**

**No**

IsAverageValue	
type	yesNo
default	No

---

## **IsBindingHandSeparation [attribute]**

Indicates if there is hand separation required or not for books with odd page counts.

*This item is restricted to the following list.*

**Yes**

**No**

attributes	
IsBindingHandSeparation	
type	yesNo

---

## **IsBoxed [attribute]**

*This item is restricted to the following list.*

**Yes**

Indicates that the operation should be performed and the specifications are included in the e-Document.

**No**

attribute	
IsBoxed	
type	isBoxed

Indicates that the operation will not be performed.

## **StandardOperatingProcedure**

Indicates the operation should be performed according to the Standard Operating Procedure manual provided by the customer that contains all procedures required for conducting business.

---

## **IsEaselBound [attribute]**

Specifies if the binding is at the top of the pages or not rather than on the side which changes the pagination of the pages.

*This item is restricted to the following list.*

**Yes**

**No**

---

## **IsFinalInvoice [attribute]**

Communicates to the receiver that this is the last invoice so that the customer can "close out" the associated PO as completely invoiced.

attribute	
<b>IsFinalInvoice</b>	
type	yesNo

*This item is restricted to the following list.*

**Yes**

**No**

---

## **IsHalftones [attribute]**

Indicates if the images are halftones or not.

*This item is restricted to the following list.*

**Yes**

**No**

attributes	
<b>IsHalftones</b>	
type	yesNo

---

## **ISOCountryCode [attribute]**

The valid list of ISO Country Codes.

Information on the content of this attribute is available at:

[http://www.iso.org/iso/country\\_codes/](http://www.iso.org/iso/country_codes/)

[iso\\_3166\\_code\\_lists/english\\_country\\_names\\_and\\_code\\_elements.htm](http://www.iso.org/iso/country_codes/iso_3166_code_lists/english_country_names_and_code_elements.htm)

(Note: No spaces in this URL. URL split onto two lines.)

attribute	
<b>ISOCountryCode</b>	
type	countryCode

---

## IsOptionalDestination [attribute]

Specifies if the Destination is optional or not. The default value is "No".

*This item is restricted to the following list.*

**Yes**

**No (default)**

attributes	
<b>IsOptionalDestination</b>	
type	yesNo
default	No

---

## IsPalletized [attribute]

The buyer's directions for how the item is to be palletized.

*This item is restricted to the following list.*

**Yes**

Indicates that the operation should be performed and the specifications are included in the e-Document.

**No**

Indicates that the operation will not be performed.

### StandardOperatingProcedure

Indicates the operation should be performed according to the Standard Operating Procedure manual provided by the customer that contains all procedures required for conducting business.

attribute	
<b>IsPalletized</b>	
type	isPalletized

---

## IsPartialIndicator [attribute]

Specifies if the container (e.g. pallet, box) is partially full or not.

*This item is restricted to the following list.*

**Yes**

**No**

<b>IsPartialIndicator</b>	
type	yesNo
default	No

---

## IsPartialPalletsAllowed [attribute]

Indicates if partial pallets are allowed or not.

*This item is restricted to the following list.*

**Yes**

**No**

attribute	
<b>IsPartialPalletsAllowed</b>	
type	yesNo

---

## IssueOrEventID

Used to communicate the identifier for a job.

<b>IssueOrEventID</b>	
type	s30

## IsThirdPartyAdvice [attribute]

An advice to a third party of a ShippingInstructions.

*This item is restricted to the following list.*

**Yes**

**No**




## IsThirdPartyShipment [attribute]

Shipment request to a party other than the party that ordered the product from the supplier

*This item is restricted to the following list.*

**Yes**

**No**




## IsTradeRegionAvailable [attribute]

Is the geographic area available or not.

*This item is restricted to the following list.*

**Yes**

**No**



## ItemCount

A count of the number of items (examples: a count of the number of boxes on a pallet or of reams in a box).

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**Value**

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

**RangeMin**


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

**RangeMax**

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the



parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## ItemDetails

A group element that identifies a specific item and measured attribute values for that item.

### ItemType [attribute]

*ItemType is mandatory. A single instance is required.*

Indicates the form of the item being reported as being used. Many of the ItemType(s) indicated here have a corresponding named element equivalent, which is referenced here for definition purposes.

Refer to ItemType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Identifier

*Identifier is mandatory. One instance is required, multiple instances might exist.*

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.

#### (choice)

*[choice] is optional because of choice construct.*

#### PaperCharacteristics

*PaperCharacteristics is optional because of choice construct.*

The identifying characteristics of paper most important to the ordering of the item. These are the characteristics that, when associated with a given grade, allow the manufacturer to produce but not convert or package, the paper.

#### PulpCharacteristics


*PulpCharacteristics is optional because of choice construct.*

The physical and chemical characteristics of the pulp product regardless of the form that it is taking.

#### RecoveredPaperAttributes

*RecoveredPaperAttributes is optional because of choice construct.*

The attributes of Recovered Paper.



## OtherDate

*OtherDate is optional. A single instance might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## ItemInfo

A grouping element that contains information about an item. The attribute `ItemType` defines the type of physical item.

Item Info describes property values of an item as well as tracking information between items processed in the supply chain.

### ItemType [attribute]

*ItemType is optional. A single instance might exist.*

Indicates the form of the item being reported as being used. Many of the `ItemType(s)` indicated here have a corresponding named element equivalent, which is referenced here for definition purposes.

Refer to `ItemType` definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Identifier

*Identifier is mandatory. Multiple instances might exist.*

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.

### TrackingReferenceID

*TrackingReferenceID is optional. Multiple instances might exist.*

A grouping element that defines tracking references between items processed in the supply chain.

### ItemReference


*ItemReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the Item as indicated by `ItemReferenceType` and `AssignedBy`.

### MapCoordinates

*MapCoordinates is optional. Multiple instances might exist.*

A group item defining and containing position co-ordinates of a location



## QuantityInformation

*QuantityInformation is optional. A single instance might exist.*

A group item containing information about quantity and informational quantity of similar items.

## PropertyValue

*PropertyValue is optional. Multiple instances might exist.*

Specifies a value for a property of an item. The property is defined by the attribute PropertyType. The attribute MeasuringMethod and AssignedBy can be used to clarified details for a how a property is measured or calculated, e.g. Diameter for a saw log can be measured "Under Bark" or "Over Bark". The attribute MeasuringMethodType defines how the value is created, e.g. measured automatically, calculated etc. The attribute IsAverageValue Indicates if the value is an average value or not.

## ItemInformation

The purpose of the ItemInformation structure is to clearly identify physical items. The attribute ItemType defines the type of physical item. Physical items can be handling units like packages as well as items contained in packages.

### ItemType [attribute]

*ItemType is mandatory. A single instance is required.*

Indicates the form of the item being reported as being used. Many of the ItemType(s) indicated here have a corresponding named element equivalent, which is referenced here for definition purposes.

Refer to ItemType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Identifier

*Identifier is mandatory. One instance is required, multiple instances might exist.*


An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.

### MillCharacteristics

*MillCharacteristics is optional. A single instance might exist.*

A group item defining the mill party and machine identifier where a product is or was produced.

### Quantity



*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## InformationalQuantity

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## ItemisedUsageLineItem

A group item containing information that relates to an itemized amount of usage.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Product

*Product is optional. A single instance might exist.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

### PurchaseOrderInformation

*PurchaseOrderInformation is optional. A single instance might exist.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.


### PurchaseOrderLineItemNumber

*PurchaseOrderLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the PurchaseOrder line item.

### Quantity

*Quantity is optional. A single instance might exist.*



The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## InformationalQuantity

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## BasisWeightVariation

*BasisWeightVariation is optional. A single instance might exist.*

BasisWeightVariation is the measured difference between the mill target basis weight and the mill actual basis weight.

## UsageLineItemDetail

*UsageLineItemDetail is mandatory. One instance is required, multiple instances might exist.*

For each ItemisedUsageLineItem there must be one or more UsageLineItemDetail. This element lists the specific product that has been consumed.

---

## ItemMeasuringInfo

A grouping element that contains information about measured items.

### UnCompletedMeasurement [attribute]

*UnCompletedMeasurement is optional. A single instance might exist.*

Indicates if the measuring of an item is uncompleted, i.e. if some measurement values are missing.

Refer to UnCompletedMeasurement definition for any enumerations.

### (sequence)


*The sequence of items below is mandatory. A single instance is required.*

#### ItemInfo

*ItemInfo is mandatory. A single instance is required.*

A grouping element that contains information about an item. The attribute ItemType defines the type of physical item. Item Info describes property values of an item as well as tracking information between items processed in the supply chain.

#### DownGradingInfo



*DownGradingInfo is optional. A single instance might exist.*

A grouping element that contains information about downgrading of products.

## **PriceAndAmountInfo**

*PriceAndAmountInfo is optional. A single instance might exist.*

A grouping element that contains information about price and amounts.

---

## **ItemReference**

An element detailing relevant references pertaining to the Item as indicated by ItemReferenceType and AssignedBy.

### **ItemReferenceType [attribute]**

*ItemReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.


Refer to ItemReferenceType definition for any enumerations.

### **AssignedBy [attribute]**

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.



---

## **ItemReferenceType [attribute]**

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse" or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute AssignedBy will communicate the information previously communicated in the prefix.

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.



## ItemsPerPallet

The number of items on the pallet (either reels or sheet or sheet-package).

ItemsPerPallet	
type	nni6

---

## ItemsPerTier

Number of items on each full tier, e.g. number of boxes, gaylords, loose books etc. on a tier on a pallet.

ItemsPerTier	
type	nni3

---

## ItemType [attribute]

Indicates the form of the item being reported as being used. Many of the ItemType(s) indicated here have a corresponding named element equivalent, which is referenced here for definition purposes.

attribute	
ItemType	
type	itemType

*This item is restricted to the following list.*

### **BaleItem**

### **Box**

### **BoxItem**

### **CalibrationCheckItem**

An item used for calibration checks of measuring equipments.

### **Log**

A cut portion of a stem.

### **LogBundle**

A bundle of logs (a virtual type of item).

### **LogPile**

A pile of logs (a virtual type of package).

### **LooseVolumeItem**

A unit containing loose volume products (during transports) (a type of virtual package).

### **Pallet**

### **PulpUnit**

### **ReamItem**

### **ReelItem**

### **ReelPackage**

### **Stem**

A tree without branches.

### **Tambour**

## JewelBox

Jewel box.

### JewelBoxType [attribute]

*JewelBoxType is optional. A single instance might exist.*

The type of jewel box (container for CD or DVD).

Refer to JewelBoxType definition for any enumerations.

### TrayColourType [attribute]

*TrayColourType is optional. A single instance might exist.*

The type of tray colour.

Refer to TrayColourType definition for any enumerations.

### InlayCardQuantity [attribute]

*InlayCardQuantity is optional. A single instance might exist.*

Inlay card quantity

Refer to InlayCardQuantity definition for any enumerations.

### WrapType [attribute]

*WrapType is optional. A single instance might exist.*

Communicates the type of material used to wrap the product.

Refer to WrapType definition for any enumerations.

### TearStripType [attribute]

*TearStripType is optional. A single instance might exist.*

Tear Strip Type

Refer to TearStripType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ColourSpecs


*ColourSpecs is optional. A single instance might exist.*

Colour specs

#### InsertReference

*InsertReference is optional. Multiple instances might exist.*

Insert reference



---

## JewelBoxType [attribute]

The type of jewel box (container for CD or DVD).

*This item is restricted to the following list.*

### Double

JewelBox holds 2 CDs.

### DoubleSlimLine

### DoubleSlimLineLiveHinge

### MidFrameDouble2SingleTray

### MidFrameDouble2LiveHinge

### Quad3-4CDs

### Quad5CDs

### Quad6CDs

### Single

JewelBox holds a single CD.

### StandardSingleTray

### Triple

JewelBox holds a single CD.

### Other



---

## JobCode

The particular identification code of printing an entire request known as a job.

### Agency [attribute]


*Agency is optional. A single instance might exist.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.




---

## JobDateTimeRange

The specification of the date range for the job.

### (sequence)

*The sequence of items below*



*is mandatory. A single instance is required.*

## **DateTimeFrom**

*DateTimeFrom is mandatory. A single instance is required.*

The start or beginning Date and Time of a date range.

## **DateTimeTo**

*DateTimeTo is mandatory. A single instance is required.*

The ending Date and Time of a date/time range.

---

## **JobDescription**

A textual description of the job.

<b>JobDescription</b>
type s60

---

## **JobID**

An element used to communicate the unique identifier of the Job

<b>JobID</b>
type s30


---

## **JobInformation**

JobInformation is optional. This construct captures information specific to the entire job set up.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### **JobCode**

*JobCode is mandatory. A single instance is required.*

The particular identification code of printing an entire request known as a job.

### **JobDescription**

*JobDescription is optional. A single instance might exist.*

A textual description of the job.

### **Pagination**

*Pagination is optional. A single instance might exist.*

Number of pages that make up a book.

## Joining

Defines the method used to join pieces of wood.

### JoiningType [attribute]

*JoiningType is optional. A single instance might exist.*

Defines the type of mechanical joint employed in manufacture of the product.

Refer to JoiningType definition for any enumerations.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### AdditionalText

*AdditionalText is optional. A single instance might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## JoiningType [attribute]

Defines the type of mechanical joint employed in manufacture of the product.


*This item is restricted to the following list.*

**FingerJointed**

**FingerJointed-VertUseOnly**

**Glued-Up**

**Other**



## L

The "L" component of the method of communicating colour termed  $L^*a^*b$ .


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).



#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

#### SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

#### TwoSigmaLower


*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

#### TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*


Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.



## Lab

A definition of colour using the L\*a\*b protocol.

L\*a\*b colour consists of a luminance or lightness component (L) and two chromatic components: a component (from green to red) and the b component (from blue to yellow). All the components of the definition are required. The structure of Luminance, "a", and "b" follows DetailMeasurement.



### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing  
Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### L

*L is optional. A single instance might exist.*

The "L" component of the method of communicating colour termed L\*a\*b.

#### a

*a is mandatory. A single instance is required.*

The "a" portion of the method of colour represented by L\*a\*b.

#### b

*b is mandatory. A single instance is required.*

The "b" component of the method of communicating colour termed L\*a\*b.

## LabelBrandName

The trade name or brand name used or, to be used for the label stock.

<b>LabelBrandName</b>
type s30

## LabelCharacteristics

A group item that organises the labeling information.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### CustomerMarks

*CustomerMarks is optional. Multiple instances might exist.*

The text that the buyer wants the seller to print on the package label or elsewhere.

#### LabelStyle

*LabelStyle is optional. A single instance might exist.*

A text field describing the type of special label layout requested by the buyer.

#### LabelBrandName

*LabelBrandName is optional. A single instance might exist.*

The trade name or brand name used or, to be used for the label stock.

#### LabelPosition

*LabelPosition is optional. A single instance might exist.*

Information about where the label is to be placed on the package.

#### NumberOfLabels

*NumberOfLabels is optional. A single instance might exist.*

The number of labels to be placed on the package.

#### Length

*Length is optional. A single instance might exist.*

The length of the object.


#### Width

*Width is optional. A single instance might exist.*

The width of the object.

#### ColourCode

*ColourCode is optional. A single instance might exist.*



A code indicating the colour.


## ColourDescription

*ColourDescription is optional. A single instance might exist.*

A free form description of the colour.

## LabelOrientation [attribute]

Specifies label orientation for loaded goods seen in the transport direction of the goods carrier. It makes the label visible during unloading from a predetermined side.



*This item is restricted to the following list.*

### BackEndSide

Goods labels are oriented towards the back-end side

### FrontEndSide

Goods labels are oriented towards the front-end side

### LeftAndRightSide

Goods labels are oriented towards the left side for goods to be unloaded from the left side and towards the right side for goods to be unloaded from the right side.

### LeftSide

Goods labels are oriented towards the left side

### RightSide

Goods labels are oriented towards the right side

## LabelPosition

Information about where the label is to be placed on the package.



## LabelStock

LabelStock contains the attributes and characteristics that define the label stock product.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### LabelStockCharacteristics

*LabelStockCharacteristics is optional. A single instance might exist.*

Label stock characteristics.



**(choice)**

*[choice] is optional because of choice construct.*

**SingleWidthReel**

*SingleWidthReel is optional because of choice construct.*

Single width reel information.

**TrimmedReel**

*TrimmedReel is optional because of choice construct.*

Trimmed reel

**Sheet**

*Sheet is optional because of choice construct.*

A group item that contains the conversion and packaging characteristics for sheets.

## LabelStockCharacteristics

Label stock characteristics.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**LabelStockLayer**

*LabelStockLayer is optional. Multiple instances might exist.*

Label stock layer

**ExtraFeature**


*ExtraFeature is optional. Multiple instances might exist.*

A special or extra feature that the label has or needs.

**AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## LabelStockLayer

Label stock layer

**(sequence)**


*The sequence of items below is mandatory. A single instance is required.*

**LabelStockLayerType**

*LabelStockLayerType is mandatory. A single instance is required.*

The label stock layer type

Refer to LabelStockLayerType definition for any enumerations.



# papiNet V2R31

---

## LabelStockLayerNumber

*LabelStockLayerNumber is mandatory. A single instance is required.*

The label stock layer number

## LayerMaterial

*LayerMaterial is optional. A single instance might exist.*

Used to identify the materials used in the layers of the label.

---

## LabelStockLayerNumber

The label stock layer number

<b>LabelStockLayerNumber</b>	
type	nni1

---

## LabelStockLayerType

The label stock layer type

*This item is restricted to the following list.*

**Adhesive**

**Backing**

**Face**

**Silicon**

<b>LabelStockLayerType</b>	
type	labelstockLayerType

---

## LabelStyle

A text field describing the type of special label layout requested by the buyer.

<b>LabelStyle</b>	
type	s255

---

## Language [attribute]

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Information on the content of this attribute is available at: <http://www.loc.gov/standards/iso639-2/> this is the official site of the ISO 639-2 Registration Authority.

<http://www.w3.org/International/O-HTML-tags.html> provides an explanation of the errata updating XML.

<http://www.ietf.org/rfc/rfc3066.txt> is the key document that is referenced in the above errata.

attribute	
<b>Language</b>	
type	languageType
default	eng


---

## LargeEndDiameter

Used to report the log butt end diameter as a measurement.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*


The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## LastDateOfChange

The last date for which changes to the line item may occur before it is "locked" in the production process.

LastDateOfChange encapsulates Date.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Date


*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

---

## Latitude

A measurement of the position of the party or contact in degrees north or south of the equator




---

## LayerMaterial

Used to identify the materials used in the layers of the label.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### ProductIdentifier

*ProductIdentifier is optional. A single instance might exist.*

Used to communicate the code of the article, in a variety of formats designated by the type.

### LayerMaterialName


*LayerMaterialName is optional. A single instance might exist.*

The layer material name

---

## LayerMaterialName


The layer material name



---

## LayersPerUnit


The number of layers on the shipping, handling, or delivery unit. (This element uses pattern matching to ensure the appropriate format for latitude.)



---

## LegStageType [attribute]

LegStageType is used to identify whether this is the primary transportation process or a transportation process that comes before or after the main transportation process.



*This item is restricted to the following list.*

### PreCarriage

The initial transport of goods from the seller's premises to the main port of shipment. Usually by truck, rail or on inland waterways.

### MainCarriage

The primary transport of goods, generally for the longest part of the journey and generally from one country to another. Usually by sea vessel or by airplane, but can be truck or rail as well.

### OnCarriage

Transport from the port of arrival in the country of destination to the buyer's premises. Usually by truck, rail or on inland waterways.


## Length

The approach to length used in the timber/lumber related constructs.

### ActualNominal [attribute]

*ActualNominal is optional. A single instance might exist.*

Indicates the



measurement approach used to communicate the dimensions of the individual pieces.

Refer to ActualNominal definition for any enumerations.

### WithGrain [attribute]

*WithGrain is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to WithGrain definition for any enumerations.

### (choice)

*[choice] is optional because of choice construct.*

#### Value

*Value is optional because of choice construct.*

A numeric value expressed in the unit of measure (UOM).

#### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax


*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

#### AdditionalText

*AdditionalText is optional because of choice construct.*


A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## Length

The following approach is used in the timber/lumber related constructs.


### ActualNominal [attribute]



*ActualNominal is optional. A single instance might exist.*

Indicates the measurement approach used to communicate the dimensions of the individual pieces.

Refer to ActualNominal definition for any enumerations.



### (choice)

*[choice] is optional because of choice construct.*

#### Value

*Value is optional because of choice construct.*

A numeric value expressed in the unit of measure (UOM).

#### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## Length

The length of the object.

### (sequence)


*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin



*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

## **RangeMax**

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## **LengthCategory**


Value of the length category.

### **UOM [attribute]**

*UOM is optional. A single instance might exist.*

Defines the unit of measure for the value.

Refer to UOM definition for any enumerations.



---

## **LengthCutDescription**


Length Cut Description

### **LengthCutType [attribute]**

*LengthCutType is optional. A single instance might exist.*

Indicates whether the timber length is in dimensional modules, free length or exact cut length.

Refer to LengthCutType definition for any enumerations.



---

## **LengthCutType [attribute]**

Indicates whether the timber length is in dimensional modules, free length or exact cut length.

*This item is restricted to the following list.*

### **ExactLength**

The product is cut within agreed tolerance.

### **FreeCut**

The product is free cut.

### **SpecialLength**

The product is cut in a specific length as usually cut.

### **Untrimmed**



e product is untrimmed.

## 1DecimeterCut

The product is cut in one decimeter interval.

## 3DecimeterCut

The product is cut in three decimeter interval.


---

## LengthFromCore

In relationship to a paper event (usually a mill join) where is the event in terms of the length of the paper.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)


---

## LengthSpecification

Length specification of the wood product.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### LengthCategory

*LengthCategory is optional. A single instance might exist.*

Value of the length category.

### TotalNumberOfUnits

*TotalNumberOfUnits is optional. A single instance might exist.*

The total number of units.

## LicenceNumber

Licence number.

Note: the spelling of this element conforms to papiNet's use of UK English.

<b>LicenceNumber</b>	
type	s30

## LightScattering

A group item used to communicate light scattering coefficients according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*


#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*



# papiNet V2R31

---

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

## DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

## StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper


*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## LineBaseAmount

For the particular e-Document being communicated the LineBaseAmount represents the quantity times the base unit price.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

---

## LineItemSubTotal

The total amount of all e-Document LineBaseAmount(s) line items without any monetary adjustments that may occur after the e-Document line items.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.


## LoadAvailable

The LoadAvailable element is the root element for the LoadAvailable e-Document.

The Supplier party or authorized agent sends a LoadAvailable e-Document to the BuyerParty(consuming mill) indicating that load(s) for specific product is(are) ready on a specific date for acceptance and pickup.

The LoadAvailable e-Document from the supplier may include a Shipper Load Number. This number may be used as the consuming mill's release number The Shipper Load Number is used for authorization for pick-up of load at supplier point.

LoadAvailable



### LoadAvailableType [attribute]

*LoadAvailableType is mandatory. A single instance is required.*

LoadAvailableType defines the type LoadAvailable e-Document.

Refer to LoadAvailableType definition for any enumerations.

### LoadAvailableStatusType [attribute]

*LoadAvailableStatusType is mandatory. A single instance is required.*

LoadAvailableStatusType defines the status of the entire LoadAvailable e-Document.

Refer to LoadAvailableStatusType definition for any enumerations.

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

### (sequence)

# papiNet V2R31

The sequence of items below is mandatory. A single instance is required.

## LoadAvailableHeader

*LoadAvailableHeader is mandatory. A single instance is required.*

The LoadAvailableHeader, a group item containing generic information common to the LoadAvailable e-Document.

## LoadAvailableLineItem

*LoadAvailableLineItem is mandatory. One instance is required, multiple instances might exist.*

LoadAvailableLineItem is a group item containing information that relates to a line in the LoadAvailable e-Document.

## LoadAvailableSummary

*LoadAvailableSummary is optional. A single instance might exist.*

LoadAvailable Summary


---

## LoadAvailableConfirmationIssuedDate

The date of response to the LoadAvailable e-Document from originating party.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.


hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## LoadAvailableHeader

The LoadAvailableHeader, a group item containing generic information common to the LoadAvailable e-Document.



### LoadAvailableHeaderStatusType [attribute]

*LoadAvailableHeaderStatusType is optional. A single instance might exist.*

LoadAvailableHeaderStatusType defines the status of the entire LoadAvailable e-Document at the header level.

Refer to LoadAvailableHeaderStatusType definition for any enumerations.

#### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### LoadAvailableInformation

*LoadAvailableInformation is mandatory. A single instance is required.*

LoadAvailableInformation is a group item containing information about the whole LoadAvailable e-Document.

#### BuyerParty

*BuyerParty is mandatory. A single instance is required.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

#### SupplierParty

*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **CarrierParty**

*CarrierParty is optional. A single instance might exist.*

The party performing the transport of the product from the pickup location to the ship-to location; could be a hauler.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **TransportModeCharacteristics**

*TransportModeCharacteristics is optional. A single instance might exist.*

A group item defining the primary mode of transport.

## **TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

## **TransportUnitCharacteristics**

*TransportUnitCharacteristics is optional. A single instance might exist.*

A group item defining and identifying the primary means of containing the goods.

In some instances, the transport unit and vehicle are the same.

## **TransportLoadingCharacteristics**

*TransportLoadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be loaded.

## **TransportUnloadingCharacteristics**

*TransportUnloadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be unloaded.

## **TransportOtherInstructions**

*TransportOtherInstructions is optional. Multiple instances might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **LoadAvailableHeaderStatusType [attribute]**

LoadAvailableHeaderStatusType defines the status of the entire LoadAvailable e-Document at the header level.

*This item is restricted to the following list.*

### **Accepted**

The supplied information is accepted.

### **Amended**

The supplied information is changed

### **NoAction**

The supplied information has not been amended and thereby requires no action.

### **Original**

The supplied information is the first version of that information.

### **Rejected**

The supplied information is rejected.




## LoadAvailableInformation

LoadAvailableInformation is a group item containing information about the whole LoadAvailable e-Document.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### LoadAvailableNumber

*LoadAvailableNumber is mandatory. A single instance is required.*

LoadAvailableNumber is a unique transaction number associated with the whole LoadAvailable. This number is provided by the originator of the LoadAvailable e-Document and follows the document through its life.

### LoadAvailableIssuedDate

*LoadAvailableIssuedDate is mandatory. A single instance is required.*

The date that the LoadAvailable was issued to the company to which the load was offered.

### LoadAvailableConfirmationIssuedDate

*LoadAvailableConfirmationIssuedDate is optional. A single instance might exist.*

The date of response to the LoadAvailable e-Document from originating party.

### TransactionHistoryNumber

*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

### TransactionHistoryConfirmationNumber

*TransactionHistoryConfirmationNumber is optional. A single instance might exist.*

A sequential number that indicates the version of the confirmation document being sent.

### LoadAvailableReference

*LoadAvailableReference is optional. Multiple instances might exist.*

LoadAvailableReferenceType provides a contextual explanation of the specific reference identifier.


---

## LoadAvailableIssuedDate

The date that the LoadAvailable was issued to the company to which the load was offered.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.


hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## LoadAvailableLineItem

LoadAvailableLineItem is a group item containing information that relates to a line in the LoadAvailable e-Document.



### LoadAvailableLineItemStatusType [attribute]

*LoadAvailableLineItemStatusType is mandatory. A single instance is required.*

LoadAvailableLineItemStatusType defines the status of each load defined by the LoadAvailableLineItemNumber in LoadAvailableLineItem.

Refer to LoadAvailableLineItemStatusType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### LoadAvailableLineItemNumber

*LoadAvailableLineItemNumber is mandatory. A single instance is required.*

LoadAvailableLineItemNumber is a unique number within a given LoadAvailable associating the number of loads available with a numeric sequence.

#### LoadReleaseNumber

*LoadReleaseNumber is optional. A single instance might exist.*

LoadReleaseNumber is a unique number identifying the load. The number comes from the company to whom the load was offered.

#### LoadAvailableReference

*LoadAvailableReference is optional. Multiple instances might exist.*

LoadAvailableReferenceType provides a contextual explanation of the specific reference identifier.

## **Product**

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **DeliveryDateWindow**

*DeliveryDateWindow is optional. Multiple instances might exist.*

A group item defining the date/time interval for delivery to take place. An element which may contain the estimated date for which delivery is expected. This date is not absolute.

## **Quantity**

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **LocationParty**

*LocationParty is optional. A single instance might exist.*

The organization or business entity where the business event took place or will take place.

## **ShipToParty**

*ShipToParty is optional. A single instance might exist.*

The name and/or address to which the goods should be delivered with the party type indicated by the PartyType attribute.

## **TransportModeCharacteristics**

*TransportModeCharacteristics is optional. A single instance might exist.*

A group item defining the primary mode of transport.

## **TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

## **TransportUnitCharacteristics**

*TransportUnitCharacteristics is optional. A single instance might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

## **TransportLoadingCharacteristics**

*TransportLoadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be loaded.

### **TransportUnloadingCharacteristics**

*TransportUnloadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be unloaded.

### **TransportOtherInstructions**

*TransportOtherInstructions is optional. Multiple instances might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

### **AdditionalText**

*AdditionalText is optional. A single instance might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **LoadAvailableLineItemNumber**

LoadAvailableLineItemNumber is a unique number within a given LoadAvailable associating the number of loads available with a numeric sequence.

<b>LoadAvailableLineItemNumber</b>
type   lineNumberType

---

## **LoadAvailableLineItemStatusType [attribute]**

LoadAvailableLineItemStatusType defines the status of each load defined by the LoadAvailableLineItemNumber in LoadAvailableLineItem.

attribute
<b>LoadAvailableLineItemStatusType</b>
type   loadAvailableLineItemStatusType

*This item is restricted to the following list.*

### **Accepted**

The supplied information is accepted.

### **Amended**

The supplied information is changed

### **Cancelled**

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### **NoAction**

The supplied information has not been amended and thereby requires no action.

### **Original**

The supplied information is the first version of that information.

## Pending

The supplied information is not complete and will be updated later.

## Rejected

The supplied information is rejected.

---


## LoadAvailableNumber

LoadAvailableNumber is a unique transaction number associated with the whole LoadAvailable. This number is provided by the originator of the LoadAvailable e-Document and follows the document through its life.

<b>LoadAvailableNumber</b>	
type	s30

## LoadAvailableReference

LoadAvailableReferenceType provides a contextual explanation of the specific reference identifier.



### LoadAvailableReferenceType [attribute]

*LoadAvailableReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to LoadAvailableReferenceType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*


Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## LoadAvailableReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In



the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## LoadAvailableStatusType [attribute]

LoadAvailableStatusType defines the status of the entire LoadAvailable e-Document.

*This item is restricted to the following list.*



### Accepted

The supplied information is accepted.

### Amended

The supplied information is changed.

### Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### Original

The supplied information is the first version of that information.

### Rejected


The supplied information is rejected.

## LoadAvailableSummary

LoadAvailable Summary

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### TotalNumberOfLineItems

*TotalNumberOfLineItems is optional. A single instance might exist.*

The total number of individual line items in the document, regardless of the status or type.

### TotalQuantityInformation

*TotalQuantityInformation is optional. Multiple instances might exist.*

A group item containing information about the total quantity and total informational quantity of similar items in the document. TotalQuantityInformation is primarily used in the summary section of e-Documents where it is repeatable to permit totalling for different units of measure.

### TermsAndDisclaimers

*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.

---

## LoadAvailableType [attribute]

LoadAvailableType defines the type LoadAvailable e-Document.

*This item is restricted to the following list.*

### LoadAvailable

LoadAvailable indicates the e-Document is from the company with the load.

### LoadAvailableConfirmation

LoadAvailableConfirmation indicates the e-Document is from the company to whom the load was offered.

attribute
<b>LoadAvailableType</b>
type loadAvailableType

---

## LoadingTolerance [attribute]

Specifies tolerance type for load quantity. Tolerance values are given by RangeMin and RangeMax in Quantity.

*This item is restricted to the following list.*

### FillUpFromOtherOrder

Fill up a full load from an other order

### Full

Always a full load

### FullWithinTolerance

Always a full load if still within given tolerance

### WithinTolerance

The load should be within given tolerance

attribute
<b>LoadingTolerance</b>
type loadingToleranceType

---

## LoadNumber

An element used to communicate the unique identifier of the LoadNumber.

<b>LoadNumber</b>
type s30

---

## LoadOpeningSide [attribute]

Specifies opening sides on a transport unit for loading and unloading seen in the transport direction of the goods carrier

*This item is restricted to the following list.*

attribute
<b>LoadOpeningSide</b>
type transportOrientationType

## BackEndSide

Opening for loading and unloading is towards the back-end side

## FrontEndSide

Opening for loading and unloading is towards the front-end side

## LeftAndRightSide

Openings for loading and unloading are both towards the left side and the right side.

## LeftSide

Opening for loading and unloading is towards the left side

## RightSide

Opening for loading and unloading is towards the right side

## LoadReleaseNumber

LoadReleaseNumber is a unique number identifying the load. The number comes from the company to whom the load was offered.

<b>LoadReleaseNumber</b>
type s30


## LoadTender

The LoadTender element is the root element for the LoadTender e-Document.

The LoadTender e-Document supports the transport booking process. Transport booking includes the following steps:

- LoadTender – more than one carrier has been informed about the upcoming transport.
- Booking – identifies a transport booking that is part of a detail transport plan, the load has been booked with a single carrier.

LoadTender



### LoadTenderType [attribute]

*LoadTenderType is mandatory. A single instance is required.*

Code indicating the function of the LoadTender e-Document.

Refer to LoadTenderType definition for any enumerations.

### LoadTenderStatusType [attribute]

*LoadTenderStatusType is mandatory. A single instance is required.*

Identifies the status of the entire LoadTender e-Document (in other words, at

the root level).

Refer to LoadTenderStatusType definition for any enumerations.

## **Reissued [attribute]**

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

## **Language [attribute]**

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **LoadTenderHeader**

*LoadTenderHeader is mandatory. A single instance is required.*

The LoadTenderHeader contains information common to the entire LoadTender.

### **LoadTenderSegment**

*LoadTenderSegment is mandatory. One instance is required, multiple instances might exist.*

The details for a particular load segment.

### **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates they type of adjustment being communicated.

### **LoadTenderSummary**


*LoadTenderSummary is mandatory. A single instance is required.*

Summary information that applies to the entire LoadTender e-Document.

---

## **LoadTenderAmount**

Total Amount for this LoadTender Line Item. Determined from Quantity times the PricePerUnit.



## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **CurrencyValue**

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

## LoadTenderHeader

The LoadTenderHeader contains information common to the entire LoadTender.

### LoadTenderHeaderStatusType [attribute]

*LoadTenderHeaderStatusType is mandatory. A single instance is required.*

Identifies the status of the header of the LoadTender e-Document.

Refer to



LoadTenderHeaderStatusType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### LoadTenderNumber

*LoadTenderNumber is mandatory. A single instance is required.*

The identifier for the LoadTender b-e-Document.

#### LoadTenderIssueDate

*LoadTenderIssueDate is mandatory. A single instance is required.*

The date when the e-Document was issued.

#### TransactionHistoryNumber

*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

#### LoadTenderReference


*LoadTenderReference is optional. Multiple instances might exist.*

An item detailing relevant references pertaining to the LoadTender. The type of reference is identified by the LoadTenderReferenceType attribute.

#### TransportInformation

*TransportInformation is optional. A single instance might exist.*

A grouping element for transport information.



## **SenderParty**

*SenderParty is mandatory. A single instance is required.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is mandatory. A single instance is required.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **SupplierParty**

*SupplierParty is optional. A single instance might exist.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **BuyerParty**

*BuyerParty is optional. A single instance might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## **BillToParty**

*BillToParty is optional. A single instance might exist.*

The address where the invoice is to be sent.

## **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **QuoteInCurrency**

*QuoteInCurrency is optional. A single instance might exist.*

Indicates that the quote is to be provided in the currency specified.

Refer to QuoteInCurrency definition for any enumerations.

## **RespondByDate**

*RespondByDate is optional. A single instance might exist.*

The date that a response to the query if required.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*


A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **LoadTenderHeaderStatusType [attribute]**

Identifies the status of the header of the LoadTender e-Document.

*This item is restricted to the following list.*



### **Amended**

The supplied information is changed.

### **Cancelled**

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### **Original**

The supplied information is the first version of that information.


---

## **LoadTenderIssueDate**

The date when the e-Document was issued.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### **Date**

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### **Time**

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however,

within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## LoadTenderLineItem

Group element identifying a line item to be included within this LoadTender Segment.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### LoadTenderLineItemNumber

LoadTenderLineItemNumber is mandatory. A single instance is required.

The sequential number that uniquely identifies the LoadTender line item.

#### SupplierParty



SupplierParty is optional. A single instance might exist.

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

#### Product

Product is optional. A single instance might exist.

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.


#### QuantityInformation

QuantityInformation is mandatory. A single instance is required.

A group item containing information about quantity and informational quantity of similar items.

#### LoadTenderLineItemBaseAmountInformation

LoadTenderLineItemBaseAmountInformation is optional. A single instance might exist.



Group element used to detail the LoadTender Line Item's PriceDetails and TotalAmount. Normally used to identify the PricePerUnit of the line item.

## **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates the type of adjustment being communicated.

## **LoadTenderLineItemAmount**

*LoadTenderLineItemAmount is optional. A single instance might exist.*

Total Amount of LoadTender Line Item including any adjustments. That is, the LoadTenderAmount plus all MonetaryAdjustments.

## **PackageInformation**

*PackageInformation is optional. Multiple instances might exist.*

The purpose of the PackageInformation structure is to clearly identify physical handling items that constitute the delivery.

PackageInformation is the highest level of product packaging it describes the shipping or warehousing unit.

If you are communicating a package, usually for logistics or transport purposes, you should include the PackageType, Identifier, ItemCount, and Quantity. (Note: you still have the ability to describe the item with one of the "named" items.)

If you are communicating one of the named Items there is no need to include PackageType, Identifier, ItemCount, and Quantity.

Since either of these two approaches can be used the entire contents of this element are optional even though the parent may be required. It is expected that you will fill in the appropriate details.

## **LengthSpecification**

*LengthSpecification is optional. Multiple instances might exist.*

Length specification of the wood product.

## **LoadTenderReference**

*LoadTenderReference is optional. Multiple instances might exist.*

An item detailing relevant references pertaining to the LoadTender. The type of reference is identified by the LoadTenderReferenceType attribute.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **SafetyAndEnvironmentalInformation**


*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

---

## LoadTenderLineItemAmount

Total Amount of LoadTender Line Item including any adjustments. That is, the LoadTenderAmount plus all MonetaryAdjustments.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### CurrencyValue


*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

---

## LoadTenderLineItemBaseAmountInformation

Group element used to detail the LoadTender Line Item's PriceDetails and TotalAmount. Normally used to identify the PricePerUnit of the line item.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### PriceDetails

*PriceDetails is mandatory. A single instance is required.*

An element that groups together price information.

### LoadTenderAmount


*LoadTenderAmount is optional. A single instance might exist.*

Total Amount for this LoadTender Line Item. Determined from Quantity times the PricePerUnit.

---

## LoadTenderLineItemNumber


The sequential number that uniquely identifies the LoadTender line item.



---

## LoadTenderNumber


The identifier for the LoadTender b-e-Document.



---

## LoadTenderReference

An item detailing relevant references pertaining to the LoadTender. The type of reference is identified by the LoadTenderReferenceType attribute.



### LoadTenderReferenceType [attribute]

*LoadTenderReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to LoadTenderReferenceType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*


Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## LoadTenderReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.



Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## LoadTenderResponse


The LoadTenderResponse element is the root element for the LoadTenderResponse e-Document.

The LoadTenderResponse e-Document supports the transport booking process and is used as a response e-Document to LoadTender e-Document.

Transport booking includes the following steps:

- LoadTenderResponse – more than one carrier has been informed about the upcoming transport.
- BookingConfirmation – identifies a transport booking that is part of a detail transport plan, the load has been booked with a single carrier.

LoadTenderResponse



The LoadTenderResponse provides a means of communicating these events.

### LoadTenderResponseType [attribute]

*LoadTenderResponseType is mandatory. A single instance is required.*

Code indicating the function of the e-Document.

Refer to LoadTenderResponseType definition for any enumerations.

### LoadTenderResponseStatusType [attribute]

*LoadTenderResponseStatusType is mandatory. A single instance is required.*

Identifies the status of the entire LoadTenderResponse e-Document (in other words, at the root level).

Refer to LoadTenderResponseStatusType definition for any enumerations.

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**LoadTenderResponseHeader**

*LoadTenderResponseHeader is mandatory. A single instance is required.*

The LoadTenderResponseHeader contains information common to the entire LoadTenderResponse.

**LoadTenderResponseSegment**

*LoadTenderResponseSegment is optional. Multiple instances might exist.*

The details for a particular load segment.

**MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates they type of adjustment being communicated.


**LoadTenderResponseSummary**

*LoadTenderResponseSummary is mandatory. A single instance is required.*

Summary information that applies to the entire LoadTenderResponse e-Document.

## LoadTenderResponseHeader

The LoadTenderResponseHeader contains information common to the entire LoadTenderResponse.



### LoadTenderResponseHeaderStatusType [attribute]

*LoadTenderResponseHeaderStatusType is mandatory. A single instance is required.*

Identifies the status of the header of the LoadTenderResponse e-Document.

Refer to LoadTenderResponseHeaderStatusType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### LoadTenderResponseNumber

*LoadTenderResponseNumber is mandatory. A single instance is required.*

The identifier for the LoadTenderResponse e-Document.

#### LoadTenderResponseIssueDate

*LoadTenderResponseIssueDate is mandatory. A single instance is required.*

The date when the e-Document was issued.

#### LoadTenderNumber

*LoadTenderNumber is optional. A single instance might exist.*

The identifier for the LoadTender b-e-Document.

## **LoadTenderIssueDate**

*LoadTenderIssueDate is optional. A single instance might exist.*

The date when the e-Document was issued.

## **TransactionHistoryNumber**

*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

## **TransactionHistoryConfirmationNumber**

*TransactionHistoryConfirmationNumber is optional. A single instance might exist.*

A sequential number that indicates the version of the confirmation document being sent.

## **LoadTenderResponseReference**

*LoadTenderResponseReference is optional. Multiple instances might exist.*

An item detailing relevant references pertaining to the LoadTenderResponse. The type of reference is identified by the LoadTenderReferenceType attribute.

## **TransportInformation**

*TransportInformation is optional. A single instance might exist.*

A grouping element for transport information.

## **SenderParty**

*SenderParty is mandatory. A single instance is required.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is mandatory. A single instance is required.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **SupplierParty**

*SupplierParty is optional. A single instance might exist.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **BuyerParty**

*BuyerParty is optional. A single instance might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-

to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## **BillToParty**

*BillToParty is optional. A single instance might exist.*

The address where the invoice is to be sent.

## **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **QuoteInCurrency**

*QuoteInCurrency is optional. A single instance might exist.*

Indicates that the quote is to be provided in the currency specified.

Refer to QuoteInCurrency definition for any enumerations.

## **ValidityPeriod**

*ValidityPeriod is optional. A single instance might exist.*

The validity period for a specific item, e.g. the validity period for an e-Document.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **LoadTenderResponseHeaderStatusType [attribute]**

Identifies the status of the header of the LoadTenderResponse e-Document.

*This item is restricted to the following list.*

attribute
<b>LoadTenderResponseHeaderStatusType</b>
type   loadTenderResponseStatusType

### **Accepted**

The supplied information is accepted.

### **Amended**

The supplied information is changed

### **Cancelled**

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

## Rejected

The supplied information is rejected.


---

## LoadTenderResponseIssueDate

The date when the e-Document was issued.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## LoadTenderResponseLineItem

The details for a particular load line item.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### LoadTenderResponseLineItemNumber

*LoadTenderResponseLineItemNumber is mandatory. A single instance is required.*

The sequential number that uniquely identifies the LoadTenderResponse line item.

### SupplierParty

*SupplierParty is optional. A single instance might exist.*

The organisation or business entity responsible for providing the product.

SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

### Product

*Product is optional. A single instance might exist.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in

papiNet.

## **QuantityInformation**

*QuantityInformation is mandatory. A single instance is required.*

A group item containing information about quantity and informational quantity of similar items.

## **LoadTenderLineItemBaseAmountInformation**

*LoadTenderLineItemBaseAmountInformation is optional. A single instance might exist.*

Group element used to detail the LoadTender Line Item's PriceDetails and TotalAmount. Normally used to identify the PricePerUnit of the line item.

## **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates they type of adjustment being communicated.

## **LoadTenderLineItemAmount**

*LoadTenderLineItemAmount is optional. A single instance might exist.*

Total Amount of LoadTender Line Item including any adjustments. That is, the LoadTenderAmount plus all MonetaryAdjustments.

## **PackageInformation**

*PackageInformation is optional. Multiple instances might exist.*

The purpose of the PackageInformation structure is to clearly identify physical handling items that constitute the delivery.

PackageInformation is the highest level of product packaging it describes the shipping or warehousing unit.

If you are communicating a package, usually for logistics or transport purposes, you should include the PackageType, Identifier, ItemCount, and Quantity. (Note: you still have the ability to describe the item with one of the "named" items.)

If you are communicating one of the named Items there is no need to include PackageType, Identifier, ItemCount, and Quantity.

Since either of these two approaches can be used the entire contents of this element are optional even though the parent may be required. It is expected that you will fill in the appropriate details.

## **LengthSpecification**

*LengthSpecification is optional. Multiple instances might exist.*

Length specification of the wood product.

## **LoadTenderResponseReference**

*LoadTenderResponseReference is optional. Multiple instances might exist.*

An item detailing relevant references pertaining to the LoadTenderResponse. The type of reference is identified by the LoadTenderReferenceType attribute.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## SafetyAndEnvironmentalInformation

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

## LoadTenderResponseLineItemNumber

The sequential number that uniquely identifies the LoadTenderResponse line item.

<b>LoadTenderResponseLineItemNumber</b>
type   lineNumberType

## LoadTenderResponseNumber

The identifier for the LoadTenderResponse e-Document.

<b>LoadTenderResponseNumber</b>
type   s30

## LoadTenderResponseReference

An item detailing relevant references pertaining to the LoadTenderResponse. The type of reference is identified by the

<b>LoadTenderResponseReference</b>
type   s255

attributes
<b>LoadTenderResponseReferenceType</b>
type   referenceType
<b>AssignedBy</b>
type   partyType

LoadTenderReferenceType attribute.

### LoadTenderResponseReferenceType [attribute]

*LoadTenderResponseReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to LoadTenderResponseReferenceType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*


Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## LoadTenderResponseReferenceType [attribute]


Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.



Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## LoadTenderResponseSegment

The details for a particular load segment.



### LoadTenderResponseSegmentStatusType [attribute]

*LoadTenderResponseSegmentStatusType* is mandatory. A single instance is required.

Identifies the status of the load tender segment.

Refer to *LoadTenderResponseSegmentStatusType* definition for any enumerations.

## **LoadTenderResponseSegmentDocumentStatus [attribute]**

*LoadTenderResponseSegmentDocumentStatus is optional. A single instance might exist.*

Defines the actual document status for the LoadTenderResponseSegment.

Refer to LoadTenderResponseSegmentDocumentStatus definition for any enumerations.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

#### **LoadTenderResponseSegmentNumber**

*LoadTenderResponseSegmentNumber is mandatory. A single instance is required.*

The identifier for the LoadTenderResponse segment.

#### **LoadTenderSegmentNumber**

*LoadTenderSegmentNumber is optional. A single instance might exist.*

The identifier for the LoadTender segment.

#### **ShipFromCharacteristics**

*ShipFromCharacteristics is optional. A single instance might exist.*

A group item that provides information pertaining to the Ship-From Party.

ShipFromCharacteristics may be referenced at both the header and line item level. The reference at the header, if it exists, acts as a default for the value at the line level, unless overridden at the line level.

#### **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

#### **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

#### **CoLoading**

*CoLoading is optional. Multiple instances might exist.*

A group item specifying information about items to be loaded or loaded on the same transport unit.

Used to identify:

- Delivery together to the drop point

- Transport Orders stuffed together in a container

- Transport Orders not splittable

#### **DeliveryDateWindow**

*DeliveryDateWindow is mandatory. One instance is required, multiple instances might exist.*

# papiNet V2R31

---

A group item defining the date/time interval for delivery to take place. An element which may contain the estimated date for which delivery is expected. This date is not absolute.

## QuantityInformation

*QuantityInformation is optional. A single instance might exist.*

A group item containing information about quantity and informational quantity of similar items.

## TransportInformation

*TransportInformation is optional. A single instance might exist.*

A grouping element for transport information.

## OrderStatusInformation

*OrderStatusInformation is optional. A single instance might exist.*

A group element that stores two levels of order status codes.

## LoadTenderResponseReference

*LoadTenderResponseReference is optional. Multiple instances might exist.*

An item detailing relevant references pertaining to the LoadTenderResponse. The type of reference is identified by the LoadTenderReferenceType attribute.

## LoadTenderResponseLineItem

*LoadTenderResponseLineItem is mandatory. One instance is required, multiple instances might exist.*

The details for a particular load line item.

## MonetaryAdjustment

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates they type of adjustment being communicated.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## LoadTenderResponseSegmentDocumentStatus [attribute]

Defines the actual document status for the LoadTenderResponseSegment.

*This item is restricted to the following list.*

### Cancelled

The supplied information of the document item is cancelled. Items that have been cancelled are not included in totals on the summary level of e-Documents.

attribute
<b>LoadTenderResponseSegmentDocumentStatus</b>
type documentStatusType.LoadTenderResponse

## Confirmed

The supplied information of the document item is agreed. If a requested change or cancellation of an existing document item can not be accepted, then the earlier agreed information of the document item will be re-confirmed.

## Pending

The supplied information of the document item is being investigated.

## Rejected

The supplied information of the document item can not be accepted. The document item is new or not earlier confirmed.

---

## LoadTenderResponseSegmentNumber

The identifier for the LoadTenderResponse segment.

<b>LoadTenderResponseSegmentNumber</b>
type   lineNumberType

---

## LoadTenderResponseSegmentStatusType [attribute]

Identifies the status of the LoadTender segment.

*This item is restricted to the following list.*

attribute
<b>LoadTenderResponseSegmentStatusType</b>
type   loadTenderResponseStatusType

### Accepted

The supplied information is accepted.

### Amended

The supplied information is changed.

### Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### Rejected

The supplied information is rejected.

---

## LoadTenderResponseStatusType [attribute]

Identifies the status of the entire LoadTender response e-Document (in other words, at the root level).

*This item is restricted to the following list.*

### Accepted

The supplied information is accepted.

### Amended

The supplied information is changed

attribute
<b>LoadTenderResponseStatusType</b>
type   loadTenderResponseStatusType

## Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

## Rejected

The supplied information is rejected.

## LoadTenderResponseSummary

Summary information that applies to the entire LoadTenderResponse e-Document.

(sequence)

The sequence of items below is mandatory. A single instance is required.

### TotalQuantityInformation

TotalQuantityInformation is optional. Multiple instances might exist.

A group item

containing

information about the total quantity and total informational quantity of similar items in the document. TotalQuantityInformation is primarily used in the summary section of e-Documents where it is repeatable to permit totalling for different units of measure.

### LineItemSubTotal

LineItemSubTotal is optional. A single instance might exist.

The total amount of all e-Document LineBaseAmount(s) line items without any monetary adjustments that may occur after the e-Document line items.

### TotalAdjustments

TotalAdjustments is optional. A single instance might exist.

The CurrencyValue of TotalAdjustments contains the total of all MonetaryAdjustmentAmount for all instances of PriceAdjustment and FlatAmountAdjustment in the document (it excludes TaxAdjustments).

### TotalTaxAmount

TotalTaxAmount is optional. A single instance might exist.


The CurrencyValue of TotalTaxAmount contains the sum of all instances of TaxAdjustment in the document. TotalTaxAmount contains the sum of all instances of the MonetaryAdjustmentAmount for tax adjustments.

### TotalNetAmount

TotalNetAmount is optional. A single instance might exist.

A field containing total amount excluding tax. For example, in the Invoice TotalNetAmount is equal to the sum of LineItemSubTotal plus TotalAdjustments. TotalNetAmount encapsulates CurrencyValue.

### TotalAmount



# papiNet V2R31

---

*TotalAmount is optional. A single instance might exist.*

A field containing the total amount including tax.

PurchaseOrder: The total amount, using a valid unit of measure of all the items in the e-Document. Multiple total amounts are allowed so different units of measure or grade sub-totals can be communicated.

CreditDebitNote and Invoice: TotalAmount is equal to TotalNetAmount plus TotalTaxAmount. In certain countries this is the amount that is due for payment based upon the terms of payment.

## **InformationalAmount**

*InformationalAmount is optional. Multiple instances might exist.*

A monetary amount used for information purposes only (not for calculation). For example, the invoice price adjustment subtotal is expressed in sterling pounds, and the buyer wants this information expressed in U.S. dollars.

CreditDebitNote and Invoice - The TaxAmount is displayed in the currency that is applicable throughout the e-Document. When a TaxAmount needs to be displayed in a different national currency, this field is used.

## **TermsInformation**

*TermsInformation is optional. Multiple instances might exist.*

An element that contains the term related information.

## **TermsAndDisclaimers**

*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.

---

## **LoadTenderResponseType [attribute]**

Code indicating the function of the e-Document.

*This item is restricted to the following list.*

<i>attribute</i>
<b>LoadTenderResponseType</b>
<i>type</i>   loadTenderResponseType

### **PreBookingConfirmation**

A communication of the requirement for a transport vehicle or unit reservation that has risen from a rough transport plan.

### **BookingConfirmation**

A communication affirming the placement of the booking with a particular party.

### **LoadTenderResponse**

Indicates the ability of the respondent to fulfill the load tender request.

## LoadTenderSegment

The details for a particular load segment.

### LoadTenderSegmentStatusType [attribute]

*LoadTenderSegmentStatusType is mandatory. A single instance is required.*

Identifies the status of the LoadTender segment.

Refer to



LoadTenderSegmentStatusType definition for any enumerations.

### LoadTenderSegmentDocumentStatus [attribute]

*LoadTenderSegmentDocumentStatus is optional. A single instance might exist.*

Defines the actual document status for the LoadTenderSegment.

Refer to LoadTenderSegmentDocumentStatus definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### LoadTenderSegmentNumber

*LoadTenderSegmentNumber is mandatory. A single instance is required.*

The identifier for the LoadTender segment.


#### ShipFromCharacteristics

*ShipFromCharacteristics is optional. A single instance might exist.*

A group item that provides information pertaining to the Ship-From Party.

ShipFromCharacteristics may be referenced at both the header and line item level. The reference at the header, if it exists, acts as a default for the value at the line level, unless overridden at the line level.

#### ShipToCharacteristics



*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **CoLoading**

*CoLoading is optional. Multiple instances might exist.*

A group item specifying information about items to be loaded or loaded on the same transport unit.

Used to identify:

- Delivery together to the drop point
- Transport Orders stuffed together in a container
- Transport Orders not splittable

## **DeliveryDateWindow**

*DeliveryDateWindow is mandatory. One instance is required, multiple instances might exist.*

A group item defining the date/time interval for delivery to take place. An element which may contain the estimated date for which delivery is expected. This date is not absolute.

## **TransportInformation**

*TransportInformation is optional. A single instance might exist.*

A grouping element for transport information.

## **QuantityInformation**

*QuantityInformation is optional. A single instance might exist.*

A group item containing information about quantity and informational quantity of similar items.

## **OrderStatusInformation**

*OrderStatusInformation is optional. A single instance might exist.*

A group element that stores two levels of order status codes.

## **LoadTenderReference**

*LoadTenderReference is optional. Multiple instances might exist.*

An item detailing relevant references pertaining to the LoadTender. The type of reference is identified by the LoadTenderReferenceType attribute.

## **LoadTenderLineItem**

*LoadTenderLineItem is mandatory. One instance is required, multiple instances might exist.*

Group element identifying a line item to be included within this LoadTender Segment.

## MonetaryAdjustment

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates they type of adjustment being communicated.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## LoadTenderSegmentDocumentStatus [attribute]

Defines the actual document status for the LoadTenderSegment.

*This item is restricted to the following list.*

attribute
<b>LoadTenderSegmentDocumentStatus</b>
type   documentStatusType.LoadTender

### Cancelled

The supplied information of the document item is cancelled. Items that have been cancelled are not included in totals on the summary level of e-Documents.

### Requested

The supplied information of the document item is ordered.

---

## LoadTenderSegmentNumber

The identifier for the LoadTender segment.

<b>LoadTenderSegmentNumber</b>
type   lineNumberType

---

## LoadTenderSegmentStatusType [attribute]

Identifies the status of the LoadTender segment.

*This item is restricted to the following list.*

attribute
<b>LoadTenderSegmentStatusType</b>
type   loadTenderStatusType

### Amended

The supplied information is changed.

### Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Documents.


### Original

The supplied information is the first version of that information.

## LoadTenderStatusType [attribute]

Identifies the status of the entire LoadTender e-Document (in other words, at the root level).

*This item is restricted to the following list.*



### Amended

The supplied information is changed

### Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### Original



The supplied information is the first version of that information.

## LoadTenderSummary

Summary information that applies to the entire LoadTender e-Document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### TotalQuantityInformation

*TotalQuantityInformation is optional. Multiple instances might exist.*

A group item containing information about the total quantity and total informational quantity of similar items in the document. TotalQuantityInformation is primarily used in the summary section of e-Documents where it is repeatable to permit totalling for different units of measure.

### LineItemSubTotal

*LineItemSubTotal is optional. A single instance might exist.*

The total amount of all e-Document LineBaseAmount(s) line items without any monetary adjustments that may occur after the e-Document line items.

### LengthSpecification

*LengthSpecification is optional. Multiple instances might exist.*

Length specification of the wood product.

### TermsAndDisclaimers


*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.

## LoadTenderType [attribute]

Code indicating the function of the LoadTender e-Document.

*This item is restricted to the following list.*



### PreBooking

A requirement for a transport vehicle or unit reservation that has risen from a rough transport plan.

### Booking

An indication that time for a service is required. For example a booking that is part of a detail transport plan.


### LoadTender

More than one carrier has been informed about the upcoming transport requirement (the load).

## LocationCode

A code used to identify a specific physical location within a site identified by a party, e.g. a loading station in a warehouse or an unloading station at a printer site.

LocationCode will be deprecated in a future version. Use SupplyPoint instead of LocationCode.



## Agency [attribute]

*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.


Refer to Agency definition for any enumerations.

## LocationIdentifier

Options for identifying a physical location.

### (choice)

*[choice] is optional because of choice construct.*



### GPSCoordinates

*GPSCoordinates is optional because of choice construct.*

The location of the party as specified using a Global Positioning System.

## MapCoordinates

*MapCoordinates is optional because of choice construct.*

A group item defining and containing position co-ordinates of a location.

## LocationInformation

A grouping element describing the location of the shipment.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### (choice)

*[choice] is optional because of choice construct.*

#### LocationIdentifier

*LocationIdentifier is optional because of choice construct.*

Options for identifying a physical location.

#### LocationParty

*LocationParty is optional because of choice construct.*

The organization or business entity where the business event took place or will take place.

### (choice)

*[choice] is optional because of choice construct.*

#### SupplyPoint

*SupplyPoint is optional because of choice construct.*

Grouping element that contains items describing a supply point. A SupplyPoint belongs to a LocationParty, e.g. in a DeliveryOrigin or DeliveryDestination, and describes where goods are stored and can be loaded or unloaded. A SupplyPoint can for example be a loading or unloading gate at a warehouse or a road side landing at a logging area in the forest.

#### LocationCode

*LocationCode is optional because of choice construct.*


A code used to identify a specific physical location within a site identified by a party, e.g. a loading station in a warehouse or an unloading station at a printer site.

LocationCode will be deprecated in a future version. Use SupplyPoint instead of LocationCode.

### StopOffInformation

*StopOffInformation is optional. A single instance might exist.*

Where is the shipment and how far to the next stop.



## LocationParty

The organization or business entity where the business event took place or will take place.

### LocationType [attribute]

*LocationType is optional. A single instance might exist.*

Defines type of location when context needs to be specified, e.g. when goods are moved from one location to a new location..

Refer to LocationType definition for any enumerations.

### PartyType [attribute]

*PartyType is mandatory. A single instance is required.*

Identifies the business role associated with the particular party

Refer to PartyType definition for any enumerations.

### LogisticsRole [attribute]

*LogisticsRole is optional. A single instance might exist.*

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PartyIdentifier

*PartyIdentifier is optional. Multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

#### NameAddress

*NameAddress is mandatory. A single instance is required.*

A group item containing name and address of an organisation or business entity.

#### URL


*URL is optional. A single instance might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

#### CommonContact


*CommonContact is optional. Multiple instances might exist.*

Identifies a specific individual associated with the party.



## LocationQualifier [attribute]

An attribute of the shipment method of payment describing the location to which the delivery terms refer. This location determines where and when the goods ownership is transferred from the seller to the buyer.



*This item is restricted to the following list.*

### **Destination**

Ownership is transferred at the final destination.

### **DistributionCentre**

Ownership is transferred at the distribution centre, which is an intermediate warehouse.

### **Dock**

Ownership is transferred at the dock.

### **Factory**

Ownership is transferred where the product is made.

### **Mill**

Ownership is transferred at the manufacturing unit (paper mill).

### **OnVesselFOBPoint**

Ownership is transferred on the vessel.

### **Origin**

Ownership is transferred at the originating shipment location.

### **OriginAfterLoadingOnEquipment**

Ownership is transferred at the time equipment is loaded at the mill/warehouse/terminal.

### **OriginShippingPoint**

Ownership is transferred at the origin shipping point, in other words, at the port of loading.

### **Plant**

Ownership does not transfer until received at the buyer's facility.

### **Port**

Ownership is transferred at the port.

### **Reload**

Ownership is transferred when the product is reloaded for final shipment.

### **Terminal**


Ownership is transferred at the terminal

### **Warehouse**

Ownership changes upon departure of the goods from the warehouse.

## LocationType [attribute]

Defines type of location when context needs to be specified, e.g. when goods are moved from one location to a new location.



*This item is restricted to the following list.*

### **Destination**

Defines location as a Destination

### **Origin**

Defines location as an Origin

---

## LocationType [attribute]

Location of Break on the Press. A group item detailing relevant locations on the press to the Performance e-Document.



*This item is restricted to the following list.*

### **AirTurn**

After Colour Unit – just prior to Dryer

### **Chills**

After Dryer – on chill rolls

### **Dryer**

Within Dryer equipment

### **Folder**

Within Folders ; prior to cut off delivery

### **Infeed**

Prior to Printing Units, after Reel Stand /Splicing Area

### **PrintingUnit**

Within any colour unit

### **ReelStand**

Non Splice phase – prior to Infeed

### **RibbonDeck**

After slitting ; prior to folder

### **Slitter**

As Web is slit to ribbons

### **Splicer**


During the pasting cycle

## Log

Log information

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### LogCharacteristics

*LogCharacteristics is optional. A single instance might exist.*

Log characteristics

### LogPackagingCharacteristics

*LogPackagingCharacteristics is optional. A single instance might exist.*

Log packaging characteristics

## LogCharacteristics

Log characteristics

### LogLengthType [attribute]

*LogLengthType is optional. A single instance might exist.*

Log length type

Refer to LogLengthType definition for any enumerations.

### Debarked [attribute]

*Debarked is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Debarked definition for any enumerations.

### LogConversionRule [attribute]

*LogConversionRule is optional. A single instance might exist.*

Used to report the standard conversion rule used when converting log size to board-feet or other volume measurement

Refer to LogConversionRule definition for any enumerations.

### (sequence)


*The sequence of items below is mandatory. A single instance is required.*

### Length

*Length is optional. A single instance might exist.*

The length of the object.

### SmallEndDiameter



# papiNet V2R31

---

*SmallEndDiameter is optional. A single instance might exist.*

Reports the log crown end diameter as a measurement.

## **LargeEndDiameter**

*LargeEndDiameter is optional. A single instance might exist.*

Used to report the log butt end diameter as a measurement.

## **DiameterBreastHeight**

*DiameterBreastHeight is optional. A single instance might exist.*

Used to report the log diameter 4.5 feet from the butt end as a measurement. Used with the LogConversionRule attribute to determine log's volume conversion to board-feet or other measure.

---

## **LogConversionRule [attribute]**

Used to report the standard conversion rule used when converting log size to board-feet or other volume measurement



*This item is restricted to the following list.*

### **Doyle**

The Doyle Log Rule, developed around 1825, is based on a mathematical formula and is widely used throughout the southern United States. This rule allows for a saw kerf of 5/16 inch and a slabbing allowance of 4 inches, which is about twice the normal amount. Because of this, the Doyle Rule is somewhat inconsistent; it underestimates small logs and overestimates large logs. As a seller of timber, you must be aware that for smaller logs the Doyle Rule will underestimate the actual volume of wood that you have in your trees.

### **International**

This rule was developed in 1906 and is based on a reasonably accurate mathematical formula. The rule allows for a 1/4-inch saw kerf and a fixed taper allowance of 1/2 inch per 4 feet of log length. Deductions are also allowed for shrinkage of boards and a slab thickness that varies with the log diameter. Overall, the International 1/4-Inch Log Rule is the most consistent and is often used as a basis of comparison for log rules.

### **Scribner**

The Scribner Log Rule, developed around 1846, is a good example of a diagram rule. It was created by drawing the cross-sections of 1-inch boards within circles representing the end view of logs. A space of 1/4 inch was left between the boards to account for saw kerf. The Scribner Rule does not have an allowance for log taper and typically underestimates logs, particularly if the log length is long.

### **ScribnerDecimalC**

The Scribner Decimal C is a different form of the Scribner Rule; it rounds the volumes to the nearest 10 board feet. For example, 392 board feet on the Scribner is equivalent to 390 board feet on the Scribner Decimal C scale.

## LogisticsRole [attribute]

Communicates the nature of the logistics role, if any, the party plays in the transaction.

*This item is restricted to the following list.*



### Consignee

The party to whom the goods are turned over to.

### Consignor

The party who is responsible for the goods prior to the shipping process.

### LogisticsProvider

The party who is responsible for logistics services. This definition of LogisticsProvider allows you to define a party as a buyer of logistics services as well as a supplier of logistics services.

## LogLengthType [attribute]

Log length type

*This item is restricted to the following list.*



### CutToLength

### RandomLength

### Short

### TreeLength

## LogPackagingCharacteristics

Log packaging characteristics

### DoubleBunked [attribute]

*DoubleBunked is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to DoubleBunked definition for any enumerations.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Identifier

*Identifier is mandatory. One instance is required, multiple instances might exist.*

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from



the barcode printed on the label.

## **ItemCount**

*ItemCount is optional. A single instance might exist.*

A count of the number of items (examples: a count of the number of boxes on a pallet or of reams in a box).

## **Quantity**

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

---

## **Longitude**

A measurement of the position of the party or contact in degrees east or west of the prime meridian

<b>Longitude</b>	
type	dec18-8

## LumberGrade

Defines quality characteristics achieved by selecting pieces based on a grading rule.

### GradeType [attribute]

*GradeType is optional. A single instance might exist.*

Grade Type

Refer to GradeType definition for any enumerations.

### GradingRule [attribute]

*GradingRule is optional. A single instance might exist.*

Grading rule, the rules under which the product has been graded.

Refer to GradingRule definition for any enumerations.

### GradeAgency [attribute]

*GradeAgency is optional. A single instance might exist.*

LumberAgency identifies which agency is responsible for assigning the lumber attributes.

Refer to GradeAgency definition for any enumerations.

### ModulusElasticity [attribute]

*ModulusElasticity is optional. A single instance might exist.*

Modulus elasticity

Refer to ModulusElasticity definition for any enumerations.

### Face [attribute]

*Face is optional. A single instance might exist.*

Used to describe which side (or face) of the product that the grade is applicable to.

Refer to Face definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### GradeName

*GradeName is optional. A single instance might exist.*


A specific product name for which the owner or source is specified in the "@AssignedBy" attribute (for example, ImprovedNewsprint-45-1479)

#### GradeCode

*GradeCode is optional. A single instance might exist.*

A specific product code for which the owner or source is specified in the "@AssignedBy" attribute

#### AdditionalText



*AdditionalText is optional. A single instance might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## LumberSpecies

Specifies the raw material species.

### SpeciesType [attribute]

*SpeciesType is optional. A single instance might exist.*

Defines the species or mix of species comprising the product.

Refer to SpeciesType definition for any enumerations.

### SpeciesOrigin [attribute]

*SpeciesOrigin is optional. A single instance might exist.*

The country of origin of the species employed in manufacture of the product.

Refer to SpeciesOrigin definition for any enumerations.

### SpeciesAgency [attribute]

*SpeciesAgency is optional. A single instance might exist.*

Defines the governing organisation of the scheme employed in determining the species of the product.

Refer to SpeciesAgency definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### SpeciesCode


*SpeciesCode is optional. A single instance might exist.*

Species Code

#### AdditionalText

*AdditionalText is optional. A single instance might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## Luminance

Luminance

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax


*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.



## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.


---

## Machine

Machine is used to capture information specific to the particular machine used in the conversion or consumption process.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### MachineID

*MachineID is mandatory. A single instance is required.*

An identifier assigned to the particular machine being referenced. For example, a machine could be a paper machine, an off-line coater, a sheeter, or a printing press. The particular machine being referenced will be determined by the business event being supported.

### ReelArm

*ReelArm is optional. A single instance might exist.*

The reel arm number.

### ReelStandUnit

*ReelStandUnit is optional. A single instance might exist.*

The reelstand unit number.

---

## MachineConditions

A grouping element for all the environmental measurement at the time of the run.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### Humidity

*Humidity is optional. Multiple instances might exist.*

Humidity

### AmbientTemperature

*AmbientTemperature is optional. Multiple instances might exist.*

The temperature of the surrounding environment.

### MachineSpeed


*MachineSpeed is optional. Multiple instances might exist.*

The rate at which the machine is, was, or should be running.

### Tension

*Tension is optional. Multiple instances might exist.*

Tension of the web on the printing press.



## MachineDownTime

The length of loss production time that a machine experienced due to malfunction regardless of cause.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



---

## MachineID

An identifier assigned to the particular machine being referenced. For example, a machine could be a paper machine, an off-line coater, a sheeter, or a printing press. The particular machine being referenced will be determined by the business event being supported.

MachineID	
type	s20

---

## MachineLocation

A unique and defined area in the operating machine. On a printing press it would include areas such as: "Splicer", "Infeed", "Print Unit", "folder", "Silcone coater". Also see PressBreakLocation.

MachineLocation	
type	s20

---

## MachineSpeed

The rate at which the machine is, was, or should be running.

### SpeedType [attribute]

*SpeedType is optional. A single instance might exist.*

Speed Type

Refer to SpeedType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## MachineStoppage [attribute]

An indicator on whether the production had to be periodically stopped.

*This item is restricted to the following list.*

**Yes**

**No**

attribute	
<b>MachineStoppage</b>	
type	yesNo
default	No

## Magenta

The Magenta component of a colour.

Magenta is a locally defined element used in the CMYK element.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

#### SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

#### TwoSigmaLower


*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

#### TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the




upper side of the standard deviation.

---

## MailAttachment

MailAttachment enables the complainer to indicate that they are providing by mail (express courier, snail mail etc.) proof of the Complaint.



### MailAttachmentType [attribute]

*MailAttachmentType is optional. A single instance might exist.*

The type of mail attachment.

Refer to MailAttachmentType definition for any enumerations.

---

## MailAttachmentType [attribute]

The type of mail attachment.

*This item is restricted to the following list.*



### BillOfLading

The mail attachment is a bill of lading.

### CMR

Collection maintenance repair, a standard book repair method

### Photo

The mail attachment is a photo.

### Sample

The mail attachment is a sample.


### Waybill

The forwarding agreement or carrying agreement that is used as a receipt for cargo and as a contract of carriage.

---

## MakeTo

Indicates upon which constraint production should be based on (length or diameter). Specifies the basis of the finished diameter of a reel, either a Diameter specification or a Length of paper specification



*This item is restricted to the following list.*

### Length

### Diameter

## ManufacturingProcess

Defines the different machining and processes made for the product.

### ManufacturingProcessType [attribute]



*ManufacturingProcessType is optional. A single instance might exist.*

Describes the exact nature of any further mechanical processing applied to the product.

Refer to ManufacturingProcessType definition for any enumerations.

### ManufacturingProcessAgency [attribute]

*ManufacturingProcessAgency is optional. A single instance might exist.*

Manufacturing process agency

Refer to ManufacturingProcessAgency definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value


*Value is optional. A single instance might exist.*

A numeric value expressed in the unit of measure (UOM).

#### AdditionalText

*AdditionalText is optional. A single instance might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## ManufacturingProcessAgency [attribute]

Manufacturing process agency

*This item is restricted to the following list.*



### ISO

International Organization for Standardization

### prEN TC(1113-1)

### Supplier

Product supplier is the agency for the coding structure.

---

## ManufacturingProcessType [attribute]

Describes the exact nature of any further mechanical processing applied to the product.

attribute
<b>ManufacturingProcessType</b>
type   lumberManufacturingProcessType

*This item is restricted to the following list.*

### **Chamfered**

The edge is beveled.

### **Combed**

### **Compressed**

### **Cut**

### **DrySplitted**

### **EndMatched**

### **Finesawn**

### **FJ-Lam**

FJ-Lam components are knotless, finger-jointed and laminated blanks up to 6 meters

### **FJ-Blank**

### **FurtherProcess**

### **FingerJointed**

### **GlueLamBeam**

### **GreenSplitted**

### **H and M**

### **H or M**

### **HeatTreated**

### **Impregnated**

### **ImpregnatedA**

### **ImpregnatedWolmanitAB**

### **KD56/30**

Phyto sanitary treatment. Kiln Dried up to a temperature in the core of the piece of at least 56 C for at least 30 minutes.

### **Lacquered**

### **Lamwood**

A piece of wood built up of plies or laminations that have been joined either with glue or with mechanical fastenings: the term is most frequently applied where the plies are too thick to be classified as veneer and when the grain of all plies is parallel.

### **MachineStrengthGraded**

### **NorthFloor**

### **Notched**

# papiNet V2R31

---

**OilTreated**

**Opti-Blank**

**Painted**

**Planed**

**Pro-Lam**

**Resawn**

**Rough**

Uneven texture, not smooth as passed through a saw.

**Rougher Headed**

**RoughSawn**

**S1E**

Surfaced one edge

**S1S**

Surfaced one side

**S1S EdgeRgh**

Surfaced one side, edge rough

**S1S1E**

Surfaced one side, one edge

**S1S2E**

Surfaced one side, two edges

**S2E**

Surfaced two edges

**S2S**

Surfaced two sides

**S2S EdgeRgh**

Surfaced two sides, edge rough

**S2S1E**

Surfaced two sides, one edge

**S4S**

Surfaced four sides

**S4SEE**

Surfaced four sides, eased edges

**Sawn**

**SawTexture**

**Smooth**

**Split**

**StrengthGraded**

Treated  
Vstol  
Other

## ManufacturingSpecifications

Manufacturing specifications.

### PressType [attribute]

*PressType is optional. A single instance might exist.*

The type of press used.

Refer to PressType definition for any enumerations.

**ManufacturingSpecifications**

### PressImpositionType [attribute]

*PressImpositionType is optional. A single instance might exist.*

The type of press imposition

Refer to PressImpositionType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Margins

*Margins is optional. A single instance might exist.*

Margins.

#### InkCharacteristics

*InkCharacteristics is optional. A single instance might exist.*

The ink characteristics.

Note: The child element, InkCoverage, will be deprecated from InkCharacteristics in an upcoming version. Use the instance of InkCoverage found in ColourSpecs.

#### FinishSpecs

*FinishSpecs is optional. A single instance might exist.*

Finish specifications

#### FinishPrep


*FinishPrep is optional. A single instance might exist.*

Finish prep

#### PrintedMediaSpecs

*PrintedMediaSpecs is optional. A single instance might exist.*

Printed media specifications



## Perforation

*Perforation is optional. Multiple instances might exist.*

Perforation information

## PrintingMaterials

*PrintingMaterials is optional. Multiple instances might exist.*

Printing materials information.

---

## MapCoordinates

A group item defining and containing position co-ordinates of a location.

### MapReferenceSystem [attribute]

*MapReferenceSystem is mandatory. A single instance is required.*

MapReferenceSystem defines the map projection and the origin of the co-ordinate system used for production of the map. Also referred to as Map Datum.

Refer to MapReferenceSystem definition for any enumerations.

### MapCoordinateType [attribute]

*MapCoordinateType is mandatory. A single instance is required.*

MapCoordinateType defines the co-ordinate system.

Refer to MapCoordinateType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Coordinates


*Coordinates is mandatory. A single instance is required.*

Contains the position co-ordinates of a location.

#### Altitude

*Altitude is optional. A single instance might exist.*

The height of a location above a ground reference point as specified by the map reference system.



---

## MapCoordinateType [attribute]

MapCoordinateType defines the co-ordinate system.

*This item is restricted to the following list.*

### ETRS-TM35FIN

ETRS-TM35FIN is a co-ordinate system used in Finland.



## **KKJ1**

KKJ zone 1 is a map coordinate system used in western part of Finland with rectangular grid-coordinates (northing, easting).

## **KKJ2**

KKJ zone 2 is a map coordinate system used in western part of Finland with rectangular grid-coordinates (northing, easting).

## **KKJ3**

KKJ zone 3 is a map coordinate system used in middle part of Finland with rectangular grid-coordinates (northing, easting).

## **KKJ4**

KKJ zone 4 is a map coordinate system used in eastern part of Finland with rectangular grid-coordinates (northing, easting).

## **Lambert93**

Lambert 93 is the official map projection of Metropolitan France since December 26, 2000 (<http://www.ign.fr/telechargement/P.I/Objectifs/Statuts/texte-26.12.2000.pdf>)

More info at:

[http://www.ign.fr/telechargement/MPro/geodesie/CIRCE/NTG\\_87.pdf](http://www.ign.fr/telechargement/MPro/geodesie/CIRCE/NTG_87.pdf)

## **Lambert1**

Lambert Zone 1 is a co-ordinate system used for the northern part of France.

More info at:

<http://www.ign.fr/telechargement/education/fiches/geodesie/projections.pdf>

[http://www.ign.fr/telechargement/education/fiches/geodesie/projections\\_EN.pdf](http://www.ign.fr/telechargement/education/fiches/geodesie/projections_EN.pdf)

## **Lambert2**

Lambert Zone 2 is a co-ordinate system used for the centre part of France.

More info at:

<http://www.ign.fr/telechargement/education/fiches/geodesie/projections.pdf>

[http://www.ign.fr/telechargement/education/fiches/geodesie/projections\\_EN.pdf](http://www.ign.fr/telechargement/education/fiches/geodesie/projections_EN.pdf)

## **Lambert3**

Lambert Zone 3 is a co-ordinate system used for the southern part of France.

More info at:

<http://www.ign.fr/telechargement/education/fiches/geodesie/projections.pdf>

[http://www.ign.fr/telechargement/education/fiches/geodesie/projections\\_EN.pdf](http://www.ign.fr/telechargement/education/fiches/geodesie/projections_EN.pdf)

## **Lambert4**

Lambert Zone 4 is a co-ordinate system used for Corsica.

More info at:

<http://www.ign.fr/telechargement/education/fiches/geodesie/projections.pdf>

[http://www.ign.fr/telechargement/education/fiches/geodesie/projections\\_EN.pdf](http://www.ign.fr/telechargement/education/fiches/geodesie/projections_EN.pdf)

## **Lambert2Etendu**

# papiNet V2R31

Lambert 2 Etendu is a co-ordinate system used for all of France. It is an extension of Lambert Zone 2 for metropolitan France.

More info at:

<http://www.ign.fr/telechargement/education/fiches/geodesie/projections.pdf>

[http://www.ign.fr/telechargement/education/fiches/geodesie/projections\\_EN.pdf](http://www.ign.fr/telechargement/education/fiches/geodesie/projections_EN.pdf)

## LatLong

Co-ordinates specified as Latitude and Longitude.

## RT90\_2.5GonV

RT90 2.5 gon V 0: -15 is a co-ordinate system used in Sweden.

More info at <http://www.lantmateriet.se>

## SWEREF99TM

SWEREF99 TM is a co-ordinate system used in Sweden.

More info at <http://www.lantmateriet.se>

## UTM

The Universal Transverse Mercator (UTM) coordinate system is a grid-based method of specifying locations on the surface of the Earth. The system employs a series of sixty zones, each of which is based on a specifically defined secant Transverse Mercator projection.

---

## MapPoint

A grouping element for items describing a point on a map. A map point is normally named waypoint in a GPS.

### MapPointType [attribute]

*MapPointType is optional. A single instance might exist.*

Type of object specified by a map point.

Refer to MapPointType definition for any enumerations.

### MapPointDisplayType [attribute]

*MapPointDisplayType is optional. A single instance might exist.*

Defines how map points are processed and displayed on maps by map applications.


Refer to MapPointDisplayType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### MapPointName

*MapPointName is mandatory. A single instance is required.*



A unique name for a point on a map. It is also normally the name of the corresponding waypoint in a GPS.

## MapPointComment

*MapPointComment is optional. Multiple instances might exist.*

A descriptive text for a point on a map. It is also normally shown in a GPS as a comment for the corresponding waypoint.

## MapCoordinates

*MapCoordinates is mandatory. One instance is required, multiple instances might exist.*

A group item defining and containing position co-ordinates of a location.

---

## MapPointComment

A descriptive text for a point on a map. It is also normally shown in a GPS as a comment for the corresponding waypoint.

<b>MapPointComment</b>	
type	s255

---

## MapPointDisplayType [attribute]

Defines how map points are processed and displayed on maps by map applications.

*This item is restricted to the following list.*

### LinePoint

A map point that is connected with a line to the next consecutive map point having the same MapPointDisplayType "LinePoint".

### UserWaypoint

A map point that is displayed as a normal waypoint visible for the user.

<b>MapPointDisplayType</b>	
type	mapPointDisplayType

---

## MapPointName

A unique name for a point on a map. It is also normally the name of the corresponding waypoint in a GPS.

<b>MapPointName</b>	
type	s60

---

## MapPointType [attribute]

Type of object specified by a map point.

*This item is restricted to the following list.*

### ApproachingWay

A map point showing the way how to approach the destination, e.g. a supply point. The advised way starts from the first given map point continuing to the next ones. Extra information about the way can be given in MapPointComment.

attribute	
<b>MapPointType</b>	
type	mapPointType

**Barrier**

An object serving to obstruct passage or to maintain separation, e.g. a gate.

**BearingCapacityRestriction**

A map point showing where bearing capacity restriction exists on the road.

**Bridge**

A bridge, e.g. for crossing over a river. A bridge might be restricted by width and bearing capacity.

**CraneTemporaryStorage**

A place where a crane used for loading and unloading can temporarily be put.

**DrivingProhibited**

A map point specifying that driving is prohibited on this leg of the road.

**Ferry**

A ferry crossing with restrictions along a road. Typically restricted by width and bearing capacity.

**ForestRoad**

Usually a light constructed road used mainly for forestry operations and wood transportations.

**HazardPlace**

A map point which needs to be noticed in order to drive or work safely, e.g. a point on a road or at a roadside landing.

**MainIntersection**

Connection point between a main road and minor roads.

**Passage**

A section or crossing with restrictions along a road. Typically restricted by width.

**PassingPossibility**

Place where vehicles can turn around.

**PointOfNatureValues**

A map point of special nature values which have to be taken into account in the operations.

**PointOfRemark**

A map point with special information which has to be taken into account in the operations.

**PowerLine**

A power line which can cause a danger to drivers and has to be taken into account in the operations.

**RoadWorks**

Repairs to a road forming a hazard or obstruction to traffic.

**RouteLegEnd**

End point of a route leg.

## **RouteLegStart**

Start point of a route leg.

## **RouteEnd**

End point of a route.

## **RouteStart**

Start point of a route.

## **Slope**

A section of a road with a gradient forming obstruction to traffic.

## **SupplyPoint**

A map point showing a supply point, e.g. a roadside landing.

## **TelephoneCable**

A telephone or a data communication cable which has to be taken into account in the operations.

## **TemporaryRoad**

Usually a light constructed and temporary road used for wood transportations and loggings, e.g. a winter road.

## **TrafficRestriction**

A map point with special restriction to the traffic. Detailed information of the restriction can be given in MapPointComment.

## **TrafficWarning**

A map point with special warning or notice concerning the traffic on the road. Detailed information of the warning can be given in MapPointComment.

## **TurningPossibility**

A place where vehicles can turn around.

## **UnderPass**

A section of a road that passes under another road, railway line, etc. Typically restricted by height and width.


## **WeighBridge**

Place for weighing of vehicles.

---

## **MapReferenceSystem [attribute]**

MapReferenceSystem defines the map projection and the origin of the co-ordinate system used for production of the map. Also referred to as Map Datum.



*This item is restricted to the following list.*

### **ETRS89**

The European Terrestrial Reference System 1989 is a three-dimensional

geodetic frame of reference - a mapping coordinate system used as the standard high accuracy system for GPS in Europe. ETRS89 is the EU-recommended frame of reference for geodata for Europe.

More info at <http://lareg.ensg.ign.fr/EUREF>

## **EUREF-FIN**

A map reference system used in Finland

## **KKJ**

A map reference system used in Finland. This older system will be replaced by ETRS89 (EUREF-FIN) on new maps.

## **NTF**

NTF is a Map reference System used in France. Although the official MapReference System in France is RGF93, NTF is still the most used reference system in year 2007.

Code EPSG used by Open Geospatial Consortium: 4807 More info at:

<http://www.ign.fr/telechargement/education/fiches/geodesie/syst%C3%A8mes.pdf>

[http://www.ign.fr/telechargement/education/fiches/geodesie/systemes\\_EN.pdf](http://www.ign.fr/telechargement/education/fiches/geodesie/systemes_EN.pdf)

[http://www.ign.fr/telechargement/education/fiches/geodesie/coordonnees\\_EN.pdf](http://www.ign.fr/telechargement/education/fiches/geodesie/coordonnees_EN.pdf)

## **RGF93**

RGF93 is the official geodetic frame of reference for France (<http://www.ign.fr/telechargement/P.I/Objectifs/Statuts/texte-26.12.2000.pdf>). It is a subset of ETRS89.

Code EPSG used by Open Geospatial Consortium for RGF93: 4965 (3D), 4171 (2D).

We can consider that the latitude and the longitude defined with the MapReferenceSystem RGF93 are equivalent to the latitude and the longitude defined with WGS84 (1 to 2 centimetres of gap).

## **RT90**

A map reference system used in Sweden.

More info at <http://www.lantmateriet.se>

## **SWEREF99**

A map reference system used in Sweden. The older reference system RT90 will be replaced by SWEREF99 on new maps.

More info at <http://www.lantmateriet.se>

## **WGS84**

The World Geodetic System defines a global reference system for the earth. WGS84 is the revision from year 1984. It is the reference system used by the Global Positioning System (GPS). WGS 84 is the most common reference system used for web based maps, e.g. Googlemaps and Google Earth.

## Margins

Margins.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### Head

Head is optional. A single instance might exist.

Head.

#### Thumb

Thumb is optional. A single instance might exist.

Thumb.

#### Gutter


Gutter is optional. A single instance might exist.

Gutter

#### Foot

Foot is optional. A single instance might exist.

Foot



## MasterReelWidth

The master reel width.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### Value

Value is mandatory. A single instance is required.

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


RangeMin is optional. A single instance might exist.

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

RangeMax is optional. A single instance might exist.

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## MasterSource [attribute]

The source of the master

*This item is restricted to the following list.*

**1610/1630**

**1/4Inch2TrackR2RTape**

**CDR**

The source is Compact Disc Recordable.

**DAT**

The source is Digital Audio Tape.

**DATWithLog**

**Diskette**

**DVD**

The source is Digital Video Disk.

**Electronic**

**Exabyte**

A company (and, by extension, a tape format) for computer data backup and transfer onto data quality 8-mm VCR tape. Exabyte units can store 5 Gbytes of data per tape.

**Jazz**

The Jazz drive is a removable storage solution developed by Iomega Corp. The Jaz drive has a 12-ms average seek time and the removable cartridges hold up to 2 GB of data.

**MagneticOptical**

**Syquest**

A removable hard disk drive that is connected to the computer via a SCSI interface.

**Zip**

A high-capacity floppy disk drive.

**Other**

attribute
<b>MasterSource</b>
type masterSource

---

## MasterStorageOption

Master storage option

<b>MasterStorageOption</b>
type s72

## MaterialCharacteristics

Material characteristics.

### FinishType [attribute]

*FinishType is optional. A single instance might exist.*

Defines the finish of a sheet of paper, which means the condition of its surface (refer to Embossing for more information).

Finishes may be produced on or off machine. Finishes that are created off-machine are called embossed. (Embossing is a child element of ReelConversionCharacteristics and

SheetConversionCharacteristics.)

Note:

Embossed" as a finish type is just a generalized choice for one of the more specific choices listed.

Unsupercalendered" as a finish type would be indicated by not communicating a finish type.

Refer to FinishType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### (sequence)

*The sequence of items below is mandatory. One instance is required, multiple instances might exist.*

### ProductIdentifier


*ProductIdentifier is mandatory. A single instance is required.*

Used to communicate the code of the article, in a variety of formats designated by the type.

### ProductDescription

*ProductDescription is optional. Multiple instances might exist.*

An element used to communicate a human readable description of the product in the language specified by the Language attribute.



## **BasisWeight**

*BasisWeight is optional. A single instance might exist.*

The weight of the paper expressed as a mass for a given surface area. In countries using the metric system, the basis weight is expressed as the weight in grams of one sheet of paper that is one square meter in area—not dependent on basic sheet size. In countries using the imperial system, the weight is expressed in pounds for a given ProductBasisSizeType.

## **Brightness**

*Brightness is optional. A single instance might exist.*

A measurement of the degree of light reflectivity of the product.

## **Caliper**

*Caliper is optional. A single instance might exist.*

The thickness of a sheet of paper under standard test conditions.

## **ColourSpecs**

*ColourSpecs is optional. A single instance might exist.*

Colour specs

## **Opacity**

*Opacity is optional. A single instance might exist.*

A group item used to communicate opacity target or test value according to a particular TestMethod.

## **PPI**

*PPI is optional. A single instance might exist.*

A group item used to communicate the number of pages in an inch of thickness either as a target or actual value. Equal to the number of sheets per inch times 2.

## **Width**

*Width is optional. A single instance might exist.*

The width of the object.

## **Length**

*Length is optional. A single instance might exist.*

The length of the object.

## **GrainDirection**

*GrainDirection is optional. A single instance might exist.*

Defines the primary orientation/alignment (Long or Short) of the cellulose fibres in a sheet or web of paper, which results from the flow of fibres in a water suspension during the papermaking process.

Refer to GrainDirection definition for any enumerations.

## **RecycledCharacteristics**

*RecycledCharacteristics is optional. A single instance might exist.*


RecycledCharacteristics groups together the concepts associated with recycled material.

## MaxCurrencyValue

The upper range of the allowed currency amount..

### CurrencyType [attribute]

*CurrencyType is optional. A single instance might exist.*



A three-character ISO 4217 currency code in capital letters. The ISO standard classification for currencies.


Refer to CurrencyType definition for any enumerations.

## MaximumClampingForce

Specifies maximum clamp force allowed during handling of an item.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*


The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## MaximumGrossWeight

The maximum weight allowed including the pallet.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

## **RangeMax**

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## **MaximumHeight**

The maximum height allowed including the pallet.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

#### **Value**

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### **RangeMin**


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### **RangeMax**

*RangeMax is optional. A single instance might exist.*


The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



---

## **MaximumNumberOfJoins**

The maximum number of joins requested (permitted). Permits customers to indicate join-free reels.



---

## MaximumOffcut

Maximum off cut.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### Value

Value is mandatory. A single instance is required.

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


RangeMin is optional. A single instance might exist.

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

RangeMax is optional. A single instance might exist.

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



---

## MaximumOrderQuantity

The maximum amount that can be ordered at one time.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### Quantity

Quantity is mandatory. A single instance is required.


The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

#### InformationalQuantity

InformationalQuantity is optional. Multiple instances might exist.

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.



## MeasurementModule

A text element describing the module used for measuring.

<b>MeasurementModule</b>	
type	s255

---

## MeasurementsAre [attribute]

Used to define for a product whether the details provided are ranges and lists of properties, or whether they are discrete, single properties of the product.

<i>attribute</i>	
<b>MeasurementsAre</b>	
type	measurementType

*This item is restricted to the following list.*

### Discreet

For a product, elements with measurements are observed or target values, and elements that allow a list of attributes for the product to be specified must have zero or one occurrence.

### Range

For a product, elements with measurements specify a range, and elements that allow a list of attributes for the product to be specified may have zero or more occurrences.

---

## MeasurementSystem

A text element describing the system used for measuring.

<b>MeasurementSystem</b>	
type	s255

---

## MeasuringAgency [attribute]

The agency defining measuring methods.

*This item is restricted to the following list.*

<i>attribute</i>	
<b>MeasuringAgency</b>	
type	agencyCode.Measuring

### Buyer

The buyer has defined the codes used in the particular element of the transaction. Care must be used when using this agency to assure that the recipient of the e-Document understands what is being communicated.

### RVR

Agency maintaining codes for the German wood supply segment.

RVR is the abbreviation for "RahmenVereinbarung für den Rohholzhandel in Deutschland".

([www.rvr-deutschland.de](http://www.rvr-deutschland.de)).

### SD

Agency maintaining codes for the Norwegian wood supply segment ([www.skogdata.no](http://www.skogdata.no)).

## SDC

Agency maintaining codes for the Swedish wood supply segment (www.sdc.se).

## Supplier

The supplier has defined the codes used in the particular element of the transaction. Care must be used when using this agency to assure that the recipient of the e-Document understands what is being communicated.


---

## MeasuringCode

A code defining the measuring procedure.

### Agency [attribute]

*Agency is mandatory. A single instance is required.*



Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

- For the element that owns this attribute.
- For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.


---

## MeasuringDate

The date when the measuring was done.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is mandatory. A single instance is required.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

- hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.
  - hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.
  - hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however,
-

within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## MeasuringDescription

A text element describing the measuring procedure.




## MeasuringEquipment

A grouping element that contains information about the equipment used for measuring.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### MeasuringEquipmentCode

*MeasuringCode is optional. Multiple instances might exist.*

A code used for identifying the measuring equipment.

### MeasurementSystem

*MeasurementSystem is optional. A single instance might exist.*

A text element describing the system used for measuring.

### MeasurementModule

*MeasurementModule is optional. A single instance might exist.*

A text element describing the module used for measuring.

### Calibration

*Calibration is optional. A single instance might exist.*


A grouping element that contains information about calibration of the measuring equipment.

## MeasuringEquipmentCode

A code used for identifying the measuring equipment.

### Agency [attribute]

*Agency is mandatory. A single instance is required.*



Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

- For the element that owns this attribute.
- For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

---

## MeasuringLineID

The unique identifier for the measuring line at a measuring location.

<b>MeasuringLineID</b>	
type	s60


---

## MeasuringLocation

A grouping element that contains information about where the measuring is taken place.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### LocationParty

*LocationParty is mandatory. A single instance is required*

The organization or business entity where the business event took place or will take place.

### MeasuringEquipment

*MeasuringEquipment is optional. Multiple instances might exist.*

A grouping element that contains information about the equipment used for measuring.

### MeasuringLineID

*MeasuringLineID is optional. A single instance might exist.*

The unique identifier for the measuring line at a measuring location.

---

## MeasuringMethod [attribute]

The method used to determine how the item under consideration is measured. Measuring methods are defined by the measuring agency.

attribute	
<b>MeasuringMethod</b>	
type	s60

---

## MeasuringMethodType [attribute]

Specifies how a measurement value is created.

*This item is restricted to the following list.*

### Automatic

The value is created by automatic measurement.

<b>MeasuringMethodType</b>	
type	measuringMethodType
default	Automatic

## Calculated

The value is calculated.

## Classified

The value is created by applying rules for classification based on a number of properties.

## Manual

The value is created by manual measurement.

## VisualEstimated

The value is created by visual estimation.

## MeasuringNumber

A unique identifier for the measuring event.



## MeasuringParty

The party that is responsible for the measurements at the measuring location.

### LogisticsRole [attribute]

*LogisticsRole is optional. A single instance might exist.*

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PartyIdentifier

*PartyIdentifier is optional. Multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

#### NameAddress


*NameAddress is mandatory. A single instance is required.*

A group item containing name and address of an organisation or business entity.

#### URL

*URL is optional. A single instance might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.



## CommonContact

*CommonContact is optional. Multiple instances might exist.*

Identifies a specific individual associated with the party.

---

## MeasuringSpecification

A grouping element that contains a specification for measurement procedures.

### MeasuringType [attribute]

*MeasuringType is mandatory. A single instance is required.*

Specifies how detailed the measurements are done.

Refer to MeasuringType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### MeasuringCode


*MeasuringCode is optional. A single instance might exist.*

A code defining the measuring procedure.

### MeasuringDescription

*MeasuringDescription is optional. Multiple instances might exist.*


A text element describing the measuring procedure.



## MeasuringTicket

The MeasuringTicket element is the root element for the MeasuringTicket e-Document.

The MeasuringTicket e-Document specifies the details from measuring of items. Packages and loads can be measured as well as individual items in packages and loads. Products, Quantities and various measured properties can be reported. These measurements can be used as a base for calculation of billable products.



### MeasuringTicketType [attribute]

*MeasuringTicketType is mandatory. A single instance is required.*

MeasuringTicketType defines the type of MeasuringTicket.

Refer to MeasuringTicketType definition for any enumerations.

### MeasuringTicketStatusType [attribute]

*MeasuringTicketStatusType is mandatory. A single instance is required.*

Identifies the status of the entire MeasuringTicket e-Document.

Refer to MeasuringTicketStatusType definition for any enumerations.

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### MeasuringTicketHeader

*MeasuringTicketHeader is mandatory. A single instance is required.*

The MeasuringTicketHeader contains information common to the entire MeasuringTicket e-Document.

#### MeasuringTicketSequence

*MeasuringTicketSequence* is mandatory. Multiple instances might exist.

A grouping element that contains information for a measuring event, e.g. a truck load.

## MeasuringTicketSummary

*MeasuringTicketSummary* is optional. A single instance might exist.

A grouping element that contains summary information that applies to the entire MeasuringTicket e-Document.

## MeasuringTicketHeader

The MeasuringTicketHeader contains information common to the entire MeasuringTicket e-Document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### MeasuringTicketNumber

*MeasuringTicketNumber* is mandatory. A single instance is required.

The unique identifier for the MeasuringTicket e-Document.

### MeasuringTicketIssueDate

*MeasuringTicketIssueDate* is mandatory. A single instance is required.

The date and time when the MeasuringTicket e-Document was issued.

### TransactionHistoryNumber

*TransactionHistoryNumber* is optional. A single instance might exist.

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.


### SenderParty

*SenderParty* is mandatory. A single instance is required.

The business entity issuing the e-Document, the source of the document.

- The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

### ReceiverParty



# papiNet V2R31

*ReceiverParty is mandatory. One instance is required, multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

- The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## MeasuringParty

*MeasuringParty is optional. A single instance might exist.*

The party that is responsible for the measurements at the measuring location.

## OtherParty

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## OtherDate

*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## MeasuringTicketReference

*MeasuringTicketReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the MeasuringTicket as indicated by MeasuringTicketReferenceType and AssignedBy.

## eAttachment

*eAttachment is optional. A single instance might exist.*

eAttachment enables the sender to provide information about attachments to the document.

- Note: An element "e-Attachment" also exists. papiNet will no longer use hyphens in our element and attribute names as this causes issues with BizTalk.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## MeasuringTicketIssueDate


The date and time when the MeasuringTicket e-Document was issued.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Date

*Date is mandatory. A single instance is required.*



# papiNet V2R31

A group element that contains the specification of Year, Month, and Day.

## Time


*Time is mandatory. A single instance is required.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

- hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.
- hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.
- hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.



## MeasuringTicketNumber

The unique identifier for the MeasuringTicket e-Document.



## MeasuringTicketReference

An element detailing relevant references pertaining to the MeasuringTicket as indicated by



MeasuringTicketReferenceType and AssignedBy.

### MeasuringTicketReferenceType [attribute]

*MeasuringTicketReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to MeasuringTicketReferenceType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is mandatory. A single instance is required.*

Identifies the type of party that has assigned the associated item, e.g. a

reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## MeasuringTicketReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", Warehouse" or Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute AssignedBy will communicate the information previously communicated in the prefix.

MeasuringTicketReferenceType	
type	referenceType

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## MeasuringTicketSequence

A grouping element that contains information for a measuring event, e.g. a truck load.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### MeasuringTicketSequenceNumber

*MeasuringTicketSequenceNumber is mandatory. A single instance is required.*

A sequential number that uniquely identifies the Sequence of a MeasuringTicket.

### MeasuringNumber


*MeasuringNumber is optional. A single instance might exist.*

A unique identifier for the measuring event.

### MeasuringDate

*MeasuringDate is optional. A single instance might exist.*

The date when the measuring was done.



### MeasuringSpecification

*MeasuringSpecification is mandatory. A single instance is required.*

A grouping element that contains a specification for measurement procedures.

### MeasuringTicketReference

*MeasuringTicketReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the MeasuringTicket as indicated by MeasuringTicketReferenceType and AssignedBy.

### OtherDate


*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

### MeasuringLocation

*MeasuringLocation is mandatory. A single instance is required.*

A grouping element that contains information about where the measuring is taken place.



## **DeliveryInfo**

*DeliveryInfo is optional. A single instance might exist.*

Information about the delivery.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **PackageMeasuringInfo**

*PackageMeasuringInfo is optional. Multiple instances might exist.*

A grouping element that contains information about a measured package or a measured load when the load is treated as one package.

## **QuantityInformation**

*QuantityInformation is mandatory. A single instance is required.*

A group item containing information about quantity and informational quantity of similar items.

## **MeasuringTicketSequenceLineItem**

*MeasuringTicketSequenceLineItem is mandatory. Multiple instances might exist.*

A grouping element identifying a line item included within the MeasuringTicket Sequence.

## **NumberOfUnCompletedMeasuredItems**

*NumberOfUnCompletedMeasuredItems is optional. A single instance might exist.*

Specifies the number of items that are uncompleted measured, i.e. some measurement values are missing for these items.

## **QuantityByProperty**

*QuantityByProperty is optional. Multiple instances might exist.*

A grouping element that contains specification of quantities per property value.

## **ChargeInformation**

*ChargeInformation is optional. Multiple instances might exist.*

A group element that contains elements that describe a charge.

## **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates they type of adjustment being communicated.

## **NetAmount**

*NetAmount is optional. A single instance might exist.*

An element that contains the net amount excluding tax. Adjustments are included in NetAmount. NetAmount encapsulates CurrencyValue.

## **Amount**

*Amount is optional. A single instance might exist.*

An element that contains the amount including tax. The Amount encapsulates

CurrencyValue.

## **SafetyAndEnvironmentalInformation**

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

## **eAttachment**

*eAttachment is optional. A single instance might exist.*

eAttachment enables the sender to provide information about attachments to the document.

- Note: An element "e-Attachment" also exists. papiNet will no longer use hyphens in our element and attribute names as this causes issues with BizTalk.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*


A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## MeasuringTicketSequenceLineItem

A grouping element identifying a line item included within the MeasuringTicket Sequence.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### MeasuringTicketSequenceLineItemNumber

*MeasuringTicketSequenceLineItemNumber is mandatory. A single instance is required.*

A sequential number that uniquely identifies the line item of the MeasuringTicket Sequence.

### Product

*Product is optional. A single instance might exist.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper,

Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **QuantityInformation**

*QuantityInformation is mandatory. A single instance is required.*

A group item containing information about quantity and informational quantity of similar items.

## **MeasuringTicketReference**

*MeasuringTicketReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the MeasuringTicket as indicated by MeasuringTicketReferenceType and AssignedBy.

## **OtherDate**

*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## **NumberOfItemMeasuringInfo**

*NumberOfItemMeasuringInfo is optional. A single instance might exist.*

Number of reported items by ItemMeasuringInfo.

## **ItemMeasuringInfo**

*ItemMeasuringInfo is optional. Multiple instances might exist.*

A grouping element that contains information about measured items.

## **NumberOfUnCompletedMeasuredItems**

*NumberOfUnCompletedMeasuredItems is optional. A single instance might exist.*

Specifies the number of items that are uncompleted measured, i.e. some measurement values are missing for these items.

## **DownGradingInfo**

*DownGradingInfo is optional. Multiple instances might exist.*

A grouping element that contains information about downgrading of products.

## **PropertyAverageValue**

*PropertyAverageValue is optional. Multiple instances might exist.*

Specifies an average value for a property for a number of items. The property is defined by the attribute PropertyType. The attribute MeasuringMethod and AssignedBy can be used to clarified details for a how a property is measured or calculated, e.g. Diameter for a sawlog can be measured "Under Bark" or "Over Bark". The attribute MeasuringMethodType defines how the value is created, e.g. measured automatically, calculated etc.

## **ChipFractionInfo**

*ChipFractionInfo is optional. A single instance might exist.*

Grouping element that contains information about analysis of chip fractions.

## **QuantityByProperty**

*QuantityByProperty is optional. Multiple instances might exist.*

A grouping element that contains specification of quantities per property value.

## **PriceAndAmountInfo**

*PriceAndAmountInfo is optional. A single instance might exist.*

A grouping element that contains information about price and amounts.

## **SafetyAndEnvironmentalInformation**

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

---

## **MeasuringTicketSequenceLineItemNumber**

A sequential number that uniquely identifies the line item of the MeasuringTicket Sequence.

MeasuringTicketSequenceLineItemNumber	
type	lineNumberType

---

## **MeasuringTicketSequenceNumber**

A sequential number that uniquely identifies the Sequence of a MeasuringTicket.

MeasuringTicketSequencellumber	
type	lineNumberType

---

## **MeasuringTicketStatusType [attribute]**

Identifies the status of the entire MeasuringTicket e-Document.

MeasuringTicketStatusType	
type	measuringTicketStatusType

*This item is restricted to the following list.*

### **Cancelled**

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### **Original**

The supplied information is the first version of that information.

### **Replaced**


The supplied information is replacing earlier supplied information. The receiver should revalidate the information in their system based upon the entire information received.

## MeasuringTicketSummary

A grouping element that contains summary information that applies to the entire MeasuringTicket e-Document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### TotalNumberOfSequences

*TotalNumberOfSequences is optional. A single instance might exist.*

The total number of sequences in the document.

### TotalQuantityInformation

*TotalQuantityInformation is mandatory. A single instance is required.*

A group item containing information about the total quantity and total informational quantity of similar items in the document.

### TotalNetAmount

*TotalNetAmount is optional. A single instance might exist.*

A field containing total amount excluding tax. For example, in the Invoice TotalNetAmount is equal to the sum of LineItemSubTotal plus TotalAdjustments. TotalNetAmount encapsulates CurrencyValue.

### TotalAmount

*TotalAmount is optional . A single instance might exist.*

A field containing the total amount including tax.

- PurchaseOrder: The total amount, using a valid unit of measure of all the items in the e-Document. Multiple total amounts are allowed so different units of measure or grade sub-totals can be communicated.
- CreditDebitNote and Invoice: TotalAmount is equal to TotalNetAmount plus TotalTaxAmount. In certain countries this is the amount that is due for payment based upon the terms of payment.

### AdditionalText

*AdditionalTexts is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

### TermsAndDisclaimers

*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.

## MeasuringTicketType [attribute]

MeasuringTicketType defines the type of MeasuringTicket.

MeasuringTicket.

*This item is restricted to the following list.*

<b>MeasuringTicketType</b>	
type	measuringTicketType

### CalibrationCheckLog

A MeasuringTicketType that contains a check log with information about calibration of measuring equipment.

### InvoiceSpecification

A MeasuringTicketType that contains information about measured products including prices and amounts. This MeasuringTicketType is normally used as a detailed specification of billable or invoiced products.

### MeasuringTicket

A MeasuringTicketType that contains detailed information about measured products and items. This information can be used as a base for calculation of billable products.

### ProductionTicket

A MeasuringTicketType that contains information about produced products and items. A ProductionTicket can also contain measuring information for produced items.

### SampleMeasuringTicket

A MeasuringTicketType that contains detailed information about measured samples taken from e.g. a delivery.

## MeasuringType [attribute]

Specifies how detailed the measurements are done.

*This item is restricted to the following list.*

<b>MeasuringType</b>	
type	measuringType

### ByItem

Each item is measured separately, e.g. a logs on a truck load.

### ByLoad

The whole truck load is measured as one unit.

### ByPackage


Each package is measured separately, e.g. packages on a truck load or a roadside logpile.

## MechanicalMaterial

Mechanical material information

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### MechanicalMaterialCharacteristics

*MechanicalMaterialCharacteristics is mandatory. A single instance is required.*

Mecahnical material characteristics.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.


---

## MechanicalMaterialCharacteristics

Mecahnical material characteristics.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### MechanicalMaterialDescription

*MechanicalMaterialDescription is mandatory. A single instance is required.*

Mechanical material description

### (choice)

*[choice] is optional because of choice construct.*

#### WireMaterial

*WireMaterial is optional because of choice construct.*

Wire Material

#### PlasticMaterial

*PlasticMaterial is optional because of choice construct.*

Describes the plastic used in the process.

### ColourCode

*ColourCode is optional. A single instance might exist.*

A code indicating the colour.

### ColourDescription


*ColourDescription is optional. A single instance might exist.*

A free form description of the colour.

---

## MechanicalMaterialDescription

Mechanical material description



## Media

Media.

### MasterSource [attribute]

*MasterSource is optional. A single instance might exist.*

The source of the master

Refer to MasterSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### TotalRunningLength

*TotalRunningLength is optional. A single instance might exist.*

Summary value of amount measured in running meters, etc.

### TotalNumberOfUnits

*TotalNumberOfUnits is optional. A single instance might exist.*

The total number of units.

### MasterStorageOption

*MasterStorageOption is optional. A single instance might exist.*

Master storage option

### (choice)

*[choice] is optional because of choice construct.*

### AudioCassette

*AudioCassette is optional because of choice construct.*

Audio cassette

### VideoCassette

*VideoCassette is optional because of choice construct.*

Video cassette information.

### CD

*CD is optional because of choice construct.*

CD

### DVD


*DVD is optional because of choice construct.*

DVD

### Slide

*Slide is optional because of choice construct.*

Slide



## MediaLength

Media length

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### TotalTime

*TotalTime is optional. A single instance might exist.*

The total time.

#### SideOneTime


*SideOneTime is optional. A single instance might exist.*

The time for side one.

#### SideTwoTime

*SideTwoTime is optional. A single instance might exist.*

The time for side two.



---

## MediaType [attribute]

The type of media

*This item is restricted to the following list.*

### CD

Compact Disk

### DVD

Digital Video Disk

### Electronic

### Jaz


High capacity storage media

### Syquest

A removable hard disk drive that is connected to the computer via a SCSI interface.

### Zip

### Other



## MerchantParty

This named party represents the merchant involved in the business transaction. This party is only used in the communication of OrderStatus otherwise it is handled via OtherParty.

### LogisticsRole [attribute]

*LogisticsRole is optional. A single instance might exist.*

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PartyIdentifier

*PartyIdentifier is optional. Multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

#### NameAddress

*NameAddress is mandatory. A single instance is required.*

A group item containing name and address of an organisation or business entity.

#### URL


*URL is optional. A single instance might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

#### CommonContact

*CommonContact is optional. Multiple instances might exist.*

Identifies a specific individual associated with the party.



## Method [attribute]


An attribute of the shipment method of payment, which defines the responsibilities of buyers and sellers for delivery under a sales contract.

It especially determines the obligations of the seller and the buyer regarding the payment of the freight costs.

*This item is restricted to the following list.*

### CollectFreight

### CollectFreightAndAllowed



## CollectFreightCreditedBackToCustomer

Defines the difference between the invoice freight cost and the allowance by the mill. This can be a credit or a debit to the customer.

## CustomerPickupBackhaul

Specifies that the carrier who is doing the delivery can pick a return load.

## Pickup

Specifies that the customer will pick up the goods; in other words, the goods transport is organised by the buyer who will therefore pay for the freight.

## PrepaidButChargedToCustomer

Specifies that the freight costs will be prepaid by the seller but will be charged back to the buyer.

## PrepaidBySeller

Specifies that the seller will prepay the freight costs.

---

## MethodOfPayment

The manner in which payment is to be transmitted to the seller.

MethodOfPayment	
type	s72


---

## MillCharacteristics

A group item defining the mill party and machine identifier where a product is or was produced.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### MillParty

*MillParty is optional. A single instance might exist.*

The organisation or business entity that actually produces the product.


### MachineID

*MachineID is optional. A single instance might exist.*

An identifier assigned to the particular machine being referenced. For example, a machine could be a paper machine, an off-line coater, a sheeter, or a printing press. The particular machine being referenced will be determined by the business event being supported.

## MillJoinLocation

A group element detailing the location of each mill join in a reel. The element DeliveryMessageReelCharacteristics/NumberOfMillJoins gives the total number of joins in a reel.



DeliveryMessageReelCharacteristics/MillJoinLocation would be repeated the NumberOfMillJoin times.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### MillJoinNumber

*MillJoinNumber is mandatory. A single instance is required.*

A sequential number that identifies each mill join in a reel. The element DeliveryMessageReelCharacteristics/NumberOfMillJoins gives the total number of joins in a reel.

#### LengthFromCore

*LengthFromCore is optional. A single instance might exist.*

In relationship to a paper event (usually a mill join) where is the event in terms of the length of the paper.


#### DistanceFromCore

*DistanceFromCore is optional. A single instance might exist.*

The distance from the radius of the core. This element can be used to communicate where a mill join is located. Compare to LengthFromCore.

## MillJoinNumber

A sequential number that identifies each mill join in a reel. The element DeliveryMessageReelCharacteristics/NumberOfMillJoins gives the total number of joins in a reel.




## MillOrderInformation

A group item containing information unique to a mill order.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



#### MillParty

*MillParty is mandatory. A single instance is required.*

The organisation or business entity that actually produces the product.

## MillOrderNumber

*MillOrderNumber is mandatory. A single instance is required.*

The manufacturing order number the mill uses.

## MillOrderLineNumber


*MillOrderLineNumber is optional. A single instance might exist.*

A number that uniquely identifies the line items of the Mill Order.

---

## MillOrderLineNumber


A number that uniquely identifies the line items of the Mill Order.



---

## MillOrderNumber

The manufacturing order number the mill uses.



---

## MillParty

The organisation or business entity that actually produces the product.

### LogisticsRole [attribute]

*LogisticsRole is optional. A single instance might exist.*

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### PartyIdentifier

*PartyIdentifier is optional. Multiple instances might exist.*


A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

### NameAddress

*NameAddress is mandatory. A single instance is required.*

A group item containing name and address of an organisation or business entity.

### URL



*URL is optional. A single instance might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

## CommonContact

*CommonContact is optional. Multiple instances might exist.*

Identifies a specific individual associated with the party.


---

## MillProductionInformation

A grouping element that contains information about production at the mill.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### MillCharacteristics

*MillCharacteristics is optional. A single instance might exist.*

A group item defining the mill party and machine identifier where a product is or was produced.

### MillOrderNumber

*MillOrderNumber is optional. A single instance might exist.*

The manufacturing order number the mill uses.

### Quantity

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified.

This permits the range to be specified in a different unit of measure than the target.


---

## Millwork

A placeholder for the further definition of millwork items.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### [Any Type]

Any type of content is permitted at this point.


---

## MinCurrencyValue

The lower range of the allowed currency amount.

### CurrencyType [attribute]

*CurrencyType is optional. A single instance might exist.*



A three-character ISO 4217 currency code in capital letters. The ISO standard classification for currencies.

Refer to CurrencyType definition for any enumerations.


---

## MinimumOrderQuantity

The minimum amount that can be ordered on a PurchaseOrder.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Quantity

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

### InformationalQuantity

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

---

## Minutes

A qualifier for the DeliveryTransitTime.



---

## MixedProductPalletIndicator [attribute]

Specifies whether a product can be mixed with other products on the same pallet.

*This item is restricted to the following list.*

**Yes**

**No**

attribute	
<b>MixedProductPalletIndicator</b>	
type	yesNo
default	No

---

## MixProductIndicator [attribute]

Specifies whether a product can be mixed with other products on the same shipment.

*This item is restricted to the following list.*

**Yes**

**No**

attribute	
<b>MixProductIndicator</b>	
type	yesNo
default	No

---

## MobilePhone

The mobile phone number of the individual associated with the ContactName.

<b>MobilePhone</b>	
type	phoneNumber

---

## ModulusElasticity [attribute]

Modulus elasticity

*This item is restricted to the following list.*

**1.0E**

**1.1E**

**1.2E**

**1.3E**

**1.4E**

**1.5E**

**1.6E**

**1.7E**

**1.8E**

**1.9E**

**2.0E**

**2.1E**

**2.2E**

**2.3E**

**2.4E**

attribute	
<b>ModulusElasticity</b>	
type	lumberModulusElasticityType

## Moisture

Desired percentage, or other indicator, of water in the product at the time of shipment.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin


*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.



## StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper


*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## MoistureContent

Defines the moisture content percentage of the product.



### MoistureContentPercentage [attribute]

*MoistureContentPercentage is optional. A single instance might exist.*

Defines the percentage moisture content to which the product has been dried. Refer to MoistureContentPercentage definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### AdditionalText

*AdditionalText is optional. A single instance might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.


---

## MoistureContentPercentage [attribute]

Defines the percentage moisture content to which the product has been dried.

*This item is restricted to the following list.*

- 1
- 2



3

4

5

6

7

8

9

10

11

12

13

14

15

16

18

19

20

21

22

23

Other

## MonetaryAdjustment

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount.

MonetaryAdjustment contains an attribute that indicates they type of adjustment being communicated.

### AdjustmentType [attribute]

*AdjustmentType is mandatory. A single instance is required.*

Describes the type of adjustment applied to a monetary oriented element. Adjustment values should always be given as negative or positive adjustments even if AdjustmentType indicates the sign. For example, a rebate of 1% on an invoice should be given as an adjustment percentage of -1%.

Refer to AdjustmentType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### MonetaryAdjustmentLine

*MonetaryAdjustmentLine is mandatory. A single instance is required.*

A sequence number indicating the order of printing or the sequence in which a group of adjustments are to be considered.

#### MonetaryAdjustmentStartAmount

*MonetaryAdjustmentStartAmount is optional. A single instance might exist.*


The beginning currency amount used in the calculation of a monetary adjustment.

#### MonetaryAdjustmentStartQuantity

*MonetaryAdjustmentStartQuantity is optional. A single instance might exist.*

The beginning quantity used in the calculation of a monetary adjustment.

### (choice)



*[choice] is optional because of choice construct.*

## **PriceAdjustment**

*PriceAdjustment is optional because of choice construct.*

A group item defining a deviation from the PricePerUnit.

## **FlatAmountAdjustment**

*FlatAmountAdjustment is optional because of choice construct.*

A group item that contains flat adjustment amount information.

## **TaxAdjustment**

*TaxAdjustment is optional because of choice construct.*

This content element contains the necessary information to describe, calculate, and handle a tax adjustment.

## **InformationalAmount**

*InformationalAmount is optional. A single instance might exist.*

A monetary amount used for information purposes only (not for calculation). For example, the invoice price adjustment subtotal is expressed in sterling pounds, and the buyer wants this information expressed in U.S. dollars.

CreditDebitNote and Invoice - The TaxAmount is displayed in the currency that is applicable throughout the e-Document. When a TaxAmount needs to be displayed in a different national currency, this field is used.

## **MonetaryAdjustmentReferenceLine**

*MonetaryAdjustmentReferenceLine is optional. A single instance might exist.*

A link to a previously defined MonetaryAdjustmentLine upon which this adjustment is based.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **GeneralLedgerAccount**

*GeneralLedgerAccount is optional. A single instance might exist.*

The general ledger account to be referenced for the item.

## **MonetaryAdjustmentAmount**

*MonetaryAdjustmentAmount is optional. A single instance might exist.*

The actual amount of the monetary adjustment.

## **AdjustmentTypeReason**

*AdjustmentTypeReason is optional. A single instance might exist.*


Provides additional information about the type of adjustment. Can be viewed as a sub-classification of the adjustment type attribute or as a textual explanation.

## MonetaryAdjustmentAmount

The actual amount of the monetary adjustment.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*




**CurrencyValue**

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.


## MonetaryAdjustmentLine

A sequence number indicating the order of printing or the sequence in which a group of adjustments are to be considered.



## MonetaryAdjustmentReferenceLine

A link to a previously defined MonetaryAdjustmentLine upon which this adjustment is based.




## MonetaryAdjustmentStartAmount

The beginning currency amount used in the calculation of a monetary adjustment.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



**CurrencyValue**

*CurrencyValue is mandatory. A single instance is required.*


The amount in the referenced currency as defined by the CurrencyType attribute.

## MonetaryAdjustmentStartQuantity

The beginning quantity used in the calculation of a monetary adjustment.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



**Value**

*Value is mandatory. A single instance is required.*

# papiNet V2R31

---

A numeric value expressed in the unit of measure (UOM).

## **RangeMin**

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

## **RangeMax**

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## **Month**

Identifies the month number when communicating a Calendar date.

<b>Month</b>	
type	monthType


## Mullen

Mullen, also called "burst strength", is the amount of pressure required to rupture paper or linerboard when applied to its surface. The unit of measure is KiloPascal (sometimes abbreviated as "kPa").

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.



### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin


*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.



# papiNet V2R31

---

## StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## MWeight

The weight of 1000 sheets.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*


The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



---

## Name1

The primary-level name of an organisation or business entity (for example, company name).



# papiNet V2R31

---

## Name2

The second-level name of an organisation or business entity (for example, department, division, and so on).

Name2	
type	s60

---

## Name3

The third-level name of an organisation or business entity.

Name3	
type	s60

## NameAddress


A group item containing name and address of an organisation or business entity.

### CommunicationRole [attribute]

*CommunicationRole is optional. A single instance might exist.*

Provides information about the sender, receiver, and participants to the document communication.

Refer to



CommunicationRole definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Name1

*Name1 is mandatory. A single instance is required.*

The primary-level name of an organisation or business entity (for example, company name).

#### Name2

*Name2 is optional. A single instance might exist.*

The second-level name of an organisation or business entity (for example, department, division, and so on).

#### Name3

*Name3 is optional. A single instance might exist.*

The third-level name of an organisation or business entity.

#### OrganisationUnit

*OrganisationUnit is optional. A single instance might exist.*


A segment of a business or the entire business.

#### Address1

*Address1 is optional. A single instance might exist.*

The primary-level address of an organisation or business entity (for example, street name, and number).

#### Address2



# papiNet V2R31

---

*Address2 is optional. A single instance might exist.*

The second-level address of an organisation or business entity.

## **Address3**

*Address3 is optional. A single instance might exist.*

The third-level address of an organisation or business entity.

## **Address4**

*Address4 is optional. A single instance might exist.*

The fourth-level address of an organisation or business entity.

## **City**

*City is optional. A single instance might exist.*

Name of the city associated with the address elements.

## **County**

*County is optional. A single instance might exist.*

The name of the county that the address is in.

## **StateOrProvince**

*StateOrProvince is optional. A single instance might exist.*

The political designation or boundary of a specific area of land.

## **PostalCode**

*PostalCode is optional. A single instance might exist.*

The postal code associated with the address elements.

## **Country**

*Country is optional. A single instance might exist.*

The name of the country associated with the address elements. To ensure reliable matching of addresses, it is suggested to use the attribute ISOCountryCode as well.

## **(choice)**

*[choice] is optional because of choice construct.*

## **GPSCoordinates**

*GPSCoordinates is optional because of choice construct.*

The location of the party as specified using a Global Positioning System.

## **MapCoordinates**

*MapCoordinates is optional because of choice construct.*

A group item defining and containing position co-ordinates of a location.

---

## **NASTA [attribute]**

Used to indicate the specification must conform to the NASTA requirements.

*This item is restricted to the following list.*

**Yes**

**No**


attribute	
<b>NASTA</b>	
type	yesNo
default	No

## NaturalWoodSiding

Natural wood siding

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### **NaturalWoodSidingCharacteristics**

*NaturalWoodSidingCharacteristics is mandatory. A single instance is required.*

Natural wood siding characteristics

### **Packaging**

*Packaging is optional. A single instance might exist.*

Type of a package that includes individual products.

## NaturalWoodSidingCharacteristics

Natural wood siding characteristics

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### LumberSpecies

*LumberSpecies is mandatory. One instance is required, multiple instances might exist.*

Specifies the raw material species.

### LumberGrade

*LumberGrade is mandatory. A single instance is required.*

Defines quality characteristics achieved by selecting pieces based on a grading rule.

### Length

*Length is optional.*

The length of the object.

### Width

*Width is optional.*

The width of the object.

### Thickness

*Thickness is optional.*

Physical dimension of a product.

### Seasoning

*Seasoning is optional. A single instance might exist.*

Describes drying/ moisture control method.

### MoistureContent

*MoistureContent is optional. A single instance might exist.*

Defines the moisture content percentage of the product.

### HeatTreatment

*HeatTreatment is optional. A single instance might exist.*

Defines the heat treatment method.

### ManufacturingProcess

*ManufacturingProcess is optional. Multiple instances might exist.*

Defines the different machining and processes made for the product.

### PatternProfile

*PatternProfile is optional. A single instance might exist.*

Defines the pattern used in machining the product.

### Trim

*Trim is optional. A single instance might exist.*



Trim

## **Joining**

*Joining is optional. A single instance might exist.*

Defines the method used to join pieces of wood.

## **PressureTreatment**

*PressureTreatment is optional. A single instance might exist.*

Method and parameter values of pressure treatment.

## **FireTreatment**

*FireTreatment is optional. A single instance might exist.*

Fire treatment

## **OtherTreatment**

*OtherTreatment is optional. A single instance might exist.*

Other treatment

## **GradeStamp**

*GradeStamp is optional. A single instance might exist.*

Grade stamp information

## **ExLog**

*ExLog is optional. A single instance might exist.*

Describes the cutting pattern of the log.

## **ClassIdentifier**

*ClassIdentifier is optional. Multiple instances might exist.*

Standard used for product identification.

## **Weight**

*Weight is optional. A single instance might exist.*

The weight of the item.

## **LabelCharacteristics**

*LabelCharacteristics is optional. A single instance might exist.*

A group item that organises the labeling information.

## **StencilCharacteristics**

*StencilCharacteristics is optional. A single instance might exist.*

A group element specifying attributes of a stencil to be applied to an item, and optional text.

## **Wrap**

*Wrap is optional. A single instance might exist.*

A group item that organises wrapping detail information.

## **SafetyAndEnvironmentalInformation**

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the

indicated agency).

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **LengthCutDescription**

*LengthCutDescription is optional. A single instance might exist.*

Length Cut Description

## **ShippingMark**

*ShippingMark is optional. A single instance might exist.*

A shipping mark identifies the producer and quality on the end side of the product. Not to be mixed with company code/logo or other product marking.


---

## **NaturalWoodSiding-Other**

Natural Wood Siding - Other

**(sequence)**

The



*sequence of items below is mandatory. A single instance is required.*

### **NaturalWoodSiding-OtherCharacteristics**

*NaturalWoodSiding-OtherCharacteristics is mandatory. A single instance is required.*

Natural Wood Siding - Other Characteristics

### **Packaging**

*Packaging is optional. A single instance might exist.*

Type of a package that includes individual products.

## NaturalWoodSiding-OtherCharacteristics

### Natural Wood Siding - Other Characteristics

**(sequence)**

The sequence of items below is mandatory. A single instance is required.

**LumberSpecies**

LumberSpecies is mandatory. One instance is required, multiple instances might exist.

Specifies the raw material species.

**LumberGrade**

LumberGrade is mandatory. A single instance is required.

Defines quality characteristics achieved by selecting pieces based on a grading rule.

**Length**

Length is optional.

The length of the object.

**Width**

Width is optional.

The width of the object.

**Thickness**

Thickness is optional.

Physical dimension of a product.

**Seasoning**

Seasoning is optional. A single instance might exist.

Describes drying/ moisture control method.

**MoistureContent**

MoistureContent is optional. A single instance might exist.

Defines the moisture content percentage of the product.

**HeatTreatment**

HeatTreatment is optional. A single instance might exist.

Defines the heat treatment method.

**ManufacturingProcess**

ManufacturingProcess is optional. Multiple instances might exist.

Defines the different machining and processes made for the product.

**PatternProfile**

PatternProfile is optional. A single instance might exist.

Defines the pattern used in machining the product.

**Trim**

Trim is optional. A single instance might exist.



Trim

## **Joining**

*Joining is optional. A single instance might exist.*

Defines the method used to join pieces of wood.

## **PressureTreatment**

*PressureTreatment is optional. A single instance might exist.*

Method and parameter values of pressure treatment.

## **FireTreatment**

*FireTreatment is optional. A single instance might exist.*

Fire treatment

## **OtherTreatment**

*OtherTreatment is optional. A single instance might exist.*

Other treatment

## **GradeStamp**

*GradeStamp is optional. A single instance might exist.*

Grade stamp information

## **ExLog**

*ExLog is optional. A single instance might exist.*

Describes the cutting pattern of the log.

## **ClassIdentifier**

*ClassIdentifier is optional. Multiple instances might exist.*

Standard used for product identification.

## **Weight**

*Weight is optional. A single instance might exist.*

The weight of the item.

## **LabelCharacteristics**

*LabelCharacteristics is optional. A single instance might exist.*

A group item that organises the labeling information.

## **StencilCharacteristics**

*StencilCharacteristics is optional. A single instance might exist.*

A group element specifying attributes of a stencil to be applied to an item, and optional text.

## **Wrap**

*Wrap is optional. A single instance might exist.*

A group item that organises wrapping detail information.

## **SafetyAndEnvironmentalInformation**

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the

indicated agency).

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **LengthCutDescription**

*LengthCutDescription is optional. A single instance might exist.*

Length Cut Description

## **ShippingMark**

*ShippingMark is optional. A single instance might exist.*


A shipping mark identifies the producer and quality on the end side of the product. Not to be mixed with company code/logo or other product marking.

---

## **NetAmount**

An element that contains the net amount excluding tax. Adjustments are included in NetAmount.

NetAmount encapsulates CurrencyValue.



### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **CurrencyValue**

*CurrencyValue is mandatory. A single instance is required.*


The amount in the referenced currency as defined by the CurrencyType attribute.

---

## **NetChargeAmount**

A field containing the sum of all instances of the Complaint charges.

### **(sequence)**



*The sequence of items below is mandatory. A single instance is required.*

### **CurrencyValue**

*CurrencyValue is mandatory. A single instance is required.*


The amount in the referenced currency as defined by the CurrencyType attribute.

---

## **NoiseReduction [attribute]**

The noise reduction method

*This item is restricted to the following list.*



## DolbyB

A simplified version of type A noise reduction targeted towards consumer recording equipment.

## DolbyC

An improvement of the B type consumer technology filters result in 20 dB of noise reduction but still confined 1KHz and over typically found built into mid and high end cassette recorders.

## DolbyS

A multiband consumer version of the Dolby system.

## None


---

## NonPressComponent

Non-press component.

### (choice)

*[choice] is optional because of choice construct.*



#### Media

*Media is optional because of choice construct.*

Media.

#### Gimmick

*Gimmick is optional because of choice construct.*

Gimmick

#### Sleeve

*Sleeve is optional because of choice construct.*

Sleeve.


---

## NonStandardPulp

The characteristics of the form that pulp in a nonstandard presentation takes.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



#### TargetMoisture

*TargetMoisture is mandatory. A single instance is required.*

The moisture target for the product being specified.

#### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific

elements.

---

## NumberOfAttachments

NumberOfAttachments indicates the number of attachments enclosed in the e-Document

NumberOfAttachments	
type	nni3

---

## NumberOfBands

The number of bands to be applied to the package.

NumberOfBands	
type	nni2

---

## NumberOfBindComponents

Total number of components contained in the book block.

NumberOfBindComponents	
type	nni4

---

## NumberOfColours

The number of colours

NumberOfColours	
type	nni4

---

## NumberOfComplaintLineItemDetail

The number of ComplaintLineItemDetail elements for a given ComplaintLineItem (Example: the number of reels in a ComplaintLineItem)

NumberOfComplaintLineItemDetail	
type	nni4

---

## NumberOfComplaintResponseLineItemDetail

The number of ComplaintResponseLineItemDetail elements for a given ComplaintResponseLineItem

NumberOfComplaintResponseLineItemDetail	
type	nni4


---

## NumberOfDocuments

Specifies the number of documents needed.

### Original [attribute]

*Original is optional. A single instance might exist.*



# papiNet V2R31

---

Either "Yes" or "No".

Refer to Original definition for any enumerations.

---

## NumberOfDocumentsRequired

The number of copies of the document required.

NumberOfDocumentsRequired	
type	nni2

---

## NumberOfGoodsReceiptPackages

A count of the number of packages detailed in the GoodsReceiptLineItem.

NumberOfGoodsReceiptPackages	
type	nni4

---

## NumberOfHits

The number of hits

NumberOfHits	
type	nni4

---

## NumberOfHoles

The number of holes punched in a sheet of paper.

NumberOfHoles	
type	nni3

---

## NumberOfInventoryChangeLineItemDetails

The number of InventoryChangeLineItemDetail elements included in the InventoryChangeLineItem.

NumberOfInventoryChangeLineItemDetails	
type	nni4

---

## NumberOfInventoryStatusLineItemDetails

The number of InventoryStatusLineItemDetail elements included in the InventoryStatusLineItem.

NumberOfInventoryStatusLineItemDetails	
type	nni4

---

## NumberOfItemMeasuringInfo

Number of reported items by ItemMeasuringInfo.

NumberOfItemMeasuringInfo	
type	nni6

# papiNet V2R31

---

## NumberOfLabels

The number of labels to be placed on the package.

NumberOfLabels	
type	nni2

---

## NumberOfMillJoins

The number of joins in the reel.

NumberOfMillJoins	
type	nni1

---

## NumberOfPackages

The number of packages in the delivery.

NumberOfPackages	
type	nni4

---

## NumberOfPackingListItems

The number of PackingList items in a PackingUnit of the PackingList.

NumberOfPackingListItems	
type	nni3

---

## NumberOfPages

The number of pages.

NumberOfPages	
type	nni6

---

## NumberOfPlies

The number of layers of paper product joined together to make the final saleable product.

NumberOfPlies	
type	nni1

---

## NumberOfRibbons

The number of ribbons.

NumberOfRibbons	
type	nni2

---

## NumberOfSides

The number of sides.

NumberOfSides	
type	nni2

## NumberOfSignatures

The number of signatures.

NumberOfSignatures	
type	nni4

## NumberOfUncompletedMeasuredItems

Specifies the number of items that are uncompleted measured, i.e. some measurement values are missing for these items.

NumberOfUncompletedMeasuredItems	
type	nni6

## NumberOfWraps

The number of turns of wrapping material to be applied to the package.

NumberOfWraps	
type	dec03-2

## NumberOrderDocumentRequired

There are certain business cases whereby a party is required to reference external documents to the transaction. Additionally, in these cases, the party is required to communicate the number of these external documents. This element is used to indicate how many of these external documents will be required. Typically used to indicate how many hard copies of the referenced document are needed.

NumberOrderDocumentRequired	
type	nni2

## NumberPerProduct

The number of components or items per assembly or constructed product

NumberPerProduct	
type	dec18-8

## NumericValue

A grouping element for a numeric value and its statistical measures.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### DetailValue

DetailValue is mandatory. A single instance is required.

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

DetailRangeMin is optional. A single instance might exist.

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

DetailRangeMax is optional. A single instance might exist.

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

StandardDeviation is optional. A single instance might exist.

A statistic used as a measure of dispersion in a distribution.

#### SampleSize

SampleSize is optional. A single instance might exist.

The number of samples used to determine the product characteristic in question.

#### TwoSigmaLower


TwoSigmaLower is optional. A single instance might exist.

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

#### TwoSigmaUpper

TwoSigmaUpper is optional. A single instance might exist.

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.



## Old InformationalQuantity

What the InformationalQuantity was prior to the event described taking place.

### QuantityType [attribute]

*QuantityType is mandatory. A single instance is required.*



QuantityType communicates information about the type of quantity being communicated and how the receiver might use the information.

Refer to QuantityType definition for any enumerations.

### QuantityTypeContext [attribute]

*QuantityTypeContext is optional. A single instance might exist.*

Provides the location in the value chain where the quantity is being reported.

Refer to QuantityTypeContext definition for any enumerations.

### AdjustmentType [attribute]

*AdjustmentType is optional. A single instance might exist.*

Describes the type of adjustment associated with a quantity.

Refer to AdjustmentType definition for any enumerations.

### MeasuringMethodType [attribute]

*MeasuringMethodType is optional. A single instance might exist.*

Specifies how a measurement value is created.

Refer to MeasuringMethodType definition for any enumerations.

### MeasuringAgency [attribute]

*MeasuringAgency is optional. A single instance might exist.*

The agency defining measuring methods.


Refer to MeasuringAgency definition for any enumerations.

### MeasuringMethod [attribute]

*MeasuringMethod is optional. A single instance might exist.*

The method used to determine how the item under consideration is measured. Measuring methods are defined by the measuring agency.

(sequence)



The sequence of items below is mandatory. A single instance is required.

## Value

Value is mandatory. A single instance is required.

A numeric value expressed in the unit of measure (UOM).

## RangeMin

RangeMin is optional. A single instance might exist.

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

## RangeMax

RangeMax is optional. A single instance might exist.

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## OldInventoryClass

A group item containing information about what the InventoryClass was prior to the event described taking place.

### InventoryStatusType

OldInventoryClass

#### [attribute]

InventoryStatusType is optional. A single instance might exist.

Provides the status type for inventory/goods belonging to a product and/or an order.

Refer to InventoryStatusType definition for any enumerations.

### InventoryOwnedBy [attribute]

InventoryOwnedBy is optional. A single instance might exist.

Specifies who is the owner of the inventory/goods.


Refer to InventoryOwnedBy definition for any enumerations.

#### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### (sequence)

The sequence of items below is optional. Multiple instances might exist.



## InventoryClassCode

*InventoryClassCode is mandatory. A single instance is required.*

A code specifying the inventory and goods status. Classification of statuses can be done on multiple levels indicated by InventoryClassLevel.

## InventoryClassDescription

*InventoryClassDescription is optional. Multiple instances might exist.*

A description of the inventory class.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## OldQuantity

What the Quantity was prior to the event described taking place

### QuantityType [attribute]

*QuantityType is mandatory. A single instance is required.*

QuantityType communicates information about the type of quantity being communicated and how the receiver might use the information.

Refer to QuantityType definition for any enumerations.

### QuantityTypeContext [attribute]

*QuantityTypeContext is optional. A single instance might exist.*

Provides the location in the value chain where the quantity is being reported.

Refer to QuantityTypeContext definition for any enumerations.

### AdjustmentType [attribute]


*AdjustmentType is optional. A single instance might exist.*

Describes the type of adjustment associated with a quantity.

Refer to AdjustmentType definition for any enumerations.

### MeasuringMethodType [attribute]

*MeasuringMethodType is optional. A single instance might exist.*



*instance might exist.*

Specifies how a measurement value is created.

Refer to MeasuringMethodType definition for any enumerations.

## **MeasuringAgency [attribute]**

*MeasuringAgency is optional. A single instance might exist.*

The agency defining measuring methods.

Refer to MeasuringAgency definition for any enumerations.

## **MeasuringMethod [attribute]**

*MeasuringMethod is optional. A single instance might exist.*

The method used to determine how the item under consideration is measured. Measuring methods are defined by the measuring agency.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **Value**

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### **RangeMin**

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### **RangeMax**

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## Opacity

A group item used to communicate opacity target or test value according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*


The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation



*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

### SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

### TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

### TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*


Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

## OrderConfirmation

The OrderConfirmation element is the root element for the OrderConfirmation e-Document.

A seller sends an OrderConfirmation e-Document to a buyer after receiving a PurchaseOrder from that buyer. The e-Document contains a response to the conditions specified in the PurchaseOrder. A supplier may also send an OrderConfirmation e-Document to convey changes that the supplier has made in the order or to convey new information such as a Supplier Reference Number or Job Number.

OrderConfirmation



### OrderConfirmationStatusType [attribute]

*OrderConfirmationStatusType is mandatory. A single instance is required.*

Identifies the status of the whole OrderConfirmation e-Document (i.e. at the root level)

Refer to OrderConfirmationStatusType definition for any enumerations.

### OrderType [attribute]

*OrderType is optional. A single instance might exist.*

Defines the type of OrderConfirmation being communicated.

Refer to OrderType definition for any enumerations.

## **Reissued [attribute]**

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

## **Language [attribute]**

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **OrderConfirmationHeader**

*OrderConfirmationHeader is mandatory. A single instance is required.*

Information that is common to all items on the OrderConfirmation.

### **OrderConfirmationLineItem**

*OrderConfirmationLineItem is mandatory. One instance is required, multiple instances might exist.*

The detail of the items that are communicated in the OrderConfirmation e-Document.

### **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates they type of adjustment being communicated.

### **OrderConfirmationSummary**

*OrderConfirmationSummary is optional. A single instance might exist.*

Summary information that applies to the whole OrderConfirmation e-Document.

## OrderConfirmationHeader

Information that is common to all items on the OrderConfirmation.

### OrderConfirmationHeaderStatusType [attribute]

*OrderConfirmationHeaderStatusType is mandatory. A single instance is required.*

An attribute defining the status of the OrderConfirmation header

Refer to

OrderConfirmationHeader

OrderConfirmationHeaderStatusType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### OrderConfirmationNumber

*OrderConfirmationNumber is optional. A single instance might exist.*

The unique order identifier as designated by the seller.

#### OrderConfirmationHeaderStatusTypeText

*OrderConfirmationHeaderStatusTypeText is optional. A single instance might exist.*

A text field that may provide detail explaining the status of the OrderConfirmationHeader.

This field is required if the OrderConfirmationHeaderStatusType is "Rejected".

When the OrderConfirmationHeaderStatusType is "Pending", the reason can be specified in this field.

Not required if the PurchaseOrder is "Accepted".

#### OrderConfirmationIssuedDate


*OrderConfirmationIssuedDate is mandatory. A single instance is required.*

The Date and optionally the Time that the OrderConfirmation was issued.

#### TransactionHistoryNumber

*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.



## **TransactionHistoryConfirmationNumber**

*TransactionHistoryConfirmationNumber is optional. A single instance might exist.*

A sequential number that indicates the version of the confirmation document being sent.

## **PurchaseOrderInformation**

*PurchaseOrderInformation is optional. A single instance might exist.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

## **OrderConfirmationReference**

*OrderConfirmationReference is optional. Multiple instances might exist.*

A group item detailing relevant references pertaining to the OrderConfirmation. Typically, the ContractNumber is referenced. OrderConfirmationReferenceType provides the identification of what the reference represents.

## **BuyerParty**

*BuyerParty is mandatory. A single instance is required.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## **BillToParty**

*BillToParty is optional. A single instance might exist.*

The address where the invoice is to be sent.

## **SupplierParty**

*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the

message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **ShipToCharacteristics**

*ShipToCharacteristics is mandatory. A single instance is required.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **TransportModeCharacteristics**

*TransportModeCharacteristics is optional. A single instance might exist.*

A group item defining the primary mode of transport.

## **TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

## **TransportUnitCharacteristics**

*TransportUnitCharacteristics is optional. A single instance might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

## **TransportLoadingCharacteristics**

*TransportLoadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be loaded.

## **TransportUnloadingCharacteristics**

*TransportUnloadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be unloaded.

## **TransportOtherInstructions**

*TransportOtherInstructions is optional. Multiple instances might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

## **OtherDate**

*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## OrderConfirmationHeaderStatusType [attribute]

An attribute defining the status of the OrderConfirmation header

*This item is restricted to the following list.*



### Accepted

The supplied information is accepted.

### Amended

The supplied information is changed.

### Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### NoAction

The supplied information has not been amended and thereby requires no action.

### Pending

The supplied information is not complete and will be updated later.


### Rejected

The supplied information is rejected.

---

## OrderConfirmationHeaderStatusTypeText

A text field that may provide detail explaining the status of the OrderConfirmationHeader.



This field is required if the OrderConfirmationHeaderStatusType is "Rejected".

When the OrderConfirmationHeaderStatusType is "Pending", the reason can be specified in this field.

Not required if the PurchaseOrder is "Accepted".


---

## OrderConfirmationIssuedDate

The Date and optionally the Time that the OrderConfirmation was issued.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

# papiNet V2R31

---

A group element that contains the specification of Year, Month, and Day.

## **Time**

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## OrderConfirmationLineItem

The detail of the items that are communicated in the OrderConfirmation e-Document.

### OrderConfirmationLineItemStatusType [attribute]

*OrderConfirmationLineItemStatusType is mandatory. A single instance is required.*

Defines the status of the OrderConfirmation line item

Refer to OrderConfirmationLineItemStatusType definition for any enumerations.

### OrderConfirmationLineItemDocumentStatus [attribute]

*OrderConfirmationLineItemDocumentStatus is optional. A single instance might exist.*

Defines the actual document status for the OrderConfirmationLineItem.

Refer to OrderConfirmationLineItemDocumentStatus definition for any enumerations.

### Billable [attribute]

*Billable is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Billable definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### OrderConfirmationLineItemNumber

*OrderConfirmationLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the OrderConfirmation line item.

#### OrderConfirmationLineItemStatusTypeText


*OrderConfirmationLineItemStatusTypeText is optional. A single instance might exist.*

A text field that may provide detail explaining the status of the OrderConfirmationLineItem.

When a PurchaseOrderLineItem is rejected, the reason for the rejection must be specified in this field.

Not required if the PurchaseOrder is accepted or no changes have been made.

If the item is pending, the reason may be specified here.



## **PurchaseOrderLineItemNumber**

*PurchaseOrderLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the PurchaseOrder line item.

## **Product**

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **OrderConfirmationReference**

*OrderConfirmationReference is optional. Multiple instances might exist.*

A group item detailing relevant references pertaining to the OrderConfirmation. Typically, the ContractNumber is referenced. OrderConfirmationReferenceType provides the identification of what the reference represents.

## **PriceDetails**

*PriceDetails is optional. Multiple instances might exist.*

An element that groups together price information.

## **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates the type of adjustment being communicated.

## **LineBaseAmount**

*LineBaseAmount is optional. A single instance might exist.*

For the particular e-Document being communicated the LineBaseAmount represents the quantity times the base unit price.

## **DeliveryDestination**

*DeliveryDestination is optional. A single instance might exist.*

The DeliveryDestination specifies the end of one leg of the delivery. In order to comply with the US Trade Act of 2002 you would use this element with a LocationParty/@PartyType of Port.

## **DeliveryOrigin**

*DeliveryOrigin is optional. A single instance might exist.*

A group item that represents the start of one leg in a route. Compare to DeliveryDestination.

The DeliveryOrigin specifies the start of one leg of the delivery.

In order to comply with the US Trade Act of 2002 you would use this element with a LocationParty/@PartyType of Port.

## **MillProductionInformation**

*MillProductionInformation is optional. Multiple instances might exist.*

A grouping element that contains information about production at the mill.

## **ProductionStatus**

*ProductionStatus is optional. A single instance might exist.*

A group item used to communicate the release of a delivery line number.

## **Quantity**

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **OtherDate**

*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## **(choice)**

*[choice] is optional because of choice construct.*

### **ShipToCharacteristics**

*ShipToCharacteristics is optional because of choice construct.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

### **ShipmentMethodOfPayment**

*ShipmentMethodOfPayment is optional because of choice construct.*

An element communicating responsibility of freight payment and when transfer of ownership will occur.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **TransportModeCharacteristics**

*TransportModeCharacteristics is optional. A single instance might exist.*

A group item defining the primary mode of transport.

## **TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

## **TransportUnitCharacteristics**

*TransportUnitCharacteristics is optional. A single instance might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

## **TransportLoadingCharacteristics**

*TransportLoadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be loaded.

## **TransportUnloadingCharacteristics**

*TransportUnloadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be unloaded.

## **TransportOtherInstructions**

*TransportOtherInstructions is optional. Multiple instances might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

## **DeliverySchedule**

*DeliverySchedule is optional. Multiple instances might exist.*

A group item defining a series of DeliveryDateWindow(s) in which specified quantities must be delivered.

## **GeneralLedgerAccount**

*GeneralLedgerAccount is optional. A single instance might exist.*

The general ledger account to be referenced for the item.

## **EndUses**

*EndUses is optional. Multiple instances might exist.*

A text element used to express in human readable form a list of applicable end uses for a product. Examples of end uses are:

- Magazine
- Book
- Commercial print
- etc

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **SafetyAndEnvironmentalInformation**

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

## OrderConfirmationLineItemDocumentStatus [attribute]

Defines the actual document status for the OrderConfirmationLineItem.

*This item is restricted to the following list.*

attribute
<b>OrderConfirmationLineItemDocumentStatus</b>
type documentStatusType.OrderConfirmation

### Cancelled

The supplied information of the document item is cancelled. Items that have been cancelled are not included in totals on the summary level of e-Documents.

### Confirmed

The supplied information of the document item is agreed. If a requested change or cancellation of an existing document item can not be accepted, then the earlier agreed information of the document item will be re-confirmed.

### Pending

The supplied information of the document item is being investigated.

### Rejected

The supplied information of the document item can not be accepted. The document item is new or not earlier confirmed.

---

## OrderConfirmationLineItemDocumentStatus [attribute]

Defines the actual document status for the OrderConfirmationLineItem.

*This item is restricted to the following list.*

attribute
<b>OrderConfirmationLineItemDocumentStatus</b>
type documentStatusType.OrderConfirmationWood

### Cancelled

The supplied information of the document item is cancelled. Items that have been cancelled are not included in totals on the summary level of e-Documents.

### Confirmed

The supplied information of the document item is agreed. If a requested change or cancellation of an existing document item can not be accepted, then the earlier agreed information of the document item will be re-confirmed.

### Pending

The supplied information of the document item is being investigated.

### Rejected

The supplied information of the document item can not be accepted. The document item is new or not earlier confirmed.

## OrderConfirmationLineItemNumber

The sequential number that uniquely identifies the OrderConfirmation line item.

<b>OrderConfirmationLineItemNumber</b>
type   s30

---

## OrderConfirmationLineItemStatusType [attribute]

Defines the status of the OrderConfirmation line item

*This item is restricted to the following list.*

attribute
<b>OrderConfirmationLineItemStatusType</b>
type   orderConfirmationLineItemStatusType

### Accepted

The supplied information is accepted.

### Amended

The supplied information is changed

### Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### NoAction

The supplied information has not been amended and thereby requires no action.

### Pending

The supplied information is not complete and will be updated later.

### Rejected

The supplied information is rejected.

---

## OrderConfirmationLineItemStatusTypeText

A text field that may provide detail explaining the status of the OrderConfirmationLineItem.

<b>OrderConfirmationLineItemStatusTypeText</b>
type   s72

When a PurchaseOrderLineItem is rejected, the reason for the rejection must be specified in this field.

Not required if the PurchaseOrder is accepted or no changes have been made.

If the item is pending, the reason may be specified here.

---

## OrderConfirmationNumber



The unique order identifier as designated by the seller.

<b>OrderConfirmationNumber</b>
type   s30

## OrderConfirmationReference

A group item detailing relevant references pertaining to the OrderConfirmation.

Typically, the ContractNumber is referenced.



OrderConfirmationReferenceType provides the identification of what the reference represents.

### OrderConfirmationReferenceType [attribute]

*OrderConfirmationReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to OrderConfirmationReferenceType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.


---

## OrderConfirmationReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an

existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.



## OrderConfirmationStatusType [attribute]

Identifies the status of the whole OrderConfirmation e-Document (i.e. at the root level)



*This item is restricted to the following list.*

### **Accepted**

The supplied information is accepted.

### **Amended**

The supplied information is changed.

### **Cancelled**

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### **Rejected**

The supplied information is rejected.

## OrderConfirmationSummary

Summary information that applies to the whole OrderConfirmation e-Document.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### TotalNumberOfLineItems

*TotalNumberOfLineItems is optional. A single instance might exist.*

The total number of individual line items in the document, regardless of the status or type.

**(sequence)**



*The sequence of items below is optional. Multiple instances might exist.*

### TotalQuantity

*TotalQuantity is mandatory. A single instance is required.*

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

### TotalInformationalQuantity

*TotalInformationalQuantity is optional. Multiple instances might exist.*

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

### LineItemSubTotal

*LineItemSubTotal is optional. A single instance might exist.*

The total amount of all e-Document LineBaseAmount(s) line items without any monetary adjustments that may occur after the e-Document line items.


### TotalAdjustments

*TotalAdjustments is optional. A single instance might exist.*

The CurrencyValue of TotalAdjustments contains the total of all MonetaryAdjustmentAmount for all instances of PriceAdjustment and FlatAmountAdjustment in the document (it excludes TaxAdjustments).

### TotalTaxAmount

*TotalTaxAmount is optional. A single instance might exist.*



# papiNet V2R31

---

The CurrencyValue of TotalTaxAmount contains the sum of all instances of TaxAdjustment in the document. TotalTaxAmount contains the sum of all instances of the MonetaryAdjustmentAmount for tax adjustments.

## **TotalNetAmount**

*TotalNetAmount is optional. A single instance might exist.*

A field containing total amount excluding tax. For example, in the Invoice TotalNetAmount is equal to the sum of LineItemSubTotal plus TotalAdjustments. TotalNetAmount encapsulates CurrencyValue.

## **TotalAmount**

*TotalAmount is optional. A single instance might exist.*

A field containing the total amount including tax.

PurchaseOrder: The total amount, using a valid unit of measure of all the items in the e-Document. Multiple total amounts are allowed so different units of measure or grade sub-totals can be communicated.

CreditDebitNote and Invoice: TotalAmount is equal to TotalNetAmount plus TotalTaxAmount. In certain countries this is the amount that is due for payment based upon the terms of payment.

## **InformationalAmount**

*InformationalAmount is optional. Multiple instances might exist.*

A monetary amount used for information purposes only (not for calculation). For example, the invoice price adjustment subtotal is expressed in sterling pounds, and the buyer wants this information expressed in U.S. dollars.

CreditDebitNote and Invoice - The TaxAmount is displayed in the currency that is applicable throughout the e-Document. When a TaxAmount needs to be displayed in a different national currency, this field is used.

## **(sequence)**

*The sequence of items below is optional. Multiple instances might exist.*

### **TermsOfPayment**

*TermsOfPayment is mandatory. A single instance is required.*

A group item that contains agreed-to terms defining when, how, and under what conditions the payment is to be made.

When TermsOfPayment is optional; if omitted, TermsOfPayment is controlled through previous negotiation.

### **TotalNetOfTermsDiscount**

*TotalNetOfTermsDiscount is optional. A single instance might exist.*

The components of the amount to be paid if prompt payment discount terms are met, including the amount that is subject to the payment terms discount, the discount amount, and the amount due after prompt payment discount.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **TermsAndDisclaimers**


*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.

## OrderConfirmationWood

The OrderConfirmationWood element is the root element for the OrderConfirmationWood e-Document.

A seller sends an OrderConfirmationWood e-Document to a buyer after receiving a PurchaseOrder from that buyer. The e-Document contains a response to the conditions specified in the PurchaseOrder. A supplier may also send an OrderConfirmationWood e-Document to convey changes that the supplier has made in the order or to convey new information such as a Supplier Reference Number or Job Number.



### OrderConfirmationStatusType [attribute]

*OrderConfirmationStatusType is mandatory. A single instance is required.*

Identifies the status of the whole OrderConfirmation e-Document (i.e. at the root level)

Refer to OrderConfirmationStatusType definition for any enumerations.

### OrderContextType [attribute]

*OrderContextType is optional. A single instance might exist.*

Qualifies the source of the PurchaseOrder.

Refer to OrderContextType definition for any enumerations.

### OrderType [attribute]

*OrderType is optional. A single instance might exist.*

Defines the type of OrderConfirmationWood being communicated.

Refer to OrderType definition for any enumerations.

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

## **Language [attribute]**

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **OrderConfirmationWoodHeader**

*OrderConfirmationWoodHeader is mandatory. A single instance is required.*

OrderConfirmationWoodHeader contains information that is consistent across the entire document.

### **OrderConfirmationWoodProductGroup**

*OrderConfirmationWoodProductGroup is mandatory. One instance is required, multiple instances might exist.*

Group element used to potentially group like products together. Construct consists of a product group id, line items, and a product grouping summary.

### **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount.

MonetaryAdjustment contains an attribute that indicates they type of adjustment being communicated.

### **OrderConfirmationWoodSummary**

*OrderConfirmationWoodSummary is optional. A single instance might exist.*

Summary information that applies to the Wood market segment OrderConfirmationWood e-Document.

## OrderConfirmationWoodHeader

OrderConfirmationWoodHeader contains information that is consistent across the entire document.

### OrderConfirmationHeaderStatusType [attribute]

*OrderConfirmationHeaderStatusType is mandatory. A single instance is required.*

An attribute defining the status of the OrderConfirmationWood header

Refer to

OrderConfirmationWoodHeader

OrderConfirmationHeaderStatusType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### OrderConfirmationNumber

*OrderConfirmationNumber is optional. A single instance might exist.*

The unique order identifier as designated by the seller.

#### OrderConfirmationHeaderStatusTypeText

*OrderConfirmationHeaderStatusTypeText is optional. A single instance might exist.*

A text field that may provide detail explaining the status of the OrderConfirmationHeader.

This field is required if the OrderConfirmationHeaderStatusType is "Rejected".

When the OrderConfirmationHeaderStatusType is "Pending", the reason can be specified in this field.

Not required if the PurchaseOrder is "Accepted".

#### OrderConfirmationIssuedDate


*OrderConfirmationIssuedDate is mandatory. A single instance is required.*

The Date and optionally the Time that the OrderConfirmation was issued.

#### TransactionHistoryNumber

*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger



transaction for which the confirmation is being sent.

## **TransactionHistoryConfirmationNumber**

*TransactionHistoryConfirmationNumber is optional. A single instance might exist.*

A sequential number that indicates the version of the confirmation document being sent.

## **PurchaseOrderInformation**

*PurchaseOrderInformation is optional. A single instance might exist.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

## **OrderDocumentRequired**

*OrderDocumentRequired is optional. Multiple instances might exist.*

Group element used to identify any external documents that need to be referenced and how many of those documents are required. Typically, used to identify hard copy documents.

This element will be deprecated in the next version of papiNet. Use the DocumentInformation element instead.

## **BuyerParty**

*BuyerParty is mandatory. A single instance is required.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## **BillToParty**

*BillToParty is optional. A single instance might exist.*

The address where the invoice is to be sent.

## **SupplierParty**

*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **ShipToInformation**

*ShipToInformation is optional. A single instance might exist.*

Group element containing information about the ship to and delivery of a product.

## **CountryOfOrigin**

*CountryOfOrigin is optional. A single instance might exist.*

The country of origin for the material.

## **CountryOfDestination**

*CountryOfDestination is optional. A single instance might exist.*

The country where the goods will be, or were, shipped to.

## **CountryOfConsumption**

*CountryOfConsumption is optional. A single instance might exist.*

The country of consumption for the material.

## **ValidityPeriod**

*ValidityPeriod is optional. A single instance might exist.*

The validity period for a specific item, e.g. the validity period for an e-Document.

## **Insurance**

*Insurance is optional. A single instance might exist.*

Group element containing information about insurance

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **OrderConfirmationReference**

*OrderConfirmationReference is optional. Multiple instances might exist.*

A group item detailing relevant references pertaining to the OrderConfirmation. Typically, the ContractNumber is referenced. OrderConfirmationReferenceType provides the identification of what the reference represents.

## **DocumentInformation**

*DocumentInformation is optional. Multiple instances might exist.*

A group element containing a specification of required documents in the business process. Additional free text to be printed on documents can also be specified.

## OrderConfirmationWoodLineItem

The details of the line items that are communicated on the Wood market segment OrderConfirmationWood.

### OrderConfirmationLineItemStatusType [attribute]

*OrderConfirmationLineItemStatusType is mandatory. A single instance is required.*

Defines the status of the OrderConfirmation line item

Refer to

OrderConfirmationWoodLineItem

OrderConfirmationLineItemStatusType definition for any enumerations.

### OrderConfirmationLineItemDocumentStatus [attribute]

*OrderConfirmationLineItemDocumentStatus is optional. A single instance might exist.*

Defines the actual document status for the OrderConfirmationLineItem.

Refer to

OrderConfirmationLineItemDocumentStatus definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### OrderConfirmationLineItemNumber

*OrderConfirmationLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the OrderConfirmation line item.

#### OrderConfirmationLineItemStatusTypeText

*OrderConfirmationLineItemStatusTypeText is optional. A single instance might exist.*

A text field that may provide detail explaining the status of the OrderConfirmationLineItem.

When a PurchaseOrderLineItem is rejected, the reason for the rejection must be specified in this field.


Not required if the PurchaseOrder is accepted or no changes have been made.

If the item is pending, the reason may be specified here.

#### PurchaseOrderLineItemNumber

*PurchaseOrderLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the PurchaseOrder line item.



## **Product**

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **DocumentReferenceInformation**

*DocumentReferenceInformation is optional. Multiple instances might exist.*

A group item containing reference information applicable to a document.

## **EndsDiscountInformation**

*EndsDiscountInformation is optional. A single instance might exist.*

Rule for calculating the ends discount, expressed by a code.

## **PriceDetails**

*PriceDetails is optional. Multiple instances might exist.*

An element that groups together price information.

## **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates the type of adjustment being communicated.

## **LineBaseAmount**

*LineBaseAmount is optional. A single instance might exist.*

For the particular e-Document being communicated the LineBaseAmount represents the quantity times the base unit price.

## **DeliveryDestination**

*DeliveryDestination is optional. A single instance might exist.*

The DeliveryDestination specifies the end of one leg of the delivery. In order to comply with the US Trade Act of 2002 you would use this element with a LocationParty/@PartyType of Port.

## **DeliveryOrigin**

*DeliveryOrigin is optional. A single instance might exist.*

A group item that represents the start of one leg in a route. Compare to DeliveryDestination.

The DeliveryOrigin specifies the start of one leg of the delivery.

In order to comply with the US Trade Act of 2002 you would use this element with a LocationParty/@PartyType of Port.

## **LocationParty**

*LocationParty is optional. Multiple instances might exist.*

The organization or business entity where the business event took place or will take place.

## **MillProductionInformation**

*MillProductionInformation is optional. Multiple instances might exist.*

A grouping element that contains information about production at the mill.

## **ProductionStatus**

*ProductionStatus is optional. A single instance might exist.*

A group item used to communicate the release of a delivery line number.

## **QuantityOrderedInformation**

*QuantityOrderedInformation is optional. A single instance might exist.*

Used to identify quantity. The construct provides via InformationalQuantity the ability to provide the Quantity in another UOM. Length is also provided to further specify the quantity.

## **OtherDate**

*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## **(choice)**

*[choice] is optional because of choice construct.*

## **ShipToInformation**

*ShipToInformation is optional because of choice construct.*

Group element containing information about the ship to and delivery of a product.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

### **DeliverySchedule**

*DeliverySchedule is optional. Multiple instances might exist.*

A group item defining a series of DeliveryDateWindow(s) in which specified quantities must be delivered.

## **ShipmentMethodOfPayment**

*ShipmentMethodOfPayment is optional because of choice construct.*

An element communicating responsibility of freight payment and when transfer of ownership will occur.

## **CountryOfOrigin**

*CountryOfOrigin is optional. A single instance might exist.*

The country of origin for the material.

## **CountryOfDestination**

*CountryOfDestination is optional. A single instance might exist.*

The country where the goods will be, or were, shipped to.

## **CountryOfConsumption**

*CountryOfConsumption is optional. A single instance might exist.*

The country of consumption for the material.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **(choice)**

*[choice] is optional because of choice construct.*

## **PackageInformation**

*PackageInformation is optional because of choice construct.*

The purpose of the PackageInformation structure is to clearly identify physical handling items that constitute the delivery.

PackageInformation is the highest level of product packaging it describes the shipping or warehousing unit.

If you are communicating a package, usually for logistics or transport purposes, you should include the PackageType, Identifier, ItemCount, and Quantity. (Note: you still have the ability to describe the item with one of the "named" items.)

If you are communicating one of the named Items there is no need to include PackageType, Identifier, ItemCount, and Quantity.

Since either of these two approaches can be used the entire contents of this element are optional even though the parent may be required. It is expected that you will fill in the appropriate details.

## **TransportPackageInformation**

*TransportPackageInformation is optional because of choice construct.*

Information of a package used in transportation, can include several normal packages.

## **ProductSummary**

*ProductSummary is optional. A single instance might exist.*

Group of elements to provide summary information on product level.

## **LengthSpecification**

*LengthSpecification is optional. Multiple instances might exist.*

Length specification of the wood product.

## **QuantityDeviation**

*QuantityDeviation is optional. A single instance might exist.*

To be deprecated in a future version. Use the Quantity element with a QuantityContext of "Deviation".

## **EndUses**

*EndUses is optional. Multiple instances might exist.*

A text element used to express in human readable form a list of applicable end uses for a product. Examples of end uses are:

Magazine

Book  
Commercial print  
etc

## SafetyAndEnvironmentalInformation

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## OrderConfirmationReference

*OrderConfirmationReference is optional. Multiple instances might exist.*

A group item detailing relevant references pertaining to the OrderConfirmation. Typically, the ContractNumber is referenced. OrderConfirmationReferenceType provides the identification of what the reference represents.

## DocumentInformation


*DocumentInformation is optional. A single instance might exist.*

A group element containing a specification of required documents in the business process. Additional free text to be printed on documents can also be specified.

---

## OrderConfirmationWoodProductGroup

Group element used to potentially group like products together. Construct consists of a product group id, line items, and a product



grouping summary.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### ProductGroupID

*ProductGroupID is optional. A single instance might exist.*

Possibility to group packages or Shipments. Example: Creating temporary group ID's for logistic reasons or lot number.

### OrderConfirmationWoodLineItem

*OrderConfirmationWoodLineItem is mandatory. One instance is required, multiple instances might exist.*

The details of the line items that are communicated on the Wood market segment OrderConfirmationWood.

## ProductGroupSummary

*ProductGroupSummary is optional. A single instance might exist.*

Group of elements to provide summary information on product level.

## OrderConfirmationWoodSummary

Summary information that applies to the Wood market segment OrderConfirmationWood e-Document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### TotalNumberOfLineItems

*TotalNumberOfLineItems is optional. A single instance might exist.*

The total number of individual line items in the document, regardless of the status or type.

### (sequence)

*The sequence of items below is optional. Multiple instances might exist.*

### TotalQuantity



*TotalQuantity is mandatory. A single instance is required.*

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

### TotalInformationalQuantity

*TotalInformationalQuantity is optional. Multiple instances might exist.*

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.


## ProductSummary

*ProductSummary is optional. A single instance might exist.*

Group of elements to provide summary information on product level.

## LengthSpecification

*LengthSpecification is optional. Multiple instances might exist.*



Length specification of the wood product.

## **QuantityDeviation**

*QuantityDeviation is optional. A single instance might exist.*

To be deprecated in a future version. Use the Quantity element with a QuantityContext of "Deviation".

## **LineItemSubTotal**

*LineItemSubTotal is optional. A single instance might exist.*

The total amount of all e-Document LineBaseAmount(s) line items without any monetary adjustments that may occur after the e-Document line items.

## **TotalAdjustments**

*TotalAdjustments is optional. A single instance might exist.*

The CurrencyValue of TotalAdjustments contains the total of all MonetaryAdjustmentAmount for all instances of PriceAdjustment and FlatAmountAdjustment in the document (it excludes TaxAdjustments).

## **TotalTaxAmount**

*TotalTaxAmount is optional. A single instance might exist.*

The CurrencyValue of TotalTaxAmount contains the sum of all instances of TaxAdjustment in the document. TotalTaxAmount contains the sum of all instances of the MonetaryAdjustmentAmount for tax adjustments.

## **TotalNetAmount**

*TotalNetAmount is optional. A single instance might exist.*

A field containing total amount excluding tax. For example, in the Invoice TotalNetAmount is equal to the sum of LineItemSubTotal plus TotalAdjustments. TotalNetAmount encapsulates CurrencyValue.

## **TotalAmount**

*TotalAmount is optional. A single instance might exist.*

A field containing the total amount including tax.

PurchaseOrder: The total amount, using a valid unit of measure of all the items in the e-Document. Multiple total amounts are allowed so different units of measure or grade sub-totals can be communicated.

CreditDebitNote and Invoice: TotalAmount is equal to TotalNetAmount plus TotalTaxAmount. In certain countries this is the amount that is due for payment based upon the terms of payment.

## **InformationalAmount**

*InformationalAmount is optional. Multiple instances might exist.*

A monetary amount used for information purposes only (not for calculation). For example, the invoice price adjustment subtotal is expressed in sterling pounds, and the buyer wants this information expressed in U.S. dollars.

CreditDebitNote and Invoice - The TaxAmount is displayed in the currency that is applicable throughout the e-Document. When a TaxAmount needs to be displayed in a different national currency, this field is used.

## **(sequence)**

*The sequence of items below is optional. Multiple instances might exist.*

## **TermsOfPayment**

# papiNet V2R31

---

*TermsOfPayment is mandatory. A single instance is required.*

A group item that contains agreed-to terms defining when, how, and under what conditions the payment is to be made.

When TermsOfPayment is optional; if omitted, TermsOfPayment is controlled through previous negotiation.

## **TotalNetOfTermsDiscount**

*TotalNetOfTermsDiscount is optional. A single instance might exist.*

The components of the amount to be paid if prompt payment discount terms are met, including the amount that is subject to the payment terms discount, the discount amount, and the amount due after prompt payment discount.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **TermsAndDisclaimers**

*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.

---

## **OrderContextType [attribute]**

Qualifies the source of the PurchaseOrder.


*This item is restricted to the following list.*

### **PurchaseOrder**

The source is the buyer.

### **SalesOrder**


The source is the supplier.



---

## **OrderDocumentRequired**

Group element used to identify any external documents that need to be referenced and how many of those documents are required. Typically, used to identify hard copy documents.



This element will be deprecated in the next version of papiNet. Use the DocumentInformation element instead.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

## NumberOrderDocumentRequired

*NumberOrderDocumentRequired is mandatory. A single instance is required.*

There are certain business cases whereby a party is required to reference external documents to the transaction. Additionally, in these cases, the party is required to communicate the number of these external documents. This element is used to indicate how many of these external documents will be required. Typically used to indicate how many hard copies of the referenced document are needed.

## DocumentRequired

*DocumentRequired is mandatory. A single instance is required.*

An element that permits the listing of the documents required.

---

## OrderHeaderStatusType [attribute]

Defines the status of the PurchaseOrder header

*This item is restricted to the following list.*

### Amended

The supplied information is changed.

### Cancelled


The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### New

The supplied information is new and supplied for the first time.

### NoAction

The supplied information has not been amended and thereby requires no action.



---

## OrderLineItemDocumentStatus [attribute]

Defines the actual document status for the PurchaseOrderLineItem.


*This item is restricted to the following list.*

### Cancelled

The supplied information of the document item is cancelled. Items that have been cancelled are not included in totals on the summary level of e- Documents.

### Requested


The supplied information of the document item is ordered.



## OrderLineItemStatusType [attribute]

Defines the status of the PurchaseOrder line item

*This item is restricted to the following list.*



### Amended

The supplied information is changed.

### Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### New

The supplied information is new and supplied for the first time.

### NoAction


The supplied information has not been amended and thereby requires no action.

## OrderPrimaryStatus

An element that contains the highest level status code pertaining to an entire order.

### OrderStatusCode [attribute]

*OrderStatusCode is mandatory. A single instance is required.*




This attribute communicates the overall status of the order. Refer to OrderStatusCode definition for any enumerations.

## OrderQuantities

An element that contains the quantities that can be used for ordering.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### MinimumOrderQuantity

*MinimumOrderQuantity is optional. A single instance might exist.*

The minimum amount that can be ordered on a PurchaseOrder.

### MaximumOrderQuantity

*MaximumOrderQuantity is optional. A single instance might exist.*

The maximum amount that can be ordered at one time.


### IncrementalOrderQuantity

*IncrementalOrderQuantity is optional. A single instance might exist.*

An incremental quantity and units of measure that is added to MinimumOrderQuantity to arrive at an order quantity.

## OrderSecondaryStatus


An element that contains a secondary status description pertaining to the entire order.



## OrderStatus

The OrderStatus element is the root element for the OrderStatus e-Document.

The OrderStatus e-Document permits the sender to report the current status of an order, specific order line items, or to report status of multiple orders based upon some specified criteria. The e-Document enables the sender to indicate a primary status as well as an additional secondary status at the order level as well as for each line and component.



### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

### OrderStatusType [attribute]

*OrderStatusType is mandatory. A single instance is required.*

Communicates the method in which the OrderStatus has been, or should be, summarized.

Refer to OrderStatusType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### OrderStatusHeader

*OrderStatusHeader is mandatory. A single instance is required.*

Information that applies to the entire OrderStatus e-Document.

#### OrderStatusDetail

*OrderStatusDetail is mandatory. One instance is required, multiple instances might exist.*

The specifics of the information being communicated in the OrderStatus e-Document.

## OrderStatusCode [attribute]

This attribute communicates the overall status of the order.

*This item is restricted to the following list.*

attribute
<b>OrderStatusCode</b>
type orderStatusCode

### **ActiveFree**

The PO, order, or line item has been accepted or confirmed by the supplier. It may not have been manufactured, packed, or shipped yet. It is free for production. This status is also known as open status.

### **ActiveHold**

The PO, order, or line item has been accepted or confirmed by the supplier. It may not have been manufactured, packed, or shipped yet. It is not free for production. Examples of this status include a reserved order or line item, the print time has not been determined, other payment terms not completed, or the last date for change has not been received.

### **Cancelled**

The PO, order, or line item has a cancelled status in the supplier's system. It will not be manufactured nor shipped.

### **Complete**

The PO, order, or line item has a complete status in the supplier's system. It has been packed, shipped, and invoiced successfully.

### **Delayed**

An unexpected event has caused a delay.

### **FinalPlanning**

The order is undergoing the final planning process.

### **Invoiced**

The PO, order, or line item has an invoiced status in the supplier's system. It has been billed to the customer for payment purposes.

### **Loaded**

The PO, order, or line item has a loaded status in the supplier's system. It has been loaded onto a transport vehicle shipping purposes.

### **NotReceived**

Not received by either the buyer or seller.

### **OrderLineConfirmed**

The order line has been confirmed.

### **Packed**

The PO, order, or line item has a packed status in the supplier's system. It has been packaged or staged for loading and shipping purposes.

### **PartiallyShipped**

The PO, order, or line item has a partially shipped status in the supplier's system. Part of the quantity requested has been shipped to the customer but

part of the request still remains to be shipped.

## **Pending**

The PO, order, or line item has a pending status in the supplier's system. It has not yet been confirmed, accepted, nor rejected by the supplier. This status indicates that the supplier requires more time to determine acceptance.

## **Planned**

The PO, order, or line item has a planned or scheduled status in the supplier's system. It has not yet begun the manufacturing process.

## **ProductionComplete**

The PO, order, or line item has completed the manufacture process by the supplier.

## **ProductionPlanned**

Production has been planned for the order.

## **ProductionStarted**

The PO, order, or line item has begun to be manufactured by the supplier.

## **Received**

The material has arrived at the destination and has been processed by that location.

## **ReservedInProductionPlanningSystem**

Material and capacity is available for production.

## **Scheduled**

The order has been scheduled.

## **ShipmentComplete**

The order has been fully shipped.

## **ShipmentPlanned**

Shipment has been planned for the order

## **Shuttled**

Material has been moved.

## **Staged**

Material has been positioned for production.

## **Transferred**

The manufacturing order has been moved.

## **TransferredToMillSystem**

The order has been loaded onto the mill manufacturing system.

## **Unscheduled**

The order has not yet been scheduled.

## **Unshipped**

The PO, order, or line item is in the supplier's mill or warehouse but has yet to be shipped.

## OrderStatusDetail

The specifics of the information being communicated in the OrderStatus e-Document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PurchaseOrderInformation

*PurchaseOrderInformation is mandatory. A single instance is required.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

#### PurchaseOrderLineItemNumber

*PurchaseOrderLineItemNumber is mandatory. A single instance is required.*

The sequential number that uniquely identifies the PurchaseOrder line item.

### (sequence)

*The sequence of items below is optional. Multiple instances might exist.*

#### SupplierOrderNumber

*SupplierOrderNumber is mandatory. A single instance is required.*

The number of the supplier order.

#### SupplierOrderLineItemNumber

*SupplierOrderLineItemNumber is optional. A single instance might exist.*

The number of the line item on the supplier order.

#### LocationParty


*LocationParty is optional. A single instance might exist.*

The organization or business entity where the business event took place or will take place.

#### Product

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics.



product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **SupplierParty**

*SupplierParty is optional. A single instance might exist.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **BuyerParty**

*BuyerParty is optional. A single instance might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## **ShipToParty**

*ShipToParty is optional. A single instance might exist.*

The name and/or address to which the goods should be delivered with the party type indicated by the PartyType attribute.

## **EndUserParty**

*EndUserParty is optional. A single instance might exist.*

The party using, consuming, or converting the product. For example, a printer using paper reels for a print job for a publisher. The final ShipTo destination for a product is normally to the end user's facilities.

## **ForwarderParty**

*ForwarderParty is optional. A single instance might exist.*

The trading partner involved in the forwarding of the shipment.

## **MerchantParty**

*MerchantParty is optional. A single instance might exist.*

This named party represents the merchant involved in the business transaction. This party is only used in the communication of OrderStatus otherwise it is handled via OtherParty.

## **SalesOfficeParty**

*SalesOfficeParty is optional. A single instance might exist.*

This named party represents the sales office involved in the business transaction. This party is only used in the communication of OrderStatus otherwise it is handled via OtherParty.

## **LocationParty**

*LocationParty is optional. A single instance might exist.*

The organization or business entity where the business event took place or will take place.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **OrderStatusInformation**

*OrderStatusInformation is optional. Multiple instances might exist.*

A group element that stores two levels of order status codes.

## **Quantity**

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **LastDateOfChange**

*LastDateOfChange is optional. A single instance might exist.*

The last date for which changes to the line item may occur before it is "locked" in the production process. LastDateOfChange encapsulates Date.

## **DeliveryDateWindow**

*DeliveryDateWindow is optional. A single instance might exist.*

A group item defining the date/time interval for delivery to take place. An element which may contain the estimated date for which delivery is expected. This date is not absolute.

## **OtherDate**

*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## **ShipmentDetails**

*ShipmentDetails is optional. Multiple instances might exist.*

A group element containing information that relates to the shipment details for the line item.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **OrderStatusReference**

*OrderStatusReference is optional. Multiple instances might exist.*

An item detailing relevant references (such as contract number) pertaining to the OrderStatus. The type of reference is identified by the attribute OrderStatusReferenceType.

## OrderStatusHeader

Information that applies to the entire OrderStatus e-Document.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### OrderStatusNumber

*OrderStatusNumber is mandatory. A single instance is required.*

A number used to identify the OrderStatus report.

### OrderStatusResponseDate

*OrderStatusResponseDate is mandatory. A single instance is required.*

The Date and Time that the OrderStatus e-Document was created.

### RequestNumber

*RequestNumber is optional. A single instance might exist.*

A unique tracking number specifically identifying the InfoRequest e-Document to the originator. The tracking number is returned with the "information", the answer, to help match the answer to the request.

### RequestingParty

*RequestingParty is optional. A single instance might exist.*

The party requesting the information.

### RespondToParty

*RespondToParty is optional. Multiple instances might exist.*

The party the document should be responded to.

### SenderParty

*SenderParty is optional. A single instance might exist.*


The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

### ReceiverParty

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.



The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## OrderStatusReference

*OrderStatusReference is optional. Multiple instances might exist.*

An item detailing relevant references (such as contract number) pertaining to the OrderStatus. The type of reference is identified by the attribute OrderStatusReferenceType.


---

## OrderStatusInformation

A group element that stores two levels of order status codes.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### OrderPrimaryStatus

*OrderPrimaryStatus is mandatory. A single instance is required.*

An element that contains the highest level status code pertaining to an entire order.

### OrderSecondaryStatus

*OrderSecondaryStatus is optional. A single instance might exist.*

An element that contains a secondary status description pertaining to the entire order.

### OrderStatusInformationDate

*OrderStatusInformationDate is optional. A single instance might exist.*

The date and time when the specified OrderStatus was achieved.

### QuantityInformation

*QuantityInformation is optional. A single instance might exist.*

A group item containing information about quantity and informational quantity of similar items.


## OrderStatusInformationDate

The date and time when the specified OrderStatus was achieved.

**(sequence)**

*The sequence of items*

*below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.


hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.


## OrderStatusNumber

A number used to identify the OrderStatus report.



## OrderStatusReference

An item detailing relevant references (such as contract number) pertaining to the OrderStatus. The type of reference is identified by the attribute OrderStatusReferenceType.



### OrderStatusReferenceType [attribute]

*OrderStatusReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be

announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to OrderStatusReferenceType definition for any enumerations.

## **AssignedBy [attribute]**

*AssignedBy is mandatory. A single instance is required.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## **OrderStatusReferenceType [attribute]**


Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse" or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute AssignedBy will communicate the information previously communicated in the prefix.

OrderStatusReferenceType	
type	referenceType

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## OrderStatusRequestDetail

The element that contains the details associated with the order status request e-Document.



### OrderStatusRequestDetailType [attribute]

*OrderStatusRequestDetailType is mandatory. A single instance is required.*

Communicates the method in which the OrderStatus should be summarized.

Refer to OrderStatusRequestDetailType definition for any enumerations.

#### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### SupplierParty

*SupplierParty is optional. Multiple instances might exist.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

#### BuyerParty

*BuyerParty is optional. Multiple instances might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## **ShipToParty**

*ShipToParty is optional. Multiple instances might exist.*

The name and/or address to which the goods should be delivered with the party type indicated by the PartyType attribute.

## **EndUserParty**

*EndUserParty is optional. Multiple instances might exist.*

The party using, consuming, or converting the product. For example, a printer using paper reels for a print job for a publisher. The final ShipTo destination for a product is normally to the end user's facilities.

## **ForwarderParty**

*ForwarderParty is optional. Multiple instances might exist.*

The trading partner involved in the forwarding of the shipment.

## **MerchantParty**

*MerchantParty is optional. Multiple instances might exist.*

This named party represents the merchant involved in the business transaction. This party is only used in the communication of OrderStatus otherwise it is handled via OtherParty.

## **SalesOfficeParty**

*SalesOfficeParty is optional. Multiple instances might exist.*

This named party represents the sales office involved in the business transaction. This party is only used in the communication of OrderStatus otherwise it is handled via OtherParty.

## **LocationParty**

*LocationParty is optional. Multiple instances might exist.*

The organization or business entity where the business event took place or will take place.

## **OrderStatusInformation**

*OrderStatusInformation is optional. A single instance might exist.*

A group element that stores two levels of O order status codes.

## **DateTimeRange**

*DateTimeRange is optional. A single instance might exist.*

The delivery date and/or time range.

## **(choice)**

*[choice] is optional because of choice construct.*

### **ByPurchaseOrder**

*ByPurchaseOrder is optional because of choice construct.*

Selection criteria for communicating purchase order information.

### **BySupplierOrderNumber**

*BySupplierOrderNumber is optional because of choice construct.*

Selection criteria for communicating Supplier Order information

## **Product**

# papiNet V2R31

*Product is optional because of choice construct.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## OrderStatusRequestDetailType [attribute]

Communicates the method in which the OrderStatus should be summarized.

*This item is restricted to the following list.*

### ByProduct


By product

### ByPurchaseOrder

By the PurchaseOrder the material was ordered

### BySupplierOrderNumber

By the order the material was manufactured




## OrderStatusResponseDate

The Date and Time that the OrderStatus e-Document was created.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is mandatory. A single instance is required.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be

in discord with other users of XML.

---

## OrderStatusType [attribute]

Communicates the method in which the OrderStatus has been, or should be, summarized.

*This item is restricted to the following list.*

### **ByProduct**

By product

### **ByPurchaseOrder**

By the PurchaseOrder the material was ordered

### **BySupplierOrderNumber**

By the order the material was manufactured

attribute
<b>OrderStatusType</b>
type infoRequestDetailType

---

## OrderStatusType [attribute]

Defines the status of the entire PurchaseOrder e-Document, in other words, at the root level

*This item is restricted to the following list.*

### **Amended**

The supplied information is changed.

### **Cancelled**

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### **Original**

The supplied information is the first version of that information.

attribute
<b>OrderStatusType</b>
type purchaseOrderStatusType

---

## OrderType [attribute]

Defines the type of OrderConfirmation being communicated.

*This item is restricted to the following list.*

### **Agreement**

A legally binding exchange of promises between parties that the law will enforce.

### **BlanketOrder**

An order that communicates the same information as a StandardOrder but also indicates that the order may be completed over a period of time or, until a certain volume is achieved or, until a certain currency amount is spent.

### **ConfirmingOrder**

A confirming order is used to electronically confirm an order that has not been

attribute
<b>OrderType</b>
type orderConfirmationType

placed electronically by the customer that is, it was placed using another mean such as fax, phone or email.

## **ConsumptionOrder**

A PurchaseOrder that is based upon consumption for a particular period of time or instance.

## **ReleaseOrder**

A release order is used to release a product to be made. This type of order refers to a previous order or agreement, such as a reservation order, a contract, or a blanket order. A release number version which is an incremented number, is used in this type.

## **ReservationOrder**

A reservation order is used to book a paper supplier's capacity for specific quantities of specific products, but it is not yet a firm commitment to buy. Consequently, all line items of a reservation order have a ProductionStatusType of NotFree. To release one or more PurchaseOrder line items of a reservation order, a buyer can use a standard order or a release order.

## **StandardOrder**

A standard order is a regular one-time order. It defines quantities for one or more products to be purchased and may also define a delivery location and date. A standard order may reference a previous agreement (for example, a quotation, a contract, or a reservation order) for information.

## **TrialOrder**

A trial order is used whenever a seller has agreed to have a buyer sample a product. The seller needs to process this order differently from other orders, because a trial order may include a product sold at a discounted rate or even provided for free. A trial order typically is for small quantities.

---

## **OrderType [attribute]**

Defines the type of OrderConfirmationWood being communicated.

*This item is restricted to the following list.*

attribute
<b>OrderType</b>
type orderConfirmationTypeWood

### **Agreement**

A legally binding exchange of promises between parties that the law will enforce.

### **BlanketOrder**

An order that communicates the same information as a StandardOrder but also indicates that the order may be completed over a period of time or, until a certain volume is achieve or, until a certain currency amount is spent.

### **ReleaseOrder**

A release order is used to release a product to be made. This type of order refers to a previous order or agreement, such as a reservation order, a contract, or a blanket order. A release number version which is an

incremented number, is used in this type.

## **ReservationOrder**

A reservation order is used to book a paper supplier's capacity for specific quantities of specific products, but it is not yet a firm commitment to buy. Consequently, all line items of a reservation order have a ProductionStatusType of NotFree. To release one or more PurchaseOrder line items of a reservation order, a buyer can use a standard order or a release order.

## **StandardOrder**

A standard order is a regular one-time order. It defines quantities for one or more products to be purchased and may also define a delivery location and date. A standard order may reference a previous agreement (for example, a quotation, a contract, or a reservation order) for information.

---

## **OrderType [attribute]**

Defines the type of PurchaseOrder issued.

*This item is restricted to the following list.*

attribute
<b>OrderType</b>
type purchaseOrderTypeWood

## **BlanketOrder**

A PurchaseOrder that communicates the same information as a StandardOrder but also indicates that the order may be completed over a period of time or, until a certain volume is achieved or, until a certain currency amount is spent.

## **ReleaseOrder**

A release order is used to release a product to be made. This type of PurchaseOrder refers to a previous order or agreement, such as a reservation order, a contract, or a blanket order. A release number version called PurchaseOrderReleaseNumber, which is an incremented number, is used in this e-Document.

## **ReservationOrder**

A reservation order is used to book a paper supplier's capacity for specific quantities of specific products, but it is not yet a firm commitment to buy. Consequently, all PurchaseOrder line items of a reservation order have a ProductionStatusType of NotFree. To release one or more PurchaseOrder line items of a reservation order, a buyer can use a standard order or a release order.

## **StandardOrder**

## OrganisationUnit

A segment of a business or the entire business.

### OrganisationUnitType [attribute]

*OrganisationUnitType is mandatory. A single instance is required.*

Identifies the type of organisation being communicated

Refer to OrganisationUnitType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### OrganisationUnitName


*OrganisationUnitName is optional. A single instance might exist.*

A description of the organisation unit.

#### OrganisationUnitCode


*OrganisationUnitCode is optional. A single instance might exist.*

A short representation for the organisation unit.




## OrganisationUnitCode

A short representation for the organisation unit.



## OrganisationUnitName

A description of the organisation unit.



## OrganisationUnitType [attribute]

Identifies the type of organisation being communicated

*This item is restricted to the following list.*

### Department

A major division of a business.

### Division

An administrative or operating unit of a business

### Dock



A place for the unloading or loading of material.

## Location

A place marked by some distinguishing feature.

## Region

An administrative area of a business.

## StorageLocation

A place that supports the functions associated with warehousing of material.

## Terminal

A point along a carrier line having facilities for the handling of freight.

## Other

Another type of unit, not defined above.

## OrientationWithFaceWoodPanelGrain [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

**Yes**

**No**



## Original [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

**Yes**

**No**



## OtherDate


A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

### DateType [attribute]

*DateType is mandatory. A single instance is required.*

Provides a context for the other date used in the document.

Refer to DateType definition for any enumerations.



## **(choice)**

*[choice] is optional because of choice construct.*

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **Date**

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### **Time**

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

### **Week**

*Week is optional because of choice construct.*

A field defining the week number of the calendar year. ISO 8601 is used as the basis for this element, "Week 01 of a year is the first week that has the Thursday in this year, which is equivalent to the week that contains the fourth day of January."

### **DateTimeRange**

*DateTimeRange is optional because of choice construct.*

The delivery date and/or time range.

## OtherParty

An organisation or business entity other than those specifically detailed within a e-Document.

### PartyType [attribute]

*PartyType is mandatory. A single instance is required.*

Identifies the business role associated with the particular party

Refer to PartyType definition for any enumerations.

### LogisticsRole [attribute]

*LogisticsRole is optional. A single instance might exist.*

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PartyIdentifier

*PartyIdentifier is optional. Multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

#### NameAddress

*NameAddress is mandatory. A single instance is required.*

A group item containing name and address of an organisation or business entity.

#### URL


*URL is optional. A single instance might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

#### CommonContact

*CommonContact is optional. Multiple instances might exist.*

Identifies a specific individual associated with the party.



## OtherTreatment

Other treatment

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### AdditionalText



# papiNet V2R31

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## Overlay

Overlay

### OverlaySide [attribute]

*OverlaySide is optional. A single instance might exist.*

Overlay side

Refer to OverlaySide definition for any enumerations.


**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## OverlaySide [attribute]

Overlay side

*This item is restricted to the following list.*

- 1
- 2



## PackageAgency [attribute]

LumberAgency identifies which agency is responsible for assigning the lumber attributes.

*This item is restricted to the following list.*

**BS**

**BS-EN**


British standard based on a European standard.

**CEN**

European Committee for Standardisation (<http://www.cenorm.be>)

**DIN**

**EN338**



**EN1912**

**EN1611-1**

**EDISAW**

**Generic**

**GOST**

Russian federal agency on technical regulating and metrology  
(<http://www.gost.ru>)

**ISO**

**JAS**

Japanese Agricultural Standard

**NELMA**

**NLGA**

**NS**

**NSLB**

**RIS**

**RT**

**SIS**

**SPIB**

**WCLIB**

**WRCLA**

**WWPA**

**Supplier**

---

## PackageCharacteristics

The package characteristics.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### Height

*Height is optional. A single instance might exist.*

The height of the object.


### Width

*Width is optional. A single instance might exist.*

The width of the object.

### Length

*Length is optional. A single instance might exist.*



# papiNet V2R31

The length of the object.


## LengthCutDescription

*LengthCutDescription is optional. A single instance might exist.*

Length Cut Description


## PackageCode

This element is used to identify the package code or identifier. This code can be no-standard and vary among companies or it can be assigned by a recognized agency.



## PackageIdentifier

The identifier of the productpackage (such as reel ID or pallet ID) that is used along with the



PurchaseOrderLineItemNumber to call off the product.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Identifier

*Identifier is mandatory. A single instance is required.*

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.

## PackageIDInformation

Group element identifying a lumber (wood) package. The package name may also be communicated.

### PackageAgency [attribute]

*PackageAgency is optional. A single instance might exist.*

LumberAgency identifies which agency is responsible for assigning the lumber attributes.


Refer to PackageAgency definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### PackageCode

*PackageCode is optional. A single instance might exist.*



# papiNet V2R31

This element is used to identify the package code or identifier. This code can be non-standard and vary among companies or it can be assigned by a recognized agency.

## PackageName

*PackageName is optional. A single instance might exist.*

Element used to identify the name of a package.

## PackageInformation

The purpose of the PackageInformation structure is to clearly identify physical handling items that constitute the delivery.

PackageInformation is the highest level of product packaging it describes the shipping or warehousing unit.

If you are communicating a package, usually for logistics or transport purposes, you should include the PackageType, Identifier, ItemCount, and Quantity. (Note: you still have the ability to describe the item with one of the "named" items.)

If you are communicating one of the named Items there is no need to include PackageType, Identifier, ItemCount, and Quantity.

Since either of these two approaches can be used the entire contents of this element are optional even though the parent may be required. It is expected that you will fill in the appropriate details.

### PackageType [attribute]

*PackageType is optional. A single instance might exist.*

Communicates the configuration of the item being reported.



Refer to PackageType definition for any enumerations.

### MixedProductPalletIndicator [attribute]

*MixedProductPalletIndicator is optional. A single instance might exist.*

Specifies whether a product can be mixed with other products on the same pallet

Refer to MixedProductPalletIndicator definition for any enumerations.



## **PackageLevel [attribute]**

*PackageLevel is optional. A single instance might exist.*

An hierarchical numbering approach that communicates containerization and identity.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

#### **Identifier**

*Identifier is optional. Multiple instances might exist.*

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.

#### **SupplierMarks**

*SupplierMarks is optional. Multiple instances might exist.*

Supplier provided markings.

#### **RawMaterialSet**

*RawMaterialSet is optional. Multiple instances might exist.*

This identifier derived element indicates a grouping of raw materials that were used to manufacture the product.

### **(sequence)**

*The sequence of items below is optional. A single instance might exist.*

#### **PartyIdentifier**

*PartyIdentifier is mandatory. One instance is required, multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

#### **MachineID**

*MachineID is optional. A single instance might exist.*

An identifier assigned to the particular machine being referenced. For example, a machine could be a paper machine, an off-line coater, a sheeter, or a printing press. The particular machine being referenced will be determined by the business event being supported.

#### **ItemCount**

*ItemCount is optional. A single instance might exist.*

A count of the number of items (examples: a count of the number of boxes on a pallet or of reams in a box).

#### **Quantity**

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at

this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **InventoryClass**

*InventoryClass is optional. A single instance might exist.*

A group item containing information about status of inventory and goods items.

## **PackageCharacteristics**

*PackageCharacteristics is optional. A single instance might exist.*

The package characteristics.

## **(choice)**

*[choice] is optional because of choice construct.*

### **BaleItem**

*BaleItem is optional because of choice construct.*

An individual bale included as part of a delivery.

### **BoxItem**

*BoxItem is optional because of choice construct.*

A four-sided container for reams or sheet items. A pallet can contain zero or more boxes. The term Carton is a synonym for BoxItem. The term "Box" is used as constraint within the ItemType attribute of the UsageLineItemDetail to refer to a box that contains other boxes.

### **ReelItem**

*ReelItem is optional because of choice construct.*

A group item representing details of an actual (as opposed to specified) reel. One or several reels can be contained in a package.

### **ReamItem**

*ReamItem is optional because of choice construct.*

A wrapped quantity of SheetItem(s).

### **SheetItem**

*SheetItem is optional because of choice construct.*

A group item consisting potentially of the date the sheets were converted into sheets and/or packaged or finished.

### **UnitItem**

*UnitItem is optional because of choice construct.*

Unit Item.

### **WoodItem**

*WoodItem is optional because of choice construct.*

Group element containing elements describing a wood industry product.

## OtherDate

*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## e-Attachment

*e-Attachment is optional. A single instance might exist.*

e-Attachment enables the sender to provide information about attachments to the document.

Note: BizTalk users may have problems in processing this element. See the papiNet FAQs (papiNet.org) for more information.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## PackageReference

*PackageReference is optional. Multiple instances might exist.*

An element detailing the relevant references pertaining to a package. The type of reference is identified by the attributes PackageReferenceType and AssignedBy.

---

## PackageLevel [attribute]


An hierarchical numbering approach that communicates containerization and identity.



---

## PackageMeasuringInfo

A grouping element that contains information about a measured package or a measured load when the load is treated as one package.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### ItemInfo

*ItemInfo is mandatory. A single instance is required.*

A grouping element that contains information about an item. The attribute ItemType defines the type of physical item. Item Info describes property values of an item as well as tracking information between items processed in the supply chain.

### ProductPercentage

*ProductPercentage is optional. Multiple instances might exist.*

The quantity of a product in percentage of the total quantity for an item containing

many products.

---

## PackageName


Element used to identify the name of a package.

<b>PackageName</b>	
type	s72

---

## PackageReference

An element detailing the relevant references pertaining to a package. The type of reference is identified by the attributes PackageReferenceType and AssignedBy.



### PackageReferenceType [attribute]

*PackageReferenceType is mandatory. A single instance is required.*

PackageReferenceType provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Customer", "Seller", and/or "Supplier". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to PackageReferenceType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*


Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## PackageReferenceType [attribute]

PackageReferenceType provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Customer", "Seller", and/or "Supplier". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.



Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## PackagesPerWrap

The number of packages wrapped together.

<b>PackagesPerWrap</b>	
type	nni2

## PackageType [attribute]

Communicates the configuration of the item being reported.

*This item is restricted to the following list.*

attribute	
<b>PackageType</b>	
type	packageType

### **Bag**

A container of flexible material used for storage.

### **Bale**

Unbound materials bulk packed without pieces of board and at least 1 band

### **Barrel**

A large cylindrical container.

### **Box**

Note: Box is the papiNet way of referring to a Carton

### **Bundle**

Unbound materials bulk packed with pieces of board at each end and at least 1 band

### **Container**

### **Crate**

A shipping container used for storage.

### **Drum**

### **FullWoodPackage**

### **HalfWoodPackage**

### **LengthPackage**

Package contains pieces of a single length.

### **Lift**

### **LogPile**

A pile of logs (a virtual type of package).

### **LooseVolumeItem**

A unit containing loose volume products (during transports) (a type of virtual package).

### **Pail**

### **Pallet**

A portable platform.

**Piece**

**PulpUnit**

**ReelPackage**

**StepPackage**

Package in which pieces are group together by length, with longest length at the bottom of the package and shortest on top.

**TruckPackage**

Package contains pieces of mixed random lengths.

**UnformedPulp**

**Vehicle**

---

## PackageType

Communicates the configuration of the item being reported.

PackageType
type   packageType

*This item is restricted to the following list.*

**Bag**

A container of flexible material used for storage.

**Bale**

Unbound materials bulk packed without pieces of board and at least 1 band

**Barrel**

A large cylindrical container.

**Box**

Note: Box is the papiNet way of referring to a Carton

**Bundle**

Unbound materials bulk packed with pieces of board at each end and at least 1 band

**Container**

**Crate**

A shipping container used for storage.

**Drum**

**FullWoodPackage**

**HalfWoodPackage**

**LengthPackage**

Package contains pieces of a single length.

**Lift**

**LogPile**

A pile of logs (a virtual type of package).

**Pail**

**Pallet**

A portable platform.

**Piece**

**PulpUnit**

**ReelPackage**

**StepPackage**

Package in which pieces are group together by length, with longest length at the bottom of the package and shortest on top.

**TruckPackage**

Package contains pieces of mixed random lengths.


**UnformedPulp**

**Vehicle**

## Packaging

Type of a package that includes individual products.

**(sequence)**



*The sequence of items below is mandatory. A single instance is required.*


**ProductPackaging**

*ProductPackaging is mandatory. A single instance is required.*

Defines the methods and materials used for packaging.

## PackagingCharacteristics

An element containing carton or pallet packing information. PackagingCharacteristics can either have the BoxCharacteristics or



PalletPackagingCharacteristics element not both.

**IsBoxed [attribute]**

*IsBoxed is optional. A single instance might exist.*

Refer to IsBoxed definition for any enumerations.

## **IsPalletized [attribute]**

*IsPalletized is optional. A single instance might exist.*

The buyer's directions for how the item is to be palletized.

Refer to IsPalletized definition for any enumerations.

## **(choice)**

*[choice] is optional because of choice construct.*

### **BoxCharacteristics**

*BoxCharacteristics is optional because of choice construct.*

BoxCharacteristics is a group element that contains information about the box (or carton)

### **PalletPackagingCharacteristics**

*PalletPackagingCharacteristics is optional because of choice construct.*

PalletPackagingCharacteristics details the characteristics of the packaging for a pallet.

### **BookUnitPacking**

*BookUnitPacking is optional because of choice construct.*

Book unit packing information

### **DocumentInformation**

*DocumentInformation is optional. Multiple instances might exist.*

A group element containing a specification of required documents in the business process. Additional free text to be printed on documents can also be specified.

---

## **PackagingCode**

PackagingCode is a code describing the packaging of the product.

### **Agency [attribute]**


*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.




---

## PackagingCodeSpecification

A grouping element specifying code and description for packaging details.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### PackagingCode

*PackagingCode mandatory. A single instance is required.*

PackagingCode is a code describing the packaging of the product.

### PackagingDescription

*PackagingDescription is optional. Multiple instances might exist.*

A text field element describing the packaging of a product A text field element describing the packaging of a product.


---

## PackagingDescription

A text field element describing the packaging of a product.

### Language [attribute]

*Language is optional. A single instance might exist.*



XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

## PackagingInformation

Group element construct used to all information associated with the packaging of a product. Measurements, package ID, label, stencil, band, pallet and wrap characteristics may all be detailed.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### QuantityInUnit

*QuantityInUnit is optional. A single instance might exist.*

Used to identify the number of items packed within this package unit.



(sequence)

#### UnitDimension

*UnitDimension is optional. A single instance might exist.*

Unit Dimension

#### Weight

*Weight is optional. A single instance might exist.*

The weight of the item.

#### PackageIDInformation

*PackageIDInformation is optional. A single instance might exist.*

Group element identifying a lumber (wood) package. The package name may also be communicated.

#### LabelCharacteristics

*LabelCharacteristics is optional. Multiple instances might exist.*

A group item that organises the labeling information.

#### StencilCharacteristics

*StencilCharacteristics is optional. Multiple instances might exist.*

A group element specifying attributes of a stencil to be applied to an item, and optional text.

#### BandCharacteristics


*BandCharacteristics is optional. Multiple instances might exist.*

A group item that organises the packaging band detail information.

#### PalletCharacteristics

*PalletCharacteristics is optional. Multiple instances might exist.*

A group item that provides pallet detail information.



## Wrap

*Wrap is optional. Multiple instances might exist.*

A group item that organises wrapping detail information.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## PackageType

*PackageType is optional. A single instance might exist.*

Communicates the configuration of the item being reported.

Refer to PackageType definition for any enumerations.

## PackingList

The PackingList element is the root element for the PackingList e-Document.

The PackingList e-Document specifies the details of a shipment that is being despatched. The seller should send the PackingList e-Document in sufficient time so that the recipient can process the information before the goods arrive. The recipient can then prepare efficiently for the receipt of the goods.

### **PackingListStatusType [attribute]**

*PackingListStatusType is mandatory. A single instance is required.*

Attribute is used to identify the PackingList status.

Refer to PackingListStatusType definition for any enumerations.

### **Reissued [attribute]**

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.


### **Language [attribute]**

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

### **(sequence)**



*The sequence of items below is mandatory. A single instance is required.*

## **PackingListHeader**

*PackingListHeader is mandatory. A single instance is required.*

Information that is applicable to every item on the PackingList e-Document.

## **PackingUnit**

*PackingUnit is mandatory. One instance is required, multiple instances might exist.*

Describes the major unit of packing the materials in the shipment.

## **PackingListSummary**

*PackingListSummary is optional. A single instance might exist.*

PackingListSummary contains summary information applicable to the entire PackingList.


---

## **PackingListDate**

Used to identify the issue date of the PackingList transaction.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### **Date**

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### **Time**

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## PackingListHeader

Information that is applicable to every item on the PackingList e-Document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PackingListNumber

*PackingListNumber is mandatory. A single instance is required.*

The PackingList identifying number.

#### TransactionHistoryNumber

*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where

TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

#### PackingListDate

*PackingListDate is mandatory. A single instance is required.*

Used to identify the issue date of the PackingList transaction.

#### PackingListReference

*PackingListReference is optional. Multiple instances might exist.*

Element used to identify any external or associated documents, identifiers, etc.

#### BuyerParty

*BuyerParty is mandatory. A single instance is required.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

#### BillToParty


*BillToParty is optional. A single instance might exist.*

The address where the invoice is to be sent.

#### SupplierParty

*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.



## **CarrierParty**

*CarrierParty is optional. A single instance might exist.*

The party performing the transport of the product from the pickup location to the ship-to location; could be a hauler.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **ShipToCharacteristics**

*ShipToCharacteristics is mandatory. A single instance is required.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **EstimatedArrivalDate**

*EstimatedArrivalDate is optional. A single instance might exist.*

An estimation of the arrival date.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*


A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## PackingListItem

The required element PackingListItem refers to one and only one PurchaseOrder and one and only one PurchaseOrderLineItem of that PurchaseOrder.

### PackingListItemType [attribute]

*PackingListItemType is mandatory. A single instance is required.*



This attribute is used to identify the type of package configuration the item is. To help with physical identification.

Refer to PackingListItemType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PackingListItemNumber

*PackingListItemNumber is mandatory. A single instance is required.*

Used to uniquely identify this item within the PackingList.

#### Identifier

*Identifier is optional. Multiple instances might exist.*

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.

#### PurchaseOrderInformation

*PurchaseOrderInformation is mandatory. A single instance is required.*


A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

#### PurchaseOrderLineItemNumber

*PurchaseOrderLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the PurchaseOrder line item.

#### PackingListReference



# papiNet V2R31

---

*PackingListReference is optional. Multiple instances might exist.*

Element used to identify any external or associated documents, identifiers, etc.

## **Product**

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **Quantity**

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **BestBeforeDate**

*BestBeforeDate is optional. A single instance might exist.*

The date, prior to which, the product is suggested to be used.

## **NumberOfMillJoins**

*NumberOfMillJoins is optional. A single instance might exist.*

The number of joins in the reel.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **PackingListItemNumber**

Used to uniquely identify this item within the PackingList.

<b>PackingListItemNumber</b>
type   lineNumberType

---

## PackingListItemType [attribute]

This attribute is used to identify the type of package configuration the item is. To help with physical identification.

*This item is restricted to the following list.*

- Box**
- Ream**
- Reel**
- Sheet**
- Other**



---

## PackingListNumber

The PackingList identifying number.




---

## PackingListReference

Element used to identify any external or associated documents, identifiers, etc.

### PackingListReferenceType [attribute]

*PackingListReferenceType is mandatory. A single instance is required.*



Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to PackingListReferenceType definition for any enumerations.

### AssignedBy [attribute]


*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

## PackingListReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.



Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## PackingListStatusType [attribute]

Attribute is used to identify the PackingList status.

*This item is restricted to the following list.*



### Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### Original

The supplied information is the first version of that information.

### Replaced


The supplied information is replacing earlier supplied information. The receiver should revalidate the information in their system based upon the entire information received.

## PackingListSummary

PackingListSummary contains summary information applicable to the entire PackingList.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



## **TotalNumberOfPackingListPackingUnits**

*TotalNumberOfPackingListPackingUnits is optional. A single instance might exist.*

TotalNumberOfPackingListPackingUnits

## **TotalNumberOfPackingListItems**

*TotalNumberOfPackingListItems is optional. A single instance might exist.*

Total Number Of PackingList Items

### **(sequence)**

*The sequence of items below is optional. Multiple instances might exist.*

### **TotalQuantity**

*TotalQuantity is mandatory. A single instance is required.*

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

### **TotalInformationalQuantity**

*TotalInformationalQuantity is optional. Multiple instances might exist.*

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

## **TermsAndDisclaimers**

*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.

## PackingUnit

Describes the major unit of packing the materials in the shipment.

### PackingUnitType [attribute]

*PackingUnitType is mandatory. A single instance is required.*

Attribute used to identify the type of this packing unit.

Refer to PackingUnitType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### PackingUnitSerialNumber

*PackingUnitSerialNumber is mandatory. A single instance is required.*

The serial number of the packing unit.

### Identifier

*Identifier is mandatory. One instance is required, multiple instances might exist.*

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.

### PackingUnitMeasurements

*PackingUnitMeasurements is optional. A single instance might exist.*

A group element construct detailing the measurements, height, weight, and length, of the specified packing unit.

### PackingListReference

*PackingListReference is optional. Multiple instances might exist.*


Element used to identify any external or associated documents, identifiers, etc.

### Quantity

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.



## InformationalQuantity

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## PackingListItem

*PackingListItem is mandatory. One instance is required, multiple instances might exist.*

The required element PackingListItem refers to one and only one PurchaseOrder and one and only one PurchaseOrderLineItem of that PurchaseOrder.

## NumberOfPackingListItems

*NumberOfPackingListItems is mandatory. A single instance is required.*


The number of PackingList items in a PackingUnit of the PackingList.

## PackingUnitMeasurements

A group element construct detailing the measurements, height, weight, and length, of the specified packing unit.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Height

*Height is optional. A single instance might exist.*

The height of the object.

### Width

*Width is optional. A single instance might exist.*

The width of the object.


### Length

*Length is optional. A single instance might exist.*

The length of the object.

## PackingUnitSerialNumber

The serial number of the packing unit.



---

## PackingUnitType [attribute]

Attribute used to identify the type of this packing unit.

*This item is restricted to the following list.*

**Container**

**Pallet**

**Stack**

**Other**

attribute	
<b>PackingUnitType</b>	
type	packingUnitType

---

## PagesPerSet

Pages per Set

<b>PagesPerSet</b>	
type	nni4

---

## PagesPerSignature

Pages per signature

<b>PagesPerSignature</b>	
type	nni4

---

## Pagination

Number of pages that make up a book.

<b>Pagination</b>	
type	s30

---

## PalletAdditionsType [attribute]

Gives additional characteristics of the pallet

*This item is restricted to the following list.*

**FullPerimeter**

The pallet has a full perimeter.

**FungicideTreatment**

The pallet wood has received a fungicide treatment.

**LongSlats**

The pallet has long slats.

**NoBlockOffset**

The pallet is a no-block offset.

**Reinforced**

The pallet is reinforced.

**TrimmedEdges**

attribute	
<b>PalletAdditionsType</b>	
type	palletAdditionsType

The pallet has trimmed edges

## PalletCharacteristics

A group item that provides pallet detail information.

### MixedProductPalletIndicator [attribute]

*MixedProductPalletIndicator is optional. A single instance might exist.*

Specifies whether a product can be mixed with other products on the same pallet

Refer to MixedProductPalletIndicator definition for any enumerations.

### PalletType [attribute]

*PalletType is optional. A single instance might exist.*

Details the type of pallet that can be used These pallets are common in the industry

Refer to PalletType definition for any enumerations.

### PalletLedgeType [attribute]

*PalletLedgeType is optional. A single instance might exist.*

Details the type of pallet ledges that can be used

Refer to PalletLedgeType definition for any enumerations.

### PalletCoverType [attribute]

*PalletCoverType is optional. A single instance might exist.*

Details the type of cover that can be used on top of the pallet body

Refer to PalletCoverType definition for any enumerations.



### PalletAdditionsType [attribute]

*PalletAdditionsType is optional. A single instance might exist.*

Gives additional characteristics of the pallet

Refer to PalletAdditionsType definition for any enumerations.

### PalletTopType [attribute]



*PalletTopType is optional. A single instance might exist.*

Details the type of pallet top that can be used

Refer to PalletTopType definition for any enumerations.

## **IsPartialPalletsAllowed [attribute]**

*IsPartialPalletsAllowed is optional. A single instance might exist.*

Indicates if partial pallets are allowed or not.

*This item is restricted to the following list.*

Refer to IsPartialPalletsAllowed definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **ProductIdentification**

*ProductIdentification is optional. A single instance might exist.*

A grouping element designed to communicate product identification related to the parent element that contains this item.

### **PalletLength**

*PalletLength is optional. A single instance might exist.*

The measurement value of the length of the pallet.

### **PalletWidth**

*PalletWidth is optional. A single instance might exist.*

The measurement value of the width of the pallet.

### **ItemsPerPallet**

*ItemsPerPallet is optional. A single instance might exist.*

The number of items on the pallet (either reels or sheet or sheet-package).

### **StacksPerPallet**

*StacksPerPallet is optional. A single instance might exist.*

The number of stacks on a pallet, where a stack is a vertical arrangement of items (looking down from above).

### **TiersPerPallet**

*TiersPerPallet is optional. A single instance might exist.*

The number of tiers on the pallet, where a tier is a layer of items.

### **MaximumHeight**

*MaximumHeight is optional. A single instance might exist.*

The maximum height allowed including the pallet.

### **StackingMethod**

*StackingMethod is optional. A single instance might exist.*

A text field describing the pattern used when stacking of pallets.

### **LabelCharacteristics**

*LabelCharacteristics is optional. A single instance might exist.*

A group item that organises the labeling information.

## ItemsPerTier

*ItemsPerTier is optional. A single instance might exist.*

Number of items on each full tier, e.g. number of boxes, gaylords, loose books etc. on a tier on a pallet.

---

## PalletCoverType [attribute]

Details the type of cover that can be used on top of the pallet body

*This item is restricted to the following list.*

attribute
<b>PalletCoverType</b>
type palletCoverType

### **MetalPlateWithPE**

A metal plate covers the pallet with polyethylene on top.

### **WithoutPE**

The pallet cover is without polyethylene on top.

### **WithPE**

The pallet cover is with polyethylene on top.

### **WithPEUnderCover**

The pallet cover is with polyethylene under the wooden plates.

### **WoodStripWithPE**

The pallet cover is made up from a wood strip with polyethylene on top

### **WoodStripWithoutPE**

The pallet cover is made up from a wood strip without polyethylene on top.

---

## PalletLedgeType [attribute]

Details the type of pallet ledges that can be used

*This item is restricted to the following list.*

attribute
<b>PalletLedgeType</b>
type palletLedgeType

### **LongWay**

The ledge wood is on the long side of the pallet.

### **LongWayWithBelt**

The ledge wood is on the long side of the pallet, with a packaging belt.

### **ShortWay**

The ledge wood is on the short side of the pallet.

### **ShortWayWithBelt**

The ledge wood is on the short side of the pallet, with a packaging belt

## PalletLength

The measurement value of the length of the pallet.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### Value

Value is mandatory. A single instance is required.

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


RangeMin is optional. A single instance might exist.

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

RangeMax is optional. A single instance might exist.

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## PalletPackagingCharacteristics

PalletPackagingCharacteristics details the characteristics of the packaging for a pallet.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### PackagingCode

PackagingCode is optional. A single instance might exist.

PackagingCode is a code describing the packaging of the product.

#### PackagingDescription


PackagingDescription is optional. A single instance might exist.

A text field element describing the packaging of a product.

#### WrapCharacteristics

WrapCharacteristics is optional. A single instance might exist.

A group element that contains elements that describe



the manner in which the item is wrapped.

## **PalletCharacteristics**

*PalletCharacteristics is optional. A single instance might exist.*

A group item that provides pallet detail information.

## **BandCharacteristics**

*BandCharacteristics is optional. A single instance might exist.*

A group item that organises the packaging band detail information.

## **LabelCharacteristics**

*LabelCharacteristics is optional. Multiple instances might exist.*

A group item that organises the labeling information.

## **StencilCharacteristics**

*StencilCharacteristics is optional. Multiple instances might exist.*

A group element specifying attributes of a stencil to be applied to an item, and optional text.

## **MaximumHeight**

*MaximumHeight is optional. A single instance might exist.*

The maximum height allowed including the pallet.

## **MaximumGrossWeight**

*MaximumGrossWeight is optional. A single instance might exist.*

The maximum weight allowed including the pallet.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **PalletTopType [attribute]**

Details the type of pallet top that can be used

*This item is restricted to the following list.*

### **CartonboardCover**

The pallet top is composed of carton-board

### **Chipboard**

The pallet top is composed of chipboard.


### **Corrugated**

The pallet top is composed of corrugated board.

### **EdgeProtection**

The pallet top has edge protections for the sheets of paper placed on top. They are placed on the top pallet edges.

### **FiveStripsOfWood**



# papiNet V2R31

---

The pallet top is composed of five strips of wood.

## **FullyCoverThreeCrossBoards**

The pallet top is composed of a fully wooden cover with three cross ledges on top.

## **FungicTreatWoodFrame**

The pallet top is composed of a wooden frame, which is treated with fungicide.

## **OneStripOfWood**

The pallet top is composed of one strip of wood.

## **PlywoodCover**

The pallet top is composed of plywood.

## **TwoStripsOfWood**

The pallet top is composed of two strips of wood.

## **ThreeStripsOfWood**

The pallet top is composed of three strips of wood.

## **WoodenFrame**

The pallet top is composed of a wooden frame

---

## **PalletType [attribute]**

Details the type of pallet that can be used These pallets are common in the industry

*This item is restricted to the following list.*

### **Euro**

The pallet is the standardized Euro pallet type.

### **Export**

The pallet is the standardized export pallet type.

### **ISPM15Treated**

Specifies that wood pallet must be treated or fumigated according to the ISPM 15 regulation.

### **NonPalletised**


The product is not on a pallet.

### **NonStop**

The pallet is the standardized non-stop pallet type.

### **Twinned**

Two pallets have been joined together



---

## PalletWidth

The measurement value of the width of the pallet.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



---

## Paper

A group item defining the characteristics of the paper product.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PaperCharacteristics

*PaperCharacteristics is optional. A single instance might exist.*

The identifying characteristics of paper most important to the ordering of the item. These are the characteristics that, when associated with a given grade, allow the manufacturer to produce but not convert or package, the paper.

### (choice)

*[choice] is optional because of choice construct.*

#### Reel


*Reel is optional because of choice construct.*

A group item that contains the conversion and packaging characteristics of a reel.

#### Sheet

*Sheet is optional because of choice construct.*

A group item that contains the conversion and packaging characteristics for sheets.



## PaperCharacteristics

The identifying characteristics of paper most important to the ordering of the item. These are the characteristics that, when associated with a given grade, allow the manufacturer to produce but not convert or package, the paper.

### CoatingTop [attribute]

*CoatingTop is optional. A single instance might exist.*

Used to specify the type of coating applied to the top or bottom of the paper sheet

Refer to CoatingTop definition for any enumerations.

### CoatingBottom [attribute]

*CoatingBottom is optional. A single instance might exist.*

Used to specify the type of coating applied to the top or bottom of the paper sheet

Refer to CoatingBottom definition for any enumerations.

### FinishType [attribute]

*FinishType is optional. A single instance might exist.*

Defines the finish of a sheet of paper, which means the condition of its surface (refer to Embossing for more information).

Finishes may be produced on or off machine. Finishes that are created off-machine are called embossed. (Embossing is a child element of ReelConversionCharacteristics and SheetConversionCharacteristics.)

Note:

Embossed" as a finish type is just a generalized choice for one of the more specific choices listed.

Unsupercalendered" as a finish type would be indicated by not communicating a finish type.

Refer to FinishType definition for any enumerations.

### PrintType [attribute]

*PrintType is optional. A single instance might exist.*

Refer to PrintType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Abrasion

*Abrasion is optional. Multiple instances might exist.*

A group item used to communicate abrasion loss target or test value.

#### AbsorptionInk

*AbsorptionInk is optional. Multiple instances might exist.*

A group item used to communicate ink absorption target or test value.

#### AbsorptionLight



*AbsorptionLight is optional. Multiple instances might exist.*

A group item used to communicate light absorption target or test value.

## **AbsorptionWater**

*AbsorptionWater is optional. Multiple instances might exist.*

A group item used to communicate water absorption target or test value.

## **Appearance**

*Appearance is optional. Multiple instances might exist.*

A group item used to communicate appearance.

## **Ash**

*Ash is optional. Multiple instances might exist.*

A group item used to communicate the ash content of the product according to a particular TestMethod.

## **BasisWeight**

*BasisWeight is optional. Multiple instances might exist.*

The weight of the paper expressed as a mass for a given surface area. In countries using the metric system, the basis weight is expressed as the weight in grams of one sheet of paper that is one square meter in area—not dependent on basic sheet size. In countries using the imperial system, the weight is expressed in pounds for a given ProductBasisSizeType.

## **BendingResistance**

*BendingResistance is optional. Multiple instances might exist.*

Bending resistance

## **BendingStiffness**

*BendingStiffness is optional. Multiple instances might exist.*

BendingStiffness

## **Brightness**

*Brightness is optional. Multiple instances might exist.*

A measurement of the degree of light reflectivity of the product.

## **Bulk**

*Bulk is optional. Multiple instances might exist.*

A group item used to communicate bulking thickness target or test value.

## **Burst**

*Burst is optional. Multiple instances might exist.*

A group item used to communicate bursting strength target or test value according to a particular TestMethod.

## **BurstIndex**

*BurstIndex is optional. Multiple instances might exist.*

The burst index.

## **Caliper**

*Caliper is optional. Multiple instances might exist.*

The thickness of a sheet of paper under standard test conditions.

## **CoatWeight**

*CoatWeight is optional. Multiple instances might exist.*

A group item used to communicate the coating thickness target or test value according to a particular TestMethod.

## **ColourDetail**

*ColourDetail is optional. Multiple instances might exist.*

A group item used to communicate details of colour according to the selected colour definition scheme.

## **Density**

*Density is optional. Multiple instances might exist.*

A group item used to communicate density target or test value according to a particular TestMethod.

## **Dirt**

*Dirt is optional. Multiple instances might exist.*

A group item used to communicate dirt content target or test value according to a particular TestMethod.

## **DominantWavelength**

*DominantWavelength is optional. Multiple instances might exist.*

Dominant wavelength

## **ExcitationPurity**

*ExcitationPurity is optional. Multiple instances might exist.*

Excitation purity

## **FibreLength**

*FibreLength is optional. Multiple instances might exist.*

A group item used to communicate fibre length target or test value according to a particular TestMethod.

## **FibreClassification**

*FibreClassification is optional. Multiple instances might exist.*

A group item used to communicate fibre classification according to the specified classification scheme.

## **Folding**

*Folding is optional. Multiple instances might exist.*

A group item used to communicate folding endurance target or test value according to a particular TestMethod.

## **Formation**

*Formation is optional. Multiple instances might exist.*

A group item used to communicate sheet formation target or test value according to a particular TestMethod.

## **Freeness**

*Freeness is optional. Multiple instances might exist.*

Freeness

## **Friction**

*Friction is optional. Multiple instances might exist.*

A group item used to communicate static and kinetic friction target or test value according to a particular TestMethod.

## **Gloss**

*Gloss is optional. Multiple instances might exist.*

A group item used to communicate specular gloss target or test value according to a particular TestMethod.

## **LightScattering**

*LightScattering is optional. Multiple instances might exist.*

A group item used to communicate light scattering coefficients according to a particular TestMethod.

## **Luminance**

*Luminance is optional. Multiple instances might exist.*

Luminance

## **Moisture**

*Moisture is optional. Multiple instances might exist.*

Desired percentage, or other indicator, of water in the product at the time of shipment.

## **Mullen**

*Mullen is optional. Multiple instances might exist.*

Mullen, also called "burst strength", is the amount of pressure required to rupture paper or linerboard when applied to its surface. The unit of measure is KiloPascal (sometimes abbreviated as "kPa").

## **Opacity**

*Opacity is optional. Multiple instances might exist.*

A group item used to communicate opacity target or test value according to a particular TestMethod.

## **Permeability**

*Permeability is optional. Multiple instances might exist.*

A group item used to communicate air permeability target or test value according to a particular TestMethod.

## **pH**

*pH is optional. Multiple instances might exist.*

A group item used to communicate pH (degree of acidity versus basicity) target or test value according to a particular TestMethod.

## **PlyBond**

*PlyBond is optional. Multiple instances might exist.*

A group item used to communicate internal bond strength target or test value between plies according to a particular TestMethod.

## **Porosity**

*Porosity is optional. Multiple instances might exist.*

A group item used to communicate a permeability target or test value.

## **PostConsumerWaste**

*PostConsumerWaste is optional. Multiple instances might exist.*

A group item used to communicate the target or test value percentage of post consumer waste fibre in the product according to a particular TestMethod.

## **PPI**

*PPI is optional. Multiple instances might exist.*

A group item used to communicate the number of pages in an inch of thickness either as a target or actual value. Equal to the number of sheets per inch times 2.

## **PreConsumerWaste**

*PreConsumerWaste is optional. Multiple instances might exist.*

A group item used to communicate the target or test value percentage of pre-consumer waste fibre in the product according to a particular TestMethod.

## **Recycled**

*Recycled is optional. Multiple instances might exist.*

A group item used to communicate the target or test value total percentage of waste fibre in the product according to a particular TestMethod.

## **Resistance**

*Resistance is optional. Multiple instances might exist.*

A group item used to communicate air resistance target or test value according to a particular TestMethod.

## **RingCrush**

*RingCrush is optional. Multiple instances might exist.*

Ring Crush

## **Roughness**

*Roughness is optional. Multiple instances might exist.*

A group item used to communicate surface roughness target or test value according to a particular TestMethod.

## **RunnabilityIndex**

*RunnabilityIndex is optional. Multiple instances might exist.*

A group item used to communicate the calculated run-ability index target or test value.

## **ShowThrough**

*ShowThrough is optional. Multiple instances might exist.*

Show through

## **Sizing**

*Sizing is optional. Multiple instances might exist.*

A group item used to communicate size test of paper by ink resistance target or test value.

## **Smoothness**

*Smoothness is optional. Multiple instances might exist.*

A group item used to communicate surface smoothness target or test value according to a particular TestMethod.

## **Stiffness**

*Stiffness is optional. Multiple instances might exist.*

A group item used to communicate stiffness target or test value.

## **Stretch**

*Stretch is optional. Multiple instances might exist.*

A group item used to communicate stretch target or test value.

## **SurfaceStrength**

*SurfaceStrength is optional. Multiple instances might exist.*

Surface Strength

## **TEA**

*TEA is optional. Multiple instances might exist.*

Tensile Energy Absorption.

## **Tear**

*Tear is optional. Multiple instances might exist.*

A group item used to communicate tearing resistance target or test value according to a particular TestMethod.

## **TearIndex**

*TearIndex is optional. Multiple instances might exist.*

TearIndex

## **Tensile**

*Tensile is optional. Multiple instances might exist.*

A group item used to communicate zero-span tensile strength target or test value according to a particular TestMethod.

## **TensileIndex**

*TensileIndex is optional. Multiple instances might exist.*

Tensile Index

## **Whiteness**

*Whiteness is optional. Multiple instances might exist.*

A group item used to communicate degree of whiteness target or test value according to a particular TestMethod.

## **AdditionalTest**

*AdditionalTest is optional. A single instance might exist.*

AdditionalTest exists to enable the inclusion of a test that has not been identified by papiNet.org. It is always a single-instance element so it is very important that users, who come upon a test that papiNet.org has not identified, communicate the need for this test to us at [www.papiNet.org](http://www.papiNet.org).

## **NumberOfPlies**

*NumberOfPlies is optional. Multiple instances might exist.*

The number of layers of paper product joined together to make the final saleable product.

## **PlyAttributes**

*PlyAttributes is optional. Multiple instances might exist.*

The characteristics of the plies of paper or tissue. Manufacturing data relevant to each ply that constitutes the final product

## **PlySet**

*PlySet is optional. Multiple instances might exist.*

PlySet.

---

## **PaperSizeType**

A field that defines the sheet size using the DIN standard (DINA4, DINA3, and so on).

<b>PaperSizeType</b>	
type	s20

---

## **PartyIdentifier**

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

### **PartyIdentifierType [attribute]**

*PartyIdentifierType is mandatory. A single instance is required.*

<b>PartyIdentifier</b>	
type	s60

attributes	
<b>PartyIdentifierType</b>	
type	partyIdentifierType
<b>Agency</b>	
type	agencyCode

Provides a contextual definition for the party identifier value. This party identifier enables the trading partners to use ID codes for the different organisation versus business entities involved in the transaction.

Refer to PartyIdentifierType definition for any enumerations.

### **Agency [attribute]**

*Agency is optional. A single instance might exist.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

---

## **PartyIdentifierType [attribute]**

Provides a contextual definition for the party identifier value. This party identifier enables the trading partners to use ID codes for the different organisation versus business entities involved in the transaction.

attribute	
<b>PartyIdentifierType</b>	
type	partyIdentifierType

*This item is restricted to the following list.*

**ABINumber**

Associazione Bancaria Italiana – Identifies the bank as an entity in Italy.

**ABNNumber**

The Australian Business Number (ABN) is a single identifier for dealings with the Australian Taxation Office (ATO). The Australian Business Register assigns it.

**AFPA**

American Forest and Paper Association identifier.

**AssignedByAgency**

A unique identifier for the party in question that has been assigned by the agency given in the attribute Agency for the PartyIdentifier. Attribute Agency is mandatory when party identifier type AssignedByAgency is used.

**AssignedByBuyer**

A unique identifier for the party in question that has been assigned by the buyer (for example, a seller's code).

**AssignedByReceiver**

A unique identifier for the party in question that has been assigned by the receiver of the e-Document.

**AssignedBySeller**

A unique identifier for the party in question that has been assigned by the seller (for example, account number for the buyer).

**AssignedBySender**

A unique identifier for the party in question that has been assigned by the sender of the e-Document.

**BankIdentificationCode**

A unique country-specific code to identify a bank organisation for electronic transaction. Used to specify the bank routing information needed for electronic remittance. This information is used with the RemitToParty information to effect payment. Examples include:

ACH Number in the United States

Sort Code in the UK

Bankleitzahl in Germany

Code banque/agence in France

BankIdentificationCode should not be mixed up with Bank Identifier Code (BIC). Bank Identifier Code (BIC) is an international standard for identifying Financial Institutions. Please see enumeration SWIFT for more information about BIC.

**BankgiroAccountNumber**

Defines an account number in the bankgiro system for domestic payments in Sweden. See <http://www.bankgirot.se/> for more information.

**CABNumber**

Codice Avviamento Bancario – Identifies which branch of the bank in Italy.

**ChamberOfCommerceRegistrationNumber**

C.C.I.A.A. Number in Italy.

## **Domicile**

Domicile

## **DunsNumber**

A 9-digit identifier maintained by Dun & Bradstreet to uniquely identify a commercial enterprise.

## **Duns4Number**

Similar to the DunsNumber that defines a parent company/organization. The additional 4 digits enable the definition/identification of a sub-entity, such as a mill/plant of this parent company/organisation.

## **EANNumber**

To be deprecated in the next version. Use GlobalLocationNumber instead.

## **EORI Number**

An Economic Operators Registration and Identification Number. This unique identifier for economic operators within European Community must be communicated to customs authorities within European Community as well as to customers. Mandatory since 26 February 2009 for all communication within customs offices. For more information please see

[http://ec.europa.eu/taxation\\_customs/resources/documents/customs/policy\\_issues/e-customs\\_initiative/it\\_projects/TAXUD1633\(2008\)\\_rev19\\_en.pdf](http://ec.europa.eu/taxation_customs/resources/documents/customs/policy_issues/e-customs_initiative/it_projects/TAXUD1633(2008)_rev19_en.pdf)

## **GlobalLocationNumber**

The globally unique EAN-UCC System identification number for legal entities, functional entities and physical locations. The Global Location Number uses the EAN/UCC-13 Data Structure. Details about the structure and usage are available at the <http://www.gs1.org> website.

## **IBAN**

International Banking Account Number. For payments emanating from and destined for abroad, the European banks (ECBS) have agreed to structure bank accounts in a uniform way.

This uniform structure of the account number is known as IBAN (International Bank Account Number). An IBAN consists of the code of the country where the account is held, 2 numeric check digits and a national account number (your traditional account number).

## **ISO6523Number**

This partyidentifier type is defined by ISO 6523, Structure for the Identification of Organizations, which defines the standard for a code to be used for party identification in electronic data interchange. The code is globally unique, because of the used structure. The structure of the identifier is, using xxxx99999999(NNNNN) as the example:

xxxx The International Code Designator (ICD-code) is a fixed-length code of four digits that identifies the authority issuing the ISO 6523 organization code; e.g. 0037 is the ICD-code (International Code Designator) for National Board of Taxes in Finland.

99999999 The organization code consists of up to 14 characters. The Code

# papiNet V2R31

---

Designator (defined by ICD-code) defines the use of the organization code. The used code can be an existing code or, the code designator assigns the code to companies based on request. The Code Designator makes sure that the codes in their list are unique.

(NNNNN) Optional variable length information, to further identify the organization. The use of this is part defined by the code designator.

## **papiNetGlobalPartyIdentifier**

A readily available and free identifier supported by IANA (the Internet Assigned Numbers Authority). Private Enterprise Numbers that conforms to proper URI naming conventions are available, free-of-charge from the Internet Assigned Numbers Authority (IANA). The application form is available at the <http://www.iana.org/cgi-bin/enterprise.pl> website. papiNet will be developing a broader recommendation for party naming in the future however, obtaining an IANA Private Enterprise Number (PEN) will permit globally unique trading partner identification.

## **PatenteNumber**

A unique four-digit assigned to each Mexican Freight broker.

## **PayeeAccountNumber**

Defines the bank account number of the party receiving payment.

## **PayeeInternalAccountNumber**

The company's internal bank which is used to settle payments between internal units. It's not the bank account.

## **PayeeFinancialInstitution**

The designation of the financial institution of the party receiving the payment.

## **PayerAccountNumber**

Defines the bank account number of the party responsible for making the payment.

## **PayerFinancialInstitution**

The designation of the financial institution of the party responsible for making the payment.

## **PlusgiroAccountNumber**

Defines an account number in the plusgiro system for domestic payments in Sweden. See [www.plusgirot.se](http://www.plusgirot.se) for more information.

## **RegisterOfCompaniesSubscriptionNumber**

Iscrizione al Reg. Imprese Nr. In Italy.

## **StandardAddressNumber**

A 7-digit code to uniquely identify an organisation and its location. The number consists of 6 digits with an 11-modulus check digit as the seventh digit. ISAN is the same with the ISO Country code as a prefix. This identifier is solely used by the book industry.

## **StandardCarrierAlphaCode**

A 4-character code identifying a trucking company. The Washington National Motor Freight Association maintains these codes in the United States.

## **StockCapital**

Capitale Sociale in Italy.

## **SWIFT**

SWIFT also refer to as Bank Identifier Code (BIC) is an international standard for identifying Financial Institutions.

The Bank Identifier Code (BIC) developed by SWIFT is adopted by the International Organization for Standardization (ISO). ISO has appointed SWIFT as the registration authority for the assignment of BICs (ISO 9362) and for the publication of BICs in the BIC Directory.

There are two types of BIC, 8 character BIC and 11 character BIC. The 8 character BIC identifies a financial institution in a country or a location. The 11 character BIC identifies the financial institution's branch.

For more information please see

[http://www.swift.com/biconline/index.cfm?fuseaction=display\\_aboutbic](http://www.swift.com/biconline/index.cfm?fuseaction=display_aboutbic)

## **TaxIdentifier**

A unique number assigned by the relevant tax authority to identify a party. This constraint is used in relation to tax. Note: This constraint must be specified when the party is tax exempt.

## **TradeRegNumber**

Trade Registration Number

## **UN/ECE**

To be deprecated in the next version. Use @Agency to indicate this selection.

## **VATIdentificationNumber**

A unique number assigned by the relevant tax authority to identify a party. This constraint is used in relation to value-added tax (VAT).

## **Other**

Used for any other identification schemes not covered by this list.

---

## **PartyType [attribute]**

Identifies the business role associated with the particular party

*This item is restricted to the following list.*



### **Auditor**

A third party that is authorized for making audits and checkings.

### **Bank**

The banking representative.

### **BillTo**

The address where the invoice is to be sent. (Not to be used for logistics BillTo, see LogisticsBillTo.)

### **BorderCrossing**

A geographic location separating two countries authorised to validate customs

documentation.

## **Broker**

The organisation acting as a broker for the buyer or supplier.

## **Buyer**

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the "Payer", the "Buyer" is the "Payer". (Not to be used for logistics buyer, see LogisticsBuyer.)

## **BuyerAgent**

The entity acting for the buyer in the transaction. (Not to be used for logistics BuyerAgent, see LogisticsBuyerAgent.)

## **Carrier**

The organisation or business entity that transports goods.

## **CarrierAssignmentResponsible**

The organisation to which the carrier has assigned some task.

## **ComponentVendor**

Vendor producing supplied components.

## **Consignee**

To be deprecated in version 3.0 (no date determined). Use LogisticsRole attribute to communicate this information.

## **Signor**

To be deprecated in version 3.0 (no date determined). Use LogisticsRole attribute to communicate this information.

## **Consuming**

The eventual consumer of the material

## **Converter**

The organisation responsible for changing one form of paper into another form, providing specialised functions not available to the supplier.

## **CreditDepartment**

The party responsible for credit authorization.

## **CrossDock**

A third party involved in the transport of goods.

## **CustomerFacility**

The type of the origin or destination location of a transport leg in a route is a buyer facility, usually a print site, or a warehouse owned by the buyer.

## **CustomerStock**

A "virtual" location that indicates that the material is owned by the customer.

## **Customs**

Any customs agency.

## **CustomsForwarder**

A forwarder responsible for managing the transfer of goods through customs.

## **DomesticForwarder**

A forwarder responsible for managing the transfer of goods.

## **EndUser**

EndUser is the party using, consuming, or converting the product. For example, a printer using paper reels to print a job for a publisher (printer is the end user). The final ShipTo destination for a product is normally to the EndUser facilities.

## **ExportForwarder**

A forwarder responsible for managing the export process.

## **ForestForwarder**

The party responsible for transporting forest wood products from logging areas to roadside landings.

## **ForestHarvester**

The party responsible for harvesting of forest wood products at logging areas.

## **Forwarder**

The party responsible for shipping arrangements.

## **FreightPayer**

The party responsible for paying freight.

## **Insurer**

The party providing insurance coverage for the goods.

## **Landowner**

The party who owns the land upon which the product was produced.

## **LoadingOperator**

A party that is carrying out loading of transport units.

## **LoggingArea**

A geographic location in the forest where logging takes place.

## **LogisticsBillTo**

The address where the logistics invoice is to be sent.

## **LogisticsBuyer**

The buyer of logistics services. The legal entity to which the service is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the "LogisticsPayer", the "LogisticsBuyer" is the payer.

## **LogisticsBuyerAgent**

The entity acting for the logistics buyer in the transaction.

## **LogisticsSeller**

The seller of logistics services. LogisticsSupplier is the seller of the service, if logistics seller is not specified as OtherParty = LogisticsSeller

## **LogisticsSupplier**

The party responsible for providing the service. LogisticsSupplier is also the seller of the service, if logistics seller is not specified as OtherParty = LogisticsSeller

## **LogisticsPayee**

The party handling and receiving logistics payments on behalf of another party.

## **LogisticsPayer**

The party handling and sending logistics payments of behalf of another party.

## **MainCarrier**

The primary carrier involved in the movement of goods.

## **Measurer**

The party that's carrying out the measurement of the products quantity and/or quality. The party is doing this for example on behalf of both the buyer and seller and the result can be used as basis for invoicing.

## **Merchant**

A third party buying and reselling products.

## **Mill**

A production facility.

## **NotifyParty**

A party that needs to be notified of the status of the transaction.

## **OnBehalfOf**

The activity in question is being made on behalf of this party.

## **OrderParty**

The organisation or business entity placing the order if different from the buyer party.

## **OriginalSupplier**

The first supplier in a supply chain. OriginalSupplier is only intended to identify the business party, not the origin of the product.

## **Payee**

The party handling and receiving payments on behalf of another party. (Not to be used for logistics payee, see LogisticsPayee.)

## **Payer**

The party handling and sending payments of behalf of another party. (Not to be used for logistics payer, see LogisticsPayer.)

## **PlaceFinalDestination**

The final destination of the goods.

## **PlaceOfAccept**

The location where acceptance of the goods is to take place.

## **PlaceOfDespatch**

The location where despatch took place.

## **PlaceOfDischarge**

The location where the goods were unloaded.

## **PlaceOfLoading**

The location where loading is to or took place.

## **PlaceOfMeasuring**

The location where the products are measured.

## **PlaceOfReloading**

A location where the goods were transferred from one transport type to another.

## **Port**

The type of the origin or destination location of a transport leg in a route. It is a maritime location.

## **PreCarrier**

The party responsible for activities prior to carrier accepting the goods (but after shipping has taken place).

## **PrinterFacility**

The location of the printer who will be using the product.

## **ProFormalInvoice**

The organisation or business entity to which the pro-forma invoice will be sent.

## **Producer**

The manufacturer of the goods.

## **RemitTo**

The organisation or business entity to which payment will be made.

## **Requestor**

The originator of the original PurchaseOrder requisition (for example, a printing plant ordering through a central purchasing organisation).

## **RoadKeeper**

The party who is responsible for the maintenance of the road.

## **RoadOwner**

The party who is the legal owner of the road.

## **SalesAgent**

The organisation or person responsible for product sales acting on behalf of the seller.

## **SalesOffice**

The functional unit in an organisation or business entity that is responsible for product sales.

## **Seller**

The seller of the product. SupplierParty is the seller of the product, if Seller is

not specified as OtherParty = Seller. (Not to be used for logistics seller, see LogisticsSeller.)

## ShipFromLocation

The location the goods were shipped from.

## ShipOwner

The owner of the vessel used to ship the goods.

## ShipTo

The address the material should be shipped to.

## SubCarrier

A sub carrier of another the shipping company.

## Supplier

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller. (Not to be used for logistics supplier, see LogisticsSupplier.)

## Terminal

The type of the origin or destination location of a transport leg in a route. It can be a sea, road or rail terminal.

## TerminalOperator

The party providing facilities such as loading, unloading, or warehousing.

## UnloadingOperator

A party that is carrying out unloading of transport units.

## Warehouse

A storage location. It can be the origin or destination location of a transport leg in a route.

## WillAdvise

Indicates that party will be identified at a later time

## Other

Any other organisation or business entity that may get involved in the transaction and that is not covered by the list.

---


## PasteDiameter

The diameter measurement of a reel when a new reel of paper is glued or pasted to it to continue running.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value



*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

## RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

## RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## PatternProfile

Defines the pattern used in machining the product.

### PatternProfileType [attribute]

*PatternProfileType is optional. A single instance might exist.*

Defines the name of any pattern or profile applied to the product.

Refer to PatternProfileType definition for any enumerations.

### PatternProfileAgency [attribute]

*PatternProfileAgency is optional. A single instance might exist.*

LumberAgency identifies which agency is responsible for assigning the lumber attributes.

Refer to PatternProfileAgency definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PatternProfileCode


*PatternProfileCode is optional. A single instance might exist.*

Defines the code which is used to describe the pattern profile.

#### AdditionalText

*AdditionalText is optional. A single instance might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



---

## PatternProfileAgency [attribute]

LumberAgency identifies which agency is responsible for assigning the lumber attributes.

*This item is restricted to the following list.*

attribute
<b>PatternProfileAgency</b>
type  lumberAgencyType

**BS**

**BS-EN**

British standard based on a European standard.

**CEN**

European Committee for Standardisation (<http://www.cenorm.be>)

**DIN**

**EN338**

**EN1912**

**EN1611-1**

**EDISAW**

**Generic**

**GOST**

Russian federal agency on technical regulating and metrology (<http://www.gost.ru>)

**ISO**

**JAS**

Japanese Agricultural Standard

**NELMA**

**NLGA**

**NS**

**NSLB**

**RIS**

**RT**

**SIS**

**SPIB**

**WCLIB**

**WRCLA**

**WWPA**

**Supplier**

---

## PatternProfileCode

Defines the code which is used to describe the pattern profile.

<b>PatternProfileCode</b>
type  s30

## PatternProfileType [attribute]

Defines the name of any pattern or profile applied to the product.

*This item is restricted to the following list.*

attribute
<b>PatternProfileType</b>
type  lumberPatternProfileType

### **Beveled Siding**

Wedge shaped boards, installed so that each board is lapped over the edge of the board below.

### **Bungalow Siding**

### **Channel Rustic Siding**

Siding that includes a decorative molding with a concave groove

### **Colonial Siding**

### **Dolly Varden Siding**

Bevel siding, which is a wedge shaped board, installed so that each board is lapped over the edge of the board below, that has the addition of an L-shaped cutout at the edge or side of the wedge, overlapping the top of the board below.

### **Log Cabin Siding**

Siding based on an Early American frontier style of housing, constructed of logs

### **Boston Pattern**

Type of roofing where shingles butt tightly against each other at the hip with alternating shingle courses lapping over the edges of the opposing shingles.

### **CaulkingSeam**

#### **CB1S**

Center bead on one side

#### **CB2S**

Center bead on two sides

#### **CG2E**

Center groove on two edges

#### **CM**

Center matched

#### **CM 1/4 T and G**

Center matched , 1/4 inch tongued and grooved

#### **CM 3/8 T and G**

Center matched, 3/8 inch tongued and grooved Center matched and edge V one side

#### **CM and EV 1S**

Center matched and edge V one side

## **CM and EV 2S**

Center matched and edge V two sided

## **CV1S**

Center V on one side

## **CV2S**

Center V on two sides

## **D and CM**

Dressed and center matched

## **DbI Plowed**

## **E and CB1S**

## **E and CB2S**

Edge and center bead one side

## **E and CV2S**

Edge and center bead two sides

## **EB1S**

Edge bead one side

## **EB2S**

Edge bead on two sides

## **EV1S**

Edge V one side

## **EV2S**

Edge V on two sides

## **Grooved for Splines**

## **Plowed**

## **S2S and CM 1/4 T and G**

Surfaced two sides, center matched , 1/4 inch tongued and grooved

## **S2S and CM 3/8 T and G**

Surfaced two sides, center matched , 3/8 inch tongued and grooved

## **ShipLap**

Boards with rabbeted edges overlapping.

## **ShipLap - 1/2 lap**

Boards with 1/2 inch rabbeted edges overlapping.

## **ShipLap - 3/8 lap**

Boards with 3/8 inch rabbeted edges overlapping.

## **ShipLap and EV1S**

Boards with rabbeted edges overlapping and edge V on one side.

## **T and G**

Tongued and grooved

**V Rustic**

**V-CV Rustic**

**Channel Decking**

**S2S CM and EV1S Decking**

**Comnation Ceiling**

**DbIBeaded Ceiling**

**Double Beaded Ceiling**

**E and CB Ceiling**

**E and CV Ceiling**

**EB Ceiling**

**EV Ceiling**

**V Ceiling**

**Beaded Partition**

**DbIBeaded Partition**

**E and CB Partition**

**E and CV Partition**

**V Partition**

**Flooring**

**Flooring D and M**

**Flooring S2S and CM**

**Special D and M Flooring**

**EasedEdge**

**Rabbeted**

**RadiusEdge**

**Beaded Shelving 2 Bead**

**Beaded Shelving 3 Bead**

**Casket Stock S3S G1E**

**Casket Stock S3S T1E**

**Corn Cribbing**

**Grooved Roofing**

**Gutter-Boston**

**Gutter-Ohio**

**Jamb**

**Ogee Batten**

**Patent Lath**

**Pulley Stile**

Still

1

2

3

4

5

6

7

8

9

10

11

12

13

14

16

18

20

50

52

54

56

58

60

62

64

66

68

71

101

102

103

104

105

106

109

110


115  
116  
117  
118  
119  
121  
122  
123  
124  
125  
130  
131  
132  
133  
134  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
153  
161  
165  
166  
168  
170  
171  
172  
173  
173 Spline  
174  
200

202  
204  
206  
220A  
222A  
224A  
300  
302  
304  
305-a  
305-b  
305-c  
305-d  
305-e  
405-a  
405-b  
405-c  
405-d  
405-e  
Other

---

## PerCarton

A field indicating the number of sheets per carton.



---

## Perforated [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

Yes  
No



## Perforation

Perforation information

### PerforationType [attribute]

*PerforationType is optional. A single instance might exist.*

Perforation type

Refer to PerforationType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### DistanceFromEdge


*DistanceFromEdge is optional. A single instance might exist.*

The distance from the edge of the paper. This element is used to communicate where the hole is.

### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.




## PerforationType [attribute]

Perforation type

*This item is restricted to the following list.*

**Pattern**

**Workbook**



## PeriodType [attribute]

Duration of time

*This item is restricted to the following list.*

**Day**

**FinancialPeriodBeginning**

**MonthBeginning**


**Period**

**QuarterBeginning**

**WeekBeginning**

**WeekNumber**

**YearBeginning**



## Permeability

A group item used to communicate air permeability target or test value according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*


The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation



# papiNet V2R31

---

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## **TwoSigmaUpper**


*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---


## **PerPallet**

A field indicating the number of sheets on the pallet.



## **PerReam**

A field indicating the number of sheets per ream.



## **PerTab**

A field indicating the number of sheets per tab marking.



## pH

A group item used to communicate pH (degree of acidity versus basicity) target or test value according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin



*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.



## StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

## PiecesPerRow

This element details the number of pieces or individual items that are to be placed/packageged in a row within the unit. Usually used to identify the standard number of pieces in a standard packaging unit of the product.

<b>PiecesPerRow</b>
type nonNegativeInteger

## PlacementInOrderOfMatter

Element used to identify where the component is to be placed amongst other components when assembling a book.

### PlacementReference [attribute]

*PlacementReference is mandatory. A single instance is required.*

Placement reference

Refer to  
PlacementReference  
definition for any enumerations.

### RelativeLocation [attribute]


*RelativeLocation is optional. A single instance might exist.*

The relative position in the end-item where the component is to be placed.

### PlacementLocation [attribute]

*PlacementLocation is mandatory. A single instance is required.*

Placement location.



# papiNet V2R31

---

Refer to PlacementLocation definition for any enumerations.

## **PlacementSequence [attribute]**

*PlacementSequence is optional. A single instance might exist.*

The placement sequence. Any non negative integer between 1 and 99.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

#### **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **PlacementLocation [attribute]**

Placement location.

*This item is restricted to the following list.*

**Inside**

**Outside**

**Before**

**After**



---

## **PlacementReference [attribute]**

Placement reference

*This item is restricted to the following list.*

**BackCover**

**BacktEndsheet**

**Chapter**


**FrontCover**

**FrontEndsheet**

**Item**

**Page**


**Signature**



---

## **PlacementSequence [attribute]**


The placement sequence. Any non negative integer between 1 and 99.



## Planning

The Planning element is the root element for the Planning e-Document.

The Planning e-Document provides a tool for trading partners to exchange forecasted or planned information for a specific product or event within a specified timeframe. The e-Document is designed to support a variety of business processes, which may include securing needed supplies or simply the exchange of information.



### **PlanningProcessType [attribute]**

*PlanningProcessType is mandatory. A single instance is required.*

The type of process that the Planning e-Document communicates.

Refer to PlanningProcessType definition for any enumerations.

### **Language [attribute]**

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

#### **PlanningHeader**

*PlanningHeader is mandatory. A single instance is required.*

Information that applies to all the items on the Planning e-Document.

#### **PlanningLineItem**

*PlanningLineItem is mandatory. One instance is required, multiple instances might exist.*

The PlanningLineItem must reference either a Product or Downtime. The PlanningLineItem presents information for a particular product or downtime event.

## PlanningBucket

PlanningBucket groups together the elements required to communicate the time and quantity related information for the parent item (either Product or Downtime).

### BucketType [attribute]

*BucketType is mandatory. A single instance is required.*

The type of planning information being communicated in the bucket.

Refer to BucketType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### TimePeriod

*TimePeriod is mandatory. A single instance is required.*

The TimePeriod element is used to communicate a duration period of time as indicated in PeriodType.

#### OtherDate

*OtherDate is optional. A single instance might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

#### Quantity

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.


The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

#### InformationalQuantity

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

#### ProductionRunNumber



# papiNet V2R31

---

*ProductionRunNumber is optional. A single instance might exist.*

The ProductionRunNumber assigned by the issuer.

## **(choice)**

*[choice] is optional because of choice construct.*

### **PurchaseOrderDetail**

*PurchaseOrderDetail is optional because of choice construct.*

Multiple PurchaseOrderDetail instances are allowed.

### **BySupplierOrder**

*BySupplierOrder is optional because of choice construct.*

Selection criteria for communicating Supplier Order information.

### **ByLoad**

*ByLoad is optional because of choice construct.*

By Load

### **ByJob**

*ByJob is optional because of choice construct.*

Information about the job being communicated.

### **HighlightedPlanningBucket**

*HighlightedPlanningBucket is optional. A single instance might exist.*

Provides an indication and information that the planning bucket should be reviewed.

---

## **PlanningBucketStatusType [attribute]**

Used to identify the Planning bucket's status. Typically used to highlight a change in status to the receiver of the e-Document.



*This item is restricted to the following list.*

### **Amended**

The supplied information is changed.

### **Cancelled**

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### **New**

The information is new and supplied for the first time.

### **NoAction**

The supplied information has not been amended and thereby requires no action.

## PlanningHeader

Information that applies to all the items on the Planning e-Document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PlanningMessageNumber

*PlanningMessageNumber is mandatory. A single instance is required.*

A unique identifier assigned to the Planning e-Document assigned by the issuer that makes this Planning unique. Subsequent Planning e-Documents with updates will use this same PlanningMessageNumber.

#### PlanningIssueDate

*PlanningIssueDate is mandatory. A single instance is required.*

The date and time this version of the Planning data was issued.

#### PlanningIdentifier

*PlanningIdentifier is optional. A single instance might exist.*

An identifier that communicates the scope or content of the Planning e-Document. This field is used to communicate which sub-set of planning information is being maintained.

#### RequestNumber

*RequestNumber is optional. A single instance might exist.*

A unique tracking number specifically identifying the InfoRequest e-Document to the originator. The tracking number is returned with the "information", the answer, to help match the answer to the request.

#### SenderParty

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.


The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

#### ReceiverParty

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for



the e-Document and not the party performing the receiving service of the electronic message.

## RequestingParty

*RequestingParty is optional. A single instance might exist.*

The party requesting the information.

## SupplierParty

*SupplierParty is optional. A single instance might exist.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## BuyerParty

*BuyerParty is optional. A single instance might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## PlanningReference

*PlanningReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the Planning e-Document.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## PlanningIdentifier

An identifier that communicates the scope or content of the Planning e-Document. This field is used to communicate which sub-set of planning information is being maintained.

PlanningIdentifier	
type	s30


---

## PlanningIssueDate

The date and time this version of the Planning data was issued.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

## papiNet V2R31

---

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## PlanningLineItem

The PlanningLineItem must reference either a Product or Downtime. The PlanningLineItem presents information for a particular product or downtime event.

### PrintType [attribute]

*PrintType is optional. A single instance might exist.*

Refer to PrintType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PlanningLineItemNumber

*PlanningLineItemNumber is mandatory. A single instance is required.*

A sequential number that uniquely identifies the PlanningLineItemNumber.

#### LocationParty

*LocationParty is mandatory. A single instance is required.*

The organization or business entity where the business event took place or will take place.

#### MachineID

*MachineID is optional. A single instance might exist.*

An identifier assigned to the particular machine being referenced. For example, a machine could be a paper machine, an off-line coater, a sheeter, or a printing press. The particular machine being referenced will be determined by the business event being supported.

#### OtherParty

*OtherParty is optional. Multiple instances might exist.*


An organisation or business entity other than those specifically detailed within a e-Document.

#### PlanningReference

*PlanningReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the Planning e-Document.

### (choice)



*[choice] is optional because of choice construct.*

## **Product**

*Product is optional because of choice construct.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **Downtime**

*Downtime is optional because of choice construct.*

An element used to communicate when equipment is not available for manufacturing purposes.

## **PlanningBucket**

*PlanningBucket is mandatory. One instance is required, multiple instances might exist.*

PlanningBucket groups together the elements required to communicate the time and quantity related information for the parent item (either Product or Downtime).

## **WasteQuantity**

*WasteQuantity is optional. Multiple instances might exist.*

The quantity of product wasted.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **EndUses**

*EndUses is optional. Multiple instances might exist.*

A text element used to express in human readable form a list of applicable end uses for a product. Examples of end uses are:

- Magazine
- Book
- Commercial print
- etc

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## PlanningLineItemNumber

A sequential number that uniquely identifies the PlanningLineItemNumber.

PlanningLineItemNumber	
type	lineNumberType

---

## PlanningMessageNumber

A unique identifier assigned to the Planning e-Document assigned by the issuer that makes this Planning unique. Subsequent Planning e-Documents with updates will use this same PlanningMessageNumber.

PlanningMessageNumber	
type	s30

---

## PlanningProcessType [attribute]

The type of process that the Planning e-Document communicates.

*This item is restricted to the following list.*

attribute	
PlanningProcessType	
type	processType

### Consumption

Consumed in manufacturing.

### DeliveryReceipt

Delivered to the ship-to location.

### Despatch

Ready to shipped.

### Inventory

In available inventory at the storage location.

### Production

The quantity added to stock through a manufacturing or conversion process.

### Sales

A PurchaseOrder has been placed for the product.

---

## PlanningReference

An element detailing relevant references pertaining to the Planning e-Document.

### PlanningReferenceType [attribute]

*PlanningReferenceType is mandatory. A single instance is required.*

PlanningReference	
type	s255

attributes	
PlanningReferenceType	
type	referenceType
AssignedBy	
type	partyType

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill",

"Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to PlanningReferenceType definition for any enumerations.

## AssignedBy [attribute]


*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

## PlanningReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.



Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## PlanningRequestDetail

Its existence is mutually exclusive with that of the InventoryStatusRequestDetail, OrderStatusRequestDetail, Availability, and ProductQuality.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Product

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.



## LocationParty

*LocationParty is optional. Multiple instances might exist.*

The organization or business entity where the business event took place or will take place.

## BuyerParty

*BuyerParty is optional. Multiple instances might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## ShipToParty

*ShipToParty is optional. Multiple instances might exist.*

The name and/or address to which the goods should be delivered with the party type indicated by the PartyType attribute.

## EndUserParty

*EndUserParty is optional. Multiple instances might exist.*

The party using, consuming, or converting the product. For example, a printer using paper reels for a print job for a publisher. The final ShipTo destination for a product is normally to the end user's facilities.

---

## PlasticMaterial

Describes the plastic used in the process.

### PlasticPrinting [attribute]

*PlasticPrinting is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to PlasticPrinting definition for any enumerations.

### PlasticMaterialType [attribute]

*PlasticMaterialType is optional. A single instance might exist.*

The type of plastic material

Refer to PlasticMaterialType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*


#### Thickness

*Thickness is mandatory. A single instance is required.*

Physical dimension of a product.

#### PlasticPrintingDescription

*PlasticPrintingDescription is optional. A single instance might exist.*



Plastic printing description

## PlasticMaterialType [attribute]

The type of plastic material

*This item is restricted to the following list.*

**PC**  
**PET**  
**PVC**  
**Other**



## PlasticPrinting [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

**Yes**  
**No**



## PlasticPrintingDescription

Plastic printing description



## Plate

The image carrying medium.


**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**PlateType**


*PlateType is optional. A single instance might exist.*

The category of material used to carry an image to reproduce a print impress.  
(paper, metal, plastic, rubber)



## PlateType

The category of material used to carry an image to reproduce a print impress. (paper, metal, plastic, rubber)



## PlyAttributes

The characteristics of the plies of paper or tissue. Manufacturing data relevant to each ply that constitutes the final product

### CoatingLocation [attribute]

*CoatingLocation is optional. A single instance might exist.*

Coating location

Refer to CoatingLocation definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### PlyNumber

*PlyNumber is mandatory. A single instance is required.*

Product attributes can be detailed for each ply. If product attributes are defined for the plies this element defines the ply that these product attributes apply to.

### Abrasion

*Abrasion is optional. Multiple instances might exist.*

A group item used to communicate abrasion loss target or test value.

### AbsorptionInk

*AbsorptionInk is optional. Multiple instances might exist.*

A group item used to communicate ink absorption target or test value.

### AbsorptionLight

*AbsorptionLight is optional. Multiple instances might exist.*

A group item used to communicate light absorption target or test value.

### AbsorptionWater

*AbsorptionWater is optional. Multiple instances might exist.*

A group item used to communicate water absorption target or test value.

### Appearance

*Appearance is optional. Multiple instances might exist.*

A group item used to communicate appearance.

### Ash

*Ash is optional. Multiple instances might exist.*

A group item used to communicate the ash content of the product according to a particular TestMethod.

### BasisWeight

*BasisWeight is optional. Multiple instances might exist.*

The weight of the paper expressed as a mass for a given surface area. In countries using the metric system, the basis weight is expressed as the weight in grams of one sheet of paper that is one square meter in area—not dependent on basic sheet size. In countries using the imperial system, the weight is expressed in pounds for a given ProductBasisSizeType.



## **BendingResistance**

*BendingResistance is optional. Multiple instances might exist.*

Bending resistance

## **BendingStiffness**

*BendingStiffness is optional. Multiple instances might exist.*

BendingStiffness

## **Brightness**

*Brightness is optional. Multiple instances might exist.*

A measurement of the degree of light reflectivity of the product.

## **Bulk**

*Bulk is optional. Multiple instances might exist.*

A group item used to communicate bulking thickness target or test value.

## **Burst**

*Burst is optional. Multiple instances might exist.*

A group item used to communicate bursting strength target or test value according to a particular TestMethod.

## **BurstIndex**

*BurstIndex is optional. Multiple instances might exist.*

The burst index.

## **Caliper**

*Caliper is optional. Multiple instances might exist.*

The thickness of a sheet of paper under standard test conditions.

## **CoatWeight**

*CoatWeight is optional. Multiple instances might exist.*

A group item used to communicate the coating thickness target or test value according to a particular TestMethod.

## **ColourDetail**

*ColourDetail is optional. Multiple instances might exist.*

A group item used to communicate details of colour according to the selected colour definition scheme.

## **Density**

*Density is optional. Multiple instances might exist.*

A group item used to communicate density target or test value according to a particular TestMethod.

## **Dirt**

*Dirt is optional. Multiple instances might exist.*

A group item used to communicate dirt content target or test value according to a particular TestMethod.

## **DominantWavelength**

*DominantWavelength is optional. Multiple instances might exist.*

Dominant wavelength

## **FibreLength**

*FibreLength is optional. Multiple instances might exist.*

A group item used to communicate fibre length target or test value according to a particular TestMethod.

## **FibreClassification**

*FibreClassification is optional. Multiple instances might exist.*

A group item used to communicate fibre classification according to the specified classification scheme.

## **Folding**

*Folding is optional. Multiple instances might exist.*

A group item used to communicate folding endurance target or test value according to a particular TestMethod.

## **Formation**

*Formation is optional. Multiple instances might exist.*

A group item used to communicate sheet formation target or test value according to a particular TestMethod.

## **Freeness**

*Freeness is optional. Multiple instances might exist.*

Freeness

## **Friction**

*Friction is optional. Multiple instances might exist.*

A group item used to communicate static and kinetic friction target or test value according to a particular TestMethod.

## **Gloss**

*Gloss is optional. Multiple instances might exist.*

A group item used to communicate specular gloss target or test value according to a particular TestMethod.

## **LightScattering**

*LightScattering is optional. Multiple instances might exist.*

A group item used to communicate light scattering coefficients according to a particular TestMethod.

## **Moisture**

*Moisture is optional. Multiple instances might exist.*

Desired percentage, or other indicator, of water in the product at the time of shipment.

## **Opacity**

*Opacity is optional. Multiple instances might exist.*

A group item used to communicate opacity target or test value according to a particular TestMethod.

## **Permeability**

*Permeability is optional. Multiple instances might exist.*

A group item used to communicate air permeability target or test value according

to a particular TestMethod.

## **pH**

*pH is optional. Multiple instances might exist.*

A group item used to communicate pH (degree of acidity versus basicity) target or test value according to a particular TestMethod.

## **PlyBond**

*PlyBond is optional. Multiple instances might exist.*

A group item used to communicate internal bond strength target or test value between plies according to a particular TestMethod.

## **Porosity**

*Porosity is optional. Multiple instances might exist.*

A group item used to communicate a permeability target or test value.

## **PostConsumerWaste**

*PostConsumerWaste is optional. Multiple instances might exist.*

A group item used to communicate the target or test value percentage of post consumer waste fibre in the product according to a particular TestMethod.

## **PPI**

*PPI is optional. Multiple instances might exist.*

A group item used to communicate the number of pages in an inch of thickness either as a target or actual value. Equal to the number of sheets per inch times 2.

## **PreConsumerWaste**

*PreConsumerWaste is optional. Multiple instances might exist.*

A group item used to communicate the target or test value percentage of pre-consumer waste fibre in the product according to a particular TestMethod.

## **Recycled**

*Recycled is optional. Multiple instances might exist.*

A group item used to communicate the target or test value total percentage of waste fibre in the product according to a particular TestMethod.

## **Resistance**

*Resistance is optional. Multiple instances might exist.*

A group item used to communicate air resistance target or test value according to a particular TestMethod.

## **RingCrush**

*RingCrush is optional. Multiple instances might exist.*

Ring Crush

## **Roughness**

*Roughness is optional. Multiple instances might exist.*

A group item used to communicate surface roughness target or test value according to a particular TestMethod.

## **RunnabilityIndex**

*RunnabilityIndex is optional. Multiple instances might exist.*

A group item used to communicate the calculated run-ability index target or test

value.

## **ShowThrough**

*ShowThrough is optional. Multiple instances might exist.*

Show through

## **Sizing**

*Sizing is optional. Multiple instances might exist.*

A group item used to communicate size test of paper by ink resistance target or test value.

## **Smoothness**

*Smoothness is optional. Multiple instances might exist.*

A group item used to communicate surface smoothness target or test value according to a particular TestMethod.

## **Stiffness**

*Stiffness is optional. Multiple instances might exist.*

A group item used to communicate stiffness target or test value.

## **Stretch**

*Stretch is optional. Multiple instances might exist.*

A group item used to communicate stretch target or test value.

## **SurfaceStrength**

*SurfaceStrength is optional. Multiple instances might exist.*

Surface Strength

## **TEA**

*TEA is optional. Multiple instances might exist.*

Tensile Energy Absorption.

## **Tear**

*Tear is optional. Multiple instances might exist.*

A group item used to communicate tearing resistance target or test value according to a particular TestMethod.

## **TearIndex**

*TearIndex is optional. Multiple instances might exist.*

TearIndex

## **Tensile**

*Tensile is optional. Multiple instances might exist.*

A group item used to communicate zero-span tensile strength target or test value according to a particular TestMethod.

## **TensileIndex**

*TensileIndex is optional. Multiple instances might exist.*

Tensile Index

## **Whiteness**

*Whiteness is optional. Multiple instances might exist.*

# papiNet V2R31

A group item used to communicate degree of whiteness target or test value according to a particular TestMethod.

## AdditionalTest

*AdditionalTest is optional. A single instance might exist.*

AdditionalTest exists to enable the inclusion of a test that has not been identified by papiNet.org. It is always a single-instance element so it is very important that users, who come upon a test that papiNet.org has not identified, communicate the need for this test to us at [www.papiNet.org](http://www.papiNet.org).

## PlyBond

A group item used to communicate internal bond strength target or test value between plies according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).



## DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

## DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

## StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper


*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## PlyNumber

Product attributes can be detailed for each ply. If product attributes are defined for the plies this element defines the ply that these product attributes apply to.



---

## PlySet

PlySet.


### EdgePaddable [attribute]

*EdgePaddable is optional. A single instance might exist.*

Refers to the process of applying edge padding glue or adhesive (Yes) or not (No). A liquid adhesive mixture which when brushed or sprayed onto the side of a pile of paper binds the sheets together along one edge, thus forming a pad.

Refer to EdgePaddable definition for any enumerations.

### (sequence)



The sequence of items below is mandatory. A single instance is required.

## NumberOfPlies

*NumberOfPlies is optional. Multiple instances might exist.*

The number of layers of paper product joined together to make the final saleable product.

## PlyAttributes

*PlyAttributes is optional. Multiple instances might exist.*


The characteristics of the plies of paper or tissue. Manufacturing data relevant to each ply that constitutes the final product

---

## PlywoodLayupStructure

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### PlywoodPlySet

*PlywoodPlySet is optional. A single instance might exist.*

### GlueExposure

*GlueExposure is optional. Multiple instances might exist.*

### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.


---

## PlywoodMachining

PlywoodMachining defines the machining made to the panel (for example, grooving).

### Agency [attribute]

*Agency is mandatory. A single instance is required.*



Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.





---

## PlywoodOSBGrade

Defines the grade of plywood, OSB product

### Face [attribute]

*Face is optional. A single instance might exist.*



Used to describe which side (or face) of the product that the grade is applicable to.

Refer to Face definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### SpanRating

*SpanRating is optional. A single instance might exist.*

Span Rating according to NIST standards and indicated on grade stamp.

Refer to SpanRating definition for any enumerations.

#### StrengthGroup

*StrengthGroup is optional. A single instance might exist.*

As defined in the NIST standard, an additional classification of panel strength.


Refer to StrengthGroup definition for any enumerations.

---

## PlywoodOSBSpecies

Defines the raw material species of plywood, OSB product.

*This item is restricted to the following list.*



**Southern**

**Western**

**Aspen**

**DF**

**Hemlock**


**Larch**

**WhiteFir**

## PlywoodPlyCharacteristics

(sequence)

The



sequence of items below is mandatory. A single instance is required.

### PlyNumber

*PlyNumber is optional. A single instance might exist.*

Product attributes can be detailed for each ply. If product attributes are defined for the plies this element defines the ply that these product attributes apply to.

### WoodPanelChracteristics


*WoodPanelChracteristics is optional. A single instance might exist.*

## PlywoodPlyGrade

Defines the grade of one ply, used with Agency to specify the grading agency.

### Agency [attribute]

*Agency is mandatory. A single instance is required.*



Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.


For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

## PlywoodPlySet

(sequence)

*The sequence of items below is mandatory. A single instance is required.*



### NumberOfPlies

*NumberOfPlies is optional. A single instance*

*might exist.*

The number of layers of paper product joined together to make the final saleable product.

## PlywoodPlyCharacteristics

*PlywoodPlyCharacteristics is optional. Multiple instances might exist.*

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## Porosity

A group item used to communicate a permeability target or test value.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*


Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### DetailValue



# papiNet V2R31

---

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

## **DetailRangeMin**

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

## **DetailRangeMax**

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

## **StandardDeviation**

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## **TwoSigmaUpper**

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## **PositionInSheet**

Location in the sheet where the defect was identified.

<b>PositionInSheet</b>	
type	s20

---

## **PositionMeasuredFrom [attribute]**

Defines from where the position is measured on an item.

<b>PositionMeasuredFrom</b>	
type	positionMeasuredFrom

*This item is restricted to the following list.*

### **Bottom**

The position is measured from the bottom of the item.

### **BackEnd**

The position is measured from the back end of the item.

### **FrontEnd**

The position is measured from the front end of the item.

## LargeEnd

The position is measured from the large end of the item.

## SmallEnd

The position is measured from the small end of the item.

## Top

The position is measured from the top of the item.

---

## PositionOnItem

Specifies a position on an item. The attribute PositionMeasuredFrom defines the reference point for the position.

### PositionMeasuredFrom [attribute]

*PositionMeasuredFrom is mandatory. A single instance is required.*

Specifies how detailed the measurements are done.


Refer to PositionMeasuredFrom definition for any enumerations.

### UOM [attribute]

*UOM is mandatory. A single instance is required.*

Defines the unit of measure for the value.

Refer to UOM definition for any enumerations.



---

## PostalCode

The postal code associated with the address elements.



## PostConsumerWaste

A group item used to communicate the target or test value percentage of post consumer waste fibre in the product according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin


*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.



# papiNet V2R31

---

## StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.


---

## PPI

A group item used to communicate the number of pages in an inch of thickness either as a target or actual value. Equal to the number of sheets per inch times 2.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## PreConsumerWaste

A group item used to communicate the target or test value percentage of pre-consumer waste fibre in the product according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin


*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.



## StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.


---

## PrepDueDate

The preparation due date.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## PrepInformation

Information related to the preparation of the Book.

### PrepType [attribute]

*PrepType is optional. A single instance might exist.*

The type of input for press preparation

Refer to PrepType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### SupplierParty

*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

### PrepShipDate

*PrepShipDate is optional. A single instance might exist.*

The preparation ship date.

### PrepDueDate

*PrepDueDate is optional. A single instance might exist.*

The preparation due date.

### PrepNeededDate


*PrepNeededDate is optional. A single instance might exist.*

The preparations need date.

### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## PrepNeededDate


The preparations need date.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Date

*Date is mandatory. A single instance is required.*



# papiNet V2R31

---

A group element that contains the specification of Year, Month, and Day.

## Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.


---

## PrepShipDate

The preparation ship date.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



## Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

## Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## PrepType [attribute]

The type of input for press preparation

*This item is restricted to the following list.*

**4PageImposedFilm**  
**8PageImposedFilm**  
**ApplicationFiles**  
**Bookmap**  
**CameraCopy**  
**CopyBook**  
**DuplicateStrip**  
**ElectronicFiles**  
**ElectronicGraphic**  
**Film**  
**FilmPageNegatives**  
**FilmPagePositives**  
**IllustrationFilm**  
**NegativeImposedPlateMakingFilm**  
**Originals**  
**OriginalArt**  
**Other**  
**Overtakes**  
**PageProof**  
**PDF**  
**PositiveImposedPlateMakingFilm**  
**RachwalFilm**  
**ReflectiveArtBoard**  
**ReproProof**  
**RestripSuppliedFlats**  
**TearSheet**  
**Transparencies**



attribute
<b>PrepType</b>
type   pressPrepInputType

## PressBreakLocation

The specific location identified within a printing press.

### LocationType [attribute]

*LocationType is mandatory. A single instance is required.*



Location of Break on the Press. A group item detailing relevant locations on the press to the Performance e-Document.

Refer to LocationType definition for any enumerations.

### FloorLocationType [attribute]

*FloorLocationType is optional. A single instance might exist.*

Floor Location Type

Refer to FloorLocationType definition for any enumerations.

## PressComponent

Press Component.

### BarcodeSuppliedByPublisher [attribute]

*BarcodeSuppliedByPublisher is optional. A single instance might exist.*

Barcode supplied by publisher

Refer to



BarcodeSuppliedByPublisher definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### NumberOfPages

*NumberOfPages is optional. A single instance might exist.*

The number of pages.

#### Signatures

*Signatures is optional. Multiple instances might exist.*


Signatures.

#### PressPrep

*PressPrep is optional. A single instance might exist.*

Press preparation information

#### ManufacturingSpecifications



*ManufacturingSpecifications is optional. A single instance might exist.*

Manufacturing specifications.

## Halftones

*Halftones is optional. A single instance might exist.*

Halftones are images made up of a series of dots in a specific pattern that simulates the look of a continuous tone image.

## Length

*Length is optional. A single instance might exist.*

The length of the object.

## Width

*Width is optional. A single instance might exist.*

The width of the object.

---

## PressConditions

Construct contains environmental conditions of the press during operations

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Humidity

*Humidity is optional. Multiple instances might exist.*

Humidity

#### AmbientTemperature

*AmbientTemperature is optional. Multiple instances might exist.*

The temperature of the surrounding environment.

#### MachineSpeed

*MachineSpeed is optional. Multiple instances might exist.*

The rate at which the machine is, was, or should be running.

#### Impressions

*Impressions is optional. Multiple instances might exist.*

The work produced by one revolution of the printing cylinder or unit.

#### Tension



*Tension is optional. Multiple instances might exist.*

Tension of the web on the printing press.

#### Alignment

*Alignment is optional. Multiple instances might exist.*

A measurement of how the reel is aligned on printing press



## PrintUnit

*PrintUnit is optional. Multiple instances might exist.*

PrintUnit identifies the unique qualities associated with the individual unit of the printing press.

## PressFormType


*PressFormType is optional. A single instance might exist.*

Description of press form, expressed as deliveries and number of pages in the signature being printed, e.g. 2X16, 4X4.

---

## PressFormType

Description of press form, expressed as deliveries and number of pages in the signature being printed, e.g. 2X16, 4X4.




---

## PressImpositionType [attribute]

The type of press imposition

*This item is restricted to the following list.*

- HeadToHead**
- FootToFoot**
- HeadToFoot**



---

## PressPrep

Press preparation information

### PressPrepOutputType [attribute]

*PressPrepOutputType is optional. A single instance might exist.*

The press prep output type.

Refer to PressPrepOutputType definition for any enumerations.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### PressPrepInput


*PressPrepInput is mandatory. One instance is required, multiple instances might exist.*

Element used to identify press preparation media and type of media required for input to the press component.



## PressPreInput

Element used to identify press preparation media and type of media required for input to the press component.



### MediaType [attribute]

*MediaType is optional. A single instance might exist.*

The type of media

Refer to MediaType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PressPreInputType

*PressPreInputType is mandatory. A single instance is required.*

Press prep input type


Refer to PressPreInputType definition for any enumerations.

---

## PressPreInputType

Press prep input type

*This item is restricted to the following list.*



**4PageImposedFilm**

**8PageImposedFilm**

**ApplicationFiles**

**Bookmap**

**CameraCopy**

**CopyBook**

**DuplicateStrip**

**ElectronicFiles**

**ElectronicGraphic**

**Film**

**FilmPageNegatives**

**FilmPagePositives**

**IllustrationFilm**

**NegativeImposedPlateMakingFilm**

**Originals**

**OriginalArt**

**Other**

**Overtakes**

**PageProof**  
**PDF**  
**PositiveImposedPlateMakingFilm**  
**RachwalFilm**  
**ReflectiveArtBoard**  
**ReproProof**  
**RestripSuppliedFlats**  
**TearSheet**  
**Transparencies**


---

## **PressPrepOutputType [attribute]**

The press prep output type.

*This item is restricted to the following list.*

**DirectToFilm**  
**DirectToPlate**  
**DirectToPress**  
**Film**



---

## **PressType [attribute]**

The type of press used.

*This item is restricted to the following list.*

**Cameron**

A type of belt press that both prints and binds a book.

**ColdsetOffset**

An offset printing method suitable for newspapers, in other words, ink dries by penetration into the paper.

**Digital**

Digital print process that uses electronic files in print production.

**DigitalInkJet.**

Digital print process that uses inkjet technology.

**DigitalToner**

Digital print process that uses toner technology.

**Electronic**

Any technology that reproduces pages without the use of traditional ink, water, chemistry, or plates; also known as plateless printing.

**Flexographic**

A type of printing that uses rubber printing plates.



## Gravure

A method of printing in which the image is etched into the printing plates, as opposed to letterpress printing, in which the image is slightly raised from the rest of the plate. Gravure printing produces consistent quality in long production runs.

## HeatsetOffset

An offset printing method.

## LetterPress

The oldest printing method, in which the image to be printed is raised from the plate, inked, and applied directly to paper.

## Offset

Use this option when you do not wish to designate which type of offset press approach to use, just that offset printing is the preferred printing method.

## SheetFed

A type of printing press that accepts paper in the form of sheets.

## SilkScreen

A printing method in which ink is pushed through a stencil, used for imprinting T-shirts and heavier paper stocks.

## Web


A printing press that uses rolls (webs) of paper rather than sheets. Also called web-fed press.

---

## PressureTreatment

Method and parameter values of pressure treatment.

(sequence)



*The sequence of items below is mandatory. A single instance is required.*

### **PressureTreatmentCompound**

*PressureTreatmentCompound is mandatory. A single instance is required.*

The substance used for pressure treatment.

### **PressureTreatmentConcentration**

*PressureTreatmentConcentration is mandatory. A single instance is required.*

Retained concentration of preservative chemical.

### **PressureTreatmentComStdorUseCategory**

*PressureTreatmentComStdorUseCategory is mandatory. A single instance is required.*

Pressure treatment compound standard or use category

Refer to PressureTreatmentComStdorUseCategory definition for any enumerations.

## PressureTreatmentCompound

The substance used for pressure treatment.

### CompoundType [attribute]

*CompoundType is optional. A single instance might exist.*


Defines the type of chemical treatment used.



### CompoundAgency [attribute]

*CompoundAgency is optional. A single instance might exist.*

The agency responsible for the compound coding. Defines the trade name of the treatment.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is optional. A single instance might exist.*

A numeric value expressed in the unit of measure (UOM).

#### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## PressureTreatmentComStdorUseCategory

Pressure treatment compound standard or use category

*This item is restricted to the following list.*



**C2**

**C3**

**C4**

**C5**

**C6**

**C9**

**C11**

C14

C15

C17

C18

C20

C22

C23

C24

C25

C27

C28

C29

C30

C31

C32

C33

C34

C35

N1

N2

UC2

UC3A

UC3B

UC4A

UC4B

UC4C

UC5A

UC5B

UC5C

UCFA

UCFB


---

### PressureTreatmentConcentration

Retained concentration of preservative chemical.

#### UOM [attribute]

*UOM is optional. A single instance*



*might exist.*

Defines the unit of measure for the value.


Refer to UOM definition for any enumerations.

## PriceAdjustment

A group item defining a deviation from the PricePerUnit.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### AdjustmentPercentage

*AdjustmentPercentage is optional. A single instance might exist.*

A percentage, either negative or positive, that is applied to either the price, or a starting amount to determine the value of the particular MonetaryAdjustment.

### AdjustmentValue

*AdjustmentValue is optional. A single instance might exist.*


A group element that contains a currency value, either positive or negative, and a measurement value (in other words a price per unit structure) that will be used in the price adjustment AdjustmentValue.

## PriceAndAmountInfo

A grouping element that contains information about price and amounts.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### BaseAmountInfo

*BaseAmountInfo is mandatory. A single instance is required.*

A grouping element that contains information about price and base amount without any taxes.

### QuantityInformation

*QuantityInformation is mandatory. A single instance is required.*

A group item containing information about quantity and informational quantity of similar items.

### MonetaryAdjustment

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount.

MonetaryAdjustment contains an attribute that indicates they type of adjustment being communicated.

## NetAmount

*NetAmount is optional. A single instance might exist.*

An element that contains the net amount excluding tax. Adjustments are included in NetAmount. NetAmount encapsulates CurrencyValue.

## Amount

*Amount is optional. A single instance might exist.*

An element that contains the amount including tax. The Amount encapsulates CurrencyValue.

## PriceDetails

An element that groups together price information.

### PriceQuantityBasis [attribute]

*PriceQuantityBasis is mandatory. A single instance is required.*

The basis for the determination of the price.

Refer to PriceQuantityBasis definition for any enumerations.

### PriceTaxBasis [attribute]

*PriceTaxBasis is optional. A single instance might exist.*

This price provides the basis for tax.

Refer to PriceTaxBasis definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PricePerUnit

*PricePerUnit is mandatory. A single instance is required.*


PricePerUnit is an element designed to support flexibility in price representation.

This structure is read as CurrencyValue per MeasurementValue, or alternatively CurrencyValue per number of UOM(s).

#### InformationalPricePerUnit

*InformationalPricePerUnit is optional. Multiple instances might exist.*

A group item containing a currency value and a measurement value used convey a secondary PricePerUnit. For example, where PricePerUnit is dollars per ton. InformationalPricePerUnit could be dollars per kilogram.



## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## ExchangeRate

*ExchangeRate is optional. A single instance might exist.*

The exchange rate as of the date included in the element.

## MonetaryAdjustment

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates they type of adjustment being communicated.

## GeneralLedgerAccount

*GeneralLedgerAccount is optional. A single instance might exist.*

The general ledger account to be referenced for the item.

---

## PricePerUnit

PricePerUnit is an element designed to support flexibility in price representation.

This structure is read as CurrencyValue per MeasurementValue, or alternatively CurrencyValue per number of UOM(s).

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact)



of how the graphic was captured and should be disregarded.)

---

## PriceQuantityBasis [attribute]

The basis for the determination of the price.

*This item is restricted to the following list.*

attribute
<b>PriceQuantityBasis</b>
type   quantityType

### **ActualVolume**

Actual product space.

### **AirDryWeight**

Contains a normal amount of moisture.

### **Area**

A number that represents the length multiplied by the width is being communicated.

### **BoneDry**

Contains insignificant moisture.

### **Count**

The number of items.

### **Distance**

The quantity being communicated is a distance.

### **GrossWeight**

The weight including all packaging and furnishing. The gross weight of the deliveries is being used, includes tare weight.

### **Energy**

The quantity represents energy content.

### **Length**

The length of the object.

### **LogPileVolume**

The volume of a pile of logs, including gaps.

### **NetWeight**

The net weight of the product is being used, does not include tare weights. May include certain conversion components.

### **NetNetWeight**

The net weight of the product without any packaging or conversion materials.

### **NominalWeight**

A calculated weight that is derived from another measurement. For example, the length of paper multiplied by the specified basis weight could be used to derive a nominal weight.

### **Percent**

The number being communicated is a percentage.

# papiNet V2R31

---

## RunningLength

The length of the reel.

## ShortLengthVolume

## SolidWoodVolume

The volume of logs, stems, chips, etc. without bark and gaps.

## TareWeight

The weight of the previously agreed to packaging and furnishing.

## Time

The number being communicated represents an amount of time.

## TippedLooseVolume

The volume of tipped loose content, including gaps. Often used as a quantity type for piles of chips, sawdust, etc.

## Volume

## WoodVolume

The volume of logs, stems, chips, etc. without gaps but including bark.

---

## PriceTaxBasis [attribute]

This price provides the basis for tax.

*This item is restricted to the following list.*

Yes

No

attribute	
<b>PriceTaxBasis</b>	
type	yesNo
default	No

## PrintedMediaSpecs

Printed media specifications

### Perforated [attribute]

*Perforated is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Perforated definition for any enumerations.

### Scored [attribute]

*Scored is optional. A single instance might exist.*

Is this item scored?

Refer to Scored definition for any enumerations.

### Folded [attribute]

*Folded is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Folded definition for any enumerations.

### Collated [attribute]

*Collated is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Collated definition for any enumerations.

### RoundCornered [attribute]

*RoundCornered is optional. A single instance might exist.*

Is the item round cornered?

Refer to RoundCornered definition for any enumerations.

### Drilled [attribute]

*Drilled is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Drilled definition for any enumerations.

### DieCut [attribute]


*DieCut is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to DieCut definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



## NumberOfSides

*NumberOfSides is optional. A single instance might exist.*

The number of sides.

## DieCutDescription

*DieCutDescription is optional. A single instance might exist.*

Die cut description

## FlatSize

*FlatSize is optional. A single instance might exist.*

Flat size

## Wrap

*Wrap is optional. A single instance might exist.*

A group item that organises wrapping detail information.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.


---

## PrintingMaterials

Printing materials information.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### MaterialCharacteristics

*MaterialCharacteristics is mandatory. A single instance is required.*

Material characteristics.

### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## PrintParameters

PrintParameters is optional. The set up parameters of how a print machine or print job is within this construct.

### PrintType [attribute]

*PrintType is optional. A single instance might exist.*

Refer to PrintType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### WebConfiguration

*WebConfiguration is optional. A single instance might exist.*

The way the web runs through the press.

#### Webbing

*Webbing is optional. A single instance might exist.*

The webbing that is used in the printing process.

#### InkDelivery


*InkDelivery is optional. A single instance might exist.*

The delivery mechanism used in the printing process.

#### PasteDiameter

*PasteDiameter is optional. A single instance might exist.*

The diameter measurement of a reel when a new reel of paper is glued or pasted to it to continue running.



---

## PrintType [attribute]

*This item is restricted to the following list.*

### ColdsetOffset

An offset printing method suitable for newspapers, in other words, ink dries by penetration into the paper.

### ContinuousForms

An offset printing method, generally without a hot drying section and suitable for reels.

### Digital

An electrostatic printing method, typically a large black-and-white or multicolour printer/copier.

### Flexography

A special printing method, which is a follow-up of letter print with advanced print cylinder surface. Suitable for sheets.

## **FoilPrint**

A special printing/finishing method suitable for foils through embossed print plate/cylinder; flat/flat, or circle/flat (form to sheet).

## **Forms**

An offset printing method, generally without a hot drying section and suitable for sheets.

## **Gravure**

A standard printing method with embossed print cylinders. Suitable for sheets.

## **HeatsetOffset**

An offset printing method.

## **InkJet**

An inkjet printing method, typically a large black-and-white or multicolour printer.

## **InstantOffset**

A standard flat printing method (for example, wet offset, or waterless offset) suitable for small print orders and small sheet sizes (for example, max. DIN A3).

## **Laser**

A laser-based printing method, typically a large black-and-white or multicolour printer/copier.

## **Letterpress**

A special printing method suitable for books or newspapers (old style) with advanced letters. Suitable for sheets.

## **LightPrint**

- A printing method similar to a facsimile print, a photo-like print with a specific prepared cylinder surface on photo basis or an artificial print.

## **MiniWeb**

A digital printing method suitable for reels less than 20 inch wide.

## **RotoFlexography**

## **RotoGravure**

## **RotoLetterpress**

## **RotoSilkScreen**

## **SheetfedOffset**

## **SilkScreen**

## **WebOffset**

## PrintUnit

PrintUnit identifies the unique qualities associated with the individual unit of the printing press.

### PrintUnitType [attribute]

*PrintUnitType is optional. A single instance might exist.*

Print UnitT ype

Refer to PrintUnitType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### PrintUnitNumber

*PrintUnitNumber is mandatory. A single instance is required.*

The number of the print unit.

### Ink

*Ink is optional. Multiple instances might exist.*

A grouping element that describes the ink used in the process.

### Blanket


*Blanket is optional. Multiple instances might exist.*

Blanket is a group element that contains elements that describe this component of the printing process.

### Plate


*Plate is optional. Multiple instances might exist.*

The image carrying medium.



## PrintUnitNumber

The number of the print unit.




## PrintUnitType [attribute]

Print UnitT ype

*This item is restricted to the following list.*

**Upper**

**Lower**



---

## PriorityOrder [attribute]

Specifies the priority order of the item as a two digit positive integer. Value 1 is the highest priority.



---

## ProcessingCode

A code defining processing details for a product.

### Agency [attribute]


*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

- For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.



---

## ProcessingCodeSpecification

A grouping element specifying code and description for processing details.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### ProcessingCode


*ProcessingCode is mandatory. A single instance is required.*

A code defining processing details for a product.

### ProcessingDescription

*ProcessingDescription is optional. Multiple instances might exist.*

A text element describing processing details for a product.



---



## ProcessingDescription

A text element describing processing details for a product.



## Product

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Forest Wood, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### (sequence)

*The sequence of items below is mandatory. One instance is required, multiple instances might exist.*

### ProductIdentifier

*ProductIdentifier is mandatory. A single instance is required.*

Used to communicate the code of the article, in a variety of formats designated by the type.

### ProductDescription

*ProductDescription is optional. Multiple instances might exist.*

An element used to communicate a human readable description of the product in the language specified by the Language attribute.

### Classification

*Classification is optional. Multiple instances might exist.*

A group item that details the product classification according to a particular organization's scheme. An item across multiple classifications would still be recognized as the same item. Examples of some product classifications are: Containerboard, Pulp-Dissolving, or Newsprint.

### (choice)

*[choice] is optional because of choice construct.*

### BookManufacturing

*BookManufacturing is optional because of choice construct.*

BookManufacturing is a group element that contains the elements that describe the book manufacturing process.

## ForestWood

*ForestWood is optional because of choice construct.*

A grouping element with information about characteristics for Forest Wood products.

## LabelStock

*LabelStock is optional because of choice construct.*

LabelStock contains the attributes and characteristics that define the label stock product.

## Paper

*Paper is optional because of choice construct.*

A group item defining the characteristics of the paper product.

## Pulp

*Pulp is optional because of choice construct.*

A group item defining the characteristics of pulp that are not dependent on a particular conversion process.

## RecoveredPaper

*RecoveredPaper is optional because of choice construct.*

A group item defining the characteristics of recycled fibre that are not dependent on a particular conversion process.

## VirginFibre

*VirginFibre is optional because of choice construct.*

Virgin Fibre

## WoodProducts

*WoodProducts is optional because of choice construct.*

A grouping element for all wood products.

## ProductAttributes


The ProductAttributes element is the root element for the ProductAttributes e-Document.

The ProductAttributes e-Document provides the means to communicate information about products between business partners.

### ProductAttributesType [attribute]

*ProductAttributesType is mandatory. A single instance is required.*

The type of information being communicated in the ProductAttributes e-Document



Refer to ProductAttributesType definition for any enumerations.

## **ProductAttributesStatusType [attribute]**

*ProductAttributesStatusType is mandatory. A single instance is required.*

Defines the status of the entire ProductAttributes e-Document, in other words, at the root level

Refer to ProductAttributesStatusType definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **ProductAttributesHeader**

*ProductAttributesHeader is mandatory. A single instance is required.*

Information that applies to the entire ProductAttributes e-Document.

### **ProductAttributesLineItem**

*ProductAttributesLineItem is optional. Multiple instances might exist.*

A group element that contains data relevant to the Product described on the line item.

## ProductAttributesHeader

Information that applies to the entire ProductAttributes e-Document.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### ProductAttributesIssueDate

*ProductAttributesIssueDate is mandatory. A single instance is required.*

The Date and Time the ProductAttributes are issued. (Compare to ValidityPeriod.)

### TransactionHistoryNumber

*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the



document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

### SenderProductAttributesIdentifier

*SenderProductAttributesIdentifier is mandatory. A single instance is required.*

A unique identifier assigned to the combination of products, properties, and ReceivingParty that makes this list of ProductAttributes unique from the SendingParty's point of view. Subsequent ProductAttributes with updates will use this same identifier.

### SenderProductAttributesName

*SenderProductAttributesName is optional. A single instance might exist.*

The name given to the set of products sent in the ProductAttributes e-Document.

### SenderProductAttributesDescription


*SenderProductAttributesDescription is optional. Multiple instances might exist.*

An element containing free text used to describe the set of products sent in the ProductAttributes.

### OtherParty

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.



## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **ProductAttributesReference**

*ProductAttributesReference is optional. Multiple instances might exist.*

References that apply to the ProductAttributes e-Document, contains the ProductAttributesReferenceType attribute.

## **ValidityPeriod**

*ValidityPeriod is optional. A single instance might exist.*

The validity period for a specific item, e.g. the validity period for an e-Document.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **TermsAndDisclaimers**

*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.


---

## ProductAttributesIssueDate

The Date and Time the ProductAttributes are issued.  
(Compare to ValidityPeriod.)

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.


hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

**ProductAttributesLineItem**

A group element that contains data relevant to the Product described on the line item.



**ProductAttributesLineItemStatusType [attribute]**

*ProductAttributesLineItemStatusType is mandatory. A single instance is required.*

Defines the status of the ProductAttributesLineItem

Refer to ProductAttributesLineItemStatusType definition for any enumerations.

**MeasurementsAre [attribute]**

*MeasurementsAre is mandatory. A single instance is required.*

Used to define for a product whether the details provided are ranges and lists of properties, or whether they are discrete, single properties of the product.

Refer to MeasurementsAre definition for any enumerations.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

## **Product**

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **SupplierParty**

*SupplierParty is optional. Multiple instances might exist.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **MillParty**

*MillParty is optional. Multiple instances might exist.*

The organisation or business entity that actually produces the product.

## **OrderQuantities**

*OrderQuantities is optional. A single instance might exist.*

An element that contains the quantities that can be used for ordering.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **PriceDetails**

*PriceDetails is optional. A single instance might exist.*

An element that groups together price information.

## **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates the type of adjustment being communicated.

## **ValidityPeriod**

*ValidityPeriod is optional. A single instance might exist.*

The validity period for a specific item, e.g. the validity period for an e-Document.

## **EndUses**

*EndUses is optional. Multiple instances might exist.*

A text element used to express in human readable form a list of applicable end uses for a product. Examples of end uses are:

- Magazine
- Book
- Commercial print

etc

## **URL**

*URL is optional. Multiple instances might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

## **ProductAttributesProductURL**

*ProductAttributesProductURL is optional. A single instance might exist.*

The web address of information pertinent to a particular product.

## **TradeRegion**

*TradeRegion is optional. Multiple instances might exist.*

A geographic area for product availability communication.

## **SafetyAndEnvironmentalInformation**

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

## **TermsAndDisclaimers**

*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.

---

## **ProductAttributesLineItemStatusType [attribute]**

Defines the status of the ProductAttributesLineItem

<b>ProductAttributesLineItemStatusType</b>
type   productAttributesLineItemStatusType

*This item is restricted to the following list.*

### **Amended**

The supplied information is changed.

### **Cancelled**

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### **Original**

The supplied information is the first version of that information.

---


## **ProductAttributesProductURL**

The web address of information pertinent to a particular product.

<b>ProductAttributesProductURL</b>
type   anyURI

## ProductAttributesReference

References that apply to the ProductAttributes e-Document, contains the



ProductAttributesReferenceType attribute.

### ProductAttributesReferenceType [attribute]

*ProductAttributesReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to ProductAttributesReferenceType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.


---

## ProductAttributesReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an

existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.



---

## ProductAttributesStatusType [attribute]

Defines the status of the entire ProductAttributes e-Document, in other words, at the root level



*This item is restricted to the following list.*

### **Amended**

The supplied information is changed.

### **Cancelled**

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### **Original**

The supplied information is the first version of that information.

### **Replaced**

The supplied information is replacing earlier supplied information. The receiver should revalidate the information in their system based upon the entire information received.

---

## ProductAttributesType [attribute]

The type of information being communicated in the ProductAttributes e-Document



*This item is restricted to the following list.*

### **PriceList**

The information represents a price list.

### **ProductCrossReference**

The information contains product cross reference information

### **ProductProperties**

The information is a representation of the properties of the products.

---

## ProductBasisSizeType [attribute]

An attribute list that indicates the size of paper used as the base for the basis weight calculation



*This item is restricted to the following list.*

### **GramsPerSquareMeter**

The basis size type is in metric measurement of grams per square meter.

### **16x18**

The surface area of a ream (500 sheets) is 16x18 in inches.

### **17x22**

The surface area of a ream (500 sheets) is 17x22 in inches. This size is also

# papiNet V2R31

---

known as Bond.

## **20x26**

The surface area of a ream (500 sheets) is 20x26 in inches. This size is also known as Cover.

## **20x30**

The surface area of a ream (500 sheets) is 20x30 in inches.

## **22.5x22.5**

The surface area of a ream (500 sheets) is 22.5x22.5 in inches.

## **22.5x28.5**

The surface area of a ream (500 sheets) is 22.5x28.5 in inches.

## **24x26**

The surface area of a ream (500 sheets) is 24x26 in inches.

## **24x36**

The surface area of a ream (500 sheets) is 24x36 in inches. This size is also known as Newsprint.

## **25x38**

The surface area of a ream (500 sheets) is 25x38 in inches. This size is also known as Book.

## **25x40**

The surface area of a ream (500 sheets) is 25x40 in inches.

## **25.5x28.5**

The surface area of a ream (500 sheets) is 25.5x28.5 in inches.

## **25.5x30.5**

The surface area of a ream (500 sheets) is 25.5x30.5 in inches.

## **35.5x30.5**

The surface area of a ream (500 sheets) is 35.5x30.5 in inches.

## **1000SqFt**

The surface area of one sheet is 1000 square feet.

---


## **ProductDescription**

An element used to communicate a human readable description of the product in the language specified by the Language attribute.

### **Language [attribute]**

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.





## TotalInformationalQuantity

*TotalInformationalQuantity is optional. Multiple instances might exist.*

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

## ProductSummary

*ProductSummary is optional. A single instance might exist.*

Group of elements to provide summary information on product level.

## LengthSpecification


*LengthSpecification is optional. Multiple instances might exist.*

Length specification of the wood product.

## ProductIdentification

A grouping element designed to communicate product identification related to the parent element that contains this item.

**(sequence)**



*The sequence of items*

*below is mandatory. A single instance is required.*

### ProductIdentifier

*ProductIdentifier is mandatory. A single instance is required.*

Used to communicate the code of the article, in a variety of formats designated by the type.

### ProductDescription

*ProductDescription is optional. Multiple instances might exist.*


An element used to communicate a human readable description of the product in the language specified by the Language attribute.

## ProductIdentifier

Used to communicate the code of the article, in a variety of formats designated by the type.

### Agency [attribute]

*Agency is mandatory. A single instance is required.*



Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

## **ProductIdentifierType [attribute]**

*ProductIdentifierType is mandatory. A single instance is required.*

Provides a contextual definition to the product identifier value.

Refer to ProductIdentifierType definition for any enumerations.

---

## **ProductIdentifierType [attribute]**

Provides a contextual definition to the product identifier value.

*This item is restricted to the following list.*



### **BrandName**

A specific product brand name for which the owner or source is specified in the "@AssignedBy" attribute.

### **CatalogueNumber**

A unique reference for a product in a catalogue.

### **CustomsTariffNumber**

### **EAN8**

An 8-digit code that uniquely identifies an article. This is the European article-numbering scheme.

### **EAN13**

A 13-digit code that uniquely identifies an article. This is the European article-numbering scheme.

### **ExportHarmonisedSystemCode**

The Harmonised System Code is an international goods classification system developed by the Customs Co-operation Council.

USA: It is a 10-digit number, the first 6 of which compose the harmonised code. The remaining 4 digits represent statistical subdivisions. The schedule is a statistical classification of domestic and foreign commodities exported from the United States.

Canada: Canadians have adopted the scheme as a basis for a new Canadian Tariff and Statistical Classification System. The Canadian export number consists of 8 digits prefixed by "HS" and is shown in the format HS5911.31.10, for example.

### **FinishedGoodIdentifier**

Product Identifier assigned by an Agency, e.g. a Publisher, to identify the finished product.

### **GradeCode**

A specific product code for which the owner or source is specified in the "@AssignedBy" attribute.

### **GradeName**

A specific product name for which the owner or source is specified in the

"@AssignedBy" attribute (for example, ImprovedNewsprint-45-1479).

## **ImportHarmonisedSystemCode**

The Harmonised System Code is an international goods classification system developed by the Customs Co-operation Council.

USA: It is a 10-digit number, the first 6 of which compose the harmonised code. The remaining 4 digits represent statistical subdivisions. The schedule is a statistical classification of domestic and foreign commodities exported from the United States.

Canada: Canadians have adopted the scheme as a basis for a new Canadian Tariff and Statistical Classification System. The Canadian export number consists of 8 digits prefixed by "HS" and is shown in the format HS5911.31.10, for example.

## **ManufacturingGradeCode**

A specific grade code to the actual manufactured product which may be different to the grade code under which the product is sold.. These codes generally refer to a product manufactured on a pulp or paper machine.

## **ManufacturingGradeName**

A specific grade name assigned to the actual manufactured product which may be different to the grade name under which the product is sold. These codes generally refer to a product manufactured on a pulp or paper machine.

## **Ondule**

A product code issued by the Groupement Ondulé, which is the European Association of Corrugated Base Papers Manufacturers.

## **PartNumber**

An equivalent to the Stock Keeping Unit (SKU) for which the owner or source is specified in the "@AssignedBy" attribute. In other words, this code fully defines the product.

## **RFQPartNumber**

The part number communicated as part of the RFQ process. This may be a form of the RFQ number itself. This field is designed to handle the situation where there is no part number assigned to the particular blend of product characteristics.

## **SKU**

The Stock Keeping Unit that is assigned by the buyer or supplier and that includes all relevant information to make an individual item ready for shipping.

## **UPC**

The Universal Product Code administered by the Universal Code Council. Note: There are several formats used for this coding scheme.

## **Other**


Used for any other product identifier type that is not covered by the list.

## ProductionLastDateOfChange

The final Date and Time that a line item or delivery line may be amended or cancelled by the buyer.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.


hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.


## ProductionRunNumber

The ProductionRunNumber assigned by the issuer.



## ProductionStatus

A group item used to communicate the release of a delivery line number.



### ProductionStatusType [attribute]

*ProductionStatusType is mandatory. A single instance is required.*

Indicates whether the ordered quantities to which it refers are allowed to be produced.

When goods are free for delivery but the buyer wants to specify a more detailed DeliverySchedule, a CallOff is used.

PurchaseOrder - Typically, a buyer sets ProductionStatusType for an order to "Free", which means the seller can produce the product(s) on the order. A PurchaseOrder of type ReservationOrder is an exception because the buyer is booking capacity at the mill but not making a commitment to buy; for this type of order, the status is "NotFree". The buyer uses one or more ReleaseOrder(s) referring to the ReservationOrder to change the ProductionStatusType to "Free" for one or more products on the ReservationOrder.

The level of specification in the DeliverySchedule element is used will indicate whether the PurchaseOrder is "Free" for delivery.

Refer to ProductionStatusType definition for any enumerations.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### **ProductionLastDateOfChange**


*ProductionLastDateOfChange is optional. A single instance might exist.*

The final Date and Time that a line item or delivery line may be amended or cancelled by the buyer.

---

## **ProductionStatusType [attribute]**

Indicates whether the ordered quantities to which it refers are allowed to be produced.



When goods are free for delivery but the buyer wants to specify a more detailed DeliverySchedule, a CallOff is used.

PurchaseOrder - Typically, a buyer sets ProductionStatusType for an order to "Free", which means the seller can produce the product(s) on the order. A PurchaseOrder of type ReservationOrder is an exception because the buyer is booking capacity at the mill but not making a commitment to buy; for this type of order, the status is "NotFree". The buyer uses one or more ReleaseOrder(s) referring to the ReservationOrder to change the ProductionStatusType to "Free" for one or more products on the ReservationOrder.

The level of specification in the DeliverySchedule element is used will indicate whether the PurchaseOrder is "Free" for delivery.

*This item is restricted to the following list.*

### **Free**

The ordered quantities to which it refers can be produced, in other words, are free to make.

### **NotFree**

The ordered quantities to which it refers cannot be produced, in other words, are not free to make

## ProductPackaging

Defines the methods and materials used for packaging.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### QuantityInUnit


QuantityInUnit is optional. A single instance might exist.

Used to identify the number of items packed within this package unit.

#### UnitDimension

UnitDimension is optional. A single instance might exist.

Unit  
Dimension



#### Weight

Weight is optional. A single instance might exist.

The weight of the item.

#### PackageIDInformation

PackageIDInformation is optional. A single instance might exist.

Group element identifying a lumber (wood) package. The package name may also be communicated.

#### LabelCharacteristics

LabelCharacteristics is optional. Multiple instances might exist.

A group item that organises the labeling information.

#### StencilCharacteristics

StencilCharacteristics is optional. Multiple instances might exist.

A group element specifying attributes of a stencil to be applied to an item, and optional text.

#### BandCharacteristics

BandCharacteristics is optional. Multiple instances might exist.

A group item that organises the packaging band detail information.

#### PalletCharacteristics


PalletCharacteristics is optional. Multiple instances might exist.

A group item that provides pallet detail information.

#### Wrap

Wrap is optional. Multiple instances might exist.

A group item that organises wrapping detail information.



## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## PackageType

*PackageType is optional. A single instance might exist.*

Communicates the configuration of the item being reported.


Refer to PackageType definition for any enumerations.

## ProductPercentage

The quantity of a product in percentage of the total quantity for an item containing many products.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### Product

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

### Value

*Value is mandatory. A single instance is required.*


A numeric value expressed in the unit of measure (UOM).

## ProductPerformance

The ProductPerformance element is the root element for the ProductPerformance e-Document.

The ProductPerformance e-Document is created by the product consumer

in order to communicate back to the manufacturer the performance of the product. This e-Document will enable the manufacturer to focus on improvements related to product defects that create inefficiency during performance. The aggregation of performance



factors by product will provide the mechanism for achieving the value aspect of the e-Document. The goal is to keep the products of the Pulp & Paper Industry attractive versus competing alternatives.

## **ProductPerformanceStatusType [attribute]**

*ProductPerformanceStatusType is mandatory. A single instance is required.*

ProductPerformanceStatusType

Refer to ProductPerformanceStatusType definition for any enumerations.

## **Reissued [attribute]**

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **ProductPerformanceHeader**

*ProductPerformanceHeader is mandatory. A single instance is required.*

Information that applies to the entire ProductPerformance e-Document.

### **ProductPerformanceLineItem**

*ProductPerformanceLineItem is mandatory. One instance is required, multiple instances might exist.*

Information for each item in the ProductPerformance e-Document.

### **ProductPerformanceSummary**

*ProductPerformanceSummary is optional. A single instance might exist.*

Summary information for the items on the ProductPerformance e-Document

---

## **ProductPerformanceConcerns**

A grouping element used to hold information about the product performance concerns.

### **ConcernIndicatorType [attribute]**

ProductPerformanceConcerns

*ConcernIndicatorType is mandatory. A single instance is required.*

Either "Yes" or "No".


Refer to ConcernIndicatorType definition for any enumerations.

## **(choice)**

*[choice] is optional because of choice construct.*

### **WebConcerns**

*WebConcerns is optional because of choice construct.*



A grouping element that contains the information about a web break.

## SheeterConcerns

*SheeterConcerns is optional because of choice construct.*

SheeterConcerns is a group element that provides information about an event on a sheeter.

## PulpConcerns


*PulpConcerns is optional because of choice construct.*

If the ConcernIndicatorType is "Y" for a pulp related product then a defect cause must be give.

---

## ProductPerformanceConditions

The ProductPerformanceConditions, while not absolutely necessary to determine whether there is a product concern is available.



**(choice)**

*[choice] is optional because of choice construct.*

### PressConditions

*PressConditions is optional because of choice construct.*

Construct contains environmental conditions of the press during operations

### SheeterConditions

*SheeterConditions is optional because of choice construct.*

Identifies the environmental conditions when the sheet was printed on.

### MachineConditions

*MachineConditions is optional because of choice construct.*

A grouping element for all the environmental measurement at the time of the run.


---

## ProductPerformanceDate

The date the e-Document was issued.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

## ProductPerformanceHeader

Information that applies to the entire ProductPerformance e-Document.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### ProductPerformanceNumber

*ProductPerformanceNumber is mandatory. A single instance is required.*

The report number used to identify the entire ProductPerformance.

### ProductPerformanceIssueDate

*ProductPerformanceIssueDate is mandatory. A single instance is required.*

The date and time the ProductPerformance was issued.

### ProductPerformanceReference

*ProductPerformanceReference is optional. Multiple instances might exist.*

Reference back to another e-Document.

### EndUserParty

*EndUserParty is mandatory. A single instance is required.*

The party using, consuming, or converting the product. For example, a printer using paper reels for a print job for a publisher. The final ShipTo destination for a product is normally to the end user's facilities.

### SupplierParty

*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

### MillParty

*MillParty is optional. A single instance might exist.*

The organisation or business entity that actually produces the product.



### SenderParty

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

### ReceiverParty



# papiNet V2R31

---

*ReceiverParty is optional. A single instance might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.


---

## **ProductPerformanceIssueDate**

The date and time the ProductPerformance was issued.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### **Date**

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### **Time**

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## ProductPerformanceLineItem

Information for each item in the ProductPerformance e-Document.

### ItemType [attribute]

*ItemType is mandatory. A single instance is required.*

Indicates the form of the item being



reported as being used. Many of the ItemType(s) indicated here have a corresponding named element equivalent, which is referenced here for definition purposes.

Refer to ItemType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ProductPerformanceLineItemNumber

*ProductPerformanceLineItemNumber is mandatory. A single instance is required.*

The line item identifying the one line being communicated from the Printer to Supplier.

#### ProductPerformanceReference

*ProductPerformanceReference is optional. Multiple instances might exist.*

Reference back to another e-Document.

#### Identifier

*Identifier is mandatory. One instance is required, multiple instances might exist.*

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.


#### LocationParty

*LocationParty is optional. A single instance might exist.*

The organization or business entity where the business event took place or will take place.

#### PrintParameters

*PrintParameters is optional. A single instance might exist.*



# papiNet V2R31

---

PrintParameters is optional. The set up parameters of how a print machine or print job is within this construct.

## **JobInformation**

*JobInformation is optional. A single instance might exist.*

JobInformation is optional. This construct captures information specific to the entire job set up.

## **Machine**

*Machine is optional. A single instance might exist.*

Machine is used to capture information specific to the particular machine used in the conversion or consumption process.

## **Product**

*Product is optional. A single instance might exist.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **ProductPerformanceConditions**

*ProductPerformanceConditions is mandatory. A single instance is required.*

The ProductPerformanceConditions, while not absolutely necessary to determine whether there is a product concern is available.

## **ProductPerformanceConcerns**

*ProductPerformanceConcerns is mandatory. A single instance is required.*

A grouping element used to hold information about the product performance concerns.

## **ProductPerformanceDate**

*ProductPerformanceDate is mandatory. A single instance is required.*

The date the e-Document was issued.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **ProductPerformanceLineItemNumber**

The line item identifying the one line being communicated from the Printer to Supplier.

<b>ProductPerformanceLineItemNumber</b>
type   lineNumberType

---

## ProductPerformanceNumber

The report number used to identify the entire ProductPerformance.

ProductPerformanceNumber	
type	s30

---

## ProductPerformanceReference

Reference back to another e-Document.

### ProductPerformanceReferenceType [attribute]

ProductPerformanceReference	
type	s255

attributes	
ProductPerformanceReferenceType	
type	referenceType
AssignedBy	
type	partyType

*ProductPerformanceReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to ProductPerformanceReferenceType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## ProductPerformanceReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

attribute	
ProductPerformanceReferenceType	
type	referenceType

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## ProductPerformanceStatusType [attribute]

ProductPerformanceStatusType


*This item is restricted to the following list.*

### Original

The supplied information is the first version of that information.

### Replaced

The supplied information is replacing earlier supplied information. The receiver should revalidate the information in their system based upon the entire information received.




## ProductPerformanceSummary

Summary information for the items on the ProductPerformance e-Document

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### TotalNumberOfLineItems

*TotalNumberOfLineItems is optional. A single instance might exist.*

The total number of individual line items in the document, regardless of the status or type.

### TotalQuantity

*TotalQuantity is optional. A single instance might exist.*

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

### TotalInformationalQuantity

*TotalInformationalQuantity is optional. Multiple instances might exist.*

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

### TermsAndDisclaimers

*TermsAndDisclaimers is optional. Multiple instances might exist.*


An element that contains legal information with an indication of what the Language is.

## ProductQuality

The ProductQuality element is the root element for the ProductQuality e-Document.

The

ProductQuality e-Document supports the exchange of quality data for individual items. The agreed properties of the product that are exchanged can include statistical values such as minimum and maximum, standard deviation, sample size, two sigma (lower-limit, upper-limit).



### ProductQualityStatusType [attribute]

*ProductQualityStatusType is mandatory. A single instance is required.*

Communicates the status of the ProductQuality e-Document

Refer to ProductQualityStatusType definition for any enumerations.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ProductQualityHeader

*ProductQualityHeader is mandatory. A single instance is required.*

Information the common to all items on the ProductQuality e-Document.

### (choice)

*[choice] is optional because of choice construct.*

#### ProductQualityPeriod

*ProductQualityPeriod is optional because of choice construct.*

ProductQualityPeriod

#### ProductQualityPurchaseOrder

*ProductQualityPurchaseOrder is optional because of choice construct.*

Multiple instances of purchase order information is allowed to support a list of purchase orders manufactured during the indicated period. Alternatively, ProductQualityPeriod may be repeated with the same TimePeriod for each PurchaseOrder if the quality data is available at this level of detail.

## ProductQualityShipment

*ProductQualityShipment is optional because of choice construct.*

Product quality information communicated by shipment.

## ProductQualityHeader

Information the common to all items on the ProductQuality e-Document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### ProductQualityIssueDate

*ProductQualityIssueDate is mandatory. A single instance is required.*

The date and time the ProductQuality was issued.

### ProductQualityMessageNumber

*ProductQualityMessageNumber is mandatory. A single instance is required.*

A unique identifier assigned to each e-Document for identification purposes.

Subsequent ProductQuality e-Documents with updates or cancellations will use this same ProductQualityMessageNumber.

### RequestNumber

*RequestNumber is optional. A single instance might exist.*

A unique tracking number specifically identifying the InfoRequest e-Document to the originator. The tracking number is returned with the "information", the answer, to help match the answer to the request.

### TransactionHistoryNumber

*TransactionHistoryNumber is optional. A single instance might exist.*


A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

### SenderParty

*SenderParty is mandatory. A single instance is required.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the



message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **BuyerParty**

*BuyerParty is optional. A single instance might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## **SupplierParty**

*SupplierParty is optional. A single instance might exist.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **ProductQualityReference**

*ProductQualityReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the ProductQuality.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **TermsAndDisclaimers**

*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.


---

## ProductQualityIssueDate

The date and time the ProductQuality was issued.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

---

## ProductQualityMessageNumber

A unique identifier assigned to each e-Document for identification purposes. Subsequent ProductQuality e-Documents with updates or cancellations will use this same ProductQualityMessageNumber.



## ProductQualityPeriod

ProductQualityPeriod

(sequence)

The sequence of items below is mandatory. A single instance is required.

### TimePeriod

TimePeriod is mandatory. A single instance is required.

The TimePeriod element is used to communicate a duration period of time as indicated in PeriodType.

### Product

Product is mandatory. A single instance is required.

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and



Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

(sequence)

The sequence of items below is optional. Multiple instances might exist.


### PurchaseOrderInformation

PurchaseOrderInformation is mandatory. A single instance is required.

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

### PurchaseOrderLineItemNumber

PurchaseOrderLineItemNumber is optional. A single instance might exist.



The sequential number that uniquely identifies the PurchaseOrder line item.

**(sequence)**

*The sequence of items below is optional. A single instance might exist.*

**LocationParty**

*LocationParty is mandatory. A single instance is required.*

The organization or business entity where the business event took place or will take place.

**MachineID**

*MachineID is optional. A single instance might exist.*

An identifier assigned to the particular machine being referenced. For example, a machine could be a paper machine, an off-line coater, a sheeter, or a printing press. The particular machine being referenced will be determined by the business event being supported.

**ShipToParty**

*ShipToParty is optional. A single instance might exist.*

The name and/or address to which the goods should be delivered with the party type indicated by the PartyType attribute.

**EndUserParty**

*EndUserParty is optional. A single instance might exist.*

The party using, consuming, or converting the product. For example, a printer using paper reels for a print job for a publisher. The final ShipTo destination for a product is normally to the end user's facilities.

**ProductQualityReference**

*ProductQualityReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the ProductQuality.

**Quantity**

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

**InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

**(sequence)**

*The sequence of items below is optional. A single instance might exist.*

**StartIdentifierRange**

*StartIdentifierRange is mandatory. A single instance is required.*

An element that identifies the starting item identifier in the range of items that contributed to the aggregated measurements for the range.

## **EndIdentifierRange**

*EndIdentifierRange is mandatory. A single instance is required.*

A group element that identifies the ending item identifier in the range of items that contributed to the aggregated measurements for the range.

### **(choice)**

*[choice] is optional because of choice construct.*

## **PaperCharacteristics**

*PaperCharacteristics is optional because of choice construct.*

The identifying characteristics of paper most important to the ordering of the item. These are the characteristics that, when associated with a given grade, allow the manufacturer to produce but not convert or package, the paper.

## **PulpCharacteristics**

*PulpCharacteristics is optional because of choice construct.*

The physical and chemical characteristics of the pulp product regardless of the form that it is taking.

## **RecoveredPaperAttributes**

*RecoveredPaperAttributes is optional because of choice construct.*

The attributes of Recovered Paper.

## **ItemDetails**

*ItemDetails is optional. Multiple instances might exist.*

A group element that identifies a specific item and measured attribute values for that item.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## ProductQualityPurchaseOrder

Multiple instances of PurchaseOrder information is allowed to support a list of purchase orders manufactured during the indicated period. Alternatively, ProductQualityPeriod may be repeated with the same TimePeriod for each PurchaseOrder if the quality data is available at this level of detail.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**PurchaseOrderInformation**

*PurchaseOrderInformation is mandatory. A single instance is required.*

A group item containing information unique to this PurchaseOrder, which



is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

**PurchaseOrderLineItemNumber**

*PurchaseOrderLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the PurchaseOrder line item.


**Product**

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

**(sequence)**

*The sequence of items below is optional. A single instance might exist.*



## **LocationParty**

*LocationParty is mandatory. A single instance is required.*

The organization or business entity where the business event took place or will take place.

## **MachineID**

*MachineID is optional. A single instance might exist.*

An identifier assigned to the particular machine being referenced. For example, a machine could be a paper machine, an off-line coater, a sheeter, or a printing press. The particular machine being referenced will be determined by the business event being supported.

## **ShipToParty**

*ShipToParty is optional. A single instance might exist.*

The name and/or address to which the goods should be delivered with the party type indicated by the PartyType attribute.

## **EndUserParty**

*EndUserParty is optional. A single instance might exist.*

The party using, consuming, or converting the product. For example, a printer using paper reels for a print job for a publisher. The final ShipTo destination for a product is normally to the end user's facilities.

## **TimePeriod**

*TimePeriod is optional. A single instance might exist.*

The TimePeriod element is used to communicate a duration period of time as indicated in PeriodType.

## **ProductQualityReference**

*ProductQualityReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the ProductQuality.

## **Quantity**

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **(choice)**

*[choice] is optional because of choice construct.*

## **PaperCharacteristics**

# papiNet V2R31

---

*PaperCharacteristics is optional because of choice construct.*

The identifying characteristics of paper most important to the ordering of the item. These are the characteristics that, when associated with a given grade, allow the manufacturer to produce but not convert or package, the paper.

## **PulpCharacteristics**

*PulpCharacteristics is optional because of choice construct.*

The physical and chemical characteristics of the pulp product regardless of the form that it is taking.

## **RecoveredPaperAttributes**

*RecoveredPaperAttributes is optional because of choice construct.*

The attributes of Recovered Paper.

## **ItemDetails**

*ItemDetails is optional. Multiple instances might exist.*

A group element that identifies a specific item and measured attribute values for that item.

## **AdditionalText**


*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **ProductQualityReference**

An element detailing relevant references pertaining to the ProductQuality.



### **ProductQualityReferenceType [attribute]**

*ProductQualityReferenceType is optional. A single instance might exist.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute `@AssignedBy` will communicate the information previously communicated in the prefix.

Refer to **ProductQualityReferenceType** definition for any enumerations.

### **AssignedBy [attribute]**


*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type `OrderNumber`.

Refer to **AssignedBy** definition for any enumerations.


## ProductQualityReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.



Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## ProductQualityRequestDetail



ProductQualityRequestDetail is a conditional element. Its existence is mutually exclusive with that of the InventoryStatusRequestDetail, OrderStatusRequestDetail, AvailabilityStatusRequestDetail, and PlanningRequestDetail.

### ProductQualityRequestDetailType [attribute]

*ProductQualityRequestDetailType is optional. A single instance might exist.*

Communicates the method in which the OrderStatus has been, or should be, summarized.

Refer to ProductQualityRequestDetailType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### SupplierParty

*SupplierParty is optional. Multiple instances might exist.*

# papiNet V2R31

---

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

**(choice)**

*[choice] is optional because of choice construct.*

**ShipToParty**

*ShipToParty is optional because of choice construct.*

The name and/or address to which the goods should be delivered with the party type indicated by the PartyType attribute.

**OtherParty**

*OtherParty is optional because of choice construct.*

An organisation or business entity other than those specifically detailed within a e-Document.

**(choice)**

*[choice] is optional because of choice construct.*

**ByPeriod**

*ByPeriod is optional because of choice construct.*

This element is mutually exclusive of ByQualifiedPurchaseOrderInformation and ByQualifiedDeliveryMessage.

**ByQualifiedPurchaseOrderInformation**

*ByQualifiedPurchaseOrderInformation is optional because of choice construct.*

ByQualifiedPurchaseOrderInformation is a conditional element. This element is mutually exclusive of ByPeriod and ByShipment. The use of the term "qualified" is to indicate that PurchaseOrderInformation is qualified by the use of PurchaseOrderLineNumber.

**ByQualifiedDeliveryMessage**

*ByQualifiedDeliveryMessage is optional because of choice construct.*

ByQualifiedDeliveryMessage is a conditional element. This element is mutually exclusive of ByQualifiedPurchaseOrderInformation and ByPeriod. The use of the term "qualified" is to indicate that DeliveryMessageNumber is qualified by the use of DeliveryMessageLineNumber.

---

## ProductQualityRequestDetailType [attribute]

Communicates the method in which the OrderStatus has been, or should be, summarized.

<b>ProductQualityRequestDetailType</b>
type   productQualityRequestDetailType

*This item is restricted to the following list.*

**ByPeriod**

ByPeriod is a conditional element. This element is mutually exclusive of ByQualifiedPurchaseOrderInformation and ByQualifiedDeliveryMessage.

**ByQualifiedPurchaseOrderInformation**

By a PurchaseOrder that has additional items associated with it. (The PO has been differentiated, or qualified, by these items.)

**ByShipment**

By shipment

**ProductQualityShipment**

Product quality information communicated by shipment.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**DeliveryMessageNumber**

*DeliveryMessageNumber is mandatory. A single instance is required.*

A unique delivery identifier assigned to each DeliveryMessage as agreed between the trading partners.

**DeliveryMessageLineItemNumber**

*DeliveryMessageLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the delivery line item.

**TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

**TransportUnitCharacteristics**


*TransportUnitCharacteristics is optional. A single instance might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

**Product**

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments



have defined their product characteristics and conversion features for implementation in papiNet.

**(sequence)**

*The sequence of items below is optional. A single instance might exist.*

**PurchaseOrderInformation**

*PurchaseOrderInformation is mandatory. A single instance is required.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

**PurchaseOrderLineItemNumber**

*PurchaseOrderLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the PurchaseOrder line item.

**(sequence)**

*The sequence of items below is optional. A single instance might exist.*

**LocationParty**

*LocationParty is mandatory. A single instance is required.*

The organization or business entity where the business event took place or will take place.

**MachineID**

*MachineID is optional. A single instance might exist.*

An identifier assigned to the particular machine being referenced. For example, a machine could be a paper machine, an off-line coater, a sheeter, or a printing press. The particular machine being referenced will be determined by the business event being supported.

**ShipToParty**

*ShipToParty is optional. A single instance might exist.*

The name and/or address to which the goods should be delivered with the party type indicated by the PartyType attribute.

**EndUserParty**

*EndUserParty is optional. A single instance might exist.*

The party using, consuming, or converting the product. For example, a printer using paper reels for a print job for a publisher. The final ShipTo destination for a product is normally to the end user's facilities.

**TimePeriod**

*TimePeriod is optional. A single instance might exist.*

The TimePeriod element is used to communicate a duration period of time as indicated in PeriodType.

**ProductQualityReference**

*ProductQualityReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the ProductQuality.

**Quantity**

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

### **(choice)**

*[choice] is optional because of choice construct.*

#### **PaperCharacteristics**

*PaperCharacteristics is optional because of choice construct.*

The identifying characteristics of paper most important to the ordering of the item. These are the characteristics that, when associated with a given grade, allow the manufacturer to produce but not convert or package, the paper.

#### **PulpCharacteristics**

*PulpCharacteristics is optional because of choice construct.*

The physical and chemical characteristics of the pulp product regardless of the form that it is taking.

#### **RecoveredPaperAttributes**

*RecoveredPaperAttributes is optional because of choice construct.*

The attributes of Recovered Paper.

## **ItemDetails**

*ItemDetails is optional. Multiple instances might exist.*

A group element that identifies a specific item and measured attribute values for that item.

### **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---


## **ProductQualityStatusType [attribute]**

Communicates the status of the ProductQuality e-Document

*This item is restricted to the following list.*

### **Cancelled**

The supplied information has been cancelled. Items that have been cancelled



are not included in totals on the summary levels of the e-Document.

## Original

The supplied information is the first version of that information.

## Replaced

The supplied information is replacing earlier supplied information. The receiver should revalidate the information in their system based upon the entire information received.


---

## ProductSummary

Group of elements to provide summary information on product level.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### TotalQuantity

*TotalQuantity is optional. A single instance might exist.*

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

### TotalInformationalQuantity

*TotalInformationalQuantity is optional. Multiple instances might exist.*

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.


---

## ProofApprovalDate

Date field indicating when proofs will be approved.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

# papiNet V2R31

---

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.


---

## ProofDueDate

Proof due date

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## ProofInformationalQuantity

ProofInformationalQuantity

### ProofType [attribute]

*ProofType is optional. A single instance might exist.*

Proof Type

Refer to ProofType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Quantity

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

### InformationalQuantity

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

### OtherParty

*OtherParty is optional. A single instance might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

### ProofApprovalDate

*ProofApprovalDate is optional. A single instance might exist.*

Date field indicating when proofs will be approved.

### ProofDueDate


*ProofDueDate is optional. A single instance might exist.*

Proof due date

### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*


A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## ProofType [attribute]

Proof Type

*This item is restricted to the following list.*



### **Blues**

Usually inexpensive, photographic proof from negatives where all colors are shown in blue.

### **ColorKey**

### **Cromalin**

A versatile toner based proofing system patented by Dupont that offers the broadest variety of process, Pantone®, fluorescent, pastel and metallic colors that work in a positive film environment.

### **CustomCromalin**

A customized version of the Dupont toner based proofing system.

### **DigitalProofs**

A digital proof is a color prepress proofing method where a job is printed from the digital file.

### **Dylux**

A DuPont Dylux® instant image proofing system that produces dry, instant image blueline proofs without processing.

### **FilmProofs**

### **FoldedGathered**

A folded, gathered assembly of prints.

### **InkDrawDown**

When printing a PMS match color on a colored paper, an ink draw-down involves the substitution of opaque white in the ink formula, increasing covering qualities of the ink.

### **Iris**

A large-format color printer from the Iris Graphics division of CreoScitex (www.creoscitex.com) that is used for digital proofing. Iris printers use a patented continuous ink jet technology to produce consistent, continuous-tone, photorealistic output on several varieties of paper, canvas, silk, linen and other low-fiber textiles. Iris prints are widely noted for their color accuracy and ability to match printing and proofing standards. They are also known for their low-cost consumables compared to other technologies.

### **MatchPrint**

### **PressProofs**

### **ReferenceCDCassette**


### **Samples**

### **T-Print**

### **Other**

## PropertyAverageValue

Specifies an average value for a property for a number of items. The property is defined by the attribute PropertyType. The attribute MeasuringMethod and AssignedBy can be used to clarified details for a how a property is measured or calculated, e.g. Diameter for a sawlog can be measured "Under Bark" or "Over Bark". The attribute MeasuringMethodType defines how the value is created, e.g. measured automatically, calculated etc.



### PropertyType [attribute]

*PropertyType is mandatory. A single instance is required.*

Defines the type of property for an item.

Refer to PropertyType definition for any enumerations.

### MeasuringMethodType [attribute]

*MeasuringMethodType is optional. A single instance might exist.*

Specifies how a measurement value is created.

Refer to MeasuringMethodType definition for any enumerations.

### MeasuringAgency [attribute]

*MeasuringAgency is optional. A single instance might exist.*

The agency defining measuring methods.

Refer to MeasuringAgency definition for any enumerations.

### MeasuringMethod [attribute]

*MeasuringMethod is optional. A single instance might exist.*

The method used to determine how the item under consideration is measured. Measuring methods are defined by the measuring agency.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

## PositionOnItem

*PositionOnItem is optional. A single instance might exist.*

Specifies a position on an item. The attribute PositionMeasuredFrom defines the reference point for the position

### (choice)

*Choice is mandatory. A single instance is required.*

#### BinaryValue

*BinaryValue is optional because of choice construct.*

A value in base-64-encoded binary format.

#### BooleanValue

*BooleanValue is optional because of choice construct.*

A value in boolean format.

#### DateTimeValue

*DateTimeValue is optional because of choice construct.*

A Date and Time value in the standard W3C xs:dateTime format.

#### NumericValue

*NumericValue is optional because of choice construct.*

A grouping element for a numeric value and its statistical measures.

#### TextValue

*TextValue is optional because of choice construct.*

A value in text format.

---

## PropertyType [attribute]

Defines the type of property for an item.

*This item is restricted to the following list.*

PropertyType	
type	propertyType

### BarkClassCode

Classification of bark. A Text value.

### BarkContent

The amount of bark content in an item. Often reported as a percentage. A Numeric value.

### BarkThickness

The double bark thickness of an item, e.g. bark thickness of a log measured across the diameter of the log on two sides. A Numeric value.

### BowDefectLength

The length of an item that can't be used because of a bow on the item. A Numeric value.

### BowDiameterReduction

Reduction of the small end diameter of an item because a bow is effecting the usability of the item. A Numeric value.

**BowHeight**

Bow height of an item. E.g. Maximum distance between cross sectional centre of a log and a straight line between centres of each log end. A Numeric value.

**BowLengthReduction**

Reduction of the length of an item because a bow is effecting the usability of the item. A Numeric value.

**DateProduction**

Date and time when an item was produced. A DateTime value.

**Diameter**

Diameter of an item. A Numeric value.

**DiameterClassCode**

The category class for the diameter of an item. A Text value.

**DiameterLargeEnd**

Diameter at largest end of a item, often referred to as butt diameter. A Numeric value.

**DiameterMid**

Diameter at mid point of an item. A Numeric value.

**DiameterReduction**

Diameter reduction of an item, value to reduce from the items actual diameter. A Numeric value.

**DiameterSmallEnd**

Diameter at smallest end of an item, often referred to as top diameter. A Numeric value.

**Dryness**

Amount of dry solids content. Expressed as percentage. A Numeric value.

**ForestRot**

The amount of an items content of rot originating from growing trees. A Numeric value.

**Height**

Height of an item. A Numeric value.

**Length**

Length of an item. A Numeric value.

**LengthClassCode**

The category class for the length of an item. A Text value.

**LengthReduction**

Length reduction of an item, value to reduce from the items actual length. A Numeric value.

**LoggingDamage**

Defines damages on a Forest Wood product caused by logging. These

damages normally cause an adjustment of the product price. A Text value.

## **Moisture**

Amount of moisture (water) in an item. It can be used for estimating of wood freshness. A Numeric value.

## **QualityClassCode**

The category class for the quality of an item. A Text value.

## **SolidWoodPercentage**

SolidWoodVolume expressed as a percentage of the measured volume of an item, e.g. a logpile. A Numeric value.

## **StorageRot**

The amount of an items content of rot caused by storage. A Numeric value.

## **SurfaceWithoutBark**

Surface of an item not covered by bark. Normally measured as percentage of the total surface area of the item. A Numeric value.

## **Taper**

Taper of an item, the difference in diameter over a length interval. A Numeric value.

## **TreeAge**

The age of a tree. A Numeric value.

## **TreeDiameterBreastHeight**

Diameter at breast height (1.3 m from ground) of a tree. A Numeric value.

## **TreeHeight**

Height of a tree from ground to the top of the tree. A Numeric value.

## **TreeLogOrder**

Log number based on order of logs from the stump and to the small end of the tree. A Numeric value.

## **TreeSpeciesGroupCode**


A code defining tree species or groups of tree species. A Text value.

## **Width**

Width of an item. A Numeric value.

## PropertyValue

Specifies a value for a property of an item. The property is defined by the attribute PropertyType. The attribute MeasuringMethod and AssignedBy can be used to clarified details for a how a property is measured or calculated, e.g. Diameter for a saw log can be measured "Under Bark" or "Over Bark". The attribute MeasuringMethodType defines how the value is created, e.g. measured automatically, calculated etc. The attribute IsAverageValue indicates if the value is an average value or not.



### PropertyType [attribute]

*PropertyType is mandatory. A single instance is required.*

Defines the type of property for an item.

Refer to PropertyType definition for any enumerations.

### MeasuringMethodType [attribute]

*MeasuringMethodType is optional. A single instance might exist.*

Specifies how a measurement value is created.

Refer to MeasuringMethodType definition for any enumerations.

### MeasuringAgency [attribute]

*MeasuringAgency is optional. A single instance might exist.*

The agency defining measuring methods.

Refer to MeasuringAgency definition for any enumerations.

### MeasuringMethod [attribute]

*MeasuringMethod is optional. A single instance might exist.*

The method used to determine how the item under consideration is measured. Measuring methods are defined by the measuring agency.

### IsAverageValue [attribute]

*IsAverageValue is optional. A single instance might exist.*

Indicates if the value is an average value or not.

Refer to IsAverageValue definition for any enumerations.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### PositionOnItem

*PositionOnItem is optional. A single instance might exist.*

Specifies a position on an item. The attribute PositionMeasuredFrom defines the reference point for the position

## (choice)

*Choice is mandatory. A single instance is required.*

### BinaryValue

*BinaryValue is optional because of choice construct.*

A value in base-64-encoded binary format.

### BooleanValue

*BooleanValue is optional because of choice construct.*

A value in boolean format.

### DateTimeValue

*DateTimeValue is optional because of choice construct.*

A Date and Time value in the standard W3C xs:dateTime format.

### NumericValue

*NumericValue is optional because of choice construct.*

A grouping element for a numeric value and its statistical measures.

### TextValue

*TextValue is optional because of choice construct.*

A value in text format.


---

## Pulp

A group item defining the characteristics of pulp that are not dependent on a particular conversion process.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### PulpCharacteristics

*PulpCharacteristics is optional. A single instance might exist.*

The physical and chemical characteristics of the pulp product regardless of the form that it is taking.

## (choice)

*[choice] is optional because of choice construct.*

## **Bale**

*Bale is optional because of choice construct.*

A single or rectangular grouping of product

## **Reel**

*Reel is optional because of choice construct.*

A group item that contains the conversion and packaging characteristics of a reel.

## **Slurry**

*Slurry is optional because of choice construct.*

Product that has moisture content high enough to prevent formation of a sheet, and which can be delivered in liquid form.

Examples:

Product that has moisture content high enough to prevent formation of a sheet, and which can be delivered in liquid form. Examples: Noodle pulp, is pumped into trucks as thick slurry, and then pumped directly into the hydropulper. It has the higher strength properties of never dried pulp.

Product that has moisture content high enough to prevent formation of a sheet, and which can be delivered in liquid form. Examples: Noodle pulp, is pumped into trucks as thick slurry, and then pumped directly into the hydropulper. It has the higher strength properties of never dried pulp. Liquid pulp, never dried pulp, often pumped directly, using a flow meter to measure the moisture and fibre content. Sold by weight of the fibre.

## **NonStandardPulp**

*NonStandardPulp is optional because of choice construct.*

The characteristics of the form that pulp in a nonstandard presentation takes.

## PulpCharacteristics

The physical and chemical characteristics of the pulp product regardless of the form that it is taking.

### **PulpingProcess [attribute]**

*PulpingProcess is optional. A single instance might exist.*

Communicates the pulping method used to produce the pulp fibre

Refer to PulpingProcess definition for any enumerations.

### **BleachingProcess [attribute]**

*BleachingProcess is optional. A single instance might exist.*

Communicates the type of bleaching process used to make the pulp fibre

Refer to BleachingProcess definition for any enumerations.

### **FibreSource [attribute]**

*FibreSource is optional. A single instance might exist.*

Communicates the source of the pulp fibre

Refer to FibreSource definition for any enumerations.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

#### **Ash**

*Ash is optional. Multiple instances might exist.*

A group item used to communicate the ash content of the product according to a particular TestMethod.

#### **BasisWeight**

*BasisWeight is optional. Multiple instances might exist.*

The weight of the paper expressed as a mass for a given surface area. In countries using the metric system, the basis weight is expressed as the weight in grams of one sheet of paper that is one square meter in area—not dependent on basic sheet size. In countries using the imperial system, the weight is expressed in pounds for a given ProductBasisSizeType.

#### **Brightness**

*Brightness is optional. Multiple instances might exist.*

A measurement of the degree of light reflectivity of the product.

#### **Burst**

*Burst is optional. Multiple instances might exist.*

A group item used to communicate bursting strength target or test value according to a particular TestMethod.

#### **BurstIndex**

*BurstIndex is optional. Multiple instances might exist.*



The burst index.

## **ColourDetail**

*ColourDetail is optional. Multiple instances might exist.*

A group item used to communicate details of colour according to the selected colour definition scheme.

## **Density**

*Density is optional. Multiple instances might exist.*

A group item used to communicate density target or test value according to a particular TestMethod.

## **Dirt**

*Dirt is optional. Multiple instances might exist.*

A group item used to communicate dirt content target or test value according to a particular TestMethod.

## **DrainageResistance**

*DrainageResistance is optional. Multiple instances might exist.*

A group item used to communicate drainage resistance target or test value.

## **FibreLength**

*FibreLength is optional. Multiple instances might exist.*

A group item used to communicate fibre length target or test value according to a particular TestMethod.

## **FibreClassification**

*FibreClassification is optional. Multiple instances might exist.*

A group item used to communicate fibre classification according to the specified classification scheme.

## **Freeness**

*Freeness is optional. Multiple instances might exist.*

Freeness

## **LightScattering**

*LightScattering is optional. Multiple instances might exist.*

A group item used to communicate light scattering coefficients according to a particular TestMethod.

## **Moisture**

*Moisture is optional. Multiple instances might exist.*

Desired percentage, or other indicator, of water in the product at the time of shipment.

## **Opacity**

*Opacity is optional. Multiple instances might exist.*

A group item used to communicate opacity target or test value according to a particular TestMethod.

## **pH**

*pH is optional. Multiple instances might exist.*

A group item used to communicate pH (degree of acidity versus basicity) target or

test value according to a particular TestMethod.

## **PostConsumerWaste**

*PostConsumerWaste is optional. Multiple instances might exist.*

A group item used to communicate the target or test value percentage of post consumer waste fibre in the product according to a particular TestMethod.

## **PreConsumerWaste**

*PreConsumerWaste is optional. Multiple instances might exist.*

A group item used to communicate the target or test value percentage of pre-consumer waste fibre in the product according to a particular TestMethod.

## **Recycled**

*Recycled is optional. Multiple instances might exist.*

A group item used to communicate the target or test value total percentage of waste fibre in the product according to a particular TestMethod.

## **Tear**

*Tear is optional. Multiple instances might exist.*

A group item used to communicate tearing resistance target or test value according to a particular TestMethod.

## **TearIndex**

*TearIndex is optional. Multiple instances might exist.*

TearIndex

## **Tensile**

*Tensile is optional. Multiple instances might exist.*

A group item used to communicate zero-span tensile strength target or test value according to a particular TestMethod.

## **TensileIndex**

*TensileIndex is optional. Multiple instances might exist.*

Tensile Index

## **Viscosity**

*Viscosity is optional. Multiple instances might exist.*

Viscosity

## **Whiteness**

*Whiteness is optional. Multiple instances might exist.*

A group item used to communicate degree of whiteness target or test value according to a particular TestMethod.

## **AdditionalTest**

*AdditionalTest is optional. A single instance might exist.*


AdditionalTest exists to enable the inclusion of a test that has not been identified by papiNet.org. It is always a single-instance element so it is very important that users, who come upon a test that papiNet.org has not identified, communicate the need for this test to us at [www.papiNet.org](http://www.papiNet.org).

## PulpConcernCode

A group of codes that qualifies the defect or issue with a particular unit of pulp.

### Agency [attribute]

Agency is mandatory. A single instance is required.



Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.


For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

## PulpConcernDescription

A narrative to correspond to the concern code.



## PulpConcerns

If the ConcernIndicatorType is "Y" for a pulp related product then a defect cause must be give.

### MachineStoppage [attribute]

MachineStoppage is optional. A single instance might exist.

An indicator on whether the production had to be periodically stopped.

Refer to MachineStoppage definition for any enumerations.

### (sequence)


The sequence of items below is mandatory. A single instance is required.

### PulpConcernCode

PulpConcernCode is mandatory. One instance is required, multiple instances might exist.

A group of codes that qualifies the defect or issue with a particular unit of pulp.

### PulpConcernDescription



*PulpConcernDescription is optional. Multiple instances might exist.*

A narrative to correspond to the concern code.

## **EventDate**

*EventDate is optional. A single instance might exist.*

The date the incident or delay on press was recorded.

## **MachineDownTime**

*MachineDownTime is optional. A single instance might exist.*

The length of loss production time that a machine experienced due to malfunction regardless of cause.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **PulpingProcess [attribute]**

Communicates the pulping method used to produce the pulp fibre

*This item is restricted to the following list.*



### **ChemicalPulp**

In chemical pulping, wood is cooked in a digester at elevated pressure with a solution of the appropriate chemicals which dissolve the lignin and leave behind the cellulose.

### **ChemoThermoMechanicalPulp**

Semi-chemical pulping process uses a combination of chemical, thermal and mechanical methods. The wood chips are partially cooked with chemicals, then heated, and the remainder of the pulping is accomplished mechanically.

### **DeinkedPulp**

Pulp produced from deinked wastepaper, like old newsprint and old magazines.

### **RefinerGroundwood**

Mechanical pulping process where the wood is pressed against a grinder which physically separates the fibers.

### **StoneGroundwood**

The oldest of the large scale methods of pulping, dating back to the late 1840's is the groundwood process, in which debarked logs are forced against a huge revolving abrasive stone which shreds the fibres from the wood.

### **ThermoMechanical**

This process, which reached commercial viability in the early 1970's, involves an initial stage in which wood chips, before entering a pressurized refiner, are softened by steam. This facilitates the separation of the cellulose and reduces damage to the individual fibres.

## PulpUnitCharacteristics

A group element that contains information primarily of use for ordering.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PackagingDescription

*PackagingDescription is optional. A single instance might exist.*

A text field element describing the packaging of a product.

#### Wrap

*Wrap is optional. A single instance might exist.*

A group item that organises wrapping detail information.

#### PalletCharacteristics

*PalletCharacteristics is optional. A single instance might exist.*

A group item that provides pallet detail information.

#### BalesPerUnit

*BalesPerUnit is optional. A single instance might exist.*

The number of bales included on the shipping, handling, or delivery unit.

#### LayersPerUnit

*LayersPerUnit is optional. A single instance might exist.*

The number of layers on the shipping, handling, or delivery unit. (This element uses pattern matching to ensure the appropriate format for latitude.)

#### LabelCharacteristics

*LabelCharacteristics is optional. A single instance might exist.*

A group item that organises the labeling information.

#### StencilCharacteristics

*StencilCharacteristics is optional. Multiple instances might exist.*

A group element specifying attributes of a stencil to be applied to an item, and optional text.

#### MaximumGrossWeight


*MaximumGrossWeight is optional. A single instance might exist.*

The maximum weight allowed including the pallet.

#### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*


A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific



elements.

## PunchedHoleDetails

A grouping element that will contain the configuration information for punched holes.



*The sequence of items below is mandatory. A single instance is required.*

### NumberOfHoles

*NumberOfHoles is optional. A single instance might exist.*

The number of holes punched in a sheet of paper.

### HoleReinforcement

*HoleReinforcement is optional. A single instance might exist.*

Hole reinforcement

Refer to HoleReinforcement definition for any enumerations.

### (choice)

*[choice] is optional because of choice construct.*

### HolePunchType

*HolePunchType is optional because of choice construct.*

Hole punch type.

Refer to HolePunchType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### StandardSpacing

*StandardSpacing is optional. A single instance might exist.*

Is the spacing standard?

Refer to StandardSpacing definition for any enumerations.

### SizeOfHolePunch

*SizeOfHolePunch is optional. A single instance might exist.*

A definition of the size and shape of the punched holes.

### HoleSpacing

*HoleSpacing is optional. A single instance might exist.*

The HoleSpacing element is used to communicate the distance between holes.

## DistanceFromEdge

*DistanceFromEdge is optional.*

The distance from the edge of the paper. This element is used to communicate where the hole is.

## HolePunchTemplateReference

*HolePunchTemplateReference is optional. Multiple instances might exist.*


Hole punch template reference

## PurchaseOrder

The PurchaseOrder element is the root element for the PurchaseOrder e-Document.

A buyer sends a PurchaseOrder e-Document to a supplier to initiate a trade transaction. This e-Document, which is a request for product, usually represents a firm commitment to buy. (For one type of PurchaseOrder, called a reservation order, the PurchaseOrder is not a firm commitment to buy).

**PurchaseOrder**



### PurchaseOrderType [attribute]

*PurchaseOrderType is mandatory. A single instance is required.*

Defines the type of PurchaseOrder issued.

Refer to PurchaseOrderType definition for any enumerations.

### PurchaseOrderStatusType [attribute]

*PurchaseOrderStatusType is mandatory. A single instance is required.*

Defines the status of the entire PurchaseOrder e-Document, in other words, at the root level

Refer to PurchaseOrderStatusType definition for any enumerations.

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an

addendum to the standard.

Refer to Language definition for any enumerations.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### **PurchaseOrderHeader**

*PurchaseOrderHeader is mandatory. A single instance is required.*

The header level of information for the PurchaseOrder containing information that relates to the entire PurchaseOrder.

### **PurchaseOrderLineItem**

*PurchaseOrderLineItem is mandatory. One instance is required, multiple instances might exist.*

PurchaseOrderLineItem is a required, multiple instances element.

### **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates they type of adjustment being communicated.

### **PurchaseOrderSummary**

*PurchaseOrderSummary is optional. A single instance might exist.*

PurchaseOrderSummary is required and single instance.

---

## **PurchaseOrderDetail**

Multiple PurchaseOrderDetail instances are allowed.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### **PurchaseOrderInformation**




*PurchaseOrderInformation is optional. A single instance might exist.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

### **PurchaseOrderLineItemNumber**

*PurchaseOrderLineItemNumber is optional. A single instance might exist.*

The sequential number that uniquely identifies the PurchaseOrder line item.



## **Quantity**

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **DeliverySchedule**

*DeliverySchedule is optional. Multiple instances might exist.*

A group item defining a series of DeliveryDateWindow(s) in which specified quantities must be delivered.

## PurchaseOrderHeader

The header level of information for the PurchaseOrder containing information that relates to the entire PurchaseOrder.

### PurchaseOrderHeaderStatusType [attribute]

*PurchaseOrderHeaderStatusType is mandatory. A single instance is required.*

Defines the status of the PurchaseOrder header

Refer to PurchaseOrderHeaderStatusType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### PurchaseOrderInformation

*PurchaseOrderInformation is mandatory. A single instance is required.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

### TransactionHistoryNumber

*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.


### BuyerParty

*BuyerParty is mandatory. A single instance is required.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

### BillToParty

*BillToParty is optional. A single instance might exist.*



The address where the invoice is to be sent.

## **SupplierParty**

*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **ShipToCharacteristics**

*ShipToCharacteristics is mandatory. A single instance is required.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **OtherDate**

*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## **TransportModeCharacteristics**

*TransportModeCharacteristics is optional. A single instance might exist.*

A group item defining the primary mode of transport.

## **TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

## **TransportUnitCharacteristics**

*TransportUnitCharacteristics is optional. A single instance might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

### **TransportLoadingCharacteristics**

*TransportLoadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be loaded.

### **TransportUnloadingCharacteristics**

*TransportUnloadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be unloaded.

### **TransportOtherInstructions**

*TransportOtherInstructions is optional. Multiple instances might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

### **TermsOfPayment**

*TermsOfPayment is optional. Multiple instances might exist.*

A group item that contains agreed-to terms defining when, how, and under what conditions the payment is to be made.

When TermsOfPayment is optional; if omitted, TermsOfPayment is controlled through previous negotiation.

### **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **PurchaseOrderHeaderStatusType [attribute]**

Defines the status of the PurchaseOrder header

*This item is restricted to the following list.*

### **Amended**

The supplied information is changed.

### **Cancelled**

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### **New**

The supplied information is new and supplied for the first time.

### **NoAction**

The supplied information has not been amended and thereby requires no action.


attribute

**PurchaseOrderHeaderStatusType**

type purchaseOrderHeaderStatusType

## PurchaseOrderInformation

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.



### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### PurchaseOrderNumber

*PurchaseOrderNumber is optional. A single instance might exist.*

The unique order identifier as designated by the customer.

#### PurchaseOrderReleaseNumber

*PurchaseOrderReleaseNumber is optional. A single instance might exist.*

The version or release of the PurchaseOrder.

#### PurchaseOrderIssuedDate

*PurchaseOrderIssuedDate is optional. A single instance might exist.*

The Date and Time on which the PurchaseOrder was issued within the buyer's system.

#### PurchaseOrderReference

*PurchaseOrderReference is optional. Multiple instances might exist.*

An item detailing relevant references (such as contract number) pertaining to the PurchaseOrder. The type of reference is identified by the PurchaseOrderReferenceType attribute.

#### ServiceLevel

*ServiceLevel is optional. Multiple instances might exist.*

A grouping element containing information about a service level. The service level can be specified in a Service Level Agreement (SLA) detailing requirements such as delivery, performance, pricing, quality, etc.


---

## PurchaseOrderIssuedDate

The Date and Time on which the PurchaseOrder was issued within the buyer's system.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## PurchaseOrderLineItem

PurchaseOrderLineItem is a required, multiple instances element.

### PurchaseOrderLineItemStatusType [attribute]

*PurchaseOrderLineItemStatusType is mandatory. A single instance is required.*

Defines the status of the PurchaseOrder line item  
Refer to PurchaseOrderLineItemStatusType definition for any enumerations.

### PurchaseOrderLineItemDocumentStatus [attribute]

*PurchaseOrderLineItemDocumentStatus is optional. A single instance might exist.*

Defines the actual document status for the PurchaseOrderLineItem.

Refer to PurchaseOrderLineItemDocumentStatus definition for any enumerations.

### Billable [attribute]

*Billable is optional. A single instance might exist.*  
Either "Yes" or "No".

Refer to Billable definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PurchaseOrderLineItemNumber

*PurchaseOrderLineItemNumber is mandatory. A single instance is required.*

The sequential number that uniquely identifies the PurchaseOrder line item.

#### PurchaseOrderReference


*PurchaseOrderReference is optional. Multiple instances might exist.*

An item detailing relevant references (such as contract number) pertaining to the PurchaseOrder. The type of reference is identified by the PurchaseOrderReferenceType attribute.

#### Product

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper,



Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **PriceDetails**

*PriceDetails is optional. Multiple instances might exist.*

An element that groups together price information.

## **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates the type of adjustment being communicated.

## **LineBaseAmount**

*LineBaseAmount is optional. A single instance might exist.*

For the particular e-Document being communicated the LineBaseAmount represents the quantity times the base unit price.

## **MillCharacteristics**

*MillCharacteristics is optional. A single instance might exist.*

A group item defining the mill party and machine identifier where a product is or was produced.

## **Quantity**

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **TotalBlanketOrderValue**

*TotalBlanketOrderValue is optional. A single instance might exist.*

The authorized amount of the blanket PurchaseOrder.

## **ValidityPeriod**

*ValidityPeriod is optional. A single instance might exist.*

The validity period for a specific item, e.g. the validity period for an e-Document.

## **ProductionStatus**

*ProductionStatus is optional. A single instance might exist.*

A group item used to communicate the release of a delivery line number.

## **OtherDate**

*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **TransportModeCharacteristics**

*TransportModeCharacteristics is optional. A single instance might exist.*

A group item defining the primary mode of transport.

## **TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

## **TransportUnitCharacteristics**

*TransportUnitCharacteristics is optional. A single instance might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

## **TransportLoadingCharacteristics**

*TransportLoadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be loaded.

## **TransportUnloadingCharacteristics**

*TransportUnloadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be unloaded.

## **TransportOtherInstructions**

*TransportOtherInstructions is optional. Multiple instances might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

## **DeliverySchedule**

*DeliverySchedule is optional. Multiple instances might exist.*

A group item defining a series of DeliveryDateWindow(s) in which specified quantities must be delivered.

## **GeneralLedgerAccount**

# papiNet V2R31

---

*GeneralLedgerAccount is optional. A single instance might exist.*

The general ledger account to be referenced for the item.

## **EndUses**

*EndUses is optional. Multiple instances might exist.*

A text element used to express in human readable form a list of applicable end uses for a product. Examples of end uses are:

Magazine  
Book  
Commercial print  
etc

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **SafetyAndEnvironmentalInformation**

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

---

## **PurchaseOrderLineItemDocumentStatus [attribute]**

Defines the actual document status for the PurchaseOrderLineItem.

*This item is restricted to the following list.*

<i>attribute</i>
<b>PurchaseOrderLineItemDocumentStatus</b>
<i>type</i> documentStatusType.PurchaseOrder

### **Cancelled**

The supplied information of the document item is cancelled. Items that have been cancelled are not included in totals on the summary level of e- Documents.

### **Requested**

The supplied information of the document item is ordered.

---

## **PurchaseOrderLineItemNumber**

The sequential number that uniquely identifies the PurchaseOrder line item.

<b>PurchaseOrderLineItemNumber</b>
<i>type</i> lineNumberType

---

## PurchaseOrderLineItemStatusType [attribute]

Defines the status of the PurchaseOrder line item

*This item is restricted to the following list.*

### Amended

The supplied information is changed.

### Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### New

The supplied information is new and supplied for the first time.

### NoAction


The supplied information has not been amended and thereby requires no action.



---

## PurchaseOrderNumber



The unique order identifier as designated by the customer.



---

## PurchaseOrderReference

An item detailing relevant references (such as contract number) pertaining to the PurchaseOrder. The type of reference is identified by the



PurchaseOrderReferenceType attribute.

### PurchaseOrderReferenceType [attribute]

*PurchaseOrderReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to PurchaseOrderReferenceType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a

reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## PurchaseOrderReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

attribute
<b>PurchaseOrderReferenceType</b>
type   referenceType

---

## PurchaseOrderReleaseNumber

The version or release of the PurchaseOrder.

<b>PurchaseOrderReleaseNumber</b>
type   s30

---

## PurchaseOrderStatusType [attribute]

Defines the status of the entire PurchaseOrder e-Document, in other words, at the root level

*This item is restricted to the following list.*

### **Amended**

The supplied information is changed.

### **Cancelled**

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### **Original**

The supplied information is the first version of that information.


attribute
<b>PurchaseOrderStatusType</b>
type   purchaseOrderStatusType

## PurchaseOrderSummary

PurchaseOrderSummary is required and single instance

### (sequence)

The sequence of items below is mandatory. A single instance is required.



### TotalNumberOfLineItems

TotalNumberOfLineItems is optional. A single instance might exist.

The total number of individual line items in the document, regardless of the status or type.

### (sequence)

The sequence of items below is mandatory. One instance is required, multiple instances might exist.

### TotalQuantity

TotalQuantity is mandatory. A single instance is required.

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

### TotalInformationalQuantity

TotalInformationalQuantity is optional. Multiple instances might exist.

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

### TotalAmount

TotalAmount is optional. A single instance might exist.

A field containing the total amount including tax.

PurchaseOrder: The total amount, using a valid unit of measure of all the items in the e-Document. Multiple total amounts are allowed so different units of measure or grade sub-totals can be communicated.

CreditDebitNote and Invoice: TotalAmount is equal to TotalNetAmount plus TotalTaxAmount. In certain countries this is the amount that is due for payment based upon the terms of payment.

### TermsAndDisclaimers

TermsAndDisclaimers is optional. Multiple instances might exist.

An element that contains legal information with an indication of what the Language is.

## PurchaseOrderType [attribute]

Defines the type of PurchaseOrder issued.

*This item is restricted to the following list.*

attribute
<b>PurchaseOrderType</b>
type purchaseOrderType

### **BlanketOrder**

An order that communicates the same information as a StandardOrder but also indicates that the order may be completed over a period of time or, until a certain volume is achieved or, until a certain currency amount is spent.

### **ConfirmingOrder**

A confirming order is used to electronically confirm an order that has not been placed electronically by the customer that is, it was placed using another means such as fax, phone or email.

### **ConsumptionOrder**

A PurchaseOrder that is based upon consumption for a particular period of time or instance.

### **ReleaseOrder**

A release order is used to release a product to be made. This type of order refers to a previous order or agreement, such as a reservation order, a contract, or a blanket order. A release number version which is an incremented number, is used in this type.

### **ReservationOrder**

A reservation order is used to book a paper supplier's capacity for specific quantities of specific products, but it is not yet a firm commitment to buy. Consequently, all line items of a reservation order have a ProductionStatusType of NotFree. To release one or more PurchaseOrder line items of a reservation order, a buyer can use a standard order or a release order.

### **StandardOrder**

A standard order is a regular one-time order. It defines quantities for one or more products to be purchased and may also define a delivery location and date. A standard order may reference a previous agreement (for example, a quotation, a contract, or a reservation order) for information.

### **TrialOrder**

A trial order is used whenever a seller has agreed to have a buyer sample a product. The seller needs to process this order differently from other orders, because a trial order may include a product sold at a discounted rate or even provided for free. A trial order typically is for small quantities.


## PurchaseOrderWood

The PurchaseOrderWood element is the root element for the PurchaseOrderWood e-Document.

A PurchaseOrderWood e-Document is set up between a buyer and a seller. In some cases an agent acts on behalf of the seller or the buyer when setting up the contract.

However, the contract is not valid until signed by the buyer and the seller. A PurchaseOrderWood may cover one delivery of merchandise on one occasion or cover a time period with several deliveries. This PurchaseOrderWood refers to a standardised contract form containing all legal details.

**PurchaseOrderWood**



### OrderType [attribute]

*OrderType is mandatory. A single instance is required.*

Defines the type of PurchaseOrder issued.

Refer to OrderType definition for any enumerations.

### OrderContextType [attribute]

*OrderContextType is optional. A single instance might exist.*

Qualifies the source of the PurchaseOrder.

Refer to OrderContextType definition for any enumerations.

### OrderStatusType [attribute]

*OrderStatusType is mandatory. A single instance is required.*

Defines the status of the entire PurchaseOrder e-Document, in other words, at the root level

Refer to OrderStatusType definition for any enumerations.

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **PurchaseOrderWoodHeader**

*PurchaseOrderWoodHeader is mandatory. A single instance is required.*

PurchaseOrderWood Header

### **PurchaseOrderWoodProductGroup**

*PurchaseOrderWoodProductGroup is mandatory. One instance is required, multiple instances might exist.*

PurchaseOrderWoodProductGroup is a required, multiple instances element.

### **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount.

MonetaryAdjustment contains an attribute that indicates the type of adjustment being communicated.

### **PurchaseOrderWoodSummary**

*PurchaseOrderWoodSummary is optional. A single instance might exist.*

Summary section of PurchaseOrderWood for wood vertical.

**PurchaseOrderWoodHeader**

PurchaseOrderWood Header

**OrderHeaderStatusType [attribute]**

*OrderHeaderStatusType is mandatory. A single instance is required.*

Defines the status of the PurchaseOrder header

Refer to OrderHeaderStatusType definition for any enumerations.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



**PurchaseOrderInformation**

*PurchaseOrderInformation is mandatory. A single instance is required.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

**TransactionHistoryNumber**

*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

**OrderDocumentRequired**

*OrderDocumentRequired is optional. Multiple instances might exist.*


Group element used to identify any external documents that need to be referenced and how many of those documents are required. Typically, used to identify hard copy documents.

This element will be deprecated in the next version of papiNet. Use the DocumentInformation element instead.

**BuyerParty**

*BuyerParty is mandatory. A single instance is required.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.



## **BillToParty**

*BillToParty is optional. A single instance might exist.*

The address where the invoice is to be sent.

## **SupplierParty**

*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product.

SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **ShipToInformation**

*ShipToInformation is optional. A single instance might exist.*

Group element containing information about the ship to and delivery of a product.

## **CountryOfOrigin**

*CountryOfOrigin is optional. A single instance might exist.*

The country of origin for the material.

## **CountryOfDestination**

*CountryOfDestination is optional. A single instance might exist.*

The country where the goods will be, or were, shipped to.

## **CountryOfConsumption**

*CountryOfConsumption is optional. A single instance might exist.*

The country of consumption for the material.

## **TermsOfPayment**

*TermsOfPayment is optional. Multiple instances might exist.*

A group item that contains agreed-to terms defining when, how, and under what conditions the payment is to be made.

When TermsOfPayment is optional; if omitted, TermsOfPayment is controlled through previous negotiation.

## **ValidityPeriod**

*ValidityPeriod is optional. A single instance might exist.*

The validity period for a specific item, e.g. the validity period for an e-Document.

## **Insurance**

*Insurance is optional. A single instance might exist.*

Group element containing information about insurance

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **DocumentInformation**

*DocumentInformation is optional. Multiple instances might exist.*

A group element containing a specification of required documents in the business process. Additional free text to be printed on documents can also be specified.

**PurchaseOrderWoodLineItem**


PurchaseOrderWood Line Item

**OrderLineItemStatusType**  
[attribute]

*OrderLineItemStatusType is mandatory. A single instance is required.*

Defines the status of the PurchaseOrder line item

Refer to OrderLineItemStatusType definition for any enumerations.



**OrderLineItemDocumentStatus**  
[attribute]

*OrderLineItemDocumentStatus is optional. A single instance might exist.*

Defines the actual document status for the PurchaseOrderLineItem.

Refer to OrderLineItemDocumentStatus definition for any enumerations.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**PurchaseOrderLineItemNumber**

*PurchaseOrderLineItemNumber is mandatory. A single instance is required.*

The sequential number that uniquely identifies the PurchaseOrder line item.

**DocumentReferenceInformation**


*DocumentReferenceInformation is optional. Multiple instances might exist.*

A group item containing reference information applicable to a document.

**Product**

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market



segments have defined their product characteristics and conversion features for implementation in papiNet.

## **EndsDiscountInformation**

*EndsDiscountInformation is optional. A single instance might exist.*

Rule for calculating the ends discount, expressed by a code.

## **PriceDetails**

*PriceDetails is optional. Multiple instances might exist.*

An element that groups together price information.

## **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates the type of adjustment being communicated.

## **LineBaseAmount**

*LineBaseAmount is optional. A single instance might exist.*

For the particular e-Document being communicated the LineBaseAmount represents the quantity times the base unit price.

## **DeliveryDestination**

*DeliveryDestination is optional. A single instance might exist.*

The DeliveryDestination specifies the end of one leg of the delivery. In order to comply with the US Trade Act of 2002 you would use this element with a LocationParty/@PartyType of Port.

## **DeliveryOrigin**

*DeliveryOrigin is optional. A single instance might exist.*

A group item that represents the start of one leg in a route. Compare to DeliveryDestination.

The DeliveryOrigin specifies the start of one leg of the delivery.

In order to comply with the US Trade Act of 2002 you would use this element with a LocationParty/@PartyType of Port.

## **LocationParty**

*LocationParty is optional. Multiple instances might exist.*

The organization or business entity where the business event took place or will take place.

## **MillCharacteristics**

*MillCharacteristics is optional. A single instance might exist.*

A group item defining the mill party and machine identifier where a product is or was produced.

## **QuantityOrderedInformation**

*QuantityOrderedInformation is mandatory. A single instance is required.*

Used to identify quantity. The construct provides via InformationalQuantity the ability to provide the Quantity in another UOM. Length is also provided to further specify the quantity.

## **OtherDate**

*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## **TotalBlanketOrderValue**

*TotalBlanketOrderValue is optional. A single instance might exist.*

The authorized amount of the blanket PurchaseOrder.

## **ValidityPeriod**

*ValidityPeriod is optional. A single instance might exist.*

The validity period for a specific item, e.g. the validity period for an e-Document.

## **ProductionStatus**

*ProductionStatus is optional. A single instance might exist.*

A group item used to communicate the release of a delivery line number.

## **(choice)**

*[choice] is optional because of choice construct.*

### **ShipToInformation**

*ShipToInformation is optional because of choice construct.*

Group element containing information about the ship to and delivery of a product.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

#### **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

#### **DeliverySchedule**

*DeliverySchedule is optional. Multiple instances might exist.*

A group item defining a series of DeliveryDateWindow(s) in which specified quantities must be delivered.

## **CountryOfOrigin**

*CountryOfOrigin is optional. A single instance might exist.*

The country of origin for the material.

## **CountryOfDestination**

*CountryOfDestination is optional. A single instance might exist.*

The country where the goods will be, or were, shipped to.

## **CountryOfConsumption**

*CountryOfConsumption is optional. A single instance might exist.*

The country of consumption for the material.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **(choice)**

*[choice] is optional because of choice construct.*

### **PackageInformation**

*PackageInformation is optional because of choice construct.*

The purpose of the PackageInformation structure is to clearly identify physical handling items that constitute the delivery.

PackageInformation is the highest level of product packaging it describes the shipping or warehousing unit.

If you are communicating a package, usually for logistics or transport purposes, you should include the PackageType, Identifier, ItemCount, and Quantity. (Note: you still have the ability to describe the item with one of the "named" items.)

If you are communicating one of the named Items there is no need to include PackageType, Identifier, ItemCount, and Quantity.

Since either of these two approaches can be used the entire contents of this element are optional even though the parent may be required. It is expected that you will fill in the appropriate details.

### **TransportPackageInformation**

*TransportPackageInformation is optional because of choice construct.*

Information of a package used in transportation, can include several normal packages.

### **ProductSummary**

*ProductSummary is optional. A single instance might exist.*

Group of elements to provide summary information on product level.

### **LengthSpecification**

*LengthSpecification is optional. Multiple instances might exist.*

Length specification of the wood product.

### **QuantityDeviation**

*QuantityDeviation is optional. A single instance might exist.*

To be deprecated in a future version. Use the Quantity element with a QuantityContext of "Deviation".

### **EndUses**

*EndUses is optional. Multiple instances might exist.*

A text element used to express in human readable form a list of applicable end uses for a product. Examples of end uses are:

Magazine

Book

Commercial print

etc

### **SafetyAndEnvironmentalInformation**

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.


---

## **PurchaseOrderWoodProductGroup**

PurchaseOrderWoodProductGroup is a required, multiple instances element.

**(sequence)**

The



*sequence of items below is mandatory. A single instance is required.*

### **ProductGroupID**

*ProductGroupID is optional. A single instance might exist.*

Possibility to group packages or Shipments. Example: Creating temporary group ID's for logistic reasons or lot number.

### **PurchaseOrderWoodLineItem**

*PurchaseOrderWoodLineItem is mandatory. One instance is required, multiple instances might exist.*

PurchaseOrderWood Line Item

### **ProductGroupSummary**

*ProductGroupSummary is optional. A single instance might exist.*

Group of elements to provide summary information on product level.

## PurchaseOrderWoodSummary

Summary section of PurchaseOrderWood for wood vertical.

**(sequence)**

The sequence of items below is mandatory. A single instance is required.

**TotalNumberOfLineItems**

TotalNumberOfLineItems is optional. A single instance might exist.

The total number of individual line items in the document, regardless of the status or type.



**(sequence)**

The sequence of items below is optional. Multiple instances might exist.

**TotalQuantity**

TotalQuantity is mandatory. A single instance is required.

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

**TotalInformationalQuantity**

TotalInformationalQuantity is optional. Multiple instances might exist.

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

**ProductSummary**

ProductSummary is optional. A single instance might exist.

Group of elements to provide summary information on product level.

**LengthSpecification**

LengthSpecification is optional. Multiple instances might exist.

Length specification of the wood product.

**QuantityDeviation**


QuantityDeviation is optional. A single instance might exist.

To be deprecated in a future version. Use the Quantity element with a QuantityContext of "Deviation".

**TotalTaxAmount**

TotalTaxAmount is optional. A single instance might exist.

The CurrencyValue of TotalTaxAmount contains the sum of all instances of



TaxAdjustment in the document. TotalTaxAmount contains the sum of all instances of the MonetaryAdjustmentAmount for tax adjustments.

## **TotalAmount**

*TotalAmount is optional. A single instance might exist.*

A field containing the total amount including tax.

PurchaseOrder: The total amount, using a valid unit of measure of all the items in the e-Document. Multiple total amounts are allowed so different units of measure or grade sub-totals can be communicated.

CreditDebitNote and Invoice: TotalAmount is equal to TotalNetAmount plus TotalTaxAmount. In certain countries this is the amount that is due for payment based upon the terms of payment.

## **TermsAndDisclaimers**

*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## Quantity

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

### QuantityType [attribute]

*QuantityType is mandatory. A single instance is required.*

QuantityType communicates information about the type of quantity being communicated and how the receiver might use the information.

Refer to QuantityType definition for any enumerations.

### QuantityTypeContext [attribute]

*QuantityTypeContext is optional. A single instance might exist.*

Provides the location in the value chain where the quantity is being reported.

Refer to QuantityTypeContext definition for any enumerations.

### AdjustmentType [attribute]

*AdjustmentType is optional. A single instance might exist.*

Describes the type of adjustment associated with a quantity.

Refer to AdjustmentType definition for any enumerations.

### MeasuringMethodType [attribute]


*MeasuringMethodType is optional. A single instance might exist.*

Specifies how a measurement value is created.

Refer to MeasuringMethodType definition for any enumerations.

### MeasuringAgency [attribute]

*MeasuringAgency is optional. A single instance might exist.*



The agency defining measuring methods.

Refer to MeasuringAgency definition for any enumerations.

## MeasuringMethod [attribute]

*MeasuringMethod is optional. A single instance might exist.*

The method used to determine how the item under consideration is measured. Measuring methods are defined by the measuring agency.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)


---

## QuantityByProperty

A grouping element that contains specification of quantities per property value.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### PropertyValue

*PropertyValue is mandatory. Multiple instances might exist.*

Specifies a value for a property of an item. The property is defined by the attribute PropertyType. The attribute MeasuringMethod and AssignedBy can be used to clarified details for a how a property is measured or calculated, e.g. Diameter for a saw log can be measured "Under Bark" or "Over Bark". The attribute MeasuringMethodType defines how the value is created, e.g. measured automatically, calculated etc. The attribute IsAverageValue indicates if the value is an average value or not.

### QuantityInformation

*QuantityInformation is mandatory. A single instance is required.*

A group item containing information about quantity and informational quantity of similar items.

## QuantityDeviation

To be deprecated in a future version. Use the Quantity element with a QuantityContext of "Deviation".

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### Value

Value is mandatory. A single instance is required.

A numeric value expressed in the unit of measure (UOM).

#### RangeMin

RangeMin is optional. A single instance might exist.

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax


RangeMax is optional. A single instance might exist.

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

#### AdditionalText

AdditionalText is optional. A single instance might exist.

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## QuantityInformation

A group item containing information about quantity and informational quantity of similar items.

### (sequence)


The sequence of items below is mandatory. A single instance is required.

#### Quantity

Quantity is mandatory. A single instance is required.

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the



target.

## InformationalQuantity

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

---

## QuantityInUnit

Used to identify the number of items packed within this package unit.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



---

## QuantityOrderedInformation

Used to identify quantity. The construct provides via InformationalQuantity the ability to provide the Quantity in another UOM. Length is also provided to further specify the quantity.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Quantity

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular



quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **Length**


*Length is optional. Multiple instances might exist.*

The length of the object.

---

## **QuantityType [attribute]**

QuantityType communicates information about the type of quantity being communicated and how the receiver might use the information.



*This item is restricted to the following list.*

### **ActualVolume**

Actual product space.

### **AirDryWeight**

Contains a normal amount of moisture.

### **Area**

A number that represents the length multiplied by the width is being communicated.

### **BoneDry**

Contains insignificant moisture.

### **Count**

The number of items.

### **Distance**

The quantity being communicated is a distance.

### **GrossWeight**

The weight including all packaging and furnishing. The gross weight of the

deliveries is being used, includes tare weight.

## **Energy**

The quantity represents energy content.

## **Length**

The length of the object.

## **LogPileVolume**

The volume of a pile of logs, including gaps.

## **NetWeight**

The net weight of the product is being used, does not include tare weights. May include certain conversion components.

## **NetNetWeight**

The net weight of the product without any packaging or conversion materials.

## **NominalWeight**

A calculated weight that is derived from another measurement. For example, the length of paper multiplied by the specified basis weight could be used to derive a nominal weight.

## **Percent**

The number being communicated is a percentage.

## **RunningLength**

The length of the reel.

## **ShortLengthVolume**

## **SolidWoodVolume**

The volume of logs, stems, chips, etc. without bark and gaps.

## **TareWeight**

The weight of the previously agreed to packaging and furnishing.

## **Time**

The number being communicated represents an amount of time.

## **TippedLooseVolume**

The volume of tipped loose content, including gaps. Often used as a quantity type for piles of chips, sawdust, etc.

## **Volume**


## **WoodVolume**

The volume of logs, stems, chips, etc. without gaps but including bark.

---

## QuantityTypeContext [attribute]

Provides the location in the value chain where the quantity is being reported.



*This item is restricted to the following list.*

### **AgreedToClaimValue**

A quantity that has been agreed to as a result of a claim.

### **Allocated**

A quantity put aside, in general terms for a particular customer, process, or use. (Compare to "Reserved".)

### **AllowableSpoilage**

Specifies the manufacturing spoilage quantity that the publisher, or other involved party, will allow.

### **Balance**

A remaining quantity.

### **CalledOff**

A quantity put aside to be sent to the customer on a call off.

### **Consumed**

Consumed in manufacturing

### **Credited**

A quantity for which a credit has been issued.

### **CutOff**

A quantity that has been cut off.

### **Damaged**

A quantity that has been damaged.

### **Delivered**

Delivered to the ship-to location.

### **Destroyed**

The product, for secure reasons, has been made unusable both for content and the actual product.

### **Deviation**

Used to identify the deviation quantity accepted for this product.

Quantity deviation is partly an ancient/traditional thing in timber trade and refers more to sea transport than others. Quantity deviation can concern both line level quantities and total quantities. Total quantity deviation is meant to really restrict volumes to exceed ship's capacity.

Example Quantity deviations used for total quantities are:

CA./Max: for example, CA./max 1000 M3 = maximum quantity 1000 m3,  
but can be -10 % less (so 900 - 1000 m3 in this case)

Min but Max: for example, min 45 max 50 m3 = volume to be between 45

and 50

Min/Max: for example, min/max 500 m<sup>3</sup> = have to be roughly accurate 500 m<sup>3</sup>

CA: for example, CA 500 m<sup>3</sup> = +-10 % (450 - 550 m<sup>3</sup>)

In some contracts, at the line level, it is said that product level variation can be +- 10% (at the same time we can have deviation for total quantity)

For example: You can have +-10 % volumes in line levels but total quantity must meet the following requirement - Min/Max 1000 m<sup>3</sup>.

## **Freight**

The quantity to be used for freight costing.

## **Handled**

The quantity moved, e.g. in a warehouse, or otherwise handled in a logistics or material handling capacity.

## **Intransit**

A quantity that is undergoing the transportation process and is (usually) not available for immediate use.

## **Invoiced**

The number to be used when preparing the invoice.

## **Loaded**

A quantity that is loaded on a transport vehicle but has not left. That is, not in-transit yet.

Measured

A quantity that has been measured by a Measuring Party.

## **OnHand**

In available inventory at the storage location.

## **Ordered**

A PurchaseOrder has been placed for the product.

## **Packed**

A quantity that is prepared for storage or, transport or, some other state from which it has to be unpacked (work applied) in order to use it.

## **Planned**

Production is anticipated but has not yet taken place.

## **Produced**

The quantity added to stock through a manufacturing or conversion process.

## **Released**

The quantity that has been authorized to be moved on to the next stage or phase in the manufacturing process or supply chain.

## **Reorder**

A quantity that has been ordered.

**ReorderPoint**

A quantity on hand below which triggers a re-order.

**Reserved**

A quantity assigned to a specific customer order, job order, or delivery order. (Compare to "Allocated".)

**Scrapped**

Scrapped specifies that a product has been removed from inventory at the location where warehoused and has not been shipped to the owner.

**Stored**

The quantity refers to goods which have been stored in a warehouse, terminal etc.

**Tested**

A quantity that is analysed, e.g. the quantity of a random sample taken for measuring of product properties.

**Transported**

The quantity that is transported in logistics business.

**Trimmed**

A quantity that has been scheduled for production on a winder or a sheeter as part of the manufacturing process.

**Unloaded**

A quantity removed from a transport vehicle.

**UnspecifiedDamage**

Damage is being communicated in the element. In order to understand the type of damage the AdjustmentType will need to be considered.

**ValueClaimed**

A quantity that relates to the value claimed.

**VendorSupplied**

A quantity that is vendor supplied.

**Wound**

A quantity that has been placed in a reel form or otherwise put on a core.

**Wrapped**


A quantity that has been protectively covered in preparation for storage or shipment.

---

**QuoteInCurrency**

Indicates that the quote is to be provided in the currency specified.

A three-character ISO 4217 currency code in capital letters. The ISO standard classification for currencies.




Refer to the ISO standard for information about the choices for the attribute's enumerations.

---

## RangeMax

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## UOM [attribute]

*UOM is mandatory. A single instance is required.*

Defines the unit of measure for the value.

Refer to UOM definition for any enumerations.

---

## RangeMin


The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

## UOM [attribute]

*UOM is mandatory. A single instance is required.*

Defines the unit of measure for the value.

Refer to UOM definition for any enumerations.



---

## RawMaterialSet

This identifier derived element indicates a grouping of raw materials that were used to manufacture the product.

## IdentifierCodeType [attribute]

*IdentifierCodeType is mandatory. A single instance is required.*


Defines the type of product identifier used (for example, reel number, ream number, bar code). This code type specifies how to decode the identifier value.

Refer to IdentifierCodeType definition for any enumerations.

## IdentifierType [attribute]

*IdentifierType is mandatory. A single instance is required.*

This attribute specifies whether the Identifier is the primary way to



identify the product or a secondary way. Only one of the given identifiers can be primary. In addition, this attribute also specifies the physical support used to code the identifier (for example, a Radio Frequency (RF) Tag).

Refer to IdentifierType definition for any enumerations.

## IdentifierFormatType [attribute]

*IdentifierFormatType is optional. A single instance might exist.*

IdentifierFormatType defines the technical format used to make an IdentifierCodeType readable by technical devices or humans. The IdentifierCodeType specifies how to decode the identifier value

Refer to IdentifierFormatType definition for any enumerations.

---

## ReamItem

A wrapped quantity of SheetItem(s).

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Identifier

*Identifier is optional. Multiple instances might exist.*

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.

#### ItemCount

*ItemCount is mandatory. A single instance is required.*

A count of the number of items (examples: a count of the number of boxes on a pallet or of reams in a box).

#### Quantity


*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

#### InformationalQuantity

*InformationalQuantity is optional. Multiple instances might exist.*



# papiNet V2R31

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## SheetItem


*SheetItem is optional. A single instance might exist.*

A group item consisting potentially of the date the sheets were converted into sheets and/or packaged or finished.

---

## ReamType

The textual description of the method used to make up the reams..



*This item is restricted to the following list.*

### Any

Any ream type is acceptable

### BoxedWithInnerReam

Boxed with inner ream

### BoxedWithoutInnerReam

Boxed without inner ream

### BulkPackedNonTabbed

Sheets are packed without ream wrapping and without sheet count markers.

### BulkPackedTabbed

Sheets are packed without ream wrapping, but with sheet count markers at predefined intervals.

### ReamWrapped

Sheets are packed ream wrapped

---

## ReamWeight

The target weight of a ream of paper.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value


*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.



## RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)


## ReasonCode [attribute]

Free-form text providing the Reason Code for the item. An Agency attribute may exist at the same level as this attribute to provide an indication of the nature of the text.



## ReasonDescription


Text associated with a particular ReasonIdentifier



## ReceiverParty

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.



### PartyType [attribute]

*PartyType is mandatory. A single instance is required.*

Identifies the business role associated with the particular party

Refer to PartyType definition for any enumerations.

### LogisticsRole [attribute]

*LogisticsRole is optional. A single instance might exist.*

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

## **PartyIdentifier**

*PartyIdentifier is optional. Multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

## **NameAddress**

*NameAddress is mandatory. A single instance is required.*

A group item containing name and address of an organisation or business entity.

## **URL**

*URL is optional. A single instance might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

## **CommonContact**


*CommonContact is optional. Multiple instances might exist.*

Identifies a specific individual associated with the party.

---

## **RecoveredPaper**

A group item defining the characteristics of recycled fibre that are not dependent on a particular conversion process.



### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

## **RecoveredPaperAttributes**

*RecoveredPaperAttributes is optional. A single instance might exist.*


The attributes of Recovered Paper.

---

## **RecoveredPaperAttributes**

The attributes of Recovered Paper.

### **(sequence)**



*The sequence of items below is mandatory. A single instance is required.*

### **[Any Type]**

Any type of content is permitted at this point.

## Recycled

A group item used to communicate the target or test value total percentage of waste fibre in the product according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin


*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.



## StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## RecycledCharacteristics

RecycledCharacteristics groups together the concepts associated with recycled material.

### RecycledRequired [attribute]

*RecycledRequired is optional. A single instance might exist.*

Indicates if Recycled Material is required

Refer to RecycledRequired definition for any enumerations.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Recycled

*Recycled is optional. A single instance might exist.*

A group item used to communicate the target or test value total percentage of waste fibre in the product according to a particular TestMethod.



---

## RecycledRequired [attribute]

Indicates if Recycled Material is required

*This item is restricted to the following list.*

**Yes**

**No**



## Red

The "Red" portion of the method of representing colour termed RGB.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).



#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

#### SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

#### TwoSigmaLower


*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

#### TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.




## Reel

A group item that contains the conversion and packaging characteristics of a reel.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



## ReelConversionCharacteristics

*ReelConversionCharacteristics is optional. A single instance might exist.*

A group item that lists the conversion elements describing how a reel is converted from a tambour.

## ReelPackagingCharacteristics


*ReelPackagingCharacteristics is optional. A single instance might exist.*

A group item that lists the packaging elements describing how a reel should be packed.

---

## ReelArm

The reel arm number.




---

## ReelBreakDiameter


The diameter of a reel at which the web break occurred. This is measured from the core to outside diameter.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



(sequence)



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## ReelConversionCharacteristics

A group item that lists the conversion elements describing how a reel is converted from a tambour.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ConversionCode

*ConversionCode is optional. A single instance might exist.*


A code, as assigned by an Agency, used to identify a group of conversion characteristics.

#### WindingDirection

*WindingDirection is optional. A single instance might exist.*

An element that indicates how the material is wound on the reel.

Refer to



WindingDirection definition for any enumerations.

#### MakeTo

*MakeTo is optional. A single instance might exist.*

Indicates upon which constraint production should be based on (length or diameter). Specifies the basis of the finished diameter of a reel, either a Diameter specification or a Length of paper specification

Refer to MakeTo definition for any enumerations.

#### ReelWidth

*ReelWidth is optional. Multiple instances might exist.*

The width of reel from edge to edge excluding packaging.

#### ReelDiameter

*ReelDiameter is optional. Multiple instances might exist.*

The diameter measurement of reel excluding packaging.

#### ReelLength

*ReelLength is optional. Multiple instances might exist.*

The total length of the paper on the reel.

#### TargetProductWeight

*TargetProductWeight is optional. A single instance might exist.*


The desired weight of the finished product.

#### CoreCharacteristics

*CoreCharacteristics is optional. Multiple instances might exist.*

A group item that details information used to fully define a core.

#### Embossing



*Embossing is optional. Multiple instances might exist.*

Embossing requirements for sheets and reels. Embossing involves a physical deformation of the paper surface as part of the conversion process. Embossing is applied either in-line (directly after the paper machine) or off-line. Refer to the attribute FinishType for additional information.

## **Watermark**

*Watermark is optional. Multiple instances might exist.*

Watermark information

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **ReelDiameter**

The diameter measurement of reel excluding packaging.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

#### **Value**

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### **RangeMin**


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### **RangeMax**

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## ReelItem

A group item representing details of an actual (as opposed to specified) reel. One or several reels can be contained in a package.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Identifier

*Identifier is mandatory. One instance is required, multiple instances might exist.*

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.

### (sequence)

*The sequence of items below is optional. A single instance might exist.*

#### PartyIdentifier

*PartyIdentifier is mandatory. One instance is required, multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

#### MachineID

*MachineID is optional. A single instance might exist.*

An identifier assigned to the particular machine being referenced. For example, a machine could be a paper machine, an off-line coater, a sheeter, or a printing press. The particular machine being referenced will be determined by the business event being supported.

#### DeliveryMessageReelCharacteristics

*DeliveryMessageReelCharacteristics is optional. A single instance might exist.*

A group item for actual measurement and manufacturing characteristics. DeliveryMessageReelCharacteristics is intended to indicate the actual measurements that apply to a reel.

#### InventoryClass


*InventoryClass is optional. A single instance might exist.*

A group item containing information about status of inventory and goods items.

#### MillOrderNumber

*MillOrderNumber is optional. A single instance might exist.*

The manufacturing order number the mill uses.



## Quantity

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## InformationalQuantity

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

---

## ReelLength

The total length of the paper on the reel.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## ReelPackagingCharacteristics


A group item that lists the packaging elements describing how a reel should be packed.

### ActionType [attribute]

*ActionType is optional. A single instance might exist.*

Used to trigger an action concerning the element to which it refers.

Refer to ActionType definition for any



enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PackagingCode

*PackagingCode is optional. A single instance might exist.*

PackagingCode is a code describing the packaging of the product.

#### PackagingDescription

*PackagingDescription is optional. A single instance might exist.*

A text field element describing the packaging of a product.

#### ReelsPerPack

*ReelsPerPack is optional. A single instance might exist.*

The number of reels within a package.

#### Wrap

*Wrap is optional. Multiple instances might exist.*

A group item that organises wrapping detail information.

#### EndCaps


*EndCaps is optional. Multiple instances might exist.*

A cover to protect the ends of the reel, usually circle shaped and made from Kraft paper or plywood.

#### CorePlugs

*CorePlugs is optional. Multiple instances might exist.*

An element that indicates if plugs are to be inserted into the ends of the core. Core plugs can be made of various materials and are used to protect the core ends.



# papiNet V2R31

---

Note: A conversion error took place between Version 1.0 of papiNet and Version 2.0 of papiNet and this item was inadvertently converted from true/false (1.0) to nni1 (2.0). This item has been reinstated to a boolean value. However, please note that for reasons of backward compatibility it is highly recommended that you use the 1/0 approach to communicating true or false where 1 = true and 0 = false. Our apologies for any issues.

## **BandCharacteristics**

*BandCharacteristics is optional. Multiple instances might exist.*

A group item that organises the packaging band detail information.

## **PalletCharacteristics**

*PalletCharacteristics is optional. Multiple instances might exist.*

A group item that provides pallet detail information.

## **LabelCharacteristics**

*LabelCharacteristics is optional. Multiple instances might exist.*

A group item that organises the labeling information.

## **StencilCharacteristics**

*StencilCharacteristics is optional. Multiple instances might exist.*

A group element specifying attributes of a stencil to be applied to an item, and optional text.

## **MaximumHeight**

*MaximumHeight is optional. A single instance might exist.*

The maximum height allowed including the pallet.

## **MaximumGrossWeight**

*MaximumGrossWeight is optional. A single instance might exist.*

The maximum weight allowed including the pallet.

## **MaximumClampingForce**

*MaximumClampingForce is optional. A single instance might exist.*

Specifies maximum clamp force allowed during handling of an item.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **ReelsPerPack**

The number of reels within a package.

<b>ReelsPerPack</b>	
type	nni2

---

## ReelStandUnit

The reelstand unit number.

ReelStandUnit	
type	s10

---

## ReelWidth

The width of reel from edge to edge excluding packaging.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



---

## referenceType [simple type]

This entry provides the definitions for the named reference types that papiNet provides. As there are 45+ of them and they all have the same enumerations and definition, presenting a single entry serves to save space. The standard definition for all reference types and their enumerations follows.

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

*This item is restricted to the following list.*

### AccountNumber

The unique reference number given to a financial account of the party involved in the transaction.

**AudioVideoSelectionNumber**

Unique number given to every audio master. Used by duplicators and replicators.

**Author**

Name of the author of the product or book.

**BarCodedSerialNumber**

The serial number in bar code form.

**BillAndHoldInvoiceNumber**

The invoice number used in a bill and hold arrangement.

**BillOfLadingMark**

Assigning party's reference mark on each package used for logistic purposes (a mark which is painted to packages just to make handling easier). Not to be confused with Bill of Lading Number.

**BillOfLadingNumber**

The unique reference number given to a bill of lading document given to the carrier transporting the product; the bill of lading is a legal document that lists all the products that are being transported.

**BindingStyleType**

BindingStyleType indicates the method used to hold the pages of the issue together. Examples are Saddle Stitch (staple through the middle fold) and Perfect Bound (glue).

**BookLanguage**

The language of the text of the book.

**BookingNumber**

The reference number used for the booking of logistics services.

**BudgetCenter**

An internal cost-centre identifier.

**BuyerBudgetCenter**

To be removed in a future version. Refer to "BudgetCenter" for the definition and use the attribute "AssignedBy" for buyer.

**BuyerClaimNumber**

To be removed in a future version. Refer to "ClaimNumber" for the definition and use the attribute "AssignedBy" for buyer.

**BuyerDivisionIdentifier**

To be removed in a future version. Refer to "DivisionIdentifier" for the definition and use the attribute "AssignedBy" for buyer.

**BuyerImprint**

To be removed in a future version. Refer to "Imprint" for the definition and use the attribute "AssignedBy" for buyer.

**BuyerJobNumber**

To be removed in a future version. Refer to "JobNumber" for the definition and use the attribute "AssignedBy" for buyer.

## **BuyerRetailPrice**

To be removed in a future version. Refer to "RetailPrice" for the definition and use the attribute "AssignedBy" for buyer.

## **CallOffConfirmationLineItemNumber**

The specific line item number for the CallOff confirmation.

## **CallOffConfirmationNumber**

The unique reference number given to a CallOff confirmation.

## **CallOffLineItemNumber**

The specific line item number for the CallOff.

## **CallOffNumber**

The unique reference number given to a CallOff. The CallOff number of a previously sent CallOff can be referenced. For example, a seller can refer to a CallOff number in a DeliveryMessage.

## **CallOffReferenceNumber**

A general informational reference (either textual or numeric) given to a CallOff. The CallOff reference number of a previously sent CallOff can be indicated. For example, a seller can refer to a CallOff reference number in a DeliveryMessage.

## **CatalogueReferenceNumber**

A unique reference for a catalogue

## **CIMNumber**

The unique reference number given to an international freight document for rail transport.

## **CMRNumber**

The unique reference number given to an international freight document for road transport.

## **CoLoadingNumber**

A reference to the identifier for the CoLoading communication.

## **ComplaintNumber**

The reference number associated with a complaint.

## **ComplaintLineItemNumber**

## **ComplaintResponseNumber**

The reference number associated with a ComplaintResponse.

## **ComplaintResponseLineItemNumber**

## **ConsigneeOrderNumber**

To be removed in a future version. Refer to "OrderNumber" for the definition and use the attribute "AssignedBy" for consignee.

## **ContainerReference**

The reference number of the container.

## **ContentLanguage**

## **ContractLineNumber**

A particular line number of a contract. Note: To reference a contract line number, the seller or buyer must include a clear reference to the corresponding contract elsewhere in the document.

## **ContractNumber**

The unique reference number given to a mutual commercial/trading agreement between a buyer and a seller. The agreement can cover a quote, a bid, a contract, pricing, invoicing, and/or payment terms.

## **ConvertingReportNumber**

An identifier used to communicate which converting report is being referred to.

## **Copyright**

The year of publication copyright.

## **CreditAuthorizationNumber**

The number of the credit authorization.

## **CreditDebitNoteNumber**

To be removed in version V3R00. Use either CreditNoteNumber or DebitNoteNumber.

## **CreditNoteNumber**

The number of the referenced Credit Note.

## **CustomerBookingNumber**

To be removed in a future version. Refer to "BookingNumber" for the definition and use the attribute "AssignedBy" for customer.

## **CustomerJobNumber**

To be removed in a future version. Refer to "JobNumber" for the definition and use the attribute "AssignedBy" for customer.

## **CustomerJobTitle**

To be removed in a future version. Refer to "JobTitle" for the definition and use the attribute "AssignedBy" for customer.

## **CustomerOrderNumber**

To be removed in a future version. Refer to "OrderNumber" for the definition and use the attribute "AssignedBy" for customer.

## **CustomerReferenceNumber**

To be removed in a future version. Refer to "ReferenceNumber" for the definition and use the attribute "AssignedBy" for customer.

## **CustomerSpecificationNumber**

To be removed in a future version. Refer to "SpecificationReferenceNumber" for the definition and use the attribute "AssignedBy" for customer.

## **DebitNoteNumber**

The number of the referenced Debit Note.

**DeliveryBookingNumber**

A number use to schedule deliveries at their site.

**DeliveryInstructionNumber**

The unique identifier given to a DeliveryInstruction.

**DeliveryInstructionSequenceNumber**

The unique reference number given to a DeliveryInstruction sequence (line item).

**DeliveryInstructionSequenceLineNumber**

A sequential number that uniquely identifies the line item of a DeliveryInstructionSequence.

**DeliveryLocation**

The location to which product is to be delivered.

**DeliveryMessageNumber**

The identifier of the DeliveryMessage e-Document.

**DeliveryMessageLineItemNumber**

**DeliveryNumber**

Alternate delivery number when the party uses secondary documents to manage their own system.

**DepartmentIdentifier**

A major division of a business.

**DespatchInformationNumber**

**DespatchInstructionNumber**

The unique reference number of the despatch instruction document. For example the despatch instructions sent from the mill to the warehouse.

**DivisionIdentifier**

The internal division identifier for the party.

**DropOffNumber**

The identifier for the stop or location that the delivery vehicle will make.

**Edition**

Identifies the version of the product for which copies were printed and published at one time; For example in book manufacturing values might be 1st, 2nd, etc

**EditionState**

List of state abbreviations. The term "National" may also be used.

**EditionSubject**

Identifies the subject matter of the book.

**EditionSubjectNumber**

Number defined by the BISAC to codify the subject matter of the book.

**EducationSubject**

Identifies the subject matter of a text book (such as Math, Science, etc.).

**EndCallOffDate**

The last date that a call off can be placed.

**FlightNumber**

The reference number given to a flight number.

**FormID**

Identifies the Form that the reference is associated with.

**FormLowFolio**

An additional identifier of a Form.

**FormPages**

The number of pages associated with a Form's Delivery (Pages on a Signature).

**FormType**

Type of printed signature.

For book manufacturing, examples are: web, sheet, folded and gathered signature.

For magazine publishing examples are: Advance, Cover, or Current.

Advance denotes those pages other than Cover and Current. They are usually advertisements and other pages that are less subject to change and can be printed further in advance of the issue date.

Cover denotes the cover pages of the issue.

Current denotes those pages that are more subject to edit changes and are therefore printed closer to the issue date.

**ForwarderReference**

To be removed in a future version. Refer to "ReferenceNumber" for the definition and use the attribute "AssignedBy" for forwarder.

**FromPurchaseOrderNumber**

The PurchaseOrder that is used as the source of information.

**FromSalesOrderNumber**

The sales order that is used as the source of information.

**FSCNumber**

A certificate registration code for a site that has been certified in accordance with the requirements of the Forest Stewardship Council A.C. for delivering of FSC certified products. This number would also be communicated in the LicenceNumber element of the SafetyAndEnvironmentalInformation.

**GeneralAgreement**

The particular standard industry contract is being used to indicate incoterms agreements, arbitration rules, chartering, insurance, payment & freight, claims, etc.

**GoodsInBillOfLadingNumber**

The unique reference number given to a bill of lading number for a transport which delivered goods into a location.

**GoodsInDeliveryNumber**

The unique reference number given to a delivery number for a transport which delivered goods into a location.

**GoodsInTransportUnitIdentifier**

The reference number given to a unit identifier for a transport which delivered goods into a location.

**GoodsInTransportVehicleIdentifier**

The reference number given to a vehicle identifier for a transport which delivered goods into a location.

**GoodsReceiptNumber**

The number of the GoodsReceipt transaction that is being referred to.

**GoodsReceiptLineItemNumber**

The line item number of the GoodsReceipt transaction that is being referred to.

**Imprint**

Identifies the imprint to which this product belongs. When communicating the "publisher's imprint" use an assigned by of "Buyer".

**IndentOrderNumber**

A unique reference number given to an order, which is to be delivered directly to the buyer's own customer (typically a paper merchant). The reference value is passed from the buyer to the seller and the information content is meaningful only to the buyer.

**InitialShipmentAdviceNumber**

The unique reference number given to an initial shipment advice. The number of a previously sent initial shipment advice can be referenced. For example, a seller can refer to an initial shipment advice number in a DeliveryMmessage.

**IntraStatNumber**

The unique reference number given to product groups by the international authority Intrastat for statistical purposes. This number must be on the invoice when importing or exporting goods.

**InventoryChangeLineItemNumber**

An identifier for the InventoryChangeLineItem.

**InventoryChangeNumber**

The identifier for the InventoryChange.

**InventoryDispositionInstructionsNumber**

The unique reference number given to an InventoryDispositionInstructions.

**InventoryDispositionInstructionsLineNumber**

The sequential reference number given to the inventory disposition line

number.

## **InventoryStatusLineItemNumber**

An identifier that allows for unique identification of the InventoryStatusLineItem.

## **InventoryStatusNumber**

An identifier that allows for unique identification of the InventoryStatus e-Document.

## **InvoiceNumber**

The number associated with the Invoice.

## **ISBN10**

10 digit ISBN code without dashes

## **ISBN10Dash**

10 digit ISBN code with dashes

## **ISBN13**

13 digit ISBN code.

## **ISBN13Dash**

A 13 character ISBN with dashes; example of ISBN-13 with dashes: 978-1-873671-00-0.

## **ISODocumentReference**

A unique ISO 9002 / 9001 document identifier.

## **IssueEvent**

A task, or other type of event, related to the creation of an issue of a publication.

## **JobNumber**

An identifier for a step in the production, publication, or manufacturing process. Usually a job has as its scope the amount of work performed by a defined resource (person or equipment).

## **JobTitle**

A name of a specific job or task to which the forecast data is to apply, along with location and item.

## **LoadPlanNumber**

A reference number given to a general unique load plan number generated in the planning phase before any physical loads exist.

## **LoadReleaseNumber**

The identifier for the Load Release.

## **LoadTenderNumber**

The identifier for the LoadTender b-e-Document.

## **LoadTenderResponseNumber**

## **LoadingInstructionNumber**

The unique reference number given to the loading instruction.

## **LoadingInstructionSequenceNumber**

A sequential number that uniquely identifies the sequence of a LoadingInstruction.

## **LoadingInstructionSequenceLineNumber**

A sequential number that uniquely identifies the sequence of a LoadingInstruction.

## **LoadingOrderNumber**

The identifier for the Loading Order.

## **LoadingOrderLineNumber**

The line item number of the Loading Order.

## **LotIdentifier**

A unique code used to identify a grouping of product with one set of quality statistics common to all members of that group. Synonym: Lot Number

## **MagazineCode**

A code used to identify a magazine.

## **ManufacturerMaterialSafetyDataSheetNumber**

To be removed in a future version. Refer to "MaterialSafetyDataSheet" for the definition and use the attribute "AssignedBy" for producer (manufacturer).

## **MarketType**

Mass Market, Picture Books, Trade, Education, etc.

## **MarketplaceReferenceNumber**

To be removed in a future version. Refer to "ReferenceNumber" for the definition and use the attribute "AssignedBy" for marketplace.

## **MasterBillOfLading**

The unique reference number given to a master bill of lading document, which contains multiple bills of lading. This is a legal document given to the carrier that transports the goods to multiple customers, each of which then receive a unique bill of lading document.

## **MasterContractNumber**

Contract number that is broader in terms of doing business between partners which for the book industry may, or may not include pricing.

## **MasterISBN10**

Refers to the ISBN10 of a product where the product being ordered is a part

## **MasterISBN13**

Refers to the ISBN13 of a product where the product being ordered is a part

## **MasterPurchaseOrder**

Refers to a Buyer's PurchaseOrder Number under which separate purchase orders are generated but the master PO will never be sent to the supplier.

## **MaterialSafetyDataSheetNumber**

A U.S. document describing the safety, environmental and physical issues, if any, for a product.

## **MeasuringInstructionNumber**

The unique identifier of a Measuring Instruction.

## **MeasuringNumber**

The unique identifier given to a measurement.

## **MeasuringTicketNumber**

The unique identifier of a MeasuringTicket.

## **MeasuringTicketSequenceNumber**

A sequential number that uniquely identifies the sequence of a MeasuringTicket.

## **MeasuringTicketSequenceLineItemNumber**

A sequential number that uniquely identifies the line item of a MeasuringTicket sequence.

## **MillOrderLineItemNumber**

To be removed in a future version. Refer to "OrderLineItemNumber" for the definition and use the attribute "AssignedBy" for mill.

## **MillOrderNumber**

To be removed in a future version. Refer to "OrderNumber" for the definition and use the attribute "AssignedBy" for mill.

## **MillSalesOfficeNumber**

To be removed in a future version. Refer to "SalesOfficeNumber" for the definition and use the attribute "AssignedBy" for mill.

## **MovementReferenceNumber**

Movement Reference Number is given by European customs authorities. This is the reference number of the goods shipment in all European custom systems. This reference number is AssignedBy "Customs". For more information please see <http://europa.eu>

## **NonconformanceReportNumber**

The number assigned to a non-conformance report.

## **OrderConfirmationNumber**

The number of the OrderConfirmation that is used to identify the transaction, or portion of the transaction.

## **OrderConfirmationLineItemNumber**

The line item on the OrderConfirmation (identified by the OrderConfirmationNumber).

## **OrderNumber**

The number of the order that is used to identify the transaction, or portion of the transaction.

## **OrderLineItemNumber**

The line item on the Order (identified by OrderNumber).

## **OrderPartyReferenceNumber**

To be removed in a future version. Refer to "ReferenceNumber" for the definition and use the attribute "AssignedBy" of "OrderParty".

## **OriginalComplaintResponseNumber**

Reference number of the original ComplaintResponse.

## **OriginalDeliveryNumber**

The unique reference number given to a DeliveryMessage number sent previously that has been replaced in the meantime.

## **OriginalGoodsReceiptNumber**

The original unique identifier of the GoodsReceipt that is to be replaced.

## **OriginalInvoiceNumber**

To be removed in version V3R00. Use InvoiceNumber.

## **OriginalProductQualityMessageNumber**

The unique reference number given to a ProductQuality document sent previously that has been replaced in the meantime.

## **OriginalPurchaseOrderNumber**

The unique reference number given to a PurchaseOrder document sent previously that has been replaced (through amendment or cancellation) in the meantime.

## **OriginalSalesOrderNumber**

The unique reference number given to a sales order previously communicated that has been replaced (through amendment or cancellation) in the meantime.

## **OriginalScaleTicketNumber**

The unique reference number given to the original ScaleTicket.

## **OriginalUsageNumber**

The unique reference number given to a Usage e-Document previously sent that has been replaced (through amendment or cancellation) in the meantime.

## **PackageMark**

A mark applied to packages. The package mark is mainly used for logistics purposes by grouping of packages together and making handling and storing easier.

## **PackageNumber**

The unique reference number given to a manufacturer's product packaging designation.

## **PackageSpecificationNumber**

The reference number given to a set of packing specifications.

## **PackageSpecificationLineNumber**

The reference number given to one line of a set of packing specifications.

## **PageCount**

Number of text pages in the book or component.

## **PageCountTotal**

Total number of pages including inserts.

## **PaymentReferenceNumber**

Payment reference number is used when paying the invoice. It associates the payment to the right invoice in an electronic payment scenario.

## **PEFCNumber**

A certificate registration code for a site that has been certified in accordance with the requirements of the Programme for the Endorsement of Forest Certification. This number would also be communicated in the LicenceNumber element of the SafetyAndEnvironmentalInformation.

## **PickUpNumber**

Indicates the route number for the pick-up location for a transport order.

## **PlanningMessageNumber**

The unique reference number to a Planning e-Document that includes estimated volumes for the product being called off.

## **PopulationNumber**

A reference number identifying a group of clearly-defined items with similar characteristics. Currently used by Forest Wood Supply for statistical Calculation adjustments.

## **PriceContractNumber**

Contract number that is specific to pricing.

## **PriceQuoteNumber**

Quote number that is specific to pricing.

## **PriceList**

The number used to identify the price list.

## **PrintingCode**

Identifies the book as a New Boo, Reprint, New Adoption, etc.

## **PrintingNumber**

A reference to the sequential print run number.

## **PriorPurchaseOrderNumber**

The preceding PurchaseOrder number.

## **ProductOriginIdentifier**

A reference number identifying the origin of the product. It is typically used as a tracking reference.

## **ProFormaInvoiceNumber**

The identification number for the Pro Forma Invoice.

## **ProNumber**

A (Progressively) sequential numbering system used to identify logistics bills.

Referred to, in Europe, as Verification Number.

Example: ANC5376559

## **ProfitCenter**

Profit center identifier

## **ProgramID**

Identifies that the item is associated with a series. In the book manufacturing industry examples would be, "Science Series 2007, "Math Series 2009".

## **PromotionNumber**

The sales promotion number.

## **PubName**

The publication name.

## **PubNumber**

The publication number.

## **PublisherReferenceNumber**

## **PupilsTeachers**

Description of the pupils/teachers edition specific to educational book products.

## **PurchaseOrderCorrelationID**

Contains a reference value which is used to identify a group of purchase orders for products that are priced based on being manufactured together because of common components.

## **PurchaseOrderNumber**

The unique reference number given to a PurchaseOrder. The PurchaseOrder number of a previously sent order can be referenced. For example, a seller can refer to a PurchaseOrder number in an Invoice.

## **PurchaseOrderLineItemCorrelationID**

Contains a reference value which is used to identify a group of PurchaseOrder Line Items that refer to the same product.

## **PurchaseOrderLineItemNumber**

A sequential number that uniquely identifies the PurchaseOrder line item.

## **PurchaseOrderReleaseNumber**

The version or release of the PurchaseOrder.

## **QualityReportNumber**

A number that uniquely identifies a quality report.

## **RandomSampleNumber**

The unique identifier of a random sample.

## **ReferenceNumber**

An informational reference (either textual or numeric) for which the owner or source is specified in the "@AssignedBy" attribute

**ReleaseNumber**

The unique identifier (either textual or numeric) given to the release of a reservation order, a contract, or a blanket order.

**RetailPrice**

Cover price of the finished product.

**RFQLineItemNumber**

The number used to identify the RFQ line item.

**RFQNumber**

The identifier of the RFQ. Usually provided when opening a PurchaseOrder that is derived from a request for quote (RFQ).

**RunNumber**

The unique reference number given to a paper-manufacturing slot on the mill production line (for example, paper machine or sheet cutter). Paper for several orders is manufactured in one run before resetting the machines for new manufacturing results.

**SalesOfficeNumber**

The number used to identify the sales office.

**SalesOrderLineItemNumber**

A number that uniquely identifies the sales order line item.

**SalesOrderNumber**

The unique reference number given to a sales order.

**ScaleTicketNumber**

The identifier for the ScaleTicket.

**SchoolGrade**

Grade level indicator of the book product, specific to educational text books such as grade 3. (K=Kindergarten, 1 through 12, CO=College)

**SchoolGradeLevel**

Further definition of the Grade level of the book product, specific to educational text books such as grade 3 level A.

**SellersInvoiceNumber**

To be removed in a future version. Refer to "InvoiceNumber" for the definition and use the attribute "AssignedBy" for seller.

**ServiceNumber**

The product number for the service.

**ShipmentStatusNumber**

The unique identifier for the ShipmentStatus e-Document.

**ShippingInstructionsLineItemNumber**

Line number reference of the shipping instruction for book shipments.

**ShippingInstructionsNumber**

Sequential number of the shipping instruction.

## **SimplifiedCustomsNumber**

A number that identifies the applicable simplified customs arrangement.

## **SpecificationNumber**

The unique reference number given to a Specification.

## **SpecificationReferenceNumber**

The assigning party's reference number for the specification. (The version number of the BookSpecification.)

## **SpecificationVersion**

The identifier for the version of the specification.

## **StanForDForwardedProductionNumber**

The identifier of the forwarded production file in the StanForD standard used by forest machines.

## **StanForDHarvestedProductionNumber**

The identifier of the harvested production file in the StanForD standard used by forest machines.

## **StanForDHarvestingQualityControlNumber**

The identifier of the harvesting quality control file in the StanForD standard used by forest machines.

## **StockOrderLineItemNumber**

A number that uniquely identifies the line item of a Stock Order. The Stock Order is identified by the StockOrderNumber.

## **StockOrderNumber**

The unique reference number given to an order, which is to be delivered to the buyer's designated stock location (typically a paper merchant). The reference value is passed from the buyer to the supplier and the information content is meaningful only to the buyer.

## **SupplierCallOffNumber**

To be removed in a future version. Refer to "CallOffNumber" for the definition and use the attribute "AssignedBy" for supplier.

## **SupplierClaimNumber**

To be removed in a future version. Refer to "ClaimNumber" for the definition and use the attribute "AssignedBy" for supplier.

## **SupplierJobNumber**

To be removed in a future version. Refer to "JobNumber" for the definition and use the attribute "AssignedBy" for supplier.

## **SupplierReferenceNumber**

To be removed in a future version. Refer to "ReferenceNumber" for the definition and use the attribute "AssignedBy" for supplier.

## **SupplierVoyageNumber**

To be removed in a future version. Refer to "VoyageNumber" for the definition and use the attribute "AssignedBy" for supplier.

## **T2L**

### **TimeTableNumber**

The reference number given to a timetable.

### **Title**

Proper title of a book product.

### **TitleAlias**

Alternate title description for book products, usually for security purposes.

### **ToPurchaseOrderNumber**

The destination of purchase order information.

### **TrackingNumber**

TrackingNumber is a logistics identifier assigned to a shipment.

### **TransactionID**

Unique system-wide identifier for a business transaction used as a source for creation of the papiNet e-Document.

### **TransportUnitIdentifier**

The reference number given to a transport unit. The transport unit is the portion of the vehicle that holds the goods.

### **TransportVehicleIdentifier**

The reference number given to a vehicle used for transport.

### **UniversalProductIdentifier**

Unique identifier for the book, component of a book product, and many other products.

### **UsageNumber**

The number used to identify the Usage activity being referred to.

### **UsageLineItemNumber**

The line item number used to identify the Usage activity being referred to.

### **VendorReferenceNumber**

To be removed in a future version. Refer to "ReferenceNumber" for the definition and use the attribute "AssignedBy" for seller.

### **VesselShipNotice**

### **VoucherNumber**

The unique reference number given to a document serving as evidence for some claimed transaction, e.g. as the receipt or expenditure of money.

### **VoyageNumber**

The assigning party's unique reference number (own internal code) given to a voyage. This may or may not be the port authority's number.

### **WarehouseDeliveryNumber**

To be removed in a future version. Refer to "DeliveryNumber" for the definition and use the attribute "AssignedBy" for warehouse.

## WaybillIdentifier

Identifies the document that acknowledges receipt of the goods being shipped and specifying the terms of delivery.

## Other

Used for any other reference that is not covered by this attribute list.

## Reissued [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*


**Yes**

**No**



## RelativeLocation [attribute]

The relative position in the end-item where the component is to be placed.



## RemitToParty

A group item containing details of the party to whom payment will be made. The RemitToParty contains all information related to remittance.

### LogisticsRole [attribute]

*LogisticsRole is optional. A single instance might exist.*

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.

### (sequence)


*The sequence of items below is mandatory. A single instance is required.*

### PartyIdentifier

*PartyIdentifier is optional. Multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

### NameAddress



# papiNet V2R31

*NameAddress is mandatory. A single instance is required.*

A group item containing name and address of an organisation or business entity.

## URL

*URL is optional. A single instance might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.


## CommonContact

*CommonContact is optional. Multiple instances might exist.*

Identifies a specific individual associated with the party.

## RequestedAction

The element that enables the party making the complaint (i.e. SenderParty) to specify what they want done regarding the Complaint (send a credit, send disposition instructions, etc.)



## RequestingParty


The party requesting the information.

### PartyType [attribute]

*PartyType is mandatory. A single instance is required.*

Identifies the business role associated with the particular party

Refer to PartyType definition for any enumerations.



### LogisticsRole [attribute]

*LogisticsRole is optional. A single instance might exist.*

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*


### PartyIdentifier

*PartyIdentifier is optional. Multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

### NameAddress

*NameAddress is mandatory. A single instance is required.*



# papiNet V2R31

A group item containing name and address of an organisation or business entity.

## URL

*URL is optional. A single instance might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

## CommonContact

*CommonContact is optional. Multiple instances might exist.*

Identifies a specific individual associated with the party.

---

## RequestNumber

A unique tracking number specifically identifying the InfoRequest e-Document to the originator. The tracking number is returned with the "information", the answer, to help match the answer to the request.

<b>RequestNumber</b>
type s30

---

## Resistance

A group item used to communicate air resistance target or test value according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]


*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*



# papiNet V2R31

---

Used to define the data source of the specified test  
Refer to ResultSource definition for any enumerations.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

### SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

### TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

### TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.


---

## RespondByDate

The date that a response to the query if required.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

# papiNet V2R31

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## RespondToParty

The party the document should be responded to.

### PartyType [attribute]

*PartyType is mandatory. A single instance is required.*

Identifies the business role associated with the particular party

Refer to PartyType definition for any enumerations.

### LogisticsRole [attribute]

*LogisticsRole is optional. A single instance might exist.*

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PartyIdentifier

*PartyIdentifier is optional. Multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.


#### NameAddress

*NameAddress is mandatory. A single instance is required.*

A group item containing name and address of an organisation or business entity.

#### URL

*URL is optional. A single instance might exist.*



# papiNet V2R31

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

## CommonContact

*CommonContact is optional. Multiple instances might exist.*


Identifies a specific individual associated with the party.

---

## ResultSource [attribute]

Used to define the data source of the specified test

*This item is restricted to the following list.*



### AutoLab

The data that gave rise to the value reported for this test came from an automated laboratory testing device.

### Calculated

### ManualLab

The data that gave rise to the value reported for this test came from a manually performed laboratory test.

### OnMachine

The data that gave rise to the value reported for this test came from an on-machine scanning device.

### Predicted

The value indicated for this test is a target value and not the result of performing a paper test

---

## ReturnReason

A group item containing the reason for the Return

### ReturnType [attribute]

*ReturnType is optional. A single instance might exist.*

Specifies the type of return.

*This item is restricted to the following list:*

#### ReturnFromBuyer

Product was returned from the Buyer

#### ReturnFromShipper


Product was returned from the Shipper

#### ReturnFromThirdParty

Product was returned from an end user

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



## ReturnReasonCode

*ReturnReasonCode is optional. A single instance might exist.*

A code for quickly communicating the type of Return Reason. The Agency responsible for the code is associated with the element.

## ReturnReasonDescription


*ReturnReasonDescription is optional. Multiple instances might exist.*

A text field element describing the reason for the Return.

---

## ReturnReasonCode

A code for quickly communicating the type of Return Reason. The Agency responsible for the code is associated with the element.



### Agency [attribute]

*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

---

## ReturnReasonDescription

A text field element describing the reason for the Return.



## ReturnType [attribute]

Specifies the type of return.

*This item is restricted to the following list.*

### ReturnFromBuyer


Product was returned from the Buyer

### ReturnFromShipper

Product was returned from the Shipper

### ReturnFromThirdParty

Product was returned from an end user




**RewoundIndicator [attribute]**

Is the date being communicated the the rewind date (Yes) or the date of original winding (No)?

*This item is restricted to the following list.*

**Yes**


**No**



**RFQ**

The RFQ element is the root element for the RFQ e-Document.

A buyer sends an RFQ e-Document to a supplier to initiate a request for quotation. This e-Document, which is a request for product information, represents a request for the supplier to provide a quotation for product availability, shipping, and price.



**RFQType [attribute]**

*RFQType is mandatory. A single instance is required.*

Defines the type of RFQ issued.

Refer to RFQType definition for any enumerations.

**RFQStatusType [attribute]**

*RFQStatusType is mandatory. A single instance is required.*

This attribute acts as a flag indicating what processing may be required.

Refer to RFQStatusType definition for any enumerations.

**Language [attribute]**

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**RFQHeader**

*RFQHeader is mandatory. A single instance is required.*

A group item containing information applicable to the entire RFQ e-Document.

**RFQLineItem**

*RFQLineItem is mandatory. One instance is required, multiple instances might exist.*

The repetitive detail for the RFQ e-Document.

## RFQSummary

*RFQSummary is optional. A single instance might exist.*

Summary information that applies to the RFQ e-Document.

## RFQHeader

A group item containing information applicable to the entire RFQ e-Document.

### RFQHeaderStatusType [attribute]

*RFQHeaderStatusType is mandatory. A single instance is required.*

Defines the status of the RFQ header

Refer to **RFQHeader** definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### RFQ Information

*RFQInformation is mandatory. A single instance is required.*

A group item containing information unique to this RFQ which is provided by the buyer.

#### TransactionHistoryNumber


*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

#### BuyerParty

*BuyerParty is mandatory. A single instance is required.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.



## **BillToParty**

*BillToParty is optional. A single instance might exist.*

The address where the invoice is to be sent.

## **SupplierParty**

*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product.

SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **TransportModeCharacteristics**

*TransportModeCharacteristics is optional. A single instance might exist.*

A group item defining the primary mode of transport.

## **TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

## **TransportUnitCharacteristics**

*TransportUnitCharacteristics is optional. A single instance might exist.*

A group item defining and identifying the primary means of containing the goods.

In some instances, the transport unit and vehicle are the same.

## **TransportLoadingCharacteristics**

*TransportLoadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be loaded.

## **TransportUnloadingCharacteristics**

*TransportUnloadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be unloaded.

## **TransportOtherInstructions**

*TransportOtherInstructions is optional. A single instance might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

## **TermsOfPayment**

*TermsOfPayment is optional. Multiple instances might exist.*

A group item that contains agreed-to terms defining when, how, and under what conditions the payment is to be made.

When TermsOfPayment is optional; if omitted, TermsOfPayment is controlled through previous negotiation.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **RFQHeaderStatusType [attribute]**

Defines the status of the RFQ header

*This item is restricted to the following list.*

### **Accepted**

The supplied information is accepted.

### **Amended**

The supplied information is changed.

### **Cancelled**


The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### **New**

The supplied information is new and supplied for the first time.

### **NoAction**

The supplied information has not been amended and thereby requires no action.




## RFQInformation

A group item containing information unique to this RFQ which is provided by the buyer.

### (sequence)

The sequence of items below is mandatory. A single instance is required.



### RFQNumber

RFQNumber is mandatory. A single instance is required.

The unique RFQ identifier as designated by the buyer.

### RFQIssuedDate

RFQIssuedDate is optional. A single instance might exist.

The Date and Time the RFQ was issued.

### RFQRespondByDate

RFQRespondByDate is mandatory. A single instance is required.

The Date and Time by which a response needs to be received by the RFQ issuer.

### RFQReference

RFQReference is optional. Multiple instances might exist.


A repeatable element that details the relevant references (such as contract number) pertaining to the RFQ. The RFQReference is defined by RFQReferenceType.

## RFQIssuedDate

The Date and Time the RFQ was issued.

### (sequence)

The sequence of items below is mandatory. A single instance is required.



### Date

Date is mandatory. A single instance is required.

A group element that contains the specification of Year, Month, and Day.

### Time

Time is optional. A single instance might exist.

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## RFQLineItem

The repetitive detail for the RFQ e-Document.

### RFQLineItemStatusType [attribute]

*RFQLineItemStatusType is mandatory. A single instance is required.*

Defines the status of the RFQ line item

Refer to RFQLineItemStatusType definition for any enumerations.

### RFQLineItemDocumentStatus [attribute]

*RFQLineItemDocumentStatus is optional. A single instance might exist.*

Defines the actual document status for the RFQLineItem.

Refer to RFQLineItemDocumentStatus definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### RFQLineItemNumber

*RFQLineItemNumber is mandatory. A single instance is required.*

A sequential number that uniquely identifies the RFQ line item.


#### RFQReference

*RFQReference is optional. Multiple instances might exist.*

A repeatable element that details the relevant references (such as contract number) pertaining to the RFQ. The RFQReference is defined by RFQReferenceType.

#### Product

*Product is mandatory. A single instance is required.*



Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **SupplierParty**

*SupplierParty is optional. A single instance might exist.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **PriceDetails**

*PriceDetails is optional. Multiple instances might exist.*

An element that groups together price information.

## **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates the type of adjustment being communicated.

## **MillCharacteristics**

*MillCharacteristics is optional. A single instance might exist.*

A group item defining the mill party and machine identifier where a product is or was produced.

## **Quantity**

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **OtherDate**

*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **TransportModeCharacteristics**

*TransportModeCharacteristics is optional. A single instance might exist.*

A group item defining the primary mode of transport.

## **TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

## **TransportUnitCharacteristics**

*TransportUnitCharacteristics is optional. A single instance might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

## **TransportLoadingCharacteristics**

*TransportLoadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be loaded.

## **TransportUnloadingCharacteristics**

*TransportUnloadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be unloaded.

## **TransportOtherInstructions**

*TransportOtherInstructions is optional. A single instance might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

## **DeliverySchedule**

*DeliverySchedule is optional. Multiple instances might exist.*

A group item defining a series of DeliveryDateWindow(s) in which specified quantities must be delivered.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **SafetyAndEnvironmentalInformation**

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

---

## RFQLineItemDocumentStatus [attribute]

Defines the actual document status for the RFQLineItem.

*This item is restricted to the following list.*

### Cancelled

The supplied information of the document item is cancelled. Items that have been cancelled are not included in totals on the summary level of e-Documents.

### Requested

The supplied information of the document item is ordered.

attribute
<b>RFQLineItemDocumentStatus</b>
type documentStatusType.RFQ

---

## RFQLineItemNumber

A sequential number that uniquely identifies the RFQ line item.

<b>RFQLineItemNumber</b>
type lineNumberType

---

## RFQLineItemStatusType [attribute]

Defines the status of the RFQ line item

*This item is restricted to the following list.*

### Accepted

The supplied information is accepted.

### Amended

The supplied information is changed.

### Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### New

The supplied information is new and supplied for the first time.

### NoAction

The supplied information has not been amended and thereby requires no action.

attribute
<b>RFQLineItemStatusType</b>
type rFQLineItemStatusType

---


## RFQNumber

The unique RFQ identifier as designated by the buyer.

<b>RFQNumber</b>
type s30

## RFQReference

A repeatable element that details the relevant references (such as contract number) pertaining to the RFQ. The RFQReference is defined by RFQReferenceType.



### RFQReferenceType [attribute]

*RFQReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to RFQReferenceType definition for any enumerations.

### AssignedBy [attribute]


*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

## RFQReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.




Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## RFQRespondByDate

The Date and Time by which a response needs to be received by the RFQ issuer.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



# papiNet V2R31

## Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

## Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.


hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## RFQResponse

The RFQResponse element is the root element for the RFQResponse e-Document.

A supplier sends an RFQResponse e-Document to a buyer as a response to an RFQ e-Document from the buyer. The e-Document specifies a quotation for product availability, shipping, and price.

**RFQResponse**



### **RFQResponseStatusType [attribute]**

*RFQResponseStatusType is mandatory. A single instance is required.*

This attribute acts as a flag indicating what processing may be required.

Refer to RFQResponseStatusType definition for any enumerations.

### **Language [attribute]**

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

## **RFQResponseHeader**

*RFQResponseHeader is mandatory. A single instance is required.*

Information that pertains to the entire RFQResponse.

## **RFQResponseLineItem**

*RFQResponseLineItem is mandatory. One instance is required, multiple instances might exist.*

A group element that contains the response details provided by the party responding to the RFQ.

## **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount. MonetaryAdjustment contains an attribute that indicates the type of adjustment being communicated.

## **RFQResponseSummary**

*RFQResponseSummary is mandatory. A single instance is required.*

A group element that contains information that summarizes the contents of the RFQResponse.

## RFQResponseHeader

Information that pertains to the entire RFQResponse.

### RFQResponseHeaderStatusType [attribute]

*RFQResponseHeaderStatusType is mandatory. A single instance is required.*

Defines the status of the RFQ header

Refer to

RFQResponseHeader

RFQResponseHeaderStatusType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### RFQResponseHeaderStatusTypeText

*RFQResponseHeaderStatusTypeText is optional. A single instance might exist.*

A text field that may provide detail explaining the status of the RFQResponse.

When an RFQ is rejected, the reason for the rejection must be specified in this field.

### RFQResponseNumber

*RFQResponseNumber is optional. A single instance might exist.*

The identifying number of the RFQResponse.

### RFQResponseIssuedDate

*RFQResponseIssuedDate is mandatory. A single instance is required.*

The Date and Time when the response to the RFQResponse was issued.


### RFQInformation

*RFQInformation is mandatory. A single instance is required.*

A group item containing information unique to this RFQ which is provided by the buyer.

### TransactionHistoryNumber

*TransactionHistoryNumber is optional. A single instance might exist.*



A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

## **RFQResponseReference**

*RFQResponseReference is optional. Multiple instances might exist.*

An element that details the relevant references (such as contract number) pertaining to the RFQResponse. RFQResponseReferenceType indicates what type of reference is being communicated.

## **BuyerParty**

*BuyerParty is mandatory. A single instance is required.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## **BillToParty**

*BillToParty is optional. A single instance might exist.*

The address where the invoice is to be sent.

## **SupplierParty**

*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To

# papiNet V2R31

---

Party.ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **TransportModeCharacteristics**

*TransportModeCharacteristics is optional. A single instance might exist.*

A group item defining the primary mode of transport.

## **TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

## **TransportUnitCharacteristics**

*TransportUnitCharacteristics is optional. A single instance might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

## **TransportLoadingCharacteristics**

*TransportLoadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be loaded.

## **TransportUnloadingCharacteristics**

*TransportUnloadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be unloaded.

## **TransportOtherInstructions**

*TransportOtherInstructions is optional. A single instance might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **RFQResponseHeaderStatusType [attribute]**

Defines the status of the RFQ header

*This item is restricted to the following list.*

### **Accepted**

The supplied information is accepted.

### **Amended**

The supplied information is changed

### **Counterproposal**

The sender is presenting a different proposal.

### **NoAction**



The supplied information has not been amended and thereby requires no action.

## Pending

The supplied information is not complete and will be updated later.

## Rejected

The supplied information is rejected.

---

## RFQResponseHeaderStatusTypeText

A text field that may provide detail explaining the status of the RFQResponse.

When an RFQ is rejected, the reason for the rejection must be specified in this field.

RFQResponseHeaderStatusTypeText	
type	s72


---

## RFQResponseIssuedDate

The Date and Time when the response to the RFQResponse was issued.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## RFQResponseLineItem

A group element that contains the response details provided by the party responding to the RFQ.

### RFQResponseLineItemStatusType [attribute]

*RFQResponseLineItemStatusType is mandatory. A single instance is required.*

RFQResponse Line Item Status Type

Refer to RFQResponseLineItemStatusType definition for any enumerations.

RFQResponseLineItem

### RFQResponseLineItemDocumentStatus [attribute]

*RFQResponseLineItemDocumentStatus is optional. A single instance might exist.*

Defines the actual document status for the RFQResponseLineItem.

Refer to RFQResponseLineItemDocumentStatus definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### RFQResponseLineItemStatusTypeText

*RFQResponseLineItemStatusTypeText is optional. A single instance might exist.*


A text field that may provide detail explaining the status of the RFQResponseLineItem.

When an RFQLineItem is rejected, the reason for the rejection must be specified in this field.

#### RFQResponseValidityDate

*RFQResponseValidityDate is mandatory. A single instance is required.*

The Date and Time within which a response to the RFQ is valid.



## **RFQLineItemNumber**

*RFQLineItemNumber is mandatory. A single instance is required.*

A sequential number that uniquely identifies the RFQ line item.

## **Product**

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **SupplierParty**

*SupplierParty is optional. A single instance might exist.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **RFQResponseReference**

*RFQResponseReference is optional. Multiple instances might exist.*

An element that details the relevant references (such as contract number) pertaining to the RFQResponse. RFQResponseReferenceType indicates what type of reference is being communicated.

## **RFQResponseLineItemPriceDetail**

*RFQResponseLineItemPriceDetail is optional. A single instance might exist.*

The pricing information associated with the response to an RFQ.

## **LineBaseAmount**

*LineBaseAmount is optional. A single instance might exist.*

For the particular e-Document being communicated the LineBaseAmount represents the quantity times the base unit price.

## **DeliveryDestination**

*DeliveryDestination is optional. A single instance might exist.*

The DeliveryDestination specifies the end of one leg of the delivery. In order to comply with the US Trade Act of 2002 you would use this element with a LocationParty/@PartyType of Port.

## **MillCharacteristics**

*MillCharacteristics is optional. A single instance might exist.*

A group item defining the mill party and machine identifier where a product is or was produced.

## **ShipmentMethodOfPayment**

*ShipmentMethodOfPayment is optional. A single instance might exist.*

An element communicating responsibility of freight payment and when transfer of ownership will occur.

## **Quantity**

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of

quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **ShipToCharacteristics**

*ShipToCharacteristics is optional. A single instance might exist.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

## **TransportModeCharacteristics**

*TransportModeCharacteristics is optional. A single instance might exist.*

A group item defining the primary mode of transport.

## **TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

## **TransportUnitCharacteristics**

*TransportUnitCharacteristics is optional. A single instance might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

## **TransportLoadingCharacteristics**

*TransportLoadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be loaded.

## **TransportUnloadingCharacteristics**

*TransportUnloadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be unloaded.

## **TransportOtherInstructions**

*TransportOtherInstructions is optional. A single instance might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

## **DeliverySchedule**

*DeliverySchedule is optional. Multiple instances might exist.*

A group item defining a series of DeliveryDateWindow(s) in which specified

quantities must be delivered.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## SafetyAndEnvironmentalInformation

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*


Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

---

## RFQResponseLineItemDocumentStatus [attribute]

Defines the actual document status for the RFQResponseLineItem.

*This item is restricted to the following list.*



### Cancelled

The supplied information of the document item is cancelled. Items that have been cancelled are not included in totals on the summary level of e-Documents.

### Confirmed

The supplied information of the document item is agreed. If a requested change or cancellation of an existing document item can not be accepted, then the earlier agreed information of the document item will be re-confirmed.

### Pending

The supplied information of the document item is being investigated.

### Rejected

The supplied information of the document item can not be accepted. The document item is new or not earlier confirmed.


---

## RFQResponseLineItemPriceDetail

The pricing information associated with the response to an RFQ.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### PriceDetails

*PriceDetails is optional. Multiple instances might exist.*

An element that groups together price information.

## **MonetaryAdjustment**

*MonetaryAdjustment is optional. Multiple instances might exist.*

The element containing the information necessary for the understanding, calculation, and treatment of an adjustment to a currency amount.

MonetaryAdjustment contains an attribute that indicates the type of adjustment being communicated.

---

## **RFQResponseLineItemStatusType [attribute]**

RFQResponse Line Item Status Type

*This item is restricted to the following list.*

### **Accepted**

The supplied information is accepted.

### **Amended**

The supplied information is changed.

### **Counterproposal**

The sender is presenting a different proposal.

### **NoAction**

The supplied information has not been amended and thereby requires no action.

### **Pending**

The supplied information is not complete and will be updated later.

### **Rejected**

The supplied information is rejected.

attribute
<b>RFQResponseLineItemStatusType</b>
type rFQResponseLineItemStatusType

---

## **RFQResponseLineItemStatusTypeText**

A text field that may provide detail explaining the status of the RFQResponseLineItem.

When an RFQLineItem is rejected, the reason for the rejection must be specified in this field.

<b>RFQResponseLineItemStatusTypeText</b>
type s72

---

## **RFQResponseNumber**


The identifying number of the RFQResponse.

<b>RFQResponseNumber</b>
type s30

---

## RFQResponseReference

An element that details the relevant references (such as contract number) pertaining to the RFQResponse.



RFQResponseReferenceType indicates what type of reference is being communicated.

### **RFQResponseReferenceType [attribute]**

*RFQResponseReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to RFQResponseReferenceType definition for any enumerations.

### **AssignedBy [attribute]**

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## RFQResponseReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.



Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## RFQResponseStatusType [attribute]

This attribute acts as a flag indicating what processing may be required.

*This item is restricted to the following list.*



### **Accepted**

The supplied information is accepted.

### **Amended**

The supplied information is changed.

### **Cancelled**

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### **Counterproposal**

The sender is presenting a different proposal.

### **Rejected**

The supplied information is rejected.

## RFQResponseSummary

A group element that contains information that summarizes the contents of the RFQResponse.

**(sequence)**


*The sequence of items below is mandatory. A single instance is required.*

### TotalNumberOfLineItems

*TotalNumberOfLineItems is optional. A single instance might exist.*

The total number of individual line items in the document, regardless of the status or type.

**(sequence)**



*The sequence of items below is mandatory. One instance is required, multiple instances might exist.*

### TotalQuantity

*TotalQuantity is mandatory. A single instance is required.*

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

### TotalInformationalQuantity

*TotalInformationalQuantity is optional. Multiple instances might exist.*

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

### LineItemSubTotal

*LineItemSubTotal is optional. A single instance might exist.*

The total amount of all e-Document LineBaseAmount(s) line items without any monetary adjustments that may occur after the e-Document line items.


### TotalAdjustments

*TotalAdjustments is optional. A single instance might exist.*

The CurrencyValue of TotalAdjustments contains the total of all MonetaryAdjustmentAmount for all instances of PriceAdjustment and FlatAmountAdjustment in the document (it excludes TaxAdjustments).

### TotalTaxAmount

*TotalTaxAmount is optional. A single instance might exist.*



# papiNet V2R31

---

The CurrencyValue of TotalTaxAmount contains the sum of all instances of TaxAdjustment in the document. TotalTaxAmount contains the sum of all instances of the MonetaryAdjustmentAmount for tax adjustments.

## **TotalNetAmount**

*TotalNetAmount is optional. A single instance might exist.*

A field containing total amount excluding tax. For example, in the Invoice TotalNetAmount is equal to the sum of LineItemSubTotal plus TotalAdjustments. TotalNetAmount encapsulates CurrencyValue.

## **TotalAmount**

*TotalAmount is mandatory. A single instance is required.*

A field containing the total amount including tax.

PurchaseOrder: The total amount, using a valid unit of measure of all the items in the e-Document. Multiple total amounts are allowed so different units of measure or grade sub-totals can be communicated.

CreditDebitNote and Invoice: TotalAmount is equal to TotalNetAmount plus TotalTaxAmount. In certain countries this is the amount that is due for payment based upon the terms of payment.

## **InformationalAmount**

*InformationalAmount is optional. Multiple instances might exist.*

A monetary amount used for information purposes only (not for calculation). For example, the invoice price adjustment subtotal is expressed in sterling pounds, and the buyer wants this information expressed in U.S. dollars.

CreditDebitNote and Invoice - The TaxAmount is displayed in the currency that is applicable throughout the e-Document. When a TaxAmount needs to be displayed in a different national currency, this field is used.

## **(sequence)**

*The sequence of items below is optional. Multiple instances might exist.*

### **TermsOfPayment**

*TermsOfPayment is mandatory. A single instance is required.*

A group item that contains agreed-to terms defining when, how, and under what conditions the payment is to be made.

When TermsOfPayment is optional; if omitted, TermsOfPayment is controlled through previous negotiation.

### **TotalNetOfTermsDiscount**

*TotalNetOfTermsDiscount is optional. A single instance might exist.*

The components of the amount to be paid if prompt payment discount terms are met, including the amount that is subject to the payment terms discount, the discount amount, and the amount due after prompt payment discount.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **TermsAndDisclaimers**

*TermsAndDisclaimers is optional. Multiple instances might exist.*


An element that contains legal information with an indication of what the Language is.

## RFQResponseValidityDate

The Date and Time within which a response to the RFQ is valid.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.


hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## RFQStatusType [attribute]

This attribute acts as a flag indicating what processing may be required.

*This item is restricted to the following list.*



### Amended

The supplied information is changed.

### Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### Original

The supplied information is the first version of that information.


## RFQSummary

Summary information that applies to the RFQ e-Document.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### TotalNumberOfLineItems



TotalNumberOfLineItems is optional. A single instance might exist.

The total number of individual line items in the document, regardless of the status or type.

### (sequence)

The sequence of items below is mandatory. One instance is required, multiple instances might exist.

#### TotalQuantity

TotalQuantity is mandatory. A single instance is required.

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

#### InformationalQuantity

InformationalQuantity is optional. Multiple instances might exist.

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

#### TotalAmount

TotalAmount is optional. A single instance might exist.

A field containing the total amount including tax.


PurchaseOrder: The total amount, using a valid unit of measure of all the items in the e-Document. Multiple total amounts are allowed so different units of measure or grade sub-totals can be communicated.

CreditDebitNote and Invoice: TotalAmount is equal to TotalNetAmount plus TotalTaxAmount. In certain countries this is the amount that is due for payment based upon the terms of payment.

#### TermsAndDisclaimers

TermsAndDisclaimers is optional. Multiple instances might exist.

An element that contains legal information with an indication of what the Language is.




## RFQType [attribute]

Defines the type of RFQ issued.

*This item is restricted to the following list.*

### StandardRFQ

The only type of RFQ.



## RGB

A definition of colour using the RGB protocol.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Red

*Red is mandatory. A single instance is required.*


The "Red" portion of the method of representing colour termed RGB.

#### Green

*Green is mandatory. A single instance is required.*

The "Green" portion of the method of representing colour termed RGB

#### Blue



*Blue is mandatory. A single instance is required.*


The "Blue" portion of the method of representing colour termed RGB.

## Ribbon

Ribbon information.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### NumberOfRibbons

*NumberOfRibbons is optional. A single instance might exist.*

The number of ribbons.

### RibbonMaterialCharacteristics

*RibbonMaterialCharacteristics is mandatory. A single instance is required.*

Ribbon material characteristics.

### RibbonExposure

*RibbonExposure is optional. A single instance might exist.*

Ribbon exposure

### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*


A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## RibbonExposure

Ribbon exposure

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

## RibbonFacingType [attribute]

The type of ribbon facing

*This item is restricted to the following list.*

**Double**

**Single**



---

## RibbonMaterialCharacteristics

Ribbon material characteristics.

### RibbonFacingType [attribute]

*RibbonFacingType is optional. A single instance might exist.*

The type of ribbon facing

Refer to RibbonFacingType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### BindingMaterialCharacteristics

*BindingMaterialCharacteristics is mandatory. A single instance is required.*

Binding Material Characteristics

#### Width


*Width is optional. A single instance might exist.*

The width of the object.

#### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## RingCrush

Ring Crush

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax


*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.



## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## RoadAccessibilityType [attribute]

Defines the largest vehicle and transport unit combination that can access the road according to the road curving, bends, hills and slopes.

*This item is restricted to the following list.*



### Trailer

Road is accessible for a truck with trailer.

### DrawBarCombination

Road is accessible for a drawbar combination.

### DrawBarCombinationWithAdjustableBogie

Road is accessible for a drawbar combination with trailer equipped with adjustable bogie.

### RigidLorry

Road is accessible for shorter vehicles that is, a rigid lorry without trailer.

---

## RoadAvailability

Defines when in the year or season the road is available.

*This item is restricted to the following list.*



### AllYear

Road is available all year for all kind of traffic.

### NotInHeavyRain

Road is not available for trucks in heavy rain periods.

### NotInSevereThawing

Road is not available for trucks in severe soil frost thawing.

### NotInWinter

Road is not available in winter season. Only available in spring, summer and autumn season.

## InWinter

Road is available for trucks only in winter season. In the Nordic region it is common with ice-roads over lakes etc in the winter season.

---

## RoadBearingCapacity

The capacity for the road to bear a load without being damaged.

### RoadBearingCapacityType [attribute]

*RoadBearingCapacityType is optional. A single instance might exist.*

Type of burden restriction for the road that is specified by RoadBearingCapacity.

Refer to RoadBearingCapacityType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



---

## RoadBearingCapacityType [attribute]

Type of burden restriction for the road that is specified by RoadBearingCapacity.

*This item is restricted to the following list.*

### BogieLoad

Maximum load for a bogie (tandem axles).

### SingleAxleLoad



Maximum axle load.

## TripleAxleLoad

Maximum load for a triple axle.

## TotalVehicleLoad

Maximum total load (gross weight) for a vehicle.

---

## RoadCharacteristics

A grouping element containing items describing characteristics specific for a road.

### RoadOwnerType [attribute]

*RoadOwnerType is optional. A single instance might exist.*

Defines the ownership for the road.

Refer to RoadOwnerType definition for any enumerations.

### RoadKeeperType [attribute]

*RoadKeeperType is optional. A single instance might exist.*

Defines the party responsible for the maintenance of the road.

Refer to RoadKeeperType definition for any enumerations.

### RoadAccessibilityType [attribute]

*RoadAccessibilityType is optional. A single instance might exist.*

Defines the largest vehicle and transport unit combination that can access the road according to the road curving, bends, hills and slopes.

Refer to RoadAccessibilityType definition for any enumerations.

### RoadTurningPossibilityType [attribute]

*RoadTurningPossibilityType is optional. A single instance might exist.*


Defines what kind of vehicle that can turn around.

Refer to RoadTurningPossibilityType definition for any enumerations.

### RoadTurningPointType [attribute]

*RoadTurningPointType is optional. A single instance might exist.*

Defines the shape of the turning point.



Refer to RoadTurningPointType definition for any enumerations.

## RoadPassingPossibility [attribute]

*RoadPassingPossibility is optional. A single instance might exist.*

Defines if it is possible for two vehicles to pass each other on the road.

Refer to RoadPassingPossibility definition for any enumerations.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### RoadName

*RoadName is optional. A single instance might exist.*

Defines the name of the road.

### RoadNumber

*RoadNumber is optional. A single instance might exist.*

Defines the official number of the road.

### RoadClassification

*RoadClassification is optional. Multiple instances might exist.*

Grouping element for items describing how roads are classified.

### RoadAvailability

*RoadAvailability is optional. Multiple instances might exist.*

Defines when in the year or season the road is available.

Refer to RoadAvailability definition for any enumerations.

### RoadBearingCapacity

*RoadBearingCapacity is optional. Multiple instances might exist.*

The capacity for the road to bear a load without being damaged.

### RoadObstruction

*RoadObstruction is optional. Multiple instances might exist.*

A grouping element containing items describing details for an obstruction on a road. If a MapPoint or MapCoordinates are specified then it marks the start point of the obstruction


---

## RoadClassification

Grouping element for items describing how roads are classified.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### RoadClassificationCode

*RoadClassificationCode is mandatory. A single instance is required.*

Classification code for the road. Code is assigned by agency.

## RoadClassificationDescription

*RoadClassificationDescription is optional. Multiple instances might exist.*

Description of the road classification.

---

## RoadClassificationCode

Classification code for the road. Code is assigned by agency.

### Agency [attribute]


*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.


Refer to Agency definition for any enumerations.



---

## RoadClassificationDescription

Description of the road classification.



---

## RoadKeeperType [attribute]

Defines the party responsible for the maintenance of the road.

*This item is restricted to the following list.*

**Public**


**Private**



---

## RoadName

Defines the name of the road.



## RoadNumber

Defines the official number of the road.

RoadNumber	
type	s20

## RoadObstruction

A grouping element containing items describing details for an obstruction on a road. If a MapPoint or MapCoordinates are specified then it marks the start point of the obstruction.

### RoadObstructionType [attribute]

*RoadObstructionType is required. A single instance must exist.*

Defines the type of hazard or obstruction on a road.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### MapPointName

*MapPointName is optional. A single instance might exist.*

A unique name for a point on a map. It is also normally the name of the corresponding waypoint in a GPS.

### MapPointComment

*MapPointComment is optional. Multiple instances might exist.*

A descriptive text for a point on a map. It is also normally shown in a GPS as a comment for the corresponding waypoint.

### MapCoordinates

*MapCoordinates is optional. Multiple instances might exist.*

A group item defining and containing position coordinates of a location.

### RoadSlopePercent

*RoadSlopePercent is optional. A single instance may exist.*

Specifies the gradient in percent for a road. A positive value indicates an uphill slope and a negative value a downhill slope


### RoadBearingCapacity

*RoadBearingCapacity is optional. Multiple instances might exist.*

The capacity for the road to bear a load without being damaged.

### Length

*Length is optional. A single instance might exist.*



The length of the object

## **Width**

*Width is optional. A single instance might exist.*

The width of the object

## **Height**

*Height is optional. A single instance might exist.*

The height of the object.

## **eAttachment**

*eAttachment is optional. A single instance might exist.*

eAttachment enables the sender to provide information about attachments to the document.

Note: An element "e-Attachment" also exists. papiNet will no longer use hyphens in our element and attribute names as this causes issues with BizTalk.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **RoadObstructionType [attribute]**

Defines the type of hazard or obstruction on a road.

*This item is restricted to the following list.*

### **Bridge**

A bridge, e.g. for crossing over a river. A bridge might be restricted by width and bearing capacity.

### **Ferry**

A ferry crossing with restrictions along a road. Typically restricted by width and bearing capacity.

### **Passage**

A section or crossing with restrictions along a road. Typically restricted by width.

### **RoadWorks**

Repairs to a road forming a hazard or obstruction to traffic.

### **Slope**

A section of a road with a gradient forming obstruction to traffic

### **UnderPass**

A section of a road that passes under another road, railway line, etc. Typically restricted by height and width.



---

## RoadOwnerType [attribute]

Defines the ownership for the road.

*This item is restricted to the following list.*

**Public**

**Private**



---


## RoadPassingPossibility [attribute]

Defines if it is possible for two vehicles to pass each other on the road.

*This item is restricted to the following list.*

**Yes**

**No**



---

## RoadSlopePercent

Specifies the gradient in percent for a road. A positive value indicates an uphill slope and a negative value a downhill slope.



---

## RoadTurningPointType [attribute]

Defines the shape of the turning point.

*This item is restricted to the following list.*

**Circle**


Circle shaped turning place.

**T-crossing**

T-cross shaped intersection.

**X-crossing**

X-shaped intersection.



---

## RoadTurningPossibilityType [attribute]

Defines what kind of vehicle that can turn around.


*This item is restricted to the following list.*

**DrawBarCombination**

Turning possibility for a drawbar combination.

**DrawBarCombinationWithAdjustableBogie**

Turning possibility for a drawbar combination with trailer equipped with adjustable bogie.



## NoTurningPossibility

There is no turning possibility, the truck has to go in reverse direction when returning.

## RigidLorry

Turning possibility for a rigid lorry without trailer.

## ThroughAccessNoTurning

There is a through access but no turning possibility.

## Trailer

Turning possibility for a truck with trailer.

---

## Roof


Defines parts and complete roofing systems.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### (choice)

*[choice] is optional because of choice construct.*



### RoofPanel

*RoofPanel is optional because of choice construct.*

Describes the roofing surface.

### RoofPackage

*RoofPackage is optional because of choice construct.*

Roof package

### RoofTruss


*RoofTruss is optional because of choice construct.*

Describes the supporting material under roofing surface.

---

## RoofingSidingDeckingFencing

A grouping element that contains the timber/lumber products that are used in roofing, siding, decking, or fencing.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### (choice)

*[choice] is optional because of choice construct.*

## **NaturalWoodSiding**

*NaturalWoodSiding is optional because of choice construct.*

Natural wood siding

## **NaturalWoodSiding-Other**

*NaturalWoodSiding-Other is optional because of choice construct.*

Natural Wood Siding - Other

## **DeckAndPorchFlooringMaterials-NaturalWood**


*DeckAndPorchFlooringMaterials-NaturalWood is optional because of choice construct.*

Deck and porch flooring materials that are used in natural wood products.

---

## **RoofPackage**


Roof package



---

## **RoofPanel**


Describes the roofing surface.



---

## **RoofTruss**

Describes the supporting material under roofing surface.



## Roughness

A group item used to communicate surface roughness target or test value according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*


The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation



# papiNet V2R31

---

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## **TwoSigmaUpper**

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## **RoundCornered [attribute]**

Is the item round cornered?

*This item is restricted to the following list.*

**Yes**

**No**

attribute
<b>RoundCornered</b>
type   yesNo

---

## **Route**

Route defines directions and characteristics for how to transport goods between two locations. A route starts at delivery origin or at the supplypoint belonging to the delivery origin.

### **RouteType [attribute]**

*RouteType is mandatory. A single instance is required.*

Defines type of start and end points for the route.

Refer to RouteType definition for any enumerations.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

#### **RouteName**

*RouteName is mandatory. A single instance is required.*

A unique name of a route. It is also normally the name of the route in a GPS.

#### **RouteComment**

*RouteComment is optional. Multiple instances might exist.*

A descriptive text for a route. It is also normally shown in a GPS as a route comment.

## SupplyPoint

*SupplyPoint is optional. A two instance might exist.*

Grouping element that contains items describing a supply point. A SupplyPoint belongs to a LocationParty, e.g. in a DeliveryOrigin or DeliveryDestination, and describes where goods are stored and can be loaded or unloaded. A SupplyPoint can for example be a loading or unloading gate at a warehouse or a road side landing at a logging area in the forest.

## MapPoint

*MapPoint is optional. Multiple instances might exist.*

A grouping element for items describing a point on a map. A mappoint is normally named waypoint in a GPS.

## RouteLength

*RouteLength is optional. A single instance might exist.*

The length for the route.

## RouteDefinition

*RouteDefinition is optional. A single instance might exist.*

List of waypoints describing the route.

## eAttachment

*eAttachment is optional. A single instance might exist.*


eAttachment enables the sender to provide information about attachments to the document.

Note: An element "e-Attachment" also exists. papiNet will no longer use hyphens in our element and attribute names as this causes issues with BizTalk.

## RouteLeg

*RouteLeg is optional. Multiple instances might exist.*

A grouping element contains items describing the route leg. A route leg is a part of a route. A route leg has its own characteristics.



---

## RouteComment


A descriptive text for a route. It is also normally shown in a GPS as a route comment.



## RouteDefinition

List of waypoints describing the route.

### RouteDefinitionFormat [attribute]



*RouteDefinitionFormat is mandatory. A single instance is required.*

The format of the RouteDefinition.

Refer to RouteDefinitionFormat definition for any enumerations.


## RouteDefinitionFormat [attribute]

The format of the RouteDefinition.

*This item is restricted to the following list.*

### gpx

GPX (the GPS Exchange Format) is a light-weight XML data format for the interchange of GPS data (waypoints, routes, and tracks) between applications and Web services on the Internet.



## RouteLeg

A grouping element contains items describing the route leg. A route leg is a part of a route. A route leg has its own characteristics.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### RouteLegNumber

*RouteLegNumber is mandatory. A single instance is required.*

A sequential number for the legs of the route.

#### RouteLegName

*RouteLegName is optional. A single instance might exist.*

A unique name for a route leg.

#### OtherParty


*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

#### MapPoint

*MapPoint is optional. Multiple instances might exist.*

A grouping element for items describing a point on a map. A mappoint is normally named waypoint in a GPS.



## RouteLegLength

*RouteLegLength is optional. A single instance might exist.*

The length for the route leg.

## RoadCharacteristics

*RoadCharacteristics is optional. A single instance might exist.*

A grouping element containing items describing characteristics specific for a road.

## eAttachment

*eAttachment is optional. A single instance might exist.*

eAttachment enables the sender to provide information about attachments to the document.

Note: An element "e-Attachment" also exists. papiNet will no longer use hyphens in our element and attribute names as this causes issues with BizTalk.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## RouteLegLength

The length for the route leg.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*


The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



---

## RouteLegName


A unique name for a route leg.



---

## RouteLegNumber

A sequential number for the legs of the route.



---

## RouteLength

The length for the route.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*


The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



---

## RouteName

A unique name of a route. It is also normally the name of the route in a GPS.



---

## RouteType [attribute]

Defines type of start and end points for the route.

*This item is restricted to the following list.*


### DeliveryOriginToDeliveryDestination

The route is specified from a delivery origin to a delivery destination.

### DeliveryOriginToMainIntersection

The route is specified from a delivery origin to a main road intersection.

### MainIntersectionToDeliveryDestination



The route is specified from a main road intersection to a delivery destination.

## SupplyPointToDeliveryDestination

The route is specified from a supply point within a delivery origin to a delivery destination.

## SupplyPointToMainIntersection

The route is specified from a supply point within a delivery origin to a main road intersection.

## RowsPerUnit

The number of rows of items, are to be placed/packaged within the unit. Usually used to identify the standard number of rows in a standard packaging unit of the product.

<b>RowsPerUnit</b>	
type	nonNegativeInteger

## RunnabilityIndex

A group item used to communicate the calculated run-ability index target or test value.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*


Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test



# papiNet V2R31

---

Refer to ResultSource definition for any enumerations.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

### SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

### TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

### TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## SafetyAndEnvironmentalCertification

Safety and Environmental Certification

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*


#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin

*RangeMin is optional. A single instance might exist.*



The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.


## RangeMax

*RangeMax is optional. A single instance might exist.*


The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## SafetyAndEnvironmentalInformation

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement



to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).



### SafetyAndEnvironmentalType [attribute]

*SafetyAndEnvironmentalType is mandatory. A single instance is required.*

The type of safety and environmental information being communicated. Defines any additional information relating to safety and/or environmental matters.

Refer to SafetyAndEnvironmentalType definition for any enumerations.

### Agency [attribute]

*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### LicenceNumber

*LicenceNumber is optional. A single instance might exist.*

Licence number.

Note: the spelling of this element conforms to papiNet's use of UK English.

## **ChainOfCustody**

*ChainOfCustody is optional. A single instance might exist.*

The chain of custody.

## **SafetyAndEnvironmentalCertification**

*SafetyAndEnvironmentalCertification is optional. A single instance might exist.*

Safety and Environmental Certification

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **SafetyAndEnvironmentalType [attribute]**

The type of safety and environmental information being communicated. Defines any additional information relating to safety and/or environmental matters.



*This item is restricted to the following list.*

**Agricultural**

**Biodegradable**

**Certified**

**Chemical**

**CSA**

Canadian Standards Authority

**Energy**

**FlamabilityReactivity**

**FSC**

To be deprecated in a future version use FSCMixed, FSCPure, or FSCRecycled

**FSCMixed**

Material contains a mixture of Forest Stewardship Council (FSC) certified material, reclaimed (recycled) material and/or controlled wood. It has been processed by an FSC chain of custody certified company, and has been identified as FSC Mixed.

For more information about the Forest Stewardship Council, visit [www.fsc.org](http://www.fsc.org).

**FSCPure**

Material is 100% FSC material from an Forest Stewardship Council (FSC) certified forest. It has been sold and/or processed by an FSC chain of custody

certified company, and has been identified as FSC Pure.

For more information about the Forest Stewardship Council, visit <http://www.fsc.org/>.

## FSCRecycled

This Forest Stewardship Council (FSC) product group contains 100% post-consumer reclaimed. Post-consumer reclaimed material includes wood and/or wood fiber that has been reclaimed from a product after that product has been used for its intended end-use purpose by individuals or businesses.

For more information about the Forest Stewardship Council, visit [www.fsc.org](http://www.fsc.org).

## HazardousMaterial

## MaterialSafetyData

## MTCC

Malaysian Timber Certification Council

## PEFC

Program for the Endorsement of Forest Certification

## Recycled

## SFI

Sustainable Forestry Initiative

## TransportationSafetyAlert

---

## SalesOfficeParty

This named party represents the sales office involved in the business transaction. This party is only used in the communication of OrderStatus otherwise it is handled via OtherParty.

### LogisticsRole [attribute]

*LogisticsRole is optional. A single instance might exist.*

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### PartyIdentifier

*PartyIdentifier is optional. Multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.



## **NameAddress**

*NameAddress is mandatory. A single instance is required.*

A group item containing name and address of an organisation or business entity.

## **URL**

*URL is optional. A single instance might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

## **CommonContact**

*CommonContact is optional. Multiple instances might exist.*

Identifies a specific individual associated with the party.

---

## **SampleSize**

The number of samples used to determine the product characteristic in question.

<b>SampleSize</b>
type nni3

---

## **SampleType [attribute]**

Communicates how sampling was done to measure the product characteristics.

*This item is restricted to the following list.*

attribute
<b>SampleType</b>
type sampleType

### **Average**

The measurement represents an average for the associated property.

### **Bottom**

The measurement was obtained from the bottom of the paper sample.

### **CDAverage**

The measurement represents the average of values in the cross-machine direction.

### **CDBottom**

The measurement represents the average of tests taken in the cross-machine direction on the bottom of the paper sample.

### **CDTop**

The measurement represents the average of tests taken in the cross-machine direction on the top of the paper sample.

### **MDAverage**

The measurement represents the average of values in the machine direction.

### **MDBottom**

The measurement represents the average of tests taken in the machine direction on the bottom of the paper sample.

### **MDTop**

The measurement represents the average of tests taken in the machine direction on the top of the paper sample.

## Target

When communicating specifications a target value is communicated.

## Top

The measurement was obtained from the top of the paper sample

---

## Saturation

Measure of colour Saturation in the HSB method of communicating colour.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).



#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

#### SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

#### TwoSigmaLower


*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

#### TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.



## Sawdust

Used to report sawdust content in chips as a detail measurement.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.


#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*



# papiNet V2R31

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper


*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## ScaleHouseID

Unique identifier for the specific scale house.



---

## ScaleHouseIn

Used to identify scale weight received into a yard, the scale house id, name, and scaler name.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ScaleHouseID

*ScaleHouseID is optional. A single instance might exist.*

Unique identifier for the specific scale house.

#### ScaleHouseName

*ScaleHouseName is optional. A single instance might exist.*

Name assigned to the scale house.

#### ScalerID

*ScalerID is optional. A single instance might exist.*


Unique identifier for the person staffing the scale house. Might be an employee number.

#### ScalerName

*ScalerName is optional. A single instance might exist.*

Name of the person staffing the scale house.

#### Quantity



*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## InformationalQuantity

*InformationalQuantity is optional. A single instance might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

---

## ScaleHouseInfo

Scale house information.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ScaleHouseIn

*ScaleHouseIn is optional. A single instance might exist.*

Used to identify scale weight received into a yard, the scale house id, name, and scaler name.

#### ScaleHouseOut

*ScaleHouseOut is optional. A single instance might exist.*

Used to identify scale weight departing a yard, the scale house id, name, and scaler name.

#### ScaleHouseTicketNumber

*ScaleHouseTicketNumber is optional. A single instance might exist.*

The ticket number issued by the scale house. Does not have to be unique.

#### ArrivalDate

*ArrivalDate is optional. A single instance might exist.*

The date of arrival.


#### DepartureDate

*DepartureDate is optional. A single instance might exist.*

The required or actual date of departure.

#### Quantity

*Quantity is mandatory. A single instance is required.*



# papiNet V2R31

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## InformationalQuantity

*InformationalQuantity is optional. A single instance might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

---

## ScaleHouseName

Name assigned to the scale house.

<b>ScaleHouseName</b>
type s60

---

## ScaleHouseOut

Used to identify scale weight departing a yard, the scale house id, name, and scaler name.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ScaleHouseID

*ScaleHouseID is optional. A single instance might exist.*

Unique identifier for the specific scale house.

#### ScaleHouseName

*ScaleHouseName is optional. A single instance might exist.*

Name assigned to the scale house.

#### ScalerID

*ScalerID is optional. A single instance might exist.*

Unique identifier for the person staffing the scale house. Might be an employee number.


#### ScalerName

*ScalerName is optional. A single instance might exist.*

Name of the person staffing the scale house.

#### Quantity

*Quantity is mandatory. A single instance is required.*



# papiNet V2R31

---

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. A single instance might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

---

## **ScaleHouseTicketNumber**

The ticket number issued by the scale house. Does not have to be unique.

<b>ScaleHouseTicketNumber</b>	
type	s60

---

## **ScalerID**

Unique identifier for the person staffing the scale house. Might be an employee number.

<b>ScalerID</b>	
type	s60

---

## **ScalerName**

Name of the person staffing the scale house.

<b>ScalerName</b>	
type	s60

## ScaleTicket

The ScaleTicket element is the root element for the ScaleTicket e-Document.

The ScaleTicket e-Document provides wood or fibre suppliers with a means to electronically incorporate scale system receiving data into their accounting systems from buying entities' back office systems.

### ScaleTicketStatusType [attribute]

*ScaleTicketStatusType is mandatory. A single instance is required.*

ScaleTicket Status Type

Refer to ScaleTicketStatusType definition for any enumerations.

### ScaleTicketAcceptance [attribute]

*ScaleTicketAcceptance is mandatory. A single instance is required.*

Defines the state of the goods received as compared to the DeliveryMessage specifications. The enumeration list is the list of choices that apply to the GoodsReceipt header and line item.

Refer to ScaleTicketAcceptance definition for any enumerations.

### ScaleTicketRejectedType [attribute]

*ScaleTicketRejectedType is optional. A single instance might exist.*

ScaleTicketRejectedType

Refer to ScaleTicketRejectedType definition for any enumerations.

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.


Refer to Language definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ScaleTicketHeader

*ScaleTicketHeader is mandatory. A single instance is required.*



Information that is common for the ScaleTicket e-Document.

## **ScaleTicketLineItem**

*ScaleTicketLineItem is mandatory. One instance is required, multiple instances might exist.*

The details for each item reported on a ScaleTicket e-Document.

## **ScaleTicketSummary**


*ScaleTicketSummary is optional. A single instance might exist.*

Summary information for the ScaleTicket e-Document.

---

## **ScaleTicketAcceptance [attribute]**

Defines the state of the goods received as compared to the DeliveryMessage specifications. The enumeration list is the list of choices that apply to the GoodsReceipt header and line item.



*This item is restricted to the following list.*

### **GoodsReceivedAsIs**

The delivered goods were received without inspection, or checking of the goods for damage, or accuracy against the DeliveryMessage.

### **GoodsReceivedAsSpecified**

Received goods agree completely with all DeliveryMessage specifications for all lines including item identifiers and item weights. There is no transit damage.

### **GoodsReceivedCancelled**

Received goods notification is being cancelled. This value is only used when the GoodsReceiptStatusType is "Cancelled".

### **GoodsReceivedRejected**

Received goods agree completely with all DeliveryMessage specifications for all lines including item identifiers and item weights; but there has been transit damage resulting in rejection of all goods.

### **GoodsReceivedWithDamage**

Received goods agree completely with all DeliveryMessage specifications for all lines including item identifiers and item weights; but there has been transit damage of some items. All transit damages must be specified.

### **GoodsReceivedWithVariance**

Received goods do not agree completely with the DeliveryMessage specifications. For those items at variance, actual received item identifiers and item weights must be specified.

Additionally, used with the VarianceType of "NotReceived" to indicate items that was on the DeliveryMessage but not in the Delivery as received.

### **GoodsReceivedWithVarianceAndDamage**

Received goods do not agree completely with all DeliveryMessage specifications for all lines including item identifiers and item weights and there has been transit damage of some items. For those items at variance or with

transit damage, actual received item identifiers, item weights, and transit damages must be specified.

## ScaleTicketHeader

Information that is common for the ScaleTicket e-Document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ScaleTicketNumber


*ScaleTicketNumber is mandatory. A single instance is required.*

Unique identifier for the ScaleTicket e-Document.

#### TransactionHistoryNumber

*TransactionHistoryNumber is mandatory. A single instance is required.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the



TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

#### ScaleTicketIssueDate

*ScaleTicketIssueDate is mandatory. A single instance is required.*

The date and time when the ScaleTicket was issued.

#### ScaleTicketReference

*ScaleTicketReference is optional. Multiple instances might exist.*

An element that details the relevant references pertaining to the ScaleTicket.

Identifies the previous unique document ID that this document replaces, if applicable.

Mandatory if Purpose = Replace.

#### ScaleHouseInfo


*ScaleHouseInfo is mandatory. A single instance is required.*

Scale house information.

#### BuyerParty

*BuyerParty is mandatory. A single instance is required.*

The legal entity to which the product is sold. Also commonly referred to as the sold-



to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## **SupplierParty**

*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. A single instance might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **ShipToParty**

*ShipToParty is optional. A single instance might exist.*

The name and/or address to which the goods should be delivered with the party type indicated by the PartyType attribute.

## **BillToParty**

*BillToParty is optional. A single instance might exist.*

The address where the invoice is to be sent.

## **RemitToParty**

*RemitToParty is optional. A single instance might exist.*

A group item containing details of the party to whom payment will be made. The RemitToParty contains all information related to remittance.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **DeliveryInfo**

*DeliveryInfo is mandatory. A single instance is required.*

Information about the delivery.

## **AdditionalText**

*AdditionalText is optional. A single instance might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific

elements.


---

## ScaleTicketIssueDate

The date and time when the ScaleTicket was issued.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is mandatory. A single instance is required.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## ScaleTicketLineItem

The details for each item reported on a ScaleTicket e-Document.

### ScaleTicketAcceptance [attribute]

*ScaleTicketAcceptance is mandatory. A single instance is required.*

Defines the state of the goods received as compared to the DeliveryMessage specifications. The enumeration list is the list of choices that apply to the GoodsReceipt header and line item.

Refer to ScaleTicketAcceptance definition for any enumerations.

### ScaleTicketRejectedType [attribute]

*ScaleTicketRejectedType is optional. A single instance might exist.*

ScaleTicketRejectedType

Refer to ScaleTicketRejectedType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ScaleTicketLineNumber

*ScaleTicketLineNumber is mandatory. A single instance is required.*

ScaleTicket Line Number

#### Product

*Product is mandatory. A single instance is required.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.


#### Quantity

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

#### InformationalQuantity



# papiNet V2R31

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **AdditionalText**

*AdditionalText is optional. A single instance might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **ScaleTicketLineNumber**

ScaleTicket Line Number

<b>ScaleTicketLineNumber</b>
type   lineNumberType

---

## **ScaleTicketNumber**

Unique identifier for the ScaleTicket e-Document.

<b>ScaleTicketNumber</b>
type   s60

---

## **ScaleTicketReference**

An element that details the relevant references pertaining to the ScaleTicket.

Identifies the previous unique document ID that this document replaces, if applicable.

<b>ScaleTicketReference</b>
type   s255

attributes
<b>ScaleTicketReferenceType</b>
type   referenceType
<b>AssignedBy</b>
type   partyType

Mandatory if Purpose = Replace.

### **ScaleTicketReferenceType [attribute]**

*ScaleTicketReferenceType is mandatory. A single instance is required.*

ScaleTicketReferenceType indicates what type of reference is being communicated.

ScaleTicketReferenceType indicates what type of reference is being communicated. Many items are currently prefixed by "Buyer", "Customer", "Seller", and/or "Supplier". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to ScaleTicketReferenceType definition for any enumerations.

### **AssignedBy [attribute]**

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy definition for any enumerations.


---

## ScaleTicketReferenceType [attribute]

ScaleTicketReferenceType indicates what type of reference is being communicated.

ScaleTicketReferenceType indicates what type of reference is being communicated. Many items are currently prefixed by "Buyer", "Customer", "Seller", and/or "Supplier". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.



---

## ScaleTicketRejectedType [attribute]

ScaleTicketRejectedType

*This item is restricted to the following list.*

### **ExcessiveTransitDamage**

The item(s) is/are damaged beyond acceptable use during transit.

### **ProductQuality**

The delivery did not match the quality of the product ordered or requested.

### **TooEarly**

The delivery has occurred prior to the agreed delivery date/time. For example, there is insufficient storage at the delivered time.

### **TooLate**

The delivery has occurred after the agreed delivery date/time. For example, delivered after press date.

### **UnableToUnload**


The delivered items cannot be unloaded. For example, damaged vehicle doors, load has shifted during transportation, or ShipTo requires reels to be palletised but they are delivered on the vehicle floor.

### **WrongBarCode**

The barcode used to identify the product is incorrect.

### **WrongBasisWeight**

The basis weight of the product is not what was ordered.



## **WrongDeliveryLocation**

The product was delivered to the wrong location.

## **WrongDiameter**

The diameter delivered is unusable. For example, a physical limitation on a reel stand is exceeded.

## **WrongLabel**

The delivered item has incorrect or missing information, or incorrect label stock that would prevent its use. For example, insufficient peel-off barcode labels.

## **WrongProduct**

The delivered item was not the product ordered or requested.

## **WrongReelWidth**

The width of the reel is incorrect.

## **WrongVehicleType**

The items have been delivered in a vehicle that cannot be unloaded at the ShipTo facility. For example, the ShipTo requires side unloading vehicles, but the delivery vehicle can only be unloaded from the rear.

## **WrongWrap**

The delivered item is wrapped in material that will prevent its use. For example, a hole is not present in the end cap for vacuum lifting.

---

## **ScaleTicketStatusType [attribute]**

ScaleTicket Status Type

*This item is restricted to the following list.*

### **Amended**

The supplied information is changed.

### **Cancelled**


The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### **Original**

The supplied information is the first version of that information.

### **Replaced**

The supplied information is replacing earlier supplied information. The receiver should revalidate the information in their system based upon the entire information received.




## ScaleTicketSummary

Summary information for the ScaleTicket e-Document.

**(sequence)**

*The sequence of items below is mandatory. A single instance is*

*required.*



### TotalNumberOfLineItems

*TotalNumberOfLineItems is optional. A single instance might exist.*

The total number of individual line items in the document, regardless of the status or type.

**(sequence)**

*The sequence of items below is mandatory. One instance is required, multiple instances might exist.*

### TotalQuantity

*TotalQuantity is mandatory. A single instance is required.*

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

### TotalInformationalQuantity

*TotalInformationalQuantity is optional. A single instance might exist.*

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

### TermsAndDisclaimers

*TermsAndDisclaimers is optional. A single instance might exist.*

An element that contains legal information with an indication of what the Language is.

---


## Scored [attribute]

Is this item scored?

*This item is restricted to the following list.*

**Yes**

**No**



---


## Screened [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

**Yes**

**No**



---

## Seasoning

Describes drying/ moisture control method.

### SeasoningType [attribute]

*SeasoningType is optional. A single instance might exist.*

Seasoning type, the classification and methodology of seasoning applied to the product.

Refer to SeasoningType definition for any enumerations.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### AdditionalText

*AdditionalText is optional. A single instance might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



---

## SeasoningType [attribute]

Seasoning type, the classification and methodology of seasoning applied to the product.

*This item is restricted to the following list.*

### Dry

Air dried lumber that is not surfaced ... i.e. rough lumber.

### Green

Not dried by any method.

### KD

Kiln dried.

### KDAT

Kiln dried after treatment... i.e. chemically treated, then redried.

### PAD

Partially air dried. In practice, doesn't mean much, since you don't know how dry. Most commonly used on boards



## ShippingDry

Dried sufficiently to enable shipment without any deterioration in condition.

## SurfacedDry

Surfaced-dry, meaning the product was dried (manner unspecified) and then surfaced (i.e. planed). Level of dryness is understood to be as required by the grading standard for the species in question. Generally it means the product was air dried to the standard, but it could have been kiln dried.

## SurfacedGreen

Surfaced while still green.

## Secure [attribute]

This attribute indicates that the product requires a secure manufacturing plant. For example when manufacturing ACT booklets and other testing products.

*This item is restricted to the following list.*

**Yes**


**No**

attribute	
<b>Secure</b>	
type	yesNo
default	No

## SenderParty

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.



### PartyType [attribute]

*PartyType is mandatory. A single instance is required.*

Identifies the business role associated with the particular party

Refer to PartyType definition for any enumerations.

### LogisticsRole [attribute]

*LogisticsRole is optional. A single instance might exist.*

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.

## (sequence)

The sequence of items below is mandatory. A single instance is required.

### PartyIdentifier

PartyIdentifier is optional. Multiple instances might exist.

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

### NameAddress

NameAddress is mandatory. A single instance is required.

A group item containing name and address of an organisation or business entity.

### URL

URL is optional. A single instance might exist.

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

### CommonContact

CommonContact is optional. Multiple instances might exist.

Identifies a specific individual associated with the party.

---

## SenderProductAttributesDescription

An element containing free text used to describe the set of products sent in the ProductAttributes.

### Language [attribute]

Language is optional. A single instance might exist.

SenderProductAttributesDescription	
type	s72

attributes	
Language	
type	languageType
default	eng

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

---

## SenderProductAttributesIdentifier

A unique identifier assigned to the combination of products, properties, and ReceivingParty that makes this list of ProductAttributes unique from the SendingParty's point of view. Subsequent ProductAttributes with updates will use this same identifier.

SenderProductAttributesIdentifier	
type	s30

---

## SenderProductAttributesName

The name given to the set of products sent in the ProductAttributes e-Document.


SenderProductAttributesName	
type	s45

## SequenceNumber

SequenceNumber	
type	nni2

## ServiceLevel

A grouping element containing information about a service level. The service level can be specified in a Service Level Agreement (SLA) detailing requirements such as delivery, performance, pricing, quality, etc.



### ServiceLevelContextType [attribute]

*ServiceLevelContextType is mandatory. A single instance is required.*

Indicates the nature of what is included in the service level.

Refer to ServiceLevelContextType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ServiceLevelText

*ServiceLevelText is optional. Multiple instances might exist.*

Text that is describing the service level.

#### ServiceLevelReference

*ServiceLevelReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the ServiceLevel. The type of reference is identified by the attributes ServiceLevelReferenceType and AssignedBy.

## ServiceLevelContextType [attribute]

Indicates the nature of what is included in the service level.

*This item is restricted to the following list.*

### Delivery

The service level is given for deliveries.


### Production

The service level is given for production.



## ServiceLevelReference

An element detailing relevant references pertaining to the ServiceLevel. The type of reference is identified by the attributes



ServiceLevelReferenceType and AssignedBy.

### ServiceLevelReferenceType [attribute]

*ServiceLevelReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier.

Refer to ServiceLevelReferenceType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is mandatory. A single instance is required.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

## ServiceLevelReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier.

*This item is restricted to the following list.*

### DeliveryChargeAccountNumber

Account Number to which the delivery charges are billed.


### ServiceLevelAgreementNumber

The unique identifier given to a service level agreement.



## ServiceLevelText

Text that is describing the service level.



## ShapeOfHole [attribute]

The shape of the hole


*This item is restricted to the following list.*

### Elongated

The shape of the hole is elongated.

### Oval

The shape of the hole is ovular.



## Round

The shape of the hole is round.

## Square

The shape of the hole is square.

## Other

The shape of the hole is other.

---

## SetNumber

The part of the radius of the Tambour that constitutes the reel.

<b>SetNumber</b>	
type	nni2

---

## SetPosition

The position of the reel in relation to the reels cut across the Tambour.

<b>SetPosition</b>	
type	nni2

---

## ShapeOfHole [attribute]

The shape of the hole

*This item is restricted to the following list.*

### Elongated

The shape of the hole is elongated.

### Oval

The shape of the hole is ovular.

### Round

The shape of the hole is round.

### Square

The shape of the hole is square.

### Other

The shape of the hole is other.

attribute	
<b>ShapeOfHole</b>	
type	holeShapeType


---

## Sheet

A group item that contains the conversion and packaging characteristics for sheets.

### (sequence)

*The sequence of items below is mandatory. A single*



instance is required.

## SheetConversionCharacteristics

*SheetConversionCharacteristics is optional. A single instance might exist.*

A group item that lists the conversion elements describing how a sheets are converted from a tambour.

## SheetPackagingCharacteristics

*SheetPackagingCharacteristics is optional. A single instance might exist.*

A group item that contains elements relative to the sheet packaging.

## SheetConcern

If the ConcernIndicatorType is "Y" then a defect cause must be given.

### SheetConcernType [attribute]

*SheetConcernType is optional. A single instance might exist.*

Sheet Concern Type

Refer to SheetConcernType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### SheetConcernCode

*SheetConcernCode is optional. A single instance might exist.*

Code used to identify problem with the sheet.

### SheetConcernDescription


*SheetConcernDescription is optional. A single instance might exist.*

Description used to narrate the problem with the sheet.

### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.




## SheetConcernCode

Code used to identify problem with the sheet.

### Agency [attribute]

*Agency is mandatory. A single instance is required.*



Describes the agency maintaining the list of codes. To be included in this

list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

---

## SheetConcernDescription

Description used to narrate the problem with the sheet.

SheetConcernDescription	
type	s72

---

## SheetConcernType [attribute]

Sheet Concern Type

*This item is restricted to the following list.*

**BladeOrApplicatorRollStreaks**

**BowedEdges**

**CaliperVariation**

**CoatedBladeScratch**

**CoatingStreaks**

**ColouredFibres**

**Curling**

**CutterWrinkles**

**Dirt**

**DyeStreaks**

**FeltMarks**

**Mottle**

**Other**

**OutOfSquareOrSize**

**ShadeVariation**

**SheetRelatedProblems**

**SlimeHole**

**SlimeSpot**

**StaticElectricity**

**Stretching**

**SurfaceDefectsOther**

**TightEdges**

attribute
SheetConcernType
type sheetConcerns

WavyEdges

WireHole

WrinklesOther

## SheetConversionCharacteristics

A group item that lists the conversion elements describing how a sheets are converted from a tambour.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### ConversionCode

*ConversionCode is optional. A single instance might exist.*

A code, as assigned by an Agency, used to identify a group of conversion characteristics.

### GrainDirection

*GrainDirection is optional. A single instance might exist.*

Defines the primary orientation/alignment (Long or Short) of the cellulose fibres in a sheet or web of paper, which results from the flow of fibres in a water suspension during the papermaking process.

Refer to GrainDirection definition for any enumerations.

### WindingDirection

*WindingDirection is optional. A single instance might exist.*

An element that indicates how the material is wound on the reel.

Refer to WindingDirection definition for any enumerations.

### SheetSize

*SheetSize is optional. Multiple instances might exist.*

A group item that contains elements relative to the sheet size.

### TargetProductWeight

*TargetProductWeight is optional. A single instance might exist.*


The desired weight of the finished product.

### PunchedHoleDetails

*PunchedHoleDetails is optional. Multiple instances might exist.*

A grouping element that will contain the configuration information for punched holes.

### CuttingDetails



*CuttingDetails is optional. Multiple instances might exist.*

Cutting Details provides information on how to cut the sheet.

## Embossing

*Embossing is optional. Multiple instances might exist.*

Embossing requirements for sheets and reels. Embossing involves a physical deformation of the paper surface as part of the conversion process. Embossing is applied either in-line (directly after the paper machine) or off-line. Refer to the attribute FinishType for additional information.

## Watermark

*Watermark is optional. Multiple instances might exist.*

Watermark information

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## SheetCount

A group item that contains information relative to the number of sheets per packaging type.

### SheetCountMethodType [attribute]

*SheetCountMethodType is optional. A single instance might exist.*

Defines the method used to count the sheets.

Refer to SheetCountMethodType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PerCarton

*PerCarton is optional. A single instance might exist.*

A field indicating the number of sheets per carton.

#### PerReam

*PerReam is optional. A single instance might exist.*

A field indicating the number of sheets per ream.


#### PerPallet

*PerPallet is optional. A single instance might exist.*

A field indicating the number of sheets on the pallet.

#### PerTab

*PerTab is optional. A single instance might exist.*



A field indicating the number of sheets per tab marking.

## SheetCountMethodType [attribute]

Defines the method used to count the sheets.

*This item is restricted to the following list.*

### Counter

Sheets will be counted using a counter at the cutter.

### Laser

Sheets will be counted using a laser scanner.

### NominalGrammage

The number of sheets will be calculated using the nominal grammage and the actual weight of the sheets.

attribute	
<b>SheetCountMethodType</b>	
type	countMethod

## SheeterConcerns

SheeterConcerns is a group element that provides information about an event on a sheeter.

### MachineStoppage [attribute]

*MachineStoppage is optional. A single instance might exist.*

An indicator on whether the production had to be periodically stopped.

Refer to MachineStoppage definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### SheetConcern

*SheetConcern is mandatory. One instance is required, multiple instances might exist.*

If the ConcernIndicatorType is "Y" then a defect cause must be given.

#### EventDate

*EventDate is optional. A single instance might exist.*

The date the incident or delay on press was recorded.


#### PositionInSheet

*PositionInSheet is optional. A single instance might exist.*

Location in the sheet where the defect was identified.

#### MachineLocation

*MachineLocation is optional. A single instance might exist.*



# papiNet V2R31

A unique and defined area in the operating machine. On a printing press it would include areas such as: "Splicer", "Infeed", "Print Unit", "folder", "Silicone coater". Also see PressBreakLocation.

## WasteImpressions

*WasteImpressions is optional. A single instance might exist.*

The number of bad revolutions produced on a printing unit.

## MachineDownTime

*MachineDownTime is optional. A single instance might exist.*

The length of loss production time that a machine experienced due to malfunction regardless of cause.

## SheeterConditions

Identifies the environmental conditions when the sheet was printed on.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Humidity

*Humidity is optional. Multiple instances might exist.*

Humidity

#### AmbientTemperature

*AmbientTemperature is optional. Multiple instances might exist.*

The temperature of the surrounding environment.

#### MachineSpeed


*MachineSpeed is optional. Multiple instances might exist.*

The rate at which the machine is, was, or should be running.

#### Tension

*Tension is optional. Multiple instances might exist.*

Tension of the web on the printing press.



## SheetItem


A group item consisting potentially of the date the sheets were converted into sheets and/or packaged or finished.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DateSheeted

*DateSheeted is optional. A single instance might exist.*



## papiNet V2R31

---

The Date and optionally the Time that the paper was sheeted.

### **DateFinished**

*DateFinished is optional. A single instance might exist.*

The Date and optionally the Time that an item was finished. For example, this could be the wrapping date for a reel or ream or the date the sheet(s) were packaged in preparation for shipment

## SheetPackagingCharacteristics

A group item that contains elements relative to the sheet packaging.

### ActionType [attribute]

*ActionType is optional. A single instance might exist.*

Used to trigger an action concerning the element to which it refers.

Refer to ActionType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### PackagingCode

*PackagingCode is optional. Multiple instances might exist.*

PackagingCode is a code describing the packaging of the product.

### PackagingDescription

*PackagingDescription is optional. Multiple instances might exist.*

A text field element describing the packaging of a product.

### ReamType

*ReamType is optional. Multiple instances might exist.*

The textual description of the method used to make up the reams..

Refer to ReamType definition for any enumerations.

### ReamWeight

*ReamWeight is optional. Multiple instances might exist.*

The target weight of a ream of paper.

### MWeight

*MWeight is optional. Multiple instances might exist.*

The weight of 1000 sheets.

### SheetCount

*SheetCount is optional. Multiple instances might exist.*



A group item that contains information relative to the number of sheets per packaging type.

### UnitsPerCarton

*UnitsPerCarton is optional. Multiple instances might exist.*

The number of units per box.

### Wrap



# papiNet V2R31

---

*Wrap is optional. Multiple instances might exist.*

A group item that organises wrapping detail information.

## **BandCharacteristics**

*BandCharacteristics is optional. Multiple instances might exist.*

A group item that organises the packaging band detail information.

## **PalletCharacteristics**

*PalletCharacteristics is optional. Multiple instances might exist.*

A group item that provides pallet detail information.

## **LabelCharacteristics**

*LabelCharacteristics is optional. Multiple instances might exist.*

A group item that organises the labeling information.

## **StencilCharacteristics**

*StencilCharacteristics is optional. Multiple instances might exist.*

A group element specifying attributes of a stencil to be applied to an item, and optional text.

## **MaximumHeight**

*MaximumHeight is optional. A single instance might exist.*

The maximum height allowed including the pallet.

## **MaximumGrossWeight**

*MaximumGrossWeight is optional. A single instance might exist.*

The maximum weight allowed including the pallet.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **SheetSize**

A group item that contains elements relative to the sheet size.

### **(choice)**

*[choice] is optional because of choice construct.*

### **(sequence)**


*The sequence of items below is mandatory. A single instance is required.*

### **Length**

*Length is mandatory. A single instance is required.*

The length of the object.

### **Width**



# papiNet V2R31

*Width is mandatory. A single instance is required.*

The width of the object.

## PaperSizeType


*PaperSizeType is optional because of choice construct.*

A field that defines the sheet size using the DIN standard (DINA4, DINA3, and so on).

---

## ShellColour

Shell colour



---

## ShellType [attribute]

The type of shell

*This item is restricted to the following list.*

**SonicWeld**

**FiveScrew**




---

## ShipFromCharacteristics

A group item that provides information pertaining to the Ship-From Party.

ShipFromCharacteristics may be referenced at both the header and line item level. The reference at the header, if it exists, acts as a default for the value at the line level, unless overridden at the line level.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### ShipFromParty

*ShipFromParty is mandatory. A single instance is required.*

The name and/or address from which the goods will be delivered with the party type indicated by the PartyType attribute.

### (choice)

*[choice] is optional because of choice construct.*

### SupplyPoint

*SupplyPoint is optional because of choice construct.*

Grouping element that contains items describing a supply point. A SupplyPoint belongs to a LocationParty, e.g. in a DeliveryOrigin or DeliveryDestination, and

describes where goods are stored and can be loaded or unloaded. A SupplyPoint can for example be a loading or unloading gate at a warehouse or a road side landing at a logging area in the forest.

## LocationCode

*LocationCode is optional because of choice construct.*

A code used to identify a specific physical location within a site identified by a party, e.g. a loading station in a warehouse or an unloading station at a printer site.

LocationCode will be deprecated in a future version. Use SupplyPoint instead of LocationCode.

## ShipFromParty

The name and/or address from which the goods will be delivered with the party type indicated by the PartyType attribute.

### PartyType [attribute]

*PartyType is mandatory. A single instance is required.*

Identifies the business role associated with the particular party

Refer to PartyType definition for any enumerations.

### LogisticsRole [attribute]

*LogisticsRole is optional. A single instance might exist.*

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### PartyIdentifier

*PartyIdentifier is optional. Multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

#### NameAddress

*NameAddress is mandatory. A single instance is required.*


A group item containing name and address of an organisation or business entity.

#### URL

*URL is optional. A single instance might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

#### CommonContact



*CommonContact is optional. Multiple instances might exist.*

Identifies a specific individual associated with the party.

## ShipmentComplete [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

**Yes**

**No**

attribute	
<b>ShipmentComplete</b>	
type	yesNo
default	No

## ShipmentDetails

A group element containing information that relates to the shipment details for the line item.

### ShipmentDetailsType [attribute]

*ShipmentDetailsType is mandatory. A single instance is required.*

Provides information about the shipment's status

Refer to ShipmentDetailsType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### ShipToParty

*ShipToParty is mandatory. A single instance is required.*

The name and/or address to which the goods should be delivered with the party type indicated by the PartyType attribute.

### Quantity

*Quantity is mandatory. A single instance is required.*


The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

### InformationalQuantity

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for



calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## ShipmentLoadDetails

*ShipmentLoadDetails is optional. Multiple instances might exist.*

A group element that containing information that relates to the shipment load details for the line item. Carrier and transport information may be detailed.

## OtherParty

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

---

## ShipmentDetailsType [attribute]

Provides information about the shipment's status

*This item is restricted to the following list.*

### Forecast

The shipment has not yet taken place

### Shipment

The shipment has taken place.




---

## ShipmentEventDate

Date of the event.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be

in discord with other users of XML.

## ShipmentEventDuration

The length of time for the shipment event being described.



The lexical representation for duration is the [ISO 8601] extended format PnYn MnDTnH nMnS, where nY represents the number of years, nM the number of months, nD the number of days, 'T' is the date/time separator, nH the number of hours, nM the number of minutes and nS the number of seconds. The number of seconds can include decimal digits to arbitrary precision. E.g. 25 hours = PT25H, 1 day and 34 minutes = P1DT23M.

## ShipmentEventIdentifier

Text to identify the Shipment Event. The Carrier should report the latest status available to the requestor.

### ShipmentEventType [attribute]

*ShipmentEventType is mandatory. A single instance is required.*

Indicates the type of event.

Refer to ShipmentEventType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is mandatory. A single instance is required.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.


Refer to AssignedBy definition for any enumerations.

### ShipmentEventQualifierType [attribute]

*ShipmentEventQualifierType is optional. A single instance might exist.*

Provides additional details related to the general shipment event.

Refer to ShipmentEventQualifierType definition for any enumerations.



## ShipmentEventInformation

A grouping element that contains the items that describe the shipment event and status situation

**(sequence)**


*The sequence of items below is mandatory. A single instance is required.*

### ShipmentEventIdentifier

*ShipmentEventIdentifier is mandatory. A single instance is required.*

Text to identify the Shipment Event. The Carrier should report the latest status available to the requestor.

### ShipmentEventDate



*ShipmentEventDate is mandatory. A single instance is required.*

Date of the event.

### ShipmentStatusIdentifier

*ShipmentStatusIdentifier is mandatory. A single instance is required.*

Text to identify the status of the event.

### ShipmentEventReference

*ShipmentEventReference is optional. Multiple instances might exist.*

An item detailing relevant references pertaining to the shipment event information. The type of reference is identified by the ShipmentEventReferenceType attribute.

### ShipmentStatusDescription

*ShipmentStatusDescription is optional. Multiple instances might exist.*

Text field that may further describe the event's status in detail.

### ShipmentStatusDate

*ShipmentStatusDate is optional. A single instance might exist.*

Date of the status of the event.


### ShipmentEventDuration

*ShipmentEventDuration is optional. A single instance might exist.*

The length of time for the shipment event being described.

The lexical representation for duration is the [ISO 8601] extended format PnYn MnDTnH nMnS, where nY represents the number of years, nM the number of months, nD the number of days, 'T' is the date/time separator, nH the number of hours, nM the number of minutes and nS the number of seconds. The number of seconds can include decimal digits to arbitrary precision. E.g. 25 hours = PT25H, 1 day and 34 minutes = P1DT23M.

### DeliveryDateWindow



*DeliveryDateWindow is optional. Multiple instances might exist.*

A group item defining the date/time interval for delivery to take place. An element which may contain the estimated date for which delivery is expected. This date is not absolute.

### **QuantityInformation**

*QuantityInformation is optional. A single instance might exist.*

A group item containing information about quantity and informational quantity of similar items.

### **LocationInformation**

*LocationInformation is optional. A single instance might exist.*

A grouping element describing the location of the shipment.

### **TransportInformation**

*TransportInformation is optional. A single instance might exist.*

A grouping element for transport information.

### **ShipmentIncident**

*ShipmentIncident is optional. Multiple instances might exist.*

A grouping element that contains information about the shipment incident.

---

## **ShipmentEventQualifierType [attribute]**

Provides additional details related to the general shipment event.

*This item is restricted to the following list.*

### **Scheduled**

The event has been scheduled.

### **Arrived**

The vehicle has arrived.

### **Started**

The event has started.

### **Completed**

The event has ended.

### **Departed**

The vehicle has departed.

### **DocumentationCompleted**


Documentation has been completed.



---

## ShipmentEventReference

An item detailing relevant references pertaining to the shipment event information. The type of reference is identified by the



ShipmentEventReferenceType attribute.

### **ShipmentEventReferenceType [attribute]**

*ShipmentEventReferenceType is mandatory. A single instance is required.*

ShipmentEventReferenceType provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Customer", "Seller", and/or "Supplier". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to ShipmentEventReferenceType definition for any enumerations.

### **AssignedBy [attribute]**

*AssignedBy is optional. A single instance might exist.*


Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## ShipmentEventReferenceType [attribute]

ShipmentEventReferenceType provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Customer", "Seller", and/or "Supplier". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.



Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

---

## ShipmentEventType [attribute]

Indicates the type of event.

*This item is restricted to the following list.*

**Loading**




## Unloading

---

### ShipmentID

The ShipmentID may be a Bill of Lading Marking, which is customer's reference mark on each package used for logistic purposes. Should not be mixed up with Bill of Lading number. Another example of ShipmentID is grouping by a ContainerID.



### ShipmentIDType [attribute]

*ShipmentIDType is optional. A single instance might exist.*

Shipment ID Type

Refer to ShipmentIDType definition for any enumerations.

---

### ShipmentIDType [attribute]

Shipment ID Type

*This item is restricted to the following list.*

#### BillOfLadingMark


Assigning party's reference mark on each package used for logistic purposes (a mark which is painted to packages just to make handling easier). Not to be confused with Bill of Lading Number.

#### ContainerID

Container ID.


#### LotIdentifier

A unique code used to identify a grouping of product with one set of quality statistics common to all members of that group. Synonym: Lot Number



## ShipmentIncident

A grouping element that contains information about the shipment incident.



### ShipmentIncidentDate

*ShipmentIncidentDate is mandatory. A single instance is required.*

The date of the shipment incident being reported.

### (choice)

*[choice] is optional because of choice construct.*

#### ShipmentIncidentCode

*ShipmentIncidentCode is optional because of choice construct.*

The ECTA-EPCA-CEFIC codes for shipment incidents. This element is validated (via patterns) to ensure that only valid codes are entered. Refer to [www.ecta.be](http://www.ecta.be) for more information.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ShipmentIncidentPartOfSupplyChain

*ShipmentIncidentPartOfSupplyChain is mandatory. A single instance is required.*

The ECTA-EPCA-CEFIC codes for the part of the supply chain within which the shipment incident occurred. Refer to [www.ecta.be](http://www.ecta.be) for more information.

Refer to ShipmentIncidentPartOfSupplyChain definition for any enumerations.

#### ShipmentIncidentCategory

*ShipmentIncidentCategory is mandatory. A single instance is required.*

The ECTA-EPCA-CEFIC codes for shipment incident categorization. Refer to [www.ecta.be](http://www.ecta.be) for more information.

Refer to ShipmentIncidentCategory definition for any enumerations.

#### ShipmentIncidentAccountability

*ShipmentIncidentAccountability is mandatory. A single instance is required.*

The ECTA-EPCA-CEFIC codes for shipment incident accountability. Refer to [www.ecta.be](http://www.ecta.be) for more information.

Refer to ShipmentIncidentAccountability definition for any enumerations.

## ShipmentIncidentCause

*ShipmentIncidentCause is optional. Multiple instances might exist.*

The ECTA-EPCA-CEFIC codes for shipment incident cause. Refer to [www.ecta.be](http://www.ecta.be) for more information.

Refer to ShipmentIncidentCause definition for any enumerations.

## AdditionalText


*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## ShipmentIncidentAccountability

The ECTA-EPCA-CEFIC codes for shipment incident accountability. Refer to [www.ecta.be](http://www.ecta.be) for more information.



*This item is restricted to the following list.*

**Haulier**

**Final Customer**

(There is a space between these words.)

**Supplier**

**Force Majeure**

Events beyond the control of anyone. (There is a space between these words.)

## Agency [attribute]

*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.


For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

## ShipmentIncidentCategory

The ECTA-EPCA-CEFIC codes for shipment incident categorization. Refer to [www.ecta.be](http://www.ecta.be) for more information.



*This item is restricted to the following list.*

### **DateAndTime**

Corresponds to the "Date & Time" ECTA-EPCA-CEFIC option.

### **Equipment**

### **Product**

### **Packaging**

### **Documentation**

### **Safety**

### **Behaviour**

## **Agency [attribute]**

*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.


For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

---

## ShipmentIncidentCause

The ECTA-EPCA-CEFIC codes for shipment incident cause. Refer to [www.ecta.be](http://www.ecta.be) for more information.



*This item is restricted to the following list.*

### **Human Error**

(There is a space between words.)

### **Communication/Information/Instructions/Instructions/Failure**

### **Documents Failure**

(There is a space between words.)

### **Breakdown of equipment**

(There is a space between words.)

**Product or packaging damage**

(There is a space between words.)

**Wrong equipment**

(There is a space between words.)

**Non-availability****Rush order**

(There is a space between words.)

**Accident****Theft and Vandalism**

(There is a space between words.)

**Unsafe conditions**

(There is a space between words.)

**Upon request**

(There is a space between words.)

**Third party**

(There is a space between words.)

**Excessive customs clearance**

(There is a space between words.)

**Traffic****Strike****Weather****Agency [attribute]**

*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

---

**ShipmentIncidentCode**

The ECTA-EPCA-CEFIC codes for shipment incidents.


This element is validated

(via patterns) to ensure

that only valid codes are

entered. Refer to

[www.ecta.be](http://www.ecta.be) for more information.



## Agency [attribute]

Agency is mandatory. A single instance is required.

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.


---

## ShipmentIncidentDate

The date of the shipment incident being reported.

### (sequence)

The sequence of items below is mandatory. A single instance is required.



### Date

Date is mandatory. A single instance is required.

A group element that contains the specification of Year, Month, and Day.

### Time

Time is optional. A single instance might exist.

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

---

## ShipmentIncidentPartOfSupplyChain

The ECTA-EPCA-CEFIC codes for the part of the supply chain within which the shipment incident occurred. Refer to [www.ecta.be](http://www.ecta.be) for more information.



*This item is restricted to the following list.*

**Delivery**

**Loading**

**Agency [attribute]**

*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

## ShipmentLoadDetails

A group element that containing information that relates to the shipment load details for the line item. Carrier and transport information may be detailed.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### DeliveryMessageNumber

*DeliveryMessageNumber is optional. A single instance might exist.*

A unique delivery identifier assigned to each DeliveryMessage as agreed between the trading partners.

### DeliveryMessageReference

*DeliveryMessageReference is optional. Multiple*



*instances might exist.*

An element that identifies the relevant references pertaining to the DeliveryMessage, identified by DeliveryMessageReferenceType.

### CarrierParty

*CarrierParty is optional. A single instance might exist.*

The party performing the transport of the product from the pickup location to the ship-to location; could be a hauler.

**(sequence)**

*The sequence of items below is optional. A single instance might exist.*

### SupplierOrderNumber

*SupplierOrderNumber is mandatory. A single instance is required.*

The number of the supplier order.

### SupplierOrderLineItemNumber


*SupplierOrderLineItemNumber is optional. A single instance might exist.*

The number of the line item on the supplier order.

### LocationParty

*LocationParty is optional. Two instances might exist.*

The organization or business entity where the business event took place or will take



place.

## **Quantity**

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

## **TransportUnitCharacteristics**

*TransportUnitCharacteristics is optional. A single instance might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

## **TransportLoadingCharacteristics**

*TransportLoadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be loaded.

## **TransportUnloadingCharacteristics**

*TransportUnloadingCharacteristics is optional. A single instance might exist.*

A group item defining how the transported items are to be unloaded.

## **TransportOtherInstructions**

*TransportOtherInstructions is optional. Multiple instances might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

## **TransportStatus**

*TransportStatus is optional. A single instance might exist.*

Text element used to communicate the current status of the shipment actually being transported to the recipient. This element could indicate the tracking status that the transport company issues. Alternatively, it could be the vendor's internal tracking status of the shipment.

## **TransportStatusIssueDate**

*TransportStatusIssueDate is optional. A single instance might exist.*

The Date and Time the transport status is issued.

## DeliveryDateWindow

*DeliveryDateWindow is optional. Multiple instances might exist.*

A group item defining the date/time interval for delivery to take place. An element which may contain the estimated date for which delivery is expected. This date is not absolute.

## ShipmentMethodOfPayment

An element communicating responsibility of freight payment and when transfer of ownership will occur.

### LocationQualifier [attribute]

*LocationQualifier is optional. A single instance might exist.*

An attribute of the shipment method of payment describing the location to which the delivery terms refer. This location determines where and when the goods ownership is transferred from the seller to the buyer.

Refer to LocationQualifier definition for any enumerations.


### Method [attribute]

*Method is optional. A single instance might exist.*

An attribute of the shipment method of payment, which defines the responsibilities of buyers and sellers for delivery under a sales contract.

It especially determines the obligations of the seller and the buyer regarding the payment of the freight costs.

Refer to Method definition for any enumerations.



## ShipmentStatus


The ShipmentStatus element is the root element for the ShipmentStatus e-Document.

The ShipmentStatus e-Document is sent to communicate the status of a shipment or consignment with references to other documents. Typically, a ShipmentStatus e-Document is sent from the forwarder or carrier to the consignor / forwarder.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.



# papiNet V2R31

Refer to Language definition for any enumerations.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### ShipmentStatusHeader

*ShipmentStatusHeader is mandatory. A single instance is required.*

The ShipmentStatusHeader contains information common to the entire ShipmentStatus e-Document.

### ShipmentStatusShipment

*ShipmentStatusShipment is mandatory. One instance is required, multiple instances might exist.*

The shipment or consignment details that are being communicated.


---

## ShipmentStatusDate

Date of the status of the event.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.


hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

---

## ShipmentStatusDescription

Text field that may further describe the event's status in detail.




## ShipmentStatusHeader

The ShipmentStatusHeader contains information common to the entire ShipmentStatus e-Document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### ShipmentStatusNumber

*ShipmentStatusNumber is mandatory. A single instance is required.*

Reference number assigned to the e-Document by the issuer.

### ShipmentStatusIssueDate

*ShipmentStatusIssueDate is mandatory. A single instance is required.*

The date and optional time when the ShipmentStatus e-Document was issued.

### RequestNumber

*RequestNumber is optional. A single instance might exist.*

A unique tracking number specifically identifying the InfoRequest e-Document to the originator. The tracking number is returned with the "information", the answer, to help match the answer to the request.

### SenderParty

*SenderParty is mandatory. A single instance is required.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

### ReceiverParty

*ReceiverParty is mandatory. A single instance is required.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.



---

## ShipmentStatusIdentifier

Text to identify the status of the event.

### ShipmentStatusType [attribute]

*ShipmentStatusType is mandatory. A single instance is required.*



Identifies the status of the shipment being reported.

Refer to ShipmentStatusType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is mandatory. A single instance is required.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy definition for any enumerations.


---

## ShipmentStatusIssueDate

The date and optional time when the ShipmentStatus e-Document was issued.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is mandatory. A single instance is required.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

---

## ShipmentStatusNumber


The unique identifier for the ShipmentStatus e-Document.

<b>ShipmentStatusNumber</b>	
type	s30

---

## ShipmentStatusReference

An item detailing relevant references pertaining to the ShipmentStatus information. The type of reference is identified by the



ShipmentStatusReferenceType attribute.

### **ShipmentStatusReferenceType [attribute]**

*ShipmentStatusReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to ShipmentStatusReferenceType definition for any enumerations.

### **AssignedBy [attribute]**

*AssignedBy is optional. A single instance might exist.*


Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## ShipmentStatusReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.



Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## ShipmentStatusRequestDetail

A grouping element that provides the parameters to be used when responding with a shipment status information (using the ShipmentStatus e-Document).

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### SupplierParty

*SupplierParty is optional. Multiple instances might exist.*

The organisation or business entity responsible for



providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

#### BuyerParty

*BuyerParty is optional. Multiple instances might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

#### ShipToParty

*ShipToParty is optional. Multiple instances might exist.*

The name and/or address to which the goods should be delivered with the party type indicated by the PartyType attribute.

#### ForwarderParty

*ForwarderParty is optional. Multiple instances might exist.*

The trading partner involved in the forwarding of the shipment.

#### CarrierParty

*CarrierParty is optional. Multiple instances might exist.*

The party performing the transport of the product from the pickup location to the ship-to location; could be a hauler.

#### OtherParty


*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

#### ShipmentStatusSearchReference

*ShipmentStatusSearchReference is mandatory. One instance is required, multiple instances might exist.*

Used to specify a transport-related item that is used, as a parameter, when



providing shipment status information.



## **DateTimeRange**

*DateTimeRange is optional. A single instance might exist.*

The delivery date and/or time range.

## **ShipmentStatusSearchReference**

Used to specify a transport-related item that is used, as a parameter, when providing shipment status information.



## **ShipmentStatusSearchReferenceType [attribute]**

*ShipmentStatusSearchReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to ShipmentStatusSearchReferenceType definition for any enumerations.

## **AssignedBy [attribute]**


*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

## **ShipmentStatusSearchReferenceType [attribute]**

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-



prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## ShipmentStatusShipment

The shipment or consignment details that are being communicated.

### LegStageType [attribute]

*LegStageType is optional. A single instance might exist.*

Refer to LegStageType definition for any enumerations.

### ShipmentComplete [attribute]

*ShipmentComplete is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to ShipmentComplete definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ShipmentStatusReference

*ShipmentStatusReference is mandatory. One instance is required, multiple instances might exist.*

An item detailing relevant references pertaining to the ShipmentStatus information. The type of reference is identified by the ShipmentStatusReferenceType attribute.


#### TimePeriod

*TimePeriod is optional. A single instance might exist.*

The TimePeriod element is used to communicate a duration period of time as indicated in PeriodType.

#### ShipmentEventInformation

*ShipmentEventInformation is mandatory. One*



# papiNet V2R31

---

*instance is required, multiple instances might exist.*

A grouping element that contains the items that describe the shipment event and status situation

## **SupplierParty**

*SupplierParty is optional. Multiple instances might exist.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **BuyerParty**

*BuyerParty is optional. Multiple instances might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## **ShipToParty**

*ShipToParty is optional. Multiple instances might exist.*

The name and/or address to which the goods should be delivered with the party type indicated by the PartyType attribute.

## **ForwarderParty**

*ForwarderParty is optional. Multiple instances might exist.*

The trading partner involved in the forwarding of the shipment.

## **CarrierParty**

*CarrierParty is optional. Multiple instances might exist.*

The party performing the transport of the product from the pickup location to the ship-to location; could be a hauler.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **ShipmentStatusType [attribute]**

Identifies the status of the shipment being reported.


*This item is restricted to the following list.*

### **OnTime**

The shipment is on-time.

### **Early**

The shipment is before planned schedule.



## Delayed

The shipment has been delayed.

## Cancelled

The shipment was cancelled. Do not deliver this product.

## Rejected

The shipment has been rejected.

## Unspecified

When a status is required to be communicated but none is available.

---

## ShipmentSummary

Summary information for an entire shipment

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### TotalQuantity

*TotalQuantity is optional. A single instance might exist.*

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

#### TotalInformationalQuantity

*TotalInformationalQuantity is optional. Multiple instances might exist.*

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

#### ProductSummary


*ProductSummary is optional. A single instance might exist.*

Group of elements to provide summary information on product level.

#### LengthSpecification

*LengthSpecification is optional. Multiple instances might exist.*

Length specification of the wood product.




## ShippingInstructions

The ShippingInstructions element is the root element for the ShippingInstructions e-Document.

The ShippingInstructions e-Document communicates delivery information for product(s) supported by a PurchaseOrder.

ShippingInstructions



### ShippingInstructionsType [attribute]

*ShippingInstructionsType is mandatory. A single instance is required.*

ShippingInstructionType defines the type of shipping instruction

Refer to ShippingInstructionsType definition for any enumerations.

### ShippingInstructionsStatusType [attribute]

*ShippingInstructionsStatusType is mandatory. A single instance is required.*

ShippingInstructions Status Type

Refer to ShippingInstructionsStatusType definition for any enumerations.

### IsThirdPartyAdvice [attribute]

*IsThirdPartyAdvice is optional. A single instance might exist.*

An advice to a third party of a ShippingInstructions.

Refer to IsThirdPartyAdvice definition for any enumerations.

### IsThirdPartyShipment [attribute]

*IsThirdPartyAdvice is optional. A single instance might exist.*

Shipment request to a party other than the party that ordered the product from the supplier.

Either "Yes" or "No".

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### ShippingInstructionsHeader

*ShippingInstructionsHeader is mandatory. A single instance is required.*

Information common to all items in a ShippingInstructions e-Document.

## (choice)

*[choice] is optional because of choice construct.*

### ByProduct

*ByProduct is optional because of choice construct.*

Identification takes place by product.

### ByShipTo

*ByShipTo is optional because of choice construct.*

ByShipTo

### ShippingInstructionsSummary


*ShippingInstructionsSummary is optional. A single instance might exist.*

Summary information for the ShippingInstructions e-Document.

---

## ShippingInstructionsConfirmationIssuedDate

The date on which the shipping instruction confirmation was issued.



## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.


hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however,

within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## ShippingInstructionsHeader

Information common to all items in a ShippingInstructions e-Document.



### ShippingInstructionsHeaderStatusType [attribute]

*ShippingInstructionsHeaderStatusType is optional. A single instance might exist.*

ShippingInstructions Header Status Type

Refer to ShippingInstructionsHeaderStatusType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ShippingInstructionsInformation

*ShippingInstructionsInformation is mandatory. A single instance is required.*

A group item containing information unique to this ShippingInstructions and reference information used to identify the product to be shipped

#### BuyerParty

*BuyerParty is mandatory. A single instance is required.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

#### BillToParty

*BillToParty is optional. A single instance might exist.*

The address where the invoice is to be sent.

#### SupplierParty

# papiNet V2R31

---

*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **SenderParty**

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## **ReceiverParty**

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **ShippingInstructionsHeaderStatusType [attribute]**

ShippingInstructions Header Status Type

*This item is restricted to the following list.*



### **Accepted**

The supplied information is accepted.

### **Amended**

The supplied information is changed.

### **NoAction**

The supplied information has not been amended and thereby requires no action.

### **Original**

The supplied information is the first version of that information.

## Rejected


The supplied information is rejected.

## ShippingInstructionsInformation

A group item containing information unique to this ShippingInstructions and reference information used to identify the product to be shipped

(sequence)

The sequence of items below is



mandatory. A single instance is required.

### ShippingInstructionsNumber

ShippingInstructionsNumber is mandatory. A single instance is required.

The unique shipping instruction.

### ShippingInstructionsIssuedDate

ShippingInstructionsIssuedDate is mandatory. A single instance is required.

The date on which the shipping instruction was issued.

### ShippingInstructionsConfirmationIssuedDate

ShippingInstructionsConfirmationIssuedDate is optional. A single instance might exist.

The date on which the shipping instruction confirmation was issued.

### TransactionHistoryNumber

TransactionHistoryNumber is optional. A single instance might exist.

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

### TransactionHistoryConfirmationNumber

TransactionHistoryConfirmationNumber is optional. A single instance might exist.

A sequential number that indicates the version of the confirmation document being sent.

### ShippingInstructionsReference

ShippingInstructionsReference is optional. Multiple instances might exist.

A group item detailing relevant references (such as ISBN) pertaining to the ShippingInstructions and/or product being shipped.


---

## ShippingInstructionsIssuedDate

The date on which the shipping instruction was issued.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*


Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

ShippingInstructionsLineItemByProduct



ShippingInstructionsLineItemByProduct

**ShippingInstructionsLineItemStatusType [attribute]**

*ShippingInstructionsLineItemStatusType is mandatory. A single instance is required.*

ShippingInstructions Line Item Status Type

Refer to ShippingInstructionsLineItemStatusType definition for any enumerations.

**IsThirdPartyShipment [attribute]**

*IsThirdPartyAdvice is optional. A single instance might exist.*

Shipment request to a party other than the party that ordered the product from the supplier.

Either "Yes" or "No".

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**ShippingInstructionsLineItemNumber**

*ShippingInstructionsLineItemNumber is mandatory. A single instance is required.*

The sequential number that uniquely identifies the ShippingInstructions line item.

**ShippingInstructionsReference**

# papiNet V2R31

*ShippingInstructionsReference is optional. Multiple instances might exist.*

A group item detailing relevant references (such as ISBN) pertaining to the ShippingInstructions and/or product being shipped.

## ShipToInformation

*ShipToInformation is mandatory. One instance is required, multiple instances might exist.*

Group element containing information about the ship to and delivery of a product.

## PackagingCharacteristics

*PackagingCharacteristics is optional. Multiple instances might exist.*

An element containing carton or pallet packing information.

PackagingCharacteristics can either have the BoxCharacteristics or PalletPackagingCharacteristics element not both.


## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## ShippingInstructionsLineItemByShipTo

ShippingInstructions  
Line Item By Ship To



## ShippingInstructionsLineItemStatusType [attribute]

*ShippingInstructionsLineItemStatusType is mandatory. A single instance is required.*

ShippingInstructions Line Item Status Type

Refer to ShippingInstructionsLineItemStatusType definition for any enumerations.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**ShippingInstructionsLineItemNumber**

*ShippingInstructionsLineItemNumber is mandatory. A single instance is required.*

The sequential number that uniquely identifies the ShippingInstructions line item.

**ShippingInstructionsReference**

*ShippingInstructionsReference is optional. Multiple instances might exist.*

A group item detailing relevant references (such as ISBN) pertaining to the ShippingInstructions and/or product being shipped.

**(choice)**

*[choice] is optional because of choice construct.*

**Product**

*Product is optional because of choice construct.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

**ShippingInstructionsPurchaseOrderLineItem**

*ShippingInstructionsPurchaseOrderLineItem is optional because of choice construct.*

PurchaseOrder line item information for PurchaseOrder being referenced in ShippingInstructions.

**OtherDate**

*OtherDate is optional. Multiple instances might exist*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

**DeliverySchedule**

*DeliverySchedule is mandatory. One instance is required, Multiple instances might exist.*

A group item defining a series of DeliveryDateWindow(s) in which specified quantities must be delivered.

**PackagingCharacteristics**

*PackagingCharacteristics is optional. Multiple instances might exist.*

An element containing carton or pallet packing information. PackagingCharacteristics can either have the BoxCharacteristics or PalletPackagingCharacteristics element not both.

**AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## ShippingInstructionsLineItemNumber

The sequential number that uniquely identifies the ShippingInstructions line item.

ShippingInstructionsLineItemNumber	
type	lineNumberType

---

## ShippingInstructionsLineItemStatusType [attribute]

ShippingInstructions Line Item Status Type

*This item is restricted to the following list.*

attribute	ShippingInstructionsLineItemStatusType	
type	shippingInstructionsLineItemStatusType	

### Accepted

The supplied information is accepted.

### Amended

The supplied information is changed.

### Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### NoAction

The supplied information has not been amended and thereby requires no action.

### Original

The supplied information is the first version of that information.

### Pending

The supplied information is not complete and will be updated later.

### Rejected

The supplied information is rejected.

---

## ShippingInstructionsNumber

The unique shipping instruction.


ShippingInstructionsNumber	
type	s30

## ShippingInstructionsPurchaseOrderLineItem

PurchaseOrder line item information for PurchaseOrder being referenced in ShippingInstructions.

**(sequence)**

*The sequence of items below is mandatory. A*



*single instance is required.*

### PurchaseOrderLineItemNumber

*PurchaseOrderLineItemNumber is mandatory. A single instance is required.*

The sequential number that uniquely identifies the PurchaseOrder line item.

### PurchaseOrderInformation

*PurchaseOrderInformation is mandatory. A single instance is required.*

A group item containing information unique to this PurchaseOrder, which is provided by the buyer. PurchaseOrderInformation can be optional in the supply chain. Invoices are created without having a PurchaseOrder in Vendor Managed Inventory. Freight invoices also will not have a PurchaseOrder number.

### PackageIdentifier

*PackageIdentifier is optional. A single instance might exist.*

The identifier of the productpackage (such as reel ID or pallet ID) that is used along with the PurchaseOrderLineItemNumber to call off the product.

### ProductIdentification

*ProductIdentification is optional. Multiple instances might exist.*

A grouping element designed to communicate product identification related to the parent element that contains this item.


### Classification

*Classification is optional. Multiple instances might exist.*

A group item that details the product classification according to a particular organization's scheme. An item across multiple classifications would still be recognized as the same item. Examples of some product classifications are: Containerboard, Pulp-Dissolving, or Newsprint.

## ShippingInstructionsReference

A group item detailing relevant references (such as ISBN) pertaining to the



ShippingInstructions and/or product

being shipped.

## **ShippingInstructionsReferenceType [attribute]**

*ShippingInstructionsReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to ShippingInstructionsReferenceType definition for any enumerations.

## **AssignedBy [attribute]**

*AssignedBy is optional. A single instance might exist.*


Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## **ShippingInstructionsReferenceType [attribute]**

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.



Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

## ShippingInstructionsRequestDetail

ShippingInstructionsRequestDetail is a conditional element. Its existence is mutually exclusive from the other approaches to requesting information.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### SupplierParty

*SupplierParty is optional. Multiple instances might exist.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

#### BuyerParty

*BuyerParty is optional. Multiple instances might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

#### ShipToParty

*ShipToParty is optional. Multiple instances might exist.*

The name and/or address to which the goods should be delivered with the party type indicated by the PartyType attribute.

#### ForwarderParty

*ForwarderParty is optional. Multiple instances might exist.*

The trading partner involved in the forwarding of the shipment.

#### CarrierParty

*CarrierParty is optional. Multiple instances might exist.*

The party performing the transport of the product from the pickup location to the ship-to location; could be a hauler.

#### OtherParty


*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

#### ByPurchaseOrder

*ByPurchaseOrder is mandatory. One instance is required, multiple instances might exist.*

Selection criteria for communicating purchase order information.



## ShippingInstructionsStatusType [attribute]

ShippingInstructions Status Type

*This item is restricted to the following list.*



### Accepted

The supplied information is accepted.

### Amended

The supplied information is changed

### Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### Original

The supplied information is the first version of that information.

### Rejected


The supplied information is rejected.

## ShippingInstructionsSummary

Summary information for the ShippingInstructions e-Document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### TotalNumberOfLineItems

*TotalNumberOfLineItems is optional. A single instance might exist.*

The total number of individual line items in the document, regardless of the status or type.

### (sequence)

*The sequence of items below is optional. Multiple instances might exist.*

### TotalQuantity

*TotalQuantity is mandatory. A single instance is required.*

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

### TotalInformationalQuantity

*TotalInformationalQuantity is optional. Multiple instances might exist.*

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

## TermsAndDisclaimers

*TermsAndDisclaimers is optional. Multiple instances might exist.*

An element that contains legal information with an indication of what the Language is.

## ShippingInstructionsType [attribute]

ShippingInstructionType defines the type of shipping instruction.

*This item is restricted to the following list.*

### ShippingInstructionsConfirmation

Confirmation of the Shipping Instruction.

### ShippingInstructionsDistribution

Shipping Instruction serves as a billable order for shipping product that was produced under a previous manufacturing order.

### ShippingInstructionsPackaging

To be deprecated in a future version. Guidance will be given to trading partners not to use this enumeration.

### ShippingInstructionsRouting

Shipping instructions issued in conjunction with a PurchaseOrder for shipping the product.

## ShippingMark

A shipping mark identifies the producer and quality on the end side of the product. Not to be mixed with company code/logo or other product marking.

ShippingMark
type s20

## ShipToCharacteristics

A group item that provides information important for the Ship-To Party.


A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level.

The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### ShipToParty



*ShipToParty is mandatory. A single instance is required.*

The name and/or address to which the goods should be delivered with the party type indicated by the PartyType attribute.

## (choice)

*[choice] is optional because of choice construct.*

### SupplyPoint

*SupplyPoint is optional because of choice construct.*

Grouping element that contains items describing a supply point. A SupplyPoint belongs to a LocationParty, e.g. in a DeliveryOrigin or DeliveryDestination, and describes where goods are stored and can be loaded or unloaded. A SupplyPoint can for example be a loading or unloading gate at a warehouse or a road side landing at a logging area in the forest.

### LocationCode

*LocationCode is optional because of choice construct.*

A code used to identify a specific physical location within a site identified by a party, e.g. a loading station in a warehouse or an unloading station at a printer site.

LocationCode will be deprecated in a future version. Use SupplyPoint instead of LocationCode.

### TermsOfDelivery

*TermsOfDelivery is optional. A single instance might exist.*

A group item defining the terms under which the delivery of goods will take place. These terms determine when and under what conditions the transfer of ownership will occur. Generally speaking, the Incoterms are primarily used in Europe, whereas the ShipmentMethodOfPayment is primarily used in North America.

### DeliveryRouteCode

*DeliveryRouteCode is optional. A single instance might exist.*

A code representing the delivery route as indicated by the Agency.

---


## ShipToInformation

Group element containing information about the ship to and delivery of a product.

### (sequence)

*The sequence of items*

*below is mandatory. A single instance is required.*



### ShipToCharacteristics

*ShipToCharacteristics is mandatory. A single instance is required.*

A group item that provides information important for the Ship-To Party.

A group item that provides information important for the Ship-To Party. ShipToCharacteristics may be referenced at both the header and line item level. The reference at the header is required and acts as a default for the value at the line level, unless overridden at the line level.

### DeliverySchedule

*DeliverySchedule is optional. Multiple instances might exist.*

A group item defining a series of DeliveryDateWindow(s) in which specified quantities must be delivered.

## ShipToParty

The name and/or address to which the goods should be delivered with the party type indicated by the PartyType attribute.

### PartyType [attribute]

*PartyType is mandatory. A single instance is required.*

Identifies the business role associated with the particular party

Refer to PartyType definition for any enumerations.

### LogisticsRole [attribute]

*LogisticsRole is optional. A single instance might exist.*

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### PartyIdentifier

*PartyIdentifier is optional. Multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

### NameAddress

*NameAddress is mandatory. A single instance is required.*

A group item containing name and address of an organisation or business entity.

### URL


*URL is optional. A single instance might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

### CommonContact

*CommonContact is optional. Multiple instances might exist.*

Identifies a specific individual associated with the party.



## ShowThrough

Show through

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax


*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.



## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## Side

The structure defines the features of a panel's side. An attribute of side element indicates which side (either top or bottom) the child elements refer to.

### TopSide [attribute]

*TopSide is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to TopSide definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Surface

*Surface is optional. A single instance might exist.*

### PlywoodPlyGrade

*PlywoodPlyGrade is optional. A single instance might exist.*

Defines the grade of one ply, used with Agency to specify the grading agency.


### Embossing

*Embossing is optional. A single instance might exist.*

Embossing requirements for sheets and reels. Embossing involves a physical deformation of the paper surface as part of the conversion process. Embossing is applied either in-line (directly after the paper machine) or off-line. Refer to the attribute FinishType for additional information.

### PlywoodMachining

*PlywoodMachining is optional. A single instance might exist.*



# papiNet V2R31

PlywoodMachining defines the machining made to the panel (for example, grooving).

## SideOneTime

The time for side one.

<b>SideOneTime</b>
type duration

## SideTwoTime

The time for side two.

<b>SideTwoTime</b>
type duration

## SignatureID

Signature ID

<b>SignatureID</b>
type s30

## Signatures

Signatures.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### PagesPerSignature

*PagesPerSignature is mandatory. A single instance is required.*

Pages per signature

### NumberOfSignatures


*NumberOfSignatures is mandatory. A single instance is required.*

The number of signatures.

### SignatureID

*SignatureID is optional. A single instance might exist.*

Signature ID




## SingleWidthReel

Single width reel information.

**(sequence)**

*The sequence*



of items below is mandatory. A single instance is required.

## SingleWidthReelConversionCharacteristics

*SingleWidthReelConversionCharacteristics is optional. A single instance might exist.*

The conversion characteristics associated with a single width reel.

## ReelPackagingCharacteristics

*ReelPackagingCharacteristics is optional. A single instance might exist.*

A group item that lists the packaging elements describing how a reel should be packed.

## SingleWidthReelConversionCharacteristics

The conversion characteristics associated with a single width reel.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### WindingDirection

*WindingDirection is optional. A single instance might exist.*



An element that indicates how the material is wound on the reel.

Refer to WindingDirection definition for any enumerations.

### TrimmedOrderType

*TrimmedOrderType is optional. A single instance might exist.*

Trimmed Order Type

Refer to TrimmedOrderType definition for any enumerations.

### ReelWidth

*ReelWidth is optional. A single instance might exist.*

The width of reel from edge to edge excluding packaging.

### ReelDiameter

*ReelDiameter is optional. A single instance might exist.*

The diameter measurement of reel excluding packaging.


### ReelLength

*ReelLength is optional. A single instance might exist.*

The total length of the paper on the reel.

### CoreCharacteristics

*CoreCharacteristics is optional. A single instance might exist.*



A group item that details information used to fully define a core.

## MaximumNumberOfJoins

*MaximumNumberOfJoins is optional. A single instance might exist.*

The maximum number of joins requested (permitted). Permits customers to indicate join-free reels.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## SizeOfHolePunch

A definition of the size and shape of the punched holes.

### ShapeOfHole [attribute]

*ShapeOfHole is optional. A single instance might exist.*

The shape of the hole

Refer to ShapeOfHole definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## Sizing

A group item used to communicate size test of paper by ink resistance target or test value.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*


The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation



*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## **TwoSigmaUpper**

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## **Sleeve**

Sleeve.

### **SpineLabel [attribute]**

*SpineLabel is mandatory. A single instance is required.*

The sleeve spine label.

### **(sequence)**


*The sequence of items below is mandatory. A single instance is required.*

### **SleeveInsertType**

*SleeveInsertType is optional. A single instance might exist.*

Sleeve insert type, examples are:

Sleeve insert type, examples are: bind-in sleeves that are actually bound-in with the pages of the booksleeves that adhere to the inside of the cover or a pagesleeves that are packaged/shrinkwrapped on the outside of the book. This enumeration is currently a free-form string of characters.



---

## **SleeveInsertType**

Sleeve insert type, examples are:

Sleeve insert type, examples are: bind-in sleeves that are actually bound-in with the pages of the booksleeves that adhere to the inside of the cover or a pagesleeves that are packaged/shrinkwrapped on the outside of the book. This enumeration is currently a free-form string of characters.



## Slide

Slide

### SlideMountNumbering [attribute]

*SlideMountNumbering is optional. A single instance might exist.*

Is the slide mount numbered.

Refer to SlideMountNumbering definition for any enumerations.

### SlideMountCaptions [attribute]

*SlideMountCaptions is optional. A single instance might exist.*

Is the slide mount captioned?

Refer to SlideMountCaptions definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### SequenceNumber

*SequenceNumber is optional. A single instance might exist.*

#### Width

*Width is optional. A single instance might exist.*

The width of the object.

#### Length

*Length is optional. A single instance might exist.*

The length of the object.

#### NumberOfColours

*NumberOfColours is optional. A single instance might exist.*

The number of colours

#### ColourSpecs

*ColourSpecs is optional. A single instance might exist.*


Colour specs

#### SlideMountDescription

*SlideMountDescription is optional. A single instance might exist.*

Slide mount description

#### SlideMountMaterial



# papiNet V2R31

---

*SlideMountMaterial is optional. A single instance might exist.*

Slide mount material

## **SlideContainerDescription**

*SlideContainerDescription is optional. A single instance might exist.*

Slide container description

## **PagesPerSet**

*PagesPerSet is optional. A single instance might exist.*

Pages per Set

## **SlidesPerPage**

*SlidesPerPage is optional. A single instance might exist.*

Slides per page

## **HolePunchInformation**

*HolePunchInformation is optional. A single instance might exist.*

Hole Punch Information.

## **SlideContainerMail**

*SlideContainerMail is optional. A single instance might exist.*

Slide container for mail.

## **SlideMailerSizeDescription**

*SlideMailerSizeDescription is optional. A single instance might exist.*

Slide mailer size description

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **SlideContainerDescription**

Slide container description

<b>SlideContainerDescription</b>	
type	s255

---

## **SlideContainerMail**

Slide container for mail.

<b>SlideContainerMail</b>	
type	s255

---

## **SlideMailerSizeDescription**

Slide mailer size description

<b>SlideMailerSizeDescription</b>	
type	s255

## SlideMountCaptions [attribute]

Is the slide mount captioned?

*This item is restricted to the following list.*

Yes

No

attribute
<b>SlideMountCaptions</b>
type   yesNo

## SlideMountDescription

Slide mount description

<b>SlideMountDescription</b>
type   s255

## SlideMountMaterial

Slide mount material

<b>SlideMountMaterial</b>
type   s255

## SlideMountNumbering [attribute]

Is the slide mount numbered.

*This item is restricted to the following list.*

Yes

No

attribute
<b>SlideMountNumbering</b>
type   yesNo

## SlidesPerPage

Slides per page

<b>SlidesPerPage</b>
type   nni2

## SlitReel

The SlitReel element represents the elements associated with reel that has been slit into multiple reels.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DeliveryIndicator

*DeliveryIndicator is optional. A single instance might exist.*

Indicates if delivery should take place or not.

Refer to DeliveryIndicator definition for any enumerations.

#### SlitReelLineNumber

*SlitReelLineNumber is mandatory. A single instance is required.*

The slit reel line number

#### SlitReelWidth

*SlitReelWidth is mandatory. A single instance is required.*

Slit Reel Width

### (choice)

*[choice] is optional because of choice construct.*

#### SlitReelOrderQuantity

*SlitReelOrderQuantity is optional because of choice construct.*

Slit reel order quantity

#### SlitReelsInSet


*SlitReelsInSet is optional because of choice construct.*

The number of slit reels in the set.

#### SlitReelReference


*SlitReelReference is optional. Multiple instances might exist.*

Communicates miscellaneous information about the slit reel.



## SlitReelLineNumber

The slit reel line number



## SlitReelOrderQuantity

Slit reel order quantity

### QuantityType [attribute]

*QuantityType is mandatory. A single instance is required.*

QuantityType communicates information about the type of quantity being communicated and how the receiver might use the information.

Refer to QuantityType definition for any enumerations.

### QuantityTypeContext [attribute]

*QuantityTypeContext is optional. A single instance might exist.*

Provides the location in the value chain where the quantity is being reported.

Refer to QuantityTypeContext definition for any enumerations.

### AdjustmentType [attribute]

*AdjustmentType is optional. A single instance might exist.*

Describes the type of adjustment associated with a quantity.

Refer to AdjustmentType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



---

## SlitReelReference

Communicates miscellaneous information about the slit reel.

### SlitReelReferenceType [attribute]

*SlitReelReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.


Refer to SlitReelReferenceType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.




---

## SlitReelReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.



---

## SlitReelsInSet

The number of slit reels in the set.



## SlitReelWidth

Slit Reel Width

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### Value

Value is mandatory. A single instance is required.

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


RangeMin is optional. A single instance might exist.

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

RangeMax is optional. A single instance might exist.

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## Slurry

Product that has moisture content high enough to prevent formation of a sheet, and which can be delivered in liquid form.

Examples:

Product that has moisture

content high enough to prevent formation of a sheet, and which can be delivered in liquid form.

Examples: Noodle pulp, is pumped into trucks as thick slurry, and then pumped directly into the hydropulper. It has the higher strength properties of never dried pulp.


Product that has moisture content high enough to prevent formation of a sheet, and which can be delivered in liquid form. Examples: Noodle pulp, is pumped into trucks as thick slurry, and then pumped directly into the hydropulper. It has the higher strength properties of never dried pulp. Liquid pulp, never dried pulp, often pumped directly, using a flow meter to measure the moisture and fibre content. Sold by weight of the fibre.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### TargetSolidsContent

TargetSolidsContent is mandatory. A single instance is required.



The target amount of solids for the slurry being produced.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **SmallEndDiameter**

Reports the log crown end diameter as a measurement.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

#### **Value**

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### **RangeMin**


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### **RangeMax**

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## Smoothness

A group item used to communicate surface smoothness target or test value according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*


The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation



*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## **TwoSigmaUpper**

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.


---

## **SoftwoodLumber**

Product structure for solid wood products made of softwood

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### **SoftwoodLumberCharacteristics**

*SoftwoodLumberCharacteristics is mandatory. A single instance is required.*

A group item that organises the softwood lumber –product information.

### **Packaging**

*Packaging is optional. A single instance might exist.*

Type of a package that includes individual products.

---

## SoftwoodLumberCharacteristics

A group item that organises the softwood lumber – product information.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### LumberSpecies

*LumberSpecies is mandatory. One instance is required, multiple instances might exist.*

Specifies the raw material species.

#### LumberGrade

*LumberGrade is mandatory. A single instance is required.*

Defines quality characteristics achieved by selecting pieces based on a grading rule.

#### Length

*Length is optional.*

The length of the object.

#### Width

*Width is optional.*

The width of the object.

#### Thickness

*Thickness is optional.*

Physical dimension of a product. The approach for thickness used in the timber/lumber related constructs.

#### Seasoning

*Seasoning is optional. A single instance might exist.*

Describes drying/ moisture control method.

#### MoistureContent

*MoistureContent is optional. A single instance might exist.*

Defines the moisture content percentage of the product.

#### HeatTreatment

*HeatTreatment is optional. A single instance might exist.*

Defines the heat treatment method.

#### ManufacturingProcess

*ManufacturingProcess is optional. Multiple instances might exist.*


Defines the different machining and processes made for the product.

#### PatternProfile

*PatternProfile is optional. A single instance might exist.*

Defines the pattern used in machining the product.

#### Trim



*Trim is optional. A single instance might exist.*

Trim

## **Joining**

*Joining is optional. A single instance might exist.*

Defines the method used to join pieces of wood.

## **PressureTreatment**

*PressureTreatment is optional. A single instance might exist.*

Method and parameter values of pressure treatment.

## **FireTreatment**

*FireTreatment is optional. A single instance might exist.*

Fire treatment

## **OtherTreatment**

*OtherTreatment is optional. A single instance might exist.*

Other treatment

## **GradeStamp**

*GradeStamp is optional. A single instance might exist.*

Grade stamp information

## **ExLog**

*ExLog is optional. A single instance might exist.*

Describes the cutting pattern of the log.

## **ClassIdentifier**

*ClassIdentifier is optional. Multiple instances might exist.*

Standard used for product identification.

## **Weight**

*Weight is optional. A single instance might exist.*

The weight of the item.

## **LabelCharacteristics**

*LabelCharacteristics is optional. A single instance might exist.*

A group item that organises the labeling information.

## **StencilCharacteristics**

*StencilCharacteristics is optional. A single instance might exist.*

A group element specifying attributes of a stencil to be applied to an item, and optional text.

## **Wrap**

*Wrap is optional. A single instance might exist.*

A group item that organises wrapping detail information.

## **SafetyAndEnvironmentalInformation**

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC).  
SafetyAndEnvironmental needs a value or measurement to communicate the

percentage of the product is certified (for example, 75% is certified by the indicated agency).

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **LengthCutDescription**

*LengthCutDescription is optional. A single instance might exist.*

Length Cut Description

## **ShippingMark**

*ShippingMark is optional. A single instance might exist.*

A shipping mark identifies the producer and quality on the end side of the product. Not to be mixed with company code/logo or other product marking.

## SoftwoodPlywood

Characteristics of wood panelling products.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### PlywoodOSBGrade

*PlywoodOSBGrade is mandatory. A single instance is required.*

Defines the grade of plywood, OSB product

#### Thickness

*Thickness is mandatory.*

Physical dimension of a product.

#### Width

*Width is mandatory.*

The width of the object.

#### Length

*Length is mandatory.*

The length of the object.

#### PlywoodOSBSpecies

*PlywoodOSBSpecies is optional. Multiple instances might exist.*

Defines the raw material species of plywood, OSB product.

Refer to PlywoodOSBSpecies definition for any enumerations.

#### PlyNumber

*PlyNumber is optional. A single instance might exist.*

Product attributes can be detailed for each ply. If product attributes are defined for the plies this element defines the ply that these product attributes apply to.

#### Surface

*Surface is optional. A single instance might exist.*

#### Overlay


*Overlay is optional.*

Overlay

#### GlueExposure

*GlueExposure is optional. A single instance might exist.*

Refer to GlueExposure definition for any enumerations.



## **Edge**

*Edge is optional. A single instance might exist.*

Describes the finishing of the edge of the board.

## **PressureTreatment**

*PressureTreatment is optional. A single instance might exist.*

Method and parameter values of pressure treatment.

## **FireTreatment**

*FireTreatment is optional. A single instance might exist.*

Fire treatment

## **Supplemental**

*Supplemental is optional. Multiple instances might exist.*

Supplemental

## **Brand**

*Brand is optional. A single instance might exist.*

Specifies a brand or trade name of wrapping material to be used when wrapping the product.

## **GradeAgency**

*GradeAgency is optional. A single instance might exist.*

North American structural panel grading agencies. Defines the governing organisation of the grading scheme employed.

Note: There is a GradeAgency attribute, as well.

Refer to GradeAgency definition for any enumerations.

## **GradeStamp**

*GradeStamp is optional. A single instance might exist.*

Grade stamp information

## **ClassIdentifier**

*ClassIdentifier is optional. A single instance might exist.*

Standard used for product identification.

## **LabelCharacteristics**

*LabelCharacteristics is optional. Multiple instances might exist.*

A group item that organises the labeling information.

## **StencilCharacteristics**

*StencilCharacteristics is optional. Multiple instances might exist.*

A group element specifying attributes of a stencil to be applied to an item, and optional text.

## **SafetyAndEnvironmentalInformation**

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

## SpanRating

Span Rating according to NIST standards and indicated on grade stamp.

*This item is restricted to the following list.*

- 16oc
- 20oc
- 24oc
- 32oc
- 48oc
- 20/0
- 24/0
- 24/16
- 32/16
- 40/20
- 48/24
- 54/32
- 60/32
- 60/48

SpanRating	
type	plywoodOSBSpanRatingType

## SpecAssembly

SpecAssembly contains assemblies that are used in the manufacturing of books.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ProductIdentifier

*ProductIdentifier is mandatory. A single instance is required.*

Used to communicate the code of the article, in a variety of formats designated by the type.


#### ProductDescription

*ProductDescription is optional. Multiple instances might exist.*

An element used to communicate a human readable description of the product in the language specified by the Language attribute.

#### BillOfMaterials

*BillOfMaterials is optional. A single instance might exist.*



# papiNet V2R31

---

A specification of the components and other items that are used to produced the item in question.

## **Height**

*Height is optional. A single instance might exist.*

The height of the object.

## **Length**

*Length is optional. A single instance might exist.*

The length of the object.

## **Width**

*Width is optional. A single instance might exist.*

The width of the object.

## **AssemblyInstructions**

*AssemblyInstructions is optional. Multiple instances might exist.*

Instructions for assembly.

## SpecBinding

SpecBinding describes the binding process.

### BindingType [attribute]

*BindingType is optional. A single instance might exist.*

Binding type

Refer to BindingType definition for any enumerations.

### BindingStyleType [attribute]

*BindingStyleType is optional. A single instance might exist.*

Indicates the style of binding used.

Refer to BindingStyleType definition for any enumerations.

### BindingCoverScoring [attribute]

*BindingCoverScoring is optional. A single instance might exist.*

Binding cover scoring

Refer to BindingCoverScoring definition for any enumerations.

### BindingReinforcement [attribute]

*BindingReinforcement is optional. A single instance might exist.*

Binding reinforcement

Refer to BindingReinforcement definition for any enumerations.

### BindingBackStyleType [attribute]

*BindingBackStyleType is optional. A single instance might exist.*

Binding back style type

Refer to BindingBackStyleType definition for any enumerations.

### BindingRibbon [attribute]


*BindingRibbon is optional. A single instance might exist.*

Binding ribbon

Refer to BindingRibbon definition for any enumerations.

### IsBindingHandSeparation [attribute]

*IsBindingHandSeparation is optional. A single*



*instance might exist.*

Indicates if there is hand separation required or not for books with odd page counts.

Refer to IsBindingHandSeparation definition for any enumerations.

## **IsEaselBound [attribute]**

*IsEaselBound is optional. A single instance might exist.*

Specifies if the binding is at the top of the pages or not rather than on the side which changes the pagination of the pages.

Refer to IsEaselBound definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **ProductIdentifier**

*ProductIdentifier is mandatory. A single instance is required.*

Used to communicate the code of the article, in a variety of formats designated by the type.

### **ProductDescription**

*ProductDescription is optional. Multiple instances might exist.*

An element used to communicate a human readable description of the product in the language specified by the Language attribute.

### **BookBlock**

*BookBlock is mandatory. A single instance is required.*

Book block information

### **EndsheetInformation**

*EndsheetInformation is optional.*

End sheet information.

### **BindingExtras**

*BindingExtras is optional. Multiple instances might exist.*

Binding extras

### **HolePunchInformation**

*HolePunchInformation is optional and repeatable. Multiple instances might exist.*

Hole Punch Information.

### **Case**

*Case is optional. A single instance might exist.*

Case information

### **MechanicalMaterial**

*MechanicalMaterial is optional. A single instance might exist.*

Mechanical material information

### **Ribbon**

*Ribbon is optional. Multiple instances might exist.*

Ribbon information.

## Perforation

*Perforation is optional and repeatable. Multiple instances might exist.*

Perforation information.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## SpecComponent

Group element used to identify all the necessary component information for this BookSpecification.

Each occurrence of this construct identifies a single component.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### ProductIdentifier

*ProductIdentifier is mandatory. A single instance is required.*

Used to communicate the code of the article, in a variety of formats designated by the type.

#### ProductDescription

*ProductDescription is optional. Multiple instances might exist.*

An element used to communicate a human readable description of the product in the language specified by the Language attribute.


### (sequence)

*The sequence of items below is mandatory. One instance is required, multiple instances might exist.*

#### Classification

*Classification is mandatory. A single instance is required.*

A group item that details the product classification according to a particular organization's scheme. An item across multiple classifications would still be recognized as the same item. Examples of



# papiNet V2R31

---

some product classifications are: Containerboard, Pulp-Dissolving, or Newsprint.

## **SubClassification**

*SubClassification is optional. Multiple instances might exist.*

SubClassification provides additional classification information.

## **BookClassification**

*BookClassification is optional. Multiple instances might exist.*

Category under which the product or a component within the product is classified.

## **NumberPerProduct**

*NumberPerProduct is optional. A single instance might exist.*

The number of components or items per assembly or constructed product

## **PlacementInOrderOfMatter**

*PlacementInOrderOfMatter is optional. Multiple instances might exist.*

Element used to identify where the component is to be placed amongst other components when assembling a book.

## **FinishedSize**

*FinishedSize is optional. A single instance might exist.*

Finished size

## **SuppliedComponentFinishSpecs**

*SuppliedComponentFinishSpecs is optional. A single instance might exist.*

Supplied Component Finish Specs

## **(choice)**

*[choice] is optional because of choice construct.*

### **PressComponent**

*PressComponent is optional because of choice construct.*

Press Component.

### **NonPressComponent**

*NonPressComponent is optional because of choice construct.*

Non-press component.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **SpecReference**

*SpecReference is optional. Multiple instances might exist.*

Used to identify any external or associated documents, identifiers, etc.

## **SafetyAndEnvironmentalInformation**

*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the

indicated agency).

## SpecGeneral

### Spec General

#### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### SpecInformation

*SpecInformation is mandatory. A single instance is required.*

Construct is used to uniquely identify this BookSpecification.

Note: ProductIdentifier, ProductDescription, and Classification removed in Version V2R30 and replaced with SpecificationNumber to more accurately reflect the business process.



#### TransactionHistoryNumber

*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

#### SenderParty

*SenderParty is mandatory. A single instance is required.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

#### ReceiverParty

*ReceiverParty is mandatory. A single instance is required.*


The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

#### OtherParty

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-



Document.

## **TrimSize**

*TrimSize is optional. A single instance might exist.*

Trim size.

## **TotalPageCount**

*TotalPageCount is optional. A single instance might exist.*

Element used to communicate the book's approximate total number of pages within each unit of the book. Total page count is more or less a reference to the "size" of the book that the customer designates. For instance, they will refer to a book as 800 pages when in fact it is 792 actual text pages with 8 pages of various inserts. This value should not be used to drive any of the other values for the component parts, but may in fact be exactly equal to the number of pages in one of the components designated as "Text".

## **BookClassification**

*BookClassification is optional. Multiple instances might exist.*

Category under which the product or a component within the product is classified.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **SpecGroupingID**

A value that will relate/link specifications together. For example, items that are usually manufactured with common components.

<b>SpecGroupingID</b>
type s60

---

## **SpeciesAgency [attribute]**

Defines the governing organisation of the scheme employed in determining the species of the product.

*This item is restricted to the following list.*

### **ISO**

International Organisation for Standardization.

### **prEN TC(1113-1)**

### **Supplier**

Supplier determined scheme.

attribute
<b>SpeciesAgency</b>
type lumberSpeciesAgencyType

---

## SpeciesCode

Species Code

<b>SpeciesCode</b>	
type	s30

---

## SpeciesOrigin [attribute]

The country of origin of the species employed in manufacture of the product.

*This item is restricted to the following list.*

attribute	
<b>SpeciesOrigin</b>	
type	lumberSpeciesOriginType

**Africa**  
**America**  
**Austria**  
**Bavaria**  
**Brasil**  
**Canada**  
**Estonia**  
**European**  
**Finland**  
**French**  
**Germany**  
**Indian**  
**Latvia**  
**Lithuania**  
**Norway**  
**Russia**  
**Sweden**  
**North**  
**South**  
**Eastern**  
**Western**  
**Coast**  
**Inland**  
**Other**

## SpeciesType [attribute]

Defines the species or mix of species comprising the product.

*This item is restricted to the following list.*

attribute
<b>SpeciesType</b>
type   lumberSpeciesType

**Afrormosia**  
**Afzelia**  
**Agba**  
**AlaskanCedar**  
**Alder**  
**AlpineFir**  
**AmabilisFir**  
**Amapa**  
**Andoung**  
**Anegre**  
**Antiaris**  
**Ash**  
**Aspen**  
**AspenPolar**  
**AustrianSpruce**  
**Avodire**  
**Ayan**  
**Ayous/Ako**  
**BalsamFir**  
**BalsamPolar**  
**Bamboo**  
**Basswood**  
**Beech**  
**Birch**  
**BirdseyeMaple**  
**BlackCherry**  
**BlackCottonwood**  
**BlackGuarea**  
**BlackSpruce**  
**Bubinga**  
**CaliforniaRedFir**  
**CaribbeanPine**  
Yes, it is Caribbean Pine.

CarolinaPine  
Cedar  
Ceiba  
CembraPine  
Cherry  
Chestnut  
CoastSpecies  
Cypress  
Danta  
DouglasFir  
Douka  
EasternCottonwood  
EasternHemlock  
EasternSoftwoods  
EasternSpruce  
EasternWhiteCedar  
EasternWhitePine  
Elliotti  
EngelmanSpruce  
Eucalyptus  
EuropeanLarch  
Exotic  
FigureSycamore  
Fir  
Frake  
Framire  
Gaboon  
GrandFir  
GreyElm  
HardMaple  
Hemlock  
Hornbeam  
IdahoWhitePine  
Ilomba  
Imbira  
IncCedar  
InlRedCedar

Ipe  
Iroko  
JackPine  
Kaya  
Koto  
Larch  
LarricioPine  
Lauan  
Limba  
Locust  
LodgepolePine  
Mahogany  
Macoré  
Mansonia  
Maple  
MaritimePine  
Meranti  
Merbeau  
MexicanPine  
MixedSoftwood  
MixedSYP  
MixedTropicalHardwood  
MntnHemlock  
Niangon  
NobelFir  
NorwaySpruce  
NorthernAspen  
NorthernPine  
NorthernSpecies  
Oak  
Okume  
OliverAsh  
Olon  
Omu  
OregonPine  
Ozigo  
PacificCoastHemlock

**PacificSilverFir**

**Padauk**

**PaoAmarello**

**Pear**

**Pearwood**

**Pine**

**Plane**

**PlywoodComposite**

Indicates that the product is made up of a group of species. It is a composite product (usually plywood).

**PonderosaPine**

**PrtOrfCed**

**Poucouli**

**Purpleheart**

**Radiata**

**RadiataPine**

**RedCedar**

**RedElm**

**RedOak**

**RedPine**

**RedSpruce**

**RedWhitewood**

**Redwood**

**RioRosewood**

**Rosewood**

**SandPine**

**SantosRosewood**

**Sapelle**

**Satinwood**

**ScotsPine**

**SilkyOak**

**SitkaSpruce**

**SouthernPine**

**SouthernPondPine**

**SouthernSprucePine**


**SPF**

**Spruce**

SugarPine  
SwissPear  
SwissStonePine  
Sycamore  
SYP  
Taeda  
Tamarack  
Tauari  
Teak  
Tiama  
Tineo  
TropicalOliver  
Utile  
VirginiaPine  
Walnut  
Wenge  
Wey  
WesternCedars  
WesternHemlock  
WesternRedCedar  
WesternWhitePine  
WesternWhiteSpruce  
WesternWoods  
WhitebarkPine  
WhiteFir  
WhiteOak  
WhiteSpruce  
WhiteWood  
YellowCedar  
YellowCypress  
YellowPoplar  
Zebrano  
Other

## SpecificationNumber


Specification Number



## SpecInformation

Construct is used to uniquely identify this BookSpecification.

Note: ProductIdentifier, ProductDescription, and Classification removed in Version V2R30 and replaced with SpecificationNumber to more accurately reflect the business process.



### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### SpecificationNumber

SpecificationNumber is mandatory. A single instance is required.

Specification Number

#### SpecVersion

SpecVersion is mandatory. A single instance is required.

The specification version

#### SpecIssueDate

SpecIssueDate is mandatory. A single instance is required.

Used to identify the issue date of this BookSpecification.

#### SpecGroupingID

SpecGroupingID is optional. A single instance might exist.

A value that will relate/link specifications together. For example, items that are usually manufactured with common components.

#### SpecReference

SpecReference is optional. Multiple instances might exist.


Used to identify any external or associated documents, identifiers, etc.

## SpecIssueDate

Used to identify the issue date of this BookSpecification.

### (sequence)

The sequence of items below is mandatory. A single instance is required.



# papiNet V2R31

## Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

## Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## SpecPacking

SpecPacking defines the book packaging parameters.

### IsBoxed [attribute]

*IsBoxed is optional. A single instance might exist.*

Refer to IsBoxed definition for any enumerations.

### IsPalletized [attribute]

*IsPalletized is optional. A single instance might exist.*

The buyer's directions for how the item is to be palletized.

Refer to IsPalletized definition for any enumerations.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### ProductIdentifier

*ProductIdentifier is mandatory. A single instance is required.*

Used to communicate the code of the article, in a variety of formats designated by the type.



## ProductDescription

*ProductDescription is optional. Multiple instances might exist.*

An element used to communicate a human readable description of the product in the language specified by the Language attribute.

## BookUnitPacking

*BookUnitPacking is optional. Multiple instances might exist.*

Book unit packing information

## BoxCharacteristics

*BoxCharacteristics is optional. A single instance might exist.*

BoxCharacteristics is a group element that contains information about the box (or carton)

## PalletPackagingCharacteristics

*PalletPackagingCharacteristics is optional. A single instance might exist.*

PalletPackagingCharacteristics details the characteristics of the packaging for a pallet.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## SpecReference

Used to identify any external or associated documents, identifiers, etc.

### SpecReferenceType [attribute]

*SpecReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.


Refer to SpecReferenceType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*


Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.



## SpecReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.




Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

---

## SpecStatusType [attribute]

Identifies the status of the entire BookSpecification e-Document (in other words, at the root level).



*This item is restricted to the following list.*

### **Amended**

The supplied information is changed.

### **Cancelled**

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### **Original**

The supplied information is the first version of that information.

### **Replaced**


The supplied information is replacing earlier supplied information. The receiver should revalidate the information in their system based upon the entire information received.

---

## SpecType [attribute]

DefinitionUsed to identify what type of BookSpecification e-Document this transaction is.

*This item is restricted to the following list.*



### **SpecOrder**

Used when the BookSpecification e-Document is intended for use with the PurchaseOrder transaction.

### **SpecRFQ**

Used when the BookSpecification e-Document is intended for use with the Request for Quote (Estimate) transaction.

## SupplierSpec

Will be removed in a future version. Recommended not to be used.  
(Old definition: Used when the BookSpecification e-Document is intended for use by the Supplier only and is not generated by, or transmitted to the Buyer).

## SpecVersion

The specification version

SpecVersion	
type	s40

## SpeedType [attribute]

Speed Type

*This item is restricted to the following list.*

**RampUp**

**RunSpeed**

**SlowDown**

SpeedType	
type	machineSpeedType
default	RunSpeed

## SpineLabel [attribute]

The sleeve spine label.

SpineLabel	
type	spineLabel

## SpineLabel [attribute]

Is there a spine label?

*This item is restricted to the following list.*

**Yes**

**No**

SpineLabel	
type	yesNo

## SpineSize

The height of the spine.


**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**Value**

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).



## StackingMethod

A text field describing the pattern used when stacking of pallets.

StackingMethod	
type	s20

## StacksPerPallet

The number of stacks on a pallet, where a stack is a vertical arrangement of items (looking down from above).

StacksPerPallet	
type	nni2

## StandardDeviation


A statistic used as a measure of dispersion in a distribution.

### UOM [attribute]

*UOM is mandatory. A single instance is required.*

Defines the unit of measure for the value.

Refer to UOM definition for any enumerations.



## StandardSpacing

Is the spacing standard?

*This item is restricted to the following list.*


**Yes**

**No**

StandardSpacing	
type	yesNo

## StartIdentifierRange

An element that identifies the starting item identifier in the range of items that contributed to the aggregated measurements for the range.



**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**Identifier**

*Identifier is mandatory. A single instance is required.*


An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be

communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.

## Statement

The Statement element is the root element for the Statement e-Document.

The Statement e-Document permits the manufacturer or supplier to report the current status of an invoice, or a list of invoices based upon specified criteria. The e-Document enables the sender to indicate payment status for the invoice.



### StatementType [attribute]

*StatementType is optional. A single instance might exist.*

Communicates how Statement information is filtered.

Refer to StatementType definition for any enumerations.

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.

### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### StatementHeader

*StatementHeader is mandatory. A single instance is required.*

Information that applies to the entire Statement e-Document.

#### StatementDetail

*StatementDetail is mandatory. One instance is required, multiple instances might exist.*

The specifics of information being communicated in the Statement e-Document.

## StatementDetail

The specifics of information being communicated in the Statement e-Document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### InvoiceNumber

*InvoiceNumber is mandatory. A single instance is required.*

The identification number of the papiNet e-Document Invoice. This number uniquely identifies documents for all InvoiceType such as Invoice, DebitNote, CreditNote, Approximate, SelfBillingStatement etc.

#### InvoiceDate

*InvoiceDate is mandatory. A single instance is required.*

A date that is qualifying the invoicing period. This date often drives payment terms. Note that this date is not necessarily the same as the issue date of the invoice.

#### InvoiceReference

*InvoiceReference is optional. Multiple instances might exist.*

A group item detailing relevant references pertaining to the invoice e-Document. InvoiceReferenceType describes the content.

#### BillToParty

*BillToParty is mandatory. A single instance is required.*

The address where the invoice is to be sent.

#### SupplierParty

*SupplierParty is mandatory. A single instance is required.*


The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

#### BuyerParty

*BuyerParty is mandatory. A single instance is required.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

#### RemitToParty



# papiNet V2R31

---

*RemitToParty is optional. A single instance might exist.*

A group item containing details of the party to whom payment will be made. The RemitToParty contains all information related to remittance.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **LocationParty**

*LocationParty is optional. Multiple instances might exist.*

The organization or business entity where the business event took place or will take place.

## **TotalAmount**

*TotalAmount is mandatory. A single instance is required.*

A field containing the total amount including tax.

PurchaseOrder: The total amount, using a valid unit of measure of all the items in the e-Document. Multiple total amounts are allowed so different units of measure or grade sub-totals can be communicated.

CreditDebitNote and Invoice: TotalAmount is equal to TotalNetAmount plus TotalTaxAmount. In certain countries this is the amount that is due for payment based upon the terms of payment.

## **InformationalAmount**

*InformationalAmount is optional. Multiple instances might exist.*

A monetary amount used for information purposes only (not for calculation). For example, the invoice price adjustment subtotal is expressed in sterling pounds, and the buyer wants this information expressed in U.S. dollars.

CreditDebitNote and Invoice - The TaxAmount is displayed in the currency that is applicable throughout the e-Document. When a TaxAmount needs to be displayed in a different national currency, this field is used.

## **(sequence)**

*The sequence of items below is optional. Multiple instances might exist.*

### **TermsOfPayment**

*TermsOfPayment is mandatory. A single instance is required.*

A group item that contains agreed-to terms defining when, how, and under what conditions the payment is to be made.

When TermsOfPayment is optional; if omitted, TermsOfPayment is controlled through previous negotiation.

### **TotalNetOfTermsDiscount**

*TotalNetOfTermsDiscount is optional. A single instance might exist.*

The components of the amount to be paid if prompt payment discount terms are met, including the amount that is subject to the payment terms discount, the discount amount, and the amount due after prompt payment discount.

## **TotalPaymentAmount**

*TotalPaymentAmount is mandatory. A single instance is required.*

The amounts which were paid and booked against the original invoice.

# papiNet V2R31

## TotalOpenAmount

*TotalOpenAmount is mandatory. A single instance is required.*

InvoiceAmount less the sum of all payment amounts, translated into one common currency.

## StatementInformation

*StatementInformation is mandatory. A single instance is required.*

Invoice information for the statement.

## OtherDate

*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

## GeneralLedgerAccount

*GeneralLedgerAccount is optional. A single instance might exist.*

The general ledger account to be referenced for the item.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## StatementHeader

Information that applies to the entire Statement e-Document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### StatementNumber

*StatementNumber is mandatory. A single instance is required.*

A number used to identify the Statement.


### StatementResponseDate

*StatementResponseDate is mandatory. A single instance is required.*

### RequestNumber

*RequestNumber is optional. A single instance might exist.*

A unique tracking number specifically identifying the InfoRequest e-Document to the originator. The



tracking number is returned with the "information", the answer, to help match the answer to the request.

## RequestingParty

*RequestingParty is optional. A single instance might exist.*

The party requesting the information.

## RespondToParty

*RespondToParty is optional. Multiple instances might exist.*

The party the document should be responded to.

## SenderParty

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## ReceiverParty

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## DateTimeRange

*DateTimeRange is optional. A single instance might exist.*

The delivery date and/or time range.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.


---

## StatementInformation

Invoice information for the Statement.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### InvoicePrimaryStatus

*InvoicePrimaryStatus is mandatory. A single instance is required.*

The primary status of the invoice.

### InvoiceSecondaryStatus

*InvoiceSecondaryStatus is optional. A single instance might exist.*

The secondary status of the invoice.

## StatementNumber

A number used to identify the Statement.

<b>StatementNumber</b>
type s30

## StatementRequestDetail

The request criteria associated with statement information.

### StatementRequestType [attribute]

*StatementRequestType is mandatory. A single instance is required.*

Communicates how statement information is filtered.

Refer to StatementRequestType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### SupplierParty

*SupplierParty is optional. Multiple instances might exist.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

### BuyerParty

*BuyerParty is optional. Multiple instances might exist.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

### ShipToParty

*ShipToParty is optional. Multiple instances might exist.*


The name and/or address to which the goods should be delivered with the party type indicated by the PartyType attribute.

### ForwarderParty

*ForwarderParty is optional. Multiple instances might exist.*

The trading partner involved in the forwarding of the shipment.

### StatementInformation



# papiNet V2R31

*StatementInformation is optional. Multiple instances might exist.*

Invoice information for the Statement.

## **DateTimeRange**

*DateTimeRange is optional. A single instance might exist.*

The delivery date and/or time range.

## **ByInvoice**

*ByInvoice is optional. A single instance might exist.*


Selection criteria for invoice information.

---

## **StatementRequestType [attribute]**

Communicates how statement information is filtered.

*This item is restricted to the following list.*



### **AllCreditsDebitsInvoices**

### **ByCreditDebit**

ByCreditDebit will be deprecated in a future version. Use AllCreditsDebitsInvoices instead.

### **ByInvoiceNumber**


### **ByDebit**

---

## **StatementResponseDate**

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### **Date**

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### **Time**

*Time is mandatory. A single instance is required.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however,

# papiNet V2R31

within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## StatementType [attribute]

Communicates how statement information is filtered.

*This item is restricted to the following list.*


**AllCreditsDebitsInvoices**

**ByCreditDebit**

ByCreditDebit will be deprecated in a future version. Use AllCreditsDebitsInvoices instead.


**ByInvoiceNumber**

**ByDebit**



## StateOrProvince

The political designation or boundary of a specific area of land.



## StateOrProvince [attribute]

The political designation or boundary of a specific area of land.



## StatisticalGoodsInformation

A group item containing statistical information about handled or traded goods.

**(sequence)**

*The sequence of*

*items below is mandatory. A single instance is required.*

**CommodityGoodsCode**


*CommodityGoodsCode is mandatory. A single instance is required.*

A code defining the type of goods handled or traded. The Harmonized Commodity Description and Coding System (HS) of the Customs Cooperation Council (CCC) is used worldwide as a reference for classifications of external trade statistics and for customs tariffs.

**PriceDetails**

*PriceDetails is optional. A single instance might exist.*


An element that groups together price information.



## Status [attribute]

Defines whether or not the electronic transaction successfully processed in the receiver ERP system.

*This item is restricted to the following list.*



### Success

Indicates that the electronic transaction successfully processed in the receiver ERP system.


### Failure

Indicates that the electronic transaction failed to process in the receiver ERP system.

---

## StatusAsOfDate

The specific Date and Time for which status is requested. This implies that all open transactions have closed for the date before the status is reported.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## StencilCharacteristics

A group element specifying attributes of a stencil to be applied to an item, and optional text.

### StencilType [attribute]

*StencilType is optional. A single instance might exist.*

The type of stencil

Refer to StencilType definition for any enumerations.

### StencilInkType [attribute]

*StencilInkType is optional. A single instance might exist.*

Specifies the characteristics of the ink to be used for the stencil

Refer to StencilInkType definition for any enumerations.

### StencilLocation [attribute]

*StencilLocation is optional. A single instance might exist.*

Specifies the location of the stencil on the product

Refer to StencilLocation definition for any enumerations.

### StencilFormat [attribute]

*StencilFormat is optional. A single instance might exist.*

Specifies how the information is to be presented in the stencil

Refer to StencilFormat definition for any enumerations.

### StencilContent [attribute]

*StencilContent is optional. A single instance might exist.*

Specifies the information contained in the stencil.

Refer to StencilContent definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.


Refer to AssignedBy definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### StencilText

StencilText is optional. Multiple instances might exist.



Plain text that is to be stenciled on the product. Used in conjunction with StencilContent = "PlainText".

---

## StencilContent [attribute]

Specifies the information contained in the stencil.

*This item is restricted to the following list.*

attribute
<b>StencilContent</b>
type stencilContent

### **Author**

Name of the author of the product or book

### **BasisWeight**

The weight of the paper expressed as a mass for a given surface area.

### **BoxWeight**

Weight of the filled box.

### **BrandName**

A specific product brand name for which the owner or source is specified in the "@AssignedBy" attribute.

### **Copyright**

The year of publication copyright.

### **Edition**

Identifies the version of the product for which copies were printed and published at one time; For example in book manufacturing values might be 1st, 2nd, etc

### **ExportShipMark**

An export shipment mark for identification.

### **GradeCode**

A specific product code for which the owner or source is specified in the "@AssignedBy" attribute.

### **GradeName**

A specific product name for which the owner or source is specified in the "@AssignedBy" attribute (for example, ImprovedNewsprint-45-1479).

### **Identifier**

Identifier of the individual item.

### **ISBN10**

10 digit ISBN code without dashes.

### **ISBN10Dash**

10 digit ISBN code with dashes.

### **ISBN13**

13 digit ISBN code.

### **ISBN13Dash**

A 13 character ISBN with dashes.

**LotIdentifier**

A unique code used to identify a grouping of product with one set of quality statistics common to all members of that group. Synonym: Lot Number.

**PartNumber**

An equivalent to the Stock Keeping Unit (SKU) for which the owner or source is specified in the "@AssignedBy" attribute. In other words, this code fully defines the product.

**PlainText**

To be removed in a future version. Use instead "ReferenceNumber".

**PrintingNumber**

A reference to the sequential print run number.

**ProductIdentifier**

To be removed in a future version. Use instead specific product identifier types such as BrandName, GradeCode, GradeName and PartNumber.

**ProfitCenter**

Profit Center identifier.

**PubName**

The publication name.

**PurchaseOrderNumber**

The unique order identifier as designated by the customer.

**PurchaseOrderReference**

To be removed in a future version. Use instead "ReferenceNumber".

**ReferenceNumber**

An informational reference (either textual or numeric) for which the owner or source is specified in the "@AssignedBy" attribute

**RetailPrice**

Cover price of the finished product.

**TambourID**

The unique identifier of the jumbo reel (also called mother reel or Tambour).

**Title**

Proper title of a book product.

**TitleAlias**

Alternate title description for book products, usually for security purposes.

**UnitsPerCarton**

Number of units per box.

**UniversalProductIdentifier**

Unique identifier for the book, component of a book product, and many other products.

**VendorBrandName**

To be removed in a future version. Use instead "BrandName" and specify owner or source is in the "@AssignedBy" attribute with enumeration "Seller".

## **VendorGradeCode**

To be removed in a future version. Use instead "GradeCode" and specify owner or source is in the "@AssignedBy" attribute with enumeration "Seller".

## **VendorGradeName**

To be removed in a future version. Use instead "GradeName" and specify owner or source is in the "@AssignedBy" attribute with enumeration "Seller".

---

## **StencilFormat [attribute]**

Specifies how the information is to be presented in the stencil

*This item is restricted to the following list.*

### **Barcode**

The information requested is to be stenciled as a barcode

### **Text**

The information requested is to be stenciled in plain text.

attribute	
<b>StencilFormat</b>	
type	labelFormat

## **StencilInkType [attribute]**

Specifies the characteristics of the ink to be used for the stencil

*This item is restricted to the following list.*

### **EdibleNotWaterSoluble**

The ink used is suitable for human consumption but will not dissolve in water.

### **EdibleWaterSoluble**

The ink used is suitable for human consumption and is soluble in water.

### **InedibleNotWaterSoluble**

The ink used is not suitable for human consumption and will not dissolve in water.

### **InedibleWaterSoluble**

The ink used is not suitable for human consumption and is soluble in water.

### **Unknown**

The characteristics of the ink used for the stencil are unknown.

attribute	
<b>StencilInkType</b>	
type	inkType
default	Unknown

## StencilLocation [attribute]

Specifies the location of the stencil on the product

*This item is restricted to the following list.*

attribute	
StencilLocation	
type	packageLocation

### End

The stencil is to be placed on the end of the product.  
E.g. on the end of a pallet, box, bale or reel.

### Top

The stencil is to be placed on the top of the product. E.g. on the top of a pallet, box, bale or reel.

### Side

The stencil is to be placed on the side of the product. E.g. on the side of a pallet, box or bale.

### UnwrappedReelBilge

The stencil is to be placed on the unwrapped (bare) reel bilge (side).

### UnwrappedReelEnd

The stencil is to be placed on the unwrapped (bare) end of a reel.

### WrappedReelBilge

The stencil is to be placed on the outside of the wrapper on a reel.

---

## StencilText

Plain text that is to be stenciled on the product. Used in conjunction with StencilContent = "PlainText".

StencilText	
type	s255

---

## StencilType [attribute]

The type of stencil

*This item is restricted to the following list.*

attribute	
StencilType	
type	stencilType

### CutOut

The stencil is a cut out.

### InkJet

The stencil is ink jetted.

### Rubber

The stencil is made of rubber.

## Stiffness

A group item used to communicate stiffness target or test value.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.


#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*



A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.


---

## StopOffInformation

Where is the shipment and how far to the next stop.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### DistanceToNextStop

*DistanceToNextStop is optional. A single instance might exist.*

The distance to the next transportation node.

### LocationParty

*LocationParty is optional. Multiple instances might exist.*


The organization or business entity where the business event took place or will take place.

---

## StrengthGroup

As defined in the NIST standard, an additional classification of panel strength.

*This item is restricted to the following list.*



**Class-I**

**Class-II**

**Group1**

**Group2**

**Group3**

**Group4**

**Struc-I**

**Decorative**

## Stretch

A group item used to communicate stretch target or test value.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*


The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation



*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.


---

## SubClassification

SubClassification provides additional classification information.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### SubClassificationCode

*SubClassificationCode is mandatory. A single instance is required.*

Sub Classification Code

### ClassificationDescription

*ClassificationDescription is optional. Multiple instances might exist.*

A free form description of the classification.


---

## SubClassificationCode

Sub Classification Code

### Agency [attribute]

*Agency is mandatory. A single instance is required.*



Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.


Refer to Agency definition for any enumerations.

## SupersType [attribute]

Supers Type

*This item is restricted to the following list.*


**Ribbed**  
**Regular**



## Supplemental

Supplemental

### SupplementalSpecification [attribute]



*SupplementalSpecification is optional. A single instance might exist.*

Supplemental specification

Refer to SupplementalSpecification definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## SupplementalSpecification [attribute]

Supplemental specification

*This item is restricted to the following list.*

**EdgeSealed**  
**Overlay-1Side**  
**Overlay-2Side**  
**B-X-band**  
**Plugged-X-Band**  
**PluggedInnerPlies**  
Solid inner plies.



---

## SuppliedComponentFinishSpecs

### Supplied Component Finish Specs

#### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### **FinishSpecs**

*FinishSpecs is optional. A single instance might exist.*

Finish specifications

#### **FinishPrep**

*FinishPrep is optional. Multiple instances might exist.*

Finish prep

#### **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

#### **Length**


*Length is optional. A single instance might exist.*

The length of the object.

#### **Width**

*Width is optional. A single instance might exist.*

The width of the object.



## SuppliedComponentInformation

Information about components supplied by the publisher to the vendor i.e. paper supplied to the print vendor or jackets supplied to the bind vendor.

### SuppliedComponentType [attribute]

*SuppliedComponentType is*



*optional. A single instance might exist.*

Supplied Component Type

Refer to SuppliedComponentType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### SupplierParty

*SupplierParty is mandatory. A single instance is required.*

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

### (sequence)

*The sequence of items below is mandatory. One instance is required, multiple instances might exist.*

#### ProductIdentifier

*ProductIdentifier is mandatory. A single instance is required.*

Used to communicate the code of the article, in a variety of formats designated by the type.


#### ProductDescription

*ProductDescription is optional. Multiple instances might exist.*

An element used to communicate a human readable description of the product in the language specified by the Language attribute.

#### Classification

*Classification is optional. Multiple instances might exist.*



A group item that details the product classification according to a particular organization's scheme. An item across multiple classifications would still be recognized as the same item. Examples of some product classifications are: Containerboard, Pulp-Dissolving, or Newsprint.

## **BookClassification**

*BookClassification is optional. Multiple instances might exist.*

Category under which the product or a component within the product is classified.

## **Paper**

*Paper is optional. A single instance might exist.*

A group item defining the characteristics of the paper product.

## **SuppliedComponentReference**

*SuppliedComponentReference is optional. Multiple instances might exist.*

Used to send component PurchaseOrder number for supplied components if they need to be returned on a invoice

## **Quantity**

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **ComponentShipDate**

*ComponentShipDate is optional. A single instance might exist.*

Date supplied component is expected to ship

## **ComponentDueDate**

*ComponentDueDate is optional. A single instance might exist.*

Date supplied component is expected to arrive

## **ComponentNeededDate**

*ComponentNeededDate is optional. A single instance might exist.*

Date the supplied component is needed by the vendor in order to make the due date of the ordered product.

## **OrderStatusInformation**

*OrderStatusInformation is optional. A single instance might exist.*

A group element that stores two levels of order status codes.

## **AdditionalText**



*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## SuppliedComponentReference

Used to send component PurchaseOrder number for supplied components if they need to be returned on a invoice



### SuppliedComponentReferenceType [attribute]

*SuppliedComponentReferenceType is optional. A single instance might exist.*

SuppliedComponentReferenceType provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Customer", "Seller", and/or "Supplier". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to SuppliedComponentReferenceType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*


Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## SuppliedComponentReferenceType [attribute]

SuppliedComponentReferenceType provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Customer", "Seller", and/or "Supplier". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.



Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

---


## SuppliedComponentType [attribute]

Supplied Component Type

*This item is restricted to the following list.*

**Component**



**RawMaterial**



## SupplierCustomsReference

Supplier Customs Reference

### SupplierCustomsReferenceType [attribute]



*SupplierCustomsReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to SupplierCustomsReferenceType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.


---

## SupplierCustomsReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an

existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.


Refer to the [referenceType](#) entry for the list of enumerations and their definitions.



---

## SupplierMarks

Supplier provided markings.



## SupplierOrderLineItemNumber

The number of the line item on the supplier order.

<b>SupplierOrderLineItemNumber</b>	
type	lineNumberType

## SupplierOrderNumber

The number of the supplier order.

<b>SupplierOrderNumber</b>	
type	s30

## SupplierParty

The organisation or business entity responsible for providing the product. SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

### LogisticsRole [attribute]

*LogisticsRole is optional. A single instance might exist.*

Communicates the nature of the logistics role, if any, the party plays in the transaction.

Refer to LogisticsRole definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### PartyIdentifier

*PartyIdentifier is optional. Multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

### NameAddress

*NameAddress is mandatory. A single instance is required.*

A group item containing name and address of an organisation or business entity.

### URL


*URL is optional. A single instance might exist.*

Universal Resource Locator. While typically a web address you could use this field to hold an email address.

### CommonContact


*CommonContact is optional. Multiple instances might exist.*

Identifies a specific individual associated with the party.



## SupplyPoint

Grouping element that contains items describing a supply point. A SupplyPoint belongs to a LocationParty, e.g. in a DeliveryOrigin or DeliveryDestination, and describes where goods are stored and can be loaded or unloaded. A SupplyPoint can for example be a loading or unloading gate at a warehouse or a road side landing at a logging area in the forest.



### LocationType [attribute]

Defines type of location when context needs to be specified, e.g. when goods are moved from one location to a new location.

Refer to LocationType for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### SupplyPointCode

*SupplyPointCode is mandatory. A single instance is required.*

Identification of the supply point. A code used to identify a SupplyPoint belonging to a LocationParty.

### SupplyPointDescription

*SupplyPointDescription is optional. Multiple instances might exist.*

A free form description of a SupplyPoint.


### MapCoordinates

*MapCoordinates is optional. Multiple instances might exist.*

A group item defining and containing position co-ordinates of a location.

## SupplyPointCode

Identification of the supply point. A code used to identify a SupplyPoint belonging to a LocationParty.



### Agency [attribute]

*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent


element.

Refer to Agency definition for any enumerations.

---

## SupplyPointDescription

A free form description of a SupplyPoint.




---

## Surface

### SurfaceType [attribute]

*SurfaceType is optional. A single instance might exist.*



Refer to SurfaceType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## SurfaceStrength

### Surface Strength

#### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

#### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

#### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

#### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

#### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

##### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

##### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

##### DetailRangeMax


*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

##### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.



## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## SurfaceType [attribute]

*This item is restricted to the following list.*

**Oiled**

**PluggedAndTouchSanded**

**Rough**

**RoughSawn**

**S1S**

Side one sanded.

**S2S**

Side two sanded.

**Sanded**

**ScratchSanded**

**Smooth**

**TouchSanded**

**Unsanded**

attribute
<b>SurfaceType</b>
type   plywoodOSBSurfaceType

---

## Tabs [attribute]

The type of tabs

*This item is restricted to the following list.*

**In**

**Out**

**None**

attribute
<b>Tabs</b>
type   tabs

---

## TambourID

The unique identifier of the jumbo reel (also called mother reel or Tambour).

TambourID
type   s20

---

## TapeDescription

Tape description

TapeDescription
type   string

---

## TargetMoisture

The moisture target for the product being specified.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



---

## TargetProductWeight

The desired weight of the finished product.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*


#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin

*RangeMin is optional. A single instance might exist.*



# papiNet V2R31

---

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

## RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## TargetSolidsContent

The target amount of solids for the slurry being produced.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## TaxAdjustment

This content element contains the necessary information to describe, calculate, and handle a tax adjustment.

### TaxCategoryType [attribute]

*TaxCategoryType is optional. A single instance might exist.*

Used to indicate if the tax is applicable

Refer to TaxCategoryType definition for any enumerations.

### TaxType [attribute]

*TaxType is mandatory. A single instance is required.*

Refer to TaxType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### TaxPercent

*TaxPercent is optional. A single instance might exist.*

The fixed tax percentage to be applied according to specific tax regulations.

The fixed tax percentage to be applied according to specific tax regulations. If the TaxCategoryType is "Zero" and there is a non-zero value in this element, the e-Document can be rejected by the receiver.

#### TaxAmount

*TaxAmount is optional. A single instance might exist.*

The monetary amount expressed in the currency of the tax applied. For the MonetaryAdjustmentLine the TaxAmount is equal to the TaxPercent multiplied by the MonetaryAdjustmentStartAmount.

#### TaxLocation

*TaxLocation is mandatory. A single instance is required.*


The location used to determine the tax. Can be a country, state, province, or city. Depends on the tax type and on buyer or ship-to location.

#### InformationalAmount

*InformationalAmount is optional. Multiple instances might exist.*

A monetary amount used for information purposes only (not for calculation). For example, the invoice price adjustment subtotal is expressed in sterling pounds, and the buyer wants this information expressed in U.S. dollars.


CreditDebitNote and Invoice - The TaxAmount is displayed in the currency that is applicable throughout the e-Document. When a TaxAmount needs to be displayed in a different national currency, this field is used.



---

## TaxAmount

The monetary amount expressed in the currency of the tax applied. For the MonetaryAdjustmentLine the TaxAmount is equal to the TaxPercent multiplied by the MonetaryAdjustmentStartAmount.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*


The amount in the referenced currency as defined by the CurrencyType attribute.

---

## TaxCategoryType [attribute]

Used to indicate if the tax is applicable

*This item is restricted to the following list.*



### Exempt

Used when the party or product in question is tax exempt. For example, an item would not be taxed on the invoice because the buyer is tax exempt. Note: In this case, the TaxIdentifier of that party must be given in the PartyIdentifierType.

### Standard

The tax is applicable in a standard manner.

### Zero

The tax related to a specific product is zero. This tax exemption is country specific. For example, newspapers are tax free in Belgium.


### Other

Used for any other tax category that is not covered by this list.

---

## TaxLocation

The location used to determine the tax. Can be a country, state, province, or city. Depends on the tax type and on buyer or ship-to location.




---

## TaxPercent

The fixed tax percentage to be applied according to specific tax regulations.

The fixed tax percentage to be applied according to specific tax regulations. If the TaxCategoryType is "Zero" and there is a non-zero value in this element, the e-Document can be rejected by the



receiver.

---


## TaxStatement

A group element for declaration of exception from normal charges of tax and the reason for tax exemption.

### (sequence)

*The sequence of items*

*below is mandatory. A single instance is required.*



### TaxStatementCode

*TaxStatementCode is optional. A single instance might exist.*

A code defining exception from normal charges of tax and the reason for tax exemption.

### TaxStatementDescription

*TaxStatementDescription is optional. A single instance might exist.*

Free-form text used to define the reason for tax exemption.

---

## TaxStatementCode

A code defining exception from normal charges of tax and the reason for tax exemption.

### Agency [attribute]


*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.


Refer to Agency definition for any enumerations.



---


## TaxStatementDescription

Free-form text used to define the reason for tax exemption.



## TaxType [attribute]

*This item is restricted to the following list.*



### **Federal**

The federal government tax.

### **GST**

The goods and services tax.

### **Harmonised**

A group of taxes have been put together to form one tax rate. For example, Harmonised = provincial/state + federal.

### **Local**

A local tax, such as a country-specific tax.

### **StateOrProvincial**

The local government tax.

### **VAT**

The value-added tax.

## TEA

Tensile Energy Absorption.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax


*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.



## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## Tear

A group item used to communicate tearing resistance target or test value according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]


*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



## **DetailValue**

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

## **DetailRangeMin**

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

## **DetailRangeMax**

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

## **StandardDeviation**

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## **TwoSigmaUpper**

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

## TearIndex

TearIndex

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax


*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.



## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## TearStripType [attribute]

Tear Strip Type

*This item is restricted to the following list.*

### Clear

The tear strip is clear.

### Gold

The tear strip is gold coloured.

### Red

The tear strip is red coloured.

### Other

Another colour is used.

attribute
<b>TearStripType</b>
type   tearStripType

---

## Telephone

The business phone number of the individual associated with the ContactName.

<b>Telephone</b>
type   phoneNumber

## Tensile

A group item used to communicate zero-span tensile strength target or test value according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*


The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation



# papiNet V2R31

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## TensileIndex

Tensile Index

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.


### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)



# papiNet V2R31

---

*The sequence of items below is mandatory. A single instance is required.*

## **DetailValue**

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

## **DetailRangeMin**

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

## **DetailRangeMax**

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

## **StandardDeviation**

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

## **SampleSize**

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## **TwoSigmaLower**

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## **TwoSigmaUpper**

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

---

## **Tension**

Tension of the web on the printing press.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

#### **Value**

*Value is mandatory. A single instance is required.*


A numeric value expressed in the unit of measure (UOM).

#### **RangeMin**

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### **RangeMax**



*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)


---

## TermsAndDisclaimers

An element that contains legal information with an indication of what the Language is.

### Language [attribute]

*Language is optional. A single instance might exist.*



XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.


---

## TermsBasisDate

The Date and Time on which the terms-of-payment calculations are based.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## TermsBasisDateType [attribute]

Indicates what date is being used as the terms basis.

attribute
<b>TermsBasisDateType</b>
type dateTypeTermsBasis

*This item is restricted to the following list.*

### **BillOfLadingDate**

The date of the Bill of Lading.

### **DefferedOrl nstallmentDate**

The date of the installment.

### **DeliveryDate**

The date the delivery was made or received.

### **DespatchDate**

The date the delivery was initiated.

### **EndOfDeliveryMonth**

The end of the month during which delivery took place.

### **EndOfDespatchMonth**

The end of the month during which despatch took place.

### **EndOfInvoiceMonth**

The end of the month during which invoicing took place.

### **EndOfMonth**

The end of the month.

### **EstimatedTimeOfArrival**

Terms are based on the estimated time of arrival that exists when the terms are defined.

### **EstimatedTimeOfDeparture**

Terms are based on the estimated time of departure.

### **ExtendedDate**

### **FixedDate**

The terms specify a fixed date.

### **FollowingMonthDate**

### **InstantDate**

### **InvoiceDate**

A date that is qualifying the invoicing period. This date often drives payment terms. Note that this date is not necessarily the same as the issue date of the invoice.

### **InvoiceReceiptDate**

The date the invoice was received.

### **InvoiceTransmissionDate**

The date the invoice was transmitted.

## LetterOfCreditExpirationDate

The date the letter of credit expires.

## NnDaysAfterEndOfMonthDate

The date a fixed number of days after the end of the month.

## OrderConfirmationDate

The date the PurchaseOrder was confirmed with a status of "Accepted".

## ProxDate

Proximo Date

## PurchaseOrderDate

The date of the PurchaseOrder.

## ReceivedDate

The date product was received.

## ShipDate

The date product was shipped.

---

## TermsDescription

A textual description of the terms of payment.

TermsDescription	
type	s255

---

## TermsDiscountDaysDue

The number of days during which the customer is allowed to deduct cash discounts from the date of TermsBasisDate.

TermsDiscountDaysDue	
type	nni3


---

## TermsDiscountDueDate

The latest Date and Time on which the terms discount is still applicable.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss,

# papiNet V2R31

hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.


hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## TermsDiscountPercent

The percentage taken away from the invoice line items; a result of the terms of payment.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*


The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## TermsInformation

An element that contains the term related information.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### TermsOfPayment

*TermsOfPayment is mandatory. A single instance is required.*

A group item that contains agreed-to terms defining when, how, and under what

# papiNet V2R31

conditions the payment is to be made.

When TermsOfPayment is optional; if omitted, TermsOfPayment is controlled through previous negotiation.

## TotalNetOfTermsDiscount

*TotalNetOfTermsDiscount is optional. A single instance might exist.*

The components of the amount to be paid if prompt payment discount terms are met, including the amount that is subject to the payment terms discount, the discount amount, and the amount due after prompt payment discount.

---

## TermsInterestPenaltyPercent

The penalty associated with not meeting the terms discount parameters.

<b>TermsInterestPenaltyPercent</b>	
type	dec18-6

---

## TermsNetDaysDue

The number of days until the full invoice amount is due on the seller's account without a discount applied.

<b>TermsNetDaysDue</b>	
type	nni3


---

## TermsNetDueDate

The latest Date and Time on which the full invoice amount is due on the seller's account without a discount applied.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.


hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be

in discord with other users of XML.

## TermsOfChartering

The terms of the vessel chartering. There are multiple types of TermsOfChartering that need to be specified. E.g.: Loading Terms and Unloading Terms



### TermsOfCharteringType [attribute]

*TermsOfCharteringType is optional. A single instance might exist.*  
 Terms of chartering type.  
 Refer to TermsOfCharteringType definition for any enumerations.

## TermsOfCharteringType [attribute]

Terms of chartering type.


*This item is restricted to the following list.*

### Loading

The charter terms apply to loading.


### Unloading

The charter terms apply to unloading.



## TermsOfDelivery

A group item defining the terms under which the delivery of goods will take place. These terms determine when and under what conditions the transfer of ownership will occur. Generally speaking, the Incoterms are primarily used in Europe, whereas the



ShipmentMethodOfPayment is primarily used in North America.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### (choice)

*[choice] is optional because of choice construct.*

## **IncotermsLocation**

*IncotermsLocation is optional because of choice construct.*

Place linked to terms of delivery showing the place where goods are to be delivered.

## **ShipmentMethodOfPayment**

*ShipmentMethodOfPayment is optional because of choice construct.*

An element communicating responsibility of freight payment and when transfer of ownership will occur.

## **FreightPayableAt**

*FreightPayableAt is optional. A single instance might exist.*

The location at which freight charges are calculated.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **ServiceLevel**

*ServiceLevel is optional. Multiple instances might exist.*

A grouping element containing information about a service level. The service level can be specified in a Service Level Agreement (SLA) detailing requirements such as delivery, performance, pricing, quality, etc.

## TermsOfPayment

A group item that contains agreed-to terms defining when, how, and under what conditions the payment is to be made.

When TermsOfPayment is optional; if omitted, TermsOfPayment is controlled through previous negotiation.



### TermsBasisDateType [attribute]

*TermsBasisDateType is optional. A single instance might exist.*

Indicates what date is being used as the terms basis.

Refer to TermsBasisDateType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### TermsOfPaymentCode

*TermsOfPaymentCode is optional. A single instance might exist.*

A code used as a shorthand representation for the TermsOfPayment. The Agency attribute is used to indicate the source of the code.

#### TermsDescription

*TermsDescription is optional. A single instance might exist.*

A textual description of the terms of payment.

#### TermsBasisDate

*TermsBasisDate is optional. A single instance might exist.*

The Date and Time on which the terms-of-payment calculations are based.

#### TermsDiscountPercent

*TermsDiscountPercent is optional. A single instance might exist.*

The percentage taken away from the invoice line items; a result of the terms of payment.

#### TermsDiscountDueDate


*TermsDiscountDueDate is optional. A single instance might exist.*

The latest Date and Time on which the terms discount is still applicable.

#### TermsDiscountDaysDue

*TermsDiscountDaysDue is optional. A single instance might exist.*

The number of days during which the customer is allowed to deduct cash discounts



from the date of TermsBasisDate.

## TermsNetDueDate

*TermsNetDueDate is optional. A single instance might exist.*

The latest Date and Time on which the full invoice amount is due on the seller's account without a discount applied.

## TermsNetDaysDue

*TermsNetDaysDue is optional. A single instance might exist.*

The number of days until the full invoice amount is due on the seller's account without a discount applied.

## TermsInterestPenaltyPercent

*TermsInterestPenaltyPercent is optional. A single instance might exist.*

The penalty associated with not meeting the terms discount parameters.

## ExchangeRate

*ExchangeRate is optional. A single instance might exist.*

The exchange rate as of the date included in the element.

## MethodOfPayment


*MethodOfPayment is optional. A single instance might exist.*

The manner in which payment is to be transmitted to the seller.

---

## TermsOfPaymentCode

A code used as a shorthand representation for the TermsOfPayment. The Agency attribute is used to indicate the source of the code.



### Agency [attribute]

*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

---

## TestAgency [attribute]

The agency that has set the parameters for the testing

*This item is restricted to the following list.*

### ASTM

American Society for Testing and Materials.



**BS**

British Standards.

**CIE**

Vienna-based Commission Internationale de l'Eclairage.

**DuPont**

DuPont.

**EN**

European standards organisation.

**GE**

General Electric

**ImageXpert**

ImageXpert.

**ISO**

International Organisation for Standardization.

**NS-EN**

Norwegian Standards, European Standards.

**PAPTAC**

Pulp and Paper Technical Association of Canada

**SCAN-test****SFS-EN****SS-EN****TAPPI**

Technical Association for the Pulp and Paper Industry

---

## TestMethod [attribute]


The method used to determine the results of the test under consideration.



---


## TextValue

A value in text format.



## Thickness

Physical dimension of a product.  
The approach for thickness used in the timber/lumber related constructs.



### ActualNominal [attribute]

*ActualNominal is optional. A single instance might exist.*

Indicates the measurement approach used to communicate the dimensions of the individual pieces.

Refer to ActualNominal definition for any enumerations.

### (choice)

*[choice] is optional because of choice construct.*

#### Value

*Value is optional because of choice construct.*

A numeric value expressed in the unit of measure (UOM).

#### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

#### AdditionalText

*AdditionalText is optional because of choice construct.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## Thickness

Physical dimension of a product.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### Value

Value is mandatory. A single instance is required.

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


RangeMin is optional. A single instance might exist.

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

RangeMax is optional. A single instance might exist.

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## Thumb

Thumb.

### Bleed [attribute]

Bleed is optional. A single instance might exist.

Either "Yes" or "No".

Refer to Bleed definition for any enumerations.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### Value

Value is mandatory. A single instance is required.

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


RangeMin is optional. A single instance might exist.

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

RangeMax is optional. A single instance might exist.

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an



# papiNet V2R31

extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## AdditionalText


*AdditionalText is optional. A single instance might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## TiersPerPallet

The number of tiers on the pallet, where a tier is a layer of items.



---

## TimberCharacteristics

Timber characteristics

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### LumberSpecies

*LumberSpecies is mandatory. One instance is required, multiple instances might exist.*

Specifies the raw material species.

#### Age


*Age is optional. A single instance might exist.*

Used to report the age of the wood.

#### Grade

*Grade is optional. A single instance might exist.*


Grade



---

## Time

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.



hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time

zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## TimePeriod

The TimePeriod element is used to communicate a duration period of time as indicated in PeriodType.

### PeriodType [attribute]

*PeriodType is optional. A single instance might exist.*

Duration of time

Refer to PeriodType definition for any enumerations.

### (choice)

*[choice] is optional because of choice construct.*

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.


hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

### DateTimeRange

*DateTimeRange is optional because of choice construct.*

The delivery date and/or time range.



## Week

*Week is optional because of choice construct.*


A field defining the week number of the calendar year. ISO 8601 is used as the basis for this element, "Week 01 of a year is the first week that has the Thursday in this year, which is equivalent to the week that contains the fourth day of January."

## TimeSlot

A period of time during which an activity can be scheduled.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### From

*From is mandatory. A single instance is required.*

The beginning point of a timeperiod.

### To

*To is mandatory. A single instance is required.*

The ending point of a timeperiod.

## TimeSlotAvailability [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

**Yes**

**No**



## TimeSlotInformation

Description of the beginning and end of a time slot and the contingencies it contains.

### TimeSlotAvailability [attribute]

*TimeSlotAvailability is mandatory. A single instance is required.*


Either "Yes" or "No".

Refer to TimeSlotAvailability definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### TimeSlot



# papiNet V2R31

*TimeSlot is mandatory. A single instance is required.*

A period of time during which an activity can be scheduled.

## QuantityInformation

*QuantityInformation is optional. Multiple instances might exist.*

A group item containing information about quantity and informational quantity of similar items.


## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## To

The ending point of a timeperiod.



## ToProduct


Defines to which product the item is downgraded.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### (sequence)

*The sequence of items below is mandatory. One instance is required, multiple instances might exist.*



### ProductIdentifier


*ProductIdentifier is mandatory. A single instance is required.*

Used to communicate the code of the article, in a variety of formats designated by the type.

### ProductDescription

*ProductDescription is optional. Multiple instances might exist.*

An element used to communicate a human readable description of the product in the language specified by the Language attribute.



## **Classification**

*Classification is optional. Multiple instances might exist.*

A group item that details the product classification according to a particular organization's scheme. An item across multiple classifications would still be recognized as the same item. Examples of some product classifications are: Containerboard, Pulp-Dissolving, or Newsprint.

### **(choice)**

*[choice] is optional because of choice construct.*

#### **BookManufacturing**

*BookManufacturing is optional because of choice construct.*

BookManufacturing is a group element that contains the elements that describe the book manufacturing process.

#### **ForestWood**

*ForestWood is optional because of choice construct.*

A grouping element with information about characteristics for Forest Wood products.

#### **LabelStock**

*LabelStock is optional because of choice construct.*

LabelStock contains the attributes and characteristics that define the label stock product.

#### **Paper**

*Paper is optional because of choice construct.*

A group item defining the characteristics of the paper product.

#### **Pulp**

*Pulp is optional because of choice construct.*

A group item defining the characteristics of pulp that are not dependent on a particular conversion process.

#### **RecoveredPaper**

*RecoveredPaper is optional because of choice construct.*

A group item defining the characteristics of recycled fibre that are not dependent on a particular conversion process.

#### **VirginFibre**

*VirginFibre is optional because of choice construct.*

Virgin Fibre

#### **WoodProducts**

*WoodProducts is optional because of choice construct.*

A grouping element for all wood products.

---


## TopSide [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

**Yes**

**No**



---

## TotalAdjustments

The CurrencyValue of TotalAdjustments contains the total of all MonetaryAdjustmentAmount for all instances of PriceAdjustment and FlatAmountAdjustment in the document (it excludes TaxAdjustments).



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*


The amount in the referenced currency as defined by the CurrencyType attribute.

---

## TotalAmount

A field containing the total amount including tax.

PurchaseOrder: The total amount, using a valid unit of measure of all the items in the e-Document. Multiple total amounts are allowed so different units of measure or grade sub-totals can be communicated.



CreditDebitNote and Invoice: TotalAmount is equal to TotalNetAmount plus TotalTaxAmount. In certain countries this is the amount that is due for payment based upon the terms of payment.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.


---

## TotalBlanketOrderValue

The authorized amount of the blanket PurchaseOrder.

### (sequence)

*The sequence of items*



*below is mandatory. A single instance is required.*

## **CurrencyValue**

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.


---

## **TotalFASAmount**

TotalFASAmount is the total Free Alongside Ship value.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



## **CurrencyValue**


*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

---

## **TotalInformationalAmount**

A monetary amount used for information purposes only (not for calculation). For example, the invoice price adjustment subtotal is expressed in sterling pounds, and the buyer wants this information expressed in U.S. dollars.



### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

## **CurrencyValue**

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## TotalInformationalQuantity

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

### QuantityType [attribute]

*QuantityType is mandatory. A single instance is required.*

QuantityType communicates information about the type of quantity being communicated and how the receiver might use the information.

Refer to QuantityType definition for any enumerations.

### QuantityTypeContext [attribute]

*QuantityTypeContext is optional. A single instance might exist.*

Provides the location in the value chain where the quantity is being reported.

Refer to QuantityTypeContext definition for any enumerations.

### AdjustmentType [attribute]

*AdjustmentType is optional. A single instance might exist.*

Describes the type of adjustment associated with a quantity.

Refer to AdjustmentType definition for any enumerations.

### MeasuringMethodType [attribute]

*MeasuringMethodType is optional. A single instance might exist.*

Specifies how a measurement value is created.

Refer to MeasuringMethodType definition for any enumerations.

### MeasuringAgency [attribute]

*MeasuringAgency is optional. A single instance might exist.*



The agency defining measuring methods.

Refer to MeasuringAgency definition for any enumerations.

### MeasuringMethod [attribute]

*MeasuringMethod is optional. A single instance might exist.*

The method used to determine how the item under consideration is measured. Measuring methods are defined by the measuring agency.



## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **Value**

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### **RangeMin**

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### **RangeMax**


*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## **TotalNetAmount**

A field containing total amount excluding tax. For example, in the Invoice TotalNetAmount is equal to the sum of LineItemSubTotal plus TotalAdjustments. TotalNetAmount encapsulates CurrencyValue.



## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **CurrencyValue**

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

## TotalNetOfTermsDiscount

The components of the amount to be paid if prompt payment discount terms are met, including the amount that is subject to the payment terms discount, the discount amount, and the amount due after prompt payment discount.

(sequence)

The sequence of items below is mandatory. A single instance is required.

### AmountSubjectToTermsDiscount

*AmountSubjectToTermsDiscount* is mandatory. A single instance is required.

The amount against which prompt payment terms can be applied.

### TotalTermsDiscountNetAmount

*TotalTermsDiscountNetAmount* is optional. A single instance might exist.

The total prompt payment discount amount excluding taxes.

### TotalTermsDiscountNetAmountTax

*TotalTermsDiscountNetAmountTax* is optional. A single instance might exist.

Tax amount calculated for prompt payment discount amount

### TotalTermsDiscountAmount

*TotalTermsDiscountNetAmount* is optional. A single instance might exist.

The total prompt payment discount amount including taxes.

### TotalTermsDiscountNetAmountDue

*TotalTermsDiscountNetAmountDue* is optional. A single instance might exist.

The total amount due after prompt payment discount excluding taxes. Encapsulates CurrencyValue.

### TotalTermsDiscountTaxAmount

*TotalTermsDiscountTaxAmount* is optional. A single instance might exist.

The total tax amount calculated after prompt payment discount.

### TotalTermsDiscountAmountDue

*TotalTermsDiscountAmountDue* is mandatory. A single instance is required.


The total amount due after prompt payment discount, includes the related taxes.

### InformationalAmount

*InformationalAmount* is optional. Multiple instances might exist.

A monetary amount used for information purposes only (not for calculation). For example, the invoice price adjustment subtotal is expressed in sterling pounds, and the buyer wants this information expressed in U.S. dollars.

CreditDebitNote and Invoice - The TaxAmount is displayed in the currency that is applicable throughout the e-Document. When a TaxAmount needs to be displayed in a different national currency, this field is used.



---

## TotalNumberOfLineItems

The total number of individual line items in the document, regardless of the status or type.

TotalNumberOfLineItems	
type	nni4

---

## TotalNumberOfPackingListItems

Total Number Of PackingList Items

TotalNumberOfPackingListItems	
type	nni3

---

## TotalNumberOfPackingListPackingUnits

TotalNumberOfPackingListPackingUnits

TotalNumberOfPackingListPackingUnits	
type	nni3

---

## TotalNumberOfSequences

The total number of sequences in the document.

TotalNumberOfSequences	
type	nni4

---

## TotalNumberOfShipments

Total number of shipments referred to in a DeliveryMessage.

TotalNumberOfShipments	
type	nni4

---

## TotalNumberOfUnits

The total number of units.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*


A numeric value expressed in the unit of measure (UOM).

#### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax




*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## TotalOldInformationalQuantity

A summary of the OldInformationQuantity in the document.

TotalOldInformationalQuantity uses the QuantityInformation attribute group and the Measurement group (element grouping).



### QuantityType [attribute]

*QuantityType is mandatory. A single instance is required.*

QuantityType communicates information about the type of quantity being communicated and how the receiver might use the information.

Refer to QuantityType definition for any enumerations.

### QuantityTypeContext [attribute]

*QuantityTypeContext is optional. A single instance might exist.*

Provides the location in the value chain where the quantity is being reported.

Refer to QuantityTypeContext definition for any enumerations.

### AdjustmentType [attribute]

*AdjustmentType is optional. A single instance might exist.*

Describes the type of adjustment associated with a quantity.

Refer to AdjustmentType definition for any enumerations.

### MeasuringMethodType [attribute]


*MeasuringMethodType is optional. A single instance might exist.*

Specifies how a measurement value is created.

Refer to MeasuringMethodType definition for any enumerations.

### MeasuringAgency [attribute]

*MeasuringAgency is optional. A single instance might exist.*



The agency defining measuring methods.

Refer to MeasuringAgency definition for any enumerations.

## **MeasuringMethod [attribute]**

*MeasuringMethod is optional. A single instance might exist.*

The method used to determine how the item under consideration is measured. Measuring methods are defined by the measuring agency.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **Value**

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### **RangeMin**

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.


### **RangeMax**

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## TotalOldQuantity

A summary of the OldQuantity in the document. TotalOldQuantity uses the QuantityInformation attribute group and the Measurement group (element grouping).



### QuantityType [attribute]

*QuantityType is mandatory. A single instance is required.*

QuantityType communicates information about the type of quantity being communicated and how the receiver might use the information.

Refer to QuantityType definition for any enumerations.

### QuantityTypeContext [attribute]

*QuantityTypeContext is optional. A single instance might exist.*

Provides the location in the value chain where the quantity is being reported.

Refer to QuantityTypeContext definition for any enumerations.

### AdjustmentType [attribute]

*AdjustmentType is optional. A single instance might exist.*

Describes the type of adjustment associated with a quantity.

Refer to AdjustmentType definition for any enumerations.

### MeasuringMethodType [attribute]

*MeasuringMethodType is optional. A single instance might exist.*

Specifies how a measurement value is created.

Refer to MeasuringMethodType definition for any enumerations.

### MeasuringAgency [attribute]

*MeasuringAgency is optional. A single instance might exist.*


The agency defining measuring methods.

Refer to MeasuringAgency definition for any enumerations.

### MeasuringMethod [attribute]

*MeasuringMethod is optional. A single instance might exist.*

The method used to determine how the item under consideration is measured. Measuring methods are defined by the measuring agency.



## (sequence)

The sequence of items below is mandatory. A single instance is required.

### Value

Value is mandatory. A single instance is required.

A numeric value expressed in the unit of measure (UOM).

### RangeMin

RangeMin is optional. A single instance might exist.

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax


RangeMax is optional. A single instance might exist.

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## TotalOpenAmount

InvoiceAmount less the sum of all payment amounts, translated into one common currency.



## (sequence)

The sequence of items below is mandatory. A single instance is required.

### CurrencyValue


CurrencyValue is mandatory. A single instance is required.

The amount in the referenced currency as defined by the CurrencyType attribute.

---

## TotalPageCount


Element used to communicate the book's approximate total number of pages within each unit of the book. Total page count is more or less a reference to the "size" of the book that the customer designates. For instance, they will refer to a book as 800 pages when in fact it is 792 actual text pages with 8 pages of various inserts. This value should not be used to drive any of the other values for the component parts, but may in fact be exactly equal to the number of pages in one of the components designated as "Text".



---

## TotalPaymentAmount

The amounts which were paid and booked against the original invoice.



## (sequence)

The sequence of items below is mandatory. A single

*instance is required.*


## CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

## TotalQuantity

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.



## QuantityType [attribute]

*QuantityType is mandatory. A single instance is required.*

QuantityType communicates information about the type of quantity being communicated and how the receiver might use the information.

Refer to QuantityType definition for any enumerations.

## QuantityTypeContext [attribute]

*QuantityTypeContext is optional. A single instance might exist.*

Provides the location in the value chain where the quantity is being reported.

Refer to QuantityTypeContext definition for any enumerations.

## AdjustmentType [attribute]

*AdjustmentType is optional. A single instance might exist.*

Describes the type of adjustment associated with a quantity.

Refer to AdjustmentType definition for any enumerations.

## MeasuringMethodType [attribute]


*MeasuringMethodType is optional. A single instance might exist.*

Specifies how a measurement value is created.

Refer to MeasuringMethodType definition for any enumerations.

## MeasuringAgency [attribute]

*MeasuringAgency is optional. A single instance might exist.*



The agency defining measuring methods.

Refer to MeasuringAgency definition for any enumerations.

## MeasuringMethod [attribute]

*MeasuringMethod is optional. A single instance might exist.*

The method used to determine how the item under consideration is measured. Measuring methods are defined by the measuring agency.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax


*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## TotalQuantityInformation

A group item containing information about the total quantity and total informational quantity of similar items in the document.



TotalQuantityInformation is primarily used in the summary section of e-Documents where it is repeatable to permit totalling for different units of measure.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### TotalQuantity

*TotalQuantity is mandatory. A single instance is required.*

The total quantity of similar items in the e-Documents. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totalling for different units of measure.

### TotalInformationalQuantity

*TotalInformationalQuantity is optional. Multiple instances might exist.*

A quantity that is used to communicate related information about the parent

element. This element represents a total that is derived from individual line items.

## TotalRunningLength

Summary value of amount measured in running meters, etc.

### QuantityType [attribute]

*QuantityType is mandatory. A single instance is required.*

QuantityType communicates information about the type of quantity being communicated and how the receiver might use the information.

Refer to QuantityType definition for any enumerations.

### QuantityTypeContext [attribute]

*QuantityTypeContext is optional. A single instance might exist.*

Provides the location in the value chain where the quantity is being reported.

Refer to QuantityTypeContext definition for any enumerations.

### AdjustmentType [attribute]

*AdjustmentType is optional. A single instance might exist.*

Describes the type of adjustment associated with a quantity.

Refer to AdjustmentType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



---

## TotalSetNumbers

The total number of sets wound from the Tambour (in the radial direction). Tambour is also called jumbo reel or mother reel.

TotalSetNumbers	
type	nni4

---

## TotalSetPositions


The total number of reels cut across the Tambour (in the width direction). Tambour is also called jumbo reel or mother reel.

TotalSetPositions	
type	nni4

---

## TotalTaxAmount

The CurrencyValue of TotalTaxAmount contains the sum of all instances of TaxAdjustment in the document. TotalTaxAmount contains the sum of all instances of the MonetaryAdjustmentAmount for tax adjustments.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### CurrencyValue


*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

---

## TotalTermsDiscountAmount

The total prompt payment discount amount including taxes.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### CurrencyValue


*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

---

## TotalTermsDiscountAmountDue

The total amount due after prompt payment discount, includes the related taxes.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

## CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*


The amount in the referenced currency as defined by the CurrencyType attribute.

---

## TotalTermsDiscountNetAmount

The total prompt payment discount amount excluding taxes.

**(sequence)**



*The sequence of items below is mandatory. A single instance is required.*

## CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.


---

## TotalTermsDiscountNetAmountDue

The total amount due after prompt payment discount excluding taxes.

Encapsulates CurrencyValue.

**(sequence)**



*The sequence of items below is mandatory. A single instance is required.*

## CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*


The amount in the referenced currency as defined by the CurrencyType attribute.

---

## TotalTermsDiscountNetAmountTax

Tax amount calculated for prompt payment discount amount.

**(sequence)**



*The sequence of items below is mandatory. A single instance is required.*

## CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*


The amount in the referenced currency as defined by the CurrencyType attribute.

---

## TotalTermsDiscountTaxAmount

The total tax amount calculated after prompt payment discount.

**(sequence)**



*The sequence of items below is mandatory. A single instance is required.*


### CurrencyValue

*CurrencyValue is mandatory. A single instance is required.*

The amount in the referenced currency as defined by the CurrencyType attribute.

## TotalTime

The total time.



## TrackingReferenceID

A grouping element that defines tracking references between items processed in the supply chain.

### TrackingReferenceIDType [attribute]

*TrackingReferenceIDType is mandatory. A single instance is required.*

Defines the type of relationship the actual item has to other the tracked items.

Refer to TrackingReferenceIDType definition for any enumerations.

### ItemType [attribute]

*ItemType is mandatory. A single instance is required.*

Indicates the form of the item being reported as being used. Many of the ItemType(s) indicated here have a corresponding named element equivalent, which is referenced here for definition purposes.

Refer to ItemType definition for any enumerations.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Identifier

*Identifier is mandatory. Multiple instances might exist.*

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.



## TrackingReferenceIDType [attribute]

Defines the type of relationship the actual item has to other the tracked items.

TrackingReferenceIDType	
type	trackingReferenceIDType

*This item is restricted to the following list.*

### Child

This item is derived from the actual item. E.g. a board from a saw log.

### Origin

The origin of the actual item. E.g. a logging area where a saw log was cut.

### Parent

The actual item is derived from this item. E.g. a sawlog is cut from a stem.

---

## TrackType [attribute]

The type of track

*This item is restricted to the following list.*

attribute	
TrackType	
type	trackType

### Mono

Track type is monaural.

### Stereo


Track type is stereophonic.

---

## TradeRegion

A geographic area for product availability communication.

### IsTradeRegionAvailable [attribute]



*IsTradeRegionAvailable is mandatory.*

*A single instance is required.*

Is the geographic area available or not.

Refer to IsTradeRegionAvailable definition for any enumerations.

---

## TransactionHistoryConfirmationNumber

A sequential number that indicates the version of the confirmation document being sent.

TransactionHistoryConfirmationNumber	
type	nni9

---

## TransactionHistoryNumber

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

<b>TransactionHistoryNumber</b>	
type	nni9

---

## TransportationComment

Textual Commentary on Transportation for an entire GoodsReceipt.


### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### AdditionalText

*AdditionalText is mandatory. A single instance is required.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



---

## TransportContextType [attribute]

Provides information about the reason for the transport.

*This item is restricted to the following list.*

### Normal (default)

The transport is a normal freight

### Return

The transport is a return freight

attributes	
<b>TransportContextType</b>	
type	transportContextType
default	Normal

---

## TransportDeckOption [attribute]

Allotment of a shipping lot that can be placed on the deck of a ship.

*This item is restricted to the following list.*

### FullDeck

The full load can be placed on the deck of the transport vehicle (ship).

### HalfDeck

Only half the load can be placed on the deck of the transport vehicle (ship).

### OneThirdDeck

attribute	
<b>TransportDeckOption</b>	
type	deckType

Only one-third of the load can be placed on the deck of the transport vehicle (ship).

## UnderDeck

The entire load must be placed under the deck of the transport vehicle (ship).

## TransportInformation


A grouping element for transport information.

### TransportContextType [attribute]

*TransportContextType is optional. A single instance might exist.*

Provides information about the reason for the transport.

Refer to



TransportContextType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### TransportModeCharacteristics

*TransportModeCharacteristics is optional. A single instance might exist.*

A group item defining the primary mode of transport.

#### TransportVehicleCharacteristics

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

#### TransportUnitCharacteristics

*TransportUnitCharacteristics is optional. Multiple instances might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

#### TransportLoadingCharacteristics

*TransportLoadingCharacteristics is optional. Multiple instances might exist.*

A group item defining how the transported items are to be loaded.

#### TransportUnloadingCharacteristics

*TransportUnloadingCharacteristics is optional. Multiple instances might exist.*



A group item defining how the transported items are to be unloaded.

## TransportOtherInstructions

*TransportOtherInstructions is optional. Multiple instances might exist.*

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.

## TransportPropertyValue

*TransportPropertyValue is optional. Multiple instances might exist.*

Specifies values for various properties for a transport.

## Route

*Route is optional. Multiple instances might exist.*

Route defines directions and characteristics for how to transport goods between two locations. A route starts at delivery origin or at the supplypoint belonging to the delivery origin.

## DocumentInformation


*DocumentInformation is optional. Multiple instances might exist.*

A group element containing a specification of required documents in the business process. Additional free text to be printed on documents can also be specified.

---

## TransportInstructionCode

A code used to define any other transport instructions that are not covered in the description of transport mode, vehicle, unit, and loading characteristics or used alternatively to summarise in one unique code the above-mentioned categories.



### Agency [attribute]

*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.


For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

---

## TransportInstructionText

A text field further describing the transport instructions.



## TransportInstructionType [attribute]

Indicates the type of instruction.

*This item is restricted to the following list.*

### LegSpecific

The text is related to the delivery leg or entire delivery.

### ProductSpecific

The text is related to the product being transported.



## TransportLoadingCharacteristics

A group item defining how the transported items are to be loaded.

### MixProductIndicator [attribute]


*MixProductIndicator is optional. A single instance may occur.*

Specifies whether a product can be mixed with other products on the same shipment.

Refer to MixProductIndicator definition for any enumerations.

### TransportLoadingType [attribute]

*TransportLoadingType is optional. A single instance might exist.*



Defines the primary loading modes for the transport of the goods

Refer to TransportLoadingType definition for any enumerations.

### TransportDeckOption [attribute]

*TransportDeckOption is optional. A single instance might exist.*


Allotment of a shipping lot that can be placed on the deck of a ship.

Refer to TransportDeckOption definition for any enumerations.

### LoadingTolerance [attribute]

*LoadingTolerance is optional. A single instance might exist.*

Specifies tolerance type for load quantity. Tolerance values are given by



RangeMin and RangeMax in Quantity.

Refer to LoadingTolerance definition for any enumerations.

## **DirectLoading [attribute]**

*DirectLoading is optional. A single instance might exist.*

Specifies if the transport unit should be loaded directly with goods received on another transport unit.

Refer to DirectLoading definition for any enumerations.

## **GoodsLoadingPrinciple [attribute]**

*GoodsLoadingPrinciple is optional. A single instance might exist.*

Defines principles for how goods are picked from warehouse and loaded

Refer to GoodsLoadingPrinciple definition for any enumerations.

## **LabelOrientation [attribute]**

*LabelOrientation is optional. A single instance might exist.*

Specifies label orientation for loaded goods seen in the transport direction of the goods carrier. It makes the label visible during unloading from a predetermined side.

Refer to LabelOrientation definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **TransportLoadingCode**

*TransportLoadingCode is optional. A single instance might exist.*

A code defining how the transported items are to be loaded.

### **TransportLoadingCodeDescription**

*TransportLoadingCodeDescription is optional. A single instance might exist.*

A group item describing the TransportLoadingCode. The document specifying how to load goods based on the TransportLoadingCode can be supplied in e-Attachment. TransportLoadingCode can be used as a Load Pattern identifier.

### **TransportLoadingText**

*TransportLoadingText is optional. Multiple instances might exist.*

A text field further describing the transport loading instructions.

---


## **TransportLoadingCode**

A code defining how the transported items are to be loaded.

### **Agency [attribute]**

*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry



organisation.

For the element that owns this attribute.


For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

---

## TransportLoadingCodeDescription

A group item describing the TransportLoadingCode. The document specifying how to load goods based on the



TransportLoadingCode can be supplied in e-Attachment. TransportLoadingCode can be used as a Load Pattern identifier.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

#### **e-Attachment**

*e-Attachment is optional. A single instance might exist.*


e-Attachment enables the sender to provide information about attachments to the document.

Note: BizTalk users may have problems in processing this element. See the papiNet FAQs ([papiNet.org](http://papiNet.org)) for more information.

---

## TransportLoadingText

A text field further describing the transport loading instructions.



---


## TransportLoadingType [attribute]

Defines the primary loading modes for the transport of the goods

*This item is restricted to the following list.*

### **ByLoadingCode**

How to load the goods is specified via the element TransportLoadingCode.



TransportLoadingCode can be used as a Load Pattern identifier. A separate document, that can be specified by element TransportLoadingCodeDescription, specifies the Load Pattern in all details.

## Lying

The goods, such as reels on the belly, have to be in a lying position during transport.

## Standing

The goods, such as reels standing on end, have to be in a standing position during transport

## StandingUpsideDown

The goods, such as reels standing on end but turned upside-down, have to be in a standing position during transport. Reels are turned upside-down to get the right unwinding direction at end user.

## Other

Used for any other loading modes not covered by this list.

## TransportModeCharacteristics

A group item defining the primary mode of transport.

### TransportModeType [attribute]

*TransportModeType is optional. A single instance might exist.*

Defines the primary mode of transport for the goods

Refer to TransportModeType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### TransportModeCode


*TransportModeCode is optional. A single instance might exist.*

A code defining the primary mode of transport.

#### TransportModeText

*TransportModeText is optional. A single instance might exist.*

A text field further describing the transport mode.




## TransportModeCode

A code defining the primary mode of transport.

### Agency [attribute]

*Agency is mandatory. A single*



*instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

---

## TransportModeText

A text field further describing the transport mode.

<b>TransportModeText</b>
type s72

---

## TransportModeType [attribute]

Defines the primary mode of transport for the goods

*This item is restricted to the following list.*

### Air

The goods will be transported by air.

### InlandWaterway

The goods will be transported by inland waterway.

### Intermodal

The movement of goods in one and the same transport unit, which uses successively two or more modes of transport without handling the goods themselves in changing modes. (Definition courtesy of the UN/ECE, the European Conference of Ministers of Transport [ECMT] and the European Commission [EC])

### Mail

The goods will be sent by post.

### Multimodal

The goods will be transported by two or more modes of transport. Handling of goods can occur in changing transport modes.

### Rail

The goods will be transported by rail.

### Road

The goods will be transported by road.

### Sea

The goods will be transported by sea.


### Other

attribute
<b>TransportModeType</b>
type transportModeType

Used for any other transport modes not covered by this list.

## TransportOtherInstructions

A group item defining any other instructions for the transport not covered in the description of transport mode, vehicle, unit, and loading characteristics or defining an alternative description for the categories mentioned above.



### TransportInstructionType [attribute]

*TransportInstructionType is optional. A single instance might exist.*

Indicates the type of instruction.

Refer to `TransportInstructionType` definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### TransportInstructionCode

*TransportInstructionCode is optional. A single instance might exist.*

A code used to define any other transport instructions that are not covered in the description of transport mode, vehicle, unit, and loading characteristics or used alternatively to summarise in one unique code the above-mentioned categories.

#### TransportInstructionText

*TransportInstructionText is optional. Multiple instances might exist.*

A text field further describing the transport instructions.

## TransportPackageInformation

Information of a package used in transportation, can include several normal packages.

### PackageType [attribute]

*PackageType is mandatory. A single instance is required.*

Communicates the configuration of the item being reported.

Refer to PackageType definition for any enumerations.



### MixedProductPalletIndicator [attribute]

*MixedProductPalletIndicator is optional. A single instance might exist.*

Specifies whether a product can be mixed with other products on the same pallet

Refer to MixedProductPalletIndicator definition for any enumerations.

### PackageLevel [attribute]

*PackageLevel is optional. A single instance might exist.*

An hierarchical numbering approach that communicates containerization and identity.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Identifier

*Identifier is mandatory. One instance is required, multiple instances might exist.*


An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.

#### RawMaterialSet

*RawMaterialSet is optional. Multiple instances might exist.*

This identifier derived element indicates a grouping of raw materials that were used to manufacture the product.

### (sequence)



*The sequence of items below is optional. A single instance might exist.*

## **PartyIdentifier**

*PartyIdentifier is mandatory. One instance is required, multiple instances might exist.*

A unique identifier of a specific party. This element contains an attribute PartyIdentifierType that indicates the type of party.

## **MachineID**

*MachineID is mandatory. A single instance is required.*

An identifier assigned to the particular machine being referenced. For example, a machine could be a paper machine, an off-line coater, a sheeter, or a printing press. The particular machine being referenced will be determined by the business event being supported.

## **ItemCount**

*ItemCount is mandatory. A single instance is required.*

A count of the number of items (examples: a count of the number of boxes on a pallet or of reams in a box).

## **Quantity**

*Quantity is mandatory. A single instance is required.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **InventoryClass**

*InventoryClass is optional. A single instance might exist.*

A group item containing information about status of inventory and goods items.

## **TransportVehicleCharacteristics**

*TransportVehicleCharacteristics is optional. A single instance might exist.*

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.

## **TransportUnitCharacteristics**

*TransportUnitCharacteristics is optional. A single instance might exist.*

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

## **PackageCharacteristics**

*PackageCharacteristics is optional. A single instance might exist.*

The package characteristics.

**(choice)**

*[choice] is optional because of choice construct.*

**BaleItem**

*BaleItem is optional because of choice construct.*

An individual bale included as part of a delivery.

**BoxItem**

*BoxItem is optional because of choice construct.*

A four-sided container for reams or sheet items. A pallet can contain zero or more boxes. The term Carton is a synonym for BoxItem. The term "Box" is used as constraint within the ItemType attribute of the UsageLineItemDetail to refer to a box that contains other boxes.

**ReelItem**

*ReelItem is optional because of choice construct.*

A group item representing details of an actual (as opposed to specified) reel. One or several reels can be contained in a package.

**ReamItem**

*ReamItem is optional because of choice construct.*

A wrapped quantity of SheetItem(s).

**SheetItem**

*SheetItem is optional because of choice construct.*

A group item consisting potentially of the date the sheets were converted into sheets and/or packaged or finished.

**UnitItem**

*UnitItem is optional because of choice construct.*

Unit Item.

**WoodItem**

*WoodItem is optional because of choice construct.*

Group element containing elements describing a wood industry product.

**OtherDate**

*OtherDate is optional. A single instance might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

---

## TransportPropertyType [attribute]

Defines the property specified for a transport.

*This item is restricted to the following list.*

**DistanceWithLoad**

Transported distance with a payload.

**DistanceWithoutLoad**



Transported distance without a payload.

## **LoadingTime**

Time elapsed during loading.

## **LoadingWaitingTime**

Time elapsed waiting for loading.

## **UnLoadingTime**

Time elapsed during unloading.

## **UnLoadingWaitingTime**

Time elapsed waiting for unloading.

---

## **TransportPropertyValue**

Specifies values for various properties for a transport.

### **TransportPropertyType [attribute]**

*TransportPropertyType is mandatory. A single instance is required.*

Defines the property specified for a transport.

Refer to TransportPropertyType definition for any enumerations.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

#### **Value**

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### **RangeMin**


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### **RangeMax**

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



---

## TransportStatus

Text element used to communicate the current status of the shipment actually being transported to the recipient. This element could indicate the tracking status that the transport company issues. Alternatively, it could be the vendor's internal tracking status of the shipment.

TransportStatus	
type	s30


---

## TransportStatusIssueDate

The Date and Time the transport status is issued.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### Time

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## TransportUnitCharacteristics

A group item defining and identifying the primary means of containing the goods. In some instances, the transport unit and vehicle are the same.

### TransportUnitType [attribute]

*TransportUnitType is mandatory. A single instance is required.*

Provides general information about the

transport unit, which is the unit containing the goods. Transport units only move using power from another source, the transport vehicle. Additional detail can be specified through a detail type.

Refer to TransportUnitType definition for any enumerations.

### TransportUnitVariable [attribute]

*TransportUnitVariable is optional. A single instance might exist.*

Indicates if there is an attribute of the transport unit that can change (is variable).

Refer to TransportUnitVariable definition for any enumerations.

### TransportUnitLevel [attribute]

*TransportUnitLevel is optional. A single instance might exist.*

The sequential number that uniquely identifies the level of stacked transport units. For example, on a train with wagons loaded with containers the transport unit levels would be wagon level 1 and container level 2.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### TransportUnitCode

*TransportUnitCode is optional. A single instance might exist.*

A code defining the primary means of containing the goods.


#### TransportUnitMeasurements

*TransportUnitMeasurements is optional. Multiple instances might exist.*

A group item containing the measurements (length, height, weight, and width) of the transport unit.

#### TransportUnitEquipment

*TransportUnitEquipment is optional. Multiple instances might exist.*



A group item defining extra equipment of the transport unit.

## **TransportUnitCount**

*TransportUnitCount is optional. A single instance might exist.*

An item defining the number of units used to transport the goods.

## **TransportUnitIdentifier**

*TransportUnitIdentifier is optional. Multiple instances might exist.*

The identifier of the transport unit, such as a container ID. It could be a license plate number if the transport unit is the vehicle at the same time. The type of identifier is indicated by the TransportUnitIdentifierType.

## **TransportUnitText**

*TransportUnitText is optional. A single instance might exist.*

A text field further describing the transport unit.

## **TransportUnitDetail**

*TransportUnitDetail is optional. A single instance might exist.*

A group item describing details for a transport unit.

---

## **TransportUnitCode**

A code defining the primary means of containing the goods.

### **Agency [attribute]**


*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.



---

## **TransportUnitCount**

An item defining the number of units used to transport the goods.



## TransportUnitDetail

A group item describing details for a transport unit.

### TransportUnitDetailType [attribute]

*TransportUnitDetailType is optional. A single instance might exist.*

Specifies detail type of a transport unit. If needed variants of a transport unit detail type can be specified by TransportUnitDetailCode in a Trading Partner Agreement as well as clarified in AdditionalText.

Refer to TransportUnitDetailType definition for any enumerations.

### LoadOpeningSide [attribute]

*LoadOpeningSide is optional. A single instance might exist.*

Specifies opening sides on a transport unit for loading and unloading seen in the transport direction of the goods carrier

Refer to LoadOpeningSide definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### TransportUnitDetailCode


*TransportUnitDetailCode is optional. A single instance might exist.*

A code defining details of a transport unit.

#### AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.



## TransportUnitDetailCode


A code defining details of a transport unit.

### Agency [attribute]

*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.




For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

---

## TransportUnitDetailType [attribute]

Specifies detail type of a transport unit. If needed variants of a transport unit detail type can be specified by TransportUnitDetailCode in a Trading Partner Agreement as well as clarified in AdditionalText.



*This item is restricted to the following list.*

### **DryFreightContainer**

The most widely used container for general cargo. It is available in 20 and 40 feet lengths. For high volume, low weight cargo, 9.5 foot high, 40 foot and 45 foot units are available giving an additional internal cubic capacity.

### **PlatformContainer**

Container Platform Flats and Flatracks are primarily used for the containerisation of oversize, awkward and project cargoes that would otherwise be carried break bulk. These units are increasingly being used as temporary 'tweendecks' for the carriage of large, indivisible loads which are loaded separately on to a bed of flat-racks or platforms spread on top of a ship's hatch cover.

### **OpenSidesContainer**

A container with loading and unloading via side and rear doors. It can also have a curtain side.

### **OpenTopContainer**

A container with an open top that can be loaded via top side and rear doors. Covered by means of removable tilt. Open top containers are designed for the carriage of awkward, indivisible or oversize cargoes. The units offer increased versatility over standard boxes as they are designed for loading through both the top of the container and the rear doors. All units are equipped with a swinging cross-door beam header, which opens outwards to give unrestricted access through the door opening. The simplicity of loading and discharge and the full protection offered by a TIR approved tarpaulin provide a container that will ensure the safe passage of a broad range of cargoes.

### **OverheadContainer**

A container with oversize measurements. Common types are "Open Top High Cube" and "Pallet Wide High Cube".

### **SwapBodyContainer**

A container with foldable legs and transported on chassis. A SwapBody can easily be stored and swapped between different transport modes, usually road/rail. No handling equipment is needed. Swapbodies are designed for two-palletwide operations. The increased internal width of a swapbody unit allows two pallets (up to a maximum of 1200mm wide) to be loaded side by side.

## **BoxTrailer**

Semi-railer completely closed only accessible with doors at rear end. The box is often made of plywood.

## **CurtainsiderTrailer**

Semi-Trailer with automatic or semi-automatic curtain that opens on the side. An other common used name is Tautliner.

## **DrawBarTrailer**

A trailer with both front and rear axles usually towed by a lorry. It can be either covered or uncovered. A drawbar trailer carries the full load on its axles compared to a semi-trailer that only carries the half load on its rear axles. A semi-trailer can't move by itself because it only has wheels at the rear end.

## **GooseneckTrailer**

Semi-Trailer with a stepdeck at the front end, i.e. not a flat platform. It can be both covered or uncovered.

## **HuckepackTrailer**

Platform or Semi-Trailer with reinforcements and specially designed to be lifted on and off rail wagons. It makes it easy to mix transport modes for the transport unit from road to rail and vice versa. Synonym: StackTrain, Piggyback.

## **FlatbedTrailer**

Semi-Trailer with an open flat platform.

## **SkeletalTrailer**

A universal extensible skeletal chassis.

## **SkeletalContainerTrailer**

A chassis designed to carry containers.

## **SkeletalDrawbarTrailer**

A chassis with a drawbar.

## **SpecialTrailer**

Semi-Trailer equipped with special features to load and unload goods. This type can have special designed floor to move goods without any external handling tools. Typical used names are CoilTrailer, Joloda, LoadMate, Rolamat, Selfloader and Walking floor. Dimensions on loading/unloading facilities, e.g. skates, may vary between makes. A CurtainSider with sliding roof is also typed as Special.

## **TerminalTrailer**

Equipment which is not allowed on public roads and used for moving goods in terminals and warehouses. Normally these trailer types have no transport unit identifiers. Typical used names are Mafi, Platform and Roltrailer.

## **TiltTrailer**

Semi-Trailer which can be closed by means of removable tilts.

## **BasketRailCar**

A railcar with a demountable sub frame, fitted with devices for vertical

handling, to allow the loading and unloading of semi-trailers or road vehicles.

## ContainerRailCar

Open railcar designed to carry Containers, SwapBodies etc.

## FlatRailCar

A railcar without roof or sides, or railcar without roof but with sides not higher than 60 cm, or swing-bolster railcar, of ordinary or special type. Railcars designed exclusively to carry containers, swap-bodies or goods vehicles are excluded.

## HighSidedRailCar

A railcar with no roof and with rigid sides higher than 60 cm.

## PocketRailCar

A railcar with a recessed pocket to accept the axle/wheel assembly of a semitrailer.


## SpineRailCar

A rail railcar with a central chassis designed to carry a semi-trailer.

---

## TransportUnitEquipment

A group item defining extra equipment of the transport unit.



### (sequence)

*The sequence of items below is mandatory.  
A single instance is required.*

#### TransportUnitEquipmentCode

*TransportUnitEquipmentCode is optional. A single instance might exist.*

TransportUnitEquipmentCode is a code describing extra equipment of the transport unit.

#### TransportUnitEquipmentDescription


*TransportUnitEquipmentDescription is optional. Multiple instances might exist.*

A text field element describing the extra equipment of the transport unit.

---

## TransportUnitEquipmentCode

TransportUnitEquipmentCode is a code describing extra equipment of the transport unit.



### Agency [attribute]

*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

---

## TransportUnitEquipmentDescription

A text field element describing the extra equipment of the transport unit.

### Language [attribute]

*Language is optional. A single instance might exist.*



XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.


---

## TransportUnitHeight

The height of the transport unit in a UOM (usually meters or feet).

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.



### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## TransportUnitIdentifier

The identifier of the transport unit, such as a container ID. It could be a license plate number if the transport unit is the vehicle at the same time. The type of identifier is indicated by the



TransportUnitIdentifierType.

### TransportUnitIdentifierType [attribute]

*TransportUnitIdentifierType is mandatory. A single instance is required.*

Provides a contextual definition for the value used to identify the transport unit.

Refer to TransportUnitIdentifierType definition for any enumerations.

### StateOrProvince [attribute]

*StateOrProvince is optional. A single instance might exist.*

The political designation or boundary of a specific area of land.

### ISOCountryCode [attribute]

*ISOCountryCode is optional. A single instance might exist.*

The valid list of ISO Country Codes.

Refer to ISOCountryCode definition for any enumerations.

## TransportUnitIdentifierType [attribute]

Provides a contextual definition for the value used to identify the transport unit.

*This item is restricted to the following list.*



### ContainerID

Defines a container identifier.

### CassetteID

Defines a cassette identifier.

### GlobalReturnableAssetIdentifier

A returnable asset is a reusable package or transport equipment of a certain value. The Global Returnable Asset Identifier (GRAI) provides for the unique identification of an asset; it utilizes a UCC assigned Company Prefix enabling a user to develop, assign and maintain a unique asset number for equipment, resources, supplies, etc. in order to track its location and/or user. The EAN.UCC identification number of a returnable asset (GRAI) is defined as a physical item with no reference to the contents. The EAN.UCC identification of a returnable asset (GRAI) enables tracking as well as recording of all relevant data.

## RailCarID

A rail car identifier.

## RFTag

The fixed built-in identifier of a RFID unit attached to a transport unit.

## SealNumber

Identifies the seal that closes the transport unit.

## SerialShippingContainerCode

The unique identification of logistics units is achieved in the EAN.UCC System by the use of the SSCC (Serial Shipping Container Code). The SSCC is an 18-digit numeric data structure. The uniqueness of the data structure is ensured through the use of the EAN.UCC Company Prefix, which is supplied by the UCC or another EAN Member Organization. This Company Prefix, when combined with the serial number that is assigned by the member company, acts as an identifier or "license plate" and provides access to information stored in computer files, which are transferred through electronic business transactions.

## TrailerID

A trailer identifier. Note: This can be a licence plate number if the transport unit is the vehicle at the same time, or if the transport unit is a trailer with a licence plate number of its own. TrailerID is also used as identifier type for DrawBarCombination and RigidLorry.

## WagonID

Will be removed in version v3r00. Use instead RailCarID

## Other

Used for any other transport unit identifiers not covered by this list.


---

## TransportUnitLength

The length of the transport unit in a valid UOM (usually meters or feet).

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## TransportUnitLevel [attribute]

The sequential number that uniquely identifies the level of stacked transport units. For example, on a train with wagons loaded with containers the transport unit levels would be wagon level 1 and container level 2.

attribute	
<b>TransportUnitLevel</b>	
type	nni1
default	1

## TransportUnitMeasurements

A group item containing the measurements (length, height, weight, and width) of the transport unit.

### AppliesTo [attribute]

*AppliesTo is optional. A single instance might exist.*

Specifies the type of item to which measurements apply to.

Refer to AppliesTo definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### TransportUnitLength

*TransportUnitLength is optional. A single instance might exist.*

The length of the transport unit in a valid UOM (usually meters or feet).

### TransportUnitWidth

*TransportUnitWidth is optional. A single instance might exist.*

The width of the transport unit in a valid UOM (usually meters or feet).

### TransportUnitHeight


*TransportUnitHeight is optional. A single instance might exist.*

The height of the transport unit in a UOM (usually meters or feet).

### TransportUnitWeight

*TransportUnitWeight is optional. A single instance might exist.*

The weight of the transport unit in a valid UOM (usually tons, pounds, or kilograms).



## TransportUnitText

A text field further describing the transport unit.

TransportUnitText	
type	s72

---

## TransportUnitType [attribute]

Provides general information about the transport unit, which is the unit containing the goods. Transport units only move using power from another source, the transport vehicle. Additional detail can be specified through a detail type.

attribute	TransportUnitType	
type	transportUnitType	

*This item is restricted to the following list.*

### **Barge**

A flat, inland waterways transport unit, which is typically towed, one or many at the same time, by a towing vessel.

### **Cassette**

A platform used for RORO vessels to roll-on and roll-off goods to be moved.

### **Container**

A generic term for a box to carry goods, strong enough for repeated use, usually stackable and fitted with devices for transfer between modes. There are a number of different types of containers.

### **ConventionalVessel**

To be removed in version v3r00. Select the best fit from the TransportUnitType list.

### **DrawBarCombination**

A RigidLorry and a DrawBarTrailer combined together and handled as one transport unit. It is typically used in Scandinavian countries.

### **Flatbed**

To be removed in version v3r00. See detail types.

### **FlatCar**

To be removed in version v3r00. See detail types.

### **RailCar**

A rail-based, covered mode of transport. Synonym: Rail Wagon.

### **RigidLorry**

Carries goods in a body mounted to the chassis of a truck. It can be covered or uncovered. Synonym: Straight Truck.

### **StackTrain**

To be removed in v3r00. See detail types.

### **SwapBodies**

To be removed in v3r00. See detail types.

## Trailer

A road trailer usually pulled by a truck.

## Wagon

To be removed in v3r00. Use instead transport unit "RailCar" and detail types of railcars.

## Other


Used for any other transport units not covered by this list. To be removed in version v3r00.

---

## TransportUnitVariable [attribute]

Indicates if there is an attribute of the transport unit that can change (is variable).

*This item is restricted to the following list.*



### CubicCapacity

### DeckOption

### Height

### Length

### RailcarDoorSize

### WeightCarryingCapacity


---

## TransportUnitWeight

The weight of the transport unit in a valid UOM (usually tons, pounds, or kilograms).

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*


The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## TransportUnitWidth

The width of the transport unit in a valid UOM (usually meters or feet).

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax


*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## TransportUnloadingCharacteristics

A group item defining how the transported items are to be unloaded.

### TransportUnloadingType [attribute]



*TransportUnloadingType is optional. A single instance might exist.*


Defines the primary unloading modes for the transport of the goods

Refer to TransportUnloadingType definition for any enumerations.

### DirectUnloading [attribute]

*DirectUnloading is optional. A single instance might exist.*

Specifies if the transport unit should be unloaded directly on to a new transport unit. Certain transport units, e.g. cassettes, can be stored in warehouses a short period waiting for direct unloading.



Refer to DirectUnloading definition for any enumerations.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### TransportUnloadingCode

*TransportUnloadingCode is optional. A single instance might exist.*

A code defining how the transported items are to be unloaded.

### TransportUnloadingCodeDescription

*TransportUnloadingCodeDescription is optional. A single instance might exist.*

A group item describing the TransportUnloadingCode. The document specifying how to unload goods based on the TransportUnloadingCode can be supplied in e-Attachment.

### TransportUnloadingText

*TransportUnloadingText is optional. Multiple instances might exist.*

A text field further describing the transport unloading instructions.

---

## TransportUnloadingCode

A code defining how the transported items are to be unloaded.

### Agency [attribute]


*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.



---


## TransportUnloadingCodeDescription

A group item describing the TransportUnloadingCode. The document specifying how to unload goods based on the

TransportUnloadingCode can be supplied in e-Attachment.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*



## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## **e-Attachment**

*e-Attachment is optional. A single instance might exist.*


e-Attachment enables the sender to provide information about attachments to the document.

Note: BizTalk users may have problems in processing this element. See the papiNet FAQs (papiNet.org) for more information.

---

## **TransportUnloadingText**

A text field further describing the transport unloading instructions.




---

## **TransportUnloadingType [attribute]**

Defines the primary unloading modes for the transport of the goods

*This item is restricted to the following list.*



### **ByUnloadingCode**

How to unload the goods is specified via the element TransportUnloadingCode. TransportUnloadingCode can be used as a Load Pattern identifier. A separate document, that can be specified by element TransportUnloadingCodeDescription, specifies the Load Pattern in all details

### **Lying**

The goods, such as reels on the belly, have to be in a lying position after unloading.

### **Standing**

The goods, such as reels standing on end, have to be in a standing position after unloading.

### **StandingUpsideDown**

The goods, such as reels standing on end but turned upside-down in a standing position after unloading. Reels are turned upside-down to get the right unwinding direction at end user.

### **Other**

Used for any other loading modes not covered by this list.

## TransportVehicleCharacteristics

A group item defining the primary means of transporting the goods, such as a side port vessel. In some instances, the transport unit and vehicle are the same.



### TransportVehicleType [attribute]

*TransportVehicleType is optional. A single instance might exist.*

Provides details on the transport vehicle. A transport vehicle has its own power and can be used to pull, carry, or tow a transport unit loaded with goods.

Refer to TransportVehicleType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### TransportVehicleCode

*TransportVehicleCode is optional. A single instance might exist.*

A code defining the primary means of transporting the goods.

#### TransportVehicleMeasurements

*TransportVehicleMeasurements is optional. A single instance might exist.*

A group item containing the measurements (length, height, weight, and width) of the transport vehicle.

#### TransportVehicleEquipment

*TransportVehicleEquipment is optional. Multiple instances might exist.*

A group item defining extra equipment of the transport vehicle.

#### TransportVehicleCount

*TransportVehicleCount is optional. A single instance might exist.*

The number of vehicles used to transport the goods.

#### TransportVehicleIdentifier


*TransportVehicleIdentifier is optional. Multiple instances might exist.*

The identifier of the transport vehicle (license plate number, voyage number, or vessel name). TransportVehicleIdentifier contains the TransportVehicleIdentifierType attribute.

#### TransportVehicleText

*TransportVehicleText is optional. A single instance might exist.*

A text field further describing the transport vehicle.




---

## TransportVehicleCode

A code defining the primary means of transporting the goods.

### Agency [attribute]

*Agency is mandatory. A single instance is required.*



Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.


For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

---

## TransportVehicleCount


The number of vehicles used to transport the goods.



---

## TransportVehicleEquipment

A group item defining extra equipment of the transport vehicle.



### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### TransportVehicleEquipmentCode

*TransportVehicleEquipmentCode is optional. A single instance might exist.*

TransportVehicleEquipmentCode is a code describing extra equipment of the transport vehicle.

#### TransportVehicleEquipmentDescription

*TransportVehicleEquipmentDescription is optional. Multiple instances might exist.*

A text field element describing the extra equipment of the transport vehicle.

## TransportVehicleEquipmentCode

TransportVehicleEquipmentCode is a code describing extra equipment of the transport vehicle.



### Agency [attribute]

*Agency is mandatory. A single instance is required.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

## TransportVehicleEquipmentDescription

A text field element describing the extra equipment of the transport vehicle.



### Language [attribute]

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

## TransportVehicleHeight

The number of vehicles used to transport the goods.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*


A numeric value expressed in the unit of measure (UOM).

#### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax




*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## TransportVehicleIdentifier

The identifier of the transport vehicle (license plate number, voyage number, or vessel name). TransportVehicleIdentifier contains the TransportVehicleIdentifierType attribute.



## TransportVehicleIdentifierType [attribute]

*TransportVehicleIdentifierType is optional. A single instance might exist.*

Provides a contextual definition for the value used to identify the transport vehicle.

Refer to TransportVehicleIdentifierType definition for any enumerations.

## StateOrProvince [attribute]

*StateOrProvince is optional. A single instance might exist.*

The political designation or boundary of a specific area of land.

## ISOCountryCode [attribute]

*ISOCountryCode is optional. A single instance might exist.*

The valid list of ISO Country Codes.

Refer to ISOCountryCode definition for any enumerations.

---

## TransportVehicleIdentifierType [attribute]

Provides a contextual definition for the value used to identify the transport vehicle.

*This item is restricted to the following list.*

### FlightNumber

A flight number.

### GlobalReturnableAssetIdentifier

To be removed in v3r00.

### IMONumber

An identifier type for a Vessel



## LicencePlateNumber

A licence plate number.

## RadioCallSign

An identifier type for a Vessel

## RFTag

The fixed built-in identifier of a RFID unit attached to transport vehicle.

## SerialisedShippingContainerCode

To be removed in v3r00.

## StandardCarrierAlphaCode

The code used to identify the carrier by the applicable governing body.

## TrainNumber

The official identifier assigned by the railways to this particular train movement.

## VesselName

The registered name of the vessel.

## VoyageNumber

The official identifier assigned for the voyage, usually by port authorities. Also known as Unique Voyage Identifier, UVI.

## Other

Used for any other transport vehicle identifiers not covered by this list.



---

## TransportVehicleLength

The length of the transport vehicle in a valid UOM (usually meters or feet).

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact)

of how the graphic was captured and should be disregarded.)


## TransportVehicleMeasurements

A group item containing the measurements (length, height, weight, and width) of the transport vehicle.

### (sequence)

*The sequence of items below is*

*mandatory. A single instance is required.*



### TransportVehicleLength

*TransportVehicleLength is optional. A single instance might exist.*

The length of the transport vehicle in a valid UOM (usually meters or feet).

### TransportVehicleWidth

*TransportVehicleWidth is optional. A single instance might exist.*

The width of the transport vehicle in a valid UOM (usually meters or feet).

### TransportVehicleHeight

*TransportVehicleHeight is optional. A single instance might exist.*

The number of vehicles used to transport the goods.


### TransportVehicleWeight

*TransportVehicleWeight is optional. A single instance might exist.*

The weight of the transport vehicle in a valid UOM (usually tons, pounds, or kilograms).


## TransportVehicleText

A text field further describing the transport vehicle.



## TransportVehicleType [attribute]

Provides details on the transport vehicle. A transport vehicle has its own power and can be used to pull, carry, or tow a transport unit loaded with goods.



*This item is restricted to the following list.*

### Barge

A flat, inland waterways vessel.

### ContainerVessel

A vessel for sea transports designed to carry containers.

## **ConventionalVessel**

A vessel for sea transports, loaded/unloaded by LOLO (lift-on/lift-off method).

## **RollOnOffShip**

A vessel for sea transport, loaded/unloaded by RORO (roll-on/roll-off method).

## **SidePortVessel**

A vessel for sea transport, loaded/unloaded through side ports in the vessel side.

## **Train**

A rail-based vehicle for towing of railcars.

## **Truck**

A road vehicle for carrying, pulling or towing of transport units. Other used names are Tractor and Lorry.

## **TruckTrailer**

To be removed in Version v3r00. Use Truck instead.

## **Other**

Used for any other transport vehicles not covered by this list.


---

## **TransportVehicleWeight**

The weight of the transport vehicle in a valid UOM (usually tons, pounds, or kilograms).

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### **Value**

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### **RangeMin**

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### **RangeMax**

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)


---

## TransportVehicleWidth


The width of the transport vehicle in a valid UOM (usually meters or feet).

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



(sequence)



### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

---

## TrayColourType [attribute]

The type of tray colour.

*This item is restricted to the following list.*

### Clear

The tray colour is clear.

### Coloured

### Frosted

### Graphite

### StandardGray/Brown


The tray colour is standard gray or brown.

### White

The tray colour is white.

### Other

Another colour is used.




## TreeSpeciesGroup

A grouping element that details information used for describing tree species.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### TreeSpeciesGroupCode

*TreeSpeciesGroupCode is mandatory. A single instance is required.*

A code defining tree species or groups of tree species.

### TreeSpeciesGroupDescription

*TreeSpeciesGroupDescription is optional. Multiple instances might exist.*


A text description of the tree species group.

## TreeSpeciesGroupCode

A code defining tree species or groups of tree species.

### Agency [attribute]

*Agency is mandatory. A single instance is required.*



Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

- For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

## TreeSpeciesGroupDescription

A text description of the tree species group.



## Trim


Trim

### TrimType [attribute]

*TrimType is optional. A single instance might exist.*

Trim type

Refer to TrimType definition for any enumerations.



## (sequence)

The sequence of items below is mandatory. A single instance is required.

### **AdditionalText**

*AdditionalText* is optional. A single instance might exist.

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## TrimmedOrderType

Trimmed Order Type

This item is restricted to the following list.

<b>TrimmedOrderType</b>
type   trimmedOrderType

**Explicit**

**Implicit**


---

## TrimmedReel

Trimmed reel

### (sequence)

The sequence of items below is mandatory. A single instance is required.



### **TrimmedReelConversionCharacteristics**

*TrimmedReelConversionCharacteristics* is optional. A single instance might exist.

Conversion characteristics associated with a trimmed reel.

### **ReelPackagingCharacteristics**

*ReelPackagingCharacteristics* is optional. A single instance might exist.

A group item that lists the packaging elements describing how a reel should be packed.

## TrimmedReelConversionCharacteristics

Conversion characteristics associated with a trimmed reel.


**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### WindingDirection

*WindingDirection is optional. A single instance might exist.*

An element that indicates how the material is wound on the reel.



Refer to WindingDirection definition for any enumerations.

### TrimmedOrderType

*TrimmedOrderType is optional. A single instance might exist.*

Trimmed Order Type

Refer to TrimmedOrderType definition for any enumerations.

### MasterReelWidth

*MasterReelWidth is optional. A single instance might exist.*

The master reel width.

### ReelDiameter

*ReelDiameter is optional. A single instance might exist.*

The diameter measurement of reel excluding packaging.

### ReelLength

*ReelLength is optional. A single instance might exist.*

The total length of the paper on the reel.

### MaximumOffcut

*MaximumOffcut is optional. A single instance might exist.*

Maximum off cut.

### CoreCharacteristics


*CoreCharacteristics is optional. A single instance might exist.*

A group item that details information used to fully define a core.

### MaximumNumberOfJoins

*MaximumNumberOfJoins is optional. A single instance might exist.*

The maximum number of joins requested (permitted). Permits customers to indicate join-free reels.



## SlitReel

*SlitReel is mandatory. One instance is required, multiple instances might exist.*

The SlitReel element represents the elements associated with reel that has been slit into multiple reels.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## TrimSize

Trim size.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Length

*Length is mandatory. A single instance is required.*

The length of the object.

#### Width

*Width is mandatory. A single instance is required.*

The width of the object.

#### BookBlockBulk


*BookBlockBulk is optional. A single instance might exist.*

Book block bulk

#### SpineSize

*SpineSize is optional. A single instance might exist.*

The height of the spine.



---

## TrimType [attribute]

Trim type


*This item is restricted to the following list.*

**DET**

**PET**

**SquareEndTrim**


**Other**



---

## TwoSigmaLower

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.



### UOM [attribute]

*UOM is mandatory. A single instance is required.*


Defines the unit of measure for the value.

Refer to UOM definition for any enumerations.

---

## TwoSigmaUpper

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.



### UOM [attribute]

*UOM is mandatory. A single instance is required.*

Defines the unit of measure for the value.

Refer to UOM definition for any enumerations.

---

## UnCompletedMeasurement [attribute]

Indicates if the measuring of an item is uncompleted, i.e. if some measurement values are missing.



*This item is restricted to the following list.*

**Yes**


**No**

---

## UnevenSpacing

Uneven Spacing

### (sequence)



*The sequence of items below is mandatory. A single instance is required.*

### [Any Type]

Any type of content is permitted at this point.

## UnitCharacteristics

Unit characteristics.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### Height

Height is optional. A single instance might exist.

The height of the object.

#### Thickness

Thickness is optional. A single instance might exist.

Physical dimension of a product.

#### Width


Width is optional. A single instance might exist.

The width of the object.

#### Weight

Weight is optional. A single instance might exist.

The weight of the item.



## UnitDimension

Unit Dimension

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### Length

Length is optional. A single instance might exist.

The following approach is used in the timber/lumber related constructs.

#### Width

Width is optional. A single instance might exist.

The approach for width used in the timber/lumber related constructs.

#### Height


Height is optional. A single instance might exist.

The height of the object. (Used in wood/timber items.)

#### PiecesPerRow

PiecesPerRow is optional. A single instance might exist.

This element details the number of pieces or individual items that are to be



placed/packaged in a row within the unit. Usually used to identify the standard number of pieces in a standard packaging unit of the product.

## RowsPerUnit

*RowsPerUnit is optional. A single instance might exist.*

The number of rows of items, are to be placed/packaged within the unit. Usually used to identify the standard number of rows in a standard packaging unit of the product.

---

## UnitItem

Unit Item.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Identifier

*Identifier is optional. Multiple instances might exist.*

An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.



#### Product

*Product is optional. A single instance might exist.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

#### UnitCharacteristics

*UnitCharacteristics is optional. A single instance might exist.*

Unit characteristics.


#### Quantity

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

#### InformationalQuantity



*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## UnitReference

*UnitReference is optional. Multiple instances might exist.*

An element detailing relevant references pertaining to the Unit. The type of reference is identified by the attributes UnitReferenceType and AssignedBy.

## OtherDate


*OtherDate is optional. Multiple instances might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

---

## UnitReference

An element detailing relevant references pertaining to the Unit. The type of reference is identified by the attributes UnitReferenceType and AssignedBy.



### UnitReferenceType [attribute]

*UnitReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to UnitReferenceType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is mandatory. A single instance is required.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## UnitReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse" or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute AssignedBy will communicate the



information previously communicated in the prefix.

Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

---

## UnitsPerCarton

The number of units per box.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



---

## UOM [attribute]

Defines the unit of measure for the value.

*This item is restricted to the following list.*

### AirDryMetricTonne


A unit of measure that identifies the product as 1000 kilograms of product that has been calculated based on an accepted standard representing the contents to be 90% fibre and 10% moisture and adjusted using a moisture percentage test. The AirDryMetricTonne is calculated as  $GrossWeight \times (100 - moisture\% / 90)$

### AirDryPercent

The percentage measured at the time of production using the air dry industry standard (90% fibre, 10% moisture) therefore,  $102 \text{ AirDryPercent} = 102 \text{ AirDryPercent} / 100 * 90\% = 91.8\% \text{ fibres}$ .

### AirDryShortTon

A unit of measure that identifies the product as 2000 pounds of product that has been calculated based on an accepted standard representing the contents to be 90% fibre and 10% moisture and further adjusted using a moisture percentage test. The AirDryShortTon is calculated as  $GrossWeight \times (100 -$



moisture% / 90)

## **Bale**

The measurement value is a count of bales. A single or rectangular grouping of product

## **BoardFoot**

The measurement value is expressed in board feet.

## **BookUnit**

A copy of a book.

## **Box**

The measurement value is a count of boxes.

## **Bundle**

The measurement value is a count of bundles.

## **C-Size**

## **Celsius**

The measurement value is in Celsius temperature degrees.

## **Centimeter**

The measurement value is expressed in centimetres.

## **CentimeterPerSecond**

Centimeter per second

## **Cord**

One cord of wood equals 128 cubic feet, or a pile of wood 4 feet high, 4 feet thick and 8 feet long.

## **CubicCentimeterPerGram**

Cubic centimeter per gram

## **CubicCentimeterPerSecond**

Cubic centimeter per second

## **CubicFoot**

The measurement value is expressed in cubic feet.

## **CubicInchesPerSecond**

Cubic inches per second

## **CubicMeter**

The measurement value is expressed in cubic meter.

## **CubicMeterKilometer**

The value is expressed as a volume in CubicMeter times a distance in Kilometer, e.g. the unit price for transporting one cubicmeter of wood one kilometer.

## **CubicMeterPerKilogram**

Cubic meter per kilogram

**Cubit**

The English cubit is 18 inches long (46 cm).

**Day**

The duration of time equal to 24 hours.

**Decimeter****Degree**

Degree

**DegreesSchopperRiegler**

Degree Schopper Riegler

**DotsPerInch**

An indication of image resolution.

**Envelope**

An envelope.

**Fahrenheit**

Fahrenheit

**Foot**

The measurement value is expressed in feet.

**Gallon**

The measurement value is in gallons.

**Gauge**

A unit of measure for diameter and thickness, e.g. for a wire or flat pieces such as sheet metal, thin plastic and film stock.

**Gram**

The measurement value is expressed in grams.

**GramCentimeter****GramForce****GramPerCubicCentimeter****GramPerMeter****GramsPerSquareMeter**

The measurement value is expressed in grams per square meter (g/m<sup>2</sup>).

**Hectare**

The measurement value is expressed in hectares (10000 square meters).

**Hour**

The measurement value is expressed in hours.

**HundredBoardFeet****HundredLinealFeet****HundredPound**

The measurement value is expressed in hundreds of pounds or hundredweight.

## **HundredSquareFeet**

## **ImpressionCount**

The measurement is in number of printed impressions.

## **Inch**

The measurement value is expressed in inches.

## **JoulePerSquareMeter**

## **Kilogram**

The measurement value is expressed in kilograms.

## **KilogramForcePerSquareCentimeter**

## **KilogramForcePerCentimeter**

## **KilogramPerCubicMeter**

## **KilogramPerSquareMeter**

## **KilogramsPerDay**

The measurement value is expressed in kilograms per day.

## **KilogramsPerWeek**

The measurement value is expressed in kilograms per week.

## **Kilometer**

The measurement value is expressed in kilometres.

## **KiloNewton**

## **KiloNewtonPerMeter**

## **KiloPascal**

## **KiloWattHour**

The measurement value is expressed in kilowatt hours (KWh)

## **KnownBreaks**

Known breaks

## **Layer**

The measurement value is a count of layers (for example, the number of boxes per layer on a pallet).

## **Leaves**

Leaves

## **LinearFoot**

The measurement value is expressed in linear feet.

## **LinesPerInch**

Lines Per Inch

## **Litre**

The measurement value is expressed in litres.

## **Load**

The measurement value is a count of shipment loads.

## **Log**

A cut portion of a stem.

## **LogPile**

A pile of logs (a virtual type of package).

## **LooseVolumeItem**

A unit containing loose volume products (during transports) (a type of virtual package).

## **MagazineUnit**

A copy of a magazine.

## **Megabyte**

A unit of information equal to 1,048,576 bytes or 1024 kilobytes.

## **MegaWattHour**

The measurement value is expressed in mega watt hours (MWh).

## **Meter**

The measurement value is expressed in meters.

## **MeterPerSecond**

The measurement value is in meters per second.

## **MetricTon**

The measurement value is expressed in metric tons (in other words, in 1000-kilogram units).

## **MetricTonKilometer**

The value is expressed as a weight in MetricTon times a distance in Kilometer, e.g. the unit price for transporting one metric ton of wood one kilometer.

## **MetricTonsPerDay**

The measurement value is expressed in metric tons per day.

## **MetricTonsPerHour**

The measurement value is expressed in metric tons per hour.

## **MetricTonsPerWeek**

The measurement value is expressed in metric tons per week.

## **MicroMeterPerPascalSecond**

## **Micron**

The measurement is expressed as the number of one-millionths of a meter.

## **MilliLitersPerMinute**

## **Millimeter**

The measurement value is expressed in millimetres.

**MillimeterPerMeter**

The measurement value is expressed in millimeter per meter.

**MilliNewton**

One thousandth of a Newton.

**MilliNewtonMeter****MilliNewtonSquareMeterPerGram****Minute**

The measurement value is expressed in minutes.

**NanoMeter****Newton**

The measurement value is expressed in the unit of force needed to accelerate a mass of one kilogram one meter per second per second.

**NewtonMeterPerGram****None**

There is no unit of measure. The value is scalar.

**Package**

The measurement value is a count of packages (for example, the number of reel packages in a shipment). 32 double-wrapped reels would equal 16 packages.

**Page**

The measurement value is expressed in number of pages.

**PagesPerForm**

The measurement value is expressed in number of pages per form.

**PagesPerImpression**

The measurement value is expressed in number of pages per printed impression.

**PagesPerInch**

The measurement value is a count of the number of pages per inch.

**PalletUnit**

The measurement value is a count of pallets.

**PartsPerMillion**

The measurement value is expressed in parts per million.

**Percentage**

The measurement being communicated is a percentage.

**PerThousand**

The measurement value is expressed in parts per thousand.

**pH**

A measurement of acidity.

**Picas**

The measurement value is expressed in picas.

**Piece**

The measurement value is number of pieces.

**PixelsPerInch**

The measurement value is expressed in pixels per inch.

**Pound**

The measurement value is expressed in pounds.

**PoundForce****PoundPerCubicFoot**

The measurement value is expressed in pounds per cubic foot.

**PoundPerSixInchDiameter**

The measurement value is expressed in pounds per six inch diameter.

**PoundPerSquareInch**

The measurement value is expressed in pounds per square inch.

**PoundsPerDay**

The measurement value is expressed in pounds per day.

**PoundsPerHour**

The measurement value is expressed in pounds per hour.

**PoundsPerWeek**

The measurement value is expressed in pounds per week.

**PulpUnit**

The measurement is related to the packaging characteristic or material handling equipment for the pulp.

**Ream**

The measurement value is a count of reams.

**Reel**

The measurement value is a count of reels.

**Set**

The measurement value is a count of sets.

**Sheet**

The measurement value is a count of sheets.

**ShortTon**

The measurement value is expressed in short tons.

**ShortTonsPerDay**

The measurement value is expressed in short tons per day.

**ShortTonsPerHour**

The measurement value is expressed in short tons per hour.

## **ShortTonsPerWeek**

The measurement value is expressed short tons per week.

## **Signature**

The measurement value is the number of print signatures.

## **Skid**

The measurement value is a count of skids.

## **SquareFeet**

The measurement value is expressed in square feet.

## **SquareInch**

The measurement value is expressed in square inches.

## **SquareMeter**

The measurement value is expressed in square meters.

## **SquareMeterPerKilogram**

## **TenKilometer**

The measurement value is expressed in units of 10 kilometers, a.k.a. Swedish mile or Norwegian mile.

## **ThousandBoardFeet**

The measurement value is expressed in thousand board feet.

## **ThousandLinealFeet**

The measurement value is expressed in thousand lineal feet.

## **ThousandPieces**

The measurement value is expressed in thousand of pieces.

## **ThousandSquareCentimeters**

The measurement value is expressed in thousand square centimeters.

## **ThousandSquareFeet**

The measurement value is expressed in thousand square feet.

## **ThousandSquareInch**

The measurement value is expressed in thousand square inches.

## **Ton**

To be deprecated in version 3.0 (no date determined). Use instead MetricTon or ShortTon.

## **TonsPerHour**

To be deprecated in version 3.0 (no date determined). Use instead MetricTonsPerHour or ShortTonsPerHour.

## **Unit**

The measurement value is expressed in individual units (pieces or eaches).

## **UnknownBreaks**

The number of paper breaks, on a printing machine, that are due to unknown causes.

## Yard


The measurement value is expressed in yards.

## Year

The measurement value is expressed in number of years.

## URL

Universal Resource Locator. While typically a web address you could use this field to hold an email address.




### URLContext [attribute]

*URLContext is optional. A single instance might exist.*

The purpose of the URL.

### URLContext [attribute]

The purpose of the URL.



## Usage

The Usage element is the root element for the Usage e-Document.

The Usage e-Document is used to notify a supplier or buyer that material has been consumed within the end user's manufacturing process.

### UsageStatusType [attribute]

*UsageStatusType is mandatory. A single instance is required.*

Identifies the status of the entire Usage e-Document


Refer to UsageStatusType definition for any enumerations.

### Reissued [attribute]

*Reissued is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to Reissued definition for any enumerations.



## **Language [attribute]**

*Language is optional. A single instance might exist.*

XML has embraced 2 and 3 digit language codes through the application of an addendum to the standard.

Refer to Language definition for any enumerations.

## **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **UsageHeader**

*UsageHeader is mandatory. A single instance is required.*

Information that is common to the entire Usage e-Document.

### **UsageLineItem**

*UsageLineItem is mandatory. One instance is required, multiple instances might exist.*

The details of the Usage e-Document.

### **UsageSummary**

*UsageSummary is optional. A single instance might exist.*

The root element of the Usage e-Document.

## UsageHeader

Information that is common to the entire Usage e-Document.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### UsageNumber


*UsageNumber is mandatory. A single instance is required.*

Unique identifier assigned to each Usage document as agreed by the trading partners.

#### UsageHeaderReference

*UsageHeaderReference is optional. Multiple instances might exist.*

An element that details relevant references to the Usage Header. The content of the UsageHeaderReference is identified by the UsageReferenceType attribute.



#### UsageIssuedDate

*UsageIssuedDate is mandatory. A single instance is required.*

Identifies the Date and Time when the Usage information has been reported.

#### TransactionHistoryNumber

*TransactionHistoryNumber is optional. A single instance might exist.*

A sequential number that keeps track of the version of a document being sent by the document originator except in the case where TransactionHistoryConfirmation is used, in which case the TransactionHistoryNumber refers to the trigger transaction for which the confirmation is being sent.

#### TimePeriod

*TimePeriod is optional. A single instance might exist.*

The TimePeriod element is used to communicate a duration period of time as indicated in PeriodType.

#### EndUserParty


*EndUserParty is mandatory. A single instance is required.*

The party using, consuming, or converting the product. For example, a printer using paper reels for a print job for a publisher. The final ShipTo destination for a product is normally to the end user's facilities.

#### SupplierParty

*SupplierParty is optional. A single instance might exist.*

The organisation or business entity responsible for providing the product.



SupplierParty is also the seller of the product, if Seller is not specified as OtherParty = Seller.

## BuyerParty

*BuyerParty is mandatory. A single instance is required.*

The legal entity to which the product is sold. Also commonly referred to as the sold-to party or customer. If no OtherParty is defined as the Payer, the Buyer is the Payer.

## OtherParty

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## SenderParty

*SenderParty is optional. A single instance might exist.*

The business entity issuing the e-Document, the source of the document.

The entity responsible for the content. If the sender party has out sourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

## ReceiverParty

*ReceiverParty is optional. Multiple instances might exist.*

The business entity for whom the e-Document is intended, the destination of the document.

The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for the e-Document and not the party performing the receiving service of the electronic message.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---


## UsageHeaderReference

An element that details relevant references to the Usage Header. The content of the UsageHeaderReference is identified by the UsageReferenceType attribute.

### UsageReferenceType [attribute]

*UsageReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be



announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to UsageReferenceType definition for any enumerations.

## **AssignedBy [attribute]**

*AssignedBy is optional. A single instance might exist.*

Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.


---

## **UsageIssuedDate**

Identifies the Date and Time when the Usage information has been reported.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*



### **Date**

*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

### **Time**

*Time is optional. A single instance might exist.*

Times are treated in a standard XML fashion with a special case used to indicate a generalized "local" time. The standard XML approach to time is hh:mm:ss, hh:mm:ssZ, or hh:mm:ss±hh:mm.

hh:mm:ss±hh:mm is used to represent a time with a time zone. The time zone is communicated as the number of hours offset from the Universal Time Coordinate (UTC), a.k.a. Greenwich Mean Time.

hh:mm:ssZ indicates the time at Zulu (another name for UTC). Based on the convention described in the next bullet it will be important for users within UTC to use "Z" when communicating a time in their time zone to other users.

hh:mm:ss or hh:mm indicates in the XML standard the time at UTC however, within papiNet it is used to represent the applicable local time. Caution should be used when processing times of this nature as the papiNet approach may be in discord with other users of XML.

## UsageLineItem

The details of the Usage e-Document.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### UsageLineItemNumber

UsageLineItemNumber is mandatory. A single instance is required.

A sequential number that uniquely identifies the Usage line item.



#### UsageReference

UsageReference is optional. Multiple instances might exist.

A repeatable element that details relevant references pertaining to the Usage. The content of the UsageReference is identified by UsageReferenceType.

#### LocationParty

LocationParty is optional. A single instance might exist.

The organization or business entity where the business event took place or will take place.

#### WasteQuantity

WasteQuantity is optional. Multiple instances might exist.

The quantity of product wasted.

#### WebBreaks

WebBreaks is optional. Multiple instances might exist.

The number of web breaks.

### (choice)

[choice] is optional because of choice construct.

#### AggregatedUsageLineItem

AggregatedUsageLineItem is optional because of choice construct.


A group item that summarises item usage at the Product level or at the Product plus PurchaseOrder level. Details concerning the individual items used are not included.

#### ItemisedUsageLineItem

ItemisedUsageLineItem is optional because of choice construct.

A group item containing information that relates to an itemized amount of usage.

#### AdditionalText



*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## UsageLineItemDetail

For each ItemisedUsageLineItem there must be one or more UsageLineItemDetail. This element lists the specific product that has been consumed.

### UsageStatus [attribute]

*UsageStatus is mandatory. A single instance is required.*

The Usage Status element identifies the state of an individual item after consumption has been applied to it.

Refer to UsageStatus definition for any enumerations.

### ItemType [attribute]

*ItemType is mandatory. A single instance is required.*

Indicates the form of the item being reported as being used. Many of the ItemType(s) indicated here have a corresponding named element equivalent, which is referenced here for definition purposes.

Refer to ItemType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Identifier

*Identifier is mandatory. A single instance is required.*


An Identifier is required for packages and items (pallets, reel packages, boxes, ream items, reel items, etc). The Identifier element contains the actual item identifier code. Identifier is repeatable so more than one identifier can be communicated. For example, the printed identifier on a label may be different from the barcode printed on the label.

#### RawMaterialSet

*RawMaterialSet is optional. Multiple instances might exist.*

This identifier derived element indicates a grouping of raw materials that were used to manufacture the product.

#### Quantity



# papiNet V2R31

---

*Quantity is optional. A single instance might exist.*

The Quantity element contains attributes that provide information about the type of quantity that is being communicated, the context in which the particular quantity is to be viewed, and (if the quantity represents an adjustment) an adjustment type.

The Quantity element contains three child elements that enable you to communicate a range of values for the quantity and a target or actual value. It is at this level (Value, RangeMin, and RangeMax) that the unit of measure is specified. This permits the range to be specified in a different unit of measure than the target.

## **InformationalQuantity**

*InformationalQuantity is optional. Multiple instances might exist.*

A quantity given in a valid UOM used for information purposes only (not for calculation). For example, an ordered quantity was 100 reels as opposed to the invoice quantity of 20,000 pounds.

## **WebBreaks**

*WebBreaks is optional. Multiple instances might exist.*

The number of web breaks.

## **Product**

*Product is optional. A single instance might exist.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

## **OtherParty**

*OtherParty is optional. Multiple instances might exist.*

An organisation or business entity other than those specifically detailed within a e-Document.

## **OtherDate**

*OtherDate is optional. A single instance might exist.*

A date that may not be specifically detailed within a document (example: print date at the PurchaseOrderLineItem).

---

## **UsageLineItemNumber**

A sequential number that uniquely identifies the Usage line item.

<b>UsageLineItemNumber</b>	
type	lineNumberType

---

## **UsageNumber**


Unique identifier assigned to each Usage document as agreed by the trading partners.

<b>UsageNumber</b>	
type	s30

---

## UsageReference

A repeatable element that details relevant references pertaining to the Usage. The content of the UsageReference is identified by UsageReferenceType.



### UsageReferenceType [attribute]

*UsageReferenceType is mandatory. A single instance is required.*

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.

Refer to UsageReferenceType definition for any enumerations.

### AssignedBy [attribute]

*AssignedBy is optional. A single instance might exist.*


Identifies the type of party that has assigned the associated item, e.g. a reference of type OrderNumber.

Refer to AssignedBy for any enumerations.

---

## UsageReferenceType [attribute]

Provides a contextual explanation of the specific reference identifier. Many items are currently prefixed by "Buyer", "Forwarder", "Manufacturer", "Mill", "Seller", "Supplier", "Warehouse", or "Vendor". Check for an existing non-prefixed version and use the non-prefixed version instead. In the (yet to be announced release date) version 3.0 the prefixed versions will be removed. Instead the attribute @AssignedBy will communicate the information previously communicated in the prefix.




Refer to the [referenceType](#) entry for the list of enumerations and their definitions.

---

## UsageStatus [attribute]

The Usage Status element identifies the state of an individual item after consumption has been applied to it.

*This item is restricted to the following list.*



### Consumed

Indicates that the entire item has been consumed.

### MachineReject

Indicates that the item has been rejected from the production machine

## **StrippedButt**

Indicates that this item has been prepped for consumption but has not been used in the manufacturing process.

## **UsableButt**

Indicates that a partial amount of a reel product has been consumed and the remainder is useable.

## **UsablePallet**

Indicates that a partial amount of a pallet product has been consumed and the remainder us useable.

## **UnusableButt**

Indicates that a partial amount of a reel product has been consumed and the remainder is not useable.

## **UnusablePallet**

Indicates that a partial amount of a pallet product has been consumed and the remainder is not useable.

---

## **UsageStatusType [attribute]**

Identifies the status of the entire Usage e-Document

*This item is restricted to the following list.*

### **Cancelled**


The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-Document.

### **Original**

The supplied information is the first version of that information.

### **Replaced**

The supplied information is replacing earlier supplied information. The receiver should revalidate the information in their system based upon the entire information received.




## UsageSummary

The root element of the Usage e-Document.

### (sequence)

The sequence of items below is mandatory. A single instance is required.



### TotalNumberOfLineItems

TotalNumberOfLineItems is optional. A single instance might exist.

The total number of individual line items in the document, regardless of the status or type.

### (sequence)

The sequence of items below is optional. Multiple instances might exist.

### TotalQuantity

TotalQuantity is mandatory. A single instance is required.

The total quantity of similar items in the e-Document. TotalQuantity is primarily used in the summary section of documents where it is repeatable to permit totaling for different units of measure.

### TotalInformationalQuantity

TotalInformationalQuantity is optional. Multiple instances might exist.

A quantity that is used to communicate related information about the parent element. This element represents a total that is derived from individual line items.

### TermsAndDisclaimers

TermsAndDisclaimers is optional. Multiple instances might exist.


An element that contains legal information with an indication of what the Language is.

## ValidityPeriod

The validity period for a specific item, e.g. the validity period for an e-Document.

### (sequence)

The sequence of items below is mandatory. A single instance is required.



### DateTimeFrom

DateTimeFrom is optional. A single instance might exist.

The start or beginning Date and Time of a date range.

### DateTimeTo

DateTimeTo is optional. A single instance might exist.

The ending Date and Time of a date/time range.

---

## Value


A numeric value expressed in the unit of measure (UOM).

### UOM [attribute]

*UOM is mandatory. A single instance is required.*

Defines the unit of measure for the value.

Refer to UOM definition for any enumerations.




---

## VarianceType [attribute]

Defines the type of difference that the GoodsReceiptPackage has from the information on the DeliveryMessage

*This item is restricted to the following list.*



### DifferingWeights

The physical item was weighed and the weight is different from the DeliveryMessage weight.

### NotReceived

The physical item that was specified on the DeliveryMessage was not received.

### ReceivedNotSpecified

The physical item was received but was not on the DeliveryMessage

## VideoCassette

Video cassette information.

### VideoFormatType [attribute]

*VideoFormatType is optional. A single instance might exist.*

The type of video format.

Refer to VideoFormatType definition for any enumerations.

### TrackType [attribute]

*TrackType is optional. A single instance might exist.*

The type of track

Refer to TrackType definition for any enumerations.

### Tabs [attribute]

*Tabs is optional. A single instance might exist.*

The type of tabs

Refer to Tabs definition for any enumerations.

### VideoCassetteCaseType [attribute]

*VideoCassetteCaseType is optional. A single instance might exist.*

The type of video cassette case.

Refer to VideoCassetteCaseType definition for any enumerations.

### AssemblyType [attribute]

*AssemblyType is optional. A single instance might exist.*

Assembly type

Refer to AssemblyType definition for any enumerations.

### WrapType [attribute]

*WrapType is optional. A single instance might exist.*


Communicates the type of material used to wrap the product.

Refer to WrapType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### SequenceNumber



# papiNet V2R31

---

*SequenceNumber is optional. A single instance might exist.*

## **ShellColour**

*ShellColour is optional. A single instance might exist.*

Shell colour

## **TapeDescription**

*TapeDescription is optional. A single instance might exist.*

Tape description

## **MediaLength**

*MediaLength is optional. A single instance might exist.*

Media length

## **CassetteLabelCharacteristics**

*CassetteLabelCharacteristics is optional.*

Cassette label characteristics

## **InsertReference**

*InsertReference is optional. Multiple instances might exist.*

Insert reference

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **VideoCassetteCaseType [attribute]**

The type of video cassette case.

*This item is restricted to the following list.*

**HardPlastic**

**VacuumAlbum**

**SleeveBottomLoaded**

**SleeveSideLoaded**



---

## **VideoFormatType [attribute]**

The type of video format.

*This item is restricted to the following list.*

**VHS**

Video Home System

**PCL**




## VirginFibre

Virgin Fibre

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### TimberCharacteristics

*TimberCharacteristics is mandatory. A single instance is required.*

Timber characteristics

### (choice)

*[choice] is optional because of choice construct.*

### Log

*Log is optional because of choice construct.*

Log information

### Chip

*Chip is optional because of choice construct.*

Chip information.

## Viscosity

Viscosity

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax


*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.



## SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

## TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

## TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.


---

## Wall

Defines parts and complete wall systems.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### (choice)

*[choice] is optional because of choice construct.*

#### WallPanel

*WallPanel is optional because of choice construct.*

Material used for wall surface.

#### WallPackage


*WallPackage is optional because of choice construct.*

Package including parts to build a wall.

---


## WallPackage

Package including parts to build a wall.



## WallPanel

Material used for wall surface.



---

## WasteImpressions

The number of bad revolutions produced on a printing unit.

WasteImpressions	
type	nni4

---

## WasteQuantity

The quantity of product wasted.

### WasteType [attribute]

*WasteType is mandatory. A single instance is required.*

An indication of where in the process the waste has taken place.

Refer to WasteType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



---

## WasteType [attribute]

An indication of where in the process the waste has taken place.

*This item is restricted to the following list.*

**Binding**

**Core**

**MakeReady**

**Running**

**Strip**

WasteType	
attribute	
type	wasteType


WrapCore  
Wrapper

## Watermark

Watermark information

### (sequence)

The sequence of items below is mandatory. A single instance is required.



### WatermarkCode

WatermarkCode is mandatory. A single instance is required.

The code representing the watermark on the paper.

### WatermarkDescription

WatermarkDescription is optional. Multiple instances might exist.


Watermark Description

## WatermarkCode

The code representing the watermark on the paper.

### Agency [attribute]

Agency is mandatory. A single instance is required.



Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.


For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

## WatermarkDescription

Watermark Description



## Webbing

The webbing that is used in the printing process.

Webbing	
type	s30

## WebBreak

Separation of the paper web during the printing process causing the operator to stop and rethread the press.

If the ConcernIndicatorType is "Y" then a defect cause must be given.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### WebBreakCause

*WebBreakCause is mandatory. A single instance is required.*

A group element that contains information that describes the cause of a web break.

#### PressBreakLocation

*PressBreakLocation is optional. Multiple instances might exist.*

The specific location identified within a printing press.

#### ReelBreakDiameter

*ReelBreakDiameter is mandatory. A single instance is required.*

The diameter of a reel at which the web break occurred. This is measured from the core to outside diameter.

#### WebBreakDate


*WebBreakDate is optional. A single instance might exist.*

The date of the web break.

#### MachineDownTime

*MachineDownTime is optional. A single instance might exist.*

The length of loss production time that a machine experienced due to malfunction regardless of cause.



## WebBreakCause

A group element that contains information that describes the cause of a web break.

### WebBreakCauseType [attribute]

*WebBreakCauseType is optional. A single instance might exist.*

Web Break Cause Type

Refer to WebBreakCauseType definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### WebBreakCauseCode


*WebBreakCauseCode is optional. A single instance might exist.*

Codes pertaining to the break supplied by the User.

#### WebBreakDescription

*WebBreakDescription is optional. Multiple instances might exist.*

Description of the web break



## WebBreakCauseAgency [attribute]

WebBreakCauseAgency

*This item is restricted to the following list.*

### AFPA

American Forest and Paper Association.

### ANSI

American National Standards Institute.

### APPITA

Technical Association of the Australian and NZ Pulp and Paper Industry

### ATA

ATA (American Truckers Association)

### BISAC

Book Industry Study Group


### Bowker

The agency that issues the StandardAddressNumber (www.bowker.com).

### BSI

British Standards Institute (refer to bsi-global.com for more information).

### Buyer



The buyer has defined the codes used in the particular element of the transaction. Care must be used when using this agency to assure that the recipient of the e-Document understands what is being communicated. (Not to be used for logistics buyer, see LogisticsBuyer.)

## **Carrier**

The carrier has defined the codes used in the particular element of the transaction. Care must be used when using this agency to assure that the recipient of the e-Document understands what is being communicated.

## **CCTI**

Composite Can and Tube Institute

## **CEN**

European Committee for Standardisation (<http://www.cenorm.be>)

## **CEPI**

Confederation of European Paper Industries.

## **CoSe**

Agency for the the wood processing industry. ([www.commonsense.at](http://www.commonsense.at))

## **Customs**

Any customs agency.

## **DUNS**

Dun & Bradstreet.

## **EAN**

European Article Numbering Agency.

## **ECTA-EPCA-CEFIC**

European Chemical Transport Association, European Petrochemical Association, European Chemical Council. Information about the joint guidelines developed by these agencies can be found at [www.ecta.be](http://www.ecta.be).

## **EndUser**

The end-user has defined the codes used in the particular element of the transaction. Care must be used when using this agency to assure that the recipient of the e-Document understands what is being communicated

## **FINFO**

Article numbering agency and system in some Nordic countries for all building products. ([www.finno.se](http://www.finno.se))

## **Forwarder**

The OtherParty indicated by party type "Forwarder" or when communicating OrderStatus the party indicated by ForwarderParty.

## **FSC**

Forest Stewardship Council

## **GCA**

Graphic Communications Association. (This agency now calls itself

IDEAlliance.)

## **GCA-CCTI**

The GCA and CCTI combined coding

## **GOST**

Russian federal agency on technical regulating and metrology  
(<http://www.gost.ru>)

## **IFRA**

INCA FIEJ Research Association (Technical Research and Consulting Association for the Newspaper Industry).

## **Intrastat**

The agency responsible for collecting statistics on the physical trade of goods between the members of the EU.

## **ISO**

International Organisation for Standardisation.

## **ISRI**

Institute of Scrap Recycling Industries

## **LogisticsBuyer**

The buyer of the logistics service has defined the codes used in the particular element of the transaction. Care must be used when using this agency to assure that the recipient of the e-Document understands what is being communicated.

## **LogisticsSeller**

The seller of the logistics service has defined the codes used in the particular element of the transaction. Care must be used when using this agency to assure that the recipient of the e-Document understands what is being communicated.

## **LogisticsSupplier**

The supplier of the logistics service has defined the codes used in the particular element of the transaction. Care must be used when using this agency to assure that the recipient of the e-Document understands what is being communicated.

## **Mill**

The OtherParty indicated by party type "Mill" or when available the party indicated by MillParty.

## **NOBB**

Norwegian Building Products database, (Norsk ByggvareBase)

## **NMFTA**

National Motor Freight Traffic Association (NMFTA)

## **NPTA**

National Paper Trade Association.

## **Ondule**

European Association of Corrugated Base Papers Manufacturers (actually Óndule).

## **PEFC**

[www.pefc.org](http://www.pefc.org)

## **PMS**

Pantone Matching System is a colour matching system that is widely used in the book industry. See [www.pantone.com](http://www.pantone.com) for more information.

## **PPPC**

Pulp and Paper Products Council

## **Publisher**

The person, company or organization responsible for placing a book, journal, or other publication on the market (as opposed to the printer or bookseller); also referred to as the "buyer".

## **RASI**

Article numbering agency and system in Finland for building products. ([www.rasi.fi](http://www.rasi.fi))

## **RevenueCanada**

Canadian Revenue Agency. See [www.cra.gc.ca](http://www.cra.gc.ca)

## **RVR**

Agency maintaining codes for the German wood supply segment. RVR is the abbreviation for "RahmenVereinbarung für den Rohholzhandel in Deutschland". ([www.rvr-deutschland.de](http://www.rvr-deutschland.de)).

## **SD**

Agency maintaining codes for the Norwegian wood supply segment ([www.skogdata.no](http://www.skogdata.no)).

## **SDC**

Agency maintaining codes for the Swedish wood supply segment ([www.sdc.se](http://www.sdc.se)).

## **Seller**

The seller of the product has defined the codes used in the particular element of the transaction. Care must be used when using this agency to assure that the recipient of the e-Document understands what is being communicated. (Not to be used for logistics seller, see LogisticsSeller.)

## **Supplier**

The supplier has defined the codes used in the particular element of the transaction. Care must be used when using this agency to assure that the recipient of the e-Document understands what is being communicated. (Not to be used for logistics supplier, see LogisticsSupplier.)

## **TAPPI**

Technical Association for the Paper and Pulp Industry

## **UCC**

The Uniform Code Council.

## **UIC**

International Union of Railways. (<http://www.uic.org>)  
(Union Internationale des Chemins de fer)

## **UN/ECE**

The United Nations – Economic Commission for Europe

## **WarehouseOperator**

## **WCO**

World Customs Organization (refer to [wcoomd.org](http://wcoomd.org) for more information).

## **XBITS**

XML Book Industry Transaction Standards

## **Other**


Used when the agency responsible for a coding system is not defined in the attribute list, or there is no agency responsible for the codes used.

---

## **WebBreakCauseCode**

Codes pertaining to the break supplied by the User.

## **WebBreakCauseAgency** **[attribute]**



*WebBreakCauseAgency is mandatory. A single instance is required.*

WebBreakCauseAgency

Refer to WebBreakCauseAgency definition for any enumerations.

---

## **WebBreakCauseType [attribute]**

Web Break Cause Type

*This item is restricted to the following list.*

**BaggyRoll**

**CalendarCut**

**CoatingScuffBack**

**Detector**

**FlatSpots**


**GlueOnRoll**

**HairCut**

**InkFellOnWeb**

**KnifeCut**

**LooseCore**



MillSplice  
MissedPaste  
PasterJamFolder  
RibbonOutFolder  
ScorchOut  
ScrapInRoll  
SlimeHole  
SlitterFoldOver  
SlitterNicks  
StartOrStop  
StuckWeb  
Telescoped  
TensionWrinklesPaste  
Unknown  
WaterFellOnWeb  
WinderBurst  
WinderWrinkles


---

## WebBreakDate

The date of the web break.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Date


*Date is mandatory. A single instance is required.*

A group element that contains the specification of Year, Month, and Day.

---

## WebBreakDescription

Description of the web break



## WebBreaks


The number of web breaks.

### WebBreakType [attribute]

*WebBreakType is mandatory. A single instance is required.*

An indication of the cause of the paper break.

Refer to WebBreakType definition for any enumerations.



### ReasonCode [attribute]

*ReasonCode is optional. A single instance might exist.*

Free-form text providing the Reason Code for the item. An Agency attribute may exist at the same level as this attribute to provide an indication of the nature of the text.

### Agency [attribute]

*Agency is optional. A single instance might exist.*

Describes the agency maintaining the list of codes. To be included in this list the agency must be a recognized standards body or industry organisation.

For the element that owns this attribute.

For another attribute in the list of attributes associated with the parent element.

Refer to Agency definition for any enumerations.

## WebBreakType [attribute]


An indication of the cause of the paper break.

*This item is restricted to the following list.*

**MachineCaused**

**PaperCaused**

**Unknown**




## WebConcerns

A grouping element that contains the information about a web break.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**WebBreak**



# papiNet V2R31

*WebBreak is mandatory. A single instance is required.*

Separation of the paper web during the printing process causing the operator to stop and rethread the press.

If the ConcernIndicatorType is "Y" then a defect cause must be given.

## **AdditionalText**

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## **WebConfiguration**

The way the web runs through the press.

<b>WebConfiguration</b>
type s30

---

## **Week**

A field defining the week number of the calendar year. ISO 8601 is used as the basis for this element, "Week 01 of a year is the first week that has the Thursday in this year, which is equivalent to the week that contains the fourth day of January."

<b>Week</b>
type weekType

---

## **Weight**

The weight of the item.

### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

#### **Value**

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### **RangeMin**


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### **RangeMax**

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## Whiteness

A group item used to communicate degree of whiteness target or test value according to a particular TestMethod.

### TestMethod [attribute]

*TestMethod is optional. A single instance might exist.*

The method used to determine the results of the test under consideration.

### TestAgency [attribute]

*TestAgency is optional. A single instance might exist.*

The agency that has set the parameters for the testing

Refer to TestAgency definition for any enumerations.

### SampleType [attribute]

*SampleType is optional. A single instance might exist.*

Communicates how sampling was done to measure the product characteristics.

Refer to SampleType definition for any enumerations.

### ResultSource [attribute]

*ResultSource is optional. A single instance might exist.*

Used to define the data source of the specified test

Refer to ResultSource definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*


The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation



*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

### SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

### TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

### TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.


## Width

The approach for width used in the timber/lumber related constructs.

### ActualNominal [attribute]

*ActualNominal is optional. A single instance might exist.*

Indicates the



measurement approach used to communicate the dimensions of the individual pieces.

Refer to ActualNominal definition for any enumerations.

### WithGrain [attribute]

*WithGrain is optional. A single instance might exist.*

Either "Yes" or "No".

Refer to WithGrain definition for any enumerations.

### (choice)

*[choice] is optional because of choice construct.*


#### Value

*Value is optional because of choice construct.*

A numeric value expressed in the unit of measure (UOM).

#### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



## RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

## RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## AdditionalText

*AdditionalText is optional because of choice construct.*


A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## Width

The approach for width used in the timber/lumber related constructs.

### ActualNominal [attribute]



*ActualNominal is optional. A single instance might exist.*

Indicates the measurement approach used to communicate the dimensions of the individual pieces.

Refer to ActualNominal definition for any enumerations.

### (choice)

*[choice] is optional because of choice construct.*

#### Value

*Value is optional because of choice construct.*

A numeric value expressed in the unit of measure (UOM).

#### (sequence)

*The sequence of items below is mandatory. A single instance is required.*


#### RangeMin

*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*



The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)

## Width

The width of the object.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### Value

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### RangeMin


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

#### RangeMax

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## WindingDirection

An element that indicates how the material is wound on the reel.

*This item is restricted to the following list.*



### FaceIn

The face of the label is wound on the inside of the reel.

### FaceOut

The face of the label is wound on the outside of the reel.

### WireSideIn

When someone looks at a finished reel, the wire side of the sheet is facing the core.

### WireSideOut

When someone looks at a finished reel, the wire side of the sheet is facing away from the core.

### Any

Any approach to winding the reel is acceptable.


## WireCoating [attribute]

Wire Coating

*This item is restricted to the following list.*

**Yes**

**No**



## WireGauge

Wire Gauge

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**Value**

*Value is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

**RangeMin**


*RangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the Measurement that is the parent of this element.

**RangeMax**

*RangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the Measurement that is the parent of this element. Some elements use the RangeMax element with an extended list of unit of measures. (Note: the red colour in the picture is an artifact of how the graphic was captured and should be disregarded.)



## WireMaterial

Wire Material

**WireCoating [attribute]**

*WireCoating is optional. A single instance might exist.*


Wire Coating

Refer to WireCoating definition for any enumerations.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**WireGauge**



*WireGauge is mandatory. A single instance is required.*

Wire Gauge

## WithGrain [attribute]

Either "Yes" or "No".

*This item is restricted to the following list.*

**Yes**


**No**



## WoodBasedPanelGrade

### Face [attribute]

*Face is optional. A single instance might exist.*



Used to describe which side (or face) of the product that the grade is applicable to.

Refer to Face definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### SpanRating

*SpanRating is optional. A single instance might exist.*

Span Rating according to NIST standards and indicated on grade stamp.

Refer to SpanRating definition for any enumerations.

#### StrengthGroup

*StrengthGroup is optional. A single instance might exist.*

As defined in the NIST standard, an additional classification of panel strength.


Refer to StrengthGroup definition for any enumerations.

## WoodItem

Group element containing elements describing a wood industry product.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*



### Product

*Product is optional. A single instance might exist.*

Product is a group item defining the article and its characteristics. Product is used to specify product characteristics organized by ProductIdentifier, ProductDescription, and Classification. Book Manufacturing, Label Stock, Paper, Pulp, Recovered Paper, Wood Products, and Virgin Fibre market segments have defined their product characteristics and conversion features for implementation in papiNet.

### PackagingInformation

*PackagingInformation is optional. A single instance might exist.*

Group element construct used to all information associated with the packaging of a product. Measurements, package ID, label, stencil, band, pallet and wrap characteristics may all be detailed.

### ProductSummary

*ProductSummary is optional. A single instance might exist.*


Group of elements to provide summary information on product level.

### LengthSpecification

*LengthSpecification is optional. Multiple instances might exist.*

Length specification of the wood product.

**WoodPanelCharacteristics**



**OrientationWithFaceWoodPanelGrain [attribute]**

*OrientationWithFaceWoodPanelGrain is mandatory. A single instance is required.*

Either "Yes" or "No".

Refer to OrientationWithFaceWoodPanelGrain definition for any enumerations.

**(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

**WoodPanelSpecies**

*WoodPanelSpecies is optional. Multiple instances might exist.*

Characteristics of the lumber used in the item.

**PlywoodPlyGrade**

*PlywoodPlyGrade is optional. A single instance might exist.*

Defines the grade of one ply, used with Agency to specify the grading agency.

**WoodPanelManufacturingMethod**

*WoodPanelManufacturingMethod is optional. A single instance might exist.*

The manufacturing method for the wood panels.

Refer to WoodPanelManufacturingMethod definition for any enumerations.

**Thickness**

*Thickness is optional.*

Physical dimension of a product.

**Width**

*Width is optional.*

The width of the object.

## Length

*Length is optional.*

The length of the object.

## AdditionalText

*AdditionalText is optional. Multiple instances might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

---

## WoodPanelManufacturingMethod

The manufacturing method for the wood panels.

<b>WoodPanelManufacturingMethod</b>
<a href="#">type</a> woodPanelManufacturingMethodType

## WoodPanelProducts

Characteristics of wood panelling products.

### (sequence)

The sequence of items below is mandatory. A single instance is required.

#### WoodBasedPanelGrade

WoodBasedPanelGrade is optional. A single instance might exist.

#### WoodPanelSpecies

WoodPanelSpecies is optional. Multiple instances might exist.

Characteristics of the lumber used in the item.

#### Thickness

Thickness is optional.

Physical dimension of a product.

#### Width

Width is optional.

The width of the object.

#### Length

Length is optional.

The length of the object.

#### PlywoodLayupStructure

PlywoodLayupStructure is optional. A single instance might exist.

#### Edge

Edge is optional.

Describes the finishing of the edge of the board.

#### Side

Side is optional.

The structure defines the features of a panel's side. An attribute of side element indicates which side (either top or bottom the child elements refer to).

#### PressureTreatment


PressureTreatment is optional. A single instance might exist.

Method and parameter values of pressure treatment.

#### FireTreatment

FireTreatment is optional. A single instance might exist.

Fire treatment



## Supplemental

*Supplemental is optional. Multiple instances might exist.*

Supplemental

## Brand

*Brand is optional. A single instance might exist.*

Specifies a brand or trade name of wrapping material to be used when wrapping the product.

## GradeAgency

*GradeAgency is optional. A single instance might exist.*

North American structural panel grading agencies. Defines the governing organisation of the grading scheme employed.

Note: There is a GradeAgency attribute, as well.

Refer to GradeAgency definition for any enumerations.

## GradeStamp

*GradeStamp is optional. A single instance might exist.*

Grade stamp information

## ClassIdentifier

*ClassIdentifier is optional. A single instance might exist.*

Standard used for product identification.

## LabelCharacteristics

*LabelCharacteristics is optional. Multiple instances might exist.*

A group item that organises the labeling information.

## StencilCharacteristics

*StencilCharacteristics is optional. Multiple instances might exist.*

A group element specifying attributes of a stencil to be applied to an item, and optional text.

---

## WoodPanelSpecies

Characteristics of the lumber used in the item.

### SpeciesType [attribute]


*SpeciesType is optional. A single instance might exist.*

Defines the species or mix of species comprising the product.

Refer to SpeciesType definition for any enumerations.

### SpeciesOrigin [attribute]

*SpeciesOrigin is optional. A single instance might exist.*



# papiNet V2R31

The country of origin of the species employed in manufacture of the product.  
Refer to SpeciesOrigin definition for any enumerations.

## SpeciesAgency [attribute]

*SpeciesAgency is optional. A single instance might exist.*

Defines the governing organisation of the scheme employed in determining the species of the product.

Refer to SpeciesAgency definition for any enumerations.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

### SpeciesCode

*SpeciesCode is optional. A single instance might exist.*

Species Code

### AdditionalText

*AdditionalText is optional. A single instance might exist.*

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

## WoodProducts


A grouping element for all wood products.

## (sequence)

*The sequence of items below is mandatory. A single instance is required.*

## (choice)

*[choice] is optional because of choice construct.*



### WoodTimbersDimensionalLumberBoards

*WoodTimbersDimensionalLumberBoards is optional because of choice construct.*

A grouping element that contains the various types of dimensional lumber.

### RoofingSidingDeckingFencing

*RoofingSidingDeckingFencing is optional because of choice construct.*

A grouping element that contains the timber/lumber products that are used in roofing, siding, decking, or fencing.

## **CompositeAndVeneerWoodPanels**

*CompositeAndVeneerWoodPanels is optional because of choice construct.*

A grouping element that contains the timber/lumber products that comprise composite and veneer wood panels.

## **ConstructionPackagesAndPreFabPanels**

*ConstructionPackagesAndPreFabPanels is optional because of choice construct.*

A grouping element that contains the timber/lumber products that comprise construction packages and pre-fabricated panels.

## **Millwork**

*Millwork is optional because of choice construct.*

A placeholder for the further definition of millwork items.

## **Gypsum**

*Gypsum is optional because of choice construct.*

A placeholder for further definition of gypsum items.

## **ProofInformationalQuantity**

*ProofInformationalQuantity is optional. Multiple instances might exist.*

ProofInformationalQuantity

## **SuppliedComponentInformation**

*SuppliedComponentInformation is optional. Multiple instances might exist.*

Information about components supplied by the publisher to the vendor i.e. paper supplied to the print vendor or jackets supplied to the bind vendor.

## **SafetyAndEnvironmentalInformation**


*SafetyAndEnvironmentalInformation is optional. Multiple instances might exist.*

Name of certification type, if any, on the goods (For example, FSC, PEFC). SafetyAndEnvironmental needs a value or measurement to communicate the percentage of the product is certified (for example, 75% is certified by the indicated agency).

---

## **WoodTimbersDimensionalLumberBoards**

A grouping element that contains the various types of dimensional lumber.



### **(sequence)**

*The sequence of items below is mandatory. A single instance is required.*

### **(choice)**

*[choice] is optional because of choice construct.*

### **SoftwoodLumber**

*SoftwoodLumber is optional because of choice construct.*

Product structure for solid wood products made of softwood

## HardwoodLumber

*HardwoodLumber is optional because of choice construct.*

Product structure for solid wood products made of hardwood.

## Wrap

A group item that organises wrapping detail information.

### WrapType [attribute]

*WrapType is optional. A single instance might exist.*

Communicates the type of material used to wrap the product.

Refer to WrapType definition for any enumerations.

### WrapProperties [attribute]

*WrapProperties is optional. A single instance might exist.*

Communicates the nature of the wrap that is used to package the product

Refer to WrapProperties definition for any enumerations.

### WrapLocation [attribute]

*WrapLocation is optional. A single instance might exist.*

Wrap Location

Refer to WrapLocation definition for any enumerations.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### NumberOfWraps


*NumberOfWraps is optional. A single instance might exist.*

The number of turns of wrapping material to be applied to the package.

#### Brand

*Brand is optional. A single instance might exist.*

Specifies a brand or trade name of wrapping material to be used when wrapping the product.



---


## WrapCharacteristics

A group element that contains elements that describe the manner in which the item is wrapped.

### (sequence)

*The sequence of items*

*below is mandatory. A single instance is required.*



### PackagesPerWrap

*PackagesPerWrap is mandatory. A single instance is required.*

The number of packages wrapped together.

### Wrap

*Wrap is mandatory. One instance is required, multiple instances might exist.*

A group item that organises wrapping detail information.

---

## WrapLocation [attribute]

Wrap Location

*This item is restricted to the following list.*

**None**

**Entire**

Indicates that the entire item (box, pallet, etc.) is wrapped.

**Top**

**Bottom**

**FiveSides**

**TopAndEnds**

**Ends**

**LongSides**



---

## WrapProperties [attribute]

Communicates the nature of the wrap that is used to package the product

*This item is restricted to the following list.*

**Bleached**

the wrapping has been bleached using one of the methods described in the data type bleachingProcess.

**Unbleached**

the wrapping has not been bleached

**MoistureBarrier**

the wrapping provides a barrier to moisture.

**Pulpable**



the wrapping can be blended with pulp and reused.

---

## WrapType [attribute]

Communicates the type of material used to wrap the product.

*This item is restricted to the following list.*

**Cardboard**

**Chipboard**

**Fibreboard**

**KraftPaper**

Kraft paper is used to wrap the product.

**Laminatedboard**

**Metal**

**None**

The product is not wrapped

**Paper**

**Peelercores**

**Plastic**

**PlasticBag**

The product is wrapped in a plastic bag.

**Plywood**

**Self**

The product is wrapped using the same material that is contained within.

**ShrinkWrap**

The product is wrapped using shrink wrap material.

**StretchWrap**

The product is wrapped using stretch wrap material.

**Timber**

attribute
<b>WrapType</b>
type   wrapType

---

## Year

Identifies the year number when communicating a calendar date.

<b>Year</b>
type   gYear

## Yellow

The Yellow component of a colour.

### (sequence)

*The sequence of items below is mandatory. A single instance is required.*

#### DetailValue

*DetailValue is mandatory. A single instance is required.*

A numeric value expressed in the unit of measure (UOM).

#### DetailRangeMin

*DetailRangeMin is optional. A single instance might exist.*

The minimum value (lower boundary) allowed for the DetailValue that is the parent of this element.

#### DetailRangeMax

*DetailRangeMax is optional. A single instance might exist.*

The maximum value (upper boundary) allowed for the DetailValue that is the parent of this element.

#### StandardDeviation

*StandardDeviation is optional. A single instance might exist.*

A statistic used as a measure of dispersion in a distribution.

#### SampleSize

*SampleSize is optional. A single instance might exist.*

The number of samples used to determine the product characteristic in question.

#### TwoSigmaLower

*TwoSigmaLower is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the lower side of the standard deviation.

#### TwoSigmaUpper

*TwoSigmaUpper is optional. A single instance might exist.*

Two sigma (a measure of dispersion associated with standard deviation) on the upper side of the standard deviation.

