



papiNet

Calendar

papiNet Standard - Version 2.31

Documentation

**Global Standard for the Paper and Forest
Products Supply Chain**

Build V2R31_20240321

Date 2024-04-14

Production Release

Calendar

papiNet Standard - Version 2.31

Copyright

Copyright 2000 - 2024 Papinet SNC ("papiNet") the "Copyright Owner". All rights reserved by the Copyright Owner under the laws of the United States, Belgium, the European Economic Community, and all states, domestic and foreign. This document may be downloaded and copied provided that all copies retain and display the copyright and any other proprietary notices contained in this document. This document may not be sold, modified, edited, or taken out of context such that it creates a false or misleading statement or impression as to the purpose or use of the papiNet specification, which is an open standard. Use of this Standard, in accord with the foregoing limited permission, shall not create for the user any rights in or to the copyright, which rights are exclusively reserved to the Copyright Owner.

papiNet, and the members of all papiNet Groups (collectively and individually, "Presenters") make no representations or warranties, express or implied, including, but not limited to, warranties of merchantability, fitness for a particular purpose, title, or non-infringement. The presenters do not make any representation or warranty that the contents of this document are free from error, suitable for any purpose of any user, or that implementation of such contents will not infringe any third party patents, copyrights, trademarks or other rights. By making use of this document, the user assumes all risks and waives all claims against Presenters.

In no event shall Presenters be liable to user (or other person) for direct, indirect, special or consequential damages arising from or related to any use of this document, including, without limitation, lost profits, business interruption, loss of programs, or other data on your information handling system even if Presenters are expressly advised of the possibility of such damages.

Use of Documents in papiNet Implementations

Documents may be used as templates for a papiNet implementation. The Presenters grant the right to modify and edit them to fit an actual implementation project provided all copies display the copyright and any other proprietary notices contained in this document. Such modified documents must not be distributed beyond the trading partners implementing or maintaining a papiNet connection.

Calendar

papiNet Standard - Version 2.31

Table of Contents

Copyright	2
Use of Documents in papiNet Implementations	2
Table of Contents	3
Calendar Documentation	4
Calendar e-Document Overview.....	4
Calendar Scope	4
Business Rules for Calendar	4
Understanding the Diagrams and Content	5
Calendar Root Element.....	7
Calendar.....	7
Primary Elements	9
CalendarHeader.....	9
CalendarSequence	10
CalendarEntry	11
Calendar Business Scenarios.....	13
Calendar Scenario Listing.....	13
Scenario A	13
Scenario B	13
Scenario C	14
Scenario D1	15
Scenario D2	15
Scenario D3	16

Calendar

papiNet Standard - Version 2.31

Calendar Documentation

Calendar e-Document Overview

The Calendar e-Document is intended to communicate opening times or other details for a location or locations.

The initial Calendar e-Document defines the opening times and/or contingencies for the given period. Further Calendar documents can update, or specify exceptions to for a given day or period.

Calendar Scope

This e-Document is used by consignor or consignee to forward information on opening times or contingencies of locations like warehouses, mills, plants etc. Typically, applicable to road and rail but may also apply to other transportation modes.

- communicate opening times (multiple for a weekday) for a certain location
- communicate contingencies at a certain location with slot times and quantity of contingent on lorry or tonnage base
- specify the validity time range of the calendar
- communicate updates on opening times or contingencies

Business Rules for Calendar

The following tables list the business rules that apply to each Calendar e-Document type. There are no general rules that apply to both e-Document types.

General Business Rules

Identifier	Business Rule
CALENDAR_001	If CalendarEntryPeriod specifies a weekday, then DateTimeRange specifies the date range within which the given times and contingencies apply to the weekday.
CALENDAR_002	Opening times and contingencies in an original Calendar e-Document have to be explicitly defined. The default is that no contingencies are available.
CALENDAR_003	A Calendar e-Document with CalendarStatus = "Amended" can only contain CalendarEntry entries for days or ranges that need to be changed.
CALENDAR_004	A Calendar e-Document with CalendarStatus = "Amended" has to contain all slots for a given day or range in the specified CalendarEntry entries:

Calendar papiNet Standard - Version 2.31

	<ul style="list-style-type: none"> • Set TimeSlotAvailability = "No" for the contingencies or opening times that have been removed • Set TimeSlotAvailability = "Yes" for contingencies or opening times that are unchanged or added <p>We use the term "all slots" to refer to each of the slots originally received in the "Original" Calendar e-Document for the given day or range.</p>
CALENDAR_005	<p>The receiver of a Calendar e-Document with CalendarStatus = "Amended" has to process the TimeSlotInformation for every given day or period in the following way:</p> <ul style="list-style-type: none"> • Only process TimeSlotInformation that refers to a date after the current system date. For example, when a CalendarEntryPeriod specifies "Monday" the system must only change the slots for future Mondays within the DateTimeRange. • Remove slots from the system whose attribute TimeSlotsAvailability = "No" • Add or update the contingencies on slots in the system whose TimeSlotAvailability is set to "Yes".
CALENDAR_006	<p>If TransportModeType = "Road" and QuantityType = "Count" then the QuantityInformation value specifies the number of trucks that can load or unload at the given time.</p>

Understanding the Diagrams and Content

This section provides a graphical view of the schema structures, a discussion of the item's children. You can find additional information about papiNet and the standard at www.papiNet.org.

The graphics contain content model indicators, cardinality indicators, and data type information.

Associated with each graphic are the definitions for the parent item and any associated child items. All attributes are listed first, followed by the elements.

The following information should help you interpret and understand this standard. Please note the following:

- Content Model and Cardinality operate together to determine if the

Calendar

papiNet Standard - Version 2.31

element or attribute are required in the instance document.

- The same attribute can never appear multiple times in the same element so, you will never see a multiple cardinality indicator.

Content model indicators:

There are three possible types of content: "sequence", "choice", and "all". The papiNet standard currently does not use the "all" construct.

- (sequence)

The sequence of the items to the right of the graphic (or below the text) is required.

- (choice)

A choice of the items to the right of the graphic (or below the text) is permitted.

- (all)

All the items to the right of the graphic are required.

Cardinality indicators:

- Dotted line around element or attribute.

A single instance of the item can optionally exist.

- Dotted line around item with range indicated below.

Multiple instances of the item can optionally exist.

- Solid line around item.

A single instance of the item must exist.

- Solid line around item with range indicated below

At least one instance must exist; multiple instances can optionally exist.

Datatype indication:

When a data type is assigned to an element (either a simple type or complex type the name of the data type is presented beneath the item name in the graphic.

- In some cases additional information about the data type is presented (the default value).

Elements can either have content that is textual/numeric in nature or content that is made up of additional elements and/or attributes.

- When the content is textual/numeric in nature "three straight horizontal lines" will appear in the upper left-hand corner of the graphic. Pay attention to these elements because they are where you will be entering your information.
- When the content is made up of additional elements and/or attributes a "gray-box" will appear on the right-hand side of the graphic.
- If the graphic shows both the horizontal lines and the gray-box then, in the papiNet standard, the content below the element are attributes.

Calendar

papiNet Standard - Version 2.31

Calendar Root Element

Calendar

The Calendar element is the root element for the Calendar e-Document.

The Calendar e-Document is intended to communicate opening times or other details for a location or locations.

CalendarType [attribute]

CalendarType is mandatory. A single instance is required.

Identifies the intention of the entire Calendar e-Document.

This item is restricted to the following list.

LoadingSchedule

The schedule for transport vehicle loading.

OfficeSchedule

The schedule for office personnel.

SupportSchedule

The support schedule for transport operations.

UnloadingSchedule

The schedule for transport vehicle unloading.

CalendarStatus [attribute]

CalendarStatus is optional. A single instance might exist.

Identifies the status of the entire Calendar e-Document.

This item is restricted to the following list.

Amended

The supplied information is changed.

Cancelled

The supplied information has been cancelled. Items that have been cancelled are not included in totals on the summary levels of the e-document.

Original

The supplied information is the first version of that information


Language [attribute]

Language is optional. A single instance might exist.

The valid Alpha 2- and Alpha 3-character list of language codes in the ISO 639-1 and 639-2 international standards.

Information on the content of this attribute is available at:
https://www.loc.gov/standards/iso639-2/php/code_list.php

(sequence)



Calendar

papiNet Standard - Version 2.31

The contents of (sequence) are mandatory. A single instance is required.

CalendarHeader

CalendarHeader is mandatory. A single instance is required.

A group item containing generic information applicable to the entire calendar.

CalendarSequence

CalendarSequence is mandatory. One instance is required, multiple instances might exist.

A group item containing information that relates to a line on the calendar.

Calendar

papiNet Standard - Version 2.31

Primary Elements

CalendarHeader

A group item containing generic information applicable to the entire Calendar.

(sequence)

The sequence of items below is mandatory. A single instance is required.

CalendarNumber

CalendarNumber is mandatory. A single instance is required.

The sequential number that uniquely identifies the Calendar e-Document.

CalendarIssueDate

CalendarIssueDate is mandatory. A single instance is required.

The date and optionally time when the Calendar e-Document was created.

TransactionHistoryNumber

TransactionHistoryNumber is optional. A single instance might exist.

A sequential number that keeps track of the version of a document.

However when the document is a confirmation document, in which case the TransactionHistoryNumber refers to the trigger transaction for the confirmation.

RequestNumber

RequestNumber is optional. A single instance might exist.

A unique tracking number specifically identifying the InfoRequest e-Document to the originator. The tracking number is returned with the "information", the answer, to help match the answer to the request.

SenderParty

SenderParty is optional. A single instance might exist.

The business entity issuing the e-Document, the source of the document.


- The entity responsible for the content. If the sender party has outsourced the message service to a third party the SenderParty is the issuer of the e-Document and not the party performing the transmission service of the electronic message.

ReceiverParty

ReceiverParty is optional. Multiple instances might exist.

The business entity for whom the e-Document is intended, the destination of the document.

- The entity interested in the content. If the receiver party has outsourced the message service to a third party the ReceiverParty is the intended party for



Calendar

papiNet Standard - Version 2.31

the e-Document and not the party performing the receiving service of the electronic message.

OtherParty

OtherParty is optional. Multiple instances might exist.

An organisation or business entity other than those specifically detailed within a e-Document.

AdditionalText

AdditionalText is optional. Multiple instances might exist.

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

CalendarSequence

A group item containing information that relates to a line on the Calendar.


(sequence)

The sequence of items below is mandatory. A single instance is required.

CalendarSequenceNumber

CalendarSequenceNumber is mandatory. A single instance is required.

The sequential number that uniquely identifies the Calendar sequence within the Calendar e-Document.



LocationParty

LocationParty is mandatory. A single instance is required.

The organization or business entity where the business event took place or will take place.

(choice)

[choice] is optional because of choice construct.

SupplyPoint


SupplyPoint is optional because of choice construct.

Grouping element that contains items describing a supply point. A SupplyPoint belongs to a LocationParty, e.g. in a DeliveryOrigin or DeliveryDestination, and describes where goods are stored and can be loaded or unloaded. A SupplyPoint can for example be a loading or unloading gate at a warehouse or a road side landing at a logging area in the forest.

LocationCode

LocationCode is optional because of choice construct.

A code used to identify a specific physical location within a site identified by a party, e.g. a loading station in a warehouse or an unloading station at a printer site.



Calendar

papiNet Standard - Version 2.31

LocationCode will be deprecated in a future version V3R00. Use SupplyPoint instead of LocationCode.

TransportInformation

TransportInformation is optional. A single instance might exist.

A grouping element for transport information.

ValidityPeriod

ValidityPeriod is optional. A single instance might exist.

The validity period for a specific item, e.g. the validity period for an e-Document.

CalendarEntry

CalendarEntry is mandatory. One instance is required, multiple instances might exist.

Detailed description of the times and contingencies for the given LocationParty.

AdditionalText

AdditionalText is optional. Multiple instances might exist.

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

CalendarEntry

Detailed description of the times and contingencies for the given LocationParty.

CalendarEntryPeriod [attribute]

CalendarEntryPeriod is mandatory. A single instance is required.

Describes the period applicable to a time slot to which the given times and contingencies apply.

This item is restricted to the following list.

AllDays

All days

Monday

Monday

Tuesday

Tuesday


Wednesday

Wednesday

Thursday

Thursday

Friday



Calendar

papiNet Standard - Version 2.31

Friday

Saturday

Saturday

Sunday

Sunday

Workdays

Monday, Tuesday, Wednesday, Thursday and Friday excluding bank holidays (red days in the local calendar).

Weekend

Saturday and Sunday and bank holidays (red days in the local calendar).

DateTimeRange

To be deprecated in next version. Use enumeration AllDays instead.

(sequence)

The contents of (sequence) are mandatory. A single instance is required.

TimeSlotInformation

TimeSlotInformation is mandatory. One instance is required, multiple instances might exist.

Description of the beginning and end of a time slot and the contingencies it contains.

DateTimeRange

DateTimeRange is optional. Multiple instances might exist.

Specifies a date and/or time range.

AdditionalText

AdditionalText is optional. Multiple instances might exist.

A text field that is used to communicate information not previously defined or for special instructions. To be used only for circumstances not covered by specific elements.

Calendar papiNet Standard - Version 2.31

Calendar Business Scenarios

Calendar Scenario Listing

Examples of how times and contingencies are specified and changed with the calendar e-Document.

Scenario A	Original Calendar from the consignor or consignee to the carrier specifying office opening times
Scenario B	Original Calendar from the consignor or consignee to the carrier specifying contingencies for loading
Scenario C	Changes to the opening times for a given date range
Scenario D1	Changes to the contingencies for a specific day (e.g. because of a national holiday).
Scenario D2	Changes to the contingencies for a date range (e.g. because of a holidays in August)
Scenario D3	Changes to the contingencies for a date range (e.g. changed amount of contingencies and slots)

Scenario A

e-Document	Calendar
Type	Any of the calendar types.
Scenario	Original Calendar from the consignor to a carrier specifying office opening times.
Outcome	Opening times are entered into the carriers system.
Initiator	Consignor
Receiver	Carrier
Preconditions	None
Trigger	None
Step 1.	Consignor sends Calendar e-Document <ul style="list-style-type: none"> • CalendarType = "Office" • TimeSlotAvailability = "Yes" for available opening times

Scenario B

e-Document	Calendar
Type	Any of the Calendar types.

Calendar papiNet Standard - Version 2.31

Scenario	Original Calendar from the consignor to the carrier specifying contingencies for loading
Outcome	Contingencies are entered into the carriers system
Initiator	Consignor
Receiver	Carrier
Preconditions	None
Trigger	None
Step 1.	Consignor sends Calendar e-Document <ul style="list-style-type: none"> • CalendarType = "Loading" • TransportModeType = "Road" • QuantityType = "Count"

Scenario C

e-Document	Calendar
Type	Any of the Calendar types.
Scenario	Changes to the opening times for a given date range
Outcome	The calendar inside the carriers system is updated
Initiator	Consignor
Receiver	Carrier
Preconditions	A original calendar for the given date range has to exist
Trigger	Consignor has changed the office hours for the given date range
Step 1.	Consignor sends Calendar e-Document <ul style="list-style-type: none"> • CalendarType = "Office" • DateTimeRange specifies for which dates the changes apply • Set TimeSlotAvailability = "No" for opening times that have been removed • Set TimeSlotAvailability = "Yes" for opening times that are unchanged or added
Step 2.	Carrier adjusts the stored opening times for the given dates

Calendar papiNet Standard - Version 2.31

Scenario D1

e-Document	Calendar
Type	Any of the Calendar types.
Scenario	Changes to the contingencies for a specific day (e.g. because of a national holiday)
Outcome	The calendar inside the carriers system is updated
Initiator	Consignor
Receiver	Carrier
Preconditions	A original calendar for the given date range has to exist
Trigger	Consignor has changed the contingencies for the given date range
Step 1.	<p>Consignor sends Calendar e-Document</p> <ul style="list-style-type: none"> • CalendarType = "Loading" • DateTimeRange specifies for which dates the changes apply • Set TimeSlotAvailability = "No" for contingencies that have been removed • Set TimeSlotAvailability = "Yes" for contingencies that are unchanged or added
Step 2.	Carrier adjusts the stored contingencies for the given dates

Scenario D2

e-Document	Calendar
Type	Any of the Calendar e-Document types.
Scenario	Changes to the contingencies for a date range (e.g. because of a holidays in August)
Outcome	The calendar inside the carriers system is updated
Initiator	Consignor
Receiver	Carrier
Preconditions	A original calendar for the given date range has to exist
Trigger	Consignor has changed the contingencies for the

Calendar papiNet Standard - Version 2.31

	given date range
Step 1.	<p>Consignor sends Calendar e-Document</p> <ul style="list-style-type: none"> • CalendarType = "Loading" • DateTimeRange specifies for which dates the changes apply • Set TimeSlotAvailability = "No" for contingencies that have been removed • Set TimeSlotAvailability = "Yes" for contingencies that are unchanged or added
Step 2.	Carrier adjusts the stored contingencies for the given dates

Scenario D3

e-Document	Calendar
Type	Any of the Calendar types.
Scenario	Changes to the contingencies for a date range (e.g. changed amount of contingencies and slots)
Outcome	The calendar inside the carriers system is updated
Initiator	Consignor
Receiver	Carrier
Preconditions	A original calendar for the given date range has to exist.
Trigger	Consignor has changed the contingencies for the given date range
Step 1.	<p>Consignor sends Calendar e-Document</p> <ul style="list-style-type: none"> • CalendarType = "Loading" • DateTimeRange specifies for which dates the changes apply • Set TimeSlotAvailability = "No" for contingencies that have been removed
Step 2.	Carrier adjusts the stored contingencies for the given dates